

# INTERNATIONAL STANDARD

# IEC 60335-2-11

1998

AMENDMENT 2  
1999-05

---

---

## Amendment 2

### Safety of household and similar electrical appliances –

#### Part 2-11: Particular requirements for tumble dryers

#### *Amendement 2*

#### *Sécurité des appareils électrodomestiques et analogues –*

#### *Partie 2-11: Règles particulières pour les sèche-linge à tambour*

© IEC 1999 — Copyright - all rights reserved

International Electrotechnical Commission  
Telefax: +41 22 919 0300

3, rue de Varembé Geneva, Switzerland  
e-mail: [inmail@iec.ch](mailto:inmail@iec.ch) IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

C

*For price, see current catalogue*

## FOREWORD

This amendment has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

| FDIS         | Report on voting |
|--------------|------------------|
| 61/1562/FDIS | 61/1605/RVD      |

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

## 7 Marking and instructions

Add:

### 7.10 Addition:

If the **off position** is only indicated by letters, the word "off" shall be used.

## 15 Moisture resistance

15.2 Add the following as the penultimate paragraph of the replacement:

*For appliances having a working surface, 0,5 l of water containing approximately 1 % NaCl and 0,6 % of acid rinsing agent, as specified in annex AA of IEC 60335-2-5, is poured over the top of the appliance, the controls being placed in the on position. The control knobs are then operated through their working range, this operation being repeated after a period of 5 min.*

## 19 Abnormal operation

19.1 Replace "19.101" by "19.101 and 19.102, if applicable".

Add the following subclause:

**19.102** For **condensation-type tumble dryers**, the test of 19.4 is repeated but with 75 % of the air outlet of the condenser blocked. The test is then carried out again with the air outlet fully blocked.

## 24 Components

*Replace the text by:*

This clause of part 1 is applicable, except as follows:

### 24.1.2 Addition:

*The number of cycles of operation for programmers is 3 000.*

**24.101** Add "or 19.102" after "19.4".

IECNORM.COM: Click to view the full PDF of IEC 60335-2-11:1993/AMD2:1999

WithDrawn