

INTERNATIONAL STANDARD

IEC 60335-2-11

2002

AMENDMENT 1
2003-01

Amendment 1

**Household and similar electrical appliances –
Safety –**

**Part 2-11:
Particular requirements for tumble dryers**

Amendement 1

*Appareils électrodomestiques et analogues –
Sécurité –*

*Partie 2-11:
Règles particulières pour les sèche-linge à tambour*

© IEC 2003 Droits de reproduction réservés — Copyright - all rights reserved

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

C

For price, see current catalogue

FOREWORD

This amendment has been prepared by technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61/2274/FDIS	61/2324/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

7 Marking and instructions

7.12.1 *Add a fourth dashed item after Note 102:*

- that the appliance must not be installed behind a lockable door, a sliding door or a door with a hinge on the opposite side to that of the tumble dryer.

20 Stability and mechanical hazards

20.101 *Replace the third sentence of the first paragraph by the following:*

For appliances with a door opening having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall not be possible to start the motor until a separate means which controls the movement of the drum is operated manually.

20.102 *Replace the first paragraph by the following:*

For appliances with a door opening having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall be possible to open the door from the inside with a force not exceeding 70 N.

NOTE 1 This requirement does not apply to washing machines having a drying function.

NOTE 2 If the appliance is supplied with a decorative door, the test is carried out with this door closed.

30 Resistance to heat and fire

Add the following subclause:

30.101 Non-metallic materials in close proximity to heating elements and on which lint could accumulate shall be resistant to spread of fire. This requirement also applies to parts on which burning lint could fall.

Compliance is checked by subjecting non-metallic surfaces located within 75 mm of the heating element to the needle-flame test of Annex E. The test is also applied to surfaces located directly below the heating element. However, parts shielded by a barrier that meets the needle-flame test are not tested.

NOTE It is considered that burning lint will not fall through a barrier with openings having a dimension less than 3 mm.

The needle-flame test is not carried out on

- *material classified as V-0 or V-1 according to IEC 60695-11-10, provided that the test sample was no thicker than the relevant part;*
- *rotating parts of fans;*
- *small parts as defined in IEC 60695-2-11.*