

IEC 60352-5
(4th edition – 2012)

SOLDERLESS CONNECTIONS –

**Part 5: Press-in connections –
General requirements, test methods and practical guidance**

CORRIGENDUM 1

Replace existing Table 5 by the following new Table 5 :

Table 5 – Qualification test schedule – Test group C

| Test phase | Test | | Measurement to be performed | | Requirement |
|-------------------|------------------------------------|-----------|---|-----------------------|--|
| | Title | Subclause | Title | Test No. of IEC 60512 | Subclause |
| CP1 | Mounting | 5.3.2.2 | | | |
| CP2 if applicable | Replacement | 5.2.2.6 | | | |
| CP3 | | | Contact resistance – millivolt level method | 2a | 5.2.3.1 |
| CP4 | Rapid change of temperature | 5.2.4.2 | | 11d | |
| CP5 | Climatic sequence | 5.2.4.3 | | 11a | |
| CP6 | Dry heat | 5.2.4.4 | | 11i | |
| CP7 | No required tests and measurements | | | | |
| CP8 | | | Contact resistance – millivolt level method | 2a | 5.2.3.1 |
| CP9 | | 5.2.2.3 | Push-out force | | 5.2.2.3 ^{a)} , minimum push-out force per termination according to 4.6 e) |

^{a)} The test for push-out force has to be performed on 14 of the 200 terminations, 7 of them out of range a and 7 of them out of range b.

Figure 9, in the bottom section of the flow chart, last column, delete:

"– Flowing mixed gas corrosion test"