

INTERNATIONAL STANDARD

QC 300101

**Fixed capacitors for use in electronic equipment –
Part 11-1: Blank detail specification – Fixed polyethylene-terephthalate film
dielectric metal foil d.c. capacitors – Assessment level EZ**

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008



INTERNATIONAL STANDARD

QC 300101

**Fixed capacitors for use in electronic equipment –
Part 11-1: Blank detail specification – Fixed polyethylene-terephthalate film
dielectric metal foil d.c. capacitors – Assessment level EZ**

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

M

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

**Part 11-1: Blank detail specification –
Fixed polyethylene-terephthalate film
dielectric metal foil d.c. capacitors –
Assessment level EZ**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-11-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition published in 1988 and constitutes a minor revision related to tables, figures and references.

The text of this standard is based on the following documents:

CDV	Report on voting
40/1840/CDV	40/1865/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The QC number that appears on the front cover of this publication is the specification number in the IECQ Quality Assessment System for Electronic Components (IECQ).

The list of all parts of the IEC 60384 series, under the (new) general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 11-1: Blank detail specification – Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors – Assessment level EZ

INTRODUCTION

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements may not be considered as being in accordance with IEC specifications nor shall they so be described.

In the preparation of detail specifications, the content of 1.4 of the sectional specification shall be taken into account.

The numbers between brackets on the first page correspond to the following information which shall be inserted in the position indicated.

Identification of the detail specification

- [1] The "International Electrotechnical Commission" or the National Standards Organization under whose authority the detail specification is drafted.
- [2] The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- [3] The number and issue number of the IEC or national generic specification.
- [4] The IEC number of the blank detail specification.

Identification of the capacitor

- [5] A short description of the type of capacitor.
- [6] Information on typical construction (when applicable).

NOTE When the capacitor is not designed for use in printed-board applications, this shall be clearly stated in the detail specification in this position.

- [7] Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an annex to the detail specification.
- [8] Application or group of applications covered and/or assessment level.

NOTE The assessment level(s) to be used in a detail specification are selected from 3.5.4 of the sectional specification. This implies that one blank detail specification may be used in combination with several assessment levels, provided the grouping of the tests does not change.

- [9] Reference data on the most important properties, to allow comparison between the various capacitor types.

	IEC 60384-11-1-XXX [2] QC 300101-XXX
[1]	
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH:	IEC 60384-11-1 [4] QC 300101
[3]	FIXED POLYETHYLENE-TEREPHTHALATE FILM DIELECTRIC METAL FOIL D.C. CAPACITORS [5]
Outline drawing: (see Table 1) [...angle projection]	[6]
[7]	Assessment level(s): EZ [8]
[Other shapes are permitted within the dimensions given.]	
For Notes [1] to [9] see preceding page.	

Information on the availability of components qualified to this detail specification is given in the Qualified Products List.

(9)

1 General data

1.1 Recommended method(s) of mounting (to be inserted)

See IEC 60384-11, 1.4.2.

1.2 Dimensions

Table 1 – Case size reference and dimensions

Case size reference	Dimensions					
	mm					
	\varnothing	L	H	d	

NOTE 1 When there is no case size reference, Table 1 may be omitted and the dimensions shall be given in Table 2, which then becomes Table 1.

NOTE 2 The dimensions shall be given as maximum dimensions or as nominal dimensions with a tolerance.

1.3 Ratings and characteristics

- Capacitance range (see Table 2)
- Tolerance on rated capacitance
- Rated voltage (see Table 2)
- Category voltage (if applicable) (see Table 2)
- Climatic category
- Rated temperature
- Max. a.c. voltage (if applicable)
- Tangent of loss angle ($\tan \delta$)
- Insulation resistance

Table 2 – Values of capacitance and of voltage related to case sizes

Rated voltage				
Category voltage^a				
	Case size	Case size	Case size	Case size
Rated capacitance (in nF and/or μ F)				
^a If different from the rated voltage.				

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60384-11, *Fixed capacitors for use in electronic equipment – Part 11: Sectional specification – Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors*

1.5 Marking

The marking of the capacitor and the package shall be in accordance with the requirements of 1.6 of IEC 60384-11.

The details of the marking of the component and package shall be given in full in the detail specification.

1.6 Ordering information

Orders for capacitors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- a) rated capacitance;
- b) tolerance on rated capacitance;
- c) rated d.c. voltage;
- d) number and issue reference of the detail specification and style reference;
- e) packaging instructions.

1.7 Certified records of released lots

Required/not required.

1.8 Additional information (not for inspection purposes)**1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification**

NOTE Additions or increased requirements should be specified only when essential.

Table 3 – Other characteristics

This table is to be used for defining characteristics which are additional to, or more severe than, those given in the sectional specification.

2 Inspection requirements**2.1 Procedures**

2.1.1 For qualification approval, the procedures shall be in accordance with 3.4 of the sectional specification, IEC 60384-11.

2.1.2 For quality conformance inspection, the test schedule (Table 4) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by 3.5.1 of IEC 60384-11.

Table 4 – Test schedule for quality conformance inspection

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			IL	n	c	
Group A inspection (lot-by-lot) Sub-group A0 4.2.2 Capacitance 4.2.3 Tangent of loss angle (tan δ) 4.2.1 Voltage proof (Test A) 4.2.4 Insulation resistance (Test A)	ND	Frequency : 1 kHz for all capacitance values Method: ... Measuring point 1a Measuring point 1a	100% ^d			Within specified tolerance As in 4.2.3.2 No breakdown or flashover As in 4.2.4.2
Group A inspection (lot-by-lot) Sub-group A1 4.1 Visual examination	ND		S-3	b	0	As in 4.1 Legible marking and as specified in 1.5 of this specification
Sub-group A2 4.1 Dimensions (gauging) ^e	ND		S-3	b	0	As specified in Table 1 of this specification

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>IL</i>	<i>n</i>	<i>c</i>	
Group B inspection (lot-by-lot) Sub-group B1	ND	Without ageing Method: ...	S-3	b	0	Good tinning as evidenced by free flowing of the solder with wetting of the terminations or solder shall flow within ... s, as applicable Legible marking
4.5 Solderability (if applicable)						
4.14 Solvent resistance of the marking (if applicable)		Solvent: ... Solvent temperature: ... Method 1 Rubbing material: cotton wool Recovery: ...				

^a Subclause numbers of tests and performance requirements refer to the sectional specification, IEC 60384-11, and Clause 1 of this specification.

^b Number to be tested: sample size as directly allotted to the code letter for *IL* in Table 2a of IEC 60410.

^c In this table:
IL = inspection level
p = periodicity in months
n = sample size
c = acceptance criterion (permitted number of non-conforming items)
D = destructive
ND = non-destructive

^d 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million ($\times 10^{-6}$). The sampling level shall be established by the manufacturer. For the calculation of $\times 10^{-6}$ values, any parametric failure shall be counted as a non-conforming item. If one or more non-conforming items occur in a sample, this lot shall be rejected.

^e This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid components exceeding the limits.

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Group C inspection (periodic)						
Sub-group C1A Part of sample of Sub-group C-1	D		6	5	0 ^f	
4.1 Dimensions (detail)						See detail specification
4.4.1 Initial measurements		Capacitance Tangent of loss angle ($\tan \delta$): For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz				
4.3 Robustness of terminations		Visual examination				No visible damage
4.4. Resistance to soldering heat		Method: ...				
4.4.2 Final measurements		Visual examination				No visible damage $\Delta C/C \leq 2\%$ of the value measured initially
4.13 Component solvent resistance (if applicable)		Solvent: ... Solvent temperature: ... Method 2 Recovery: ...				See detail specification
Sub-group C1B Other part of sample of Subgroup C1	D		6	5	0 ^f	
4.6.1 Initial measurements		Capacitance Tangent of loss angle ($\tan \delta$): For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz				
4.6 Rapid change of temperature		T_A = Lower category temperature T_B = Upper category temperature Five cycles Duration $t_1 = 30$ min Visual examination				No visible damage
4.7 Vibration		Method of mounting, see 1.1 of this specification Procedure B4 Frequency range: ... Hz to ... Hz Amplitude: 0,75 mm or acceleration 98 m/s^2 (whichever is the less severe) Total duration: 6 h				

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			p	n	c	
4.7.2 Final inspection		Visual examination				No visible damage
4.8 Bump (or shock, see 4.9)		Method of mounting, see 1.1 of this specification Number of bumps: ... Acceleration: ... m/s ² Duration of pulse: ... ms				
4.9 Shock (or bump, see 4.8)		Method of mounting: see 1.1 of this specification Acceleration: ... m/s ² Duration of pulse: ... ms				
4.8.3 Final measurements or 4.9.3		Visual examination Capacitance Tangent of loss angle (tan δ)				No visible damage ΔC/C ≤ 5 % of value measured in 4.6.1 See detail specification
Sub-group C1 Combined sample of specimens of Subgroups C1A and C1B	D		6	10	0 ^f	
4.10 Climatic sequence						
4.10.2 Dry heat		Temperature: upper category temperature Duration: 16 h				
4.10.3 Damp heat, cyclic, Test Db, first cycle						
4.10.4 Cold		Temperature: lower category temperature Duration: 2 h				
4.10.5 Low air pressure (if required by the detail specification)		Air pressure: 8,5 kPa (85 mbar)				
4.10.5.3 Intermediate inspection		Visual examination				No permanent breakdown, flashover or harmful deformation of the case
4.10.6 Damp heat, cyclic, Test Db, remaining cycles		Recovery: 1 h to 2 h				
4.10.6.2 Final measurements		Visual examination Capacitance Tangent of loss angle (tan δ) Insulation resistance				No visible damage Legible marking ΔC/C: ≤ 5 % of value measured in 4.4.2, 4.8.3 or 4.9.3 as applicable Tan δ ≤ 0,01 or 1,2 times values measured in 4.3.1 or 4.6.1, as applicable, whichever is the greater ≥50 % of values in 4.2.4.2

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Sub-group C2 4.11 Damp heat, steady state 4.11.1 Initial measurements 4.11.3 Final measurements		Capacitance Tangent of loss angle ($\tan \delta$) For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz Recovery: 1 to 2 h Visual examination Capacitance Tangent of loss angle ($\tan \delta$) Insulation resistance	6	10	0 ^f	No visible damage Legible marking $\Delta C/C \leq 5\%$ of value measured in 4.11.1 $\tan \delta \leq 0,01$ or 1,2 times values measured in 4.11.1, whichever is the greater $\geq 50\%$ of values in 4.2.4.2
Sub-group C3 4.12 Endurance 4.12.1 Initial measurements 4.12.5 Final measurements	D	Duration: 1 000 h Capacitance Tangent of loss angle ($\tan \delta$) For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz Recovery: 1 h to 2 h Visual examination Capacitance Tangent of loss angle ($\tan \delta$) Insulation resistance	6	10	0 ^f	No visible damage Legible marking $\Delta C/C \leq 5\%$ of value measured in 4.12.1 $\tan \delta \leq 0,01$ or 1,2 times values measured in 4.12.1, whichever is the greater $\geq 50\%$ of values in 4.2.4.2
Sub-group C4 4.2.5 Characteristics depending on temperature	ND	Capacitance	6	10	0 ^f	As in 4.2.5

Table 4 – Test schedule for quality conformance inspection (continued)

- a Subclause numbers of tests and performance requirements refer to the sectional specification, IEC 60384-11, and Clause 1 of this specification.
- b Number to be tested: sample size as directly allotted to the code letter for *IL* in Table 2a of IEC 60410.
- c In this table:
 - IL* = inspection level
 - p* = periodicity in months
 - n* = sample size
 - c* = acceptance criterion (permitted number of non-conforming items)
 - D = destructive
 - ND = non-destructive
- d 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million ($\times 10^{-6}$). The sampling level shall be established by the manufacturer. For the calculation of $\times 10^{-6}$ values, any parametric failure shall be counted as a non-conforming item. If one or more non-conforming items occur in a sample, this lot shall be rejected.
- e This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid components exceeding the limits.
- f If one non-conforming item is obtained, all the tests of the subgroup shall be repeated on a new sample and then no further non-conforming items are permitted. Release of product may continue during repeat testing.

IECNORM.COM : Click to view the full PDF of IEC 60384-11-1:2008