

INTERNATIONAL STANDARD

IEC
60936-3

First edition
2002-04

Maritime navigation and radiocommunication equipment and systems – Radar –

Part 3: Radar with chart facilities – Performance requirements – Methods of testing and required test results



Reference number
IEC 60936-3:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/catlg-e.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/JP.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60936-3

First edition
2002-04

Maritime navigation and radiocommunication equipment and systems – Radar –

Part 3: Radar with chart facilities – Performance requirements – Methods of testing and required test results

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

S

For price, see current catalogue

CONTENTS

| | |
|-----------------------------------------------------------------------------------------------|----|
| FOREWORD..... | 3 |
| 1 Scope..... | 4 |
| 2 Normative references..... | 4 |
| 3 Definitions and abbreviations..... | 5 |
| 4 Performance requirements..... | 6 |
| 4.1 General..... | 6 |
| 4.2 Display requirements..... | 7 |
| 4.3 Display of SENC information..... | 7 |
| 4.4 Superimposition (A4/3.3.10)..... | 8 |
| 4.5 Colours and symbols..... | 9 |
| 4.6 Presentation..... | 10 |
| 4.7 Interfacing..... | 10 |
| 4.8 Alarms and indications..... | 10 |
| 4.9 Ergonomics..... | 10 |
| 4.10 ENC issue status..... | 10 |
| 4.11 Installation matters..... | 11 |
| 5 Methods of testing and required test results..... | 11 |
| 5.1 General conditions of measurement and definitions..... | 11 |
| 5.2 General tests..... | 11 |
| 5.3 Display tests..... | 12 |
| 5.4 Display of SENC information tests..... | 12 |
| 5.5 Superimposition tests..... | 13 |
| 5.6 Colours and symbols..... | 14 |
| 5.7 Presentation tests..... | 14 |
| 5.8 Interfacing tests..... | 15 |
| 5.9 Alarms and indications tests..... | 15 |
| 5.10 Ergonomic tests..... | 15 |
| 5.11 ENC issue status..... | 16 |
| 5.12 Installation handbook checks..... | 16 |
| Annex A (normative) Specification of chart symbols and colours to be used..... | 17 |
| A.1 Minimum SENC information..... | 17 |
| A.2 Presentation of chart symbols..... | 17 |
| A.3 Colour fill..... | 18 |
| A.4 Coastlines..... | 18 |
| A.5 Own ship's safety contour..... | 18 |
| A.6 Day and night colours..... | 18 |
| Annex B (normative) Performance checks during environment testing..... | 19 |
| B.1 Method of measurement:..... | 19 |
| B.2 Confirmation..... | 19 |
| B.3 Results required..... | 19 |
| Annex C (normative) Additional requirements for 'standalone' radar with chart facilities..... | 20 |
| C.1 Provision and updating of chart information..... | 20 |
| C.2 Content and structure of chart data..... | 20 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS – RADAR –**
**Part 3: Radar with chart facilities – Performance requirements –
Methods of testing and required test results**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60936-3 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|-------------|------------------|
| 80/337/FDIS | 80/342/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

Annexes A, B and C form an integral part of this standard.

The committee has decided that the contents of this publication will remain unchanged until 2006. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – RADAR –

Part 3: Radar with chart facilities – Performance requirements – Methods of testing and required test results

1 Scope

This part of IEC 60936 specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in Resolution MSC.64(67) Annex 4 Radar clauses 3.3.9 and 3.3.10 for the optional requirements for superimposition of selected parts of SENC information. In addition it takes account of IMO Resolution A.694 and is associated with IEC 60945. When a requirement of this standard is different from IEC 60945, the requirement in this standard shall take precedence.

A High Speed Craft (HSC) radar, as defined in IEC 60936-2, that uses 'selected parts of the SENC' shall comply with the requirements of this standard.

This standard does not include the mandatory performance requirements for the shipborne radar or HSC radar. These are specified in IEC 60936-1, Shipborne radar, and IEC 60936-2, HSC radar respectively.

All text in this standard, whose wording is identical to that in IMO Resolution MSC.64(67) Annex 4 is printed in *italics* and the Resolution (abbreviated to – A4) and paragraph numbers are indicated in brackets, i.e. (A4/3.3).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60872-1, *Maritime navigation and radiocommunication equipment and systems – Radar plotting aids – Part 1: Automatic radar plotting aids (ARPA) – Methods of testing and required test results*

IEC 60872-2, *Maritime navigation and radiocommunication equipment and systems – Radar plotting aids – Part 2: Automatic tracking aids (ATA) – Methods of testing and required test results*

IEC 60872-3, *Maritime navigation and radiocommunication equipment and systems – Radar plotting aids – Part 3: Electronic plotting aid (EPA) – Methods of testing and required test results*

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 60936-1, *Maritime navigation and radiocommunication equipment and systems – Radar – Part 1: Shipborne radar – Performance requirements – Methods of testing and required test results*

IEC 60936-2, *Maritime navigation and radiocommunication equipment and systems – Radar – Part 2: Shipborne radar for high-speed craft (HSC)– Methods of testing and required test results*

IEC 61162, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IMO Convention for the Safety of Life at Sea (SOLAS) as amended

IMO Resolution MSC.64(67) Annex 4 *Recommendation on performance standards for radar equipment.*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system and for electronic navigational aids*

IMO Resolution A.820(19), *Performance standards for navigational radar equipment for high-speed craft*

IMO Resolution A.817(19), *Performance standards for electronic chart display and information systems*

IHO S52 and appendices

3 Definitions and abbreviations

For the purposes of this part of IEC 60936 the following definitions and abbreviations apply.

3.1 Definitions

3.1.1

ECDIS

IEC 61174 'Electronic chart display and information system' (ECDIS) means a navigation information system which, with adequate backup arrangements, can be accepted as complying with the up-to-date chart required by regulation V/20 of the 1974 SOLAS Convention. It displays selected information from a system electronic navigational chart (SENC) with positional information from navigational sensors to assist the mariner in route planning and route monitoring, and by displaying additional navigation-related information. The reference geodetic datum is WGS-84

3.1.2

SENC

System Electronic Navigational Chart (SENC) means a database resulting from the transformation of the ENC for appropriate use, updates to the ENC by appropriate means, and other data added by the mariner. It is this database that is actually accessed for the display generation and other navigational functions, and which is the equivalent to an up-to-date paper chart. The SENC may also contain information from other sources

3.1.3**ENC**

Electronic Navigation Chart (ENC) means the database, standardized as to content, structure and format, issued for use with ECDIS on the authority of government authorized hydrographic offices. The ENC contains all the chart information necessary for safe navigation and may contain supplementary information in addition to that contained in the paper chart (e.g. sailing directions) which may be considered necessary for safe navigation. The content, structure and format of the ENC are specified in IHO S-57 Edition 3 including the associated ENC product specification

3.1.4**ENC test data set**

a standardized data set supplied on behalf of the International Hydrographic Organisation (IHO) that is necessary to accomplish IEC testing requirements for ECDIS. This test data set is encoded according to the IHO S-57 ENC product specification and contains update information based on IHO S-52 appendix 1. The specific requirements are listed in IEC 61174 annex F

3.1.5**consistent common reference system**

sensor input data, providing identical and obligatory reference pertaining to position, course, heading, bearing, speed, velocity, etc. and horizontal datum to different sub-systems within an integrated navigation system

3.1.6**degrade**

reduce the information content of

3.1.7**primary chart-information set**

coastlines, own ship's safety contour, dangers to navigation and fixed and floating aids to navigation, as further detailed in IMO Resolution A.817 Appendix 2 clauses 1.1, 1.2, 1.3, 1.4 and 2.3 only. See annex A of this standard for the specification of chart symbols and features, to be used.

3.2 Abbreviations

| | |
|-------|-------------------------------------------------|
| ECDIS | Electronic chart display and information system |
| ENC | Electronic navigation chart |
| EPFS | Electronic position fixing system |
| EUT | Equipment under test |
| HSC | High speed craft |
| IHO | International Hydrographic Organisation |
| SENC | System electronic navigational chart |
| TM | True motion |
| N UP | North up |

4 Performance requirements**4.1 General**

The performance of the shipborne radar (or HSC radar) shall not be inferior to the performance requirements adopted by the IMO in MSC.64(67) Annex 4 Radar (or A.820(19) HSC radar) as specified in IEC 60936-1 and IEC 60936-2 respectively.

4.1.1 Quality assurance

The Administration shall require that the manufacturers have a quality control system audited by a competent authority to ensure continuous compliance with the type approval conditions (SOLAS Chapter V / Regulation 18.5).

4.2 Display requirements

4.2.1 Display conflict

It shall not be possible for radar maps to be displayed at the same time as SENC navigational information. However, the navigational lines, other than those used for maps, and symbols given in IEC 60936-1, annex C, clauses C.3, C.4 and C.5 are permitted, provided there is no conflict between these sets of information.

Raster nautical charts (RNC) are not applicable for chart radar.

4.2.2 Display size

The equipment shall provide, without external magnification, a daylight display with a radar minimum effective diameter within the bearing scale of not less than 250 mm.

4.2.3 Display resolution

The display shall have a minimum resolution of (L) lines per mm given by $L = 800/s$, where s is the smaller dimension of the SENC information area. (e.g. for the minimum chart area, $s = 250$ mm and the resolution $L = 3,20$ lines per mm, giving a picture unit size of 0,312 mm.)

4.2.4 Display colour

The display shall be multi-colour. The colours used for navigational lines and symbols and the SENC information shall harmonize. The SENC information is permitted to be in shades of grey.

4.3 Display of SENC information

4.3.1 Display degradation (A4/3.3.9)

Selected parts of the System Electronic Navigation Chart (SENC) information shall be displayed in such a way that the radar and plotting information is not masked, obscured or degraded

4.3.2 SENC information brilliance

The SENC information brilliance shall be adjustable by the user at any time.

4.3.3 Display functionality and response time

The radar functionality and response time shall not be adversely affected by the SENC information.

4.3.4 Primary chart-information set

The SENC information made available for use on a radar display shall at least include coastlines, own ship's safety contour, dangers to navigation and fixed and floating aids to navigation. This set of information shall be known as the 'primary chart-information set'.

The radar shall be capable of displaying the 'primary chart-information set' of SENC information. Any additional SENC information as specified by the manufacturer shall meet the requirements of this standard.

The radar shall present the 'primary chart-information set' of SENC required at any time by dedicated controls or primary access in an associated menu.

4.3.5 Selection of parts of SENC for display

From the radar display *the mariner shall be able to select those parts of the SENC, which can be made available and the mariner requires to be displayed.*

The selected parts of SENC shall be displayed with minimum reduction of the information content.

It shall be possible to suppress or remove all SENC information with a momentary control function and it shall be possible to remove all SENC information from the radar display at any time by a dedicated control or primary access in an associated menu.

It shall be possible to remove or add categories of the SENC information made available to the radar. The addition or deletion of information shall be limited to categories of information, for example prohibited and restricted areas, spot soundings, etc., but not individual items such as individual area or an individual sounding. Full details and relevant safety cautions, shall be provided in the operator's handbook.

If a facility has been provided to call up information associated with an object by cursor enquiry on its symbol, then the data shall be presented outside the radar video area. Where this facility is provided, the text shall not appear automatically whenever the object with which it is associated appears on the display. If depth information is displayed, it shall only be presented as it has been provided in the ENC and not adjusted by tidal height.

4.4 Superimposition (A4/3.3.10)

For the superimposition of selected parts of the SENC:

4.4.1 Reference management

Reference management is required to ensure that the information displayed is correlated and in the same reference and co-ordinate system;

A consistent common reference of position (with a datum of WGS84), including antenna positions, heading and speed shall be used. The operations manual shall contain appropriate information including the expected tolerance (uncertainty) of the chart to radar picture.

4.4.2 Display area

The whole effective radar display area shall contain the available radar and SENC information. The SENC information shall not be displayed outside this area, unless there is a clear indication of the radar display area limit, for example bearing scale.

4.4.3 Matching and adjustment

In case of any deviations between the chart image and the radar image through detectable causes, manual adjustment of the SENC shall be possible. Any manual adjustment shall be clearly indicated as long as it is activated. Resetting shall be possible in a simple manner.

- a) The SENC information shall match within appropriate tolerances the range scale, orientation and projection of the radar information.
- b) The radar with chart facilities shall provide an indication if the SENC information is displayed at a larger scale than contained in the ENC.

4.4.4 Priority in the display

The display of radar information shall have priority. (See 4.3.)

Provided the functional requirements in 4.3 and 4.4.6 a) are met, all methods of presentation are permitted.

4.4.5 Stabilization

The equipment shall be capable of appropriately stabilising the radar image, ARPA, ATA and EPA vectors and SENC information. The operating mode shall be clearly indicated.

- a) The SENC information may be maintained or re-introduced by switching to an alternative method of stabilization only by operator action. A clear indication of the active mode shall be given.
- b) If the position sensor fails or is switched off, the SENC information shall be removed automatically within 1 min. An alternative position information source, such as Loran-C, DR, etc. may be provided together with a clear indication.
- c) If the azimuth stabilization sensor fails or is switched off, the SENC information shall be removed automatically within 1 min.
- d) The display of SENC information is permitted in all radar modes.

4.4.6 Independence of radar image, ARPA, ATA, EPA and SENC

- a) The SENC information shall not have an adverse effect on the radar picture.
- b) *Radar/ARPA, ATA and EPA information and SENC information shall be clearly recognisable as such.*
- c) *In the case of a detectable malfunction of one component (the radar or source of SENC information), the function of the other component shall not be adversely affected.* If the radar fails while SENC information is selected a clear visual indication shall be displayed in the radar video area. The SENC information may remain.

4.5 Colours and symbols

4.5.1 Background colour

- a) Radar background and water surfaces in the SENC information shall be in the same basic colour.
- b) Different shades of the colour of water are permitted to indicate water with depth greater than or less than the safety contour. Lighter shades shall indicate shallower water.
- c) Day and night modes shall be provided. The colours provided shall be documented in the operator's handbook.
- d) If land colour infill is used it shall be in a different colour to the water colour (or, if used, a different shade of grey).
- e) If the SENC information covers only part of the radar video area, the limitations for SENC information shall be clearly indicated when SENC information is present.
- f) For borderlines between No-Data, Official-Data and Non-Official-Data, the appropriate line styles defined in S-52 shall be used.
- g) For areas in which no data are provided the NO-DATA-Pattern according to S-52 shall not be used.
- h) If Non-Official-Data are used a clear indication shall be given to the user according to S-52.

4.5.2 Chart symbols and colours

At least the simplified chart symbols shall be displayed, using size, shape and colour as specified in annex A of this standard which is based on IHO S52 Appendix 2.

4.6 Presentation

4.6.1 SENC availability

The SENC information shall be available, as a minimum, for TM, N UP mode on 3 nm, 6 nm and 12 nm range scales. Presentation of SENC information is permitted in other presentation modes. If other display modes and range scales are provided, the same requirements shall be met for presentation of SENC information, as for the minimum requirements.

4.6.2 New chart latency

After a change of range scale or upon radar origin resetting, SENC information that is incompatible with the selected radar presentation in use shall be suppressed and an indication given until the new chart is fully displayed. The new chart shall be fully displayed within 10 s of this suppression occurring.

4.6.3 Own ships turn

The equipment shall be capable of operating with the SENC information continuously displayed in the presence of a turn. The turn rate shall be 12 °/s at 30 kt for SOLAS chapter V craft, and 20 °/s at a speed of 70 kt for HSC to SOLAS Chapter X, on all radar modes for which SENC information is available.

4.6.4 SENC latency

While the SENC information is continuously displayed the SENC positioning latency shall not exceed the time required to complete one radar scan, for example 3 s for a scanner turning rate of 20 rpm or 1,5 s for a scanner turning rate of 40 rpm and pro rata for other scanner turning rates.

4.7 Interfacing

- a) All interfacing to external sensors and sources that are additionally required for SENC information purposes shall be to appropriate IEC 61162 interface standards.
- b) If no suitable IEC 61162 interface standard is available, an appropriate interface may be used. Full details of such interfaces shall be adequately documented.

4.8 Alarms and indications

If an operational alarm for crossing a safety contour is provided it shall conform to the ECDIS standard as defined in IEC 61174.

The input from the position sensor and SENC shall be on the same geodetic datum (WGS84). An alarm shall be given if this is not the case.

4.9 Ergonomics

The ergonomic requirements of IEC 60945 and IEC 60936-1 or IEC 60936-2 as appropriate, shall apply.

4.10 ENC issue status

The date and number of last update affecting the cells currently in use and the edition number and date of issue of the ENC shall be available.

4.11 Installation matters

Alignment matters and their means of adjustment and limitations shall be included in the manufacturer's manual. The manual shall include qualitative information on the limitations of accuracy caused by the antenna(s) location, and the relative geographic antenna position, with respect to the SENC information.

5 Methods of testing and required test results

This clause defines the type test methods and results required ensuring that equipment complies with the requirements of clause 4.

5.1 General conditions of measurement and definitions

The equipment under test (EUT) shall be tested to IEC 60936-1 or IEC 60936-2 as applicable. All the tests to the general requirements of IEC 60945 shall be carried out to verify that the EUT meets these technical requirements. The equipment shall comply with those requirements of IEC 60945 appropriate to its category or evidence of prior testing supplied.

The manufacturer shall declare which equipment or units are 'protected' or 'exposed'. The manufacturer shall declare if 'preconditioning' is required before environmental checks.

For the purposes of this standard the following definitions shall apply:

- performance check – Reconfiguration of the EUT and carry out the appropriate IEC 60936 performance check. See annex B;
- performance test – For radar EUT, shall be identical to the performance check for the purposes of IEC 60945. See annex B;
- by inspection – a visual check of the equipment or documentation;
- 'clear indication' or 'visibility of test targets' – shall mean being visible for 50 % of the antenna scans;
- standard operating mode – in the operational condition defined in 4.5, for example TM, N UP.

The ENC test data set and a matched radar simulator are required, together with a source of SENC information.

All radar modes offered by the manufacturer with SENC information shall be exercised

An IEC 61162 interface simulator is required capable of transmitting valid and invalid messages with correct and incorrect checksum.

5.1.1 Test site

Tests will normally be carried out at test sites selected by the type test authority. The manufacturer shall, unless otherwise agreed, set up the equipment and ensure that it is operating normally before type testing commences.

5.2 General tests

5.2.1 Quality assurance

(See 4.1.1)

Test by inspection of the manufacturer's documentation.

5.3 Display tests

5.3.1 Display conflict

(See 4.2.1)

By observation.

5.3.2 Display size

(See 4.2.2)

By measurement and inspection.

5.3.3 Display resolution

(See 4.2.3)

From information supplied by the manufacturer, verify that the resolution defined in 4.2.3 is met.

5.3.4 Display colour

(See 4.2.4)

By observation.

5.4 Display of SENC information tests

(See 4.3)

5.4.1 Display degradation test

(See 4.3.1)

5.4.1.1 Objective

To show that the selected parts of the SENC do not mask, obscure or degrade the radar and plotting displays.

5.4.1.2 Method of test

- a) Switch the radar to TM N UP and 3 nm range scale
- b) Apply the SENC test data set and matching simulated radar information
- c) Display 20 targets (at sea) with 10 being tracked or plotted
- d) Display the 'primary chart-information set'

5.4.1.3 Results required

The requirements of 4.3.1 shall be met.

The test shall be repeated at all other range scales where the SENC information is provided.

5.4.2 SENC information brilliance

(See 4.3.2)

Check that the SENC information brilliance is adjustable.

5.4.3 Display functionality and response time tests

(See 4.3.3)

5.4.3.1 Objective

To check functionality and response time.

5.4.3.2 Method of test

Use the method of test in 5.4.1 with additionally the following:

- a) switch the radar to all other modes and range scales for which SENC information is provided;
- b) add to the 'primary chart information set' all other SENC information that is provided;
- c) move the cursor, rotate the EBL and change the VRM, change the vector from relative to true.

5.4.3.3 Results required

The radar functionality and response time shall be as required in the IEC 60936 radar series and IEC 60872 radar plotting series of standards as appropriate.

5.4.4 Primary chart information set

(See 4.3.4)

By inspection.

5.4.5 Selection of parts of SENC for display

(See 4.3.5)

By inspection of the EUT and handbooks.

5.5 Superimposition tests

(See 4.4)

5.5.1 Reference management

(See 4.4.1)

By inspection of the EUT and the handbooks. Check the manufacturers handbooks for guidance on installation matters and on the use of the 'consistent common reference system'.

5.5.2 Display area

(See 4.4.2)

By inspection.

5.5.3 Matching and adjustment

(See 4.4.3)

5.5.3.1 Objective

Test of SENC and radar matching.

5.5.3.2 Method of measurement

- a) Using SENC information covering the area surrounding 70° N or S, simulate own ship position to 70° N or S respectively. Set range scale to 12 nm.
- b) Measure, using the radar tools (EBL/VRM and or cursor) the range and bearing to 4 points in the chart. The 4 points shall be situated at a range between 10 and 12 nm and bearings of 45°, 135°, 225° and 315° with a bearing tolerance of ±5°.
- c) Check by observation that manual adjustment of SENC information is available, that an indication is given and that resetting is simple

5.5.3.3 Results required

The measurements, using the radar tools, shall be within 0,25 nm in range and 1,0° in bearing as compared to those taken from the SENC information.

5.5.4 Priority in the display

(See 4.4.4)

No further test is required as already done in 5.4.2.

5.5.5 Stabilization

(See 4.4.5)

Repeat 5.4.2 functional test while exercising position and rotation at 12 °/s and 30 kt, for equipment complying with IEC 60936-1 or 20 °/s and 70 kt for equipment complying with IEC 60936-2, for at least 20 consecutive scans.

Results required: the chart and radar images remain matched, by visual assessment, after each radar update. The operating mode shall be clearly indicated.

5.5.6 Independence of radar image, ARPA, ATA, EPA and SENC

(See 4.4.6)

Test and inspect all EUT available modes.

5.6 Colours and symbols

(See 4.5)

5.6.1 Background colour

(See 4.5.1)

Using the test data set (and annex A) and by inspection.

5.6.2 Chart symbols and colours

(See 4.5.2)

By inspection and using annex A.

5.7 Presentation tests

(See 4.6)

5.7.1 SENC availability

(See 4.6.1)

By observation.

5.7.2 New chart latency

(See 4.6.2)

5.7.2.1 Method of test

- a) Repeat 5.4.1.
- b) Select other range scales supporting the SENC information.

5.7.2.2 Results required

Check that the SENC information is suppressed and that there is an indication until the required data has been generated. The new SENC information shall be fully displayed within 10 s.

5.7.3 Own ships turn

(See 4.6.3)

By observation during 5.5.5

5.7.4 SENC latency

(See 4.6.4)

5.7.4.1 Method of test

Repeat test 5.5.5 and after 1 min stop the rotation.

5.7.4.2 Results required

The SENC positioning latency shall not exceed one radar scan.

5.8 Interfacing tests

(See 4.7)

- a) All interfaces that conform to IEC 61162 shall be tested in accordance with the relevant annex of IEC 61162, for example annex C of IEC 61162-1.
- b) Any additional interfaces based on IEC 61162 standards shall be tested to the appropriate IEC 61162 standard.
- c) All other interfaces shall be tested in accordance with the documentation provided by the manufacturer.

5.9 Alarms and indications tests

(See 4.8)

Verify that an alarm is generated when the vessel is going to cross the safety contour within the time specified by the mariner.

Test by demonstration that an inappropriate datum (i.e. non-WGS84) is alarmed.

5.10 Ergonomic tests

(See 4.9)

Check that the EUT complies the ergonomic requirements of IEC 60945 and IEC 60936-1 or IEC 60936-2 as appropriate.

5.11 ENC issue status

(See 4.10)

Check the availability of date / number of update / issue number and date of issue of the SENC information on the display

5.12 Installation handbook checks

(See 4.11)

Check that the manufacturer's installation and operation manual includes appropriate cautions, setting up, commissioning and other installation matters.

IECNORM.COM: Click to view the full PDF of IEC 60936-3:2002
Withdrawn

Annex A (normative)

Specification of chart symbols and colours to be used

A.1 Minimum SENC information.

The minimum SENC information to be made available shall be the 'primary chart-information set' as defined in 3.1.

A.1.1 Primary chart information set

The chart features and symbols that make up the 'primary chart information set' are based on those defined in source documents of IEC 61174 and IHO S52 Appendix 2 as given in Table A.1.

Table A.1 – Specification reference for chart features and symbols

| Feature or Symbol | Specification | Based on IEC 61174 annex A | Colour See A.1.3 | Size See A.1.2 |
|-------------------|-----------------------------|----------------------------|----------------------------------------|-----------------------|
| 1 | Fixed and floating A to N | | See A.1.3 | 9x |
| 2 | Coastlines | 1.1 | See A.1.3 | 2x |
| 2.1 | Land (area fill) | – | See A.1.3 | – |
| 3 | Own ship's safety contour | 1.2 | Clearly differentiated from coastlines | 4x |
| 3.1 | Shallow side (area fill) | – | Lighter than radar background | – |
| 3.2 | Deep side (area fill) | – | As radar background | – |
| 4 | Dangers to navigation | 1.3, 1.4 | See A.1.3 | Symbol 4x Lines 2x |
| 5 | Chart boundary | 2.7 | | 2x |
| 5.1 | No chart domain (area fill) | – | | – |

A.1.2 Size

The size column gives the minimum permitted line width or symbol definition in pixels, i.e. at least 9 pixels for symbols and at least 4 pixels wide for the line defining the safety contour.

A.1.3 Colours

The colours shall be compatible with those of a radar map as given in annex C of IEC 60936-1 and are related to those in IEC 61174.

Where grey is used for certain features, the shade shall be chosen to distinguish between their respective features and radar information.

A.2 Presentation of chart symbols

The display presentation of chart symbols shall be within the SCAMIN and SCAMAX range as given in the ENC.