

# ECMA

Standardizing Information and Communication Systems

---

---

---

## Alphabetical Reference Index to IEC 950

---

---

IECNORM.COM : Click to view the full text of IEC 60950:1995 CSV

IECNORM.COM : Click to view the full PDF of IEC 60950-1:1995 CSV

# Withdrawn

# ECMA

Standardizing Information and Communication Systems

---

---

## **Alphabetical Reference Index to IEC 950**

**(IEC 950 second edition, including  
amendments 1, 2, 3 and 4)**

---

IECNORM.COM : Click to view the full PDF of IEC 60950:1995 CSV

IECNORM.COM : Click to view the full PDF of IEC 60950-1:1995 CSV

# Withdrawn

## Brief history

IEC 950, the safety standard for Information Technology equipment, is a large and complex document dealing with subjects as diverse as electrical safety, chemical safety, protection from heat and connection to telecommunication networks. It was considered that an index would be useful to facilitate the use of IEC 950 for both designers and test agencies.

In April 1993, ECMA TC12 (Safety for ITE) had the opportunity to organise this work. It was agreed that the document should take the form of a formal ECMA Technical Report, and as such, once approved, it would be made available free to any person or organisation requesting it. Incorporation of the Index in other documents is permitted, and subject to quoting the origin of the document. To this effect, a soft version is available from ECMA.

This Index, modified as necessary, is also part of the second edition of Standard ECMA-129, "Information Technology Equipment - Safety".

Liaison was maintained with IEC/TC74, and this third edition of ECMA TR/63 takes into account Amendment 4 to IEC 950.

Comments by users of this index on its usefulness and completeness will assist ECMA in the preparation of any future edition, and will be welcomed.

Adopted as an ECMA Technical Report by the General Assembly of December 1995.

IECNORM.COM : Click to view the full PDF of IEC 60950-1:1995 CSV

# Withdrawn

## Introduction

This index has been prepared under the auspices of ECMA/TC12 - Product Safety. It relates to IEC 950 - Safety of Information Technology Equipment, second edition (1991), including amendments 1, 2, 3 and 4.

This index is for information only and the selection of indexed items does not imply any particular importance.

Location references are clause or sub-clause numbers or annex letters.

Principal references are printed **Bold**.

References to the Introduction (Principles of Safety) are indicated as Introduction.

If a term is defined in the standard, its definition is indicated in the index by an asterisk, e.g. **RATED VOLTAGE** 1.2.1.1\*.

<b>A</b>		with a <b>TOOL</b>	1.7.18
		see also <b>RESTRICTED ACCESS LOCATIONS</b>	
abnormal conditions	Introduction, 1.3.1, <b>5.4</b>		
heating elements	4.3.20	accessibility <i>see</i> access	
overload protection	5.4.1, 5.4.3	actuators, mechanical, in interlock systems	2.8.7
sequence of testing	1.4.3	additional requirements outside the standard	1.1.2
simulated	5.4.6	adhesive	
fan not running	4.4.8	ageing test	4.3.22
general	4.4.1	application	2.9.6
one at a time	1.4.12	adjustment	
tests under abnormal conditions of		marking	
electrical components	5.4.6	for rated voltage	1.7.4
electromechanical components	5.4.5	for thermostats etc	1.7.13
heating thermoplastic parts	5.4.10	must not create a hazard	4.3.1, 4.3.2
motors	5.4.2, B.2	worst case conditions for tests	1.4.4, 1.4.9, 2.1.2, annex H
thermostats	K.6	air filters, flammability	4.4.3.1, 4.4.3.6
thermal cutout operates	1.2.11.4	air gaps	
within <b>FIRE ENCLOSURES</b>	4.4.6	<b>CLEARANCES</b> applicable	2.5.1, 2.9.2 (table 3 condition 6, table 5 condition 7)
abnormal operating conditions <i>see</i> abnormal conditions		<b>CLEARANCES</b> not applicable	2.9.1
abrasion resistance test	2.9.5	disconnect devices	2.6.2
access, accessibility		interlock switches	2.8.6
by		tip of test finger if voltage is over 1 kV	2.1.2, annex F (figure F.14 point A)
<b>OPERATORS</b> <i>see</i> <b>OPERATOR ACCESS AREAS</b>		altitude (elevation)	
<b>SERVICE PERSONNEL</b> <i>see</i> <b>SERVICE ACCESS AREAS</b>		during operation	1.1.2
definitions	<b>1.2.7</b>	during testing	5.3.2
means <b>OPERATOR</b> access (area)	1.2.7.1	ampacity of	
prevention by interlock	1.2.7.6	protective earthing conductors	2.3.3.3, 2.5.11
restricted	1.2.8.8, 2.1.4.1, 2.1.4.2, 6.2.2	power supply cords	<b>3.2.4</b>
through openings in <b>ENCLOSURES</b>		telecommunication wiring	6.5
2.1.2, annex F (figure F.14, point A)		terminals	3.3.5, 3.3.6
to		wires and cables	<b>3.1.1, 6.5</b>
controls	4.3.2	apertures <i>see</i> openings	
<b>ELV CIRCUITS</b> <i>see</i> <b>ELV CIRCUITS</b> , accessibility		appliance couplers	annex P (IEC 320)
energized parts	<b>2.1.1</b>	as disconnect devices <i>see</i> disconnection for servicing	
handles, levers, knobs	2.1.8, 4.3.5	as means of connection to power	3.2.1
interlocks	2.8.3, 2.8.5	fault testing	5.4.6
internal wiring	2.1.3, 2.9.4.4	in <b>PLUGGABLE EQUIPMENT</b>	1.2.5.1, 1.2.5.2
lasers	4.3.12, IEC 825	on detachable power supply cords	1.2.5.4
plugs and sockets	4.3.17		
moving parts	2.8.2, 4.1.2, 4.1.3		
sharp edges	4.1.4		
<b>TELECOMMUNICATION NETWORKS</b>	6.3.1, 6.4.1		
terminals	3.2.8		
<b>TNV CIRCUITS</b> <i>see</i> <b>TNV CIRCUITS</b> , accessibility			



stored charge	2.1.10, 2.4	WORKING VOLTAGES	2.2.7
cathode ray tubes, mechanical strength	4.2.8	in PRIMARY CIRCUITS	2.2.7.2
CCITT Recommendations <i>see</i> ITU-T Recommendations		in SECONDARY CIRCUITS	2.2.7.3
cemented joints in insulation	2.9.7, figures F.5, F.6, F.7	coated printed boards	2.9.5, annex F (figure F.13), R.1
ceramic and glass insulation		colours	
on printed boards	2.9.4.3	controls and indicators	1.7.8.2, annex P (IEC 73, ISO 3864)
temperature during tests	2.9.3 (table 6 condition 6), 5.1 (table 16 part 2), 5.4.9	flexible printed wiring	2.5.5
<i>see also</i> beads, ceramic		protective earthing conductors	2.5.5, 3.1.6, 3.2.4
CFR 47, part 68	M.3, annex P	comparative tracking index <i>see</i> c.t.i.	
chemical hazards	Introduction	components (definitions)	1.2.11*
<i>see also</i> corrosion and ozone		bridging insulation <i>see</i> bridging of insulation	
circuit characteristics (definitions)	1.2.8*	electro-magnetic	2.8.4, 5.4.5
circuits		mains voltage rating	1.6.3, 1.6.4
interconnection	2.10.1, 2.10.2	selection	1.5, 4.4
ELV <i>see</i> ELV CIRCUITS		separate testing	1.4.3, 2.2.3
LIMITED CURRENT <i>see</i> LIMITED CURRENT CIRCUITS		wound	2.9.4.4, 2.9.6, annex U
PRIMARY <i>see</i> PRIMARY CIRCUITS		<i>see also</i> transformers	
SECONDARY <i>see</i> SECONDARY CIRCUITS		conductive liquids	1.4.10
SELV <i>see</i> SELV CIRCUITS		conductor sizes <i>see</i> ampacity	
TNV <i>see</i> TNV CIRCUITS		connection terminals	1.7.7, 3.3
CLASS I and CLASS II EQUIPMENT in same system	2.5.4	connections <i>see also</i> disconnection	
CLASS I EQUIPMENT	1.2.4.1*, 1.7.2, 2.3.2, 5.4.9 (note)	definitions	1.2.5, 1.2.8.1, 1.2.12
BASIC INSULATION to be tested	5.4.9	between circuits	2.3.5, 2.4.3, 6.2.1.2
earthing	2.5.1, 6.3.2	INTERCONNECTING CABLES	1.2.11.7, 1.5.5, 3.1.1
marking of earthing terminals	1.7.7.1	to	
leakage current	5.2.5, 6.3.4, G.5	functional earth	2.5.2
CLASS II EQUIPMENT	1.2.4.2*, 1.7.1	other equipment	2.5.4, 2.10, 6.4.1
different from IEC 536 term	1.2.4.2 (note)	power supply	1.4.9, 3.1, 3.2, 3.3
earthing	2.5.2	protective earth	2.5, 3.1.6
leakage current	5.2.2, 6.3.4, G.2	TELECOMMUNICATION NETWORKS	2.3.1, 2.3.2 (note), clause 6, annex P (CFR 47, part 68)
CLASS III EQUIPMENT	1.2.4.3*	connectors	2.3.4, 3.2.1, 3.2.3, 4.3.17
no requirement for electric shock	1.3.3	contact by test probe	6.2.2.1, 6.4.1
classification of equipment	1.3.3	protective earthing contacts in	2.5.6, 2.5.7
CLEARANCES	1.2.10.2*, 2.2.1, 2.9.1, 2.9.2, annex F	<i>see also</i> appliance couplers, mains plugs, plugs, socket-outlets, <i>and</i> sockets	
<i>see also</i> IEC 664, interpolation, <i>and</i> separation distances		construction details	4.3
1.5 kV transients assumed	2.9.2.2 (note)	contact	
as OPERATIONAL INSULATION	5.4.4	gaps <i>see</i> air gaps	
at high altitudes	5.3.2 (table 18 condition 2)	pressure	3.1.8, 3.1.9, 3.1.10, 3.3.7
behind conductive ENCLOSURES	2.1.6	reliability	K.1
between uninsulated conductors	3.1.4	touching <i>see</i> access	
divided by floating parts	2.9.1, annex F (figure F.15)	CONTINUOUS OPERATION	1.2.2.3*, 5.1
in		control, quality <i>see</i> quality control	
encapsulated parts	2.9.7	controls	
enclosed parts	2.9.6	<i>see also</i> colours	
PRIMARY CIRCUITS	2.9.2.1	mains voltage adjustment	1.7.8, 4.3.1
SECONDARY CIRCUITS	2.9.2.2	manual	
increased by coatings	2.9.8	accessibility	4.3.2
integrity in service	2.9.1, C.2	fixing	4.3.5
measured through openings	2.9.1, annex F (figure F.14 point B)	isolation	2.1.7, 2.1.8
must be adequate	2.2.4	operated during test	5.2.3, 5.2.4, G.3.2, G.4.2, annex H
reduced	R.2	marking	1.7.8
variable	2.9.9, 5.3.2	temperature	5.3.2 (table 16 part 2)

thermal	1.2.11, 1.4.4, 1.5.2, 5.4.8, annex K	MANUAL RESET	1.2.11.6*
cord anchorage bushings, flammability	4.4.3.5	CLEARANCES not applicable	2.9.1
cord anchorages, power cord	3.2.5	reliability	K.5
cord guards, power cord	3.2.7		
integral with cord	1.2.5.5	<b>D</b>	
ON CLASS II EQUIPMENT	3.2.6	d.c. component of waveform	1.4.11, 6.2.1.1
CORDS, power supply <i>see</i> power (supply) cords		<i>see also</i> ripple	
corrosion		d.c. current for tests	2.5.11
by consumable materials	4.3.4	d.c. motors, testing	B.1, B.7, B.10
of protective earthing terminals	2.5.10	D.C. VOLTAGE	Introduction, 1.2.14.3*
country notes		for tests, instead of a.c.	6.4.2.2, 6.4.2.3, annex R
general	1.1.2, 3.2.2, 3.2.4, M.1	testing capacitors	5.3.2
Austria	6.4.2.1	supply	1.4.5, 1.7.1, 5.1 (table 18 conditions 6, 7 and 8)
Canada	4.4.5.2	<i>see also</i> ripple	
CENELEC countries	2.7.1	DECORATIVE PARTS	1.2.6.5*, 4.4.4
Denmark	2.5.2, 6.2.1.2, 6.3.3.1	<i>see also</i> ENCLOSURES	
Finland	6.2.1.4	definitions	<b>1.2</b>
Norway	1.6.4, 1.7.2, 2.9.1, 5.4.9, 6.2.1.2, 6.2.1.4, 6.2.1.5, 6.3.3.2	changed	annex V
Sweden	1.7.2, 6.3.3.1	miscellaneous	1.2.14
United Kingdom	3.2.1	DETACHABLE POWER SUPPLY CORDS <i>see</i> power (supply) cords	
United States of America	4.4.4, 4.4.5.2	DIRECT PLUG-IN EQUIPMENT	1.2.3.6*, 3.2.1, 4.2.5, 4.2.7, 4.3.18
coverings, protective, in place during tests	5.4.7	disconnect devices <i>see</i> disconnection for servicing	
covers <i>see also</i> doors and covers		disconnection	2.6
of supply wiring space	3.2.8	automatic	<b>2.7</b> , 4.3.20, 5.4.2
transparent	4.2.1, 4.4.4	by interlocks	2.8
CREEPAGE DISTANCES	1.2.10.1*, 2.2.1, 2.9.1, <b>2.9.3</b> , annex F	for servicing (isolation)	2.6
as OPERATIONAL INSULATION	5.4.4	disconnect devices	2.6.2, 2.6.6, 2.6.7
between uninsulated conductors	3.1.4	appliance couplers	2.5.7
divided by floating parts	2.9.1, annex F (figure F.15)	heating elements	4.3.20
in encapsulated parts	2.9.7	in building installations	2.6.3, 2.6.6, 2.6.7
in enclosed parts	2.9.6	switches	2.6.5, 2.6.8
increased by coatings	2.9.8	three-phase	2.6.7
integrity in service	C.2	multiple sources, marking	1.7.9
measured through openings	2.9.1, annex F (figure F.14 point B)	from TELECOMMUNICATION NETWORKS	6.2.2.2
must be adequate	2.2.4	distances through insulation	2.5, <b>2.9.4.1</b>
variable	2.9.9, 5.3.2	ELV CIRCUITS	2.1.3.1
WORKING VOLTAGES	2.2.7.4	must be adequate	2.2.4
<i>see also</i> IEC 664, interpolation, and separation distances		printed boards	2.9.4.3
c.t.i.	2.9.3 (table 6), annex P (IEC 112)	variable	2.9.9, 5.3.2
current <i>see also</i> RATED CURRENT		doors and covers	4.2.2, 4.3.15, 4.3.16, 4.4.7
in human body	Introduction, annex Q (IEC 479)	access through	2.1.2, 2.8.2, 2.8.3
input determination	1.4.9	marking on	1.7.1
input maximum	1.6.1	doors, position during stability tests	4.1.1
leakage	Introduction, 5.2, 6.3.4, annex D, annex G	DOUBLE INSULATION	Introduction, 1.2.4.1, 1.2.4.2, 1.2.9.4*, 1.2.9.5
high	1.7.12, 5.2.5, G.5	application	2.1.8, 2.1.9, 2.2.6
maximum	5.2.2, 6.3.4, G.2	in	
locked rotor	B.1, B.5	CLASS I EQUIPMENT	1.2.4.1, 2.5.1
maximum ringing signal	M.2, M.3	CLASS II EQUIPMENT	1.2.4.2, 2.5.2
r.m.s. value implied unless otherwise specified	1.2	HAZARDOUS VOLTAGE circuits	2.1.3.2
to telecommunication wiring	6.5	internal wiring	2.1.3.2
current-carrying capacity <i>see</i> ampacity		SELV CIRCUITS	2.3.3, 2.3.3.1, 2.3.5
CUT-OUTS, THERMAL	1.2.11.4*, 4.2.7, 4.3.20, 5.4, B.2, C.1	TNV CIRCUITS	6.2.1.4, 6.2.1.5
AUTOMATIC RESET	1.2.11.5*, 4.1.2	wound components	2.9.4.4

on coated printed boards	2.9.5, annex F (figure F.14)	accessibility	2.1.1, 2.1.2, 2.1.4.1, 2.1.7, 3.2.1
BASIC and SUPPLEMENTARY can be interchanged	2.2.6	in SERVICE ACCESS AREAS	2.1.4.1
bridging <i>see</i> bridging of insulation		of insulation	2.1.3.1
care while testing	5.3.2	as interconnection circuits	2.10.2, 2.10.3
dimensions	2.9.2 (table 3 condition 3, table 5 condition 2)	insulation	2.2.6
<i>see also</i> BASIC and SUPPLEMENTARY INSULATION		reed switches in	2.8.6.3
internal wiring	2.1.3.2	e.m.c. <i>see</i> electrical filters	
integrity		enamel, not adequate safety insulation	2.1.2, 2.9.4.2, 2.9.7
after a test	5.4.9	encapsulated parts	2.9.7
in service	3.3.9	enclosed parts	2.9.6
unearthed parts within	2.2.6	ENCLOSURES	4.2, 4.4.4, 5.4.9
WORKING VOLTAGES	2.2.7	bottoms	4.3.16, 4.4.6, A.5.1
meaning, for DOUBLE INSULATION	2.2.7.1	definitions	1.2.6*
drop test	4.2.5, 4.2.7	conductive	2.1.6, 2.9.2.1 (table 3 condition 6)
duty cycles, marking short-time intermittent	1.7.3	flammability	A.1, A.2, A.5
dust		inlet bushings in	3.2.6
additional requirements if present	1.1.3, 4.3.4	openings in	2.1.2, 2.9.1, 4.3.14, 4.3.15, 4.3.16, 4.3.22
explosion limit	1.2.13.10	<i>see also</i> ELECTRICAL ENCLOSURES, FIRE ENCLOSURES, MECHANICAL ENCLOSURES, DECORATIVE PARTS, IEC 529, and IEC 1032	
excluded in pollution degree 1	2.9.1	energy hazards	Introduction, 5.4.9
<b>E</b>		disconnection	2.6.11
earth, earthing	2.5	in	
functional	2.5.2, 5.4.4	LIMITED CURRENT CIRCUITS	2.4.2
protective <i>see</i> protective earth, and protective earthing		OPERATOR ACCESS AREAS	2.1.1, 2.1.5
permanent connection	6.3.3.2	SERVICE ACCESS AREAS	2.1.4.1
potential	2.3.1, 6.1	RESTRICTED ACCESS LOCATIONS	2.1.4.2
voltage measurements to	1.4.13	multiple sources	1.7.9
earth fault protection	2.7	reduced by interlocks	2.8.2
earth leakage current, <i>see</i> leakage current		within ENCLOSURES	2.1.6
electric shock	Introduction	ENERGY LEVELS, HAZARDOUS	1.2.8.7*
caused by		equipment electrical ratings (definitions)	1.2.1
heat damage	5.4.4	EQUIPMENT FOR BUILDING-IN	1.2.3.5*, 2.1.2, 5.1
overload	5.4.1	equivalent materials permitted	1.4.14
stored charge	2.1.10	explosion	
touching bare conductive parts	2.1.1	(implosion) of cathode ray tube	4.2.8
classification of equipment for protection	1.2.4, 1.3.3	of battery	1.7.17, 4.3.21, 4.4.8
by insulation	1.3.1	of high pressure lamp	4.1.5
by interlocks	1.2.9	limit <i>see</i> LIMIT, EXPLOSION	
by TNV CIRCUITS	2.8.2	<b>F</b>	
two levels	6.2	failures	5.4.1
warning marks	Introduction	consequences	1.4.1
electric strength tests	5.3	of	
WORKING VOLTAGES for	2.2.7.1, 2.2.7.5	components	Introduction, 2.3.3, 5.4.6
<i>NOTE - electric strength tests are required in numerous places in the standard</i>		in LIMITED CURRENT CIRCUITS	2.4.1, 2.4.3
ELECTRICAL ENCLOSURES	1.2.4.2, 1.2.6.4*, 1.2.10.3, 2.1.2, 4.3.15, 4.3.16, 4.4.4	in SELV CIRCUITS	2.3.1, 2.3.5
<i>see also</i> ENCLOSURES		in TNV CIRCUITS	6.2.1.1, 6.2.1.2, 6.2.1.5
electrical filters	2.9.2.2 (table 5 condition 4), 5.2.4, 5.3.2, 5.4.6, G.4	ENCLOSURES	4.1.2, 4.2.4, 4.2.7
electrochemical potentials	2.5.10, annex J	equipment to operate	4.4.6, 5.4.5
electromechanical components	2.11, 5.4.5	insulation	2.3.3
elevation <i>see</i> altitude		motor capacitors	B.8
ELV CIRCUITS	1.2.8.4*	screwed connections	4.3.13
		mechanical	5.4.5
		<i>see also</i> faults	

fault conditions		FLAMMABILITY CLASS	
difference between ELV CIRCUITS and SELV CIRCUITS	2.3.3	5V	1.2.13.5*, A.9
protection required	2.7.1, 2.7.3, 2.7.4, 4.4.3.3	applications	1.2.13.1, 4.4.1, 4.4.4
fault current	2.3.3.3, 2.7.3, 2.7.4	HB	1.2.13.8*, A.8
faults	1.3.1, 5.4	applications	1.2.13.1, 4.4.3.3, 4.4.3.5, 4.4.3.6, 4.4.1, 4.4.4
affecting air filters	4.4.3.6	HBF (foamed material)	1.2.13.9*, A.7
consequential	Introduction, 1.4.12, 1.5.3, 2.4.1	applications	1.2.13.1, 4.4.3.3, 4.4.3.6, 4.4.1
earth	2.7.1, 2.7.4	HF-1 (foamed material)	1.2.13.6*, A.7
in		applications	1.2.13.1, 4.4.1
capacitors	1.4.12, 4.4.1, 4.4.3.3	HF-2 (foamed material)	1.2.13.7*, A.7
CLASS I EQUIPMENT	2.5.1	applications	1.2.13.1, 4.4.1
LIMITED CURRENT CIRCUITS	1.2.8.6, 2.4.1	V-0	1.2.13.2*, A.6
limited power sources	2.11	applications	1.2.13.1, 4.4.1, A.3.6
power distribution systems	1.2.14.7 (note 2), 2.3.1, 6.1, annex V	V-1	1.2.13.3*, A.6
protective earthing connections	5.2, annex G	applications	1.2.13.1, 4.4.1, 4.4.2, 4.4.3.3, 4.4.3.6, 4.4.4, 4.4.5, 4.4.6, 5.4.4
ringing signal circuits	M.2, M.3.3	V-2	1.2.13.4*, A.6
not covered in 5.4	2.7.2	applications	1.2.13.1, 1.5.4, 4.4.1, 4.4.3.2, 4.4.3.3, 4.4.3.4, 4.4.3.6
simulated	1.4.12, 2.7.4, 5.4.5, 5.4.6	flammability	4.4.3.2
single		better class permitted	1.4.14
limits to be maintained	2.3.1, 2.11, 6.2.1.1, 6.2.1.2	exemptions	4.4.3.3
no hazard	Introduction, 1.2.8.5, 1.2.8.6	tests	A.1, A.2, A.6, A.7, A.8, A.9
<i>see also</i> abnormal conditions <i>and</i> failure		for FIRE ENCLOSURES	A.1, A.2
FCC Rules, Part 68	M.3, annex P	floating parts and windings	<i>see</i> unearthed parts and windings
FEP (fluoro ethylene propylene)	2.9.4.4, 4.4.3.4, 4.4.5.2, 4.4.6	foil (conductive)	
filters, air, flammability	4.4.3.1, 4.4.3.6	in definitions	1.2.7.5, 1.2.10.3
filters, electrical <i>see</i> electrical filters <i>and</i> capacitors, filter		in tests	
FIRE ENCLOSURES	1.2.6.2*	on non-conductive surfaces	2.9.1, 2.9.7, 5.3.2, 6.4.2
air filters in	4.4.3.6	10 cm x 20 cm	5.2.2, G.2
components in	4.4.5	on wire 3.1.5	
construction	4.4.6, 4.4.7, A.1, A.2, A.5	frequency	
required	4.4.5	in LIMITED CURRENT CIRCUITS	2.4.2
<i>see also</i> ENCLOSURES		of supply	1.4.11, 1.7.1, 2.6.12, 3.2.1, C.1
fire protection equipment, not in Scope of standard	1.1.3	during tests	1.4.6
fire risks	Introduction, 1.3.1, 4.4.2, annex P (IEC 695)	of test voltages	5.3.2, 6.4.2.2, R.1, R.2
caused by		of WORKING VOLTAGES	2.2.2, 2.9.1
batteries	4.3.21	of ringing signals	M.2, M.3
flammable liquids	4.4.8	in TNV CIRCUITS	6.2.1.1 b), 6.4.2.1
ingress of water	annex T	FREQUENCY, RATED	1.2.1.4*, 1.4.6, 1.7.1, 1.7.4
OPERATIONAL INSULATION	5.4.4	FREQUENCY RANGE, RATED	1.2.1.5*, 1.4.6, 1.7.1, 1.7.4
overloads	5.4.1	fuses	annex Q (IEC 127)
FIXED EQUIPMENT	1.2.3.4*, 1.7.1	breaking capacity	2.7.3
fixed wiring <i>see</i> building installations		in neutral conductors	2.7.6
fixing (securing) of		location	1.7.11, 2.7.4
parts		marking	1.7.6
adhesives	4.3.22	minimum number	2.7.4
cord guards	3.2.7	not allowed in protective earthing conductors	2.5.3
conductors	3.3.2, 3.3.4, 3.3.7	operating during motor tests	B.2
controls	4.3.5	performance	2.11 (table 9 condition 4)
insulation	2.5.1, 2.9.6, 3.1.7	protecting capacitors	5.4.8
inlet bushings	3.2.6	warning to SERVICE PERSONNEL	2.7.6
minor parts	4.3.9	<b>G</b>	
two fixings not loose at the same time	3.3.4, 4.3.9, C.2	gap <i>see</i> air gap	
wiring	2.1.3.1, 2.1.3.2, 2.3.3.1	gas discharge tubes	5.3, 6.4.2.3
units of equipment	1.2.3.4, 4.1.1	<i>see also</i> surge arrestors	

gas flames for flammability testing	annex A	heat	
gases		hazards	Introduction, 1.7.7.2
flammable	1.1.2, 1.2.13.10, 4.3.12	red, ceramic curing temperature	2.9.4.3
inert	4.4.3.3	shock test	U.2.3
produced by equipment	4.3.4	sinks	5.1
		<i>see also fire hazards</i>	
glass <i>see also</i> ceramic and glass insulation		heating	5.1
as ENCLOSURE material	4.4.4	heating elements	4.3.20
cloth, prepreg	2.9.4.3 (note 1)	high current arcing ignition tests	4.4.4, A.3
platen, no steel ball test	4.2.4	high voltage components	1.5.4
grease	4.3.11, 4.4.8	hot flaming oil tests	4.4.6, A.5
green-and-yellow <i>see</i> colours		hot wire ignition tests	4.4.4, A.4
grips <i>see</i> handles		humidity	2.2.2
ground <i>see</i> earth		additional requirements if high	1.1.2
guards, mechanical	2.1.4.1, 2.1.4.2	conditioning (treatment)	2.2.2, 2.2.3, 2.9.5, 2.9.6
		relative (r.h.) during tests	4.2.6, 4.3.22, A.6.3, A.7.3, A.8.3, A.9.3, U.2
<b>H</b>		hygroscopic material, not to be used as insulation	2.2.2
HAND-HELD EQUIPMENT	1.2.3.2*		
leakage current	5.2.2, G.2	<b>I</b>	
maximum RATED VOLTAGE 250 V	1.6.2	ICRP 15	annex H, annex Q
mechanical strength	4.2.5	IEC 65	1.5.4, 4.2.8, annex P
power cords	3.2.7, 3.2.8	IEC 73	1.7.8.2, annex P
separation from TELECOMMUNICATION NETWORKS	6.4.1 c)	IEC 83	1.7.5, 2.1.2, 2.3.4, annex P
handles		IEC 85	1.4.7, 5.1 (table 16 condition 2), annex P
conductive	2.1.8	IEC 112	2.9.3, annex P
must be reliably fixed	4.3.5	IEC 127	2.7.3, annex Q
no mechanical strength test	4.2.1	IEC 227	3.2.4, annex P
shafts of	2.1.7	IEC 245	3.2.4, annex P
temperature rise	5.1	IEC 309	1.2.5.2, 3.2.3, annex P
HAZARDOUS ENERGY LEVEL	1.2.8.7*	IEC 320	2.3.4, 3.2.3, 3.2.4, annex P
<i>see also</i> energy hazards		IEC 364	1.2.8.5, annex P
HAZARDOUS VOLTAGE circuits		IEC 364-7-707	1.7.12, annex Q
insulation	2.1.3.2	IEC 384-14	1.5.6, 2.2.8.1, annex P
<i>see also</i> HAZARDOUS VOLTAGES		IEC 410	annex Q, R.1, R.2
HAZARDOUS VOLTAGES	1.2.8.3*	IEC 417	1.7.1, 1.7.7.1, 1.7.8.3, annex P
multiple sources	1.7.9, 2.6.11	IEC 479	M.2, annex Q
not to be accessible		IEC 529	annex Q
after tests	4.2.4, 5.4.9	IEC 529, extract	annex T
at appliance inlets	3.2.3	IEC 536	1.2.4.2, annex Q
at connectors	3.2.1	IEC 664	1.1.2, 2.9.1, 2.9.2.1 (table 3), annex P
in OPERATOR ACCESS AREAS	2.1	IEC 695-2-2	A.2.7, annex P
on thermoplastic parts	5.4.10	IEC 707	1.2.13.5, 1.7.12, annex Q
protection by earthing	2.5.1, 2.5.2	IEC 730-1	2.1.1, annex P
separation from			
SELV CIRCUITS	2.3.3, 2.3.4		
TNV CIRCUITS	6.2.1.4, 6.2.1.5		
warning notices	1.7.9, 2.7.6		
hazards	Introduction		
access using a TOOL	1.7.18		
basis of design	Introduction, 1.3.1		
energy <i>see</i> energy hazards			
fire <i>see</i> fire risks			
information to the USER	1.3.2		
not to be accessible after tests	4.2.4, 5.4.9		

IEC 825	4.13.12, annex P	tests	5.3.2, 6.3.3, 6.4.2
IEC 851	annex P, U.2, U.3	with varying dimensions	2.9.9, 5.3.2
IEC 885-1	3.1.5, annex P	interconnection <i>see</i> connections	
IEC 1032	Figure 19 (p. 239), Figure 20 (p. 241), annex Q	interleaved insulation in wound components	2.9.4.1, 2.9.4.2, 2.9.4.4, annex U
IEC 1058-1	2.6.2, 2.8.6, annex P	INTERLOCKS <i>see</i> SAFETY INTERLOCKS	
ignition tests	4.4.4, A.3, A.4, A.5	INTERMITTENT OPERATION	1.2.2.5*, 5.1, 5.4.8
impact tests	4.2.4, 4.2.7	interpolation	
implosion of cathode ray tubes	4.2.8	insulation spacings	2.9.1, 2.9.2 (tables 3 and 5), 2.9.3, 2.9.5 (table 7)
impulse tests <i>see</i> tests, impulse		electric strength test voltages	5.3.2 (table 18)
indicators		ionizing radiation	Introduction, 4.3.12, annex H
colours	1.7.8.2, , annex P (IEC 73, ISO 3864)	ISO 216	1.1.3, annex P
marking	1.7.8	ISO 261	3.3.3, annex P
lamps exempt from flammability requirements	4.4.3.3	ISO 262	3.3.3, annex P
information technology equipment,		ISO 2859	annex Q, R.1, R.2
connection to TELECOMMUNICATION NETWORKS	<b>clause 6</b>	ISO 3864	1.7.18, annex P
examples in Scope of standard	1.1.1	ISO 4045	B.7, annex P
INTERCONNECTING CABLES	1.2.11.7, 1.5.5	ISO 7000	1.7.1, annex P
interconnection of equipment	2.10	isolation (from the supply) <i>see</i> disconnection for servicing	
internal wiring	2.1.3	IT POWER SYSTEMS	1.2.12.3*
ingress of water	1.1.2, 2.9.6, 2.9.7, annex T	heating elements	4.3.20
ink	4.4.8	leakage current	annex G
ink tubes	4.4.3.3	marking of equipment	1.7.10
inlet bushings, power cord	3.2	primary power isolation (three phase)	2.6.7
installations, building <i>see</i> building installations		protective devices	2.7.4
installation categories <i>see</i> transients (overvoltage categories)		voltage rating of components	1.6.4
installation instructions	1.7.2, 1.7.4	ITU-T Recommendation K.11	6.1, annex Q
disconnect devices	2.6.3, 2.6.6, 2.6.7, 2.6.9	ITU-T Recommendation K.17	annex N, annex P
physical	4.1.1, annex T	ITU-T Recommendation K.21	annex N, annex P
RESTRICTED ACCESS LOCATIONS	1.7.19	<i>NOTE - ITU-T Recommendations were formerly CCITT Recommendations</i>	
wiring		<b>K</b>	
earth	6.2.1.2, 6.3.2, 6.3.3.2	knobs <i>see</i> handles	
power	1.7.7.2, 1.7.10, 1.7.11	<b>L</b>	
telecommunication	6.5	labels <i>see</i> warning labels	
instructions	1.7.2, 2.5.10, annex R	lamps	
<i>see also</i> installation instructions <i>and</i> operating instructions		high pressure	4.1.5
insulation	1.2.9, 2.2	left in place during tests	2.1.2
application	2.2.5, 2.2.6	no flammability requirement	4.4.3.3
BASIC <i>see</i> BASIC INSULATION		languages for instructions and marking	1.7.14
better grade permitted	1.4.14	lasers	Introduction, 4.3.12, annex P (IEC 825)
bridging <i>see</i> bridging of insulation		leakage current	5.2, 6.3.4, annex G
dimensions	2.2.7, 2.9	high	1.7.12, 5.2.5, G.2.5
DOUBLE <i>see</i> DOUBLE INSULATION		IT POWER SYSTEMS	annex G
for more than one requirement	6.1 (note 3)	measuring instrument	annex D
in transformers	2.2.6, 2.2.7.1, 2.9.9, C.2		
on winding wire <i>see</i> winding wire			
OPERATIONAL <i>see</i> OPERATIONAL INSULATION			
printed boards <i>see</i> printed boards			
REINFORCED <i>see</i> REINFORCED INSULATION			
SUPPLEMENTARY <i>see</i> SUPPLEMENTARY INSULATION			

to and from TELECOMMUNICATION NETWORKS	<b>6.3.4</b>	material group (tracking) <i>see</i> c.t.i.	
legal requirements	1.1.2 (note), 6.1 (note 2)	materials	
<i>see also</i> country notes		to be reliable	Introduction
levers <i>see</i> handles		use of better materials permitted	1.4.14
lightning <i>see</i> transients		maximum	
LIMIT, EXPLOSION	1.2.13.10*, 4.4.8	amount of flammable liquid	4.4.8
limits <i>see</i> maximum		current to telecommunication wiring	6.5
LIMITED CURRENT CIRCUITS	1.2.8.6*, <b>2.4</b> , 2.2.6 (table 0.1 condition 6)	input current	1.6.1
connections to other equipment	2.10.2	ionizing radiation	4.3.12, annex H
in OPERATOR ACCESS AREAS	2.1.1, 2.2.8.3	leakage current	5.2.2, 6.3.4, G.2
limited power sources	2.11, 4.4.5.1, 4.4.5.2	LIMITED CURRENT CIRCUIT levels	2.4
LIMITERS, TEMPERATURE	1.2.11.3*, annex K	limited power source levels	2.11
liquids	4.3.4, 4.3.19, 4.4.3.3	ozone level	1.7.2
conductive	1.4.10	RATED VOLTAGE	
flammable	4.3.12, 4.4.8	600 V in Scope of standard	1.1.1
parts in contact	5.1	250 V for HAND-HELD EQUIPMENT	1.6.2
loosening <i>see</i> fixing		ringing signal level	M.2, M.3
louvres	4.3.16	ripple, <i>see</i> ripple	
<i>see also</i> openings		SELV CIRCUIT voltages	
<b>M</b>		normal	2.3.2
mains	5.3.2	fault conditions	2.3.3
as telecommunication transmission medium	1.2.14.7	temperature (rise)	1.4.7, 5.1
capacitors	1.5.6, 2.1.10	in OPERATOR ACCESS AREAS	<b>5.1</b>
earth	2.5.11	of	
frequency	1.4.11	conductors	3.1.1
neutral	2.6.6	insulation during tests	5.4.9
plugs	1.2.3.6, 2.5.7, 3.2.1, 4.3.18	materials and components	<b>5.1</b>
transients	1.1.2	motors	B.3
voltage	1.6.5, 1.7.1, 2.9.2.1	transformers	C.1
adjustment	1.7.4	windings	1.4.8, annex E
d.c.	1.4.5, 1.7.1, 5.1 (table 18 conditions 6, 7 and 8)	TNV CIRCUIT voltages	
defined as phase to neutral	2.9.1	TNV-1 CIRCUITS	6.2.1.1 a)
<i>see also</i> PRIMARY CIRCUITS		TNV-2 and TNV-3 CIRCUITS	6.2.1.1 b)
marking	<b>1.7</b>	transients <i>see</i> transients	
<i>see also</i> warning labels		MECHANICAL ENCLOSURES	1.2.6.3*, <b>4.1.2</b> , 4.1.5, 4.4.4
battery compartments	6.2.2.2	<i>see also</i> ENCLOSURES	
durability	1.7.15	mechanical hazards	Introduction, 2.8.2, 4.1
equipment in RESTRICTED ACCESS LOCATIONS	1.7.19	mechanical shock	
equipment that must be earthed	6.3.3.2	affecting CLEARANCES	2.9.1
high leakage current	1.7.2	affecting interlocks	2.8.3
labels <i>see</i> warning labels		mechanical strength	<b>4.2</b>
lithium batteries	1.7.17	cathode ray tubes	4.2.8
mating of plugs and sockets	4.3.17	handles	4.2.1
multiple sources	2.6.12	no test in MECHANICAL ENCLOSURES	4.2.1
of stabilizing devices	4.1.1	mechanical stress, on insulation	2.9.4.1, 2.9.4.4
T-marking	5.1	mechanically operated interlock switches	2.8.4, 2.8.6
unearthed parts in SERVICE ACCESS AREAS	2.5.1	mobility of equipment (definitions)	1.2.3
mass		moisture <i>see</i> humidity <i>and</i> water ingress	
of equipment, criterion for test	1.2.3.1, 2.1.2, 3.2.4, 3.2.5, 4.1.1, 4.2.5, 4.4.4, A.1, A.2	motor overload	5.4.2
cord guard test	3.2.7	motor tests	annex B
steel ball test	4.2.4	motor-generator sets, not in Scope of standard	1.1.3
		motors	
		requirements	5.4.2
		tests	annex B

at RATED VOLTAGE	B.2	OPERATIONAL INSULATION	1.2.9.1*
d.c. motors	B.6, B.7	application	2.1.1, 2.1.2, 2.2.6
locked rotor	B.5	bridging <i>see</i> bridging of insulation	
running overload	B.4	dimensions	<b>2.9.2, 2.9.3, 2.9.4.1</b> , annex F
series motors	B.10	electric strength	5.3.2
stepper motors	B.1	failure to be simulated	5.4.4 c)
three-phase motors	B.9	smaller spacings permitted	2.9.1, 5.4.4
MOVABLE EQUIPMENT	1.2.3.1*, 1.2.3.3	WORKING VOLTAGES	2.2.7
FIRE ENCLOSURES	4.4.4, A.1, A.2	OPERATORS ( <i>or</i> USERS)	1.2.14.5*
leakage current	5.2.2, 6.3.4, G.2	information supplied to	1.3.2, 1.7.2
power supply cord flexing test	3.2.4	of telecommunications equipment	6.3, 6.4
movable parts of equipment	2.9.1	servicing by OPERATOR	
moving parts of equipment	2.8.2, 4.1.2, 4.1.3	handling insulation	2.9.4.2
multiple power sources	1.1.3, 2.6.12	high pressure lamps	4.1.5
		stability	4.1.1
		test samples to be as supplied to USERS	1.4.3
<b>N</b>		OPERATOR ACCESS AREAS	Introduction, 1.2.7.1*, <b>2.1</b>
national requirements <i>see</i> country notes		access probes	2.1.2, 6.2.2.1, 6.2.2.2
neoprene	4.4.3.4, 4.4.5.2, 4.4.6	batteries in	1.7.17
<i>see also</i> rubber, synthetic		compared with RESTRICTED ACCESS LOCATIONS	1.2.7.3
networks <i>see</i> TELECOMMUNICATION NETWORKS		doors in FIRE ENCLOSURES	4.4.7
neutral conductors	1.6.3	energy hazards in	Introduction, 2.1.5
disconnection by disconnect devices	2.6.6, 2.6.7	fuses	1.7.6
disconnection by protective devices	2.7.4, 4.3.20	insulation	
fuses in neutral, warning required	2.7.6	of ELV CIRCUITS	2.1.3.1
marking of terminals	1.7.7.2	of HAZARDOUS VOLTAGE circuits	2.1.3.2
reliably identified	2.6.6, 2.7.4	ionizing radiation in	Introduction, 4.3.12, annex H
nominal mains voltages	2.9.2.1 (tables 3 and 5)	LIMITED CURRENT CIRCUITS	2.4.1
NON-DETACHABLE POWER SUPPLY CORDS		marking for lithium batteries	1.7.17
<i>see</i> power (supply) cords		marking of power outlets	1.7.5
NORMAL LOAD conditions	1.2.2.1*, 1.6.1, 5.1, annex L	markings to be visible	1.7.1
normative references	annex P	TOOL required for access	1.2.7.1, 1.7.18
<b>O</b>		overcurrent and earth fault protection	Introduction, <b>2.7</b>
oil	4.3.11, 4.4.8	overcurrent protection devices	
hot flaming oil test	A.5	air gaps	2.9.1
<i>see also</i> liquids		in limited power sources	2.11
openings	4.3.14	not damaged during tests	4.2.7
access through	2.1.2, 4.1.2	overcurrent protection for telecommunication wiring	6.5
for power cords	3.2.6, 3.2.7	overcurrent protection for transformers	5.4.3, C.1
in FIRE ENCLOSURES	4.4.3.3, A.2.1	overriding interlocks	2.8.5
in sides of ENCLOSURES	4.3.16	overheating of telecommunication wiring	6.5
in tops of ENCLOSURES	4.3.15	overload	
measuring through	2.9.1	mechanical	5.4.1
ventilation	4.4.3.3, A.2.1	electrical	3.1.1, 5.4.1, 6.2.1, 6.5
operating conditions (definitions)	1.2.2	<i>see also</i> overcurrent	
operating instructions	1.2.2.1, 1.2.7.1, 1.4.4, 1.7.2, 1.7.17, 4.4.7, 4.4.8, 6.2.2.2, annex L	motors	5.4.2, B.2 (table B.2), B.4, B.5, B.6, B.7
OPERATION, CONTINUOUS	1.2.2.3*, 5.1	tests	5.4.6
OPERATION, INTERMITTENT	1.2.2.5*, 5.1, 5.4.2	transformers	<b>5.4.3, C.1, C.2</b>
OPERATION, SHORT-TIME	1.2.2.4*, 5.1, 5.4.2, 5.4.8	overvoltage categories <i>see</i> transients (overvoltage categories)	
		overvoltages	1.1.2, 1.2.8.9, 1.2.8.10, 1.2.8.11, 2.3.2, (note), 6.1 (note 1), annex Q (ITU-T Recommendation K.11)
		<i>see also</i> transients	
		ozone	1.7.2

<b>P</b>		ordinary	1.7.7.2, 3.2.8, 3.3.1, 3.3.8
		special	3.3.2
Part 68, FCC Rules	M.3, annex P	inside the equipment	3.1.5
passive devices, not in Scope of standard	1.1.3	screened	3.2.5
peak, overvoltage	2.9.1, 2.9.2.1, 2.9.2.2, 6.1, 6.4.2.5	voltage drop not measured	1.4.13, 2.5.11
peak voltage, repetitive	2.2.7.2, 2.9.2.1	power supply (units)	1.7.7.1, 2.2.7 (note)
PERMANENTLY CONNECTED EQUIPMENT	1.2.5.3*	POWER SYSTEMS <i>see</i> IT, TN, and TT POWER SYSTEMS	
discharge of capacitors	2.1.10	single phase, three wire	1.2.12.1
disconnect devices	2.6.3	prepreg	2.9.4.3 (note 1)
marking	1.7.2, 1.7.7.2, 1.7.11	PRIMARY CIRCUITS	1.2.8.1*, 1.2.8.2, 2.9.2.2
leakage current	5.2.2, 5.2.5, G.2, G.5	CLEARANCES in	2.9.2.1
overcurrent protection	1.7.11, 2.7.3	components in	5.4.6
terminals	3.2.2, 3.3.1	fuses	2.7.3
permission to connect to TELECOMMUNICATION NETWORKS		interlock switches	2.8.6.1
<i>see</i> legal requirements		filters in	Introduction, 5.2, annex G
personnel, network service	6.3	marking of switches	1.7.8.3
PERSONNEL, SERVICE <i>see</i> SERVICE PERSONNEL		marking of terminals	1.7.7.2
plating, protective earthing components	2.5.10	protection	2.7.1
PLUGGABLE EQUIPMENT	1.7.2, 4.3.20	WORKING VOLTAGES in	2.2.7.1, 2.2.7.2
discharging filter capacitors	2.1.10	<i>see also</i> mains	
isolation	2.6.2, 2.6.6	PRIMARY power	
leakage current	5.2.2, G.2	connections	3.2
overcurrent protection	2.7.3, 2.7.4	isolation <i>see</i> disconnection	
TYPE A	1.2.5.1*	overload	3.1.1
test BASIC INSULATION	5.4.9	principles of safety	Introduction (page 17)
TYPE B	1.2.5.2*, 1.7.11, 2.7.3, 5.2.5, G.5	printed boards	
plugs	2.3.4	coated, CLEARANCES and CREEPAGE DISTANCES	2.9.5, annex F (figure F.13)
mismatching	4.3.17	distances through insulation	2.9.4.3
<i>see also</i> mains plugs		metal core	2.9.5
pollution (degree)	2.2.2, 2.9.1, 2.9.3	multi-layer	2.9.4.3
pollution degree 1 applies	2.9.6, 2.9.7	quality control	R.1
polyimide insulating material	2.9.4.3 (note 2), 2.9.4.4, 4.4.5.2	printed wiring <i>see also</i> printed boards	
powder	4.3.4	colours of flexible	2.5.5
containers	4.4.3.3	protection	
power		against electric shock and energy hazards	2.1, clause 6
connections to equipment	3.2	against overcurrent and earth faults	2.7
distribution (definitions)	1.2.12	backup protection	2.7.2
<i>see also</i> IT, TT, and TN POWER SYSTEMS		provided by building installations	1.7.11, 2.7.1, 2.7.3, 2.7.4
factor	A.3.3	in SERVICE ACCESS AREAS	2.1.4.1
interfaces	1.6	in RESTRICTED ACCESS LOCATIONS	2.1.4.2
no power required, excluded from Scope	1.1.3	of network SERVICE PERSONNEL	6.3
outlets on equipment <i>see</i> socket-outlets on equipment		of (telecommunication) equipment USERS	6.3, 6.4
supplied to telecommunication wiring	6.5	of telecommunication wiring	6.5
rating, marking	1.7.1, 1.7.4	protective coverings in place during tests	5.4.7
sources for equipment		protective devices	1.7.11, 2.7.4
any, included in Scope	1.1.1	protective earth and TELECOMMUNICATION NETWORKS	6.3.2
multiple	2.6.12	protective earthing	2.5, 6.2.1.2
marking	1.7.9	colour of insulation	2.5.5, 3.1.6
power (supply) cords	2.5.9, 3.2.1, 3.2.4	conductors	2.5.3, 3.2.5
DETACHABLE POWER SUPPLY CORDS	1.2.5.4*	voltage drop not measured	1.4.13, 2.5.11
marking of wiring terminals	1.7.7	continuity to be assured	2.5, 3.1.11, 6.2.1.2, 6.3.3.2
NON-DETACHABLE POWER SUPPLY CORDS	1.2.5.5*,	<i>see also</i> PLUGGABLE EQUIPMENT TYPE B	
2.9.1, 3.2.2, 3.2.5, 3.2.6, 3.2.7, 5.1 (table 16 part 1)		materials for conductors	2.5.10

reliance on	1.2.4.1, 1.2.4.2	in	
PTFE, Polytetrafluoro ethylene	4.4.3.4, 4.4.5.2, 4.4.6	CLASS I EQUIPMENT	1.2.4.1, 2.5.1
PVC, Polyvinyl chloride	3.2.4, 4.4.3.4, 4.4.3.5, 4.4.5.2, 4.4.6, 5.1, annex P (IEC 227)	CLASS II EQUIPMENT	1.2.4.2, 2.5.2
<b>Q</b>		HAZARDOUS VOLTAGE circuits	2.1.3.2
quality control	2.9.2 (table 3 condition 3, table 5 condition 2), 2.9.5, 2.9.8	internal wiring	2.1.3.2
quality control programmes	annex R	printed boards	2.9.4.3
<b>R</b>		SELV CIRCUITS	2.3.3, 2.3.3.1, 2.3.5
radiation hazards	Introduction, 4.3.12, annex H	TNV CIRCUITS	6.2.1.4, 6.2.1.5
radiation, laser	4.3.12, annex P, annex Q	wound components	2.9.4.4
range		on coated printed boards	2.9.5, annex F (figure F.13)
of conductor sizes	3.2.8, 3.3.5	bridging <i>see</i> bridging of insulation	
current	1.7.1	dimensions	2.9.2, 2.9.3, 2.9.4, annex F, R.1, R.2
frequency <i>see</i> RATED FREQUENCY RANGE		electric strength	5.3.2
voltage, <i>see</i> RATED VOLTAGE RANGE		integrity	
RATED CURRENT	1.2.1.3*	after tests	4.2.7, 5.4.4, 5.4.6, 5.4.9
input current not to exceed	1.6.1	in service	3.1.8, 4.3.9
marking	1.7.1	WORKING VOLTAGES	2.2.7
POWER SUPPLY CORD ampacity	3.2.4	relative humidity <i>see</i> humidity	
purpose of marking	1.7.1	relays	
range	1.7.1	in FIRE ENCLOSURES	1.5.1, 4.4.5.1
terminal sizes	3.3.6	motor starting	B.5
rated current of overcurrent devices	1.7.6, 2.11	reliability	
RATED FREQUENCY	1.2.1.4*, 1.4.6, 1.7.1, 1.7.4	interlock switches	2.8.6.3
RATED FREQUENCY RANGE	1.2.1.5*, 1.4.6, 1.7.1, 1.7.4	thermal controls	K.2, K.5
RATED OPERATING TIME	1.2.2.2*, 1.7.3, 5.1, 5.4.8	repetitive peak voltage	2.2.7.2, 2.9.2.1
RATED VOLTAGE of equipment	1.2.1.1*	resistance, protective earthing conductors	2.5.11
IT POWER SYSTEMS	1.6.4	resistance to fire <i>see</i> fire risk	
marking	1.7.1	resistors	
maximum value		bridging <i>see</i> bridging of insulation	
600 V in Scope of standard	1.1.1	faults in	1.4.12
250 V for HAND-HELD EQUIPMENT	1.6.2	RESTRICTED ACCESS LOCATIONS	1.2.7.3*, 2.1.4.2, 6.2.2.1
tolerance	1.6.5	compared with OPERATOR ACCESS AREAS	1.2.7.3, 2.1.4.2
used for tests	1.4.5, 5.2.2, B.2, G.2, annex K	installation instructions	1.7.19
when measuring input current	1.6.1	temperature rise, exception for heat sinks	5.1
RATED VOLTAGE RANGE of equipment	1.2.1.2*	r.f.i. <i>see</i> electrical filters	
marking	1.7.1	ringing signals <i>see</i> telephone ringing signals	
used for tests	1.4.5, 5.2.2, B.2, G.2, annex K	ripple in D.C. VOLTAGE, definition	1.2.14.3
when measuring input current	1.6.1	in WORKING VOLTAGES	2.2.7.2, 2.2.7.3, 2.2.7.4
rated voltage of components		for CLEARANCE	2.9.2.2 (table 5 condition 4)
fuses	1.7.6	for electric strength tests	5.3.2
capacitors	1.6.4, 2.2.8.1	in limited power sources	2.11 (tables 8 and 9, condition 1)
motors	B.6	r.m.s. values implied unless otherwise specified	1.2
surge suppressors	6.3.3.1	ROUTINE TESTS	1.2.14.2*
redundant power supplies <i>see</i> backup sources of power		coated printed boards	2.9.4.3, 2.9.5, annex R (tables R.1 and R.2)
reed switches, reliability tests	2.8.6.3	reduced CLEARANCES	2.9.2.1 (table 3 condition 3), 2.9.2.2 (table 5 condition 2)
REINFORCED INSULATION	Introduction, 1.2.4.1, 1.2.4.2, 1.2.9.5*	wound components without interleaved insulation	2.9.4.4, U.3
application	2.1.8, 2.2.6	routing of wiring	2.1.3.1, 2.1.3.2, 2.3.3.1
		rubber	annex P (IEC 245)
		natural, not to be used as insulation	2.2.2
		rollers	4.4.3.3
		synthetic, as insulation	3.2.4, 5.1 (table 16),

running overload tests			connected to TELECOMMUNICATION NETWORKS	
a.c. motors		B.4		2.3.1, 2.3.2 (note), 6.1, <b>6.3.1</b>
d.c. motors		B.6	connections to other circuits	2.3.5
			connections to other equipment	2.10.1
<b>S</b>			connectors	2.3.4
SAFETY INTERLOCKS		2.8	different from the term SELV in IEC 364	1.2.8.5 (note 2)
fail-safe operation		2.8.4	earthed	2.5.11
mechanical actuators		2.8.6, 2.8.7	faults	1.2.8.5*, 2.3.1, 2.3.3
not damaged during tests		4.2.7	insulation	2.2.6
protection		2.8.1, 2.8.2, 2.8.3	maximum voltages	
overriding interlocks			normal conditions	2.3.2
by SERVICE PERSONNEL		2.8.5	fault conditions	2.3.3, 6.2.1.2
TOOLS required		2.8.5	methods of protecting	<b>2.3.3</b>
mechanical shock affecting		2.8.3	separation from TNV CIRCUITS	6.2.1.2
switches		2.8, 2.9.1	TELECOMMUNICATION NETWORKS, excluded from	1.2.14.7, 2.3.2 (note)
			WORKING VOLTAGES	2.2.7.2
samples for test			semiconductor devices <i>see also</i> components	
components		1.5.2	as surge arrestors	(S.3)
equipment		1.2.14.1, 1.4.3	faults	1.4.12, 5.4.6
scope of standard		1.1	in FIRE ENCLOSURES	4.4.5.1
screens			separation distances under coatings	
conductive			around terminals	2.9.8, annex F (figure F.12)
earthed		Introduction, 1.4.12, 2.2.6, 2.9.2.2, C.2	printed boards	2.9.5, R.1
for SELV CIRCUITS		2.3.3.2, 2.3.5	SERVICE ACCESS AREAS	1.2.7.2*
for TNV CIRCUITS		6.2.1.4	<i>see also</i> SERVICE PERSONNEL	
unearthed		2.2.6 (table 0.1 condition 6), C.2	service manuals	1.7.4
mechanical		4.2.1, 4.3.22, 4.4.3, 4.4.6	SERVICE PERSONNEL	1.2.14.4*
secured with adhesive		4.3.22	connectors accessible to	4.3.17
screw connections		3.1.8, 3.3.3, 4.3.13	of TELECOMMUNICATION NETWORKS	6.3
screws		annex P (ISO 261, ISO 262)	overriding interlocks	2.8.5
in insulating material			protection	
thread cutting		3.1.9	by earthing	2.5.1
sealed, sealing			from unexpected hazards	2.1.4.1, 2.1.4.2, 2.6.4
components		2.9.1, 2.9.6, 4.4.3.3	mechanical hazards	4.1.2
compounds		2.1.2, 4.3.5, 5.1	stability	4.1.1
layers of tape		U.1	warning notices	1.7.9, 2.7.6
liquid reservoirs		4.4.8	servicing controls	annex H
kits (against moisture)		annex T	servicing instructions <i>see also</i> SERVICE PERSONNEL	
SECONDARY CIRCUITS		Introduction, 1.2.8.2*, 1.2.8.4, 1.2.8.5, 2.2.6	disconnection	2.6.12
CLEARANCES in		2.9.2.2 (table 5)	fuse ratings	1.7.1
electromagnetic components in		5.4.5	languages	1.7.14
floating		2.9.1, 2.9.2.2	lithium batteries	1.7.17
in SERVICE ACCESS AREAS		2.1.4.2	mains voltage adjustment	1.7.4
transients in		2.2.7.2, 2.9.1, 2.9.2.2	maintenance	1.7.2
TNV CIRCUITS		1.2.8.8	sheaths (of power supply cords)	3.1.5, 3.2.4, 3.2.6
where FIRE ENCLOSURE is not required		4.4.5.2	shields, <i>see</i> screens, electromagnetic	
WORKING VOLTAGE		5.3.2 (table 18 condition 3)	shock, electric <i>see</i> electric shock	
between PRIMARY CIRCUITS and			shock, mechanical <i>see</i> mechanical shock	
SECONDARY CIRCUITS		2.2.7.1	short-circuits	2.7
secondary winding overload tests		C.1	of	
securing <i>see</i> fixing			limited power sources	2.11
SELV CIRCUITS		Introduction, 1.2.8.5*, 2.3, annex V	batteries	4.3.21
accessibility		<b>2.1.1</b>	insulation	2.2.7.1, 5.4.4, 6.2.1.2
as interconnection circuits		2.10.2	motor capacitors	B.8
barriers in		2.3.3.1		
boundaries of		2.3.5		

parts with HAZARDOUS ENERGY LEVELS	Introduction, 2.1.4.1, 2.1.4.2, 2.1.5	sub-assembly testing	1.4.3, 2.2.2, 5.4.6
temperature limiters in unattended equipment	5.4.8	SUPPLEMENTARY INSULATION	Introduction, 1.2.9.3*, 1.2.9.4, 1.2.9.5
transformers	C.1	application	2.1.8, 2.1.9, 2.2.6
protection against	1.7.11, 2.7, 3.1.1, 5.4.1	as sleeving	3.1.5, 4.3.7
SHORT-TIME OPERATION	1.2.2.4*, 5.1, 5.4.8	in	
simulated		cord anchorages	3.2.5
conditions for test	1.4.9, 5.1, 5.4.7, 6.2.1.2, 6.2.1.5, B.2, annex C, annex L, annex T	internal wiring	2.1.3.1
external voltages	6.2.1.3	printed boards	2.9.4.3
interference	annex N	SELV CIRCUITS	2.3.3
sleeving as additional insulation	3.1.5, 4.3.7, 4.9.4.4	wound components	2.9.4.4
around insulating beads	3.1.7	on	
small parts, flammability	4.4.3.3	coated printed boards	2.9.5, annex F (figure F.13)
socket-outlets	annex P (IEC83, IEC 309)	power supply cords	3.1.5
in building installations		capacitor casings	2.1.9
for DIRECT PLUG-IN EQUIPMENT	1.2.3.6, 4.3.18	bridging <i>see</i> bridging of insulation	
for PLUGGABLE EQUIPMENT	1.2.5.1, 1.2.5.2, 1.7.2	consequences of failure	2.3.3, 2.4.1
protective earthing connection required	6.3.3.2	dimensions	2.9.2, 2.9.3, 2.9.4, annex F, R.1, R.2
reversible	2.6.6, 4.3.20	electric strength	5.3.2
on equipment	1.7.5	integrity	
accessibility	2.1.2	after a test	4.2.7, 5.4.4, 5.4.6, 5.4.9
loads to be taken into account	1.4.9, 5.4.6	in service	3.1.8, 3.3.9, 4.3.9
sockets, multiway	2.3.4	interchanged with BASIC INSULATION	2.2.6
mismatching	4.3.17	one element of DOUBLE INSULATION	2.2.7.1, 5.4.9
softening of insulating materials	5.1 (table 16 condition 7)	WORKING VOLTAGES	2.2.7
solenoids	5.4.5	surge arrestors (suppressors)	5.3, 6.1 (note 1), 6.3.3.1, 6.4.1, 6.4.2.2, 6.4.2.3, annex S
in FIRE ENCLOSURE	4.4.5.1	switch mode power supplies	2.2.7 (note)
solid insulation	2.2.1, 2.5.1, 2.9.1, 2.9.4	<i>see also</i> repetitive peak voltage	
electric strength	5.3.2 (table 18 condition 2)	switches <i>see also</i> IEC 1058-1	
<i>see also</i> distances through insulation		arcing	4.4.4
stability		as disconnect devices <i>see</i> disconnection for servicing	
of operation, thermal controls	K.6	forbidden in protective earthing conductors	2.5.3
physical	4.1	functional	2.6.2
stand-by condition, marking	1.7.8.3	in FIRE ENCLOSURES	4.4.5
STATIONARY EQUIPMENT	1.2.3.3*, 1.2.3.4, 4.4.4, 5.1 (table 16 part 1)	in PRIMARY CIRCUITS	5.4.6
ENCLOSURES	4.4.4, A.1, A.2, A.5	isolating	2.6.2, 2.6.5, 2.6.8
leakage current	5.2.2, 5.2.5, G.2, G.5	marking	1.7.8, 4.3.5
temperature of earthing terminals	5.1 (table 16 part 1)	microgap	2.9.1 (note 3)
steady force tests, 10 or 30 N, when measuring CLEARANCE	2.9.1	reed	2.8.6.3
steady force tests, 30 N	4.2.2, 4.2.7	safety interlock	2.8, 2.9.1 (note 3)
steady force tests, 250 N	4.2.3, 4.2.7	terminals of	3.3.3
steel ball impact tests	4.2.4, 4.2.7	thermal control	annex K
strain relief		symbols, marking	1.7.1, 1.7.7, 1.7.8.3, 5.1 (table 16 condition 6)
on fluid containers	4.4.8	<b>T</b>	
on power cords	3.2.5	TELECOMMUNICATION NETWORKS	1.2.14.7*
stranded conductors		connected to SELV CIRCUITS or TNV CIRCUITS	1.2.14.7 (note 1), 2.3.1, 2.3.2 (note), 6.1, 6.3.1
power supply cord	1.2.5.5, 3.3.4, 3.3.9	connections to	1.2.11.7, 2.3.1, 6.1, 6.3.1
soldered	3.3.4, 3.1.10	equipment powered from, included in Scope of standard	1.1.1
stress, mechanical, on insulation	2.9.4.1	leakage current, to and from	6.3.4
stress relief test on plastic materials	4.2.6, 4.2.7	operating voltages generated in	6.2.1.3
		<i>see also</i> telephone ringing signals	
		protection by earthing	6.3.2
		power limit 15 VA	4.4.5.2
		separation from	
		earth	6.3.3

hazardous voltages	6.3.1	thermal ageing	2.9.4.3, 2.9.4.4, 2.9.5
parts of equipment	6.4	thermal cycling	2.9.4.3, 2.9.4.4, 2.9.5, 2.9.6, 2.9.7
surge protection	6.1 (note 1), 6.4.1	transformers <i>see</i> transformer testing	
telecommunication wiring, protection	6.5	TYPE	1.2.14.1*, 1.4.2, 1.5.2, U.2
telegraph signals	6.2.1.1 (note 3)	TFE, tetrafluoro ethylene	4.4.3.4, 4.4.5.2, 4.4.6
telephone ringing signals		thermal ageing	2.9.4.3, 2.9.5
considered as operating voltages	2.3.1	thermal cycling	2.9.4.3, 2.9.5, 2.9.6, 2.9.7
disregarded for CREEPAGE DISTANCES	2.2.7.4	thermal controls	2.11, annex K, annex P (IEC 730-1)
frequency	M.2 (note), M.3.1.1	THERMAL CUTOUTS	1.2.11.4*, annex K
maximum levels	6.2.1.1 b)	contacts	2.9.1
power supplies for	2.1.4.2	integrity after tests	4.2.7
television distribution systems	1.2.14.7	not to operate during heating tests	5.1
temperature, temperature rise		thermoplastic parts	5.4.10
ambient during tests	1.4.7, 4.3.22, B.5, annex E, U.2	THERMOSTATS	1.2.11.2*, 5.4.8, annex K
applied to parts under test	2.2.2, 2.2.3, 2.9.5, 2.9.6, 2.9.7, 4.2.6, 5.3.1, 5.4.8, 5.4.10	contacts	2.9.1
conditioning	A.1.2, A.2.2, A.6.2, A.7.3, A.8.2, A.9.2	thickness (of insulation), <i>see</i> distance through insulation	
heat sinks	5.1	thin sheet insulating material	2.9.4.2, 2.9.4.3, 5.3.1, C.2
maximum <i>see</i> maximum temperature (rise)		three-phase	
measurement	1.4.7, 1.4.8, 5.1	disconnect devices	2.6.7
TEMPERATURE LIMITERS	1.2.11.3, annex K	equipment	
temperature sensing devices	4.3.20	leakage current	5.2.4, 5.2.5, 6.3.4, G.4, G.5
terminals <i>see</i> wiring terminals		protection	2.7.4
test <i>see also</i> tests		motors	B.9
fingers	2.1.2, 2.1.4.2, 6.2.2.1, 6.4.1 b), figure 19 (page 239), annex F (figure F.14 point A)	rotation, marking if critical	1.7.7.2
pins	2.1.2, figure 20 (page 241)	TIME, RATED OPERATING	1.2.2.2*, 1.7.3, 5.1, 5.4.8
probes	6.2.2.1, 6.4.1 b), figure 16 (page 229)	TN POWER SYSTEMS	1.2.12.1*
tests		leakage current	5.2.1
abnormal conditions	5.4	protective devices	2.7.4
abrasion resistance	2.9.5	TNV CIRCUITS	1.2.8.3, 1.2.8.8*, 6.2, annex V
adhesive ageing	4.3.22	accessibility	2.1.4.1, 2.1.4.2 (note), 6.2.2.1
ball-pressure	5.4.10, figure 21 (page 241)	in battery compartments	6.2.2.2
current supplied to telecommunication wiring	6.5	via other circuits	6.4.1
drop	4.2.5, 4.2.7	as interconnection circuits	2.10.2
flammability	A.1, A.2, A.6, A.7, A.8, A.9	boundaries of	6.2.1.5
electric strength <i>see</i> electric strength tests		connected to SELV CIRCUITS	6.2.1.2
endurance		connected to TELECOMMUNICATION NETWORKS	6.1, 6.3.1
interlock switches	2.8.6.2	connections to other circuits	6.2.1.5
thermal controls	K.3, K.4	connections to other equipment	2.10.1
high current arcing ignition tests	4.4.4, A.3	considered to be SECONDARY CIRCUITS	1.2.8.8
hot flaming oil	4.4.6, A.5	faults	6.2.1.1, 6.2.1.2
hot wire ignition	4.4.4, A.4	insulation	2.2.6, 6.2.1.2
ignition	4.4.4, A.3, A.4, A.5	maximum voltages	6.2.1.1
impact	4.2.4, 4.2.7	not requiring FIRE ENCLOSURES	4.4.5.2
implosion tests (cathode ray tubes)	4.2.8	separation	
impulse	6.4.2.1, 6.4.2.2, 6.4.2.3, R.1, R.2, annex S	from accessible parts	6.2.1.2
floating circuits	2.9.1, 2.9.2.1	from HAZARDOUS VOLTAGES	6.2.1.4
test generators	annex N	from SELV CIRCUITS and other TNV CIRCUITS	6.2.1.2
leakage current	5.2, 6.3.4, annex G	TNV-1 CIRCUITS	1.2.9.9*, 6.2.1.1 a), annex V
motors <i>see</i> motor tests		separation from parts of equipment	6.4.1
ROUTINE <i>see</i> ROUTINE TESTS		treated as TNV-3 CIRCUITS	6.2.1.2
steady force, 10 or 30 N, when measuring CLEARANCE	2.9.1	TNV-2 CIRCUITS	1.2.9.10*, 6.2.1.1 b), annex V
steady force, 30 N	4.2.2, 4.2.7	treated as TNV-3 CIRCUITS	6.2.1.2
steady force, 250 N	4.2.3, 4.2.7	TNV-3 CIRCUITS	1.2.9.11*, 6.2.1.1 b), annex V
steel ball impact	4.2.4, 4.2.7	separation from parts of equipment	6.4.1
stress relief on plastic materials	4.2.6, 4.2.7		

