

INTERNATIONAL STANDARD

IEC 61121

2002

AMENDMENT 1
2005-05

Amendment 1

**Tumble dryers for household use –
Methods for measuring the performance**

IECNORM.COM. Click to view the full PDF of IEC 61121:2002/AMD1:2005

© IEC 2005 Droits de reproduction réservés — Copyright - all rights reserved

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

C

For price, see current catalogue

FOREWORD

This amendment has been prepared by subcommittee 59D: Home laundry appliances, of IEC technical committee 59: Performance of household electrical appliances.

The text of this amendment is based on the following documents:

| FDIS | Report on voting |
|--------------|------------------|
| 59D/286/FDIS | 59D/296/RVD |

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

Page 10

6.2.3 Ambient temperature

Amend, in the second line, the reference to

“...(20 ± 2) °C...”

to read “

... (23 ± 2) °C...”:

6.2.4 Ambient humidity

Amend, in the first line, the reference to

“...(65 ± 5) %...”

to read

“...(55 ± 5) %...”.

Page 12

7.3.3 Conditioning

Replace the existing second and third paragraphs by the following text:

Three methods could be used alternatively:

- 1) the textiles are left at least for 15 h in an ambient temperature of (20 ± 2) °C and an ambient humidity of (65 ± 5) %.

The textile is conditioned when the weight of the load changes by less than 0,5 % for two successive weighings. The weighings are carried out at two-hour intervals;

- 2) the textiles shall be hung singly and separately so that air can freely circulate. The load is left in an ambient temperature of (20 ± 2) °C and an ambient humidity of (65 ± 5) % for a period of not less than 15 h;
- 3) the bone-dry method (see Annex C).

IECNORM.COM. Click to view the full PDF of IEC 61121-2002/AM1:2005