

INTERNATIONAL STANDARD

IEC
61156-6-1

First edition
2002-05

Multicore and symmetrical pair/quad cables for digital communications –

Part 6-1: Symmetrical pair/quad cables with transmission characteristics up to 600 MHz – Work area wiring – Blank detail specification

*Câbles multiconducteurs à paires symétriques et quartes
pour transmissions numériques –*

*Partie 6-1:
Câbles à paires symétriques et quartes avec caractéristiques
de transmission allant jusqu'à 600 MHz –
Raccordement de terminal –
Spécification particulière cadre*



Reference number
IEC 61156-6-1:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/catlg-e.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/JP.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 61156-6-1

First edition
2002-05

Multicore and symmetrical pair/quad cables for digital communications –

Part 6-1: Symmetrical pair/quad cables with transmission characteristics up to 600 MHz – Work area wiring – Blank detail specification

*Câbles multiconducteurs à paires symétriques et quartes
pour transmissions numériques –*

*Partie 6-1:
Câbles à paires symétriques et quartes avec caractéristiques
de transmission allant jusqu'à 600 MHz –
Raccordement de terminal –
Spécification particulière cadre*

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

J

For price, see current catalogue

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –**

**Part 6-1: Symmetrical pair/quad cables with transmission
characteristics up to 600 MHz –Work area wiring –
Blank detail specification**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-6-1 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors and accessories for communication and signalling.

The text of this standard is based on the following documents:

FDIS	Report on voting
46C/514/FDIS	46C/522/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2006. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 6-1: Symmetrical pair/quad cables with transmission characteristics up to 600 MHz – Work area wiring – Blank detail specification

1 Scope

This blank detail specification describes symmetrical pair/quad cables intended to construct patch, equipment, and work area cords in digital communication systems such as ISDN, local area networks and data communication systems using frequencies up to 600 MHz.

This specification should be used in conjunction with IEC 61156-1 and IEC 61156-6. The blank detail specification determines the layout and style for detail specifications describing symmetrical pair/quad cables with transmission characteristics up to 600 MHz for digital communications. Detail specifications, based on the blank detail specification, may be prepared by a national organization, a manufacturer, or a user.

The designation "Category 5e" is used herein to describe an enhanced Category 5 cable (see 1.1 of IEC 61156-6).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-6, *Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 600 MHz – Work area wiring – Sectional specification*

ISO/IEC 11801:2000, *Information technology – Generic cabling for customer premises*

3 Guidance for preparation of detail specifications

It is necessary to keep the transmission characteristics indicated in the relevant sectional specification for the referenced category number, i.e. 5e, 6 or 7 and the characteristic impedance.

The detail specification shall be written in accordance with the layout of the blank detail specification, which forms part of this standard.

NOTE 1 When a characteristic does not apply, then NA (for not applicable) should be entered in the appropriate space.

NOTE 2 When a characteristic applies but a specific value is not considered necessary, then NS (for not specified) should be entered in the appropriate space. When NS is used, the appropriate requirement in the sectional specification should apply.

The numbers shown in brackets in this and the following pages correspond to the following items of required information, which should be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable, national reference, trade name, etc.
- [6] A complete description of the cable which shall include
 - a) type and number of elements;
 - b) nominal impedance;
 - c) screening;
 - d) application;
 - e) category;
 - f) other distinguishing performance characteristics.

Example: 4-pair, unshielded twisted pair cable for use in work area wiring, having a nominal impedance of 100 Ω , and meeting the transmission requirements of Category 6 and the coupling attenuation requirements of Type III.
- [7] Details of the cable material and construction.
- [8] Special requirements for bending radius or operating temperatures.
- [9] List of cable characteristics. They are separated into electrical, transmission, mechanical and environmental characteristics.
- [10] Appropriate subclause references in the generic specification IEC 61156-1.
- [11] Appropriate subclause references in the sectional specification IEC 61156-6.
- [12] Requirements applicable to this cable. The values entered shall meet as a minimum the requirements of sectional specification IEC 61156-6.
- [13] Comments – Relevant remarks.

4 Blank detail specification for symmetrical pair/quad cables with transmission characteristics up to 600 MHz for digital communications in work area wiring

[1] Prepared by:		[2] Document: Issue: Date:	
[3] Available from:		[4] Generic specification: IEC 61156-1 Sectional specification: IEC 61156-6 Blank detail specification: IEC 61156-6-1	
[5] Additional references: ISO/IEC 11801			
[6] Cable description: a) Type and number of elements: b) Nominal impedance: c) Screening: d) Application: e) Category: f) Other distinguishing performance characteristics:			
[7] Cable construction:	61156-1 subclause	61156-6 subclause	
	2.2.3	2.2.3	Conductor description:
	2.2.4	2.2.4	Insulation description: Maximum diameter:
	2.2.5	2.2.5	Colour code of elements:
	2.2.6	2.2.6	Number of elements (pair(s)/quad(s)):
	2.2.7	2.2.7	Screening of the cable element: Tape material Drain wire Braid wire Braid material
	2.2.8	2.2.8	Cross web, spacer or protective wrapping(s):
	2.2.9	2.2.9	Screen of the cable core: Tape material Minimum overlap Drain wire Braid wire Braid material
	- 1)	2.2.10	Ripcord:
	2.2.10	2.2.10	Sheath Material Nominal thickness
	2.2.11	2.2.11	Colour Maximum overall Diameter
	2.2.12	2.2.12	Marking
	2.2.13	2.2.13	Packaging:
1) Not specified in IEC 61156-1.			

[8]				
Minimum bending radius for static bending:		mm		
Minimum bending radius for dynamic bending:		mm		
Temperature range for installation		°C		
Operating temperature range:		°C		
[9] Characteristics	[10] 61156-1 subclause	[11] 61156-6 subclause	[12] Requirements	[13] Comments
Electrical Characteristics	3.2	3.2		
Conductor resistance	3.2.1	3.2.1	≤ ... Ω/km	
Resistance unbalance	3.2.2	3.2.2	≤ ... %	
Dielectric strength				
Conductor/conductor	3.2.3	3.2.3 kV	
Conductor/screen	3.2.3	3.2.3 kV	
Insulation resistance				
Conductor/conductor	3.2.4	3.2.4	≥ ... MΩ/km	
Conductor/screen	3.2.4	3.2.4	≥ ... MΩ/km	
Mutual capacitance	3.2.5	3.2.5	≤ ... nF/km	
Capacitance unbalance pair to ground	3.2.6	3.2.6	≤ ... pF/km	
Transfer impedance	3.2.7	3.2.7		
1 MHz			≤ ... MΩ/m	
10 MHz			≤ ... MΩ/m	
30 MHz			≤ ... MΩ/m	
100 MHz			≤ ... MΩ/m	
Resistance of the screen	- 1)	3.2.8	≤ ... Ω/km	
1) Not specified in IEC 61156-1.				

Transmission characteristics	3.3	3.3		
Velocity of propagation	3.3.1	3.3.1.1	$\geq \dots$ km/s	
Delay	- ¹⁾	3.3.1.2	$\leq \dots$ ns/100 m	
Differential phase delay (skew)	- ¹⁾	3.3.1.3	$\leq \dots$ ns/100 m	
Environmental effects	- ¹⁾	3.3.1.4	$\leq \dots$ ns/100 m	
Attenuation	3.3.2	3.3.2	$\leq \dots$ dB/100 m	
Temperature effects	- ¹⁾	3.3.2.1	$\leq \dots$ %/°C	
Environmental effects	- ¹⁾	3.3.3.2	$\geq \dots$ %	
Unbalance attenuation near-end (TCL)	3.3.3	3.3.3	$\geq \dots$ dB	
Unbalance attenuation far-end (EL TCTL)	3.3.3	3.3.3	$\geq \dots$ dB	
Near-end crosstalk (power sum)	3.3.4	3.3.4	$\geq \dots$ dB	
Near-end crosstalk (pair-to-pair)	3.3.4	3.3.4	$\geq \dots$ dB	
Far-end crosstalk (power sum)	3.3.5	3.3.5	$\geq \dots$ dB	
Far-end crosstalk (pair-to-pair)	3.3.5	3.3.5	$\geq \dots$ dB	
Open-/short-circuit impedance (input impedance)	3.3.6.2.2	3.3.6.1	$\dots \Omega$	
Function fitted impedance	3.3.6.3	3.3.6.2	$\dots \Omega$	
Mean characteristic impedance	3.3.6.2.3	3.3.6.2	$\dots \Omega$	
Return loss	3.3.7.1	3.3.7	$\geq \dots$ dB	
Screening attenuation	- ¹⁾	3.3.9	$\geq \dots$ dB	
Coupling attenuation	- ¹⁾	3.3.10	$\geq \dots$ dB	

¹⁾ Not specified in IEC 61156-1.

Mechanical and dimensional characteristics	3.4	3.4		
Insulation diameter	3.4.1	3.4.1	... mm	
Sheath thickness	–	3.4.1	... mm	
Cable diameter	–	3.4.1	... mm	
Elongation at break of the conductor	3.4.2	3.4.2	≥ ... %	
Elongation at break of the insulation	– ¹⁾	3.4.3	≥ ... %	
Elongation at break of the sheath	3.4.4	3.4.4	≥ ... %	
Tensile strength of the sheath	3.4.5	3.4.5	≥ ... MPa	
Crush test of the cable	3.4.6	3.4.6		
Impact test of the cable	3.4.7	3.4.7		
Bending under tension	– ²⁾	3.4.8		
Tensile performance of the cable	3.4.9	3.4.9		
¹⁾ Not specified in IEC 61156-1. ²⁾ Not specified in IEC 61156-1. Instead, a requirement for tensile strength of insulation is specified.				

IECNORM.COM: Click to view the full PDF of IEC 61156-6-1:2002

Environmental characteristics	3.5	3.5		
Shrinkage of the insulation	3.5.1	3.5.1	≤ ... %	
Wrapping test of insulation after thermal ageing	3.5.2	3.5.2	NA	
Bending test of insulation at low temperature	3.5.3	3.5.3		
Elongation at break of the sheath after ageing	3.5.4	3.5.4	≥ ... %	
Tensile strength of the sheath after ageing	3.5.5	3.5.5	≥ ... MPa	Initial value
Sheath pressure test at high temperature	3.5.6	3.5.6	NA	Initial value
Cold bend test of cable	3.5.7	3.5.7		
Heat shock test	3.5.8	3.5.8	NA	
Flame propagation of a single cable	3.5.9	3.5.9		
Flame propagation characteristics of bunched cables	3.5.10	3.5.10		
Acid gas evolution	3.5.11	3.5.11		
Smoke generation	3.5.12	3.5.12		
Toxic gas emission	3.5.13	3.5.13		
Integrated fire test	3.5.14	3.5.14		UC
UC: under consideration.				

IECNORM.COM: Click to view the full PDF of IEC 61756-6-1:2002

Withdrawn