



IEC 61162-1

Edition 4.0 2010-11

INTERNATIONAL STANDARD



**Maritime navigation and radiocommunication equipment and systems – Digital
interfaces –
Part 1: Single talker and multiple listeners**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XG**

ICS 47.020.70

ISBN 978-2-88912-256-1

CONTENTS

FOREWORD	7
INTRODUCTION	9
1 Scope	10
2 Normative references	10
3 Terms and definitions	11
4 Manufacturer's documentation	11
5 Hardware specification	11
5.1 General	11
5.2 Interconnecting wire	11
5.3 Conductor definitions	11
5.4 Electrical connections/shield requirements	12
5.5 Connector	12
5.6 Electrical signal characteristics	12
5.6.1 General	12
5.6.2 Signal state definitions	12
5.6.3 Talker drive circuits	12
5.6.4 Listener receive circuits	12
5.6.5 Electrical isolation	13
5.6.6 Maximum voltage on bus	13
6 Data transmission	13
7 Data format protocol	14
7.1 Characters	14
7.1.1 General	14
7.1.2 Reserved characters	14
7.1.3 Valid characters	14
7.1.4 Undefined characters	14
7.1.5 Character symbols	14
7.2 Fields	14
7.2.1 String	14
7.2.2 Address field	15
7.2.3 Data fields	15
7.2.4 Checksum field	16
7.2.5 Sequential message identifier field	17
7.3 Sentences	17
7.3.1 General structure	17
7.3.2 Description of approved sentences	17
7.3.3 Parametric sentences	18
7.3.4 Encapsulation sentences	19
7.3.5 Query sentences	21
7.3.6 Proprietary sentences	21
7.3.7 Command sentences	22
7.3.8 Valid sentences	23
7.3.9 Multi-sentence messages	23
7.3.10 Sentence transmission timing	23
7.3.11 Additions to approved sentences	23

7.4	Error detection and handling.....	24
7.5	Handling of deprecated sentences	24
8	Data content	24
8.1	Character definitions.....	24
8.2	Field definitions.....	27
8.3	Approved sentences	29
8.3.1	General format	29
8.3.2	AAM – Waypoint arrival alarm	29
8.3.3	ABK – AIS addressed and binary broadcast acknowledgement.....	29
8.3.4	ABM – AIS addressed binary and safety related message.....	31
8.3.5	ACA – AIS channel assignment message	31
8.3.6	ACK – Acknowledge alarm	33
8.3.7	ACS – AIS channel management information source.....	33
8.3.8	AIR – AIS interrogation request	33
8.3.9	AKD – Acknowledge detail alarm condition.....	35
8.3.10	ALA – Report detailed alarm condition	35
8.3.11	ALR – Set alarm state.....	36
8.3.12	APB – Heading/track controller (autopilot) sentence B.....	37
8.3.13	BBM – AIS broadcast binary message.....	37
8.3.14	BEC – Bearing and distance to waypoint – Dead reckoning.....	38
8.3.15	BOD – Bearing origin to destination	39
8.3.16	BWC – Bearing and distance to waypoint – Great circle	39
8.3.17	BWR – Bearing and distance to waypoint – Rhumb line.....	39
8.3.18	BWW – Bearing waypoint to waypoint	40
8.3.19	CBR – Configure broadcast rates for AIS AtoN station message command.....	40
8.3.20	CUR – Water current layer – Multi-layer water current data	41
8.3.21	DBT – Depth below transducer	41
8.3.22	DDC – Display dimming control	42
8.3.23	DOR – Door status detection	42
8.3.24	DPT – Depth	44
8.3.25	DSC – Digital selective calling information.....	44
8.3.26	DSE – Expanded digital selective calling.....	45
8.3.27	DTM – Datum reference.....	45
8.3.28	ETL – Engine telegraph operation status	46
8.3.29	EVE – General event message	47
8.3.30	FIR – Fire detection.....	47
8.3.31	FSI – Frequency set information.....	49
8.3.32	GBS – GNSS satellite fault detection	49
8.3.33	GEN – Generic binary information	51
8.3.34	GFA – GNSS fix accuracy and integrity.....	52
8.3.35	GGA – Global positioning system (GPS) fix data	53
8.3.36	GLL – Geographic position – Latitude/longitude	53
8.3.37	GNS – GNSS fix data	54
8.3.38	GRS – GNSS range residuals	55
8.3.39	GSA – GNSS DOP and active satellites	57
8.3.40	GST – GNSS pseudorange noise statistics	59
8.3.41	GSV – GNSS satellites in view	60

8.3.42	HBT – Heartbeat supervision sentence.....	61
8.3.43	HDG – Heading, deviation and variation.....	62
8.3.44	HDT – Heading true.....	62
8.3.45	HMR – Heading monitor receive.....	63
8.3.46	HMS – Heading monitor set.....	63
8.3.47	HSC – Heading steering command.....	64
8.3.48	HSS – Hull stress surveillance systems.....	64
8.3.49	HTC – Heading/track control command; HTD – Heading /track control data.....	64
8.3.50	LR1 – AIS long-range reply sentence 1.....	66
8.3.51	LR2 – AIS long-range reply sentence 2.....	66
8.3.52	LR3 – AIS long-range reply sentence 3.....	67
8.3.53	LRF – AIS long-range function.....	67
8.3.54	LRI – AIS long-range interrogation.....	68
8.3.55	MEB – Message input for broadcast command.....	69
8.3.56	MSK – MSK receiver interface.....	71
8.3.57	MSS – MSK receiver signal status.....	71
8.3.58	MTW – Water temperature.....	71
8.3.59	MWD – Wind direction and speed.....	71
8.3.60	MWV – Wind speed and angle.....	72
8.3.61	NAK – Negative acknowledgement.....	72
8.3.62	NRM – NAVTEX receiver mask.....	73
8.3.63	NRX – NAVTEX received message.....	74
8.3.64	OSD – Own ship data.....	75
8.3.65	POS – Device position and ship dimensions report or configuration command.....	76
8.3.66	PRC – Propulsion remote control status.....	77
8.3.67	RMA – Recommended minimum specific LORAN-C data.....	78
8.3.68	RMB – Recommended minimum navigation information.....	79
8.3.69	RMC – Recommended minimum specific GNSS data.....	79
8.3.70	ROR – Rudder order status.....	81
8.3.71	ROT – Rate of turn.....	81
8.3.72	RPM – Revolutions.....	81
8.3.73	RSA – Rudder sensor angle.....	81
8.3.74	RSD – Radar system data.....	82
8.3.75	RTE – Routes.....	82
8.3.76	SFI – Scanning frequency information.....	83
8.3.77	SSD – AIS ship static data.....	83
8.3.78	STN – Multiple data ID.....	85
8.3.79	THS – True heading and status.....	85
8.3.80	TLB – Target label.....	85
8.3.81	TLL – Target latitude and longitude.....	86
8.3.82	TRC – Thruster control data.....	86
8.3.83	TRD – Thruster response data.....	87
8.3.84	TTD – Tracked target data.....	87
8.3.85	TTM – Tracked target message.....	90
8.3.86	TUT – Transmission of multi-language text.....	90
8.3.87	TXT – Text transmission.....	92
8.3.88	UID – User identification code transmission.....	92

8.3.89	VBW – Dual ground/water speed.....	93
8.3.90	VDM – AIS VHF data-link message.....	93
8.3.91	VDO – AIS VHF data-link own-vessel report.....	94
8.3.92	VDR – Set and drift.....	94
8.3.93	VER – Version.....	95
8.3.94	VHW – Water speed and heading.....	96
8.3.95	VLW – Dual ground/water distance.....	96
8.3.96	VPW – Speed measured parallel to wind.....	96
8.3.97	VSD – AIS voyage static data.....	96
8.3.98	VTG – Course over ground and ground speed.....	98
8.3.99	WAT – Water level detection.....	98
8.3.100	WCV – Waypoint closure velocity.....	99
8.3.101	WNC – Distance waypoint to waypoint.....	99
8.3.102	WPL – Waypoint location.....	99
8.3.103	XDR – Transducer measurements.....	100
8.3.104	XTE – Cross-track error, measured.....	101
8.3.105	XTR – Cross-track error, dead reckoning.....	101
8.3.106	ZDA – Time and date.....	101
8.3.107	ZDL – Time and distance to variable point.....	102
8.3.108	ZFO – UTC and time from origin waypoint.....	102
8.3.109	ZTG – UTC and time to destination waypoint.....	102
9	Applications.....	102
9.1	Example parametric sentences.....	102
9.1.1	General.....	102
9.1.2	Example 1 – LORAN-C latitude/longitude.....	102
9.1.3	Example 2 – LORAN-C arrival alarm.....	103
9.1.4	Example 3 – Proprietary sentence.....	103
9.1.5	Example 4 – RMA examples.....	104
9.1.6	Example 5 – FSI examples.....	104
9.1.7	Example 6 – MSK/MSS examples.....	105
9.1.8	Example 7 – DSC and DSE sentences.....	105
9.1.9	Example 8 – FIR, DOR and WAT sentences.....	106
9.2	Example encapsulation sentences.....	106
9.3	Examples of receiver diagrams.....	106
Annex A	(informative) Glossary.....	108
Annex B	(normative) Guidelines for methods of testing and required test results.....	116
Annex C	(normative) Six-bit binary field conversion.....	122
Annex D	(normative) Alarm system fields.....	125
Annex E	(informative) Example of use of FIR, DOR and WAT sentences.....	135
Annex F	(informative) Example encapsulation sentence.....	139
Bibliography	145

Figure 1 – Listener receive circuit	13
Figure 2 – Data transmission format.....	14
Figure 3 – Example 1, J-FET, N channel, opto-isolator based listener circuit.....	106
Figure 4 – Example 2, NPN opto-isolator based listener circuit.....	107
Figure C.1 – 6-bit binary code converted to valid IEC 61162-1 character	123
Figure C.2 – Valid IEC 61162-1 character converted to 6-bit binary code	124
Figure E.1 – Example system diagram	136
Figure F.1 – Message data format.....	140
Figure F.2 – Work sheet for decoding and interpreting encapsulated string	144
Table 1 – Reserved characters	24
Table 2 – Valid characters	25
Table 3 – Character symbol	26
Table 4 – Talker identifier mnemonics.....	27
Table 5 – Field type summary.....	28
Table B.1 – Example – Data string GGA sent by the EUT to the test receiver (listener)	119
Table B.2 – Checksum	120
Table B.3 – Example – Data string GGA received by the EUT	120
Table B.4 – Example – Checksum.....	121
Table B.5 – Break of data line.....	121
Table C.1 – Six-bit binary field conversion table	122
Table D.1 – System alarm fields	125
Table F.1 – Example message from: ITU-R M.1371.....	143

IECNORM.COM : Click to view the full PDF of IEC 61162-1 ed 4.0 :2010

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
DIGITAL INTERFACES –****Part 1: Single talker and multiple listeners**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61162-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This fourth edition cancels and replaces the third edition published in 2007, and constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- in Table 1 the "comment" block delimiter has been renamed "TAG" block delimiter,
- new identifiers have been added to Table 4,
- the following sentences have been removed from 8.3 as they are not used by other standards prepared by technical committee 80: ALM and MLA which described almanac data from satellite navigation systems, DCN which described DECCA data, DSI and DSR

which controlled the DSC transponder, GLC and LCD which described LORAN data, and GMP which supported land use of map projections,

- new sentences CBR, GFA, HBT, NAK, MEB, POS, TTD and VER have been added,
- corrections have been made to the following sentences: ABK, BBM, DOR, FIR, SSD, TUT, and VTG,
- extra fields have been added to AIR to support further ITU messages,
- new fields have been added to GBS, GRS, GSA and GSV to support new satellite navigation systems,
- a new navigational status indicator has been added to GNS and RMC,
- a new sentence status flag had been added to DDC, FSI, HSC and NRM,
- three additional tests have been added to Annex B.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/606/FDIS	80/609/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61162 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.