

# INTERNATIONAL STANDARD

Coaxial communication cables –  
Part 1-209: Environmental test methods – Thermal cycling

IECNORM.COM : Click to view the full PDF of IEC 61196-1-209:2016



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2016 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

**IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

**IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

IECNORM.COM : Click to view the full text of IEC 61966-1-209:2016

# INTERNATIONAL STANDARD

---

**Coaxial communication cables –  
Part 1-209: Environmental test methods – Thermal cycling**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.120.10

ISBN 978-2-8322-3250-7

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions .....	5
4 Symbols .....	5
5 Method.....	6
5.1 Thermal cycle profile method.....	6
5.2 Adjustment factors .....	6
5.2.1 General .....	6
5.2.2 Transition rate adjustment factor .....	7
5.2.3 Upper and lower temperature exposure test adjustment factor.....	7
5.3 Sample .....	7
5.4 Requirements.....	7
6 Test report.....	8
Annex A (informative) Reliability acceleration factor .....	9
Table 1 – Mass and exposure times .....	6

IECNORM.COM : Click to view the full PDF of IEC 61196-1-209:2016

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## COAXIAL COMMUNICATION CABLES –

## Part 1-209: Environmental test methods – Thermal cycling

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61196-1-209 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
46A/1298/FDIS	46A/1301/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 61196 series published under the general title *Coaxial communication cables* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 61196-1-209:2016

## COAXIAL COMMUNICATION CABLES –

### Part 1-209: Environmental test methods – Thermal cycling

#### 1 Scope

This part of IEC 61196 specifies a test method to determine the ability of a coaxial cable to withstand the effects of temperature cycling on its transmission performance.

The purpose of this procedure is to accelerate the effects of temperature cycling on a cable.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1, *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 62506, *Methods for product accelerated testing*

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61196-1 apply.

#### 4 Symbols

$\Delta T$	difference between the upper and lower exposure temperature limits, in °C
$\Delta T_1$	difference between the upper and lower operational temperature limits, in °C
$\Delta T_i$	temperature change difference other than $\Delta T_1$ , in °C
$\zeta_{\text{Test}}$	transition rate of temperature of the test, in °C/minute
$A$	adjustment factor for the number of cycles for different transition temperature rates and exposure temperatures limits than standard conditions
$A_{\text{tr}}$	adjustment factor for the number of cycles with regards to the transition rate
$A_{\Delta T}$	adjustment factor for the number of cycles with regards to the upper and lower exposure temperatures

## 5 Method

### 5.1 Thermal cycle profile method

The test shall be done in accordance with the IEC 60068-2-14 with a transition time of 2 °C/minute. The temperature exposure time should be at the upper and lower operational limits of cable ( $\Delta T_1$ ) as given in relevant cable specification, unless otherwise modified as described in 5.2.

A cycle shall consist of one complete exposure at upper and lower temperature test limits.

Twenty cycles should be conducted.

The time exposed at the upper and lower test temperatures shall be sufficient for the DUT to reach the specified temperature.

Mass and exposure times are given in Table 1.

**Table 1 – Mass and exposure times**

Mass of specimen/fixtures	Exposure time hr
≤ 30 g	¼
> 30 g to ≤ 150 g	½
> 150 g to ≤ 1,5 kg	1
> 1,5 kg to ≤ 7,5 kg	1,5
>7,5 kg to ≤ 15 kg	2
> 15 kg to ≤ 75 kg	3
> 75 kg to ≤ 150 kg	4
> 150 kg	8

### 5.2 Adjustment factors

#### 5.2.1 General

The number of cycles should be adjusted when the transition rate and temperature change varies from 5.1 by the following:

$$N = 20 \times A_{tr} \times A_{\Delta T} \quad (1)$$

The calculation will most likely lead to a number that will not be an integer and therefore will contain a fraction of a complete cycle. Any fraction of a cycle should be adjusted to the next higher integer number.

### 5.2.2 Transition rate adjustment factor

The number of cycles should be adjusted to other transition rates according to equation (1) and (2).

$$A_{tr} = \left( \frac{2}{\zeta_{Test}} \right)^{1/3} \quad (2)$$

The maximum adjustment factor should be limited to 4.

### 5.2.3 Upper and lower temperature exposure test adjustment factor

If different temperature exposure limits are used, the number of cycles should be adjusted as specified by the following.

$$A_{\Delta T} = \left( \frac{\Delta T_1}{\Delta T_i} \right)^{2,5} \quad (3)$$

## 5.3 Sample

Electrical and mechanical tests shall be done on a 50 m ± 5 m length unless otherwise specified. Each test shall require a minimum of one sample.

The samples shall be loosely coiled in the test chamber to ensure that adjacent windings have airspace between each coil, adjacent samples, and walls of the chamber.

The mechanical sample shall be cut flush at both ends.

Suitable connectors shall be attached for the electrical tests.

Tests that should be considered are: impedance, return loss, passive intermodulation distortion, contact resistance, etc.

## 5.4 Requirements

The mechanical test shall monitor dielectric and conductor movement. The criteria for acceptance shall be described in the detailed specification.

The RF performance characteristics shall be evaluated at the conclusion of the test and may be also evaluated at intervals during the test. The criteria for acceptance shall be specified in the detailed specification.

## 6 Test report

The test report shall include

- initial measurement;
- number of samples tested;
- sample length;
- connector used;
- test conditions
  - low temperature,
  - high temperature,
  - rate of temperature change,
  - number of cycles,
  - duration of cycle,
  - details of sample placement;
- final measurements and changes in results from the initial measurements;
- calculations made;
- deviations from the standard method.

IECNORM.COM : Click to view the full PDF of IEC 61196-1-209:2016

## Annex A (informative)

### Reliability acceleration factor

The effects of thermal cycling in use may be accelerated by increasing the temperature range and transition time from what is the normal operation. This is known as the acceleration factor  $A_{TC}$ .

$$A_{TC} = \left( \frac{\Delta T_1}{\Delta T_2} \right)^m \cdot \left( \frac{\varsigma_1}{\varsigma_2} \right)^{1/n} \quad (\text{A.1})$$

where

$\Delta T_1$  is the change in temperature that occurs in test 1;

$\Delta T_2$  is the change in temperature that occurs in test 2 or actual change in usage;

$\varsigma_1$  is the ramp speed in test that occurs in test 1;

$\varsigma_2$  is the ramp speed that occurs in test 2 or actual ramp rate in usage;

$m$  is a number for the difference between the exposure test limits and is determined by the component/material;

$n$  is a number for the transition rate of temperature.

In actual use, the thermal cycle profile may not be consistent from day to day and therefore some approximation shall be used.

The  $m$  and  $n$  may be obtained from testing, field experience, data sources, etc.

Additional information can be obtained in IEC 62506.

#### Comments

If the acceleration factor is 25, which means 1 thermal cycle is equivalent to 25, thermal cycles of the base line model shall be used. If the baseline model is 1 day of use, an acceleration factor is equivalent to 25 days of use for each cycle.

Typically daily operational cycles are complex and more than one cycle occurs per day. It is typical practice to model these multiple cycles as one cycle to make the complications easy. However, one can use each mini-cycle and perform individual calculations.

The degree that acceleration can be achieved may be limited based on the temperature ratings of the materials used in the construction of the cable.

The  $m$  and  $n$  exponents can be determined form experimentation, however, when they are not known, a conservative number of 2,5 is used for  $m$  and 1/3 is used for  $n$ .

#### Example 1:

Perform a test on two 50 m cables with one having connectors on both ends and the other having its ends cut flush.

The operational temperature limits are:  $-50$  °C and  $+70$  °C.

The cable mass is of 1 kg per meter.