



# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications –  
Part 2: Lithium systems**

**Accumulateurs alcalins et autres accumulateurs à électrolyte non acide –  
Exigences de sécurité pour les accumulateurs portables étanches, et pour les batteries qui en sont constituées, destinés à l'utilisation dans des applications portables –  
Partie 2: Systèmes au lithium**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 29.220.30

ISBN 978-2-8322-3910-0

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 Parameter measurement tolerances .....	10
5 General safety considerations .....	10
5.1 General.....	10
5.2 Insulation and wiring .....	11
5.3 Venting .....	11
5.4 Temperature, voltage and current management .....	11
5.5 Terminal contacts .....	11
5.6 Assembly of cells into batteries .....	12
5.6.1 General .....	12
5.6.2 Design recommendation .....	12
5.6.3 Mechanical protection for cells and components of batteries.....	13
5.7 Quality plan .....	13
5.8 Battery safety components.....	13
6 Type test and sample size .....	13
7 Specific requirements and tests .....	14
7.1 Charging procedures for test purposes .....	14
7.1.1 First procedure .....	14
7.1.2 Second procedure .....	14
7.2 Intended use .....	15
7.2.1 Continuous charging at constant voltage (cells) .....	15
7.2.2 Case stress at high ambient temperature (battery).....	15
7.3 Reasonably foreseeable misuse.....	15
7.3.1 External short-circuit (cell).....	15
7.3.2 External short-circuit (battery).....	16
7.3.3 Free fall.....	16
7.3.4 Thermal abuse (cells) .....	16
7.3.5 Crush (cells) .....	17
7.3.6 Over-charging of battery .....	17
7.3.7 Forced discharge (cells) .....	17
7.3.8 Mechanical tests (batteries).....	18
7.3.9 Design evaluation – Forced internal short-circuit (cells) .....	19
8 Information for safety.....	21
8.1 General.....	21
8.2 Small cell and battery safety information .....	22
9 Marking .....	22
9.1 Cell marking.....	22
9.2 Battery marking.....	23
9.3 Caution for ingestion of small cells and batteries .....	23
9.4 Other information .....	23
10 Packaging and transport.....	23
Annex A (normative) Charging and discharging range of secondary lithium ion cells for safe use.....	24

A.1	General.....	24
A.2	Safety of lithium ion secondary battery.....	24
A.3	Consideration on charging voltage .....	24
A.3.1	General .....	24
A.3.2	Upper limit charging voltage .....	24
A.4	Consideration of temperature and charging current.....	26
A.4.1	General .....	26
A.4.2	Recommended temperature range .....	26
A.4.3	High temperature range .....	27
A.4.4	Low temperature range .....	28
A.4.5	Scope of the application of charging current .....	29
A.4.6	Consideration of discharge .....	29
A.5	Sample preparation.....	30
A.5.1	General .....	30
A.5.2	Insertion procedure for nickel particle to generate internal short .....	30
A.5.3	Disassembly of charged cell .....	31
A.5.4	Shape of nickel particle .....	31
A.5.5	Insertion of nickel particle in cylindrical cell .....	31
A.5.6	Insertion of nickel particle in prismatic cell.....	34
A.6	Experimental procedure of the forced internal short-circuit test .....	36
A.6.1	Material and tools for preparation of nickel particle .....	36
A.6.2	Example of a nickel particle preparation procedure .....	37
A.6.3	Positioning (or placement) of a nickel particle .....	37
A.6.4	Damaged separator precaution.....	38
A.6.5	Caution for rewinding separator and electrode .....	38
A.6.6	Insulation film for preventing short-circuit .....	39
A.6.7	Caution when disassembling a cell .....	39
A.6.8	Protective equipment for safety .....	39
A.6.9	Caution in the case of fire during disassembling .....	39
A.6.10	Caution for the disassembling process and pressing the electrode core.....	39
A.6.11	Recommended specifications for the pressing device .....	39
Annex B (informative)	Recommendations to equipment manufacturers and battery assemblers .....	42
Annex C (informative)	Recommendations to the end-users .....	43
Annex D (normative)	Measurement of the internal AC resistance for coin cells .....	44
D.1	General.....	44
D.2	Method .....	44
Annex E (informative)	Packaging and transport.....	45
Annex F (informative)	Component standards references .....	46
Bibliography	.....	47
Figure 1	– Forced discharge time chart .....	18
Figure 2	– Jig for pressing .....	21
Figure 3	– Ingestion gauge .....	22
Figure A.1	– Representation of lithium ion cells operating region for charging.....	25
Figure A.2	– Representation of lithium ion cell operating region for discharging .....	30
Figure A.3	– Shape of nickel particle.....	31

Figure A.4 – Nickel particle insertion position between positive and negative active material coated area of cylindrical cell .....	31
Figure A.5 – Nickel particle insertion position between positive aluminium foil and negative active material coated area of cylindrical cell .....	32
Figure A.6 – Disassembly of cylindrical cell .....	33
Figure A.7 – Nickel particle insertion position between positive and negative (active material) coated area of prismatic cell.....	34
Figure A.8 – Nickel particle insertion position between positive aluminium foil and negative (active material) coated area of prismatic cell .....	35
Figure A.9 – Disassembly of prismatic cells .....	36
Figure A.10 – Dimensions of a completed nickel particle.....	37
Figure A.11 – Positioning of the nickel particle when it cannot be placed in the specified area .....	38
Figure A.12 – Cylindrical cell .....	38
Figure A.13 – Distance / time ratio of several types of pressing devices .....	41
Table 1 – Sample size for type tests .....	14
Table 2 – Condition of charging procedure.....	15
Table 3 – Conditions for vibration test.....	19
Table 4 – Shock parameters .....	19
Table 5 – Ambient temperature for cell test.....	20
Table A.1 – Examples of operating region charging parameters .....	25
Table A.2 – Recommended specifications of a pressing device.....	40
Table F.1 – Component standard references .....	46

IECNORM.COM : Click to view the full PDF of IEC 62133-2 ed 1.0:2017

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SAFETY REQUIREMENTS FOR PORTABLE SEALED SECONDARY CELLS, AND FOR BATTERIES MADE FROM THEM, FOR USE IN PORTABLE APPLICATIONS –

## Part 2: Lithium systems

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62133-2 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This first edition cancels and replaces the second edition of IEC 62133 published in 2012. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62133:2012:

- separation of nickel systems into a separate Part 1;
- inclusion of coin cell requirements;

- update of assembly of cells into batteries (5.6);
- mechanical tests [vibration, shock] (7.3.8.1, 7.3.8.2);
- insertion of IEC TR 62914 within the Bibliography.

The text of this standard is based on the following documents:

FDIS	Report on voting
21A/620/FDIS	21A/628/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The following different practices of a less permanent nature exist in the countries indicated below.

7.3.9: Design evaluation – Forced internal short-circuit test only applies to Korea, Japan, Switzerland and France.

A list of all parts of the IEC 62133 series, published under the general title *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

**SECONDARY CELLS AND BATTERIES CONTAINING  
ALKALINE OR OTHER NON-ACID ELECTROLYTES –  
SAFETY REQUIREMENTS FOR PORTABLE SEALED  
SECONDARY CELLS, AND FOR BATTERIES MADE  
FROM THEM, FOR USE IN PORTABLE APPLICATIONS –**

**Part 2: Lithium systems**

**1 Scope**

This part of IEC 62133 specifies requirements and tests for the safe operation of portable sealed secondary lithium cells and batteries containing non-acid electrolyte, under intended use and reasonably foreseeable misuse.

**2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482:2004, *International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries* (available at <http://www.electropedia.org>)

IEC 61960, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for portable applications*

ISO/IEC Guide 51, *Safety aspects – Guidelines for their inclusion in standards*

## SOMMAIRE

AVANT-PROPOS .....	51
1 Domaine d'application .....	53
2 Références normatives .....	53
3 Termes et définitions .....	53
4 Tolérances de mesure relatives aux paramètres .....	56
5 Considérations générales de sécurité .....	57
5.1 Généralités .....	57
5.2 Isolement et câblage .....	57
5.3 Échappement de gaz .....	57
5.4 Gestion de la température, de la tension et du courant .....	58
5.5 Contacts des bornes .....	58
5.6 Assemblage des éléments dans les batteries .....	58
5.6.1 Généralités .....	58
5.6.2 Recommandation de conception .....	58
5.6.3 Protection mécanique des éléments et des composants de batteries .....	59
5.7 Plan qualité .....	59
5.8 Composants de sécurité de la batterie .....	59
6 Essai d'homologation et effectif d'échantillon .....	59
7 Exigences spécifiques et essais .....	60
7.1 Procédures de charge pour les besoins des essais .....	60
7.1.1 Première procédure .....	60
7.1.2 Deuxième procédure .....	61
7.2 Utilisation prévue .....	61
7.2.1 Charge continue à tension constante (éléments) .....	61
7.2.2 Contrainte de moulage du boîtier à température ambiante élevée (batterie) .....	61
7.3 Utilisation abusive raisonnablement prévisible .....	62
7.3.1 Court-circuit externe (élément) .....	62
7.3.2 Court-circuit externe (batterie) .....	62
7.3.3 Chute libre .....	62
7.3.4 Température abusive (éléments) .....	63
7.3.5 Écrasement (éléments) .....	63
7.3.6 Surcharge de la batterie .....	63
7.3.7 Décharge forcée (éléments) .....	64
7.3.8 Essais mécaniques (batteries) .....	65
7.3.9 Évaluation de la conception – Court-circuit interne forcé (éléments) .....	66
8 Informations relatives à la sécurité .....	68
8.1 Généralités .....	68
8.2 Informations relatives à la sécurité des éléments et batteries de petite taille .....	69
9 Marquage .....	69
9.1 Marquage des éléments .....	69
9.2 Marquage des batteries .....	69
9.3 Mise en garde contre l'ingestion des éléments et batteries de petite taille .....	70
9.4 Autres informations .....	70
10 Emballage et transport .....	70

Annexe A (normative) Plage de charge et de décharge des éléments d'accumulateurs lithium ion pour une utilisation en toute sécurité.....	71
A.1 Généralités .....	71
A.2 Sécurité des batteries d'accumulateurs lithium ion .....	71
A.3 Considérations concernant la tension de charge .....	71
A.3.1 Généralités .....	71
A.3.2 Limite supérieure de la tension de charge.....	71
A.4 Considérations relatives à la température et au courant de charge .....	73
A.4.1 Généralités .....	73
A.4.2 Plage de températures recommandées .....	74
A.4.3 Plage de températures élevées.....	74
A.4.4 Plage de températures basses.....	75
A.4.5 Domaine d'application du courant de charge.....	76
A.4.6 Considération relative à la décharge.....	77
A.5 Préparation de l'échantillon.....	78
A.5.1 Généralités .....	78
A.5.2 Procédure d'insertion d'une particule de nickel pour créer un court-circuit interne.....	78
A.5.3 Démontage de l'élément chargé.....	78
A.5.4 Forme de la particule de nickel .....	78
A.5.5 Insertion de la particule de nickel dans l'élément cylindrique .....	78
A.5.6 Insertion de la particule de nickel dans l'élément parallélépipédique .....	81
A.6 Procédure expérimentale de l'essai de court-circuit interne forcé .....	83
A.6.1 Matière et outils pour préparation d'une particule de nickel.....	83
A.6.2 Exemple de procédure de préparation d'une particule de nickel .....	84
A.6.3 Positionnement (ou mise en place) d'une particule de nickel.....	85
A.6.4 Précautions en cas de séparateur endommagé.....	85
A.6.5 Mise en garde lors du rembobinage du séparateur et de l'électrode .....	85
A.6.6 Film isolant pour la prévention des court-circuits .....	86
A.6.7 Mise en garde lors du démontage d'un élément .....	86
A.6.8 Équipement de protection pour la sécurité .....	86
A.6.9 Mise en garde en cas de feu lors du démontage .....	86
A.6.10 Mise en garde lors du processus de démontage et de serrage sous pression du noyau de l'électrode .....	86
A.6.11 Spécifications recommandées pour le dispositif de pressage .....	87
Annexe B (informative) Recommandations à l'attention des fabricants d'équipements et assembleurs de batteries .....	89
Annexe C (informative) Recommandations à l'attention des utilisateurs finaux .....	90
Annexe D (normative) Mesure de la résistance interne en courant alternatif des éléments boutons .....	91
D.1 Généralités .....	91
D.2 Méthode.....	91
Annexe E (informative) Emballage et transport .....	92
Annexe F (informative) Références des normes relatives aux composants.....	93
Bibliographie.....	94
Figure 1 – Graphique chronologique de la décharge forcée .....	64
Figure 2 – Gabarit de serrage sous pression.....	68

Figure 3 – Gabarit d'ingestion .....	69
Figure A.1 – Représentation de la région de fonctionnement des éléments lithium ion pour la charge.....	72
Figure A.2 – Représentation de la région de fonctionnement d'un élément lithium ion pour la décharge.....	77
Figure A.3 – Forme de la particule de nickel .....	78
Figure A.4 – Position d'insertion de la particule de nickel entre les zones enduites de matière active positive et négative dans un élément cylindrique.....	79
Figure A.5 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone imprégnée de matière active négative de l'élément cylindrique .....	79
Figure A.6 – Démontage d'un élément cylindrique.....	80
Figure A.7 – Position d'insertion de la particule de nickel entre les zones positive et négative enduites (de matière active) de l'élément parallélépipédique .....	81
Figure A.8 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone enduite (de matière active) négative de l'élément parallélépipédique .....	82
Figure A.9 – Démontage des éléments parallélépipédiques .....	83
Figure A.10 – Dimensions de la particule de nickel obtenue.....	84
Figure A.11 – Positionnement de la particule de nickel lorsqu'elle ne peut pas être placée dans la zone spécifiée .....	85
Figure A.12 – Élément cylindrique .....	86
Figure A.13 – Rapport distance / durée de plusieurs types de dispositifs de pressage .....	88
Tableau 1 – Effectif d'échantillon pour essais d'homologation .....	60
Tableau 2 – Condition de la procédure de charge .....	61
Tableau 3 – Conditions des essais de vibrations.....	65
Tableau 4 – Paramètres de choc .....	66
Tableau 5 – Température ambiante pour l'essai d'un élément .....	66
Tableau A.1 – Exemples de paramètres de charge d'une région de fonctionnement.....	72
Tableau A.2 – Spécifications recommandées pour un dispositif de pressage .....	87
Tableau F.1 – Références des normes relatives aux composants .....	93

IECNORM.COM - Click to view the full PDF of IEC 62133-2:2017