

INTERNATIONAL STANDARD

Dynamic modules – General and guidance

IECNORM.COM: Click to view the full PDF of IEC 62343:2013



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



INTERNATIONAL STANDARD

Dynamic modules – General and guidance

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

Q


ICS 33.180.01; 33.180.99

ISBN 978-2-83220-854-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope and object.....	7
2 Normative references	7
3 Terms and definitions	7
3.1 General terms	8
3.2 Dynamic module terms	8
3.3 Dynamic channel equalizer (DCE) terms	8
3.4 Tuneable dispersion compensator (TDC) or dynamic chromatic dispersion compensator (DCDC) terms.....	9
3.5 Dynamic gain tilt equalizer (DGTE) terms	10
3.6 Optical channel monitor (OCM) terms.....	11
4 Abbreviations	14
5 Preparation of standards	14
5.1 General	14
5.2 Product definition	15
5.3 Tests.....	15
5.4 Details.....	15
5.5 Requirements	15
5.6 Sample size	15
5.7 Sample definition.....	15
5.8 Groupings/sequences.....	15
5.9 Pass/fail criteria	15
5.10 Reference product definition.....	15
5.11 Performance standard test report.....	15
6 Electromagnetic compatibility (EMC) requirements	16
Bibliography.....	17



INTERNATIONAL ELECTROTECHNICAL COMMISSION

DYNAMIC MODULES – GENERAL AND GUIDANCE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62343 has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

CDV	Report on voting
86C/1055/CDV	86C/1088/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62343 series, published under the general title *Dynamic modules*, can be found on the IEC website.

The structure of the IEC 62343 series, under the general title *Dynamic modules*, is as follows:

- 62343-1 series Part 1: Performance standards
- 62343-2 Part 2: Reliability qualification
- 62343-3 Performance specification templates
- 62343-4 series Software and hardware interface standards
- 62343-5 series Test methods
- 62343-6 series Technical reports

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM: Click to view the full PDF of IEC 62343:2013
Withdrawn

INTRODUCTION

This International Standard applies to dynamic devices as defined in IEC/TS 62538. It contains general guidance for the IEC 62343 series related to dynamic devices, and definitions which apply to dynamic devices. The dynamic module, or device, has two distinguishing characteristics: dynamic and module.

“Dynamic” highlights the functions of the products to include “tuning, varying, switching, configuring, and other continuous optimization,” often accomplished by electronics, firmware, software or their combinations. The dynamic device usually has a certain level of intelligence to monitor or measure the situation and make decisions for necessary (optimization) actions. The behaviour of dynamic modules may be characterized by transient characteristics as the dynamic module undergoes tuning, switching, configuring and other continuous optimization. Characterization of transient characteristics will be considered in individual dynamic module standards.

“Module” defines that the products covered by the standard are the integration of active and passive components (either or both), through interconnecting materials or devices. The controlling electronics can be inside or outside the optical package (that contains all or most of the optical components and interconnection). The product can look like a small printed wiring board (PWB or child-board with mounted optical module) or a small box (housing) with optical components and electronics enclosed. In the former case, it is more like an assembly (generally not packaged in a box or housing) than a module (generally packaged in a box or housing).

For historical reasons and convenience, a dynamic module or device is referred to as a dynamic module in the IEC 62343-X series.

The number of dynamic modules and devices is rapidly growing as optical communications networks evolve. The following list provides some examples of the products covered by the IEC 62343-X series. It should be noted that the list is not exhaustive and the products to be covered are not limited by the listed examples:

- channel gain equalizer;
- dynamic channel equalizer;
- dynamic gain tilt equalizer;
- dynamic slope equalizer;
- tuneable chromatic dispersion compensator;
- polarization mode dispersion compensator;
- reconfigurable optical add-drop multiplexer;
- switch with monitoring and controls;
- variable optical attenuator with monitoring and controls.

The IEC 62343 series will cover performance templates, performance standards, reliability qualification requirements, hardware and software interfaces, and related testing methods.

A complete set of standards related to a dynamic module or device should include the following:

- optical performance standards;
- reliability qualification standards;
- optical performance specification templates;
- hardware and software interface standards;
- test methods;

- technical reports.

The safety standards related to dynamic modules are mostly optical power considerations, which are covered by IEC TC 76: Optical radiation safety and laser equipment.

Only those dynamic modules for which standards are complete or in preparation are included in Clause 3. To reflect the rapidly growing market for dynamic modules, additional terms and definitions will be added in subsequent revisions as the series expands.

It should be noted that optical amplifiers could be regarded as dynamic modules. They are not included in the IEC 62343-X series, but are covered in their own series of IEC standards.

IECNORM.COM: Click to view the full PDF of IEC 62343:2013
Withdrawn

DYNAMIC MODULES – GENERAL AND GUIDANCE

1 Scope and object

This International Standard applies to all commercially available optical dynamic modules and devices. It describes the products covered by the IEC 62343-X series, defines terminology, fundamental considerations and basic approaches.

The object of this standard is to

- establish uniform requirements for operation, reliability and environmental properties of DMs to be implemented in the appropriate DM standard,
- provide assistance to the purchaser in the selection of consistently high-quality DM products for his particular applications, as well as in the consultation of the appropriate specific DM standard(s).

This standard covers performance templates, performance standards, reliability qualification requirements, hardware and software interfaces and related testing methods.

Since a dynamic module integrates an optical module/device, printed wiring board, and software/firmware, the standards developed in the series will mimic appropriate existing standards. On the other hand, since "dynamic module" is a relatively new product category, the dynamic module standards series will not be bounded by the existing practices where requirements differ.

The safety standards as related to dynamic modules are mostly optical power considerations, which is covered by IEC TC 76: Optical radiation safety and laser equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-731, *International Electrotechnical Vocabulary – Chapter 731: Optical fibre communication*

IEC/TR 61931, *Fibre optic – Terminology*

IEC 62343-1 (all parts), *Dynamic modules – Optical performance standards*

IEC 62343-3 (all parts), *Dynamic modules – Optical performance specification templates*

IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

The definitions listed in this clause refer to the meaning of the terms used in the specifications of DMs. Only those parameters listed in the appropriate performance standard in the IEC 62343-1 series and performance specification templates in the IEC 62343-3 series are intended to be specified.

The list of parameter definitions of DMs, given in this clause, is divided into subclauses by the type of DM. See also IEC 60050-731 and IEC/TR 61931.

3.1 General terms

3.1.1

optical dynamic device

optical device which is designed to monitor and control dynamically some characteristics of one or more optical signals, by means of suitable electronic controls, in order to improve or to maintain definite performances of the system in which it is intended to be inserted

Note 1 to entry: Said characteristics may include optical paths, optical intensities, spectral characteristics, polarization states, dispersion, etc.

Note 2 to entry: Optical dynamic devices may comprise optical active and optical passive elements or components.

Note 3 to entry: The control/response time of optical dynamic devices is much larger than the signal time characteristics and typically may range from few microseconds to tens of seconds.

[SOURCE: IEC/TS 62538:2008, definition 2.1.1]

3.1.2

optical module

packaged integration of optical components and/or elements, accomplishing defined functionality, typically repairable and re-workable

[SOURCE: IEC/TS 62538:2008, definition 2.2.5, modified – the Notes to entry in the source have been omitted]

3.2 Dynamic module terms

The following definitions apply to all dynamic modules

3.2.1

operating wavelength range

specified range of wavelengths from λ_{imin} to λ_{imax} about a nominal operating wavelength λ_1 , within which a dynamic optical module is designed to operate with a specified performance

3.2.2

channel frequency range

frequency range within which a device is expected to operate with a specified performance

Note 1 to entry: For a particular nominal channel central frequency, f_{nomi} , this frequency range is from $f_{imin} = (f_{nomi} - \Delta f_{max})$ to $f_{imax} = (f_{nomi} + \Delta f_{max})$, where Δf_{max} is the maximum channel central frequency deviation.

3.2.3

channel spacing

centre-to-centre difference in frequency (or wavelength) between adjacent channels in a device

3.3 Dynamic channel equalizer (DCE) terms

The following definitions apply to the dynamic channel equalizer

3.3.1

dynamic channel equalizer

DCE

device capable of transforming, by internal or external automatic control, a multichannel input signal with time-varying averaged powers into an output signal in which all working channel powers are nominally equal or are set for a required level of pre-emphasis

Note 1 to entry: This device may also provide the extinction of one or more of the input channels.

[SOURCE: IEC 62343-3-1:2010, definition 3.5]

3.3.2

channel non-uniformity

difference between the powers of the channel with the most power (in dBm) and the channel with the least power (in dBm)

Note 1 to entry: This applies to a multichannel signal across the operating wavelength range.

Note 2 to entry: Channel non-uniformity is expressed in dB.

[SOURCE: IEC 62343-3-1:2010, definition 3.2, modified – Additional information with respect to applicability has been transferred to Note 1 to entry; Note 2 to entry is additional]

3.3.3

in-band extinction ratio

within the operating wavelength range, the difference between the minimum power of the non-extinguished channels (in dBm) and the maximum power of the extinguished channels (in dBm)

Note 1 to entry: In-band extinction ratio is expressed in dB

[SOURCE: IEC 62343-3-1:2010, definition 3.6, modified – Information relating to the units (dBm) now appears in the form of Note 1 to entry]

3.3.4

out-of-band attenuation

attenuation of channels that fall outside of the operating wavelength range

Note 1 to entry: Out-of-band attenuation is expressed in dB.

[SOURCE: IEC 62343-3-1:2010, definition 3.8, modified – Information relating to the units (dB) now appears in the form of Note 1 to entry]

3.3.5

ripple

peak-to-peak difference in insertion loss within a channel frequency (or wavelength) range

[SOURCE: IEC 62343-3-1:2010, definition 3.9]

3.3.6

channel response time

elapsed time it takes a device to transform a channel from a specified initial power level to a specified final power level desired state, when the resulting output channel non-uniformity tolerance is met, measured from the time the actuation energy is applied or removed

[SOURCE: IEC 62343-3-1:2010, definition 3.3]

3.4 Tuneable dispersion compensator (TDC) or dynamic chromatic dispersion compensator (DCDC) terms

The following definitions apply to the tuneable dispersion compensator (TDC) or dynamic chromatic dispersion compensator (DCDC)

3.4.1

tuneable dispersion compensator

dynamic chromatic dispersion compensator

TDC (DCDC)

two-port in-line device that is capable of transforming, by internal or external automatic control, an input signal with time-varying dispersion into an output signal in which an output channel dispersion value is set for a required level of value

3.4.2

insertion loss ripple

maximum peak-to-peak variation of the insertion loss within a channel frequency (or wavelength) range

3.4.3

dispersion tuning time

longest elapsed time it takes a module to change a dispersion setting from an arbitrary initial dispersion value to a desired final dispersion value, when the resulting dispersion target tolerance is met

3.5 Dynamic gain tilt equalizer (DGTE) terms

The following definitions apply to the dynamic gain tilt equalizer (DGTE)

3.5.1

dynamic spectral equalizer

DSE

two port in-line dynamic module that converts an input signal with time-varying spectral shape into an output signal in which spectral shape is nominally flat, or is set for a required spectral shape for pre-emphasis

3.5.2

dynamic gain tilt equalizer

DGTE

dynamic spectral equalizer used in an optical amplifier that converts input signals with time-varying gain tilt into output signals in which gain tilt is nominally flat, or is set for a required gain tilt

3.5.3

dynamic gain tilt range

difference between the maximum and minimum deviation of attenuation over operating wavelength range, to which the dynamic gain tilt equalizer can be set

3.5.4

positive slope type

type of DGTE for which dynamic gain tilt range can be set for positive gain tilt

3.5.5

negative slope type

type of DGTE for which dynamic gain tilt range can be set for negative gain tilt

3.5.6

both slope type

type of DGTE to which dynamic gain tilt range can be set for both positive and negative gain tilt

3.5.7

slope linearity

maximum deviation of attenuation between the spectral shape by dynamic gain tilt equalizer and linear slope over the operating wavelength range

3.5.8

response time

longest elapsed time it takes a dynamic gain tilt equalizer to change a gain tilt setting from an arbitrary initial gain tilt value to a desired final gain tilt value, when the resulting gain tilt target tolerance is met

3.6 Optical channel monitor (OCM) terms

The following definitions apply to the optical channel monitor (OCM)

3.6.1

input channel plan

entire set of ITU channels on which the optical channel monitor is reporting

3.6.2

input channel frequency spacing tolerance

centre-to-centre difference in frequency (or wavelength) between adjacent channels in a device

3.6.3

input channel power dynamic range

full range of input power per channel between the saturation and sensitivity limits

3.6.4

input channel non-uniformity

difference (in dB) between the powers of the channel with the most power (in dBm) and the channel with the least power (in dBm) during one measurement within the response time

Note 1 to entry: This applies to a multichannel signal across the operating wavelength range.

3.6.5

input adjacent channel non-uniformity

difference between the powers of adjacent channels present during one measurement within the response time

Note 1 to entry: This applies to a multichannel signal across the operating wavelength range.

Note 2 to entry: In-band extinction ratio is expressed in dB.

3.6.6

input channel non-uniformity for channel identification

difference between the powers of the channel with the most power and the channel with the least power during one measurement within the response time for positively identifying all channels present and not falsely identifying channels that are not present

Note 1 to entry: This applies to a multichannel signal across the operating wavelength range.

Note 2 to entry: In-band extinction ratio is expressed in dB.

3.6.7

input adjacent channel non-uniformity for channel identification

difference between the powers of adjacent channels present during one measurement within the response time for positively identifying all channels present and not falsely identifying channels that are not present

Note 1 to entry: This applies to a multichannel signal across the operating wavelength range.

Note 2 to entry: In-band extinction ratio is expressed in dB.

3.6.8

input total band power dynamic range for channel measurements

full range of input total band power between the saturation or sensitivity limits of channel measurements

3.6.9

input total band power dynamic range for total band power measurements

full range of input total band power between the saturation or sensitivity limits of total band power measurements

3.6.10

input OSNR dynamic range

full range of input OSNR per channel within which the power, total band power and OSNR measurements remain within their respectively specified error limits

3.6.11

input channels bit rates

list of bit rates to which any channel may be modulated

3.6.12

reference measurement bandwidth

integration bandwidth of the optical power measurement

3.6.13

noise equivalent bandwidth

integration bandwidth of the optical noise measurement

3.6.14

channel power absolute error

maximum difference between the measured channel power and the calibrated reference channel power, within the specified measurement integration bandwidth, during one measurement within the response time, specified over all input and operating ranges

3.6.15

channel power relative error

maximum variation of the channel power absolute error, during one measurement within the response time, specified over all input and operating ranges

3.6.16

channel power variability

maximum variation of the channel power absolute error over the repeatability time interval at a given input and operating condition, specified over all input and operating ranges

3.6.17

channel power resolution interval

smallest increment of the reported channel power measurement value

3.6.18

channel power polarization dependent error

maximum power measurement difference over all polarization states at a given input and operating condition, during one measurement within the response time, specified over all input and operating ranges

3.6.19

total band power absolute error

difference between the measured total power and the calibrated total power reference, each integrated over the frequency band, during one measurement within the response time, specified over all input and operating ranges

3.6.20**total band power relative error**

maximum variation of the total band absolute error, during one measurement within the response time, specified over all input and operating ranges

3.6.21**total band power variability**

maximum variation of the total band power absolute error over the repeatability time interval at given input and operating conditions, specified over all input and operating ranges

3.6.22**total band power resolution interval**

smallest increment of the reported total band power measurement value

3.6.23**frequency absolute error**

maximum difference between the measured frequency and the calibrated reference frequency, during one measurement within the response time, specified over all input and operating ranges

3.6.24**frequency relative error**

maximum variation of the frequency absolute error, during one measurement within the response time, specified over all input and operating ranges

3.6.25**frequency variability**

maximum variation of the frequency absolute error over the repeatability time interval at given input and operating conditions, specified over all input and operating ranges

3.6.26**frequency resolution interval**

smallest increment of the reported frequency measurement value

3.6.27**frequency polarization dependent error**

maximum frequency measurement difference over all polarization states at given input and operating conditions, during one measurement within the response time, specified over all input and operating ranges

3.6.28**OSNR absolute error**

maximum difference between the measured and the calibrated reference OSNR, during one measurement within the response time, specified over all input and operating ranges

3.6.29**OSNR relative error**

maximum variation of the OSNR absolute error, during one measurement within the response time, specified over all input and operating ranges

3.6.30**OSNR variability**

maximum variation of the OSNR absolute error over the repeatability time interval at given input and operating conditions, specified over all input and operating ranges

3.6.31**OSNR resolution interval**

smallest increment of the reported OSNR measurement value

3.6.32**OSNR polarization dependent error**

maximum OSNR measurement difference over all polarization states at given input and operating conditions, during one measurement within the response time, specified over all input and operating ranges

3.6.33**back reflection**

fraction of the optical signal reflected at the input optical port over the entire band, specified over all input and operating ranges

3.6.34**response time**

time required to perform the specified measurements for all channels and transfer these values over the communications interface to the external controller that issues a measurement request, specified over all input and operating ranges

3.6.35**repeatability time interval**

minimum time interval over which a given measurement repeatability is performed

4 Abbreviations

DCDC	dynamic chromatic dispersion compensator
DCE	dynamic channel equalizer
DGTE	dynamic gain tilt equalizer
DM	dynamic module
DSE	dynamic spectral equalizer
EMC	electromagnetic compatibility
ESD	electrostatic discharge
OCM	optical channel monitor
OSNR	optical signal-to-noise ratio
PWB	printed wiring board
TDC	tuneable dispersion compensator

5 Preparation of standards**5.1 General**

In the preparation of a performance standard, the following items shall be considered and instructions pertaining to them included:

- product definition;
- tests;
- details;
- requirements;
- sample size;
- sample definition;
- groupings/sequences;
- pass/fail criteria;
- reference product definition;

- performance standard test report.

5.2 Product definition

The product to which the performance standard relates shall be clearly defined.

5.3 Tests

The tests to be carried out on the product in order for it to meet the performance standard shall be clearly defined. No ambiguity or options shall be allowed.

The test method to be used shall be clearly defined for each test. Wherever possible the test method shall be selected from IEC referenced tests; where this is not possible other test methods may be defined. If an undefined test method is used, the test method and details to be specified shall be included in the appropriate annex of the performance standard.

5.4 Details

Details to be considered shall be given for all tests and measurements presented in a performance standard. These should be directly related to the requirements specified for a product location within an operating or service environment to which the performance standard is intended to correspond. No ambiguity or options shall be allowed.

5.5 Requirements

The performance requirements that must be satisfied in order for the product to comply with the performance standard shall be specified for each test and /or measurement. No ambiguities shall be allowed.

5.6 Sample size

The sample size for each test shall be defined in an annex of the performance standard.

5.7 Sample definition

The sample to be tested shall be defined in the relevant performance standard.

5.8 Groupings/sequences

Test groups and test sequences shall be defined in the appropriate annex of the performance standard as required by the user, user group or manufacturer. The number of samples for each test group shall also be defined in the annex.

5.9 Pass/fail criteria

The pass/fail criteria shall be unambiguously stated for each test within the performance standard. No deviation or exceptions shall be allowed.

5.10 Reference product definition

Where a performance standard requires the use of a reference product or component, the reference product shall be clearly defined in the appropriate annex of the performance standard.

5.11 Performance standard test report

Conformance to a performance standard shall be supported by a test report. The test report shall clearly demonstrate that the tests were carried out in accordance with the requirements of the performance standard and provide full details of the tests together with a pass/fail