

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 62841-2-6
Edition 1.0 2020-07

**ELECTRIC MOTOR-OPERATED HAND-HELD
TOOLS, TRANSPORTABLE TOOLS AND LAWN
AND GARDEN MACHINERY – SAFETY –**

**Part 2-6: Particular requirements for hand-held
hammers**

IEC 62841-2-6
Édition 1.0 2020-07

**OUTILS ÉLECTROPORTATIFS À MOTEUR,
OUTILS PORTABLES ET MACHINES POUR
JARDINS ET PELOUSES – SÉCURITÉ –**

**Partie 2-6: Exigences particulières pour les
marteaux portatifs**

CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

Annex I – Measurement of noise and vibration emissions

Replace the first row of Table I.102, modified by Amendment 1, with the following new text:

Table I.102 – Noise test conditions for rotary hammers

Orientation	<p>Drilling vertically down into a concrete block having the formulation specified in Table I.103 and having the minimum dimensions 500 mm × 500 mm and 200 mm in height and supported on resilient material. The concrete block, its support and the tool shall be so oriented that</p> <ul style="list-style-type: none">– the geometric centre of the tool is 1 m above the reflecting plane;– the centre of the concrete block is located under the top microphone "5"; as shown in Figure I.2 of Part 1; and– the sides of the concrete block are parallel to the square formed by the microphones "1" to "4" as shown in Figure I.2 of Part 1. <p>For consistency of results the drilled holes are blind holes. If the drill bit breaks through, reducing the depth of the hole slightly is a method to avoid this.</p>
--------------------	---