


# INTERNATIONAL STANDARD

**Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – Safety –  
Part 2-9: Particular requirements for hand-held tappers and threaders**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2025 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IECNORM.COM : Click to view the full PDF of IEC 60947-1:2015+AMD1:2025 CSV



IEC 62841-2-9

Edition 1.1 2025-02  
CONSOLIDATED VERSION

# INTERNATIONAL STANDARD

**Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – Safety –  
Part 2-9: Particular requirements for hand-held tappers and threaders**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 25.140.20

ISBN 978-2-8327-0249-9

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 General requirements .....	6
5 General conditions for the tests .....	6
6 Radiation, toxicity and similar hazards .....	7
7 Classification .....	7
8 Marking and instructions .....	7
9 Protection against access to live parts .....	8
10 Starting .....	8
11 Input and current .....	8
12 Heating .....	8
13 Resistance to heat and fire .....	9
14 Moisture resistance .....	9
15 Resistance to rusting .....	9
16 Overload protection of transformers and associated circuits .....	9
17 Endurance .....	9
18 Abnormal operation .....	9
19 Mechanical hazards .....	10
20 Mechanical strength .....	10
21 Construction .....	11
22 Internal wiring .....	11
23 Components .....	11
24 Supply connection and external flexible cords .....	11
25 Terminals for external conductors .....	11
26 Provision for earthing .....	12
27 Screws and connections .....	12
28 Creepage distances, clearances and distances through insulation .....	12
Annexes .....	14
Annex J (informative) Measurement of noise and vibration emissions .....	14
Annex K (normative) Battery tools and battery packs .....	17
Bibliography .....	18
Figure 101 – Threader with support device .....	12
Figure 102 – Set-up for testing the support device .....	13
Figure I.101 – Position of transducers for tappers .....	15
Figure I.102 – Position of transducers for threaders .....	16
Table 101 – Load torque .....	9
Table 4 – Required performance levels .....	10
Table I.101 – Operating conditions for tappers and threaders .....	15

Table 4 – Required performance levels ..... 17

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS,  
TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY –  
SAFETY –****Part 2-9: Particular requirements for hand-held tappers and threaders**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.**

**IEC 62841-2-9 edition 1.1 contains the first edition (2015-01) [documents 116/199/FDIS and 116/212/RVD], its corrigendum 1 (2015-10) and its amendment 1 (2025-02) [documents 116/861/FDIS and 116/876/RVD].**

**In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.**

International Standard IEC 62841-2-9 has been prepared by IEC technical committee 116: Safety of motor-operated electric tools.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 2-9 is to be used in conjunction with the first edition of IEC 62841-1 (2014).

This Part 2-9 supplements or modifies the corresponding clauses in IEC 62841-1, so as to convert it into the IEC Standard: Particular requirements for hand-held tappers and threaders.

Where a particular subclause of Part 1 is not mentioned in this Part 2-9, that subclause applies as far as reasonable. Where this standard states “addition”, “modification” or “replacement”, the relevant text in Part 1 is to be adapted accordingly.

The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

The terms defined in Clause 3 are printed in **bold typeface**.

Subclauses, notes and figures which are additional to those in Part 1 are numbered starting from 101.

A list of all parts of the IEC 62841 series, under the general title: *Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – Safety*, can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 36 months from the date of publication.

# ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

## Part 2-9: Particular requirements for hand-held tappers and threaders

### 1 Scope

This clause of Part 1 is applicable, except as follows:

*Addition:*

This standard applies to hand-held **tappers** and **threaders**.

### 2 Normative references

This clause of Part 1 is applicable, except as follows:

*Addition:*

ISO 7-1:1994, *Pipe threads where pressure-tight joints are made on the threads – Part 1: Dimensions, tolerances and designation*

ISO 65:1981, *Carbon steel tubes suitable for screwing in accordance with ISO 7-1*

### 3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

*Addition:*

#### 3.101

##### **tapper**

tool intended for cutting internal screw threads

#### 3.102

##### **threader**

tool intended for cutting external threads

### 4 General requirements

This clause of Part 1 is applicable.

### 5 General conditions for the tests

This clause of Part 1 is applicable, except as follows:

**5.17 Addition:**

The mass of a **tapper/threader** includes the auxiliary handle, if any. Any support device as illustrated in Figure 101 for a **threader** is not regarded as part of the tool.

## 6 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.

## 7 Classification

This clause of Part 1 is applicable.

## 8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

**8.1 Addition:**

In addition the tool shall have the following marking:

- maximum diameter, in millimetres (for **tappers**) or in inches (for **threaders**), of the thread which can be cut.

NOTE According to the International System of Units, only SI units should be used. Nevertheless, some pipe diameters and threads are still specified in inches internationally.

For **tappers**, the diameter shall refer to a unified ISO thread to be cut into steel having a tensile strength of 390 N/mm<sup>2</sup> and a thickness of twice the thread diameter, unless otherwise indicated on the tool.

For **threaders**, the diameter shall refer to a taper style thread in accordance with ISO 7-1 to be cut on steel tubes in accordance with ISO 65, unless otherwise indicated on the tool.

**8.14.1 Addition:**

For **threaders**, the additional safety instructions as specified in 8.14.1.101 shall be given. This part may be printed separately from the “General Power Tool Safety Warnings”.

### 8.14.1.101 Threader safety warnings

- Always use the support device provided with the tool.** Loss of control during operation can result in personal injury.
- Keep sleeves and jackets buttoned while operating the tool. Do not reach across the tool or pipe.** Clothing can be caught by the pipe or the tool resulting in entanglement.
- Only one person must control the work process and tool operation.** Additional people involved in the process may result in unintended operation and personal injury.
- Keep floors dry and free of slippery materials such as oil.** Slippery floors invite accidents.

**8.14.2 a) Addition:**

101) for **threaders**: instructions for mounting and use of the support device.

**8.14.2 b) Addition:**

101) for **threaders**: instructions to always use the support device supplied with the tool;

102) for **threaders** with multiple gear box settings: information about which gear box setting is to be used for each pipe diameter.

## 9 Protection against access to live parts

This clause of Part 1 is applicable.

## 10 Starting

This clause of Part 1 is applicable.

## 11 Input and current

This clause of Part 1 is applicable, except as follows:

*Modification:*

For **threaders**, the requirements of this clause are replaced by the following:

The **rated input** or **rated current** shall be at least 100 % of the measured input or current applying the torque in Table 101.

*Compliance is checked by measuring the power input or current of the tool when stabilized while all circuits which can operate simultaneously are in operation.*

*For tools marked with one or more **rated voltages**, the test is made at each of the **rated voltages**. For tools marked with one or more **rated voltage ranges**, the test is made at both the upper and lower limits of the ranges. For tools with multiple gear box settings, the test is made at each specified gear box setting in accordance with 8.14.2 b). The highest value of input or current is applicable.*

## 12 Heating

This clause of Part 1 is applicable, except as follows:

### 12.2.1 Replacement:

**Tappers** are operated intermittently for 30 cycles or until thermal equilibrium is reached, whichever is achieved first, each cycle comprising a period of continuous operation of 30 s and a rest period of 90 s with the tool switched off, the tool being loaded during the periods of operation by means of a brake adjusted so as to attain **rated input** or **rated current**. The temperature rises are measured at the end of the last "on" period.

**Threaders** are operated for 30 s at load followed by 30 s no load and then switched off for a rest period of 60 s. This cycle is continued until thermal equilibrium is reached, or for 30 cycles, whichever is achieved first. The tool is loaded during the periods of operation by means of a brake adjusted to attain the torque specified in Table 101. The brake load may be ramped up to the specified torque over a period of time not to exceed 5 s. This ramp up time is added to the 30 s cycle at load. The temperature rises are measured at the end of the last load period.

The above test cycle may, at the manufacturer's option, be replaced by continuous operation of the tool until thermal equilibrium is reached.

NOTE Continuous operation is not typical for these tools and is regarded as a more severe test. Therefore, this is an option for the cycle test in order to simplify the testing.

**Table 101 – Load torque**

Maximum diameter of thread inch	Torque Nm
1	125
1,25	150
1,5	160
2	180

**12.5 Addition:**

For **threaders**, the temperature-rise limit specified for the external enclosure does not apply to the enclosure of the gear box. However, the above exemption does not apply to handles adjacent to the gear box.

**13 Resistance to heat and fire**

This clause of Part 1 is applicable.

**14 Moisture resistance**

This clause of Part 1 is applicable.

**15 Resistance to rusting**

This clause of Part 1 is applicable.

**16 Overload protection of transformers and associated circuits**

This clause of Part 1 is applicable.

**17 Endurance**

This clause of Part 1 is applicable.

**18 Abnormal operation**

This clause of Part 1 is applicable, except as follows:

**18.8 Replacement of Table 4:**

**Table 4 – Required performance levels**

Type and purpose of SCF	Minimum performance level (PL)
<b>Power switch</b> – prevent unwanted switch-on for <b>tappers</b>	a
<b>Power switch</b> – prevent unwanted switch-on for <b>threaders</b>	a
<b>Power switch</b> – provide desired switch-off for <b>tappers</b>	b
<b>Power switch</b> – provide desired switch-off for <b>threaders</b>	c
Provide desired direction of rotation	Not an <b>SCF</b>
Any electronic control to pass the test of 18.3	Not an <b>SCF</b>
Any speed limiting device	Not an <b>SCF</b>
Prevent exceeding thermal limits as in <del>Clause 18</del> 18.4 and 18.5.3	a

## 19 Mechanical hazards

This clause of Part 1 is applicable, except as follows:

**19.6** This subclause is not applicable.

## 20 Mechanical strength

This clause of Part 1 is applicable, except as follows:

**20.5** This subclause is not applicable.

**20.101** The device to support the **threader** shall withstand the torque output generated by the tool while cutting a thread in either direction.

*Compliance is checked by the following test:*

*The tool is set with the largest die head in accordance with 8.1 on to a pipe as specified in 8.1. The point of contact with the support device and tool is determined. The support device is mounted in accordance with 8.14.2 a) so there is an 8 mm minimum clearance between the device and the point of contact. See Figure 102.*

*A thread is cut until one of the following occurs:*

- *the tool stalls;*
- *the thread is destroyed allowing the die head to continue rotating;*
- *the die head stops rotating due to failure of the tool or by means of a mechanical or electrical/electronic device.*

*As a result of the test, none of the following shall occur:*

- *ejection of parts from the tool or from the die head;*
- *rotation of the support device exceeding 30° or lateral movement exceeding 25 mm;*
- *cracked or broken parts of the support device, however bending is allowed.*

## 21 Construction

This clause of Part 1 is applicable, except as follows:

### 21.18.1.1 *Addition:*

**Threaders** are regarded as tools with a risk associated with continued locked-on operation.

**21.18.1.2** This subclause is not applicable.

**21.30** This subclause is not applicable.

**21.32** This subclause is not applicable.

**21.35** This subclause is not applicable.

**21.101 Threaders** shall be supplied with a device to support the tool while cutting a thread.

Figure 101 shows an example of a **threader** with a support device.

*Compliance is checked by inspection.*

## 22 Internal wiring

This clause of Part 1 is applicable.

## 23 Components

This clause of Part 1 is applicable, except as follows:

~~**23.1.10.2** *Modification:*~~

~~**Power switches for threaders** are tested for 10 000 cycles.~~

**23.3** This subclause is not applicable.

## 24 Supply connection and external flexible cords

This clause of Part 1 is applicable, except as follows:

### **24.4** *Addition:*

If rubber insulated cables are used, they shall be polychloroprene or other equivalent synthetic elastomer sheathed cables (code designation 60245 IEC 57 or 60245 IEC 66).

## 25 Terminals for external conductors

This clause of Part 1 is applicable.

## 26 Provision for earthing


This clause of Part 1 is applicable.

## 27 Screws and connections

This clause of Part 1 is applicable.

## 28 Creepage distances, clearances and distances through insulation

This clause of Part 1 is applicable.




IEC

### Key

- 1 pipe
- 2 support device
- 3 threader

Figure 101 – Threader with support device



IEC

**Key**

- $d_1, d_2, d_3$  distance between support device and point of contact, depending on design of the tool
- 1 pipe
- 2 support device
- 3 threader

**Figure 102 – Set-up for testing the support device**

## Annexes

The annexes of Part 1 are applicable except as follows.

### Annex I (informative)

#### Measurement of noise and vibration emissions

NOTE In Europe (EN 62841-2-9), Annex I is normative.

#### I.2 Noise test code (grade 2)

This clause of Part 1 is applicable except as follows:

##### I.2.4 Installation and mounting conditions of the power tools during noise tests

*Addition:*

**Tappers** and **threaders** are suspended. The main axis of the tool shall be horizontal.

##### I.2.5 Operating conditions

*Addition:*

**Tappers** and **threaders** are tested at no-load.

The temperature requirements of 5.6 are not applicable.

#### I.3 Vibration

This clause of Part 1 is applicable except as follows:

##### I.3.3.2 Location of measurement

*Addition:*

Figure I.101 shows the positions for **tappers**. Figure I.102 shows the positions for **threaders**.

##### I.3.5.1 General

*Addition:*

For **battery** operated tools, the tests are conducted with the lightest **battery** in accordance with K.8.14.2 e) 2) of Part 1 that has sufficient capacity to operate the tool at no-load for at least 25 min.

##### I.3.5.3 Operating conditions

*Addition:*

**Tappers** and **threaders** are tested observing the conditions shown in Table I.101.


**Table I.101 – Operating conditions for tappers and threaders**

<b>Orientation</b>	<b>Tappers</b> and <b>threaders</b> are tested at no-load. The <b>tapper</b> is held vertically during the test. The <b>threader</b> is held horizontally during the test.
<b>Tool bit</b>	Tool bit of medium length and size.
<b>Grip force</b>	Hold the machine with normal gripping force, avoiding excessive gripping force.
<b>Test cycle</b>	One test cycle is given when the tool is switched on for no-load at maximum speed for more than 10 s and then switched off again. The measurement is conducted during 10 s within this period.
<p>NOTE 1 As it is difficult to measure load applications of <b>tappers</b> and <b>threaders</b> in laboratories and results have shown that the load has no influence on the vibration results, no-load has been chosen as operating condition.</p> <p>NOTE 2 For <b>threaders</b>, the handle adjacent to the gear box is needed to achieve a horizontal position, however it is not used during actual operation.</p>	


**I.3.6.2 Declaration of the vibration total value**

*Addition:*

The vibration total value  $a_h$  of the handle with the highest emission and the uncertainty  $K$  shall be declared.



**Figure I.101 – Position of transducers for tappers**



IEC

NOTE The handle adjacent to the gear box is only used for setting up the threading operation and is not used during tool operation.

**Figure I.102 – Position of transducers for threaders**

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV

## Annex K (normative)

### Battery tools and battery packs

#### K.1 Scope

*Addition:*

All clauses of this Part 2-9 apply unless otherwise specified in this annex.

#### K.11 Input and current

This clause is not applicable.

**K.12.2.1** This subclause is not applicable.

#### K.18 Abnormal operation

This clause is applicable except as follows:

**K.18.8** *Replacement of Table 4:*

**Table 4 – Required performance levels**

Type and purpose of SCF	Minimum performance level (PL)
<b>Power switch</b> – prevent unwanted switch-on for <b>tappers</b>	a
<b>Power switch</b> – prevent unwanted switch-on for <b>threaders</b>	a
<b>Power switch</b> – provide desired switch-off for <b>tappers</b>	a
<b>Power switch</b> – provide desired switch-off for <b>threaders</b>	c
Provide desired direction of rotation	Not an <b>SCF</b>
Any electronic control to pass the test of 18.3	Not an <b>SCF</b>
Any speed limiting device	Not an <b>SCF</b>
Prevent exceeding thermal limits as in Clause 18	a

## Bibliography

The bibliography of Part 1 is applicable.

---

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV

## CONTENTS

FOREWORD .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 General requirements .....	6
5 General conditions for the tests .....	6
6 Radiation, toxicity and similar hazards .....	7
7 Classification .....	7
8 Marking and instructions .....	7
9 Protection against access to live parts .....	8
10 Starting .....	8
11 Input and current .....	8
12 Heating .....	8
13 Resistance to heat and fire .....	9
14 Moisture resistance .....	9
15 Resistance to rusting .....	9
16 Overload protection of transformers and associated circuits .....	9
17 Endurance .....	9
18 Abnormal operation .....	9
19 Mechanical hazards .....	10
20 Mechanical strength .....	10
21 Construction .....	11
22 Internal wiring .....	11
23 Components .....	11
24 Supply connection and external flexible cords .....	11
25 Terminals for external conductors .....	11
26 Provision for earthing .....	11
27 Screws and connections .....	12
28 Creepage distances, clearances and distances through insulation .....	12
Annexes .....	14
Annex J (informative) Measurement of noise and vibration emissions .....	14
Annex K (normative) Battery tools and battery packs .....	17
Bibliography .....	18
Figure 101 – Threader with support device .....	12
Figure 102 – Set-up for testing the support device .....	13
Figure I.101 – Position of transducers for tappers .....	15
Figure I.102 – Position of transducers for threaders .....	16
Table 101 – Load torque .....	9
Table 4 – Required performance levels .....	10
Table I.101 – Operating conditions for tappers and threaders .....	15

Table 4 – Required performance levels ..... 17

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS,  
TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY –  
SAFETY –****Part 2-9: Particular requirements for hand-held tappers and threaders**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.**

**IEC 62841-2-9 edition 1.1 contains the first edition (2015-01) [documents 116/199/FDIS and 116/212/RVD], its corrigendum 1 (2015-10) and its amendment 1 (2025-02) [documents 116/861/FDIS and 116/876/RVD].**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

International Standard IEC 62841-2-9 has been prepared by IEC technical committee 116: Safety of motor-operated electric tools.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 2-9 is to be used in conjunction with the first edition of IEC 62841-1 (2014).

This Part 2-9 supplements or modifies the corresponding clauses in IEC 62841-1, so as to convert it into the IEC Standard: Particular requirements for hand-held tappers and threaders.

Where a particular subclause of Part 1 is not mentioned in this Part 2-9, that subclause applies as far as reasonable. Where this standard states “addition”, “modification” or “replacement”, the relevant text in Part 1 is to be adapted accordingly.

The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

The terms defined in Clause 3 are printed in **bold typeface**.

Subclauses, notes and figures which are additional to those in Part 1 are numbered starting from 101.

A list of all parts of the IEC 62841 series, under the general title: *Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – Safety*, can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 36 months from the date of publication.

# ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

## Part 2-9: Particular requirements for hand-held tappers and threaders

### 1 Scope

This clause of Part 1 is applicable, except as follows:

*Addition:*

This standard applies to hand-held **tappers** and **threaders**.

### 2 Normative references

This clause of Part 1 is applicable, except as follows:

*Addition:*

ISO 7-1:1994, *Pipe threads where pressure-tight joints are made on the threads – Part 1: Dimensions, tolerances and designation*

ISO 65:1981, *Carbon steel tubes suitable for screwing in accordance with ISO 7-1*

### 3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

*Addition:*

#### 3.101

##### **tapper**

tool intended for cutting internal screw threads

#### 3.102

##### **threader**

tool intended for cutting external threads

### 4 General requirements

This clause of Part 1 is applicable.

### 5 General conditions for the tests

This clause of Part 1 is applicable, except as follows:

**5.17 Addition:**

The mass of a **tapper/threader** includes the auxiliary handle, if any. Any support device as illustrated in Figure 101 for a **threader** is not regarded as part of the tool.

## 6 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.

## 7 Classification

This clause of Part 1 is applicable.

## 8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

**8.1 Addition:**

In addition the tool shall have the following marking:

- maximum diameter, in millimetres (for **tappers**) or in inches (for **threaders**), of the thread which can be cut.

NOTE According to the International System of Units, only SI units should be used. Nevertheless, some pipe diameters and threads are still specified in inches internationally.

For **tappers**, the diameter shall refer to a unified ISO thread to be cut into steel having a tensile strength of 390 N/mm<sup>2</sup> and a thickness of twice the thread diameter, unless otherwise indicated on the tool.

For **threaders**, the diameter shall refer to a taper style thread in accordance with ISO 7-1 to be cut on steel tubes in accordance with ISO 65, unless otherwise indicated on the tool.

**8.14.1 Addition:**

For **threaders**, the additional safety instructions as specified in 8.14.1.101 shall be given. This part may be printed separately from the “General Power Tool Safety Warnings”.

### 8.14.1.101 Threader safety warnings

- Always use the support device provided with the tool.** Loss of control during operation can result in personal injury.
- Keep sleeves and jackets buttoned while operating the tool. Do not reach across the tool or pipe.** Clothing can be caught by the pipe or the tool resulting in entanglement.
- Only one person must control the work process and tool operation.** Additional people involved in the process may result in unintended operation and personal injury.
- Keep floors dry and free of slippery materials such as oil.** Slippery floors invite accidents.

**8.14.2 a) Addition:**

101) for **threaders**: instructions for mounting and use of the support device.

**8.14.2 b) Addition:**

101) for **threaders**: instructions to always use the support device supplied with the tool;

102) for **threaders** with multiple gear box settings: information about which gear box setting is to be used for each pipe diameter.

## 9 Protection against access to live parts

This clause of Part 1 is applicable.

## 10 Starting

This clause of Part 1 is applicable.

## 11 Input and current

This clause of Part 1 is applicable, except as follows:

*Modification:*

For **threaders**, the requirements of this clause are replaced by the following:

The **rated input** or **rated current** shall be at least 100 % of the measured input or current applying the torque in Table 101.

*Compliance is checked by measuring the power input or current of the tool when stabilized while all circuits which can operate simultaneously are in operation.*

*For tools marked with one or more **rated voltages**, the test is made at each of the **rated voltages**. For tools marked with one or more **rated voltage ranges**, the test is made at both the upper and lower limits of the ranges. For tools with multiple gear box settings, the test is made at each specified gear box setting in accordance with 8.14.2 b). The highest value of input or current is applicable.*

## 12 Heating

This clause of Part 1 is applicable, except as follows:

### 12.2.1 Replacement:

**Tappers** are operated intermittently for 30 cycles or until thermal equilibrium is reached, whichever is achieved first, each cycle comprising a period of continuous operation of 30 s and a rest period of 90 s with the tool switched off, the tool being loaded during the periods of operation by means of a brake adjusted so as to attain **rated input** or **rated current**. The temperature rises are measured at the end of the last "on" period.

**Threaders** are operated for 30 s at load followed by 30 s no load and then switched off for a rest period of 60 s. This cycle is continued until thermal equilibrium is reached, or for 30 cycles, whichever is achieved first. The tool is loaded during the periods of operation by means of a brake adjusted to attain the torque specified in Table 101. The brake load may be ramped up to the specified torque over a period of time not to exceed 5 s. This ramp up time is added to the 30 s cycle at load. The temperature rises are measured at the end of the last load period.

The above test cycle may, at the manufacturer's option, be replaced by continuous operation of the tool until thermal equilibrium is reached.

NOTE Continuous operation is not typical for these tools and is regarded as a more severe test. Therefore, this is an option for the cycle test in order to simplify the testing.

**Table 101 – Load torque**

Maximum diameter of thread inch	Torque Nm
1	125
1,25	150
1,5	160
2	180

**12.5 Addition:**

For **threaders**, the temperature-rise limit specified for the external enclosure does not apply to the enclosure of the gear box. However, the above exemption does not apply to handles adjacent to the gear box.

**13 Resistance to heat and fire**

This clause of Part 1 is applicable.

**14 Moisture resistance**

This clause of Part 1 is applicable.

**15 Resistance to rusting**

This clause of Part 1 is applicable.

**16 Overload protection of transformers and associated circuits**

This clause of Part 1 is applicable.

**17 Endurance**

This clause of Part 1 is applicable.

**18 Abnormal operation**

This clause of Part 1 is applicable, except as follows:

**18.8 Replacement of Table 4:**

**Table 4 – Required performance levels**

Type and purpose of SCF	Minimum performance level (PL)
<b>Power switch</b> – prevent unwanted switch-on for <b>tappers</b>	a
<b>Power switch</b> – prevent unwanted switch-on for <b>threaders</b>	a
<b>Power switch</b> – provide desired switch-off for <b>tappers</b>	b
<b>Power switch</b> – provide desired switch-off for <b>threaders</b>	c
Provide desired direction of rotation	Not an <b>SCF</b>
Any electronic control to pass the test of 18.3	Not an <b>SCF</b>
Any speed limiting device	Not an <b>SCF</b>
Prevent exceeding thermal limits as in 18.4 and 18.5.3	a

## 19 Mechanical hazards

This clause of Part 1 is applicable, except as follows:

**19.6** This subclause is not applicable.

## 20 Mechanical strength

This clause of Part 1 is applicable, except as follows:

**20.5** This subclause is not applicable.

**20.101** The device to support the **threader** shall withstand the torque output generated by the tool while cutting a thread in either direction.

*Compliance is checked by the following test:*

*The tool is set with the largest die head in accordance with 8.1 on to a pipe as specified in 8.1. The point of contact with the support device and tool is determined. The support device is mounted in accordance with 8.14.2 a) so there is an 8 mm minimum clearance between the device and the point of contact. See Figure 102.*

*A thread is cut until one of the following occurs:*

- *the tool stalls;*
- *the thread is destroyed allowing the die head to continue rotating;*
- *the die head stops rotating due to failure of the tool or by means of a mechanical or electrical/electronic device.*

*As a result of the test, none of the following shall occur:*

- *ejection of parts from the tool or from the die head;*
- *rotation of the support device exceeding 30° or lateral movement exceeding 25 mm;*
- *cracked or broken parts of the support device, however bending is allowed.*

## 21 Construction

This clause of Part 1 is applicable, except as follows:

### 21.18.1.1 *Addition:*

**Threaders** are regarded as tools with a risk associated with continued locked-on operation.

21.18.1.2 This subclause is not applicable.

21.30 This subclause is not applicable.

21.32 This subclause is not applicable.

21.35 This subclause is not applicable.

21.101 **Threaders** shall be supplied with a device to support the tool while cutting a thread.

Figure 101 shows an example of a **threader** with a support device.

*Compliance is checked by inspection.*

## 22 Internal wiring

This clause of Part 1 is applicable.

## 23 Components

This clause of Part 1 is applicable, except as follows:

23.3 This subclause is not applicable.

## 24 Supply connection and external flexible cords

This clause of Part 1 is applicable, except as follows:

### 24.4 *Addition:*

If rubber insulated cables are used, they shall be polychloroprene or other equivalent synthetic elastomer sheathed cables (code designation 60245 IEC 57 or 60245 IEC 66).

## 25 Terminals for external conductors

This clause of Part 1 is applicable.

## 26 Provision for earthing


This clause of Part 1 is applicable.

## 27 Screws and connections

This clause of Part 1 is applicable.

## 28 Creepage distances, clearances and distances through insulation

This clause of Part 1 is applicable.



IEC

### Key

- 1 pipe
- 2 support device
- 3 threader

Figure 101 – Threader with support device

IECNORM.COM : Click to view the full PDF of IEC 62841-2-9:2015+AMD1:2025 CSV