

TECHNICAL REPORT

**Electrical installations in ships –
Part 370: Guidance on the selection of cables for telecommunication and data
transfer including radio-frequency cables**

IECNORM.COM : Click to view the full PDF of IEC TR 60092-370:2019



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IECNORM.COM : Click to view the full text of IEC TC 37:2019

TECHNICAL REPORT

**Electrical installations in ships –
Part 370: Guidance on the selection of cables for telecommunication and data
transfer including radio-frequency cables**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.060.20; 47.020.60

ISBN 978-2-8322-7596-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Selection of cables	6
5 Fundamental considerations	7
6 Constructional considerations	7
6.1 Selection of conductor	7
6.2 Selection of insulation	7
6.3 Cable elements	7
6.4 Selection of screen, core screen or shield	8
6.5 Selection of outer sheath	8
6.6 Selection of metallic sheath (covering), braid or armour	8
7 Marking	8
8 Guidance on the selection of appropriate tests	9
9 Guide to use	9
9.1 Purpose	9
9.2 General	9
9.3 Voltage rating	10
9.3.1 Data and telecommunication cables	10
9.3.2 High-frequency radio communications cables	10
9.4 Current ratings	10
9.5 Thermal considerations	10
9.6 Size of conductors	10
9.7 Radius of bend	11
9.8 Tensile stress	11
9.9 Compression	11
9.10 Mechanical damage	11
9.11 Electromagnetic interference	12
9.12 Terminations	12
9.13 Joints	12
10 Performance in a fire	12
Annex A (informative) Table of tests	14
Bibliography	17
Table 1 – Classification of cables by frequency range	9
Table A.1 – Table of tests for cables according to the standard IEC 60092-370	14

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRICAL INSTALLATIONS IN SHIPS –**Part 370: Guidance on the selection of cables for telecommunication
and data transfer including radio-frequency cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 60092-370, which is a Technical Report, has been prepared by subcommittee 18A: Electric cables for ships and mobile and fixed offshore units, of IEC technical committee 18: Electrical installations of ships and of mobile and fixed offshore units.

This second edition cancels and replaces the first edition published in 2009. This edition constitutes a technical revision.

This edition includes the following significant technical change with respect to the previous edition: 30 V AC was added in voltage rating for data cables.

The text of this Technical Report is based on the following documents:

Draft TR	Report on voting
18A/421/DTR	18A/422/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60092 series, published under the general title *Electrical installations in ships*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC TR 60092-370:2019

INTRODUCTION

IEC 60092 (all parts) concerns electrical installations in sea-going ships, and fixed and mobile offshore units, incorporating good practice and co-ordinating as far as possible existing rules.

These standards form a code of practical interpretation and amplification of the requirements of the International Convention on Safety of Life at Sea, a guide for future regulations which may be prepared and a statement of practice for use by shipowners, shipbuilders, mobile and fixed offshore units owners and builders and appropriate organisations.

Cables selected for installation on board ships and on offshore installations are usually installed and are expected to operate in much harsher environments than equivalent land based types. The risk of mechanical abuse during installation, physical dislocation due to tension and bending allied with extremes of temperature are examples of the conditions to which these cables may be subject. If faults occur unlike onshore installations, trained experienced technicians may not always be readily available to affect a repair or replacement.

IECNORM.COM : Click to view the full PDF of IEC TR 60092-370:2019

ELECTRICAL INSTALLATIONS IN SHIPS –

Part 370: Guidance on the selection of cables for telecommunication and data transfer including radio-frequency cables

1 Scope

This part of IEC 60092, which is a Technical Report, gives guidance and lays down the basic recommendations for the selection and installation of shipboard and offshore unit cables intended for electrical systems used in both essential and non-essential analogue or digital signal communication, transmission and control networks, including types suitable for high-frequency signals (i.e. signals with a frequency of more than 10^5 Hz). These cables are not suitable for direct connection to low impedance supplies. Where such cables are required, attention is drawn to IEC 60092-353.

Cables intended to have limited circuit integrity (fire resistance) when affected by fire are not covered by this document.

Fibre optical cables are not included.

Sub-sea or umbilical cables are not included.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60092-350, *Electrical installations in ships – Part 350: General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60092-350 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Selection of cables

Cables with physical and electrical characteristics in accordance with IEC 60092 (all parts) are recommended for use in the marine environment.

Cables constructed in accordance with the following standards are acceptable provided that due consideration has been given to their use in a marine environment: IEC 60189-1, IEC 60189-2, IEC 60189-3, and IEC 60096-0-1.

5 Fundamental considerations

The choice of materials and cable construction should be suitable for the intended application and installation of the cable.

The high level of electrical performance associated with many modern cables is only achieved by the accurate, consistent positioning of the various components within the cable. Careless or excess tension, compression or bending can alter this relationship. This may then have significant detrimental effects upon the fundamental performance of the cable at high data rates.

Similarly, these high levels of electrical performance can usually only be achieved by the use of polymers and insulation systems that may not have the same reaction to fire characteristics as the more traditional materials used in other marine cables. In recognition of this, careful consideration should be given to the method of installation to select that most appropriate to the particular application (see also Clause 8).

6 Constructional considerations

6.1 Selection of conductor

Only circular copper conductors, either plain or metal coated, or copper covered steel, are recommended for use in a marine environment. Stranded conductors are recommended for general use. Where the applicable product standard specifies solid conductors, consideration should be given to the possible effects of vibration (due to the movement of the ship or installation) or movement (due to motion of the ship or installation).

The properties of copper conductors should be in accordance with IEC 60228. Joints in solid conductors or complete stranded conductors are not permitted; however, joints in individual strands are allowed.

When cables are subject to continuous flexing, the advice of the manufacture should be sought.

6.2 Selection of insulation

The range of materials for use as conductor insulation should, where possible, be selected from those listed in IEC 60092-360 or as given in IEC 60096-0-1 and IEC 61156-5-1. For cables operating at the higher frequencies, the insulation may be solid, cellular or a foam skin composite. The rated operating temperature of the insulating material should be at least 10 °C higher than the maximum ambient temperature likely to exist, or to be produced, in the space where the cable is installed.

The insulation should be continuous, having a thickness as uniform as possible. The insulation should be applied to fit closely to the conductor.

6.3 Cable elements

The cores within each pair, triple, or quad should be clearly identified by colour or number as given in the applicable cable standard. The identification used should be durable and legible.

The choice of the maximum average length of lay in the finished cable should be selected with respect to the specified crosstalk requirements, handling performance and the pair or quad integrity.

6.4 Selection of screen, core screen or shield

If a screen is required, it may consist of the following:

- a) a metallic laminated tape bonded to polyester and a drain wire in direct contact with the metallic side of the tape;
- a) plain or metal coated copper braid;
- b) a metallic laminated tape bonded to polyester and a drain wire in direct contact with the metallic side of the tape with a plain or metal coated copper braid.

The construction of the screen, core screen or shield should be as listed in IEC 60092-350 or the applicable cable standard. Care should be taken when putting dissimilar metals in contact with each other. Coatings or other methods of protection may be necessary to prevent galvanic interaction often encountered in the marine environment.

6.5 Selection of outer sheath

The range of materials for use as protective sheath should, where possible, be selected from those listed in IEC 60092-360, which have been proven by experience to be suitable for use in the marine environment. Materials listed in IEC 60096-0-1 and IEC 61156-1 may also be considered; the material chosen should meet the requirements of this document.

The material selected should be compatible with the cable components with which it is in contact and compatible with the intended environment and operating temperature of the cable.

In instances where the construction of a cable does not conform with a standard from IEC 60092 (all parts), it should be ensured that the material used as the protective sheath has adequate mechanical strength in respect of the mechanical hazards to which it may be subjected during installation and service. The potential for corrosion, of underlying layers, encountered in the marine environment should also be considered. Attention is drawn to the list of permitted protective coverings given in IEC 60092-350.

Due consideration should be given to fluid resistance for cables installed where water condensation or harmful vapours (including oil vapour) may be present. In this instance, the cables should meet the appropriate fluid resistance requirements of IEC 60092-360.

Also, consideration should be given to the fire performance characteristics given in Clause 10.

The minimum thickness of sheath considered as being acceptable for cables for installation on board a ship or offshore installation is 0,7 mm.

6.6 Selection of metallic sheath (covering), braid or armour

The construction of the metal braid armour should be in accordance with IEC 60092-350. The type of metal braid armour should be carefully selected by the user in respect of not only the mechanical hazards but also the potential for corrosion encountered in the marine environment. Care should be taken when putting dissimilar metals in contact with each other. Coatings or other methods of protection may be necessary to prevent galvanic interaction often encountered in the marine environment.

7 Marking

Cables should be provided with a continuous indication of origin (manufacturers name or trade mark), by one of the following methods:

- a) printing, indenting or embossing on the outer sheath;
- b) a printed tape within the cable;

- c) the inclusion of identification threads within the cable;
- d) printing on the insulation of at least one core.

The marking should be durable and legible.

The spacings and dimensions of the indication of origin should be as given in the applicable product standard.

8 Guidance on the selection of appropriate tests

Unless otherwise specified in the applicable product standard, tests should be made at an ambient temperature of $(20 \pm 15) ^\circ\text{C}$.

This document defines, by the frequency range in the intended application, seven classes of cable (Table 1) and, in Annex A, gives guidance in the selection of the appropriate tests to be applied, related to each class.

Table 1 – Classification of cables by frequency range

Cable type	Frequency range
1	$f_{\text{max}} < 100 \text{ kHz}$
2	$100 \text{ kHz} < f < 1 \text{ MHz}$
3	$1 \text{ MHz} < f < 16 \text{ MHz}$
4	$16 \text{ MHz} < f < 125 \text{ MHz}$
5	$125 \text{ MHz} < f < 250 \text{ MHz}$
6	$250 \text{ MHz} < f < 600 \text{ MHz}$
7	$250 \text{ Hz} < f < 1\,000 \text{ MHz}$
NOTE All cables are backwards compatible.	

9 Guide to use

9.1 Purpose

The aim of Clause 9 is to inform users of characteristics and limitations of electric cables and thereby to minimise misuse.

It is assumed that the design of installation and the specification, purchase and installation of cables in accordance with this document is entrusted to suitable skilled and competent people.

In case of doubt as to the suitability of cables covered by this document for a particular use, further specific information should be obtained from the manufacturer.

9.2 General

All cables should be stored in a suitable place until required. Consideration should be given to security and environmental conditions.

Any protective packaging should not be removed until the cable is to be installed.

The ends of cables should always remain sealed during storage and installation to prevent the ingress of water and other contaminants.

9.3 Voltage rating

9.3.1 Data and telecommunication cables

All cables covered by this document should be subject to electrical tests applicable to their maximum rated voltage. Recommended maximum rated voltages for data and telecommunication cables are:

- 30 V AC;
- 60 V AC;
- 250 V AC.

The rated voltage of any cable should not be lower than the nominal voltage of the circuit for which it is used.

NOTE These cables are not intended to be used for power supply.

9.3.2 High-frequency radio communications cables

The voltage rating of the cable should not be lower than the nominal voltage of the radio communication system in which it will be used.

9.4 Current ratings

The cables covered by this document are only recommended for use in circuits carrying analogue and digital signals.

Where high power co-axial feeder cables are to be used, advice from the cable manufacturer should be sought.

9.5 Thermal considerations

It is recommended that the rated operating temperature of the cable selected shall be at least 10 K higher than the maximum ambient temperature likely to exist, or to be produced, in the space where the cable is installed.

These cables should not normally be run in groups or bundles containing power cables operating at or near their maximum operating temperature. Where this is unavoidable, then the operating temperature should be based upon the lowest maximum operating temperature of any cable in the group or bundle.

All insulation and sheathing materials used for cables become progressively stiffer as their temperature is lowered below the normal ambient temperature to the point where they become brittle. This should be carefully considered when comparing the minimum operating temperature of the cable with the intended environment and application.

The cable should be acclimatised at the recommended environmental conditions before installation.

9.6 Size of conductors

The selection of the size of each conductor should not be based upon the attenuation or the electrical characteristics of the circuit alone. Account should be taken of the mechanical strength, the method, as well as the route, upon which the cable is to be installed. The cable should be of sufficient size as to mitigate mechanical damage, and impairment of its electrical integrity and characteristics, during installation and subsequent operation in the conditions encountered in the marine environment.

9.7 Radius of bend

The internal radius of bend for the installation of all cables should be chosen according to the type of cable as recommended by the manufacturer such that the electrical integrity and characteristics of the cable are not impaired due to disassociation of components within the cable.

The minimum bending radius used should never be less than what is recommended by the manufacturer.

Particular care should be taken when dressing cable, inserting cable into conduit, bending around corners in conduit or at the transition from vertical to horizontal tray to ensure that the cable is never bent below the recommended minimum bending radius.

Cable runs should be selected to keep the number of bends to a minimum.

Cables with class 5 conductors are not intended for flexible applications.

9.8 Tensile stress

In assessing the risk of mechanical damage to cables, account should be taken of any mechanical strains likely to be imposed during the normal process of installation of cables.

Cables should be so installed that the tensile stress applied to them, either by reason of their own weight or for any other reason, is minimised. Excessive tension can cause disassociation of components within the cable resulting in the impairment of the electrical integrity and characteristics of the cable. These precautions are particularly important for cables of small cross-section and for cables on vertical runs or in vertical conduit or ducting.

The distances between supports should be as recommended by the cable manufacturer and chosen to avoid excessive tension due to sagging in the cable. Careful consideration should be given to cable runs along weather decks, when the cable run is arranged so that the cables can be subjected to forces by water washing over the deck.

The mechanical strength of conductors should be sufficient for the method of installation and working conditions.

9.9 Compression

Fixings and supports used should have a surface area sufficiently large and be shaped so that the cables remain tight without their coverings being damaged. Care should be exercised to ensure that the forces applied by these fixings do not cause impairment of the electrical integrity and characteristics of the cable due to disassociation of components within the cable. Installations should be such that tensions in cables and cinching of bundles shall be minimized. The cable sheath should not be deformed.

Where individual stuffing glands or boxes containing several cables are used to penetrate bulkheads or decks, care needs to be taken to avoid excessive clamping or compressive forces causing impairment of the electrical integrity and characteristics of the cable due to disassociation of components within the cable. Installations shall be such that tensions in cables and cinching of bundles are minimized. The cable sheath should not be deformed.

9.10 Mechanical damage

To avoid the risk of mechanical damage, data, telecommunication and high-frequency radio communications cables should not normally be installed within the same conduit or trunking as cables of other services. Where this is impractical, they should be separated by a strong, rigid and continuous partition.

9.11 Electromagnetic interference

In order to avoid as much as possible the effects of unwanted electromagnetic interference, attention should be given to IEC 60533. This might be of particular importance for the installation of cables in vicinity of radio equipment and for the installation of cables belonging to sensitive electronic control and monitoring systems.

Careful consideration shall be given to the earthing of metal coverings of cables to ensure that safety of personnel and equipment is achieved as well as meeting the requirements of the electrical characteristics of the circuit.

As general guidance, earthing of the metal covering at one end only will be effective against static electricity, spikes and discharges. However, the cable may then act as an antenna. Earthing of the metal covering at both ends will be effective against magnetic fields. However, ground loops or circulating currents may be set up in the cable.

The metal covering of cables may be earthed by means of glands intended for the purpose and so designed as to ensure an effective earth connection.

The electrical continuity of all metal coverings throughout the length of the cables, particularly at joints and tapings, should be ensured.

Metal casings, pipes and conduits or trunking should be effectively earthed.

9.12 Terminations

Only approved proprietary terminations should be used when terminating essential, and non-essential, analogue or digital signal, communication, transmission and control cables. The length of sheath and protection removed should be minimised to prevent disassociation of the components within the cable.

9.13 Joints

Cable runs should not normally include joints. Where the use of joints is unavoidable, the advice of the cable manufacturer should be sought.

10 Performance in a fire

The high-level signal transmission characteristics achieved by some types of cables rely upon the use of polymers and insulation systems with reaction to fire properties that may not match those of the more traditional materials listed in IEC 60092-360, especially where cables are installed in large bunches. This problem has been recognised and there are now several possible solutions to it. Careful consideration should be given to each installation to select the most appropriate method. Examples of these solutions relate to the installation methods employed as well as material types. Typical methods are:

- a) Installation techniques:
 - the use of additional fire stops;
 - additional segregation.
- b) General housekeeping:
 - removal of redundant obsolete cables.
- c) Materials and related matters:
 - the use of intumescent coatings.

NOTE 1 The above examples are neither exhaustive, nor show any particular order of preference.

Care should be taken with the use of methods in c) as some materials, if they burn, release significant quantities of dense smoke, which may obscure an escape route, and/or gases that can be corrosive to equipment or harmful to personnel.

NOTE 2 For the use of fire stops, see Annex C of IEC 60092-352:2005.

Notwithstanding the foregoing, all cables should meet the requirements for flame as given in:

- IEC 60332-1-1 and IEC 60332-1-2, and
- IEC 60332-3-25.

The cables should be tested in a touching configuration.

NOTE 3 If a cable or an insulated wire meets the requirements of IEC 60332-1-2, it cannot be assumed that a bunch of similar cables or insulated wires will behave in a similar manner. The flame spread performance of bunched cables is assessed by the requirements of IEC 60332-3-25. This performance requirement has been chosen to best reflect the installation conditions generally observed on board ships. Experience has shown that the test for the flame spread of cables installed vertically is adequate for horizontal installations, all other parameters being generally the same.

For systems intended to maintain electrical circuit integrity under fire conditions, the selection of cable should only be made after consultation with the appropriate approval and regulatory authority.

Requirements for smoke emission and acid gas evolution should be considered where applicable and when the cables are evaluated in accordance with the test methods cited in the IEC 60092-350.

IECNORM.COM : Click to view the full PDF of IEC TR 60092-370:2019

Annex A (informative)

Table of tests

Table A.1 shows the tests for cables according to this document.

Table A.1 – Table of tests for cables according to this document

Test	Test basis IEC 61156-1:2007 and IEC 61156-1:2007/ AMD1:2009	Requirements	Applicable to cable classification	T	S	R
		General properties				
Visual inspection		Material free of cracks, splits, irregularities, foreign material, colour code and marking	1,2,3,4,5,6	X	X	X
Dimensions		Outer sheath thickness	1,2,3,4,5,6	X		X
		Electrical properties, low-frequency and DC				
Conductor loop resistance	6.2.1	The maximum value shall be $\leq 19 \Omega/100 \text{ m}$	1,2,3,4,5,6	X	X	X
Conductor resistance unbalance	6.2.2	$\leq 2 \%$	3,4,5,6	X	X	X
Dielectric strength conductor/conductor and conductor/screen	6.2.3	1,0 kV DC or 0,7 kV AC for 1 min or 2,5 kV DC or 1,7 kV AC for 2 s	1,2,3,4,5,6	X	X	X
Insulation resistance	6.2.4	$\geq 500 \text{ M}\Omega\cdot\text{km}$ using 100 V to 500 V test voltage	1,2,3,4,5,6	X	X	X
Mutual capacitance	6.2.5	Measure and record in the test report	1			
Capacitance unbalance to earth	6.2.6	$\leq 1 \text{ 600 pF/km}$	2,3,4,5,6	X	X	X
		Electrical properties, high frequency				
Velocity of propagation	6.3.1	Phase delay $\leq 534 + 36 / \sqrt{f}$ ns/100 m, $1 \text{ MHz} \leq f \leq 600 \text{ MHz}$	2,3,4,5,6	X	X	
Propagation delay difference (skew)	IEC 61156-1	$\leq 45 \text{ ns/100 m}$ at 100 MHz $\leq 25 \text{ ns/100 m}$ at 100 MHz	3,4,5 6	X X	X X	
Longitudinal attenuation	6.3.3	$\alpha \leq 1,910 \text{ 8 } \sqrt{f} + 0,022 \text{ 2 } f + 0,2 / \sqrt{f}$, $1 \text{ MHz} \leq f \leq 100 \text{ MHz}$	2,3,4	X	X	X
		$\alpha \leq 1,82 \sqrt{f} + 0,016 \text{ 9 } f + 0,25 / \sqrt{f}$, $1 \text{ MHz} \leq f \leq 250 \text{ MHz}$	5	X	X	X
		$\alpha \leq 1,75 \sqrt{f} + 0,01 f + 0,2 / \sqrt{f}$, $1 \text{ MHz} \leq f \leq 600 \text{ MHz}$	6	X	X	X
Longitudinal attenuation	6.3.3	$\alpha \leq 1,5 (1,910 \text{ 8 } \sqrt{f} + 0,022 \text{ 2 } f + 0,2 / \sqrt{f})$, $1 \text{ MHz} \leq f \leq 100 \text{ MHz}$	2,3,4	X	X	X
		$\alpha \leq 1,5 (1,82 \sqrt{f} + 0,016 \text{ 9 } f + 0,25 / \sqrt{f})$, $1 \text{ MHz} \leq f \leq 250 \text{ MHz}$	5	X	X	X
		$\alpha \leq 1,5 (1,75 \sqrt{f} + 0,01 f + 0,2 / \sqrt{f})$, $100 \text{ MHz} \leq f \leq 600 \text{ MHz}$	6	X	X	X
Near-end crosstalk (NEXT)	6.3.5	$\geq 4,0 \text{ MHz} \geq f < 125,0 \text{ MHz}$, $65,3 - 15 \log f$	2,3,4	X	X	X

Test	Test basis IEC 61156-1:2007 and IEC 61156-1:2007/ AMD1:2009	Requirements	Applicable to cable classification	T	S	R
		$\geq 4,0 \text{ MHz} \geq f < 250,0 \text{ MHz}$, $75,3 - 15 \log f$	5	X	X	X
		$\geq 80,01 \text{ MHz} \geq f < 31,25 \text{ MHz}$, $80 - 15 \log f / 31,25 \text{ MHz} \leq f \leq$ 600 MHz	6	X	X	X
Power sum near-end crosstalk (PSNEXT)	IEC 61156-1	$\geq 4,0 \text{ MHz} \geq f < 125,0 \text{ MHz}$, $62,3 - 15 \log f$	2,3,4	X	X	X
		$\geq 4,0 \text{ MHz} \geq f < 250,0 \text{ MHz}$, $72,3 - 15 \log f$	5	X	X	X
		$\geq 77,01 \text{ MHz} \leq f < 31,25 \text{ MHz}$, $77,0 - 15 \log f / 31,25 \text{ MHz} \leq f$ $\leq 600 \text{ MHz}$	6	X	X	X
Equal level far-end crosstalk (ELFEXT)	IEC 61156-1	$\geq 4,0 \text{ MHz} \geq f < 125,0 \text{ MHz}$, $62,3 - 20 \log f$	4	X	X	
		$\geq 4,0 \text{ MHz} \geq f < 250,0 \text{ MHz}$, $72,3 - 20 \log f$	5	X	X	
		$\geq 80,01 \text{ MHz} \leq f \geq 4 \text{ MHz}$, $94 - 20 \log f$, $4 \text{ MHz} f \leq 600 \text{ MHz}$, values ref. to 100 m	6	X	X	
Power sum equal level far-end crosstalk (PSELFEXT)	IEC 61156-1	$\geq 4,0 \text{ MHz} \geq f < 100 \text{ MHz}$, $61,0 - 20 \log f$	4	X	X	
		$\geq 4,0 \text{ MHz} \geq f < 250,0 \text{ MHz}$, $65,0 - 20 \log f$	5	X	X	
		$\geq 94 - 20 \log(f)$, $4 \text{ MHz} < f \leq 600 \text{ MHz}$ (77 dB max.), values ref. to 100 m	6	X	X	
Mean characteristic impedance	6.3.10	$100 \Omega \pm 5 \Omega$, $120 \Omega \pm 5 \Omega$, at 100 MHz; f.f.s	2,3,4,5,6	X	X	X
Return loss	IEC 61156-1	$\geq 20 + 5 \log(f)$, $4 \text{ MHz} \leq f \leq 10 \text{ MHz}$; 25 dB, $10 \text{ MHz} \leq f < 20 \text{ MHz}$; $25 - 7 \log(f/20)$, $20 \text{ MHz} < f \leq 100$	3,4	X	X	X
		$\geq 20 + 5 \log(f)$, $4 \text{ MHz} \leq f \leq 10 \text{ MHz}$; 25 dB, $10 \text{ MHz} \leq f < 20 \text{ MHz}$; $25 - 7 \log(f/20)$, $20 \text{ MHz} < f \leq 250$	5	X	X	X
		$\geq 20 + 5 \log(f)$, $4 \text{ MHz} \leq f \leq 10 \text{ MHz}$; 25 dB, $10 \text{ MHz} \leq f < 20 \text{ MHz}$; $25 - 7 \log(f/20)$, $20 \text{ MHz} < f \leq$ 250 MHz ; 17,3 dB, $250 \text{ MHz} < f \leq 600 \text{ MHz}$; f.f.s	6	X	X	X
Near end unbalance attenuation	IEC 61156-1	$\geq 40 - 10 \log(f) \text{ dB}$, $1 \text{ MHz} \leq f \leq$ 600 MHz ; f.f.s	2,3,4	X	X	
Coupling attenuation	IEC 61156-1	$\geq 80 \text{ dB}$, $30 \text{ MHz} \leq f \leq 100 \text{ MHz}$; f.f.s $\geq 80 - 20 \log(f/100) \text{ dB}$, $100 \text{ MHz} < f \leq 1\,000 \text{ MHz}$; f.f.s	4,5,6	X	X	
Transfer impedance	6.2.7	$\leq 15 \text{ m}\Omega/\text{m}$ at 1 MHz; $\leq 10 \text{ m}\Omega/\text{m}$ at 10 MHz; $\leq 30 \text{ m}\Omega/\text{m}$ at 30 MHz	1,2,3,4,5,6	X	X	
Screening attenuation	IEC 61156-1	$\geq 55 \text{ dB}$, $30 \text{ MHz} \leq f \leq 600 \text{ MHz}$; f.f.s Note: measured to 1 GHz	1,2,3,4,5,6	X	X	
		Tests to assess installation characteristics				