

TECHNICAL REPORT



Graphical symbols for use on equipment – Graphical symbols for multimedia equipment – Current practice

IECNORM.COM : Click to view the full PDF of IEC TR 62964:2015



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IECNORM.COM : Click to view the full text of IEC 62984:2015

TECHNICAL REPORT



Graphical symbols for use on equipment – Graphical symbols for multimedia equipment – Current practice

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 01.080.20; 33.160.60

ISBN 978-2-8322-2644-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Current practice.....	7
4.1 General.....	7
4.2 Current practice for control	7
4.3 Current practice for indication	10
Bibliography.....	14
Table 1 – Current practice for controls	8
Table 2 – Current practice for indication	11

IECNORM.COM : Click to view the full PDF of IEC TR 62964:2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**GRAPHICAL SYMBOLS FOR USE ON EQUIPMENT –
GRAPHICAL SYMBOLS FOR MULTIMEDIA EQUIPMENT –
CURRENT PRACTICE**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62964, which is a Technical Report, has been prepared by subcommittee 3C: Graphical symbols for use on equipment, of IEC technical committee 3: Information structures and elements, identification and marking principles, documentation and graphical symbols.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
3C/1953/DTR	3C/2006/RVC

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this Technical Report, the following type is used:

– *terms defined in Clause 3: in italic type*

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

IECNORM.COM : Click to view the full PDF of IEC TR 62964:2015

INTRODUCTION

The first edition of IEC 60417, *Graphical symbols for use on equipment*, was published in 1973. Since then the publication has been maintained and updated continuously, mainly by adding new graphical symbols in order to meet the requirements of technical committees and subcommittees within the IEC as well as ISO/IEC JTC 1 together with industries.

This Technical Report thus includes classical graphical symbols targeted to specific application areas as well as basic graphical symbols for general application.

In the era of information communication technology (ICT), new graphical symbols for use on such equipment as multimedia equipment have been in strong demand for standardization. These graphical symbols are not only printed, engraved, embossed, or moulded on the equipment, but also used on screens and displays. In the latter case, the appearance of a graphical symbol is dynamically changed to indicate a state of the equipment.

This Technical Report intends to highlight current tendency and practice of using graphical symbols for use on equipment.

IECNORM.COM : Click to view the full PDF of IEC TR 62964:2015

GRAPHICAL SYMBOLS FOR USE ON EQUIPMENT – GRAPHICAL SYMBOLS FOR MULTIMEDIA EQUIPMENT – CURRENT PRACTICE

1 Scope

This Technical Report provides the result of a study of some of the *graphical symbols* for use on *equipment* standardized in IEC 60417 being primarily intended to:

- identify the *equipment* or a part of the *equipment* (e.g. a control or display);
- indicate a functional state (e.g. on, off, alarm);
- designate connections (e.g. terminals, filling points for materials);
- provide information on packaging (e.g. identification of contents, instructions for handling);
- provide instruction for the operation of the *equipment* (e.g. limitations of use);

in the focus of contemporary use of *graphical symbols* for use on multimedia *equipment*, and new possible meanings to be envisaged as well as new *graphical symbols* not yet standardized in IEC 60417.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

None.

3 Terms and definitions

For the purposes of this document the following terms and definitions apply.

3.1

equipment

associated assemblies intended to achieve a defined final objective

[SOURCE: IEC 80416-1:2008, 3.3]

3.2

graphical symbol

visually perceptible figure with a particular meaning used to transmit information independently of language

[SOURCE: IEC 80416-1:2008, 3.4]

3.3

glyph

recognizable abstract graphic symbol which is independent of any specific design

[SOURCE: ISO/IEC 9541-1:2012, 3.12]

3.4

glyph image

image of a *glyph*, as obtained from a *glyph* representation displayed on a presentation surface

[SOURCE: ISO/IEC 9541-1:2012, 3.15]

3.5

icon

graphical symbol presented on a screen or display

Note 1 to entry: Icons can be static, interactive and change as the result of user input or dynamic and change as the result of *equipment* status.

[SOURCE: IEC 62648:2012, 3.11]

4 Current practice

4.1 General

One of the important expectation and function of the *graphical symbols* in IEC 60417 is to serve as a pool of standardized *graphical symbols* for use on *equipment* to be used, in accordance with the provisions given in IEC 80416-3:2002 and IEC 80416-3:2002/AMD1:2011, 4.4, in IEC publications following the rules given in ISO/IEC Directives, Part 2:2011, 6.6.5.6. The actual applications and use of such *graphical symbols* include some modifications to fit specific purposes, which are allowed in accordance with the provisions given in IEC 80416-3:2002 and IEC 80416-3:2002/AMD1:2011, Clause 6.

To accommodate any difficulties to follow the rules, a set of procedures which constitute a compromise are given in IEC 62648, in agreement with IEC Guide 108.

In addition, as a result of quickly changing demand in industries such as digital cameras, multimedia, ICT and mobile equipment, there are new *graphical symbols* not yet standardized in IEC 60417.

This Technical Report classifies some of these *graphical symbols* including *icons* and *glyph images* into two categories:

- a) *Graphical symbols* for control
- b) *Graphical symbols* for indication





Some of the graphical representations shown on the right-hand columns of Table 1 and Table 2 are state of the art candidates for future standardization in IEC 60417.




4.2 Current practice for control

Graphical symbols to identify controls of equipment in general are important and many *graphical symbols* have been standardized in IEC 60417 for the purpose of different categories of equipment.

Subclause 4.2 highlights the result of study on current practice of *graphical symbols* to identify the *equipment* or a part of *equipment* in the field of multimedia technology. Table 1 shows such *graphical symbols* for use on multimedia *equipment* to trigger one of the functionalities and to change one function to another, as non-exhaustive examples.

Table 1 – Current practice for controls

Standardized graphical symbols	State of the art (examples)
<p>IEC 60417-5022 Movement in one direction</p>  <p>To indicate that a control, or an object by means of a control, can be moved in the indicated direction.</p> <p>NOTE Only the linear version is given, since the radius of the arrow of the curved version depends on the diameter of the control concerned. The curved version is shown in ISO 7000-0004.</p> <p>IEC 60417-5107A Normal run; normal speed</p>  <p>To identify the switch or switch position by means of which a normal run (e.g. of tape) is started in the indicated direction.</p> <p>NOTE In the orientation shown, the symbol means "normal run, forward". If shown reversed, the symbol means "normal run, backward".</p> <p>IEC 60417-5107B</p>  <p>IEC 60417-5023 Movement in both directions</p>  <p>To indicate that a control or an object, by means of a control, can be moved in both the indicated directions.</p> <p>NOTE Only the linear version is given, since the radius of the arrow of the curved version depends on the diameter of the control concerned. The curved version is shown in ISO 7000-0005.</p>	<p>IEC 80416-3, Examples of allowable modification</p>  <p>(a) IEC 60417-5964 (2005-06): X-ray source, longitudinal movement</p> <p>(b) IEC 60417-5964 applied with closed arrow heads</p> <p>(c) IEC 60417-5964 applied with filled arrows and no arrow shafts</p> <p>Figure 11 – Examples of arrows</p>
<p>ISO 7000-0493 Co-ordinate tracing</p>  <p>To identify the action of tracing in a co-ordinate plane during welding or thermal cutting, or to indicate a <u>reference to movements in four directions</u> (all directions in a plane).</p>	<p>ISO/IEC DIS 17549-2 Menu navigation</p>  <p>To identify the control for navigation in four directions; left, right, up and down.</p> <p>NOTE Graphical appearances are the combination of 5107B (top), the combination of IEC 60417-5107A with the tail shortened (middle) and the combination of the arrow head only of IEC 60417-5022 (bottom).</p>

Standardized graphical symbols		State of the art (examples)	
<p>IEC 60417-5025</p>  <p>Effect or action away from a reference point</p> <p>To indicate the direction of a certain effect or action away from a real or imaginary reference point or mark, which is realized by means of the control marked with this symbol.</p>		 <p>Skip; skip, short</p> <p>To identify the control for or the indicator of the function to skip a part of data, e.g. video data, corresponding to a specific time duration.</p> <p>NOTE See also IEC 60417-5125B.</p>	
<p>ISO 7000-0936</p>  <p>Movement in arrow direction with skip of a stop</p> <p>To identify the control for a movement in the arrow direction and to skip a stop where there would normally be one.</p>			
<p>ISO 7000-0933</p>  <p>Movement from a limit in arrow direction with skip of a stop</p> <p>To identify the control for a movement from a determined point in the arrow direction and to skip a stop where there would normally be one.</p>			
<p>IEC 60417-5815</p>  <p>Next image series</p> <p>To identify the control or the indicator to select the next series of images to be displayed on the screen.</p> <p>NOTE If the first image of the series is to be displayed, then this may be emphasized by hatching the representation of this image in the graphical symbol.</p>		 <p>Slide show</p> <p>To identify the control for or the indicator of automatic visualization of the data, e.g. video and slide data, as a slide show.</p>	
<p>IEC 60417-5471</p>  <p>Frame by frame, general</p> <p>To identify the control to operate in a frame by frame mode, i.e. for still pictures which are viewed individually.</p> <p>NOTE 1 The triangle may be filled in.</p> <p>NOTE 2 On video equipment, symbol 5471-1 may be used.</p>			
<p>ISO 7000-1123</p>  <p>Cine radiographic exposure</p> <p>To indicate a reference to the operating mode for cine radiographic exposure.</p>		 <p>Movie; cinema</p> <p>To identify the control to start moving pictures and to indicate the link to them.</p>	
<p>IEC 60417-5464</p>  <p>Satellite reception mode, general</p> <p>On telecommunications receivers.</p> <p>To identify the control which allows the equipment to receive satellite broadcasting transmissions.</p>		<p>ISO/IEC 10646 (3)</p>  <p>SATELLITE ANTENNA UCS: 1F4E1 = position indicator, news</p>  <p>Global positioning system; GPS</p> <p>To identify the indicator of global positioning system (GPS) function.</p>	




Standardized graphical symbols		State of the art (examples)	
<p>IEC 60417-5792</p>  <p>Enlargement of region of interest</p> <p>To identify the control or the indicator to enlarge the region of interest of the displayed image (zoom).</p> <p>NOTE 1 The curved line representing a light reflection may be omitted.</p> <p>NOTE 2 To indicate "increase enlargement" or "reduce enlargement," the curved line inside the symbol may be replaced with a plus or minus letter symbol.</p>	<p>ISO/IEC 10646 (3)</p>  <p>Q LEFT-POINTING MAGNIFYING GLASS UCS: 1F50D = search</p>  <p>P RIGHT-POINTING MAGNIFYING GLASS UCS: 1F50E = get more details</p> <p>ISO/IEC 11581-5</p>  <p>Zoom</p> <p>To enlarge or reduce the magnification of a selected area.</p>		
	<p>ISO/IEC 10646 (1)</p>  <p>★ WHITE STAR UCS: 2606 → 2729 ☆ stress outlined white star</p> <p>My favourites</p> <p>To identify the function for personal favourite bookmarks.</p>		


4.3 Current practice for indication

Graphical symbols to indicate a functional state of *equipment* or a part of *equipment* in general are also important and many *graphical symbols* have been standardized in IEC 60417 for the purpose of different categories of *equipment*.

Subclause 4.3 highlights the result of study on current practice of *graphical symbols* to indicate functional states of *equipment* in the field of multimedia technology. Table 2 shows such *graphical symbols* for use on multimedia equipment to show the states as non-exhaustive examples.

Table 2 – Current practice for indication

Standardized graphical symbols		State of the art (examples)	
IEC 60417-5546	Battery check	ISO/IEC 24755	Battery status indicator
	<p>To identify a control to check the condition of a primary or secondary battery or to identify the battery condition indicator.</p>		<p>On personal mobile communication devices.</p>
	<p>NOTE 1 According to the condition of the battery, the size of the darkened area may vary.</p>		<p>To show the amount of the charge of an internal battery. There are four states: fully charged, charged, weak or empty.</p>
	<p>NOTE 2 In combination with an indicator such as an LED, this symbol may be used to indicate the battery is being charged.</p>		
IEC 60417-5639	Rechargeable battery		
	<p>To identify equipment which shall only be used with rechargeable (secondary) cells or batteries, or to identify rechargeable cells or batteries.</p>		
	<p>When shown on a battery holder, the symbol also indicates the positioning of the cells.</p>		
IEC 60417-6019	Vibration	ISO/IEC 10646 (3)	VIBRATION MODE UCS: 1F4F3
	<p>To identify the control or the indicator for vibration.</p>		Vibration
		ISO/IEC 24755	On personal mobile communication devices
			<p>To show that the setting of vibration is on. The vibration will activate to notify the user that an e-mail or telephone call has been received.</p>
			
			
			

Standardized graphical symbols		State of the art (examples)	
<p>IEC 60417-5039</p>  <p>Aerial; antenna</p> <p>On radio receiving and transmitting equipment.</p> <p>To identify the aerial (antenna) terminals.</p> <p>This symbol should be used unless it is essential to specify the type of aerial (antenna).</p>		<p>ISO/IEC 10646 (3)</p>  <p>ANTENNA WITH BARS</p> <p>UCS: 1F4F6 =cellular reception</p> <p>To indicate the strength of wireless signal.</p> <p>ISO/IEC 24755</p>  <p>Wireless carrier connection</p> <p>On personal mobile communication devices.</p> <p>To show the strength of the wireless signal when it connects to the carrier connection. There are five states: very strong, strong, weak, very weak or not detected.</p>	
<p>IEC 60417-5140</p>  <p>Non-ionizing electromagnetic radiation</p> <p>To indicate generally elevated, potentially hazardous, levels of non-ionizing radiation, or to indicate equipment or systems e.g. in the medical electrical area that include RF transmitters or that intentionally apply RF electromagnetic energy for diagnosis or treatment.</p> <p>NOTE In case of application in a warning sign the rules according to ISO 3864 shall be adhered to.</p>		<p>ISO/IEC 24755</p>  <p>Wireless network connection</p> <p>On personal mobile communication devices</p> <p>To show strength of the wireless signal when it connects to the network. There are five states: very strong, strong, weak, very weak or not detected.</p> <p>NOTE The icon can change dynamically to represent the current signal strengths.</p>	