

# TECHNICAL SPECIFICATION IEC TS 61400-14

First edition  
2005-03

---

---

**Wind turbines –**

**Part 14:  
Declaration of apparent sound  
power level and tonality values**

IECNORM.COM : Click to view the full PDF of IEC TS 61400-14:2005



Reference number  
IEC/TS 61400-14:2005(E)

## Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

## Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

## Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** ([www.iec.ch](http://www.iec.ch))

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site ([www.iec.ch/searchpub](http://www.iec.ch/searchpub)) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications ([www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: [custserv@iec.ch](mailto:custserv@iec.ch)  
Tel: +41 22 919 02 11  
Fax: +41 22 919 03 00

# TECHNICAL SPECIFICATION IEC TS 61400-14

First edition  
2005-03

---

---

## Wind turbines –

### Part 14: Declaration of apparent sound power level and tonality values

IECNORM.COM : Click to view the full PDF of IEC TS 61400-14:2005

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

L

*For price, see current catalogue*

## CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 General .....	7
5 Declaration.....	7
5.1 Declaration of apparent sound power level for a wind turbine.....	7
5.2 Declaration of tonality.....	8
6 Information to be reported.....	8
Annex A (informative) Method of calculating apparent sound power level to another hub height .....	9
Annex B (informative) Influence of turbine and site characteristics on the acoustical performance .....	11

IECNORM.COM : Click to view the full PDF of IEC TS 61400-14:2005

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## WIND TURBINES –

**Part 14: Declaration of apparent sound power level  
and tonality values**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 61400-14, which is a technical specification, has been prepared by IEC technical committee 88: Wind turbines.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
88/193/DTS	88/222/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61400 consists of the following parts, under the general title *Wind turbines*:

- Part 1: Design requirements
- Part 2: Safety of small wind turbines
- Part 11: Acoustic noise measurement techniques
- Part 12: Wind turbine power performance testing
- Part 13: Measurement of mechanical loads
- Part 14: Declaration of apparent sound power level and tonality values
- Part 21: Measurement and assessment of power quality characteristics of grid connected wind turbines
- Part 23: Full-scale structural testing of rotor blades
- Part 24: Lightning protection

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

Information on the apparent sound power level and tonality of wind turbines is needed by planners, manufacturers and authorities. At present, wind turbine noise specifications tend to be based on measurement results from a single turbine of a particular make and model, and these are then taken to be representative of these turbines as a whole. Clearly, this is unlikely to be the case, as there will be individual variation between different turbines. The intention of this technical specification is to determine declared noise emission values from a sample of turbines of the same type. The declaration will increase the reliability of wind farm planning and facilitate the comparison of apparent sound power levels and tonality values of different types of wind turbines.

IECNORM.COM : Click to view the full PDF of IEC TS 61400-14:2005

## WIND TURBINES –

### Part 14: Declaration of apparent sound power level and tonality values

#### 1 Scope

This part of IEC 61400 gives guidelines for declaring the apparent sound power level and tonality of a batch of wind turbines. The measurement procedures for apparent sound power level and tonality are defined in IEC 61400-11.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61400-11:2002, *Wind turbines – Part 11: Acoustic noise measurement techniques*

ISO 4871:1996, *Acoustics – Declaration and verification of noise emission values of machinery and equipment*

ISO 7574 (all parts), *Acoustics – Statistical methods for determining and verifying stated noise emission values of machinery and equipment*

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

##### 3.1

##### **standard deviation of reproducibility $\sigma_R$**

standard deviation of noise emission values obtained under reproducibility conditions, i.e. the repeated application of the same noise emission measurement method on the same wind turbine at different times and under different conditions (different wind directions, different personnel, different apparatus)

##### 3.2

##### **standard deviation of production $\sigma_P$**

standard deviation of measured noise emission values obtained at different turbines from a batch, using the same noise emission measurement method under repeatability conditions (same operators, same apparatus)

##### 3.3

##### **total standard deviation $\sigma_t$**

$\sigma_t$  is defined as

$$\sigma_t = \sqrt{\sigma_P^2 + \sigma_R^2} \quad (1)$$

##### 3.4

##### **batch**

wind turbines of the same make and model with identical specifications constitute a batch. A batch is characterized by the same declared apparent sound power level and tonality. The range of components included in a declaration is specified in the related manufacturer's statement.

NOTE Since slight changes in the turbine design affect the apparent sound power level and the tonality, Annex B contains information on the influence of turbine parameters on measured acoustic characteristics.

## 4 General

In ISO 4871 and ISO 7574 general procedures for declaration and verification of acoustic noise emitted by machinery and equipment are described. For batches, the declaration and verification procedure is based on the assumption that the standard deviation of production of the type is known from measurements.

The declaration procedure specified here differs from the ISO procedure and allows a declaration based on a minimum of three measurements.

The declaration procedures may be used to declare values at any wind speed for which measurement results are available.

## 5 Declaration

### 5.1 Declaration of apparent sound power level for a wind turbine

The apparent sound power level according to IEC 61400-11 shall be declared.

The declared apparent sound power level for a wind turbine can be determined from  $n$  measurement results  $\{L_i\}$   $i = 1, \dots, n$  obtained by performing one measurement at each of  $n$  individual turbines of the same type. For wind turbines of the same type and tower but of different hub heights, the sound power level may be converted to another hub height according to Annex A.

The  $n$  measurements result in a mean value  $\bar{L}_W$  and a standard deviation  $s$  defined as follows:

$$\bar{L}_W = \frac{1}{n} \sum_{i=1}^n L_i \quad (2)$$

$$s = \sqrt{\frac{1}{n-1} \sum_{i=1}^n (L_i - \bar{L}_W)^2} \quad (3)$$

The standard deviation of production  $\sigma_P$  can be estimated from

$$\sqrt{s^2 - \sigma_R^2} \leq \sigma_P \leq s \quad (4)$$

An estimate of the standard deviation of reproducibility  $\sigma_R$  is 0,9 dB (see typical uncertainties given in Annex D of IEC 61400-11). As long as only limited data on the real standard deviation of reproducibility is available, and, as for some cases, very small values of  $\sigma_R$  were found, the relation  $\sigma_P = s$  shall be used.

The standard deviation  $\sigma$  used for the declaration (including the standard deviation  $\sigma_R$  and  $\sigma_P$  from the  $n$  existing measurements and the standard deviation  $\sigma_R$  and  $\sigma_P$  of a verification measurement) is then determined by

$$\sigma = \sqrt{\frac{1}{n}(\sigma_R^2 + \sigma_P^2) + (\sigma_R^2 + \sigma_P^2)} = \sqrt{\frac{1+n}{n}(\sigma_R^2 + \sigma_P^2)} \quad (5)$$

with  $\sigma_R = 0,9$  dB and  $\sigma_P = s$ .

The declared apparent sound power level is calculated from

$$L_{Wd} = \bar{L}_W + K = \bar{L}_W + 1,645 \sigma \quad (6)$$

The apparent sound power level shall be declared by dual-number noise emission values reporting both  $\bar{L}_W$  and  $K$ .  $K$  represents a certain confidence level and  $K = 1,645 \sigma$  reflects a probability of 5 % that an apparent sound power level measurement result made according to IEC 61400-11 performed at a turbine of the batch exceeds the declared value.

## 5.2 Declaration of tonality

Declaration of tonality reports the tonality and frequency(ies) of each turbine from the batch. Declaration of tonality shall not be performed in the same way as for the apparent sound power level. At present, very limited data for statistical treatment is available.

## 6 Information to be reported

All the individual measurement reports shall be annexed to the declaration report.

Further information to be reported is as follows.

- a) Wind turbine details
  - turbine manufacturer;
  - model number/name;
  - rated power;
  - hub height;
  - rotor diameter;
  - manufacturer certificates detailing component differences, provided by manufacturer.
- b) Declaration results
 

Apparent sound power level results

  - the individually measured apparent sound power levels  $\{L_i\} i = 1, \dots, n$ ;
  - the mean of the measured apparent sound power levels  $\bar{L}_W$ ;
  - the sample standard deviation of the apparent sound power levels,  $s$ ;
  - $\sigma_P, \sigma_R, \sigma_s$ ;
  - $K$ ;
  - declared value,  $L_{Wd}$ .
- c) Tonality results
 

For all measurements the tonality and the tonal frequency(ies).

## Annex A (informative)

### Method of calculating apparent sound power level to another hub height

For wind turbines of the same type and tower but of different hub heights, the sound power level may be converted to another hub height under the assumption of a logarithmic wind profile.

If the sound pressure level is measured and the sound power level  $L_{WA,P, meas}$  is calculated for a wind turbine, the sound power level  $L_{WA,P, new}$  for the same wind turbine at another hub height may be determined using the regression values of the measured turbines.

The wind speed value ( $v_{10,i}$ ) at 10 m above ground causes the same power output at the measured wind turbine as on the same wind turbine at a new hub height for chosen wind speed ( $v_{10,ref}$ ) at 10 m above ground.

$$v_{10,i} = v_{10,ref} \left[ \frac{\ln \frac{h_{new}}{z_0}}{\ln \frac{h_{meas}}{z_0}} \right] \quad (A.1)$$

where

- $v_{10,i}$  is the determined wind speed at 10 m above ground;
- $v_{10,ref}$  is the reference wind speed at 10 m above ground;
- $h_{new}$  is the new hub height of wind turbine;
- $h_{meas}$  is the hub height of measured wind turbine;
- $z_0$  is the roughness length.

The sound pressure is then determined using the regression coefficients of the measured wind turbine for total and background noise using the calculated wind speed ( $v_{10,i}$ ) from equation A.1. The background corrected sound pressure value is determined using equation A.2.

$$L_{Aeq,c,meas}(v_{10,i}) = 10 \lg(10^{L_{Aeq,meas}(v_{10,i}) \times 0,1} - 10^{L_{back,meas}(v_{10,i}) \times 0,1}) \quad (A.2)$$

where

- $L_{Aeq,c,meas}(v_{10,i})$  is the background corrected sound pressure level of wind turbine related to wind speed at 10 m above ground (measured wind turbine);
- $L_{Aeq,meas}(v_{10,i})$  is the sound pressure level of total noise related to wind speed at 10 m above ground;
- $L_{back,meas}(v_{10,i})$  is the sound pressure level of background noise related to wind speed at 10 m above ground.

Using this sound pressure value ( $L_{Aeq,c,meas}(v_{10,i})$ ) the sound power level ( $L_{WA,P,meas}(v_{10,i})$ ) will be determined considering the geometric data of the measured wind turbine.

$$L_{WA,P,meas}(v_{10,i}) = L_{Aeq,meas}(v_{10,i}) - 6 + 10 \lg \left[ \frac{4\pi R_1^2}{s_0} \right] \quad (A.3)$$