
Identification cards — Test methods —

Part 6:

Proximity cards

AMENDMENT 3: Exchange of additional parameters, block numbering, unmatched AFI and TR2

Cartes d'identification — Méthodes d'essai —

Partie 6: Cartes de proximité

AMENDEMENT 3: Échange de paramètres additionnels, numérotation des blocs, AFI non correspondant et TR2

IECNORM.COM : Click to view the full PDF of ISO/IEC 10373-6:2011/Amd 3:2012

ISO/IEC 10373-6:2011/Amd.3:2012

ISO/IEC 10373-6:2011/Amd.3:2012



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 3 to ISO/IEC 10373-6:2011 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

IECNORM.COM : Click to view the full PDF of ISO/IEC 10373-6:2011/Amd 3:2012

Identification cards — Test methods —

Part 6: Proximity cards

AMENDMENT 3: Exchange of additional parameters, block numbering, unmatched AFI and TR2

Page 91, G.3.3.2.2

Add the following note after Table G.7:

NOTE 7.5.3 The block number may be 0 or 1 dependent on block numbering rules defined in ISO/IEC 14443-4:2008, 7.5.3.

Page 116, G.4.4.1.2

Add the following note after Table G.38:

NOTE 7.5.3 The block number may be 0 or 1 dependent on block numbering rules defined in ISO/IEC 14443-4:2008, 7.5.3.

Page 116, G.4.4.2.2

Add table footnote "e" to REQB and WUPB in Transition column of first and second rows in Table G.39.

Add table footnote "f" to REQB(Unmatched AFI) and WUPB(Unmatched AFI) in Transition column of tenth and eleventh rows in Table G.39.

Add table footnotes "e" and "f" in last row in Table G.39:

- e All matched AFIs as defined by the PICC manufacturer shall be tested.
- f The unmatched AFI used in this test shall not be an RFU value. If the PICC accepts all AFIs this test is not applicable.

Page 118, G.4.4.3.2

Add table footnote "e" to REQB and WUPB in Transition column of first and second rows in Table G.41.

Add table footnote "f" to REQB(Unmatched AFI) and WUPB(Unmatched AFI) in Transition column of twelfth and thirteenth rows in Table G.41.

Add table footnotes "e" and "f" in last row in Table G.41:

- e All matched AFIs as defined by the PICC manufacturer shall be tested.
- f The unmatched AFI used in this test shall not be an RFU value. If the PICC accepts all AFIs this test is not applicable.

Page 119, G.4.4.4.2

Add table footnote “e” to REQB and WUPB in Transition column of first and second rows in Table G.43.

Add table footnote “f” to REQB(Unmatched AFI) and WUPB(Unmatched AFI) in Transition column of fourteenth and fifteenth rows in Table G.43.

Add table footnotes “e” and “f” in last row in Table G.43:

- e All matched AFIs as defined by the PICC manufacturer shall be tested.
- f The unmatched AFI used in this test shall not be an RFU value. If the PICC accepts all AFIs this test is not applicable.

Page 121, G.4.4.5.2

Add table footnote “d” to REQB and WUPB in Transition column of first and second rows in Table G.45.

Add table footnote “e” to REQB(Unmatched AFI) and WUPB(Unmatched AFI) in Transition column of ninth and tenth rows in Table G.45.

Add table footnotes “d” and “e” in last row in Table G.45:

- d All matched AFIs as defined by the PICC manufacturer shall be tested.
- e The unmatched AFI used in this test shall not be an RFU value. If the PICC accepts all AFIs this test is not applicable.

Page 123, G.4.4.6.2

Add table footnote “b” to REQB and WUPB in Transition column of first and second rows in Table G.47.

Add table footnote “c” to WUPB(Unmatched AFI) and REQB(Unmatched AFI) in Transition column of tenth and eleventh rows in Table G.47.

Add table footnotes “b” and “c” in last row in Table G.47:

- b All matched AFIs as defined by the PICC manufacturer shall be tested.
- c The unmatched AFI used in this test shall not be an RFU value. If the PICC accepts all AFIs this test is not applicable.

Page 142, G.5.4.2

Add the following new Scenario after Scenario G.62:

Scenario G.66: CID on S(PARAMETERS)-block

Step	PICC-test-apparatus	PICC
1	S(PARAMETERS, CID = cid _{cmd})	<p>→</p> <p>← Response 1: S(PARAMETERS, CID = cid_{cmd}) Response 2: Mute^a</p>
^a Response 1 or response 2 according to Table G.55 or Table G.56.		

Page 143, after G.5.5.3

Add the following new clauses at the end of G.5.5.3:

G.5.6 PICC reaction on S(PARAMETERS) blocks

G.5.6.1 Scope

This test is to determine the behavior of the PICC according to ISO/IEC 14443-4:2008/Amd.1:2012, 7.5.1. This test uses implementations of the protocol Scenarios of ISO/IEC 14443-4:2008/Amd.1:2012, Annex B.2.6.

G.5.6.2 Procedure

Perform the following steps for each of Scenario G.67 through G.70 listed in this subclause.

- a) Activate the PICC as described in G.5.1.1, use CID = 0 and FSDI = 0.
- b) For each step in the Scenario do:
 - 1) Send the command as described in the PICC-test-apparatus column.
 - 2) Check that the PICC response matches the one of the PICC column.
- c) End for.

Scenario G.67: Exchange of additional parameters

Step	PICC-test-apparatus		PICC
1	I(0) ₀ (TEST_COMMAND1(1))	→	
		←	I(0) ₀ (TEST_RESPONSE1(1))
2	S(PARAMETERS)	→	
		←	S(PARAMETERS)
3	I(0) ₁ (TEST_COMMAND1(1))	→	
		←	I(0) ₁ (TEST_RESPONSE1(1))

Scenario G.68: Exchange of additional parameters

Step	PICC-test-apparatus		PICC
1	S(PARAMETERS)	→	
		←	S(PARAMETERS)
2	I(0) ₀ (TEST_COMMAND1(1))	→	
		←	I(0) ₀ (TEST_RESPONSE1(1))

Scenario G.69: Exchange of additional parameters

Step	PICC-test-apparatus		PICC
1	S(PARAMETERS)	→	
		←	S(PARAMETERS)
2	S(PARAMETERS)	→	
		←	S(PARAMETERS)
3	I(0) _o (TEST_COMMAND1(1))	→	
		←	I(0) _o (TEST_RESPONSE1(1))

Scenario G.70: Exchange of additional parameters

Step	PICC-test-apparatus		PICC
1	S(PARAMETERS, ~CRC)	→	
		←	Mute
2	S(PARAMETERS)	→	
		←	S(PARAMETERS)
3	I(0) _o (TEST_COMMAND1(1))	→	
		←	I(0) _o (TEST_RESPONSE1(1))

G.5.6.3 Test report

Fill the appropriate rows in Table G.63 according to Table Amd.3-1.

Table Amd.3-1 — Result criteria for exchange of additional parameters

Explanation	Test result
Only when the PICC responded as indicated in the procedure	PASS
Any other case	FAIL

Page 144, G.6

Remove Line No 10 of Table G.60 referring to parameter TR2.