

First edition
1992-06-15

AMENDMENT 1
1996-07-15

**Information technology —
Telecommunications and information
exchange between systems — Intermediate
system to Intermediate system intra-domain
routing information exchange protocol for
use in conjunction with the protocol for
providing the connectionless-mode Network
Service (ISO 8473)**

AMENDMENT 1:

Implementation conformance statement proformas

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Protocole intra-domaine de routage d'un
système intermédiaire à un système intermédiaire à utiliser conjointement
avec le protocole fournissant le service de réseau en mode sans
connexion (ISO 8473)*

*AMENDEMENT 1: Proformes de déclaration de conformité de mise en
œuvre*



Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 10589:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office · Case postale 56 · CH-1211 Genève · Switzerland

Printed in Switzerland

Information technology – Telecommunications and information exchange between systems – Intermediate system to intermediate system intra-domain routing information exchange protocol for use in conjunction with the protocol for providing the connectionless-mode Network Service (ISO 8473)

AMENDMENT 1:

Implementation conformance statement proformas

Page 1

Add the following as the last paragraph of Clause 1 "Scope":

"

Annexes G, H, I and J, which are integral parts of this International Standard provide ICS proformas associated with intra-domain routing protocol management information.

"

Add the following references to clause 2 "Normative references":

"

ISO/IEC 8825: 1990, *Information technology - Open Systems Interconnection - Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1)*.

ISO/IEC 9646-1: 1994, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts*.

ISO/IEC 9646-2: 1994, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification*.

NOTE - ISO/IEC 9646-1:1994 and ISO/IEC 9646-2:1994 supersede ISO/IEC 9646-1:1991 and ISO/IEC 9646-2:1991 respectively. However, when this International Standard was under development, the previous editions were valid and this International Standard is therefore based on these editions, which are listed below.

ISO/IEC 9646-1: 1991, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts*.

ISO/IEC 9646-2: 1991, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract test suite specification*.

ISO/IEC 9646-7: 1995, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements*.

ISO/IEC 10165-6: 1994, *Information technology - Open Systems Interconnection - Structure of management information: Requirements and guidelines for implementation conformance statement proformas associated with OSI management*.

"

Page 4

Add the following abbreviations to subclause 4.4 "Miscellaneous":

"

MCS	management conformance summary
MICS	management information conformance statement
MOCS	managed object conformance statement
MRCS	managed relationship conformance statement

"

Page 101

Add the following after the title "12 Conformance".

"

12.1 Conformance for protocol implementation

This subclause specifies the conformance for protocol implementation of intra-domain routing protocol. The supplier of implementation for protocol implementation shall support the following specification.

NOTE – The conformance for protocol implementation is independent of the conformance for management information implementation specified in subclause 12.2.

"

Replace title number of "12.1", "12.1.1", "12.1.2", "12.1.3", "12.1.4", "12.2", "12.2.1", "12.2.2", "12.2.2.1", "12.2.3", "12.2.4", "12.2.4.1", "12.2.4.2", "12.2.4.3" and "12.2.4.4" with "12.1", "12.1.1", "12.1.1.1", "12.1.1.2", "12.1.1.3", "12.1.1.4", "12.1.2", "12.1.2.1", "12.1.2.2", "12.1.2.2.1", "12.1.2.3", "12.1.2.4", "12.1.2.4.1", "12.1.2.4.2", "12.1.2.4.3" and "12.1.2.4.4", respectively.

Delete "y)" of subclause 12.1.1.2 "Static conformance requirements for all ISs", and rename "z)" with "y)".

Add the following after subclause 12.1.2.4.4.

"

12.2 Conformance for management information implementation

This subclause specifies the conformance for management information implementation of intra-domain routing protocol. The supplier of implementation for management information implementation shall support the following specification.

NOTE – The conformance for management information implementation is independent of the conformance for protocol implementation specified in subclause 12.1.

12.2.1 Static conformance

The implementation shall conform to the requirements of this International Standard in the manager role, the agent role, or both roles. A claim of conformance to at least one role shall be made in Table G.1 of this International Standard.

If a claim of conformance is made for support in the manager role, the implementation shall support at least one management operation or notification or action of the managed objects specified by this International Standard. The conformance requirements in the manager role for those management operations and notifications and actions are identified in Table G.3 and further tables referenced by Annex G.

If a claim of conformance is made for support in the agent role, the implementation shall support one or more instances of the adjacency managed object class, the destination managed object class, the destination area managed object, the destination system managed object class, the reachable address managed object class and the virtual adjacency managed object class identified in Table G.4 of this International Standard and further tables referenced by Annex G.

If a claim of conformance is made for support in the agent role, the implementation shall support at least one name binding identified in Table G.8 of this International Standard for each supported managed object.

The implementation shall support the transfer syntax derived from the encoding rules specified in CCITT Rec. X.209 | ISO/IEC 8825 named {joint-iso-ccitt asn1(1) basicEncoding(1)} for the abstract data types referenced by the definitions for which support is claimed.

12.2.2 Dynamic conformance

Implementations claiming to conform to this International Standard shall support the elements of procedure and definitions of semantics corresponding to the definitions for which support is claimed.

12.2.3 Management implementation conformance statement requirements

Any MCS proforma, MICS proforma, MOCS proforma, and MRCS proforma which conform to this International Standard shall be technically identical to the proformas specified in Annexes G, H, I, and J preserving table numbering and the index numbers of items, and differing only in pagination and page headers.

The supplier of an implementation which is claimed to conform to this International Standard shall complete a copy of the management conformance summary (MCS) provided in Annex G as part of the conformance requirements together with any other ICS proformas referenced as applicable from that MCS. Any MCS, MICS, MOCS, and MRCS which conform to this International Standard shall:

- describe an implementation which conforms to this International Standard;
- have been completed in accordance with the instructions for completion given in ITU-T Rec. X.724 | ISO/IEC 10165-6;
- include the information necessary to uniquely identify both the supplier and the implementation.

12.2.4 IS level specific conformance requirements

The supplier of an implementation which is claimed to conform to this International Standard shall support at least level 1 IS identified in Table G.2 of this International Standard.

12.2.4.1 Conformance to level 1 ISs

An implementation claiming conformance to the level 1 IS of this International Standard in the agent role as a managed implementation shall support the adjacency MO and the destination system MO.

12.2.4.2 Conformance to level 2 ISs

An implementation claiming conformance to the level 2 IS of this International Standard in the agent role as a managed implementation shall support the adjacency MO, the destination system MO, the destination area MO, the virtual adjacency MO and the reachable address MO.

"

Page 142

Add the following Annexes after Annex F.

Annex G (normative)

MCS proforma¹⁾

G.1 Introduction

G.1.1 Purpose and structure

The management conformance summary (MCS) is a statement by a supplier that identifies an implementation and provides information on whether the implementation claims conformance to any of the listed set of documents that specify conformance requirements to OSI management.

The MCS proforma is a document, in the form of a questionnaire that when completed by the supplier of an implementation becomes the MCS.

G.1.2 Instructions for completing the MCS proforma to produce an MCS²⁾

The supplier of the implementation shall enter an explicit statement in each of the boxes provided. Specific instruction is provided in the text which precedes each table.

G.1.3 Symbols, abbreviations and terms

For all remaining annexes of this International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7 are used for the Status column:

- m mandatory;
- o optional;
- c conditional;
- x prohibited;
- not applicable or out of scope.

NOTES

1 - 'c', 'm', and 'o' are prefixed by a 'c' when nested under a conditional or optional item of the same table;

2 - 'o' may be suffixed by 'N' (where N is a unique number) for mutually exclusive or selectable options among a set of status values. Support of at least one of the choices (from the items with the same values of N) is required.

For all remaining annexes of this International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7 are used for the Support column:

- Y implemented;
- N not implemented;
- no answer required;
- Ig the item is ignored (i.e. processed syntactically but not semantically).

¹⁾ Users of this International Standard may freely reproduce the MCS proforma in this annex so that it can be used for its intended purpose, and may further publish the completed MCS.

²⁾ Instructions for completing the MCS proforma are specified in ITU-T Rec.X.724 | ISO/IEC 10165-6 .

G.2 Identification of the implementation

G.2.1 Date of statement

The supplier of the implementation shall enter the date of this statement in the box below. Use the format DD-MM-YYYY.

Date of statement

G.2.2 Identification of the implementation

The supplier of the implementation shall enter information necessary to uniquely identify the implementation and the system(s) in which it may reside, in the box below.

--

G.2.3 Contact

The supplier of the implementation shall provide information on whom to contact if there are any queries concerning the content of the MCS, in the box below.

--

G.3 Identification of the International Standard in which the management information is defined

The supplier of the implementation shall enter the title, reference number and date of the publication of the International Standard which specifies the management information to which conformance is claimed, in the box below.

International Standard to which conformance is claimed
--

G.3.1 Technical corrigenda implemented

The supplier of the implementation shall enter the reference numbers of implemented technical corrigenda which modify the identified International Standard, in the box below.

--

G.3.2 Amendments implemented

The supplier of the implementation shall state the titles and reference numbers of implemented amendments to the identified International Standard, in the box below.

G.4 Management conformance summary

The supplier of implementation shall state the capabilities and features supported and provide summary of conformance claims to International Standards using the tables in this annex.

The supplier of the implementation shall specify the roles that are supported, in Table G.1

Table G.1 – Roles

Index	Roles supported	Status	Support	Additional information
1	Manager role support	o.1		
2	Agent role support	o.1		

The supplier of the implementation shall specify the level of IS that are supported, in Table G.2

Table G.2 – Level of IS

Index	Level supported	Status	Support	Additional information
1	Level 1 IS support	m		
2	Level 2 IS support	o		

The supplier of the implementation shall specify support for management information in the manager role, in Table G.3.

Table G.3 – Manager role minimum conformance requirement

Index	Item	Status	Support	Additional information
1	Operations on managed objects	c1		
2	Activate action for reachableAddress	c1		
3	Deactivate action reachableAddress	c1		
4	State change notification for Adjacency managed object	c1		
5	Object creation notification for reachableAddress managed object	c1		
6	Object deletion notification for reachableAddress managed object	c1		
7	State change notification for reachableAddress managed object	c1		

c1: if G.1/1a then o.2 else -

The supplier of the implementation shall specify support for management information in the agent role, in Table G.4.

Table G.4 – Agent role minimum conformance requirement

Index	Item	Status	Support	Additional information
1	adjacency managed object	m		
2	destinationArea managed object	c2		
3	destinationSystem managed object	m		
4	reachableAddress managed object	c2		
5	virtualAdjacency managed object	c2		

c2: if G.2/2a then m else -

NOTE – The Table reference column in the above table is the managed object class, notification, attribute or action table reference of the MOCS supplied by the supplier of the managed object which claims to import the notification or attribute from this International Standard.

Table G.5 – Logging of event records

Index		Status	Support	Additional information
1	Does the implementation support logging of event records in agent role?	c3		

c3: if G.1/2a then o else -

NOTE – Conformance to this International Standard does not require conformance to CCITT Rec. X.735 | ISO/IEC 10164-6.

The supplier of the implementation shall provide information on claims of conformance to any of the International Standards summarized in the following tables. For each International Standard that the supplier of the implementation claims conformance to, the corresponding conformance statement(s) shall be completed, or referenced by, the MCS. The supplier of the implementation shall complete the Support, Table numbers and Additional information columns.

In tables G.6, G.7, and G.8, the Status column is used to indicate whether the supplier of the implementation is required to complete the referenced tables or referenced items. Conformance requirements are as specified in the referenced tables or referenced items and are not changed by the value of the MCS Status column. Similarly, the Support column is used by the supplier of the implementation to indicate completion of the referenced tables or referenced items.

Table G.6 – MOCS support summary

Index	Identification of the document that includes the MOCS proforma	Table numbers of MOCS proforma	Description	Constraints and values	Status	Support	Table numbers of MOCS	Additional information
1	"ISO/IEC 10589"	Table I.1 - I.6	adjacency	—	m			
2	"ISO/IEC 10589"	Table I.7 - I.10	virtualAdjacency	—	c4			
3	"ISO/IEC 10589"	Table I.11 - I.14	destinationSystem	—	m			
4	"ISO/IEC 10589"	Table I.15 - I.18	destinationArea	—	c5			
5	"ISO/IEC 10589"	Table I.19 - I.24	reachableAddress	—	c6			
6	"ISO/IEC 10164-1"	Table C.1 - C.4	objectCreationRecord	—	c7			
7	"ISO/IEC 10164-1"	Table C.5 - C.8	objectDeletionRecord	—	c7			
8	"ISO/IEC 10164-2"	Table C.9 - C.12	stateChangeRecord	—	c8			

c4: if G.4/5a then m else -

c5: if G.4/2a then m else -

c6: if G.4/4a then m else -

c7: if G.4/4a and G.5/1a then m else -

c8: if G.5/1a then m else -

Table G.7 – MRCS support summary

Index	Identification of the document that includes the MRCS proforma	Table numbers of MRCS proforma	Description	Constraints and values	Status	Support	Table numbers of MRCS	Additional information
1	"ISO/IEC 10589"	Table J.1/1	adjacency-linkage	—	o.3			
2	"ISO/IEC 10589"	Table J.1/2	adjacency-linkage-management	—	o.3			
3	"ISO/IEC 10589"	Table J.1/3	virtualAdjacency-cLNS	—	c9			
4	"ISO/IEC 10589"	Table J.1/4	destinationSystem-cLNS	—	m			
5	"ISO/IEC 10589"	Table J.1/5	destinationArea-cLNS	—	c10			
6	"ISO/IEC 10589"	Table J.1/6	reachableAddress-linkage-imported	—	c11			
7	"ISO/IEC 10589"	Table J.1/7	reachableAddress-linkage-management	—	c11			
8	"ISO/IEC 10164-6"	Table D.1/1	logRecord-log	—	c12			

c9: if G.6/2a then m else -

c10: if G.6/4a then m else -

c11: if G.6/5a then o.4 else -

c12: G.5/1a then o else -

Table G.8 – MICS support summary

Index	Identification of the document that includes the MICS proforma	Table numbers of MICS proforma	Description	Constraints and values	Status	Support	Table numbers of MICS	Additional information
1	"ISO/IEC 10589"	Table H.1 to H.7	management operations	—	c13			
2	"ISO/IEC 10589"	Table H.8	notifications	—	c14			
3	"ISO/IEC 10589"	Table H.9	actions	—	c15			

c13: if G.3/1a then m else -

c14: if G.3/4a or G.3/5a or G.3/6a or G.3/7a then m else -

c15: if G.3/2a or G.3/3a then m else -

Annex H
(normative)

MICS proforma¹⁾

H.1 Introduction

The purpose of this MICS proforma is to provide a mechanism for a supplier of an implementation which claims conformance, in the manager role, to management information specified in this International Standard, to provide conformance information in a standard form.

H.2 Instructions for completing the MICS proforma to produce a MICS

The MICS proforma contained in this annex is comprised of information in tabular form, in accordance with ITU-T Rec. X.724 | ISO/IEC 10165-6. In addition to the general guidance given in ITU-T Rec. X.724 | ISO/IEC 10165-6, the Additional information column shall be used to identify the object classes for which the management operations are supported. The supplier of the implementation shall state which items are supported in tables below and if necessary, provide additional information.

H.3 Symbols, abbreviations and terms

The MICS proforma contained in this Annex is comprised of information in tabular form, in accordance with CCITT Rec. X.291 | ISO/IEC 9646-2.

The notations used in the Status and Support columns are specified in G.13.

H.4 Statement of conformance to the management information

H.4.1 Attributes

The supplier of a manager role implementation that claims to support management operations on the attributes specified in this International Standard shall import a copy of the following tables and complete them.

H.4.1.1 Adjacency managed object

Table H.1 – adjacency managed object Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	c1		0.5		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	c1		0.5		-		-		-		-		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	c1		0.5		-		-		-		-		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c1		0.5		-		-		-		-		
5	"ISO/IEC 10589": adjacencyId	{2 13 0 1 7 77}	GraphicString	c1		0.5		-		-		-		-		
6	"ISO/IEC 10589": adjacencyState	{2 13 0 1 7 78}	ISIS.AdjacencyState	-		0.5		-		-		-		-		
7	"ISO/IEC 10589": neighbourSNPAAddress	{2 13 0 1 7 79}	ISIS.ANPAAAddress	-		0.5		-		-		-		-		

¹⁾ Users of this International Standard may freely reproduce the PICS proforma in this Annex so that it can be used for its intended purpose, and may further publish the completed PICS.

Table H.1 (concluded) – adjacency managed object Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
8	"ISO/IEC 10589": neighbourSystemType	{2 13 0 17 80}	ENUMERATED	-		0.5		-		-		-		-		
9	"ISO/IEC 10589": neighbourSystemIds	{2 13 0 17 83}	SET OF OCTETSTRING	-		0.5		-		-		-		-		
10	"ISO/IEC 10589": adjacencyUsage	{2 13 0 17 82}	ISIS AdjacencyUsage	-		0.5		-		-		-		-		
11	"ISO/IEC 10589": areaAddressesOfNeighbour	{2 13 0 17 84}	ISIS AreaAddresses	-		0.5		-		-		-		-		
12	"ISO/IEC 10589": holdingTimer	{2 13 0 17 85}	timer	-		0.5		-		-		-		-		
13	"ISO/IEC 10589": priorityOfNeighbour	{2 13 0 17 86}	ISIS Intermediate SystemPriority	-		0.5		-		-		-		-		

c1: if H.6/1a then 0.5 else x

H.4.1.2 Virtual adjacency managed object

Table H.2 – virtualAdjacency Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	-		0.5		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	-		0.5		-		-		-		-		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	-		0.5		-		-		-		-		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	-		0.5		-		-		-		-		
5	"ISO/IEC 10589 : 1992": networkEntityType	{2 13 0 17 88}	ISIS NAddress	-		0.5		-		-		-		-		
6	"ISO/IEC 10589 : 1992": metric	{2 13 0 17 89}	ISIS PathMetric	-		0.5		-		-		-		-		

H.4.1.3 Destination system managed object

Table H.3 – destinationSystem Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	-		0.5		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	-		0.5		-		-		-		-		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	-		0.5		-		-		-		x		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	-		0.5		-		-		-		-		
5	"ISO/IEC 10589": defaultMetricOutputAdjacencies	{2 13 0 17 91}	ISIS OutputAdjacencies	-		0.5		0.5		-		-		-		
6	"ISO/IEC 10589": defaultMetricPathCost	{2 13 0 17 90}	ISIS PathMetric	-		0.5		0.5		-		-		-		

Table H.3 (concluded) – destinationSystem Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort			
7	"ISO/IEC 10589": delayMetricOutputAdjancencies	{2 13 0 17 93}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
8	"ISO/IEC 10589": delayMetricPathCost	{2 13 0 17 92}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
9	"ISO/IEC 10589": errorMetricOutputAdjancencies	{2 13 0 17 97}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
10	"ISO/IEC 10589": errorMetricPathCost	{2 13 0 17 96}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
11	"ISO/IEC 10589": expenseMetricOutputAdjancencies	{2 13 0 17 95}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
12	"ISO/IEC 10589": expenseMetricPathCost	{2 13 0 17 94}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
13	"ISO/IEC 10589": networkEntotyTitle	{2 13 0 17 88}	ISIS.NAddress	-		0.5		-		-		-		-		

H.4.1.4 Destination area managed object

Table H.4 – destinationArea Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort			
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	-		0.5		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	-		0.5		-		-		-		-		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	-		0.5		-		-		-		-		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	-		0.5		-		-		-		-		
5	"ISO/IEC 10589": defaultMetricOutputAdjancencies	{2 13 0 17 91}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
6	"ISO/IEC 10589": defaultMetricPathCost	{2 13 0 17 90}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
7	"ISO/IEC 10589": delayMetricOutputAdjancencies	{2 13 0 17 93}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
8	"ISO/IEC 10589": delayMetricPathCost	{2 13 0 17 92}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
9	"ISO/IEC 10589": errorMetricOutputAdjancencies	{2 13 0 17 97}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
10	"ISO/IEC 10589": errorMetricPathCost	{2 13 0 17 96}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
11	"ISO/IEC 10589": expenseMetricOutputAdjancencies	{2 13 0 17 95}	ISIS.OutputAdjancencies	-		0.5		0.5		-		-		-		
12	"ISO/IEC 10589": expenseMetricPathCost	{2 13 0 17 94}	ISIS.PathMetric	-		0.5		0.5		-		-		-		
13	"ISO/IEC 10589": addressPrefix	{2 13 0 17 88}	ISIS.NAddress	-		0.5		-		-		-		-		

H.4.1.5 Reachable address managed object

Table H.5 – reachableAddress Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	c2	0.5			--		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	c2	0.5			-		-		-		-		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	c2	0.5			-		-		-		-		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c2	0.5			-		-		-		-		
5	"ISO/IEC 10589": reachableAddressId	{2 13 0 1 7 121}	ISIS.GraphicString	c2	0.5			-		-		-		-		
6	"ISO/IEC 10589": mappingType	{2 13 0 1 7 107}	ENUMERATED	-	0.5			-		-		-		-		
7	"ISO/IEC 10589": addressPrefix	{2 13 0 1 7 98}	BITSTRING	-	0.5			-		-		-		-		
8	"ISO/IEC 10589": defaultMetric	{2 13 0 1 7 99}	ISIS.MetricType	c2	0.5			0.5		-		-		0.5		
9	"ISO/IEC 10589": delayMetric	{2 13 0 1 7 100}	ISIS.HopMetric	c2	0.5			0.5		-		-		0.5		
10	"ISO/IEC 10589": expenseMetric	{2 13 0 1 7 101}	ISIS.HopMetric	c2	0.5			0.5		-		-		0.5		
11	"ISO/IEC 10589": errorMetric	{2 13 0 1 7 102}	ISIS.HopMetric	c2	0.5			0.5		-		-		0.5		
12	"ISO/IEC 10589": defaultMetricType	{2 13 0 1 7 103}	ISIS.MetricType	c2	0.5			0.5		-		-		0.5		
13	"ISO/IEC 10589": delayMetricType	{2 13 0 1 7 104}	ISIS.MetricType	c2	0.5			0.5		-		-		0.5		
14	"ISO/IEC 10589": expenseMetricType	{2 13 0 1 7 105}	ISIS.MetricType	c2	0.5			0.5		-		-		0.5		
15	"ISO/IEC 10589": errorMetricType	{2 13 0 1 7 106}	ISIS.MetricType	c2	0.5			0.5		-		-		0.5		
16	"Rec. X.721 ISO/IEC 10165-2 : 1992": operationalState	{2 9 3 2 7 35}	ENUMERATED	c2	0.5			0.5		-		-		0.5		
17	"ISO/IEC 10589": sNPAAAddresses	{2 13 0 1 7 109}	ISIS.ANPAAAddress	c2	0.5			0.5		-		-		0.5		
18	"ISO/IEC 10589": sNPAMask	{2 13 0 1 7 122}	ISIS.NAddress	c2	0.5			0.5		-		-		0.5		
19	"ISO/IEC 10589": sNPAPrefix	{2 13 0 1 7 123}	ISIS.SNPAPrefix	c2	0.5			0.5		-		-		0.5		

c2: if H.7/1a then 0.5 else-

H.4.2 Attribute groups

The supplier of a manager role implementation that claims to support management operations on the attribute groups specified in this International Standard shall import a copy of this table and complete it.

H.4.3 Create and delete management operations

The supplier of a manager role implementation that claims to support the create or delete management operations on the managed objects specified in this International Standard shall import a copy of this table and complete it.

H.4.3.1 Adjacency managed object

Table H.6 — Create and delete support

Index	Operation	Constraints and values	Status	Support	Additional information
1	Create support	adjacency MO	o		
1.1	Create with reference object	—	o		
2	Delete support	adjacency MO	o		

H.4.3.2 Reachable address managed object

Table H.7 — Create and delete support

Index	Operation	Constraints and values	Status	Support	Additional information
1	Create support	reachableAddress MO	o		
1.1	Create with reference object	—	o		
2	Delete support	reachableAddress MO	o		

H.4.4 Notifications

The supplier of a manager role implementation that claims to support the notifications specified in this International Standard shall import a copy of this table and complete it.

Table H.8 – Notification support

Index	Notification type template label	Value of object identifier for notification type	Constraints and values	Status	Support		Additional information	Subindex	Notification field name label	Value of object identifier of attribute type associated with field	Constraints and values	Status	Support	Additional information
					Confirmed	Non-confirmed								
1	"Rec. X.721 ISO/IEC 10165-2 : 1992". objectCreation	{2 9 3 2 10 6}		c3				1.1	ObjectInfo		Information Syntax SEQUENCE	c3		
								1.1.1	sourceIndicator	{2 9 3 2 7 26}	ENUMERATED	c:m		
								1.1.2	attributeList	{2 9 3 2 7 9}	SET OF Attribute	c:m		
								1.1.3	notificationIdentifier	{2 9 3 2 7 16}	INTEGER	c:m		
								1.1.4	correlatedNotifications	{2 9 3 2 7 12}	SET OF SEQUENCE	c:m		
								1.1.4.1	correlatedNotifications	{2 9 3 2 7 12}	SET OF INTEGER	c:m		
								1.1.4.2	sourceObjectInst	-	ObjectInstance	c:m		
								1.1.5	additionalText	{2 9 3 2 7 7}	GraphicString	c:m		
1.1.6	additionalInformation	{2 9 3 2 7 6}	SET OF SEQUENCE	c:m										
2	"Rec. X.721 ISO/IEC 10165-2 : 1992". objectDeletion	{2 9 3 2 10 7}		c4				2.1	ObjectInfo		Information Syntax SEQUENCE	c4		
								2.1.1	sourceIndicator	{2 9 3 2 7 26}	ENUMERATED	c:m		
								2.1.2	attributeList	{2 9 3 2 7 9}	SET OF Attribute	c:m		
								2.1.3	notificationIdentifier	{2 9 3 2 7 16}	INTEGER	c:m		
								2.1.4	correlatedNotifications	{2 9 3 2 7 12}	SET OF SEQUENCE	c:m		
								2.1.4.1	correlatedNotifications	{2 9 3 2 7 12}	SET OF INTEGER	c:m		
								2.1.4.2	sourceObjectInst	-	ObjectInstance	c:m		
								2.1.5	additionalText	{2 9 3 2 7 7}	GraphicString	c:m		
2.1.6	additionalInformation	{2 9 3 2 7 6}	SET OF SEQUENCE	c:m										
3	"Rec. X.721 ISO/IEC 10165-2 : 1992". stateChange	{2 9 3 2 10 14}		c5				3.1	StateChangeInfo		Information Syntax SEQUENCE	c5		
								3.1.1	sourceIndicator	{2 9 3 2 7 26}	ENUMERATED	c:m		
								3.1.2	attributeIdentifierList	{2 9 3 2 7 8}	SET OF AttributeId	c:m		

Table H.8 (concluded) – Notification support

Index	Notification type template label	Value of object identifier for notification type	Constraints and values	Status	Support		Additional information	Subindex	Notification field name label	Value of object identifier of attribute type associated with field	Constraints and values	Status	Support	Additional information
					Confirmed	Nonconfirmed								
								3.1.3	stateChangeDefinition	(2 9 3 2 7 28)	SET OF SEQUENCE	c:m		
								3.1.3.1	attributeID	-	AttributeID	c:m		
								3.1.3.2	oldAttributeValue	-	ANY DEFINED BY attributeID	c:m		
								3.1.3.3	newAttributeValue	-	ANY DEFINED BY attributeID	c:m		
								3.1.4	notificationIdentifier	(2 9 3 2 7 16)	INTEGER	c:m		
								3.1.5	correlatedNotifications	(2 9 3 2 7 12)	SET OF SEQUENCE	c:m		
								3.1.5.1	correlatedNotifications	(2 9 3 2 7 12)	SET OF INTEGER	c:m		
								3.1.5.2	sourceObjectInst	-	ObjectInstance	c:m		
								3.1.6	additionalText	(2 9 3 2 7 7)	GraphicString	c:m		
								3.1.7	additionalInformation	(2 9 3 2 7 8)	SET OF SEQUENCE	c:m		

c3: if G.3/6a then m else -

c4: if G.3/7a then m else -

c5: if G.3/5a or G.3/8a then m else -

H.4.4 Actions

The supplier of a manager role implementation that claims to support the actions specified in this International Standard shall import a copy of this table and complete it.

Table H.9 – Action support

Index	Action type template label	Value of object identifier for action type	Constraints and values	Status	Support		Additional information	Subindex	Action field name label	Constraints and values	Status	Support	Additional information
					Confirmed	Nonconfirmed							
1	"CCITT Rec. X.723 (1993) ISO/IEC 10165-5 : 1994": activate	(2 9 3 5 9 0)		c6				1.1	ActionInfo	Information Syntax SET OF SEQUENCE	c6		
								1.1.1	identifier	OBJECT IDENTIFIER	c:m		
								1.1.2	significance	BOOLEAN	c:o		
								1.1.3	information	ANY DEFINED BY identifier	c:m		
								1.2	ActionReply	Reply Syntax SET OF SEQUENCE	c:m		
								1.2.1	identifier	OBJECT IDENTIFIER	c:m		
								1.2.2	significance	BOOLEAN	c:o		
								1.2.3	information	ANY DEFINED BY identifier	c:m		
2	"CCITT Rec. X.723 (1993) ISO/IEC 10165-5 : 1994": deactivate	(2 9 3 5 9 1)		c7				2.1	ActionInfo	Information Syntax SET OF SEQUENCE	c7		
								2.1.1	identifier	OBJECT IDENTIFIER	c:m		
								2.1.2	significance	BOOLEAN	c:o		
								2.1.3	information	ANY DEFINED BY identifier	c:m		
								2.2	ActionReply	Reply Syntax SET OF SEQUENCE	c:m		
								2.2.1	identifier	OBJECT IDENTIFIER	c:m		
								2.2.2	significance	BOOLEAN	c:o		
								2.2.3	information	ANY DEFINED BY identifier	c:m		

c6: if G.3/2a then m else -

c7: if G.3/3a then m else -

H.4.5 Parameters

The supplier of a manager role implementation that claims to support the parameters specified in this International Standard shall import a copy of this table and complete it.

Table H.10 – Parameter support

Index	Parameter template label	Value of object identifier for parameter	Constraints and values	Status	Support	Additional information
1	constraintViolation	{SIS.pro constraint Violation(10)}	SPECIFIC-ERROR neighbourSNPAddress	c8		"The specific error returned on failure of a REPLACE operation when the MO prohibits such operations under certain conditions, for example while the MO is in the disabled operational state"

c8: if H.1/7a or H.1/7b or H.1/7c or H.1/7f then m else -

IECNORM.COM: Click to view the full PDF of ISO/IEC 10589:1992/Amd1:1996
 WithoutAMM

Annex I (normative)

MOCS proforma¹⁾

I.1 Introduction

The purpose of this MOCS proforma is to provide a mechanism for a supplier of an implementation of a International Standard which claims conformance to a managed object class, to provide conformance information in a standard form.

I.1.1 Instructions for completing the MOCS proforma to produce a MOCS²⁾

The MOCS proforma contained in this annex is comprised of information in tabular form, in accordance with ITU-T Rec X.724 | ISO/IEC 10165-6. The supplier of the implementation shall state which items are supported in tables below and if necessary provide additional information.

I.1.2 Symbols, abbreviations and terms

The MOCS proforma contained in this Annex is comprised of information in tabular form, in accordance with CCITT Rec. X.291 | ISO/IEC 9646-2.

The notations used in the Status and Support columns are specified in G.1.3.

I.2 Adjacency managed object

I.2.1 Statement of conformance to the managed object class

Table I.1 – adjacency Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	adjacency	{2 13 0 1 3 1}		

If the answer to the actual class question in the managed object class support table is no, the supplier of the implementation shall fill in the actual class support table below.

Table I.2 – adjacency Actual class support

Index	Managed object class template for actual class	Value of object identifier for managed object class definition of actual class	Additional information

¹⁾ Users of this International Standard may freely reproduce the PICS proforma in this Annex so that it can be used for its intended purpose, and may further publish the completed PICS.

²⁾ Instructions for MOCS proforma are specified in ITU-T Rec. X.724 | ISO/IEC 10165-6.

I.2.2 Packages

The supplier of the implementation shall state whether or not the packages specified by this managed object of this class are supported, in Table I.3.

Table I.3 – adjacency Package support

Index	Package template label	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphicPackage	{2 9 3 2 4 17}	"if an object supports allomorphism"	c1		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": packagesPackage	{2 9 3 2 4 16}	"any registered package, other than this package has been instantiated"	c2		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": topPackage	-	Mandatory	m		
4	"ISO/IEC 10589 : 1993": adjacency-P	-	Mandatory	m		
5	"ISO/IEC 10589 : 1992": iSAdjacency	{2 13 0 1 4 9}	"the adjacency is to an IS"	o		
6	"ISO/IEC 10589 : 1992": broadcastISAdjacency-P	{2 13 0 1 4 20}	"the parent Linkage MO is of type broadcast and is to an IS as above"	o		

c1: if I.1/1b then - else m

c2: if I.3/1a then m else -

I.2.3 Attributes

The supplier of the implementation shall state whether or not the attributes specified by all of the packages instantiated in a managed object of this class are supported, in the Support and Additional information columns of Table I.4. The supplier of the implementation shall indicate support for each of the operations for each attribute supported.

Table I.4 – adjacency managed object Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorpha	{2 9 3 2 7 50}	SET OF ObjectClass	c3		c7		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	c4		m		x		-		-		x		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	c5		m		x		-		-		x		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c6		c9		c8		c8		c8		c8		
5	"ISO/IEC 10589": adjacencyId	{2 13 0 1 7 77}	GraphicString	c4		m		x		-		-		x		
6	"ISO/IEC 10589": adjacencyState	{2 13 0 1 7 78}	ISIS.AdjacencyState	c10		m		c12		-		-		c12		
7	"ISO/IEC 10589": neighbourSNPAAAddress	{2 13 0 1 7 79}	ISIS.ANPAAAddress	c11		m		c12		-		-		c12		
8	"ISO/IEC 10589": neighbourSystemType	{2 13 0 1 7 80}	ENUMERATED	c10		m		c12		-		-		c12		
9	"ISO/IEC 10589": neighbourSystemIds	{2 13 0 1 7 83}	SET OF OCTETSTRING	c11		m		c12		c12		c12		c12		
10	"ISO/IEC 10589": adjacencyUsage	{2 13 0 1 7 82}	ISIS.AdjacencyUsage	c13		m		c12		-		-		c12		
11	"ISO/IEC 10589": areaAddressesOfNeighbour	{2 13 0 1 7 84}	ISIS.AreaAddresses	c13		c14		c13		-		-		c13		
12	"ISO/IEC 10589": holdingTimer	{2 13 0 1 7 85}	timer	c13		c14		c13		-		-		c13		
13	"ISO/IEC 10589": priorityOfNeighbour	{2 13 0 1 7 86}	ISIS.IntermediateSystemPriority	c15		c16		c15		-		-		c15		

- c3: if I.3/1a then (if J.1/2a then o else x) else -
- c4: if J.1/2a then o else x
- c5: if J.1/2a then m else x
- c6: if I.3/2a then (if J.1/2a then o else x) else -
- c7: if I.3/1a then m else -
- c8: if I.3/2a then x else -
- c9: if I.3/2a then m else -
- c10: if J.1/2a and I.1/1b then x else -
- c11: if J.1/2a and I.1/1b then m else -
- c12: if I.1/1b then x else -
- c13: if I.3/5a and J.1/2a and I.1/1b then x else -
- c14: if I.3/5a then m else o
- c15: if I.3/6a and J.1/2a and I.1/1b then x else -
- c16: if I.3/6a and J.1/2a and I.1/1b then m else -

I.2.4 Notifications

Table I.5 – adjacency Notification support

Index	Notification type template label	Value of object identifier for notification type	Constraints and values	Status	Support		Additional information	Subindex	Notification field name label	Value of object identifier of attribute type associated with field	Constraints and values	Status	Support	Additional information
					Confirmed	Nonconfirmed								
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": stateChange	{2 9 3 2 10 14}		m				1.1	StateChangeInfo		Information Syntax SEQUENCE	m		
								1.1.1	sourceIndicator	{2 9 3 2 7 26}	ENUMERATED	o		
								1.1.2	attributeIdentifierList	{2 9 3 2 7 8}	SET OF AttributeId	o		
								1.1.3	stateChangeDefinition	{2 9 3 2 7 28}	SET OF SEQUENCE	m		
								1.1.3.1	attributeID	-	AttributeId	m		
								1.1.3.2	oldAttributeValue	-	ANY DEFINED BY attributeID	o		
								1.1.3.3	newAttributeValue	-	ANY DEFINED BY attributeID	m		
								1.1.4	notificationIdentifier	{2 9 3 2 7 16}	INTEGER	o		
								1.1.5	correlatedNotifications	{2 9 3 2 7 12}	SET OF SEQUENCE	o		
								1.1.5.1	correlatedNotifications	{2 9 3 2 7 12}	SET OF INTEGER	c:m		
								1.1.5.2	sourceObjectInst	-	ObjectInstance	c:o		
								1.1.6	additionalText	{2 9 3 2 7 7}	GraphicString	o		
								1.1.7	additionalInformation	{2 9 3 2 7 6}	SET OF SEQUENCE	o		
								1.1.7.1	identifier	-	OBJECT IDENTIFIER	c:m		
								1.1.7.2	significance	-	BOOLEAN	c:o		
								1.1.7.3	information	-	ANY DEFINED BY identifier	c:m		

I.2.6 Parameters

Table I.6 – adjacency Parameter support

Index	Parameter template label	Value of object identifier for parameter	Constraints and values	Status	Support	Additional information
1	constraintViolation	{(SIS.pro) constraint Violation(10)}	SPECIFIC-ERROR	m		"The specific error returned on failure of a REPLACE operation when the MO prohibits such operations under certain conditions, for example while the MO is in the disabled operational state"

I.3 Virtual adjacency managed object

I.3.1 Statement of conformance to the managed object class

Table I.7 – virtualAdjacency Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	virtualadjacency	{2 13 0 1 3 2}		

If the answer to the actual class question in the managed object class support table is no, the supplier of the implementation shall fill in the actual class support table below.

Table I.8 – virtualAdjacency Actual class support

Index	Managed object class template for actual class	Value of object identifier for managed object class definition of actual class	Additional information

F.3.2 Packages

The supplier of the implementation shall state whether or not the packages specified by this managed object of this class are supported, in Table I.9.

Table I.9 – virtualAdjacency Package support

Index	Package template label	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphicPackage	{2 9 3 2 4 17}	"if an object supports allomorphy"	c17		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": packagesPackage	{2 9 3 2 4 16}	"any registered package, other than this package has been instantiated"	c18		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": topPackage	-	Mandatory	m		
4	"ISO/IEC 10589": virtualAdjacency-P	-	Mandatory	m		

c17: if I.7/1b then - else m

c18: if I.9/1a then m else -

I.3.3 Attributes

The supplier of the implementation shall state whether or not the attributes specified by all of the packages instantiated in a managed object of this class are supported, in the Support and Additional information columns of Table I.10. The supplier of the implementation shall indicate support for each of the operations for each attribute supported.

Table I.10 – virtualAdjacency Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	c19		c20		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	x		m		x		-		-		x		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	x		m		x		-		-		x		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c21		c22		c21		c21		c21		c21		
5	"ISO/IEC 10589: 1992": networkEntityTitle	{2 13 0 1 7 88}	ISIS.NAddress	x		m		x		-		-		x		
6	"ISO/IEC 10589: 1992": metric	{2 13 0 1 7 89}	ISIS PathMetric	x		m		x		-		-				

c19: if I.9/1a then x else -

c20: if I.9/1a then m else -

c21: if I.9/2a then x else -

c22: if I.9/2a then m else -

I.4 Destination system managed object

I.4.1 Statement of conformance to the managed object class

Table I.11 – destinationSystem Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	destinationSystem	{2 13 0 13 4}		

If the answer to the actual class question in the managed object class support table is no, the supplier of the implementation shall fill in the actual class support table below.

Table I.12 – destinationSystem Actual class support

Index	Managed object class template for actual class	Value of object identifier for managed object class definition of actual class	Additional information

I.4.2 Packages

The supplier of the implementation shall state whether or not the packages specified by this managed object of this class are supported, in Table I.13.

Table I.13 – package support

Index	Package template label	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphicPackage	{2 9 3 2 4 17}	" if an object supports allomorism "	c23		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": packagesPackage	{2 9 3 2 4 16}	"any registered package. other than this package has been instantiated"	c24		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": topPackage	-	Mandatory	m		
4	"ISO/IEC 10589": destination-P	-	Mandatory	m		
5	"Rec. X.721 ISO/IEC 10165-2 : 1992": tdestinationSystem-P	-	Mandatory	m		

c23: if I.11/1b then - else m

c24: if I.13/1a then m else -

I.4.3 Attributes

The supplier of the implementation shall state whether or not the attributes specified by all of the packages instantiated in a managed object of this class are supported, in the Support and Additional information columns of Table I.14. The supplier of the implementation shall indicate support for each of the operations for each attribute supported.

Table I.14 – destinationSystem Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	c25		c26		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	x		m		x		-		-		x		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	x		m		x		-		-		x		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c27		c28		c27		c27		c27		c27		
5	"ISO/IEC 10589": defaultMetricOutputAdjancencies	{2 13 0 1 7 91}	ISIS.OutputAdjancencies	x		m		m		-		-		c29		
6	"ISO/IEC 10589": defaultMetricPathCost	{2 13 0 1 7 90}	ISIS.PathMetric	x		m		m		-		-		c29		
7	"ISO/IEC 10589": delayMetricOutputAdjancencies	{2 13 0 1 7 93}	ISIS.OutputAdjancencies	x		m		m		-		-		c29		
8	"ISO/IEC 10589": delayMetricPathCost	{2 13 0 1 7 92}	ISIS.PathMetric	x		m		m		-		-		c29		
9	"ISO/IEC 10589": errorMetricOutputAdjancencies	{2 13 0 1 7 97}	ISIS.OutputAdjancencies	x		m		m		-		-		c29		
10	"ISO/IEC 10589": errorMetricPathCost	{2 13 0 1 7 96}	ISIS.PathMetric	x		m		m		-		-		c29		
11	"ISO/IEC 10589": expenseMetricOutputAdjancencies	{2 13 0 1 7 95}	ISIS.OutputAdjancencies	x		m		m		-		-		c29		
12	"ISO/IEC 10589": expenseMetricPathCost	{2 13 0 1 7 94}	ISIS.PathMetric	x		m		m		-		-		c29		
13	"ISO/IEC 10589": networkEntityTitle	{2 13 0 1 7 88}	ISIS.NAddress	x		m		x		-		-		x		

c25: if I.13/1a then x else -

c26: if I.13/1a then m else -

c27: if I.13/2a then x else -

c28: if I.13/2a then m else -

c29: if I.11/1b then x else -

I.5 Destination area managed object

I.5.1 Statement of conformance to the managed object class

Table I.15 – destinationArea Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	destinationArea	{2 13 0 1 3 7}		

If the answer to the actual class question in the managed object class support table is no, the supplier of the implementation shall fill in the actual class support table below.

Table I.16 – destinationArea Actual class support

Index	Managed object class template for actual class	Value of object identifier for managed object class definition of actual class	Additional information

I.5.2 Packages

The supplier of the implementation shall state whether or not the packages specified by this managed object of this class are supported, in Table I.17.

Table I.17 – destinationArea Package support

Index	Package template label	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphicPackage	{2 9 3 2 4 17}	"if an object supports allomorphy"	c30		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": packagesPackage	{2 9 3 2 4 16}	"any registered package, other than this package has been instantiated"	c31		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": topPackage	-	Mandatory	m		
4	"ISO/IEC 10589": destination-P	-	Mandatory	m		
5	"ISO/IEC 10589": destinationArea-P	-	Mandatory	m		

c30: if I.15/1b then - else m

c31: if I.17/1a then m else -

I.5.3 Attributes

The supplier of the implementation shall state whether or not the attributes specified by all of the packages instantiated in a managed object of this class are supported, in the Support and Additional information columns of Table I.18. The supplier of the implementation shall indicate support for each of the operations for each attribute supported.

Table I.18 – destinationArea Attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by create		Get		Replace		Add		Remove		Set to default		Additional information
				Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	Stat us	Supp ort	
1	"Rec. X.721 ISO/IEC 10165-2 : 1992": allomorphs	{2 9 3 2 7 50}	SET OF ObjectClass	c32		c33		-		-		-		-		
2	"Rec. X.721 ISO/IEC 10165-2 : 1992": nameBinding	{2 9 3 2 7 63}	OBJECT IDENTIFIER	x		m		x		-		-		x		
3	"Rec. X.721 ISO/IEC 10165-2 : 1992": objectClass	{2 9 3 2 7 65}	ObjectClass	x		m		x		-		-		x		
4	"Rec. X.721 ISO/IEC 10165-2 : 1992": packages	{2 9 3 2 7 66}	SET OF OBJECT IDENTIFIER	c34		c35		c34		c34		c34		c34		
5	"ISO/IEC 10589": defaultMetricOutputAdjancencies	{2 13 0 1 7 91}	ISIS.OutputAdjancencies	x		m		m		-		-		c36		
6	"ISO/IEC 10589": defaultMetricPathCost	{2 13 0 1 7 90}	ISIS.PathMetric	x		m		m		-		-		c36		
7	"ISO/IEC 10589": delayMetricOutputAdjancencies	{2 13 0 1 7 93}	ISIS.OutputAdjancencies	x		m		m		-		-		c36		
8	"ISO/IEC 10589": delayMetricPathCost	{2 13 0 1 7 92}	ISIS.PathMetric	x		m		m		-		-		c36		
9	"ISO/IEC 10589": errorMetricOutputAdjancencies	{2 13 0 1 7 97}	ISIS.OutputAdjancencies	x		m		m		-		-		c36		
10	"ISO/IEC 10589": errorMetricPathCost	{2 13 0 1 7 96}	ISIS.PathMetric	x		m		m		-		-		c36		
11	"ISO/IEC 10589": expenseMetricOutputAdjancencies	{2 13 0 1 7 95}	ISIS.OutputAdjancencies	x		m		m		-		-		c36		
12	"ISO/IEC 10589": expenseMetricPathCost	{2 13 0 1 7 94}	ISIS.PathMetric	x		m		m		-		-		c36		
13	"ISO/IEC 10589": addressPrefix	{2 13 0 1 7 98}	ISIS.NAddressPrefix	x		m		x		-		-		x		

- c32: if I.17/1a then x else -
- c33: if I.17/1a then m else -
- c34: if I.17/2a then x else -
- c35: if I.17/2a then m else -
- c36: if I.15/1b then x else -

I.6 reachableAddress ["ISO/IEC 10589"]

I.6.1 Statement of conformance to the managed object class

Table I.19 – reachableAddress Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	reachableAddress	{2 13 0 1 3 8}		