

INTERNATIONAL
STANDARD

ISO/IEC
10728

First edition
1993-04-15

AMENDMENT 1
1995-12-15

**Information technology — Information
Resource Dictionary System (IRDS)
Services Interface**

AMENDMENT 1: C language binding

*Technologies de l'information — Interface de services du gestionnaire de
ressources du système d'informations (IRDS)*

AMENDEMENT 1: Liant de langage C



Reference number
ISO/IEC 10728:1993/Amd.1:1995(E)

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 10728:1993 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open systems interconnection, data management and open distributed processing*.

IECNORM.COM : Click to view the full PDF of ISO/IEC 10728:1993/Amd 1:1995

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland
Printed in Switzerland

Information technology — Information Resource Dictionary System (IRDS) Service Interface

AMENDMENT 1: C language binding

Page v

Contents

Add a new entry to the Table of Contents as follows:

"Annex C - C language binding"

Page 1

Clause 1

Add a new sentence in clause 1 paragraph 2, before the last sentence.

"A language binding for the C language is provided in annex C."

Page 5

Subclause 4.4

Add a new sentence in subclause 4.4.

"Data structures for use with the C language are defined in annex C."

Page 5

Subclause 4.5

Add a new sentence in subclause 4.5.

"C language bindings for the services are provided in annex C."

Page 71

Subclause 8.1

Amend the first sentence of the NOTE in subclause 8.1 to read:

"For the Pascal language binding specified in this clause and the C language binding specified in annex C, enumerated types are"

Page 75

Clause 9

Amend the first sentence of the second paragraph of Clause 9 to read:

"The service formats are specified in this clause using ISO standard Pascal. Alternative service formats for use with the C language are specified in annex C."

Page 105

Add a new annex C as follows:

Annex C (normative) C language binding

The IRDS Services Interface language bindings for the C language are presented in the form of a C .h file as set out in clause C.3 below.

C.1 Strategy for the Language Binding

In this binding the data names and data structures defined in clause 8 have been adhered to except where the C language does not provide an appropriate construct.

In this binding the procedure names and their parameters defined in clause 8 have been adhered to except where the C language does not provide an appropriate construct.

Macros have been used for various limits instead of const-qualified variables. Standard C requires that the length of an array be a compile-time constant integer expression and a const-qualified variable does not have this property.

Use of this language binding requires the use of a C implementation that conforms to ISO/IEC 9899:1990.

C.2 General Rules

1. Those data names in C.2 below that also appear in Clause 8 shall have the same meaning as is defined in Clause 8. The same rules for the use of separators as defined in Clause 8 shall apply.
2. The function and parameter names in C.2 below shall have the same meaning as is defined in Clause 9.
3. The Service Return Codes returned shall be those defined by Clause 9 and Annex A and they shall have the same meaning.
4. The following mappings from SQL data types to C data types have been used:

SQL DATA TYPE	C DATA TYPE	
CHARACTER	pIrdstText	/* See 8.2.1 */
CHARACTER VARYING	pIrdstText	/* See 8.2.1 */
NATIONAL CHARACTER	pIrdstText	/* See 8.2.1 */
NATIONAL CHARACTER VARYING	pIrdstText	/* See 8.2.1 */
REAL	float	
DOUBLE PRECISION	double	
FLOAT	float	
INTEGER	long	
SMALLINT	short	
NUMERIC	long	
DECIMAL	long	
DATE	IrdstDate	/* See 8.2.1 */
TIME	IrdstTime	/* See 8.2.1 */

TIMESTAMP	IrdsTimeStamp	/* See 8.2.1 */
INTERVAL	IrdsInterval	/* See 8.2.1 */

5. Every function returns an int which is to be set to the value of the NumStates field of the RetCode returned by the function.

C.3 Notes for Implementors

1. To ensure uniqueness all externally visible names start with the characters Irds.
2. For readability and because of the above requirement, many names are not unique within the first six characters of the name. Those implementors whose implementations do not support long names are to add suitable #define statements to ensure that all names are distinguished by their implementation. For example,

```
#define IrdsOpen I_O
#define IrdsOpenCursor I_OC
```

C.4 C language .h file

```
/* This file is called irds.h
 *
 * This version of this header conforms to:
 *     ISO/IEC 10728:1993 (E)
 *     IRDS Services Interface
 *
 * © Copyright ISO 1995
 */

/* Protect against multiple inclusion of the header file */
#ifndef IRDS_H
#define IRDS_H

/* Allow use by C++ Compilers */

#ifdef __cplusplus
extern "C" {
#endif

#include <stddef.h>
    /* to ensure that NULL is defined */

/* Implementor defined length limits */

/* Clause 8.1.1 */

#define IrdsNameLim    t1    /* t1 is to be replaced by an
                             implementor defined
                             value */
```

```
/* IrdsNameLim is used in 8.2.2 below */

#define IrdsVarLim      t2    /* t2 is to be replaced by an
                               implementor defined
                               value */
/* IrdsVarLim is used in 8.2.2 below */

/* Clause 8.1.2 */

#define IrdsTextLim    t3    /* t3 is to be replaced by an
                               implementor defined
                               value */

/* Note that although no use is made of IrdsTextLim in this
language
binding, it is included so that a program may refer to the
value
to test the length of a string. */

/* Clause 8.1.3 - these definitions are used in 8.2.3 below */

/* The numeric values n1, n2, n3, n4 in this clause are to be
replaced by implementor defined values. */

#define IrdsSessIdLim   n1
/* IrdsSessIdLim used in 8.2.3 below */
#define IrdsCurIdLim   n2
/* IrdsCurIdLim used in 8.2.3 below */
#define IrdsImpDicNameLen n3
/* IrdsImpDicNameLen used in 8.2.3 below */

#define IrdsKeyLen      n4
/* IrdsKeyLen used in 8.2.1 below */
```

```

/* Clause 8.1.4 Data Types */

typedef enum
{
    IrdsDataTypeChar,          /* SQL CHARACTER */
    IrdsDataTypeCharVar,     /* SQL CHARACTER VARYING */
    IrdsDataTypeNatChar,     /* SQL NATIONAL CHARACTER */
    IrdsDataTypeNatCharVar,  /* SQL NATIONAL CHARACTER VARYING */
    IrdsDataTypeReal,        /* SQL REAL */
    IrdsDataTypeDouble,     /* SQL DOUBLE PRECISION */
    IrdsDataTypeFloat,       /* SQL FLOAT */
    IrdsDataTypeInteger,     /* SQL INTEGER */
    IrdsDataTypeSmallint,    /* SQL SMALLINT */
    IrdsDataTypeNumeric,     /* SQL NUMERIC */
    IrdsDataTypeDecimal,     /* SQL DECIMAL */
    IrdsDataTypeDate,        /* SQL DATE */
    IrdsDataTypeTime,        /* SQL TIME */
    IrdsDataTypeTimestamp,   /* SQL TIMESTAMP */
    IrdsDataTypeInterval,    /* SQL INTERVAL */
    IrdsDataTypeIrdsKey      /* SQL IRDS KEY */
} IrdsDataType;

/* Clause 8.1.5 IRD Content Status Classes */

typedef enum
{
    IrdsDcsClsUcntl,         /* Uncontrolled */
    IrdsDcsClsCntl,         /* Controlled */
    IrdsDcsClsArch          /* Archived */
} IrdsDcsCls;

```

```
/* Clause 8.1.6 Close Type parameter */

typedef enum
{
    RequestIrdsCommit,          /* COMMIT      */
    RequestIrdsRollback        /* ROLLBACK    */
} IrdsCloseType;

/* Clause 8.2.1 Column data types */

typedef char * pIrdsText;
/* Note that in this language binding a pointer to a text
   string is used instead of an array of char as specified
   in the Pascal binding in Clause 8. This removes the
   length limit on text.
*/

typedef struct
{
    char Year[4];
    char Sep1;
    char Month[2];
    char Sep2;
    char Day[2];
} IrdsDate;

typedef struct
{
    char Hour[2];
    char Sep1;
    char Minute[2];
    char Sep2;
    char Second[2];
    char Sep3;
    char Fraction[3];
    IrdsTime;
} IrdsTime;

typedef struct
{
    IrdsDate    Date;
    char        SepT;
    IrdsTime    Time;
} IrdsTimestamp;
```

```
typedef struct
{
    char    Days[7];
    char    SepI;
    IrdsTime Time;
}    IrdsInterval;

typedef char IrdsKey[IrdsKeyLen];
/* IrdsKeyLen is defined in 8.1.3 above */

/* Clause 8.2.2 Object Names */

typedef char IrdsSQLName[128];
/* 128 is set by ISO/IEC 9075:1992 database
Language SQL */

typedef char IrdsName[IrdsNameLim];
/* IrdsNameLim is defined in 8.1.1 above */

typedef char IrdsVarName[IrdsVarLim];
/* IrdsVarLim is defined in 8.1.1 above */

typedef char UserId[IrdsNameLim];
/* IrdsNameLim is defined in 8.1.1 above */

/* Clause 8.2.3 Control Identifiers */

typedef char IrdsSessId[IrdsSessIdLim];
/* IrdsSessIdLim is defined in 8.1.3 above */

typedef char IrdsCurId[IrdsCurIdLim];
/* IrdsCurIdLim is defined in 8.1.3 above */

typedef char IrdsImpDicName[IrdsImpDicNameLen];
/* IrdsImpDicNameLen is defined in 8.1.3 above */

/* Clause 8.2.4 Diagnostics Area */

typedef struct
{
    char    StateClass[2];
    char    StateSubClass[3];
}    IrdsState;
/* IrdsState is used in 8.2.5 below */
```

```

typedef struct
{
    int          IrdStateSeq;
    IrdState     IrdReturnedState;
    IrdSQLName   IrdConstraintSchema;
    IrdSQLName   IrdConstraintName;
    IrdSQLName   IrdSchemaName;
    IrdSQLName   IrdTableName;
    int          IrdColumnName;
    IrdSQLName   IrdColumnName;
} IrdStateRec;
/* IrdStateRec is used in the
   Get Diagnostics Service in
   9.1.8 below */

/* Clause 8.2.5 Service Return Code */

typedef struct
{
    int          NumStates;
    IrdState     State;
} IrdRetCode;

/* Clause 8.2.6 Column List parameters */

/* In the C binding the column list actually is a list.
   In the Pascal binding the list was actually an array.
   In IrdColList the FirstColumn points to the first
   IrdSingleColSpec.
   In each IrdSingleColSpec, NextColumn points to the following
   IrdSingleColSpec and so on.

   The definition of a boolean data type is not included
   in the C language definition, but many environments
   defines one automatically. To be secure, an IrdBoolean
   is defined.
*/
typedef enum {Ird_False = 0, Ird_True = 1} Ird_Boolean;

```

```

typedef union
{
    pIrdsText          ColValText;
                        /* Note that this is a
                        pointer to text */
    double             ColValReal;
    short              ColValShortInteger;
    long               ColValLongInteger;
    IrdsDate           ColValDate;
    IrdsTime           ColValTime;
    IrdsTimestamp      ColValTimestamp;
    IrdsInterval       ColValInterval;
} IrdsDataTypeUnion;

struct IrdsSingleColSpec
{
    IrdsSQLName        ColName;
    Irds_Boolean       ColNull;
    IrdsDataType       ColType;
    IrdsDataTypeUnion  IrdsColVal;
    struct IrdsSingleColSpec* NextColumn;
};
typedef struct IrdsSingleColSpec* pIrdsSingleColSpec;

/* Note that unlike Pascal, C offers no enforcement of
the interpretation of the data type of IrdsColVal
according to the value of ColType. It is therefore
the responsibility of the client to interpret data
returned by the IRDS according to the value of ColType.
*/

typedef struct
{
    int                NumCols;
    char               StateSubClass[3];
    pIrdsSingleColSpec FirstColumn;
} IrdsColList;
typedef IrdsColList* pIrdsColList;

```

```
/* IRDS C function prototypes */

/* All functions return an int which is the value of the
   NumStates field of the RetCode returned by the function.
   See clause 8.2.5 */

/* Clause 9.1.1 Create IRD Definition Service */

int IrdsCreateIRDDefinition
(
    const UserId          IrdsUser,
    const IrdsImpDicName IrdDefName,
    IrdsSessId           CurrSessId,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.2 Drop IRD Definition Service */

int IrdsDropIRDDefinition
(
    const UserId          IrdsUser,
    const IrdsImpDicName IrdDefName,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.3 Open IRDS Service */

int IrdsOpen
(
    const UserId          IrdsUser,
    const IrdsImpDicName IrdDefName,
    const IrdsName       IrdDicName,
    const Irds_Boolean   WillUpdate,
    IrdsSessId           CurrSessId,
    IrdsRetCode*         RetCode
);
```

```
/* Clause 9.1.4 Prepare Service */

int IrdsPrepare
(
    const IrdsSessId      CurrSessId,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.5 Commit Service */

int IrdsCommit
(
    const IrdsSessId      CurrSessId,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.6 Rollback Service */

int IrdsRollback
(
    const IrdsSessId      CurrSessId,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.7 Close IRDS Service */

int IrdsClose
(
    const IrdsSessId      CurrSessId,
    const IrdsCloseType  CloseType,
    IrdsRetCode*         RetCode
);

/* Clause 9.1.8 GetDiagnostics Service */

int IrdsGetDiagnostics
(
    const IrdsSessId      CurrSessId,
    const int             StateNum,
    IrdsStateRec*        StateRec,
    IrdsRetCode*         RetCode
);
```

```
/* Clause 9.2.1 Set Context Service */

int IrdsSetContext
(
    const IrdsSessId      CurrSessId,
    const IrdsName       SessWkgSetName,
    const IrdsName       SessWkgSetVerId,
    const Irds_Boolean   WillUpdate,
    IrdsRetCode*         RetCode
);

/* Clause 9.2.2 Add Object Service */

int IrdsAddObject
(
    const IrdsSessId      CurrSessId,
    const IrdsName       ObjType,
    const IrdsCollList*  NewCols,
    IrdsRetCode*         RetCode
);

/* Clause 9.2.3 Open Cursor Service */

int IrdsOpenCursor
(
    const IrdsSessId      CurrSessId,
    const Irds_Boolean   UseContext,
    const pIrdsText      ObjSelExpr,
    const IrdsName       WkgSetName,
    const IrdsName       WkgSetVerId,
    const Irds_Boolean   FullContext,
    const Irds_Boolean   WillUpdate,
    IrdsCurId*          ObjCurId,
    IrdsRetCode*         RetCode
);
```

```
/* Clause 9.2.4 Retrieve Object Service */

int IrdsRetrieveObject
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId     ObjCurId,
    IrdsCollList*        RequestedCols,
    IrdsRetCode*         RetCode
);

/* Clause 9.2.5 Modify Object Service */

int IrdsModifyObject
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId     ObjCurId,
    const IrdsCollList*  ModifiedCols,
    IrdsRetCode*         RetCode
);

/* Clause 9.2.6 Delete Object Service */

int IrdsDeleteObject
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId     ObjCurId,
    IrdsRetCode*         RetCode
);

/* Clause 9.2.7 IrdsDeclassifyObject Object Service */

int IrdsDeclassifyObject
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId     ObjCurId,
    IrdsRetCode*         RetCode
);
```

```
/* Clause 9.2.8 IrdsReclassifyObject Object Service */
```

```
int IrdsReclassifyObject
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId      ObjCurId,
    const IrdsName        NewObjType,
    const IrdsCollList*   NewCols,
    IrdsRetCode*          RetCode
);
```

```
/* Clause 9.2.9 Close Cursor Service */
```

```
int IrdsCloseCursor
(
    const IrdsSessId      CurrSessId,
    const IrdsCurId      ObjCurId,
    IrdsRetCode*          RetCode
);
```

```
/* Clause 9.2.10 Create Working Set Service */
```

```
int IrdsCreateWorkingSet
(
    const IrdsSessId      CurrSessId,
    const IrdsName        NewWkgSetName,
    const IrdsName        NewWkgSetVerId,
    const IrdsName        NewDcs,
    const IrdsName        BasisWkgSetName,
    const IrdsName        BasisWkgSetVerId,
    const Irds_Boolean    Versionable,
    IrdsRetCode*          RetCode
);
```

```
/* Clause 9.2.11 Drop Working Set Service */
```

```
int IrdsDropWorkingSet
(
    const IrdsSessId      CurrSessId,
    const IrdsName        WkgSetName,
    const IrdsName        WkgSetVerId,
    IrdsRetCode*          RetCode
);
```

```
/* Clause 9.2.12 Modify Content Status Service */
```