
**Information technology — Digital
compression and coding of
continuous-tone still images —**

**Part 7:
Reference software**

*Technologies de l'information — Compression numérique et codage
des images fixes à modelé continu —*

Partie 7: Logiciel de référence

IECNORM.COM : Click to view the full PDF of ISO/IEC 10918-7:2021



IECNORM.COM : Click to view the full PDF of ISO/IEC 10918-7:2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier; Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by ITU-T as Rec. ITU-T T.873 (06/2021) and drafted in accordance with its editorial rules, in collaboration with Joint Technical Committee ISO/IEC JTC 1, *Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information*.

This second edition cancels and replaces the first edition (ISO/IEC 10918-7:2019), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the reference software implementations are updated to version 1.58 for reference software 1, and to version 2.0.5 for reference software 2. These versions do not include any new features, they correct implementation errors and improve the overall stability of the software.

A list of all parts in the ISO/IEC 10918 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

[IECNORM.COM](https://www.iecnorm.com) : Click to view the full PDF of ISO/IEC 10918-7:2021

CONTENTS

	<i>Page</i>
1	Scope 1
2	Normative references..... 1
3	Definitions..... 1
4	Abbreviations 1
5	Conventions 2
6	Reference software 2
6.1	Purpose..... 2
6.2	Examples of use..... 2
6.3	General..... 2
Annex A	– Unpacking and compiling reference software A 4
Annex B	– Using reference software A 5
B.1	General 5
B.2	Encoder options defining the quality of the image..... 5
B.3	Options controlling the colour space 5
B.4	Options controlling the scan generation and entropy coding..... 5
B.5	Options controlling the quantizer 6
B.6	Options controlling the subsampling of components 6
B.7	Miscellaneous options 6
B.8	Decoder options..... 6
Annex C	– Unpacking and compiling reference software B 7
Annex D	– Using reference software B 9
D.1	General..... 9
D.2	Encoder options defining the quality of the base and full image 9
D.3	Encoder options controlling the colour space 9
D.4	Encoder options controlling the scan generation and entropy coding..... 9
D.5	Encoder options controlling the DCT implementation..... 10
D.6	Encoder options controlling the subsampling of components 10
D.7	Miscellaneous encoder options 10
D.8	Decoder options controlling the choice of the inverse discrete cosine transform..... 11
D.9	Decoder options selecting the output file format 11
D.10	Decoder options controlling the rendering of the output image..... 11
D.11	Miscellaneous decoder options 12
D.12	Decompressing to pgx 12
Bibliography 13
Electronic attachment with two reference implementations of Rec. ITU-T T.81 ISO/IEC 10918-1.	

Introduction

Rec. ITU-T T.81 | ISO/IEC 10918-1 specifies the codestream format and the decoding process, and is designed primarily for compression of continuous-tone photographic content.

This Recommendation | International Standard provides reference software for Rec. ITU-T T.81 | ISO/IEC 10918-1. The software has been successfully compiled and tested on Linux and Windows operating systems and conforms to the decoder requirements set forth in Rec. ITU-T T.83 | ISO/IEC 10918-2. It has also been tested for conformance to Rec. ITU-T T.86 | ISO/IEC 10918-4 and ISO/IEC 18477-4.

Instructions for unpacking and building the software are found in Annexes A and C. Instructions for its use are listed in Annexes B and D.

IECNORM.COM : Click to view the full PDF of ISO/IEC 10918-7:2021

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – Digital compression and coding of continuous-tone still images: Reference software

1 Scope

This Specification provides reference software for the coding technology specified in Recommendation ITU-T T.81 | ISO/IEC 10918-1. While the reference implementations also provide an encoder, conformance testing of their encoding process is beyond the scope of this Specification.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. At the time of publication, the editions indicated in dated references were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

- Recommendation ITU-T T.81 (latest) | ISO/IEC 10918-1 (latest), *Information technology – Digital compression and coding of continuous-tone still images: Requirements and guidelines*.

3 Definitions

For the purposes of this Specification, the terms and definitions specified in Rec. ITU-T T.81 | ISO/IEC 10918-1 and the following apply.

3.1 codestream; JPEG file: Sequence of bytes.

3.2 pgx format; portable graphics format: Image format describing integer-based continuous-tone images.

NOTE – For the purposes of this Specification, the image format is as specified in Rec. ITU-T T.803 | ISO/IEC 15444-4.

3.3 pnm format; portable any map format: Image format describing integer-based continuous-tone images of either one or three components consisting of a header determining image dimensions and sample precision and component-interleaved image samples encoded as 8-bit or 16-bit big-endian integers.

NOTE – For a specification of the pnm format, see Bourke (1997).

3.4 R'G'B': Colour space that describes a colour by three gamma-corrected coordinates relative to three colour primaries.

3.5 upsampling: Procedure that increases the spatial or temporal sampling rate of a time-discretely sampled signal.

3.6 Y'CbCr: Colour space that describes a colour by 1 luma coordinate and 2 chroma coordinates derived from a gamma-corrected R'G'B' colour space by a linear transformation.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

DCT	Discrete Cosine Transform
DNL	Define Number of Lines
IDCT	Inverse Discrete Cosine Transform
MCU	Minimum Coded Unit
POSIX	Portable Operating System Interface

5 Conventions

Text in Times New Roman provides instructions, comments or details for the reader.

Text in Courier New indicates program input or output as necessary to either run the software or as generated by the software on the console.

6 Reference software

6.1 Purpose

The purpose of this Specification is to provide:

- a reference decoder software capable of decoding codestreams that conform to Rec. ITU-T T.81 | ISO/IEC 10918-1;
- a sample encoder software capable of producing codestreams that conform to Rec. ITU-T T.81 | ISO/IEC 10918-1.

The use of the reference software is not required to implement an encoder or decoder in conformance to Rec. ITU-T T.81 | ISO/IEC 10918-1. Requirements established in Rec. ITU-T T.81 | ISO/IEC 10918-1 take precedence over the behaviour of the reference software.

6.2 Examples of use

Some examples of use for the reference decoder software implementations are:

- as an illustration of how to perform the decoding processes specified in Rec. ITU-T T.81 | ISO/IEC 10918-1;
- as the starting basis for the implementation of a decoder that conforms to Rec. ITU-T T.81 | ISO/IEC 10918-1;
- for (non-exhaustive) testing of the conformance of a codestream (or file) to the constraints specified in Rec. ITU-T T.81 | ISO/IEC 10918-1.

NOTE 1 – The lack of detection of any conformance violation by any reference software implementation cannot be considered as a definitive proof that the codestream under test conforms to Rec. ITU-T T.81 | ISO/IEC 10918-1.

Some examples of use for reference encoder software are as:

- an illustration of how to implement an encoding process that produces codestreams that conform to Rec. ITU-T T.81 | ISO/IEC 10918-1;
- a starting point for an implementation of an encoder that conforms to Rec. ITU-T T.81 | ISO/IEC 10918-1;
- a means of generating codestreams conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1 for testing purposes;
- a means of demonstrating and evaluating examples of the quality that can be achieved by an encoding process that conforms to Rec. ITU-T T.81 | ISO/IEC 10918-1.

NOTE 2 – No guarantee of the quality that will be achieved by an encoder is provided by its conformance to Rec. ITU-T T.81 | ISO/IEC 10918-1, as the conformance is only defined in terms of specific constraints imposed on the syntax of the generated codestream and maximum tolerable errors of the discrete cosine transform (DCT) coefficients after reconstruction. In particular, while sample encoder software implementations could suffice to provide some illustrative examples of which quality can be achieved within Rec. ITU-T T.81 | ISO/IEC 10918-1, they provide neither an assurance of minimum guaranteed image encoding quality nor maximum achievable image encoding quality.

NOTE 3 – The computation resource characteristics in terms of program or data memory usage, execution speed, etc. of sample software encoder or decoder implementations cannot be construed as representative of the typical, minimal or maximal computational resource characteristics to be exhibited by implementations of some parts of Rec. ITU-T T.81 | ISO/IEC 10918-1.

6.3 General

The reference software implementations for Rec. ITU-T T.81 | ISO/IEC 10918-1 are available from ISO at <https://standards.iso.org/iso-iec/10918/-7/ed-2/en> and also from ITU at <https://www.itu.int/rec/T-REC-T.873/en>. Each of the two zip archives contains one reference software implementation.

- The file "referenceA.zip" contains a reference implementation for all processes of Rec. ITU-T T.81 | ISO/IEC 10918-1. Unpacking and compilation of this software is explained in Annex A. Guidance on how to use this software is given in Annex B.

- The file "referenceB.zip" contains a reference implementation for the baseline and extended Huffman and arithmetic coding DCT processes of Rec. ITU-T T.81 | ISO/IEC 10918-1. This software does not implement the lossless and hierarchical processes of Rec. ITU-T T.81 | ISO/IEC 10918-1. Unpacking and compilation of this software is explained in Annex C. Guidance on how to use this software is given in Annex D.

NOTE – In ISO ReferenceA.zip and Reference B.zip are called DIS_10918att1.zip and DIS_10918att2.zip, respectively.

IECNORM.COM : Click to view the full PDF of ISO/IEC 10918-7:2021

Annex A

Unpacking and compiling reference software A¹

(This annex does not form an integral part of this document.)

Source code of the reference software implementation is provided in a zip archive available at <https://standards.iso.org/iso-iec/10918/-7/ed-2/en>, and <https://www.itu.int/rec/T-REC-T.873/en>. Unpacking a zip file is operating system specific. Under portable operating system interface (POSIX) compliant operating systems, open a command line window and enter

```
unzip referenceA.zip
```

This will unpack all components of the software into the current directory.

To compile the software, follow these steps:

- for POSIX compliant operating systems, go to the directory into which the electronic attachment was unpacked, then enter on the command line

```
./configure  
make
```

This assumes that a POSIX compliant shell is available, and the GNU compiler (make, gcc compiler and linker) are installed on the system. The reference software will then be built in the current directory, and a binary named "jpeg" will be created.

- For Microsoft Windows, the Visual Studio VS2010 or VS2013 compiler suite provides another option for building the software. A VS2010 solution file allowing loading and compiling the project can be found in the directory "vs10.0/jpeg". A solution file for VS2013 can be found in the directory "vs12.0/jpeg".

The compiler will generate a command line tool without any graphical interface that compresses images represented in the pnm format into JPEG and expands JPEG images into pnm or pgx files. pnm-files represent one component integer grey-scale or three-component integer colour data, whereas pgx files describe non-upsampled N-component raw sample data bare any colour interpretation.

For the purpose of testing for conformance to Rec. ITU-T T.81 | ISO/IEC 10918-1, the pgx output is preferable as it includes neither a transformation from Y'C_BC_R to R'G'B' and nor an upsampling process. These processes are not formally part of Rec. ITU-T T.81 | ISO/IEC 10918-1, but have been included in later standards, such as Rec. ITU-T T.871 | ISO/IEC 10918-5, also known as JFIF, or ISO/IEC 18477-1.

¹ In the ISO distribution ReferenceA.zip is called DIS_10918att1.zip.

Annex B

Using reference software A

(This annex does not form an integral part of this Recommendation | International Standard.)

B.1 General

This annex describes the usage of the software prepared and compiled with the instructions given in Annex A.

The software can both compress images to JPEG files and expand such files back to pnm or pgx. The encoder and decoder are both contained in the same executable, named "jpeg". If a quality parameter (see clause B.2) is included on the command line, or the command line parameters request lossless coding, the executable encodes images. If only an input and an output file are provided, the software attempts to expand the input file to the output file.

The encoder requires one input image encoded in the pnm format that is to be compressed. For lossy compression, the `-q` parameter defines a quality parameter between 0 and 100. The `-p` parameter will enable lossless compression.

The command line parameters for the encoders are as follows:

```
jpeg [options] source target
```

where `options` is a set of command line options, all starting with a hyphen, `source` is the source image to be compressed, and the `target` is the output file to which the encoder writes the output codestream. Command line switches control the operations of the software. They are listed in clauses B.2 to B.8.

Decoding from a JPEG file to a ppm or pfm file requires only the input and output file name:

```
jpeg [options] source target
```

The only command line options recognized for decoding are `-c` and `-U`, which are described in subclause B.3.

B.2 Encoder options defining the quality of the image

The following options control the quality of the encoded images.

`-q quality` selects the encoding mode and defines the quality of the base image

B.3 Options controlling the colour space

The following options control how out of gamut colours and gamut extension is handled:

`-c` inserts a marker into the codestream that signals that the transformation from $Y'C_B C_R$ to $R'G'B'$ is disabled by the decoder

NOTE – Colour space interpretation and specifically the usage of this marker is beyond the scope of Rec. ITU-T T.81 | ISO/IEC 10918-1 and is further specified in Rec. ITU-T T.871 | ISO/IEC 10918-5 and ISO/IEC 18447-1.

B.4 Options controlling the scan generation and entropy coding

The following parameters control the entropy coding and generation of scan patterns for JPEG scans. Especially the `-h` parameter (optimize Huffman tables) is recommended, and for most configurations even necessary as Rec. ITU-T T.81 | ISO/IEC 10918-1 does not provide for all modes examples for tables the encoder could choose.

`-h` optimize the Huffman tables

`-v` use progressive instead of sequential encoding

`-p` use the lossless (predictive) mode of Rec. ITU-T T.81 | ISO/IEC 10918-1

`-y N` use hierarchical coding with N hierarchical layers. If N is 0, a two-scan hierarchical process is initiated of which the first scan is a DCT process and the second hierarchical scan is a lossless coding process

- a selects arithmetic coding instead of Huffman coding. Can be combined with -v, -p and -y

B.5 Options controlling the quantizer

The following parameters control the quantizer:

- qt n defines the quantization table
The following tables are defined:
 - n = 0 the example tables from Rec. ITU-T T.81 | ISO/IEC 10918-1 (default)
 - n = 1 a completely flat table that should be PSNR-optimal
 - n = 2 a MS-SSIM (see Wang *et al.* (2003)) optimized table
 - n = 3 the table suggested by ImageMagick
 - n = 4 an HSV-PSNR optimized table
 - n = 5 the table from Klein *et al.* (1992)
 - n = 6 the table from Watson *et al.* (1997)
 - n = 7 the table from Ahumada and Peterson (1993)
 - n = 8 the table from Peterson *et al.* (1993)
- dz enables a deadzone quantizer which replaces the default uniform quantizer

B.6 Options controlling the subsampling of components

The following parameters control the subsampling of components. Unlike other implementations, this software does not specify the subsampling by means of the minimum coded unit (MCU) sizes, but directly by giving the subsampling factors. By default, the software uses 4:4:4 sampling. 4:2:0 chroma subsampling is, for example, defined by the parameters -s 1x1, 2x2, 2x2, 4:2:2 subsampling by -s 1x1, 2x1, 2x1.

- s WxH, ... define subsampling factors for all components

NOTE – The arguments to -s are not MCU sizes.

B.7 Miscellaneous options

The following options control miscellaneous encoder options.

- z mcus defines the restart interval size, if the argument is 0, restart markers are disabled
- n signals the image height by a define number of lines (DNL) marker instead of writing the image height into the frame header

B.8 Decoder options

The following options control the decoding process.

- c disables the transformation from Y'C_BC_R to R'G'B'

NOTE – This transformation is not part of Rec. ITU-T T.81 | ISO/IEC 10918-1 but has been specified in Rec. ITU-T T.871 | ISO/IEC 10918-5.

- U writes the output in pgx format rather than pnm format and disables upsampling of components and the transformation from Y'C_BC_R to R'G'B'
Neither upsampling nor this transformation are formally part of the Rec. ITU-T T.81 | ISO/IEC 10918-1 process and hence should be disabled for the purpose of conformance testing with Rec. ITU-T T.83 | ISO/IEC 10918-2.

Annex C

Unpacking and compiling reference software B²

(This annex does not form an integral part of this Recommendation | International Standard.)

The source code of the software is provided in a zip archive available at <https://standards.iso.org/iso-iec/10918/-7/ed-2/en> and <https://www.itu.int/rec/T-REC-T.873/en>. Unpacking a zip file is operating system specific. Under POSIX compliant operating systems, open a command line window and enter

```
unzip referenceB.zip
```

This will unpack all components of the software into the current directory.

To compile the software, follow these steps:

- In order to compile a command line tool that supports the 8 bit baseline, sequential and progressive DCT coding modes on POSIX compliant operating systems, go to the directory into which the electronic attachment was unpacked, then enter on the command line

```
cmake .
make
make -f Makefile-pgx
```

The following tools are required for successful building:

- a POSIX compliant shell
- CMake 2.8.12 (Kitware (Internet-1))
- The GNU compiler (make, gcc compiler and linker)
- The NASM assembler (NASM Development Team (Internet)) or Yasm assembler (Yasm (Internet))

The reference software will then be built in the current directory consisting of two binaries, the encoder "cjpeg" and the decoder "djpeg", and a compliance-testing enabled decoder "djpegtopgx". The binaries created this way will be only capable of encoding and decoding to the 8 bit sequential or progressive DCT modes.

- In order to compile binaries that support the 12 bit sequential and progressive Huffman-coded DCT modes, enter the following sequence of commands on the command line:

```
cmake -D WITH_12BIT=1 .
make
make -f Makefile-pgx
```

NOTE – The supplied software cannot be built in such a way that both 8 bit and 12 bit modes are supported simultaneously by the same executable.

- For Microsoft Windows, the following tools are required to build the software:
 - The Visual Studio VS2008, VS2010 or VS2013 compiler suite
 - CMake 2.8.12 (Kitware (Internet-1))

The following steps need to be performed to compile the software:

- Generate a Visual Studio project file for building the tool, which can be done either through the CMake graphical user interface or from the command line. For the latter, go to the directory into which sources have been unpacked, then enter

```
cmake -G "Visual Studio 10 2010" .
```

where the argument behind `-G` needs to be adapted to the target version of Visual Studio. For a list of supported platforms, see Kitware (Internet-2).

The command in the previous paragraph will generate suitable project files in the current directory that can be opened directly from the Visual Studio IDE. Details of the building procedure can be found in the file BUILDING.md in the source directory of the software.

² In the ISO distribution ReferenceB.zip is called DIS_10918att2.zip.

ISO/IEC 10918-7:2021 (E)

- Open the Visual Studio project file generated by the step in the previous paragraph from the graphical user interface and rebuild the software from the menu.
- The compiler will generate two command line tools: "cjpeg" will compress images represented in pnm (Picture AnyMap) into JPEG; and "djpeg" expands JPEG and JPEG XT part 1 images into pnm-files.

IECNORM.COM : Click to view the full PDF of ISO/IEC 10918-7:2021

Annex D

Using reference software B

(This annex does not form an integral part of this Recommendation | International Standard.)

D.1 General

This annex describes the usage of the software prepared and compiled with the instructions given in Annex C.

The compilation process results in three executables. The "cjpeg" executable compresses pnm files into JPEG files, the "djpeg" file expands JPEG files into pnm files and the "djpegtopgx" files expands JPEG files into pgx files. Depending on the build process, the executables will either support the 8 bit or the 12-bit DCT modes of Rec. ITU-T T.81 | ISO/IEC 10918-1. There is no integrated version of the software that supports both the 8 bit and the 12-bit modes from the same executable.

The encoder "cjpeg" requires a single input image encoded in the pnm format and compresses its input stream to a JPEG file on its output stream, with the `-quality` option controlling approximately the quality and, through that, the byte size of the generated stream.

```
cjpeg [options] <source >target
```

where `options` is a set of command line options, all starting with a hyphen, `source` is the source image to compressed, and the `target` is the output file to which the encoder writes its output. Command line switches control the operations of the software.

Decoding from a JPEG file to a ppm file requires the "djpeg" decoder to be called as follows:

```
djpeg [options] <source >target
```

NOTE – In this command line, the angle brackets are part of the input/output redirection of the operating system. Without them, "djpeg" reads from the input stream and writes to the output stream.

Decoding from a JPEG file to a pgx file requires the "djpegtopgx" decoder to be called as follows:

```
djpegtopgx source target
```

The `djpegtopgx` decoder does not take any command line options beyond the compressed stream and output file.

D.2 Encoder options defining the quality of the base and full image

The following options of the `cjpeg` command control the quality of the encoded images:

`-q quality` defines the quality of the image, where the `quality` parameter is a number between 0 and 100, where 0 indicates the lowest and 100 the highest quality

D.3 Encoder options controlling the colour space

The following options of the `cjpeg` command control the colour space:

`-grayscale` creates monochrome JPEG files

`-rgb` Includes a marker in the codestream that instructs the decoder to disable the $Y'_{CB}C_R$ to R'_{GB} transformation, and the encoder encodes the source image data directly in R'_{GB} space without a conversion to $Y'_{CB}C_R$. This marker and the corresponding transformation between R'_{GB} and $Y'_{CB}C_R$ is not part of Rec ITU-T T.81 | ISO/IEC 10918-1, but has been specified in Rec. ITU-T T.871 | ISO/IEC 10918-5 and ISO/IEC 18477-1.

D.4 Encoder options controlling the scan generation and entropy coding

The following command line parameters of the `cjpeg` command control the entropy coding process.

ISO/IEC 10918-7:2021 (E)

- optimize optimizes the Huffman tables instead of using the example Huffman tables from Rec. ITU-T T.81 | ISO/IEC 10918-1
- progressive use the progressive rather than sequential process for encoding data
- arithmetic use arithmetic coding rather than Huffman coding. Can be combined with -progressive
- baseline enforce that quantization parameters follow the more restrictive baseline Huffman process rather than the (extended) sequential process

D.5 Encoder options controlling the DCT implementation

The following `cjpeg` command line parameters control the choice of the DCT implementation.

- dct int use an integer-based DCT process
- dct fast use a fast, less accurate DCT process

NOTE – While this DCT process conforms to Rec. ITU-T T.83 | ISO/IEC 10918-2, it is not sufficiently accurate to pass the conformance requirements of ISO/IEC 18477-1.

- dct float use a floating-point based DCT process

D.6 Encoder options controlling the subsampling of components

The following `cjpeg` command line parameters control the subsampling of components.

- sample HxV, [HxV, [...]] Set the component MCU sizes. If only a single MCU size is given, this applies to the luma component only and all other MCU sizes are 1x1. The default is 4:2:0 subsampling, which is identical to the command line option `-sample 2x2`.

Unlike reference software A, the parameters define the MCU sizes, not the subsampling factors derived from them. For 4:4:4 sampling, set all MCU sizes to 1x1. Since chroma MCU sizes default to 1x1, this is identical to the command line parameter `-sample 1x1`. For 4:2:0 subsampling, the MCU sizes of the first component are 2x2, and 1x1 for the second and third component. Due to the default MCU sizes for the chroma components, the command line argument `-sample 2x2` is sufficient to enable 4:2:0 subsampling. Similarly, 4:2:2 subsampling is requested with `-sample 2x1`.

D.7 Miscellaneous encoder options

- targa use the targa format instead of the pnm image format for the input images
- restart N insert every N MCUs a restart marker into the codestream
- smooth N smooth dithered input prior to compression where N is a smoothing strength between 1 and 100
- maxmemory N Specify how much memory the encoder may allocate at most, where N is given in kilobytes
- outfile name write to the given output file name instead of the standard output of the command
- memdst write to memory instead of a file (useful for benchmarking)
- verbose generate debug output
- debug generate debug output, identical to `-verbose`
- version print version information and exit immediately
- qtables name read the quantization table from a given file rather than using the example tables from Rec. ITU-T T.81 | ISO/IEC 10918-1
- qslots N[N, [...]] define the quantization table slots per component