
**Information technology — Coding of
audio-visual objects —**

Part 11:

Scene description and application engine

AMENDMENT 7: ExtendedCore2D profile

Technologies de l'information — Codage des objets audiovisuels —

Partie 11: Description de scène et moteur d'application

AMENDEMENT 7: Profil ExtendedCore2D

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

ISO/IEC NORM.COM : Click to view the full PDF of ISO/IEC 14496-11:2005/Amd 7:2010



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 7 to ISO/IEC 14496-11:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

IECNORM.COM : Click to view the full PDF of ISO/IEC 14496-11:2005/Amd 7:2010

Information technology — Coding of audio-visual objects —

Part 11: Scene description and application engine

AMENDMENT 7: ExtendedCore2D profile

In 7.2, add the following subclauses in node alphabetical order:

7.2.2.ZZ CacheTexture

7.2.2.ZZ.1 Node interface

CacheTexture {			
Field	SFInt32	objectTypeIndication	0
Field	SFString	decoderSpecificInfo	NULL
Field	SFString	image	NULL
Field	SFString	cacheURL	NULL
Field	MFURL	cacheOD	[]
Field	SFInt32	expirationDate	0
Field	SFBool	repeatS	TRUE
Field	SFBool	repeatT	TRUE
}			

NOTE For the binary encoding of this node see node coding tables in electronic attachment.

7.2.2.ZZ.2 Functionality and semantics

The CacheTexture allows carriage of visual data embedded inside the BIFS stream rather than using the OD framework. The **objectTypeIndication** field identifies the media type of the visual data. The compressed data is carried in the **image** field, as a single access unit. If a decoder configuration is needed, it may be carried in the **decoderSpecificInfo** field. The node can be used as a texture object in an **Appearance** node. The node can also be used in as a child node of a 2D or 3D container when it is only used for image caching. Additionally, the CacheTexture node allows for caching the embedded image by specifying a **cacheURL** name to be referred to by other nodes in the scene, as well as an **expirationDate** indicating the time in seconds the terminal should keep the data in its cache. If **expirationDate** is 0, the data shall not be cached. If **expirationDate** is strictly negative, the data should be cached for as long as possible. In any case, whether the data is cached or not is implementation specific.

The **cacheOD** field identifies an existing OD in the scene to be cached with the given **cacheName** and **expirationDate**. If **cacheOD** is set, **image**, **decoderSpecificInfo** and **objectTypeIndication** shall be ignored. Results are undefined if the OD indicated by the **cacheOD** is not a still image object such as JPEG or PNG.

The scoping of the CacheTexture node shall be done at the service level (same broadcast channel or same service URL of the initial scene). Sub-scenes opened through inline nodes are part of the same caching scope as the parent scene.

Example of cache usage

```
Shape {
  appearance Appearance {
    texture ImageTexture {
      url "some_cache_url_name"
    }
  }
}
...
CacheTexture {
  objectTypeIndication 0x6D
  image ...
  cacheURL "some_cache_url_name"
  expirationDate 3600 //one hour caching
}
....
```

7.2.2.ZZ EnvironmentTest

7.2.2.ZZ.1 Node interface

```
EnvironmentTest {
  eventIn          SFBool
  exposedField     SFBool
  exposedField     SFInt32
  exposedField     SFString
  exposedField     SFBool
  eventOut         SFBool
  eventOut         SFBool
  eventOut         SFBool
  eventOut         SFString
  evaluate         SFBool
  enabled          TRUE
  parameter        0
  compareValue     NULL
  evaluateOnChange TRUE
  valueLarger
  valueEqual
  valueSmaller
  parameterValue
}
```

NOTE For the binary encoding of this node see node coding tables in electronic attachment.

7.2.2.ZZ.2 Functionality and semantics

The EnvironmentTest node enables testing a **parameter** of the terminal environment, possibly comparing their values with the **compareValue**. The evaluation of the parameter triggers different eventOuts depending on the type of the parameter:

- If the **parameter** type is Boolean, the evaluation triggers a **valueEqual** eventOut, and the **compareValue** field is ignored.
- If the **parameter** type is a number and the **compareValue** represents a number, the two values are compared and the following eventOuts are generated:
 - **valueEqual** if **parameter** and **compareValue** are equal
 - **valueLarger** if **compareValue** is strictly larger than **parameter**
 - **valueSmaller** if **compareValue** is strictly less than than **parameter**

The supported parameter types are defined in Table AMD7.1.

In any case, the **parameterValue** eventOut is triggered after evaluation.

If **evaluateOnChange** is set to FALSE, the node only evaluates upon receiving the **evaluate** eventIn; otherwise, the node evaluates on any change of **parameter** or **compareValue**.

The node evaluates and triggers events only when its **enabled** field is true.

Table AMD7.1 — Environmental parameters

Value	Definition	Type
0	Display region Aspect Ratio (larger dimension divided by smaller dimension, regardless of screen orientation)	Float
1	Portrait mode of the display region (TRUE if width<height)	Boolean
2	Display region width in pixels	Integer
3	Display region height in pixels	Integer
4	Horizontal DPI	Integer
5	Vertical DPI	Integer
6	Automotive Situation (terminal user drives a moving vehicle)	Boolean
7	User is Visually Challenged	Boolean
8	Touch Screen present on terminal	Boolean
9	Navigation Keypad present on terminal	Boolean
0x00000007-0xEEFFFFFF	ISO Reserved	
0xF0000000-0xFFFFFFFF	User Reserved	

The display region is the area onto which the BIFS content is rendered. This region may be the entire screen, some part of the screen or an off-screen memory region.

7.2.2.ZZ KeyNavigator

7.2.2.ZZ.1 Node interface

```

KeyNavigator {
  eventIn          SFBool          setFocus
  exposedField     SFNode          sensor           NULL
  exposedField     SFNode          left             NULL
  exposedField     SFNode          right            NULL
  exposedField     SFNode          up                NULL
  exposedField     SFNode          down              NULL
  exposedField     SFNode          select            NULL
  exposedField     SFNode          quit              NULL
  exposedField     SFFloat         step              0
  eventOut         SFBool          focusSet
}

```

NOTE For the binary encoding of this node see node coding tables in electronic attachment.

7.2.2.ZZ.2 Functionality and semantics

The KeyNavigator node enables simple, pre-defined 2D navigation in the scene. Each KeyNavigator is associated with an existing sensor node (TouchSensor, PlaneSensor2D...) through the **sensor** field. The first KeyNavigator node found in the scene is used to determine the initial focusable object. If the attached **sensor** node is NULL or is disabled, the focus is not attached to any visual part of the scene. Focus can be changed by using the navigation pad of the terminal as follows:

- Pressing the left key will move focus to the **left** KeyNavigator node
- Pressing the right key will move focus to the **right** KeyNavigator node
- Pressing the up key will move focus to the **up** KeyNavigator node
- Pressing the down key will move focus to the **down** KeyNavigator node
- Pressing the validation key (OK, Enter, Select...) will move focus to the **select** KeyNavigator node

- Pressing the escape key (escape, back, end call...) will move focus to the **quit** KeyNavigator node
- At any time, a KeyNavigator can be focused by sending the node a **setFocus** eventIn.

Whenever a KeyNavigator node receives the focus, it triggers a **focusSet = true** eventOut. When the KeyNavigator node loses the focus, it triggers a **focusSet = false** eventOut.

A pointing device sensor is controlled through the keypad as indicated in Table AMD7.2, with directions given in the local coordinate system of the sensor node. Processing of keystrokes by the KeyNavigator node is inhibited while the sensor is active.

NOTE The attribution of keys for activation and deactivation of the associated sensor is implementation specific.

The **step** field indicates the horizontal or vertical mouse displacement to simulate when using directional keys, and indicates the displacement in the sensor local coordinate system. If the value of **step** is less than or equal to 0, the mouse displacement is implementation specific.

Table AMD7.2 — Mapping of keys for BIFS sensor nodes

Sensor Type	focusIn	focusOut	LEFT	RIGHT	UP	DOWN
TouchSensor	isOver=true	isOver=false	N/A	N/A	N/A	N/A
PlaneSensor2D	N/A	N/A	Left move	Right move	up move	Down move
DiscSensor	N/A	N/A	Counter clockwise move	Clockwise move	N/A	N/A
PlaneSensor	N/A	N/A	Left move	Right move	up move	Down move
CylinderSensor	N/A	N/A	Counter clockwise move	Clockwise move	N/A	N/A
SphereSensor	N/A	N/A	I/S	I/S	I/S	I/S

N/A: Non-Applicable - I/S: Implementation Specific.

NOTE 1 Authors should be aware that when activating a TouchSensor node, the focus might automatically be moved to the **select** field of the associated key navigator.

NOTE 2 A terminal handling both key navigation and pointing device should automatically manage the active KeyNavigator node. When the pointing device moves over an active sensor associated with a KeyNavigator node, this KeyNavigator node should become the current focused KeyNavigator node.

NOTE 3 A terminal should trigger the key events on key down and handle key repeat, when the key is not released for some period of time.

7.2.2.ZZ Storage

7.2.2.ZZ.1 Node interface

```
Storage {
    eventIn          SFBool          forceSave
    eventIn          SFBool          forceRestore
    exposedField    SFBool          auto           TRUE
    Field            SFInt32         expireAfter  0
    Field            SFString        name          NULL
    Field            MFAttrRef       storageList  []
}
```

NOTE For the binary encoding of this node see node coding tables in electronic attachment.

7.2.2.ZZ.2 Functionality and semantics

The Storage node enables saving and restoring any field values in a scene to a private storage zone of the terminal. The **name** parameter allows defining several storage zones in a single scene. The terminal should keep the stored value for the number of seconds indicated in the **expireAfter** field, or for an undetermined period of time, up to the implementation, if this value is less than or equal to zero. The scoping of the Storage

node shall be done at the service level (e.g., same broadcast channel or same service URL of the initial scene). Sub-scenes opened through inline nodes are part of the same storage scope as the parent scene. In a same service, there shall not be more than one storage node with a given name field.

The set of node fields to be saved or restored is specified in the **storageList** field. Conceptually, saving node fields is equivalent to remembering the number of fields, their types and their values, and restoring is the opposite operation. This allows saving and restoring of node fields independently from node IDs which may vary across different scenes. The target field shall be an SF or an MF field with an underlying SF type equal to SFBool, SFInt32, SFFloat, SFTime, SFString, SFVec3f, SFVec2f, SFColor, and SFRotation. For complexity reasons, storing and restoring of SFNode/MFNode, SFImage/MFImage and SFCommandBuffer fields are not allowed.

Results are undefined if the target field types do not match between the save and the restore operations.

If **auto** is TRUE, then the terminal restores the information after decoding of the Storage object, and saves the information upon exiting the scene. If **auto** is FALSE, the terminal saves the node field values when the eventIn **forceSave** is triggered, and restores them when the eventIn **forceRestore** is triggered.

In 7.2.2.74.2, add the following:

If the major mode in the justify field of the layout is "JUSTIFY", then the layout of children starts at the "BEGIN" edge of the layout and ends at the "END" edge of the layout with space adjustments if needed. "BEGIN" and "END" are defined in the FontStyle node semantics. If wrap is false and the line is larger than the layout frame, the terminal may alter the text to indicate it has been truncated.

At the end of 7.2.2.135.2 before the final example, add the following:

If the eventIn is inMFString then the outSFString eventOut shall be created by using the first element of inMFString input if the "Sum" field is set to "false", or the concatenation of all strings in the inMFString input if the "Sum" field is set to "true". In this special case, FactorX and OffsetX fields are ignored.

In 7.9.2.3, replace Table 41 with the following:

Scene Graph Tools	Scene Graph Profiles									
	Basic 2D	Simple 2D	Core 2D	Extended Core 2D	Main 2D	Advanced 2D	Complete 2D	Audio	3D Audio	Complete
AcousticScene									X	
AdvancedAudioBuffer										
AnimationStream						X	X		X	X
Anchor			X	X	X	X	X		X	X
ApplicationWindow										
AudioBuffer						X	X	X	X	X
AudioDelay							X	X	X	X
AudioFX							X	X	X	X
AudioMix							X	X	X	X
AudioSwitch						X	X	X	X	X
Billboard									X	X
BitWrapper										
CacheTexture				X						
Clipper2D										
ColorInterpolator			X	X	X	X	X			X
ColorTransform										
Collision										X
CompositeTexture2D				X			X			X
CompositeTexture3D										X
Conditional			X	X	X	X	X		X	X
CoordinateInterpolator2D			X	X	X	X	X			X
CoordinateInterpolator									X	X
CoordinateInterpolator4D										
CylinderSensor										X
DirectiveSound									X	
DiscSensor					X	X	X			X
EnvironmentTest				X						
Form							X			X
Group						X	X	X	X	X
Inline			X	X	X	X	X		X	X
InputSensor			X	X	X	X				
KeyNavigator				X						
Layer2D				X	X	X	X			X
Layer3D										X
Layout				X			X			X
ListeningPoint							X	X	X	X
LOD									X	X
MediaBuffer						X				
MediaControl			X	X	X	X				
MediaSensor			X	X	X	X				
NavigationInfo										X
NormalInterpolator										X
OrderedGroup	X	X	X	X	X	X	X			X

Scene Graph Tools	Scene Graph Profiles									
	Basic 2D	Simple 2D	Core 2D	Extended Core 2D	Main 2D	Advanced 2D	Complete 2D	Audio	3D Audio	Complete
OrientationInterpolator									X	X
PathLayout										
PerceptualParameters									X	
PlaneSensor2D					X	X	X			X
PlaneSensor										X
PositionAnimator										
PositionAnimator2D										
PositionInterpolator									X	X
PositionInterpolator2D			X	X	X	X	X			X
PositionInterpolator4D										
ProximitySensor									X	X
ProximitySensor2D					X	X	X			X
QuantizationParameter			X	X	?	X	X		X	X
ScalarAnimator										
ScalarInterpolator			X	X	X	X	X			X
Script						X			X	X
ServerCommand			X	X	X	X				
Sound								X	X	X
Sound2D	X	X	X	X	X	X	X		X	X
SphereSensor										X
Storage				X						
Switch			X	X	X	X	X		X	X
TemporalTransform					X	X				
TemporalGroup					X	X				
TermCap						X	X		X	X
TimeSensor			X	X	X	X	X		X	X
TouchSensor			X	X	X	X	X		X	X
Transform									X	X
Transform2D		X	X	X	X	X	X			X
Transform3DAudio										
TransformMatrix2D				X						
Valuator			X	X	X	X	X		X	X
Viewpoint									X	X
Viewport				X						
VisibilitySensor									X	X
WorldInfo				X		X	X		X	X
Node Update			X	X	X	X	X		X	X
Route Update			X	X	X	X	X		X	X
Scene Update		X	X	X	X	X	X	X	X	X
ROUTE			X	X	X	X	X		X	X
PROTO				X		X				
Extended Updates				X						
Interpolator Compression										
PredictiveMF coding						X				

NOTE Extended Updates comprise the following scene updates: PROTOlist, PROTOlistDeletion, removal of all protos, MultipleIndexedFieldReplacement, MultipleFieldReplacement, GlobalQuantizationConfiguration, NodeDeletionEx, ExtendedReplace, ReplaceFromExternalData, ReplaceToExternalData.

In 7.9.2.4, Table 44, replace the line:

0x14-0x7F	reserved for ISO use	-
-----------	----------------------	---

with the lines:

0x14	ExtendedCore2D	L1
0x15-0x7F	reserved for ISO use	-

In 7.9.2.4, add the following new subclause:

7.9.2.4.10 Levels for the ExtendedCore2D Scene Graph Profile

7.9.2.4.10.1 Functionalities provided

The ExtendedCore2D Scene Graph profile comprises all Core 2D Scene Graph functionalities. The ExtendedCore2D Scene Graph profile allows in addition: advanced 2D composition, advanced local interaction.

7.9.2.4.10.2 Level 1

The following restrictions apply for the XCore2D Scene Graph Profile at Level 1:

Table AMD7.3 — Restrictions for ExtendedCore2D Scene Graph Profile at Level 1

Nodes	Restrictions
Anchor	<i>addChildren</i> and <i>removeChildren</i> not supported 31 <i>children</i> maximum allowed
AudioClip	<i>pitch</i> , <i>description</i> ignored
AudioSource	<i>addChildren</i> , <i>removeChildren</i> , <i>children</i> , <i>pitch</i> , <i>speed</i> , <i>numChan</i> , <i>phaseGroup</i> not supported (no rewind nor fast forward)
CacheTexture	<i>repeatS</i> , <i>repeatT</i> not supported
ColorInterpolator	255 key-value pairs
CompositeTexture2D	No scene commands or ROUTEs connected to the node or a node in the subtree of the node; an implementation is allowed to cache the rasterized version of the node and discard the node subtree.
Conditional	No restriction
CoordinateInterpolator2D	31 coordinates per <i>keyValue</i> 255 key-value pairs
EnvironmentTest	<i>No restrictions</i>
ImageTexture	<i>repeatS</i> , <i>repeatT</i> not supported
Inline	No restriction
InputSensor	restriction to mice, keyboards, remote controls
Layer2D	<i>addChildren</i> , <i>removeChildren</i> not supported 31 <i>children</i> maximum allowed Background and viewport nodes only allowed as fields of the Layer2D node. Any Background2D or Viewport node present in the subtree of the Layer2D shall be ignored.

Nodes	Restrictions
Layout	addChildren, removeChildren not supported 31 children maximum allowed scroll fields supported ? Only text children are supported. Text children shall only be present once on screen at the same time. Size not animatable nor updatable.
MediaControl	<i>mediaSpeed</i> not supported (no rewind nor fast forward) 31 <i>url</i> maximum
MediaSensor	<i>Info</i> ignored
MovieTexture	<i>speed</i> ignored (no rewind nor fast forward) <i>repeatS</i> , <i>repeatT</i> not supported
Node Update	Add and remove commands for addChildren and removeChildren fields are not supported
OrderedGroup	<i>addChildren</i> and <i>removeChildren</i> not supported 31 <i>children</i> maximum allowed
PositionInterpolator2D	255 key-value pairs
QuantizationParameter	No restriction
ROUTE	No restriction
ROUTE Update	No restriction
ScalarInterpolator	255 key-value pairs
Scene Update	All updates and Extended Updates
ServerCommand	No restriction
Storage	No restriction
Sound2D	<i>Intensity</i> , <i>spatialize</i> , <i>location</i> not supported
Switch	No restriction
TimeSensor	Ignored if <i>cycleInterval</i> < 0.03 second
TouchSensor	No restriction
Transform2D	<i>addChildren</i> and <i>removeChildren</i> not supported. 31 <i>children</i> maximum allowed.
TransformMatrix2D	<i>addChildren</i> and <i>removeChildren</i> not supported. 31 <i>children</i> maximum allowed.
Valuator	No restriction
Viewport	Only 1 Viewport node allowed in a context (a scene, a Layer2D node or a CompositeTexture node) <i>set_bind</i> , <i>bindTime</i> , <i>isBound</i> are not supported.
WorldInfo	No restriction
PROTO	Nested proto declarations and nested protos are forbidden. DEF/USE nodes are not allowed within a proto.

The maximum number of nodes that is allowed in a scene compliant with the ExtendedCore2D Scene Graph Profile @ Level 1 is 8,191 including all instances of these nodes through Inline, DEF/USE or PROTO mechanism.

In 7.9.3.3, replace Table 61 with the following:

Graphics Tools	Graphics Profiles							
	Simple2D	Simple2D+Text	Core 2D	ExtendedCore 2D	Advanced 2D	Complete 2D	3D Audio	Complete
AcousticMaterial							X	
Appearance	X	X	X	X	X	X	X	X
Background								X
Background2D		X	X	X	X	X		X
BAP								
BDP								
Bitmap	X	X	X	X	X	X		X
Body								
BodyDefTable								
BodySegment ConnectionHint								
Box								X
Circle			X	X	X	X		X
Color			X	X	X	X		X
Cone								X
Coordinate							X	X
Coordinate2D			X	X	X	X		X
Curve2D				X	X	X		X
Cylinder								X
DirectionalLight								X
ElevationGrid								X
Ellipse				X				
Expression								X
Extrusion								X
Face								X
FaceDefMesh								X
FaceDefTable								X
FaceDefTransform								X
FAP								X
FDP								X
FIT								X
Fog								X
FontStyle		X	X	X	X	X		X
Hierarchical3Dmesh								
IndexedFaceSet							X	X
IndexedFaceSet2D			X	X	X	X		X
IndexedLineSet								X
IndexedLineSet2D					X	X		X
LineProperties				X	X	X		X
LinearGradient				X				
Material								X
Material2D		X	X	X	X	X		X
MaterialKey					X			
MatteTexture					X			
Normal							X	X
PixelTexture			X	X	X	X		X
PointLight								X
PointSet								X

Graphics Tools	Graphics Profiles							
	Simple2D	Simple2D+Text	Core 2D	ExtendedCore 2D	Advanced 2D	Complete 2D	3D Audio	Complete
PointSet2D						X		X
RadialGradient				X				
Rectangle		X	X	X	X	X		X
Shape	X	X	X	X	X	X	X	X
Sphere								X
SpotLight								X
Text		X	X	X	X	X		X
TextureCoordinate					X	X		X
TextureTransform					X	X		X
Viseme								X
XCurve2D				X				
XfontStyle								
XlineProperties				X				

In 7.9.3.4, Table 62, replace the line:

0x08-0x7F	reserved for ISO use	
-----------	----------------------	--

with:

0x08	ExtendedCore2D profile	L1
0x09-0x7F	reserved for ISO use	

In 7.9.3.4, insert the following new subclause:

7.9.3.4.8 Levels for the ExtendedCore2D Graphics Profile

7.9.3.4.8.1 Functionalities provided

The ExtendedCore2D Graphics profile comprises all Core 2D Scene Graphics functionalities. The ExtendedCore2D Graphics profile allows in addition the ability to draw ellipses, curves, lines and gradients.

7.9.3.4.8.2 Level 1

The following restrictions apply for the ExtendedCore2D Scene Graphics Profile at Level 1:

Table AMD7.4 — Restrictions for ExtendedCore2D Graphics Profile at Level 1

Nodes	Restrictions
Appearance	<i>textureTransform</i> not supported
Background2D	only 1 Background2D node allowed in a context (a scene, a Layer2D node or a CompositeTexture2D node). <i>set_bind</i> not supported
Bitmap	No restriction.
Circle	No texture mapping allowed
Color	65535 <i>colors</i> maximum in the scene at a time
Coordinate2D	65535 <i>points</i> maximum
Curve2D	255 <i>Curve2D</i> or <i>XCurve2D</i> nodes maximum in a scene. 65 535 total elements in all type fields in the scene. No texture mapping allowed
Ellipse	No texture mapping allowed
FontStyle	No restriction
IndexedFaceSet2D	255 IndexedFaceSet2D nodes maximum in a scene 65 535 total indices maximum in all index fields in the scene Face list shall be well-defined as follows : 1. Each face is terminated with -1, including the last face in the array 2. Each face contains at least three non-coincident vertices 3. A given coordIndex is not repeated in a face 4. The vertices of a face shall define a planar polygon 5. The vertices of a face shall not define a self-intersecting polygon
LineProperties	No restriction
LinearGradient	No restriction
Material2D	No restriction
PixelTexture	32x32 maximum image size 8 PixelTexture nodes maximum in a scene at a time
RadialGradient	No restriction
Rectangle	If a natural texture (image, video) is mapped on the node, rectangle shall not be rotated
Shape	No restriction
Text	6 480 characters maximum in the scene at a time. No texture mapping allowed. No rotations allowed.
XCurve2D	255 <i>Curve2D</i> or <i>XCurve2D</i> nodes maximum in a scene. 65 535 total elements in all type fields in the scene. No natural textures (image, video) allowed. Segment type "elliptical arc" is not allowed
XLineProperties	<i>texture</i> and <i>textureTransform</i> are not supported No texturing (gradients or natural images) allowed. No animatable or updatable dash patterns. Dash offset not supported.

In 8.2.8, add the following at the end of the subclause:

```
NodeData getNodeFromMFField (FieldData field, int position);
```

Returns the node located at the given position for the MFNode field identified by the specified field.

In 8.6.6.1, add the following cases:

```

case 7:
    ExtendedReplace xReplace();
    break;
case 8:
    ReplaceToExternalData replaceTo();
    break;
case 9:
    ReplaceFromExternalData replaceFrom();
    break;

```

Add the following new subclauses and renumber subsequent 8.6.n subclauses:

8.6.13 ExtendedReplace

8.6.13.1 Syntax

```

class ExtendedReplace () {
    int position;
    boolean forceSF = false;

    FieldData targetField;
    bit(BIFSConfiguration.nodeIDbits) targetNodeID;
    NodeData targetNode = GetNodeFromID(targetNodeID);
    int(targetNode.nINbits) inID;
    targetField = targetNode.field[ targetNode.in2all[inID] ];

    if (!isSF(targetField) ) {
        bit (1) indexedReplacement;
        if (indexedReplacement) {
            bit (1) dynamicIndex;
            if (dynamicIndex) {
                bit(BIFSConfiguration.nodeIDbits) idxNodeID ;
                NodeData idxNode = GetNodeFromID(idxNodeID);
                int(idxNode.nDEFbits) defID;
                idxField = idxNode.field[ idxNode.def2all[defID] ];
                position = 0;
                switch (idxField.fieldType) {
                    case SFInt32:
                        //if field value is >=0, position is field value, otherwise position is 0
                        break;
                    case SFBool:
                        //if field value is true, position is 1, otherwise position is 0
                        break;
                    case SFFloat:
                        //if field value is >=0, position is floor(field value) , otherwise position is 0
                        break;
                    case SFTime:
                        //if field value is >=0, position is floor(field value) , otherwise position is 0
                        break;
                    default: //other field types default to position = 0
                        break;
                }
            } else {
                bit(2) replacementPosition;
                switch (replacementPosition) {
                    case 0: // replacement at a specified position
                        bit (16) idx;
                        position = idx;
                        break;
                    case 2: // replacement at the beginning of the field
                        break;
                    case 3: // replacement at the end of the field
                        break;
                }
            }
        }
    }
}

```