

---

---

**Information technology — Document  
Schema Definition Language (DSDL) —**

Part 2:

**Regular-grammar-based validation —  
RELAX NG**

**AMENDMENT 1: Compact Syntax**

*Technologies de l'information — Langage de définition de schéma de documents (DSDL) —*

*Partie 2: Validation de grammaire orientée courante — RELAX NG*

*AMENDEMENT 1: Syntaxe compacte*

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

IECNORM.COM : Click to view the full PDF of ISO/IEC 19757-2:2003/Amd 1:2006

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 19757-2:2003 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 34, *Document description and processing languages*.

IECNORM.COM : Click to view the full PDF of ISO/IEC 19757-2:2003/Amd 1:2006

# Information technology — Document Schema Definition Language (DSDL) —

## Part 2: Regular-grammar-based validation — RELAX NG

### AMENDMENT 1: Compact Syntax

*Page 8, Clause 5*

Add the following sentence at the end of Clause 5:

An alternative compact syntax is described in Annex C.

*Page 34*

Add Annex C before the Bibliography.

## **Annex C** (normative)

### **RELAX NG Compact Syntax**

#### **C.1 Introduction**

This Annex describes a compact, non-XML syntax for RELAX NG.

The goals of the compact syntax are to:

- maximize readability
- support all features of RELAX NG; it must be possible to translate a schema from the XML syntax to the compact syntax and back without losing significant information
- support separate translation; a RELAX NG schema may be spread amongst multiple files; it must be possible to represent each of the files separately in the compact syntax; the representation of each file must not depend on the other files

#### **C.2 Syntax**

The following is a summary of the syntax in EBNF. Square brackets are used to indicate optionality. The start symbol is topLevel.

```

topLevel ::=
decl* (pattern | grammarContent*)

decl ::=
("namespace" identifierOrKeyword "=" namespaceURLiteral)
| ("default" "namespace" [identifierOrKeyword] "=" namespaceURLiteral)
| ("datatypes" identifierOrKeyword "=" literal)

pattern ::=
("element" nameClass "{" pattern ")")
| ("attribute" nameClass "{" pattern ")")
| (pattern ("," pattern)+)
| (pattern ("&" pattern)+)
| (pattern ("|" pattern)+)
| (pattern "?")
| (pattern "*")
| (pattern "+")
| ("list" "{" pattern ")")
| ("mixed" "{" pattern ")")
| identifier
| ("parent" identifier)
| "empty"
| "text"
| ([datatypeName] datatypeValue)
| (datatypeName [{" param* "}"] [exceptPattern])
| "notAllowed"
| ("external" anyURLiteral [inherit])
| ("grammar" { grammarContent* })
| ("(" pattern ")")

param ::=
identifierOrKeyword "=" literal

exceptPattern ::=
"-" pattern

grammarContent ::=
start
| define
| ("div" "{" grammarContent* ")")
| ("include" anyURLiteral [inherit] [{" includeContent* "}"])

includeContent ::=
define
| start
| ("div" "{" includeContent* ")")

start ::=
"start" assignMethod pattern

define ::=
identifier assignMethod pattern

assignMethod ::=
"="
| "|="
| "&="

nameClass ::=
name

```

```

| (nsName [exceptNameClass])
| (anyName [exceptNameClass])
| (nameClass | nameClass)
| ("(" nameClass ")")

name ::=
identifierOrKeyword
| CName

exceptNameClass ::=
"-" nameClass

datatypeName ::=
CName
| "string"
| "token"

datatypeValue ::=
literal

anyURLiteral ::=
literal

namespaceURLiteral ::=
literal
| "inherit"

inherit ::=
"inherit" "=" identifierOrKeyword

identifierOrKeyword ::=
identifier
| keyword

identifier ::=
NCName
| quotedIdentifier

quotedIdentifier ::=
"\ " NCName

CName ::=
NCName ":" NCName

nsName ::=
NCName ":" "*"

anyName ::=
"*"

literal ::=
literalSegment ("~" literalSegment)+

literalSegment ::=
('"' (Char - ('"' | newline) )* '"')
| ("'" (Char - ('"' | newline) )* "'")
| (''''' (['''']['''']) (Char - ''') )* ''''''')
| (''''' (['''']['''']) (Char - ''') )* ''''''''')

```

```

keyword ::=
"attribute"
| "default"
| "datatypes"
| "div"
| "element"
| "empty"
| "external"
| "grammar"
| "include"
| "inherit"
| "list"
| "mixed"
| "namespace"
| "notAllowed"
| "parent"
| "start"
| "string"
| "text"
| "token"

```

NCName is defined in W3C XML Schema<sup>[4]</sup>. Char is defined in W3C XML<sup>[5]</sup>. A formal definition for the compact syntax is defined in an Oasis Committee Specification<sup>[6]</sup>.

In order to use a keyword as an identifier, it must be quoted with \. It is not necessary to quote a keyword that is used as the name of an element or attribute or as datatype parameter.

The value of a literal is the concatenation of the values of its constituent literalSegments. A literalSegment is always terminated only by an occurrence of the same delimiter that began it. The delimiter used to begin a literalSegment may be either one or three occurrences of a single or double quote character. Newlines are allowed only in literalSegments delimited by three quote characters. The value of a literal segment consists of the characters between its delimiters. One way to get a literal whose value contains both a single and a double quote is to divide the literal into multiple literalSegments so that the single and double quote are in separate literalSegments. Another way is to use a literalSegment delimited by three single or double quotes.

Annotations can be specified as described in C.5.

There is no notion of operator precedence. It is an error for patterns to combine the |, &, , and - operators without using parentheses to make the grouping explicit. For example, foo | bar, baz is not allowed; instead, either (foo | bar), baz or foo | (bar, baz) must be used. A similar restriction applies to name classes and the use of the | and - operators. These restrictions are not expressed in the above EBNF.

The value of an anyURLiteral specified with include or external is a URI reference to a grammar in the compact syntax.

### C.3 Lexical structure

Whitespace is allowed between tokens. Tokens are the strings occurring in double quotes in the EBNF in C.2, except that literalSegment, nsName, CName, identifier and quotedIdentifier are single tokens.

Comments are also allowed between tokens. Comments start with a # and continue to the end of the line. Comments starting with ## are treated specially; see C.5.

A Unicode character with hex code N can be represented by the escape sequence \x{N}. Using such an escape sequence is completely equivalent to the entering the corresponding character directly. For example,

```
element \x{66}\x{6f}\x{6f} { empty }
```

is equivalent to

```
element foo { empty }
```

## C.4 Declarations

A datatypes declaration declares a prefix used in a QName identifying a datatype. For example,

```
datatypes xsd = "http://www.w3.org/2001/XMLSchema-datatypes"
element height { xsd:double }
```

In fact, in the above example, the datatypes declaration is not required: the xsd prefix is predeclared to the above URI.

A namespace declaration declares a prefix used in a QName specifying the name of an element or attribute. For example,

```
namespace rng = "http://relaxng.org/ns/structure/1.0"
element rng:text { empty }
```

As in XML, the xml prefix is predeclared.

A default namespace declaration declares the namespace used for unprefix names specifying the name of an element (but not of an attribute). For example,

```
default namespace = "http://example.com"
element foo { attribute bar { string } }
```

is equivalent to

```
namespace ex = "http://example.com"
element ex:foo { attribute bar { string } }
```

A default namespace declaration may have a prefix as well. For example,

```
default namespace ex = "http://example.com"
```

is equivalent to

```
default namespace = "http://example.com"
namespace ex = "http://example.com"
```

The URI may be empty. This makes the prefix stand for the absent namespace URI. This is necessary for specifying a name class that matches any name with an absent namespace URI. For example,

```
namespace local = ""
element foo { attribute * - local:* { string }* }
```

is equivalent to

```
<element xmlns="http://relaxng.org/ns/structure/1.0" name="foo" ns="http://example.com">
  <zeroOrMore>
    <attribute>
      <anyName>
        <except>
          <nsName ns="" />
        </except>
      </anyName>
      <data type="string"/>
    </attribute>
  </zeroOrMore>
</element>
```

RELAX NG has the feature that if a file does not specify an ns attribute then the ns attribute can be inherited from the including file. To support this feature, the keyword inherit can be specified in place of the namespace URI in a namespace declaration. For example,

```
default namespace this = inherit
element foo { element * - this:* { string }* }
```

is equivalent to

```
<element xmlns="http://relaxng.org/ns/structure/1.0" name="foo">
  <zeroOrMore>
    <element>
      <anyName>
        <except>
          <nsName/>
        </except>
      </anyName>
      <data type="string"/>
    </element>
  </zeroOrMore>
</element>
```

In addition, the include and external patterns can specify inherit = prefix to specify the namespace to be inherited by the referenced file. For example,

```
namespace x = "http://www.example.com"
external "foo.rng" inherit = x
```

is equivalent to

```
<externalRef href="foo.rng"
  ns="http://www.example.com"
  xmlns="http://relaxng.org/ns/structure/1.0"/>
```

In the absence of an inherit parameter on include or external, the default namespace will be inherited by the referenced file.

In the absence of a default namespace declaration, a declaration of

```
default namespace = inherit
```

is assumed.

## C.5 Annotations

### C.5.1 Support for annotations

The RELAX NG XML syntax allows foreign elements and attributes to be used to annotate a RELAX NG schema.

A schema in the compact syntax can also have annotations, which will turn into foreign elements and attributes when the schema is translated into XML syntax. The way these annotations are specified depends on where the foreign elements and attributes are to appear in the translated schema. There is also a special shorthand syntax when the foreign element is a documentation element.

### C.5.2 Initial annotations

An annotation in square brackets can be inserted immediately before a pattern, param, nameClass, grammarContent or includeContent. It has the following syntax:

```

annotation ::=
[" annotationAttribute* annotationElement* "]

annotationAttribute ::=
name "=" literal

annotationElement ::=
name "[" annotationAttribute* (annotationElement | literal)* "]"

```

Each of the annotationAttributes will turn into attributes on the corresponding RELAX NG element. Each of the annotationElements will turn into initial children of the corresponding RELAX NG element, except in the case where the RELAX NG element cannot have children, in which case they will turn into following elements.

### C.5.3 Documentation shorthand

Comments starting with ## are used to specify documentation elements from the <http://relaxng.org/ns/compatibility/annotations/1.0> namespace. For example,

```

## Represents a language
element lang {
## English
"en" |
## Japanese
"jp"
}

```

turns into

```

<element name="lang"
  xmlns:a="http://relaxng.org/ns/compatibility/annotations/1.0"
  xmlns="http://relaxng.org/ns/structure/1.0">
  <a:documentation>Represents a language</a:documentation>
  <choice>
    <value>en</value>
    <a:documentation>English</a:documentation>
    <value>jp</value>
    <a:documentation>Japanese</a:documentation>
  </choice>
</element>

```

## comments can only be used immediately before a pattern, nameClass, grammarContent or includeContent. Multiple ## comments are allowed. Multiple adjacent ## comments without any intervening blank lines are merged into a single documentation element. Any ## comments must precede any annotation in square brackets.

### C.5.4 Following annotations

A pattern or nameClass may be followed by any number of followAnnotations with the following syntax:

```

followAnnotation ::=
">>" annotationElement

```

Each such annotationElement turns into a following sibling of the RELAX NG element representing the pattern or nameClass.

### C.5.5 Grammar annotations

An annotationElement may be used in any place where grammarContent or includeContent is allowed. For example,

```
namespace x = "http://www.example.com"
start = foo
x:entity [ name="picture" systemId="picture.jpeg" notation="jpeg" ]
foo = element foo { empty }
```

turns into

```
<grammar xmlns:x="http://www.example.com"
  xmlns="http://relaxng.org/ns/structure/1.0">
  <start>
    <ref name="foo"/>
  </start>
  <x:entity name="picture" systemId="picture.jpeg" notation="jpeg"/>
  <define name="foo">
    <element name="foo">
      <empty/>
    </element>
  </define>
</grammar>
```

If the name of such an element is a keyword, then it must be quoted with `l`.

## C.6 Conformance

### C.6.1 Types of conformance

There are three types of conformant implementation of the compact syntax.

### C.6.2 Validator

A validator conforming to this specification must be able to determine whether a textual object is a correct RELAX NG Compact Syntax schema as specified in this Annex. It must also be able to determine for any XML document and for any correct RELAX NG Compact Syntax schema whether the document is valid (as defined in Clause 9) with respect to the translation of the schema into XML syntax. It need not be able to output a representation of the translation of the schema into XML syntax.

The requirements in the preceding paragraph are subject to the provisions of the second paragraph of Clause 11.

### C.6.3 Structure preserving translator

A structure preserving translator must be able to translate any correct RELAX NG Compact Syntax schema into an XML document whose data model is strictly equivalent to the translation specified in this Annex. For this purpose, two instances of the data model (as specified in Clause 5) are considered strictly equivalent if they are identical after applying the simplifications specified in Sections 7.2, 7.3, 7.4, 7.8, 7.9 and 7.10, with the exception that the base URI in the context of elements may differ.

NOTE 1: The RELAX NG compact syntax is not a representation of the XML syntax of a RELAX NG schema; rather it is a representation of the semantics of a RELAX NG schema. Details of the XML syntax that were judged to be insignificant are not captured in the compact syntax. For example, in the XML syntax if the name class for an element or attribute pattern consists of just a single name, it can be expressed either as a name attribute or as a name element; however, in the compact syntax, there is only one way to express such a name class. The simplifications listed in the previous paragraph correspond to those syntactic details that are not captured in the compact syntax.

When comparing two include or externalRef patterns in the XML source for strict equivalence, the value of the href attributes are not compared; instead the referenced XML documents are compared for strict equivalence.