

---

---

**Information technology — JPEG XS  
low-latency lightweight image coding  
system —**

**Part 4:  
Conformance testing**

*Technologies de l'information — Système de codage d'images léger à faible latence JPEG XS —*

*Partie 4: Essais de conformité*

IECNORM.COM : Click to view the full PDF of ISO/IEC 21122-4:2020



IECNORM.COM : Click to view the full PDF of ISO/IEC 21122-4:2020



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>2</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Typesetting conventions</b> .....	<b>3</b>
<b>5 Overview</b> .....	<b>3</b>
<b>6 General description</b> .....	<b>3</b>
6.1 Overview.....	3
6.2 Codestream syntax testing.....	3
6.3 Test procedures to test decoders for conformance to ISO/IEC 21122-1.....	3
6.4 Test procedures to test decoders for conformance to ISO/IEC 21122-3.....	3
6.5 File format syntax testing.....	3
6.6 Profile, level and sublevel conformance testing.....	4
6.7 Buffer model conformance testing.....	4
6.8 Electronic attachments.....	4
<b>7 Conformance files availability and updates</b> .....	<b>4</b>
<b>Annex A (normative) Codestream syntax testing procedures</b> .....	<b>5</b>
<b>Annex B (normative) Decoder testing procedures</b> .....	<b>6</b>
<b>Annex C (normative) Decoder conformance tests</b> .....	<b>9</b>
<b>Annex D (normative) File format syntax testing procedures</b> .....	<b>13</b>
<b>Annex E (normative) Buffer model conformance testing</b> .....	<b>14</b>
<b>Annex F (informative) Electronic attachments</b> .....	<b>16</b>
<b>Bibliography</b> .....	<b>18</b>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any of all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see <http://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

A list of all parts in the ISO/IEC 21122 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Information technology — JPEG XS low-latency lightweight image coding system —

## Part 4: Conformance testing

### 1 Scope

This document specifies the framework, concepts, methodology for testing, and criteria to be achieved to claim conformance to multiple parts of the ISO/IEC 21122 series. It lists the conformance testing procedures.

This document specifies:

- Conformance testing procedures for decoders implementing ISO/IEC 21122-1.
- Conformance testing procedures for decoders implementing ISO/IEC 21122-3.
- Tests to check codestreams for conformance to ISO/IEC 21122-1. As such, it provides means to test whether encoder implementations generate syntactically correct codestreams, and whether codestreams generated by such implementations follow the requirements of a particular profile, level and sublevel, and the buffer model implied by them.
- Tests to check files for conformance to ISO/IEC 21122-3.
- Conformance testing procedures that allow testing whether codestreams conform to any of the profiles specified in ISO/IEC 21122-2.
- Conformance testing procedures that allow testing whether codestreams conform to the buffer model specified in ISO/IEC 21122-2 as part of a profile, level and sublevel.
- Codestreams, decoded images, and error metrics to be used within the decoder testing procedures.
- A buffer model test.
- Abstract test suites.

This document does not specify:

- Testing the reconstruction of a full resolution image from a subsampled image format. In particular, upsampling from 4:2:2 to 4:4:4 sampling is a non-normative extension and as such its testing is beyond the scope of this document.
- Testing the conversion of the sample values reconstructed by an ISO/IEC 21122-3 decoder to the target colour space by means of the colour specification box of ISO/IEC 21122-3.
- Testing of the composition of background and foreground for images reconstructed from ISO/IEC 21122-3 files or codestreams.
- Acceptance testing: the process of determining whether an implementation satisfies acceptance criteria and enables the user to determine whether or not to accept the implementation. This includes the planning and execution of several kinds of tests (e.g. functionality, quality, and speed performance testing) that demonstrate that the implementation satisfies the user requirements.
- Performance testing: measures the performance characteristics of an implementation under test (IUT) such as its throughput, responsiveness, etc. under various conditions.

- Robustness testing: the process of determining how well an implementation is able to conceal problems from attempting to reconstruct an image from an ill-formed codestream.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 21122-1, *Information technology — JPEG XS low-latency lightweight image coding system — Part 1: Core coding system*

ISO/IEC 21122-2, *Information technology — JPEG XS low-latency lightweight image coding system — Part 2: Profiles and buffer models*

ISO/IEC 21122-3, *Information technology — JPEG XS low-latency lightweight image coding system — Part 3: Transport and container formats*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 21122-3 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### 3.1

#### ASCII

#### American Standard Code for Information Interchange

binary encoding of 7-bit characters

Note 1 to entry: This encoding is as defined by ISO/IEC 646.

### 3.2

#### ETS

#### executable test suite

set of executable test cases in the form of codestreams that are input into an implementation under test

### 3.3

#### IUT

#### implementation under test

implementation that is being evaluated for conformance

### 3.4

#### JPEG XS file

sequence of bytes encoding an image in the JXS file format

Note 1 to entry: This format is specified in ISO/IEC 21122-3.

### 3.5

#### procedure

set of steps which accomplishes one of the tasks which comprise an encoding or decoding process

### 3.6

#### TCS

#### test codestream set

(sub-)set of codestreams that are input to an implementation under test for a particular test purpose

### 3.7

#### testing

process of evaluating conformance

## 4 Typesetting conventions

Regular face fonts as this text describe normative or informative text that provides specifications, instructions, comments or details for the reader.

Monospaced text as this paragraph indicates file names, or program input or output as necessary to either run software, or as generated by the software on the console.

## 5 Overview

The conformance files including codestreams, reference decoded images, descriptive files and auxiliary software to facilitate testing are provided at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>, in compressed form. File locations given in this document are expressed relative to the top level directory tree within this compressed file. A Unix style file structure and delimiters are assumed.

This document contains instructions for the use of these files.

## 6 General description

### 6.1 Overview

The ISO/IEC 21122 series, also known as JPEG XS, consists of multiple parts of which for ISO/IEC 21122-1 describes the core coding system and the syntax of a codestream, for ISO/IEC 21122-2 describes profiles and buffer models and for ISO/IEC 21122-3 describes transport and container formats. This document defines test suites for decoder conformance tests for ISO/IEC 21122-1, ISO/IEC 21122-2 and ISO/IEC 21122-3.

### 6.2 Codestream syntax testing

The procedures of [Annex A](#) shall be used for testing codestreams for syntactical correctness. They depend on a codestream syntax parsing tool whose source code is provided at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

### 6.3 Test procedures to test decoders for conformance to ISO/IEC 21122-1

The procedures defined in [Annex B](#) and the subset of ETS defined in [Annex C, subclauses C.2 to C.10](#) that correspond to the profiles, levels and sublevels supported by the decoder shall be used for testing decoders for compliance to ISO/IEC 21122-1. These procedures and ETS allow an IUT to evaluate conformance to ISO/IEC 21122-1 only.

### 6.4 Test procedures to test decoders for conformance to ISO/IEC 21122-3

The procedures defined in [Annex B](#) and the subset of ETS defined in [Annex C, subclause C.11](#) that correspond to the profiles, levels and sublevels supported by the decoder shall be used for testing decoders for compliance to ISO/IEC 21122-3. These procedures and ETS allow an IUT to evaluate conformance to ISO/IEC 21122-1 and ISO/IEC 21122-3.

### 6.5 File format syntax testing

The procedures that shall be used for testing JPEG XS files for compliance to the file format specified in ISO/IEC 21122-3 are defined in [Annex D](#). They depend on a codestream syntax parsing tool whose source code is provided at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

## 6.6 Profile, level and sublevel conformance testing

[Annex A](#) also specifies a test procedure that shall be used for testing whether a codestream is conforming to a particular profile, level and sublevel, and whether, in particular, its coding parameters are within the constraints of the profile, level and sublevel indicated in the codestream. The test in [Annex A](#) depends on a program that is given at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

## 6.7 Buffer model conformance testing

[Annex E](#) specifies test procedures that shall be used for testing whether a codestream is conforming to a buffer model implied by the profile, level and sublevel indicated in the codestream. The tests in [Annex E](#) depend on a program that is given at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

## 6.8 Electronic attachments

[Annex F](#) lists the electronic attachments to this document and describes how to compile and use them.

## 7 Conformance files availability and updates

The conformance test images, streams and conformance test software released with this document are the latest tested versions available at the date at which the text was released.

IECNORM.COM : Click to view the full PDF of ISO/IEC 21122-4:2020

## Annex A (normative)

### Codestream syntax testing procedures

#### A.1 General

This annex defines a procedure that shall be followed for determining whether a codestream is syntactically well-formed and follows the syntactical requirements of ISO/IEC 21122-1. The test procedure also checks whether the coding parameters of a given codestream are consistent with the profile, level and sublevel indicators that are part of the picture header (see ISO/IEC 21122-1). A typical use case for this test is to check whether a given encoder generates profile, level and sublevel information correctly. To this end, a Python<sup>1)</sup> test script `jxscodestream.py` that performs a syntax analysis of a given codestream is provided at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

#### A.2 Installation

The test tool requires installation of a Python 2.7 interpreter<sup>1)</sup> on the computer system to be used for performing a test. Python is available for multiple operating systems at <https://docs.python.org>.

#### A.3 Usage of the syntax test tool

For testing a particular codestream for syntactical correctness and correct indication of profile, level and sublevel, the syntax analyser `jxscodestream.py` tool shall be run on a command line as follows:

```
jxscodestream.py codestream.jxs
```

where `codestream.jxs` is the codestream to be tested. A codestream is not conforming in case the above tool reports any error.

The lack of detection of any conformance violation by the syntax test tool should not be considered as a definite proof that the codestream under testing conforms to all constraints required for conformance to ISO/IEC 21122-1 and ISO/IEC 21122-2. ISO/IEC 21122-5<sup>2)</sup> provides additional means for testing a codestream for conformance to the ISO/IEC 21122 series by feeding it into the reference software implementation.

---

1) Python is a trademark of the Python Software Foundation. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO/IEC of the product named. Equivalent products may be used if they can be shown to lead to the same results.

2) Under preparation. Stage at time of publication: ISO/IEC DIS 21122-5:2020.

## Annex B (normative)

### Decoder testing procedures

#### B.1 General

This annex defines procedures that shall be followed for determining whether a JPEG XS decoder implementation is conforming to a particular profile, level and sublevel.

#### B.2 Decoder test procedure

The following steps shall be performed for the purpose of testing a decoder implementation:

- Select to test for ISO/IEC 21122-1 only or ISO/IEC 21122-1 and ISO/IEC 21122-3.
- Select a profile, level and sublevel to test against.
- The profile, level and sublevel define a TCS (test codestream set), which consists of codestreams or files within the test suite that conform to
  - the codestream syntax specified in ISO/IEC 21122-1 or the file format specified in ISO/IEC 21122-3,
  - the selected profile,
  - a level whose sample count and sample rate is smaller than or equal to the sample count and sample rate of the selected level, and
  - to a sublevel whose bitrate is smaller or equal than the bitrate of the selected sublevel.
- Decode each codestream or file using the implementation under test.
- The decoded outputs are format converted if necessary.
- The difference between the decoded outputs and reference outputs is measured.
- If the decoded and reference are identical, the test proceeds to the next codestream in the TCS.
- If the decoded image differs from the reference image, the implementation is non-conforming and testing aborts.

The entire set of test codestreams is defined in more detail in a later clause of [Annex C](#). Failure to match the reference output for a single test codestream results in the decoder failing to be conforming with the given profile, level and sublevel being tested.

#### B.3 Files for testing

A particular ETS defines the input codestreams. These are specified in [Annex C](#) for all profiles.

#### B.4 Decoder settings

Decoders may have mechanisms for supporting various decompression settings. These may be set in the most advantageous way to achieve conformance. For example, a decoder with a "fast mode" and an "accurate mode" may be set to the "accurate mode" to determine conformance. These settings should

be noted in any statement of conformance. Settings that allow the output resolution or spatial region of the reference decoded images to be matched may be changed for each decoded image. The same user-controlled settings for accuracy shall be used for all test codestreams of a TCS.

## B.5 Output file format conversion

The reference decoded images are provided in a specific file format defined below. In order to compare decoded images from the decoder under test with these images, several conversions can be necessary. These conversions may be done as post-processing steps outside of the decoder solely for determining conformance. There is no requirement for a conforming decoder to perform these processes as part of its normal operation. These conversions shall not introduce a quality change (either loss or gain) except as required by the specific conversions described in the following clauses.

## B.6 Sample format conversion

Image sample values are always unsigned integers. For the purpose of testing, it is of advantage to represent the integer output of the IUT in the pgx format defined in subclause B.7 as ISO/IEC provide tools to measure on such files directly. Any up-sampling or colour space format conversions shall be disabled for the purpose of testing should a decoder offer these as optional features.

There is no requirement that a conforming decoder has to generate output to the specified format, and the representation of the output of the IUT in this format only facilitates the testing process. That is, it is acceptable to include additional lossless format conversions in the testing procedure provided the comparison between reconstructed and reference images is performed in the normative way.

Conversion from  $YCbCr$  to RGB, colour space conversions and up-sampling to a full sample grid may be provided as optional features of a decoder implementation and need to be disabled for testing purposes. This conversion between colour spaces is not related to the RCT transformation that is normatively defined in ISO/IEC 21122-1. Conformance testing applies to the reconstructed sample values only, bare any interpretation relative to a colour space, and no colour space conversions are made for the purpose of testing.

## B.7 Reference components file format

### B.7.1 General

This subclause specifies the file format, called pgx, of the reference images used for comparison with the output of the decoder under test. The decoder under test is not required to produce this particular file format, though it is advantageous to perform a conversion to this file format for testing purposes as ISO/IEC provides test tools that are able to decode this format. Any necessary lossless conversion to this format, as specified by subclause B.5, may be applied as part of the test procedure.

The format consists of a directory file, one header file per component, and one raw data file per component.

NOTE The `diffstest_ng` tool, provided at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>, can convert the pgx file format to many other formats. It is therefore not necessary to support the file format listed here directly.

### B.7.2 Directory file format

The directory file is the file that is provided as input file to the comparison tool. It consists, for each component, of the file name of the raw data file encoded in ISO/IEC 646 (ASCII), relative to the path where the directory file is located. Each raw data file name is terminated by a single line feed character (ISO/IEC 646 code 10, hex 0x0a).

NOTE The pgx directory file does not separate lines by CR/LF pairs, i.e. the ISO/IEC 646 code sequence 12, 10 / hex 0x0c 0x0a.

### B.7.3 Header file format

The header file is derived from the file name of the raw data file listed in the directory file by removing the postfix `.raw` and replacing it by the postfix `.h`. It describes the format in which the raw format is encoded. There is a separate header file per component.

Each header file consists of a single line, terminated by a single ISO/IEC 646 line feed character (code 10, hex 0x0a) describing the format. It consists of the following fields, where angle brackets `< >` indicate parameters described below and SPC indicates an ISO/IEC 646 blank space (code 32, hex 0x20):

`P<data format>SPC<endianness>SPC<signedness><precision>SPC<width>SPC<height>`

where

<code>P</code>	identifies the header file and shall be present. It has no particular meaning beyond format identification.
<code>&lt;data format&gt;</code>	identifies the sample format. ISO/IEC 21122 stores integer samples only, which are indicated by the single character <code>G</code> as data format.
<code>&lt;endianness&gt;</code>	identifies the endianness of the encoded data. The character sequence <code>ML</code> indicates big endian encoding, i.e. most significant byte first, the character sequence <code>LM</code> little endian encoding, i.e. least significant byte first.
<code>&lt;signedness&gt;</code>	indicates whether sample values are signed or unsigned. ISO/IEC 21122 covers only unsigned samples, indicated by the character <code>+</code> in this field.
<code>&lt;precision&gt;</code>	indicates the bit-precision of the sample values in the component described by this header file. The bit-precision is encoded as ISO/IEC 646 encoded decimal number.
<code>&lt;width&gt;</code>	is the number of samples per line for this component, represented as ISO/IEC 646 encoded decimal number.
<code>&lt;height&gt;</code>	is the number of lines of the image, represented as ISO/IEC 646 encoded decimal number.

### B.7.4 Data file format

Each data file contains the sample values themselves in raster scan order, left to right, top to bottom. If the precision of the component is 8 or below, each sample is represented in 8 bits, right aligned to the entire byte, i.e. unused bits remain 0 and make up the most-significant bits of the byte. If the precision is larger than 8, each sample is represented by two bytes, encoded in the order indicated by the header, i.e. either most significant byte first if the endianness field is `ML`, or with the least significant byte first if the endianness field is `LM`. The data bits are right-aligned into the two bits, most significant bits remain 0 if necessary.

## B.8 Comparison of decoded and formatted components with reference components

The image reconstructed from a TCS and the reference test image for the TCS need to be identical sample by sample in order to pass a test. Any deviation from the reference test image shall be considered a failure.

NOTE The `diffptest_ng` test tool available as an electronic attachment to this document can be used to implement such a test. If `diffptest_ng` reports a peak signal to noise ratio (PSNR) of INF when applied to reconstructed and reference test image, the test is considered successful, otherwise it is considered a failure.

## Annex C (normative)

### Decoder conformance tests

#### C.1 General

This annex specifies the abstract test suites and executable test suites that shall be used in the conformance test procedures from [Annex B](#). References reconstructed images are given by substituting the suffix `.jxs` by `.pgx`.

#### C.2 Reference codestreams for the light subline 422.10 profile

[Table C.1](#) lists the codestreams for testing implementations against the light subline 422.10 profile.

**Table C.1 — Light subline 422.10 profile test streams**

TCS	Level	Sublevel
2.jxs	4k-2	3bpp
48.jxs	4k-2	3bpp
20.jxs	unre- stricted	9bpp
28.jxs	4k-1	unre- stricted
50.jxs	4k-1	unre- stricted
36.jxs	2k-1	unre- stricted

#### C.3 Reference codestreams for the light 422.10 profile

[Table C.2](#) lists the codestreams for testing implementations against the light 422.10 profile.

**Table C.2 — Light 422.10 profile test streams**

TCS	Level	Sublevel
3.jxs	4k-2	6bpp
49.jxs	4k-2	3bpp
12.jxs	4k-2	3bpp
51.jxs	4k-2	6bpp
21.jxs	unre- stricted	12bpp
29.jxs	4k-1	12bpp
37.jxs	2k-1	9bpp

#### C.4 Reference codestreams for the light 444.12 profile

[Table C.3](#) lists the codestreams for testing implementations against the light 444.12 profile.

**Table C.3 — Light 444.12 profile test streams**

TCS	Level	Sublevel
4.jxs	4k-2	3bpp
52.jxs	4k-2	6bpp
13.jxs	4k-1	9bpp
22.jxs	unre- stricted	12bpp
53.jxs	unre- stricted	12bpp
30.jxs	4k-1	12bpp
38.jxs	2k-1	unre- stricted

### C.5 Reference codestreams for the main 422.10 profile

[Table C.4](#) lists the codestreams for testing implementations against the main 422.10 profile.

**Table C.4 — Main 422.10 profile test streams**

TCS	Level	Sublevel
5.jxs	4k-2	3bpp
54.jxs	4k-2	6bpp
14.jxs	4k-2	9bpp
23.jxs	unre- stricted	12bpp
31.jxs	4k-1	12bpp
39.jxs	2k-1	9bpp
66.jxs	2k-1	12bpp

### C.6 Reference codestreams for the main 444.12 profile

[Table C.5](#) lists the codestreams for testing implementations against the main 444.12 profile.

**Table C.5 — Main 444.12 profile test streams**

TCS	Level	Sublevel
6.jxs	4k-2	3bpp
55.jxs	4k-2	6bpp
11.jxs	4k-2	6bpp
15.jxs	4k-1	9bpp
24.jxs	unre- stricted	12bpp
56.jxs	unre- stricted	12bpp
32.jxs	4k-1	12bpp
40.jxs	2k-1	unre- stricted

## C.7 Reference codestreams for the main 4444.12 profile

[Table C.6](#) lists the codestreams for testing implementations against the main 4444.12 profile.

**Table C.6 — Main 4444.12 profile test streams**

TCS	Level	Sublevel
8.jxs	4k-2	3bpp
57.jxs	4k-2	6bpp
17.jxs	4k-1	9bpp
26.jxs	unrestricted	12bpp
58.jxs	unrestricted	12bpp
34.jxs	4k-1	12bpp
42.jxs	2k-1	9bpp
44.jxs	8k-1	9bpp
59.jxs	4k-1	12bpp
46.jxs	4k-1	12bpp

## C.8 Reference codestreams for the high 444.12 profile

[Table C.7](#) lists the codestreams for testing implementations against the high 444.12 profile.

**Table C.7 — High 444.12 profile test streams**

TCS	Level	Sublevel
7.jxs	4k-2	3bpp
60.jxs	4k-2	6bpp
16.jxs	4k-1	9bpp
25.jxs	unrestricted	12bpp
61.jxs	unrestricted	12bpp
33.jxs	4k-1	12bpp
41.jxs	2k-1	unrestricted

## C.9 Reference codestreams for the high 4444.12 profile

[Table C.8](#) lists the codestreams for testing implementations against the high 4444.12 profile.

**Table C.8 — High 4444.12 profile test streams**

TCS	Level	Sublevel
9.jxs	4k-2	3bpp
62.jxs	4k-2	6bpp
18.jxs	4k-1	9bpp
27.jxs	unrestricted	12bpp
63.jxs	unrestricted	12bpp

Table C.8 (continued)

TCS	Level	Sublevel
35.jxs	4k-1	12bpp
43.jxs	2k-1	9bpp
45.jxs	8k-1	6bpp
47.jxs	4k-1	12bpp
64.jxs	4k-1	12bpp

### C.10 Reference codestreams for the unrestricted profile

Table C.9 lists the codestreams for testing implementations against the unrestricted profile.

Table C.9 — Unrestricted profile test streams

TCS	Level	Sublevel
10.jxs	unre- stricted	3bpp
65.jxs	unre- stricted	6bpp
19.jxs	4K-1	9bpp
64.jxs	4k-1	12bpp

### C.11 Reference files for file format conformance testing

Table C.9 lists the files for testing implementations against the file format specified in ISO/IEC 21122-3 and the main 444.12 profile.

Table C.10 — Main 444.12 profile test streams

TCS	Level	Sublevel
1.jxs	4k-2	3bpp

## Annex D (normative)

### File format syntax testing procedures

#### D.1 General

This annex defines procedures that shall be followed to determine whether a JXS file is syntactically well-formed and follows the syntactical requirements of ISO/IEC 21122-3. To this end, a Python<sup>3)</sup> test script `jp2file.py` has been attached to this document that performs a syntax analysis of a given codestream.

#### D.2 Installation

In order to run the tool, a Python 2.7 interpreter must be installed on the computer. Python is available for multiple operating systems at <https://docs.python.org>.

#### D.3 Usage of the syntax test tool

To test a particular JXS file for syntactical correctness, the syntax analyser shall be run from a command line as follows:

```
jp2file.py jxsfile.jxs
```

where `jxsfile.jxs` is the file to be tested. A file fails the conformance test if the above syntax analysis tool reports any error.

The lack of detection of any conformance violation by the syntax test tool should not be considered as a definite proof that the file under test conforms to all constraints required for conformance to ISO/IEC 21122-3.

---

3) Python is a trademark of the Python Software Foundation. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO/IEC of the product named. Equivalent products may be used if they can be shown to lead to the same results.

## Annex E (normative)

### Buffer model conformance testing

#### E.1 General

This annex defines a method that shall be used to test whether a particular codestream conforms to the JPEG XS buffer model specified in ISO/IEC 21122-2, and hence if a JPEG XS decoder with a smoothing buffer sized according to ISO/IEC 21122-2 is able to receive and decode the codestream under test without running into a buffer underflow or overflow. This test is also useful to test encoder implementations, as to ensure whether the generated codestreams are satisfying the buffer model requirements of ISO/IEC 21122-2. The test itself is implemented by a Python<sup>4)</sup> program `bufferModelChecker.py` that is available at <https://standards.iso.org/iso-iec/21122/-4/ed-1/en>.

#### E.2 Installation

In order to run the test, a Python 3 interpreter must be installed on the computer. In addition, the test depends on a suitable decoder implementation that extracts buffer information from the codestream. Python is available for multiple operating systems at <https://docs.python.org>.

NOTE The JPEG XS reference software contained in ISO/IEC 21122-5 implements the required feature extraction and can therefore be used to obtain this information.

#### E.3 Using the buffer model test tool

##### E.3.1 General

Testing a codestream for conformance to the JPEG XS buffer model involves two steps: first, the extraction of codestream fragment sizes and number of coding groups from the codestream under test, and second, the analysis of the data generated by the first step with the buffer model checker.

##### E.3.2 Extraction of codestream fragment sizes and code group counts

The buffer model test tool requires as input information on the codestream fragments represented by the codestream under test. For the purpose of buffer model testing, the following data shall be extracted from the codestream:

- a contiguous counter, starting from 0, that enumerates all codestream fragments;
- the size of the codestream fragment in bits;
- the number of code groups encoded by the packet that is included in the codestream fragment.

For the definition of packets and code groups, see ISO/IEC 21122-1. For the definition of codestream fragments, see ISO/IEC 21122-2.

The data on codestream fragments and code group counts shall then be formatted in a file that contains for each codestream fragment a line as follows:

---

4) Python is a trademark of the Python Software Foundation. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO/IEC of the product named. Equivalent products may be used if they can be shown to lead to the same results.

<counter>;<size>;<code groups>

where <counter> enumerates the codestream fragments in increasing order, starting from 0, <size> is the size of the codestream fragment in bits, and <code groups> is the number of code groups in the packet. This file is input to the buffer model checker described in the following subclause.

**NOTE** The JPEG XS Reference software contained in ISO/IEC 21122-5 can be used to extract this information from a given codestream with the command line option `-F` that writes this information to the file name following this option.

### E.3.3 Testing codestream fragment information

In the second step, the output of the codestream analysis shall be fed into the buffer model checker which will perform the conformance check. For this, `bufferModelChecker.py` shall be run on the command line as follows:

```
bufferModelChecker.py --profile <profile> --mainlevel <level> --sublevel <sublevel>
--colorFormat <format> --type <buffermodeltype> --imageWidth <width> [--jxs <codestream>]
<fragmentinfo>
```

where the parameters are defined as follows:

<profile>	is the profile the codestream claims to be conforming to. Possible values are: Main444.10, Main444.12, High444.12, Main4444.12, Light444.12, LightSubline422.10, High4444.12, High322.10, Light422.10
<level>	is the level the codestream claims to be conforming to. Possible values are: 8k-2, 4k-3, 8k-3, 4k-2, 4k-1, 2k-1, 10k-1, 8k-1
<sublevel>	is the sublevel the codestream claims to be conforming to. Possible values are: Sublev9bpp, Sublev3bpp, Sublev12bpp, Sublev6bpp
<format>	is the sampling format of the input image. Possible values are: 400, 422, 444, 4224, 4444
<buffermodeltype>	is the type of the buffer model to be assumed. The following values are accepted: 1: a constant bitrate smoothing buffer with limited transmission latency is assumed; 2: a constant bitrate buffer with variable transmission latency is assumed.
<jxsfile>	is, optionally, the input codestream itself. If given, a file size check against sublevel constraints is performed.
<fragmentinfo>	is the file generated in the first step containing fragment index, fragment bit size and number of included code groups, separated by semicolons.
<width>	is the width of the image in sample grid points.

The output of the buffer model checker is a JSON-encoded line as follows:

```
{'BM_Result' : <ok>}
```

This output encodes whether the codestream is acceptable for the selected buffer model. The parameter <ok> is `True` in case it is, and `False` in case the conformance test fails.