



ISO/IEC 29341-16-10

Edition 1.0 2011-08

INTERNATIONAL STANDARD



Information technology – UPnP device architecture –
Part 16-10: Low Power Device Control Protocol – Low Power Proxy Service

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-16-10:2011



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2011 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-16-10:2011



ISO/IEC 29341-16-10

Edition 1.0 2011-08

INTERNATIONAL STANDARD



**Information technology – UPnP device architecture –
Part 16-10: Low Power Device Control Protocol – Low Power Proxy Service**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

F

ICS 35.200

ISBN 978-2-88912-642-2

CONTENTS

1 Overview and Scope.....2

1.1 Referenced Specifications2

1.1.1 Normative References2

1.1.2 Informative References2

1.2 Abbreviations3

2 Service Modeling Definitions for Basic Power Management Proxy3

2.1 ServiceType3

2.2 State Variables.....3

2.2.1 Derived data Types.....3

2.2.2 A_ARG_TYPE_SearchCriteria.....4

2.2.3 A_ARG_TYPE_PowerState4

2.2.4 DeviceListInfo5

2.2.5 A_ARG_TYPE_UUID6

2.2.6 A_ARG_TYPE_Success.....6

2.3 Eventing and Moderation6

2.4 Actions.....6

2.4.1 SearchSleepingDevices6

2.4.2 WakeupDevice.....7

2.5 Theory of Operation.....8

2.5.1 Basic Power Management Proxy Control Point Behavior.....8

2.5.2 Basic Power Management Proxy Service.....9

3 XML Service Description9

4 Test11

Annex A (informative) Sample argument XML string12

Table 1-1 — Abbreviations.....3

Table 2-1 — State Variables for Basic Power Management Proxy Service4

Table 2-2 — Values for A_ARG_TYPE_PowerState:5

Table 2-3 — Event Moderation.....6

Table 2-4 — Actions for BPMPX6

Table 2-5 — Arguments for SearchSleepingDevices.....7

Table 2-6 — Error Codes for SearchSleepingDevices.....7

Table 2-7 — Arguments for WakeupDevice8

Table 2-8 — Error Codes for WakeupDevice8

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 16-10: Low Power Device Control Protocol – Low Power Proxy Service

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-16-10 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

¹ UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-16-10:2011

1 Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0. [DEVICE10]

This service-type enables modeling of “Basic Power Management Proxy” function capabilities. Basic Power Management Proxy (BPMPX) is a combination of UPnP service and a control point. As Control Point, Proxy discovers and controls Low Power Device services running in the network, and as UPnP Proxy service, it advertises itself to the network, and responds to actions from low power aware Control Point. [LPARCH] Basic functions that BPMPX does are as follows:

- Receive multicast discovery messages from power managed UPnP devices in order to be aware of their power states (i.e. the BPMPX will act as Control Point).
- Send multicast or unicast discovery messages (i.e. M-SEARCH) to query UPnP devices and keep track of their power states (i.e. the BPMPX will act as Control Point).
- Send GetPowerManagementInfo action to obtain power management mechanism provided by power-aware devices.
- Should send the appropriate wakeup message to the specified sleeping device when it receives WakeupDevice action from power aware Control Point. [LPARCH]
- Act as UPnP service
 - Sending BPMPX service announcements and M-Search replies.
 - Respond to SearchSleepingDevices action to provide the information of sleeping devices in network.
 - Respond to Wakeup action from Control Point. (Wake up action is directed to the low power devices and not for waking up the BPMPX)

1.1 Referenced Specifications

Unless stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification.

1.1.1 Normative References

This clause lists the normative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[DEVICE10] UPnP Device Architecture, version 1.0.

[XML10] Extensible Markup Language (XML) 1.0 (Second Edition), T. Bray, J.Paoli, C. M. Sperberg-McQueen, E Maler, eds. W3C Recommendations, 6 October 2000.

[LPDEV1] LowPowerDevice:1 Mika Saaranen, Jose Costa-Requena, Shailendra Sinha, Ujwal Paidipathi, Yin-Ling Liong, Yinghua Ye, and Bruce Fairman, etc.

1.1.2 Informative References

This clause lists the informative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[LPARCH] UPnP Low Power Architecture. Ujwal Paidipathi, Jose Costa-Requena, Shailendra Sinha, Yin-Ling Liong, Yinghua Ye, Bruce Fairman, etc.

1.2 Abbreviations

Table 1-1 — Abbreviations

Definition	Description
BPMPX	Basic Power Management Proxy
UUID	Universal Unique Identifier
DDURI	Device Description Document Uniform Resource Identifier

2 Service Modeling Definitions for Basic Power Management Proxy

2.1 ServiceType

The following service type identifies BPMPX service:

urn:schemas-upnp-org:service:LowPowerProxy:1

2.2 State Variables

Reader Note: For first-time reader, it may be more insightful to read the action definitions before reading the state variable definitions.

2.2.1 Derived data Types

This clause defines some derived data types that are represented as UPnP string data types with special syntax.

2.2.1.1 XML Documents as UPnP Arguments

The UPnP Low Power service framework often uses XML documents as arguments in UPnP actions. The UPnP data type is a string. This places restrictions on a string's content; it has to represent a well-formed XML fragment (this includes a complete XML document).

The XML schemas used in UPnP Low Power are defined in the respective files located on <http://www.upnp.org/schemas/lp>

In the XML documents, implementations may use an explicit reference to appropriate name spaces.

Finally, an XML document, conforming to the UPnP V1.0 architecture [DEVICE10], needs to be escaped by using the normal XML rules, defined in clause 2.4 Character Data and Markup of Extensible Markup Language 0, before embedding it in a SOAP request or response message. The XML escaping rules are summarized from the reference 0 mentioned above:

- The (<) character is encoded as (<)
- The (>) character is encoded as (>)
- The (&) character is encoded as (&)
- The (") character is encoded as (")
- The (') character is encoded as (')

Table 2-1 — State Variables for Basic Power Management Proxy Service

Variable Name	Req. or Opt. ^a	Data Type	Allowed Value ^b	Default Value ^b	Eng. Units
A_ARG_TYPE_SearchCriteria	R	string	See clause 2.2.2	N/A	N/A
A_ARG_TYPE_PowerState	R	ui1	See clause 2.2.3	N/A	N/A
DeviceListInfo	R	string (XML document)	See clause 2.2.4	N/A	N/A
A_ARG_TYPE_UUID	O	string	See clause 2.2.5	N/A	N/A
A_ARG_TYPE_Success	O	boolean	See clause 2.2.6	N/A	N/A
<p>^a R = Required, O = Optional, X = Non-standard</p> <p>^b Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.</p>					

2.2.2 A_ARG_TYPE_SearchCriteria

This is a string variable. Allowed values are listed below.

- a) [ssdp:all](#).
Search for all low power enabled device types.
- b) [upnp:rootdevice](#).
[Search for low power enabled root devices only](#).
- c) [uuid:device-UUID](#).
Search for particular low power enabled device. Device "UUID" specified by UPnP vendor.
- d) [urn:schemas-upnp-org:device:deviceType:v](#).
Search for any low power enabled device with this type. Device type and version defined by UPnP forum working committee.
- e) [urn:schemas-upnp-org:service:serviceType:v](#).
Search for any low power enabled device that has a service of this type. Service type and version defined by UPnP forum working committee.
- f) [urn:domain-name:device:deviceType:v](#).
Search for any low power enabled device with matching domain name and this non-standard device type.
- g) [urn:domain-name:service:serviceType:v](#).
Search for any low power enabled device with matching domain name and this non-standard service type.

2.2.3 A_ARG_TYPE_PowerState

This is an integer type state variable. This variable is introduced to provide type information for the "PowerState" parameter in action "SearchSleepingDevices". Allowed values are listed in the Table 2-2.

Table 2-2 — Values for A_ARG_TYPE_PowerState:

Interested PowerState(s)	Value
Reserved for future purposes	1
Deep Sleep Online	2
Deep Sleep Online	3
Deep Sleep Offline	4
Deep Sleep Offline	5
Deep Sleep Online OR Deep Sleep Offline	6
Deep Sleep Online OR Deep Sleep Offline	7

2.2.4 DeviceListInfo

This is escaped XML string as specified in clause 2.2.1.1. DeviceListInfo is a structure that provides information about the sleeping low power enabled devices in the network.

This variable is described by schema identified by “urn: schema-upnp-org:lp:DeviceListInfo”; and it is located at : <http://www.upnp.org/schemas/DeviceListInfo.xsd>.

DeviceInfo: This is a required field if there is a device with matching search criteria and power state in the proxy device list. It is defined as an XML element. A device definition is required for each matching device in the device list.

DeviceFriendlyName: This is optional field. The value is of type string and contains the device friendly name. [DEVICE10]

DDURI: This is a required field. Contains a URL to the UPnP description of the root device. Normally the host portion contains a literal IP address rather than a domain name in unmanaged networks. Specified by UPnP vendor. Single URL.

UUID: This is a required field. The field contains the Universally Unique Identifier of the device. UUIDs are 128 bit numbers that must be formatted as specified by the following grammar.

```

UUID          = 4*<hexOctet>"-" 2*<hexOctet>"-" 2*<hexOctet> "-"
                2*<hexOctet> "-" 6*<hexOctet>
hexOctet      = <hexDigit> <hexDigit>

```

DeviceType: This is a required field. The value is of type string and contains the device type information. For more information about device types refer to [DEVICE10].

Service: This is a required field and defined as an XML element. This field describes the service of the device. A service definition is required for each service supported by the device.

ServiceType: This is required field. The value is of type string and contains service type information. For more information about service type refer to [DEVICE10].

ServiceID: This is required field. The value is of type string and contains the Service Identifier. For more information about serviceID refer to [DEVICE10].

EmbeddedDeviceInfo: This is an optional field and defined as an XML element. This field describes the embedded device information.

EmbeddedService: This is an optional field and defined as an XML element. This field describes the service information of embedded device.

PowerState: This is a required field. The value is an integer and contains the power state of the device. Refer to [LPDEV1] and [LPARCH] for details.

SleepPeriod: This is a required field. The value is an integer and contains the sleep period of the device. Refer to [LPDEV1] and [LPARCH] for details.

WakeupMethod: This is a required field and defined as an XML element. This field describes the method how to wake up the device. Refer to [LPDEV1] and [LPARCH] for details.

ProxyWakeUpPossible: This is a required field. The value is of type string and contains one of the 2 values (Yes, No). This field indicates BPMPX's capabilities of waking up the device.

The sample argument XML string is presented in Annex A.

2.2.5 A_ARG_TYPE_UUID

This is a string type state variable. For more details about the data format refer to [DEVICE10]. This state variable provides type of information for the "UUID" parameter in action WakeupDevice, and contains the "UUID" of the sleeping device that the low power aware control point wants to wake up.

2.2.6 A_ARG_TYPE_Success

This is a Boolean type state variable. This state variable provides type of information for the "Success" parameter in action WakeupDevice. It contains one of the two value ("1", "0"). For more information about the Boolean data type, refer to [DEVICE10].

2.3 Eventing and Moderation

Table 2-3 — Event Moderation

Variable Name	Evented	Moderated Event	Max Event Rate ^a	Logical Combination	Min Delta per Event ^b
DeviceListInfo	No	N/A	N/A	N/A	N/A
^a Determined by N, where Rate = (Event)/(N secs). ^b (N) * (allowedValueRange Step).					

2.4 Actions

Immediately following this table is detailed information about action for a BPMPX, including short descriptions of the action, the effects of the action on state variables, and error codes defined by the actions.

Table 2-4 — Actions for BPMPX

Name	Req. or Opt. ^a
<i>SearchSleepingDevices</i>	R
<i>WakeupDevice</i>	O
^a R = Required, O = Optional, X = Non-standard.	

2.4.1 SearchSleepingDevices

This action allows Low Power Aware Control Points to retrieve the list of sleeping devices that the BPMPX caches. The BPMPX returns the list of sleeping devices matching the

SearchCriteria and the PowerState specified by the Low Power Aware Control Point, included in the “DeviceList” parameter. The “DeviceList” parameter may be NULL (empty string) if there is no matching device found on the BPMPX. The BPMPX only searches the information available on the interface that it used to receive the SearchSleepingDevices action.

2.4.1.1 Arguments

Table 2-5 — Arguments for SearchSleepingDevices

Argument	Direction	relatedStateVariable
SearchCriteria	IN	A_ARG_TYPE_SearchCriteria
PowerState	IN	A_ARG_TYPE_PowerState
DeviceList	OUT	DeviceListInfo

2.4.1.2 Dependency on State (if any)

None

2.4.1.3 Effect on State (if any)

This action doesn't have any effect on the current state of the BPMPX.

2.4.1.4 Errors

Table 2-6 — Error Codes for SearchSleepingDevices

ErrorCode	ErrorDescription	Description
400-499		See UPnP Device Architecture clause on Control.
500-599		See UPnP Device Architecture clause on Control.
600-699		See UPnP Device Architecture clause on Control.
701	Unsupported or invalid Search Criteria	The search criteria is not supported or is invalid
702	PowerState value is out of range	The specified value for the PowerState parameter is out of range.
703	Cannot process the request	Cannot process the request.

2.4.2 WakeupDevice

This action is used to wake up a sleeping device specified by the “UUID”. After receiving wakeup action, the BPMPX will execute the appropriate wakeup method, which should be recognized by the sleeping device. If the device is in Deep Sleep Offline, the BPMPX would require using bearer dependent out of band wake up mechanism.

Success argument value “1” indicates BPMPX successfully executed the appropriate wakeup mechanism to wake up the sleeping device specified by “UUID”. However there is no guarantee that device will be woken up. Value of “0” indicates BPMPX failed to execute the WakeupDevice control action.

2.4.2.1 Arguments

Table 2-7 — Arguments for WakeupDevice

Argument	Direction	RelatedStateVariable
Uuid	IN	A_ARG_TYPE_UUID
Success	OUT	A_ARG_TYPE_Success

2.4.2.2 Dependency on State (if any)

The supplied “UUID” has to be known by BPMPX.

2.4.2.3 Effect on State (if any)

If the action succeeds, the representation of the low power device in BPMPX will change after BPMPX receives the SSDP announcements from the device. If the action fails, the representation of the low power device in BPMPX changes to disconnected.

2.4.2.4 Errors.

Table 2-8 — Error Codes for WakeupDevice

ErrorCode	ErrorDescription	Description
400-499		See UPnP Device Architecture clause on Control.
500-599		See UPnP Device Architecture clause on Control.
600-699		See UPnP Device Architecture clause on Control.
704	Current BPMPX does not know the wakeup mechanism of the sleeping device.	BPMPX does not know how to wake up the device specified by “UUID”.
705	Invalid “UUID” reference	The “UUID” reference argument does not refer to a valid sleeping device.
706	Device is active	The device specified by “UUID” is in active state.

2.5 Theory of Operation

Basic Power Management Proxy (BPMPX) is responsible for discovering Low Power devices and facilitating the discovery of Low Power device in a Low Power state by Low Power Aware Control Points in the network.

2.5.1 Basic Power Management Proxy Control Point Behavior

This clause briefly outlines some typical operations of embedded control point of the BPMPX:

- Discovery of the low power devices and interpretation of their power states in the extended SSDP headers. [LPDEV1] SSDP discovery messages consist of two parts: SSDP announcement messages from low power devices and replies to M-Search messages sent by the BPMPX. When sleeping devices change their power states or leave the network, BPMPX should be able to update DeviceListInfo.
- Use “GetPowerManagementInfo” control action, exposed by the LowPowerDevice -service, [LPDEV1] to get power management related information about the device.
- Use “Wakeup” control action, exposed by the LowPowerDevice -service, to wake up the low power device. [LPDEV1]
- May use bearer specific wake up mechanism [LPARCH] to wake up the low power device.

2.5.2 Basic Power Management Proxy Service

The UPnP BPMPX, which works as a proxy service, exposes the “SearchSleepingDevices” action to the low power aware Control Point. The BPMPX maintains the power management related information of the sleeping devices. On receiving the “SearchSleepingDevices” action, the BPMPX retrieves the list of sleeping devices/services matching the input argument parameters from its stored power management related information. The input argument parameters SearchCriteria and PowerState provide the matching criteria for “SearchSleepingDevices”. The returned DeviceList has to contain at least the following information:

- Device and/or service information as in the SSDP search response
- The power state of the low power enabled device.
- The sleep period of the low power enabled device.
- Whether the current BPMPX can wake up the low power enabled device.
- The bearer specific wake up method of the low power enabled device.

On receiving the “WakeupDevice” action, if the BPMPX knows the bearer specific wakeup mechanism of the device specified by the “UUID” and if the specified device is in deep sleep offline state, the bearer specific wakeup messages will be sent from BPMPX to the sleeping device. If the sleeping device is in deep sleep online state, the Wakeup action will be sent from BPMPX to the sleeping device. If the BPMPX does not get a response from the device, it may try to use the bearer specific wakeup mechanism. If BPMPX receives the action, but fails to send out message(s) to the sleeping device, the OUT argument parameter “Success” returns “0”.

3 XML Service Description

```
<?xml version="1.0" encoding="utf-8"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <actionList>
    <action>
      <name>SearchSleepingDevices</name>
      <argumentList>
        <argument>
          <name>SearchCriteria</name>
          <direction>in</direction>
          <relatedStateVariable>
            A_ARG_TYPE_SearchCriteria
          </relatedStateVariable>
        </argument>
        <argument>
          <name>PowerState</name>
          <direction>in</direction>
          <relatedStateVariable>A_ARG_TYPE_PowerState</relatedStateVariable>
        </argument>
        <argument>
          <name>DeviceList</name>
          <direction>out</direction>
          <relatedStateVariable>DeviceListInfo</relatedStateVariable>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>WakeupDevice</name>
      <argumentList>
        <argument>
          <name>Success</name>
          <direction>in</direction>

```

```

        <relatedStateVariable>A_ARG_TYPE_Success</relatedStateVariable>
      </argument>
    <argument>
      <name>Uuid</name>
      <direction>out</direction>
      <relatedStateVariable>A_ARG_TYPE_UUID</relatedStateVariable>
    </argument>
  </argumentList>
</action>
</actionList>
<serviceStateTable>
  <stateVariable sendEvents="no">
    <name>A_ARG_TYPE_SearchCriteria</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>A_ARG_TYPE_PowerState</name>
    <dataType>u1</dataType>
    <allowedValueRange>
      <minimum>1</minimum>
      <maximum>7</maximum>
    </allowedValueRange>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>DeviceListInfo</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>A_ARG_TYPE_UUID</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>A_ARG_TYPE_Success</name>
    <dataType>boolean</dataType>
  </stateVariable>
</serviceStateTable>
</scpd>

```

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-16-10:2011

4 Test

No semantic tests have been specified for this service.

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-16-10:2011