



ISO/IEC 29341-8-1

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –  
Part 8-1: Internet Gateway Device Control Protocol – Internet Gateway Device

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2008 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008



ISO/IEC 29341-8-1

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

Information technology – UPnP Device Architecture –  
Part 8-1: Internet Gateway Device Control Protocol – Internet Gateway Device

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

**E**

---

ICS 35.200

ISBN 2-8318-1009-2

## CONTENTS

FOREWORD .....	3
ORIGINAL UPNP DOCUMENTS (informative) .....	5
<b>1. Overview and Scope .....</b>	<b>7</b>
1.1. Requirements for an Internet Gateway Device .....	7
1.2. Focus and Goals for DCP version 1.0.....	8
1.3. Non-Goals for DCP version 1.0.....	9
<b>2. Device Definitions .....</b>	<b>10</b>
2.1. Device Type .....	10
2.2. Device Model.....	10
2.2.1. Description of Device Requirements .....	11
2.2.2. Relationships Between Services.....	11
2.3. Theory of Operation .....	12
<b>3. XML Device Description .....</b>	<b>13</b>
<b>4. Test.....</b>	<b>16</b>

## LIST OF TABLES

Table 1: Device Requirements .....	10
------------------------------------	----

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008

# INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

## Part 8-1: Internet Gateway Device Control Protocol – Internet Gateway Device

### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation  
Standards Licensing Department  
5200 NE Elam Young Parkway  
MS: JFS-98  
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 / US

Information may be obtained from:

Microsoft Corporation  
One Microsoft Way  
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S  
High Tech campus, building 44 3A21  
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)  
High Tech campus 60  
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.  
1-3-7 Shiromi, Chuoh-ku  
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company  
1501 Page Mill Road  
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.  
416 Maetan-3 Dong, Yeongtang-Gu,  
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-8-1 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

## ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPoEConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QoSDevice:1 Service	ISO/IEC 29341-10-10
UPnP QoSManager:1 Service	ISO/IEC 29341-10-11
UPnP QoSPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

<b>UPnP Document Title</b>	<b>ISO/IEC 29341 Part</b>
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008

# 1. Overview and Scope

This device template is compliant with the UPnP Device Architecture, Version 1.0.

This document defines the REQUIRED **ROOT** device  
**urn:schemas-upnp-org:device:InternetGatewayDevice.**

The **InternetGatewayDevice** encapsulates all sub-devices and services for the Internet Gateway Device Control Protocol (DCP).

The Internet Gateway is an “edge” interconnect device between a residential Local Area Network (LAN) and the Wide Area Network (WAN), providing connectivity to the Internet. The gateway MAY be physically implemented as a dedicated, standalone device or modeled as a set of UPnP devices and services on a PC. This version of the DCP does not cover small business networks. Discovery and access to these services from outside the home network is not recommended, unless adequate authentication, authorization and access control mechanisms are built into the device, beyond what is currently specified within the UPnP architecture framework.

Figure 1 below is a conceptual illustration of a generic Internet Gateway device consisting of one or more physical WAN and LAN interfaces.




Figure 1: **InternetGatewayDevice** with LAN and WAN Interfaces

## 1.1. Requirements for an Internet Gateway Device

The following list of requirements has been identified on the capabilities of an Internet Gateway in coming up with the devices and services hierarchy for the gateway DCP.

- The **InternetGatewayDevice** MUST support 1 WAN interface, but MAY support more than one physical WAN interface to connect to the Internet.
- The **InternetGatewayDevice** MUST support 1 LAN interface, but MAY support more than one physical LAN interface to connect to the residential network.

An implementation MAY host the WAN interface and LAN interface (mentioned above) on the same physical network interface card (NIC).

- Each WAN interface MUST support one Internet connection, but MAY simultaneously support more than one Internet connection. Each of these connections will be modeled as instances of a service in the DCP.
- The **InternetGatewayDevice** must be IP addressable from the residential LAN at all times to be UPnP compliant. More specifically, in the case of gateways with broadband modems on the WAN side, the **InternetGatewayDevice** must be addressable
  - When the device is not configured for WAN access or does not have any WAN connectivity
  - Before, during and after modem and link configuration with a head-end device in the Internet service provider's central office.
- Connectivity on the WAN side MUST enable nodes on the residential LAN to access resources on the Internet. A gateway MAY support modems and/or connections on a modem to a service provider, not resulting in Internet connectivity – for example, POTS dial-up access to a modem bank of a home security monitoring service provider. Such connections are outside the scope and requirements of the gateway DCP.

In this document, an Internet connection implies IP connectivity to an Internet Service Provider. Figure 2 illustrates the hierarchy of devices and services in an **InternetGatewayDevice**. A physical modem on the WAN side and a connection interface/port on the LAN side of the **InternetGatewayDevice** are modeled by a **WANDevice** and a **LANDevice** instance respectively. Depending on the hardware capabilities of an Internet Gateway, more than 1 instance of **WANDevice** and/or **LANDevice** are possible in an actual implementation of the gateway DCP description document. Virtual connection interfaces – such as Virtual Circuits (VC) on a DSL modem, are modeled by one or more instances of **WANConnectionDevice**. Sub-devices and services mentioned in this document are defined in companion documents that together specify the DCP for an Internet Gateway.




Figure 2: **InternetGatewayDevice** Devices and Services Hierarchy

## 1.2. Focus and Goals for DCP version 1.0

The Gateway Working Committee (IGD WC) agreed to focus on the following set of requirements in coming up with the hierarchy of devices and services for DCP v1.0.

- Sharing and configurable initiation of Internet data access among networked devices in the residential network.
- Richer end-user experience for UPnP enabled devices
  - Provide status and events on connections
  - Control of initiation and termination of connections
- Management of host configuration services
  - DHCP, Dynamic DNS (DDNS)
- Preserve ability of non-UPnP devices to initiate and/or share Internet access.

### 1.3. Non-Goals for DCP version 1.0

The following work items were discussed and considered to be beyond the scope of this version of the DCP.

- Configuration and connection management services for an ISDN modem
- Access control and user/device authentication services
- Advanced routing mechanisms across multiple, simultaneous, active connections on multiple WAN interfaces
- LAN interface physical layer services
- Fine-grained configuration and management of features specific to Ethernet bridging across multiple LAN segments / subnets and/or between LAN segments and WAN Internet connection(s).
- VPN services (outside-in or a VPN client initiating from the Internet Gateway)
- Services enabling bandwidth management on active Internet connections
- Exclusivity on initiation and sharing of active connections
- Modeling of firewall features
  - Too many technologies and component layers makes it hard to model
  - May be offered as vendor extensions
- Issues that come up in the context of multiple, simultaneously active Internet Gateway devices – for example, default gateway conflict resolution, load balancing and fail over
- Other non-connectivity related gateway functions
  - Multimedia translation and caching
  - Interfacing to “service” gateways

IECNORM.COM : Click to view the full PDF of ISO/IEC 29341-8-1:2008

## 2. Device Definitions

### 2.1. Device Type

The following device type identifies a device that is compliant with this template:

urn:[schemas-upnp-org:device:InternetGatewayDevice:1](#)

### 2.2. Device Model

Products that expose devices of the type urn:schemas-upnp-org:device:[InternetGatewayDevice:1](#) must implement minimum version numbers of all required embedded devices and services specified in the table below.

Table 1: Device Requirements

DeviceType	Root	Req. or Opt. <sup>1</sup>	ServiceType	Req. or Opt. <sup>1</sup>	Service ID <sup>2</sup>
			<a href="#">Layer3Forwarding:1</a>	<u>O</u>	<a href="#">L3Forwarding1</a>
			<i>Non-standard services embedded by an UPnP vendor go here.</i>	X	TBD
<a href="#">WANDevice:1</a>		<u>R</u>	<a href="#">WANCommonInterfaceConfig:1</a>	<u>R</u>	<a href="#">WANCommonIFC1</a>
			<i>Non-standard services embedded by an UPnP vendor go here.</i>	X	TBD
<a href="#">WANConnectionDevice:1</a> <i>(an instance of WANDevice may include one or more WANConnectionDevice instances)</i>		<u>R</u>	<a href="#">WANPOTSLinkConfig:1</a>	<u>O for POTS modems</u>	<a href="#">WANPOTSLinkC1</a>
			<a href="#">WANDSLLinkConfig:1</a>	<u>O for DSL modems</u>	<a href="#">WANDSLLinkC1</a>
			<a href="#">WANCableLinkConfig:1</a>	<u>O for Cable modems</u>	<a href="#">WANCableLinkC1</a>
			<a href="#">WANEthernetLinkConfig:1</a>	<u>O for Ethernet attached modems</u>	<a href="#">WANEthLinkC1</a>
			<a href="#">WANPPPConnection:1</a>	<u>R for modems that support PPP based connections</u>	<u>Multiple instances possible within a WANConnectionDevice. ServiceIDs for multiple instances will be WANPPPConn1, WANPPPConn2, WANPPPConn3 and so on.</u>
			<a href="#">WANIPConnection:1</a>	<u>R for modems that support IP based connections</u>	<u>Only 1 instance per WANConnectionDevice is envisioned at this time, although the design could support multiple instances in future. ServiceIDs for multiple instances</u>

					<i>will be WANIPConn1, WANIPConn2, WANIPConn3 and so on.</i>
			<i>Non-standard services embedded by an UPnP vendor go here.</i>	<i>X</i>	<i>TBD</i>
<i>LANDevice:1</i>		<i>O</i>	<i>LANHostConfigManagement:1</i>	<i>O</i>	<i>LANHostCf1</i>
<i>Non-standard devices embedded by a UPnP vendor go here.</i>	<i>TBD</i>	<i>X</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

<sup>1</sup> R = Required, O = Optional, X = Non-standard.

<sup>2</sup> Prefixed by urn:[upnp-org](http://www.upnp.org):[serviceId](http://www.upnp.org): .

### 2.2.1. Description of Device Requirements

As shown in the table above, the DCP defines 2 **Connection** services and 4 **LinkConfig** services to accommodate various types of WAN interfaces and connection types. The following table briefly describes the purpose of each of the services. An actual implementation of the DCP will instance only those **Connection** and **LinkConfig** services that are appropriate for the gateway device being modeled.

Service Name	Service Description
WANPPPConnection	PPP connections originating at the gateway or relayed or bridged through the gateway
WANIPConnection	IP connections originating or relayed or bridged through the gateway
WANPOTSLinkConfig	Configuration parameters associated with a WAN link on a Plain Old Telephone Service (POTS) modem
WANDSLLinkConfig	Configuration parameters associated with a WAN link on a Digital Subscriber Link (DSL) modem
WANCableLinkConfig	Configuration parameters associated with a WAN link on a cable modem
WANEthernetLinkConfig	Configuration parameters associated with an Ethernet- attached external modem (cable or DSL). If proprietary mechanisms are available to discover and configure an external modem, it is recommended that modem-specific <b>LinkConfig</b> services be modeled instead of this service.

### 2.2.2. Relationships Between Services

**Layer3Forwarding** identifies a default service, which is a specific instance of **WAN{PPP/IP}Connection** in a **WANConnectionDevice**. **WANCommonInterfaceConfig** defines variables and actions common across all instances of **WAN{PPP/IP}Connections** in a **WANDevice**. There may also be dependencies between a specific instance of **WAN\*LinkConfig** and **WAN\*\*Connection** service in a **WANConnectionDevice**.

## 2.3. Theory of Operation

Each **WANDevice** in Figure 1 can be viewed as an instantiation of a physical WAN interface. If an **InternetGatewayDevice** provides multiple WAN physical interfaces to UPnP clients, each of these will typically be included in the device description document as distinct **WANDevice** instances. However, an implementation may choose to encapsulate more than one physical WAN interface in a single **WANDevice**. This may be done, for example, in applications that use asymmetric connections like a satellite downlink and POTS uplink. Another example would be where multiple physical WAN interfaces are pooled and presented as one device. Aspects such as load balancing between the pooled resources would be transparent to UPnP clients in this case.

All Internet connections are set up from or through a WAN interface of the **InternetGatewayDevice** to Internet Service Providers (ISPs). **WANDevice** is a container for all UPnP services associated with a physical WAN device. It is assumed that clients are connected to **InternetGatewayDevice** via a LAN (IP-based network). Each link on a WAN interface is modeled by an instance of **WANConnectionDevice** in **WANDevice**. A **WANConnectionDevice** in turn contains one link-specific **WAN\*LinkConfig**<sup>1</sup> service (where \* can be POTS, DSL, Cable or Ethernet) and one or more instances of **WAN\*\*Connection** service (where \*\* can be PPP or IP).

In accordance with UPnP Device Architecture version 1.0, the maximum number of **WAN\*\*Connection** service instances is static and specified in the **InternetGatewayDevice** description document.

A **WANDevice** provides a **WANCommonInterfaceConfig** service that encapsulates Layer 1 and Layer 2 properties relevant to Internet access common to the specific WAN access type and across multiple **WAN\*\*Connection** service instances.

The gateway device may also support multiple physical LAN interfaces. It may support distinct subnets of client nodes on the residential network. Each **LANDevice** – identified in the device description document with a UDN – typically corresponds to a physical LAN interface (or port) on the **InternetGatewayDevice**. However, an implementation may choose to encapsulate more than one physical LAN interface in a single **LANDevice**. This would be the case if two LAN subnets that are bridged are to be presented as a single logical LAN interface. Devices on a LAN may configure, initiate and/or share Internet connections.

The **InternetGatewayDevice** may also support Layer-3 packet transformation and forwarding functions managed and applicable across all connection instances. These functions are currently modeled in **Layer3Forwarding** service. Layer-3 packet forwarding functions that are specific to a connection will be modeled in each **WAN\*\*Connection** service instance.

<sup>1</sup> The WC has not defined link configuration services for interfaces types other than those listed above. If needed, these can be implemented as vendor-proprietary extensions.

### 3. XML Device Description

```

<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <deviceType>urn:schemas-upnp-
org:device:InternetGatewayDevice:1</deviceType>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelName>model number</modelName>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <iconList>
      <icon>
        <mimetype>image/format</mimetype>
        <width>horizontal pixels</width>
        <height>vertical pixels</height>
        <depth>color depth</depth>
        <url>URL to icon</url>
      </icon>
      <!-- XML to declare other icons, if any, go here -->
    </iconList>
    <serviceList>
      <service>
        <serviceType>urn:schemas-upnp-
org:service:Layer3Forwarding:1</serviceType>
        <serviceId>urn:upnp-org:serviceId:L3Forwarding1</serviceId>
        <SCPURL>URL to service description</SCPURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      <!-- Declarations for other services added by UPnP vendor (if
any) go here -->
    </serviceList>
  </deviceList>
  <deviceList>
    <device>
      <deviceType>urn:schemas-upnp-org:device:WANDevice:1</deviceType>
      <friendlyName>short user-friendly title</friendlyName>
      <manufacturer>manufacturer name</manufacturer>
      <manufacturerURL>URL to manufacturer site</manufacturerURL>
      <modelDescription>long user-friendly title</modelDescription>
      <modelName>model name</modelName>
      <modelName>model number</modelName>
      <modelURL>URL to model site</modelURL>
      <serialNumber>manufacturer's serial number</serialNumber>
      <UDN>uuid:UUID</UDN>
      <UPC>Universal Product Code</UPC>
      <iconList>
        <icon>
          <mimetype>image/format</mimetype>
          <width>horizontal pixels</width>
          <height>vertical pixels</height>
        </icon>
      </iconList>
    </device>
  </deviceList>
</root>

```

```

        <depth>color depth</depth>
        <url>URL to icon</url>
    </icon>
    XML to declare other icons, if any, go here
</iconList>
<serviceList>
    <service>
        <serviceType>urn:schemas-upnp-
org:service:WANCommonInterfaceConfig:1</serviceType>
        <serviceId>urn:upnp-org:serviceId:WANCommonIFC1</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
    </service>
    <!-- Declarations for other services added by UPnP vendor (if
any) go here -->
</serviceList>
<deviceList>
    <device>
        <deviceType>urn:schemas-upnp-
org:device:WANConnectionDevice:1</deviceType>
        <friendlyName>short user-friendly title</friendlyName>
        <manufacturer>manufacturer name</manufacturer>
        <manufacturerURL>URL to manufacturer site</manufacturerURL>
        <modelDescription>long user-friendly title</modelDescription>
        <modelName>model name</modelName>
        <modelName>model name</modelName>
        <modelNumber>model number</modelNumber>
        <modelURL>URL to model site</modelURL>
        <serialNumber>manufacturer's serial number</serialNumber>
        <UDN>uuid:UUID</UDN>
        <UPC>Universal Product Code</UPC>
        <iconList>
            <icon>
                <mimetype>image/format</mimetype>
                <width>horizontal pixels</width>
                <height>vertical pixels</height>
                <depth>color depth</depth>
                <url>URL to icon</url>
            </icon>
            XML to declare other icons, if any, go here
        </iconList>
        <serviceList>
            <service>
                <serviceType>urn:schemas-upnp-
org:service:WANPOTSLinkConfig:1</serviceType>
                <serviceId>urn:upnp-
org:serviceId:WANPOTSLinkC1</serviceId>
                <SCPDURL>URL to service description</SCPDURL>
                <controlURL>URL for control</controlURL>
                <eventSubURL>URL for eventing</eventSubURL>
            </service>
            <service>
                <serviceType>urn:schemas-upnp-
org:service:WANPPPConnection:1</serviceType>
                <serviceId>urn:upnp-org:serviceId:WANPPPConn1</serviceId>
                <SCPDURL>URL to service description</SCPDURL>
                <controlURL>URL for control</controlURL>
            </service>
        </serviceList>
    </device>
</deviceList>

```

<sup>2</sup> NOTE to implementers: This template is representative of one device type – a POTS modem in this case. Depending on the type of modem, substitute or add device specific service names.

<sup>3</sup> NOTE to implementers: This template is representative of one connection type – dial-up PPP in this case. Depending on the type of connection, substitute or add device specific service names.