
**Information technology — Open Systems
Interconnection — Connection-oriented
Session protocol: Protocol Implementation
Conformance Statement (PICS) proforma**

*Technologies de l'information — Interconnexion de systèmes
ouverts (OSI) — Protocole de session en mode orienté connexion:
Formulaire de déclaration de conformité de la mise en œuvre du protocole
(PICS)*

IECNORM.COM : Click to view the full PDF of ISO/IEC 8327-2:1996

Contents

| | <i>Page</i> |
|---|-------------|
| 1 Scope..... | 1 |
| 2 Normative references | 1 |
| 2.1 Identical Recommendations International Standards | 1 |
| 2.2 Paired Recommendations International Standards equivalent in technical content | 1 |
| 3 Definitions..... | 2 |
| 4 Abbreviations | 2 |
| 5 Conformance..... | 2 |
| Annex A – Protocol Implementation Conformance Statement (PICS) Proforma for the Connection-Oriented Session Protocol..... | 3 |
| A.1 Identification of PICS proforma corrigenda | 3 |
| A.2 Instructions..... | 3 |
| A.2.1 Purpose and structure of the proforma..... | 3 |
| A.2.2 Symbols, terms and abbreviations | 3 |
| A.2.2.1 Introduction..... | 3 |
| A.2.2.2 Item numbering..... | 4 |
| A.2.2.3 Status column..... | 4 |
| A.2.2.4 Support column..... | 6 |
| A.2.2.5 Value column..... | 6 |
| A.2.2.6 Mnemonic column | 6 |
| A.2.2.7 Length column | 6 |
| A.2.3 Instructions for completion | 7 |
| A.3 Identification of the implementation..... | 7 |
| A.3.1 Date of statement | 7 |
| A.3.2 Implementation details..... | 7 |
| A.4 Protocol Identification | 8 |
| A.4.1 ITU-T Rec. X.225 ISO/IEC 8327-1 protocol details | 8 |
| A.4.2 ITU-T Rec. X.225 ISO/IEC 8327-1 protocol versions | 8 |
| A.4.3 ITU-T Rec. X.225 ISO/IEC 8327-1 technical corrigenda implemented..... | 8 |
| A.5 Global statement of conformance | 8 |
| A.6 Supported functional units and protocol mechanisms | 9 |
| A.6.1 Functional units..... | 9 |
| A.6.2 Protocol mechanisms | 9 |

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

| | | |
|--------|---|----|
| A.7 | Supported SPDUs | 10 |
| A.7.1 | Kernel functional unit | 10 |
| | A.7.1.1 Supported roles | 10 |
| | A.7.1.2 Support for the SPDUs associated with the Kernel functional unit | 11 |
| | A.7.1.3 Support for the SPDUs associated with Token Exchange | 11 |
| A.7.2 | Negotiated Release functional unit | 11 |
| | A.7.2.1 Supported roles | 11 |
| | A.7.2.2 Support for the SPDUs associated with the Negotiated Release functional unit | 11 |
| A.7.3 | Half Duplex functional unit | 12 |
| | A.7.3.1 Supported roles | 12 |
| | A.7.3.2 Support for the SPDUs associated with the Half Duplex functional unit | 12 |
| A.7.4 | Duplex functional unit | 12 |
| A.7.5 | Expedited Data functional unit | 12 |
| | A.7.5.1 Supported roles | 12 |
| | A.7.5.2 Support for the SPDU associated with the Expedited Data functional unit | 12 |
| A.7.6 | Typed Data functional unit | 12 |
| | A.7.6.1 Supported roles | 12 |
| | A.7.6.2 Support for the SPDU associated with the Typed Data functional unit | 13 |
| A.7.7 | Capability Data functional unit | 13 |
| | A.7.7.1 Supported roles | 13 |
| | A.7.7.2 Support for the SPDUs associated with the Capability Data functional unit | 13 |
| A.7.8 | Minor synchronize functional unit | 13 |
| | A.7.8.1 Supported roles | 13 |
| | A.7.8.2 Support for the SPDUs associated with the Minor synchronize functional unit | 13 |
| A.7.9 | Symmetric synchronize functional unit | 14 |
| | A.7.9.1 Supported roles | 14 |
| | A.7.9.2 Support for the SPDUs associated with the Symmetric synchronize functional unit | 14 |
| A.7.10 | Data separation functional unit | 14 |
| A.7.11 | Major synchronize functional unit | 14 |
| | A.7.11.1 Supported roles | 14 |
| | A.7.11.2 Support for the SPDUs associated with the Major synchronize functional unit | 14 |
| A.7.12 | Resynchronize functional unit | 15 |
| | A.7.12.1 Supported roles | 15 |
| | A.7.12.2 Supported resynchronize types | 15 |
| | A.7.12.3 Support for the SPDUs associated with the Resynchronize functional unit | 15 |
| A.7.13 | Exceptions functional unit | 15 |
| | A.7.13.1 Supported roles | 15 |
| | A.7.13.2 Support for the SPDUs associated with the Exceptions functional unit | 16 |
| A.7.14 | Activity management functional unit | 16 |
| | A.7.14.1 Supported roles | 16 |
| | A.7.14.2 Support for the SPDUs associated with the Activity management functional unit | 17 |
| A.8 | Supported SPDU-parameters | 18 |
| A.8.1 | Connect (CN) SPDU | 18 |
| | A.8.1.1 Connection Identifier | 18 |
| | A.8.1.2 Connect/Accept Item | 18 |
| | A.8.1.3 Single Items | 19 |
| A.8.2 | Overflow Accept (OA) SPDU | 19 |
| A.8.3 | Connect Data Overflow (CDO) SPDU | 19 |

| | | |
|---|--|----|
| A.8.4 | Accept (AC) SPDU..... | 20 |
| | A.8.4.1 Connection Identifier | 20 |
| | A.8.4.2 Connect/Accept Item..... | 20 |
| | A.8.4.3 Single Items | 21 |
| A.8.5 | Refuse (RF) SPDU..... | 21 |
| | A.8.5.1 Connection Identifier | 21 |
| | A.8.5.2 Single Items | 22 |
| A.8.6 | Finish (FN) SPDU..... | 22 |
| A.8.7 | Disconnect (DN) SPDU..... | 22 |
| A.8.8 | Not Finish (NF) SPDU..... | 23 |
| A.8.9 | Abort (AB) SPDU..... | 23 |
| A.8.10 | Abort Accept (AA) SPDU | 23 |
| A.8.11 | Data Transfer (DT) SPDU | 23 |
| A.8.12 | Expedited Data (EX) SPDU..... | 23 |
| A.8.13 | Typed Data (TD) SPDU..... | 24 |
| A.8.14 | Capability Data (CD) SPDU..... | 24 |
| A.8.15 | Capability Data Ack (CDA) SPDU | 24 |
| A.8.16 | Give Tokens (GT) SPDU..... | 24 |
| A.8.17 | Please Tokens (PT) SPDU | 25 |
| A.8.18 | Minor Sync Point (MIP) SPDU | 25 |
| A.8.19 | Minor Sync Ack (MIA) SPDU | 25 |
| A.8.20 | Major Sync Point (MAP) SPDU..... | 26 |
| A.8.21 | Major Sync Ack (MAA) SPDU | 26 |
| A.8.22 | Resynchronize (RS) SPDU | 26 |
| A.8.23 | Resynchronize Ack (RA) SPDU..... | 27 |
| A.8.24 | Prepare (PR) SPDU..... | 27 |
| A.8.25 | Exception Report (ER) SPDU..... | 27 |
| A.8.26 | Exception Data (ED) SPDU..... | 27 |
| A.8.27 | Give Tokens Confirm (GTC) SPDU..... | 28 |
| A.8.28 | Give Tokens Ack (GTA) SPDU | 28 |
| A.8.29 | Activity Start (AS) SPDU | 28 |
| A.8.30 | Activity Resume (AR) SPDU | 28 |
| | A.8.30.1 Linking Information..... | 28 |
| | A.8.30.2 Single Items | 29 |
| A.8.31 | Activity Interrupt (AI) SPDU | 29 |
| A.8.32 | Activity Interrupt Ack (AIA) SPDU..... | 29 |
| A.8.33 | Activity Discard (AD) SPDU | 29 |
| A.8.34 | Activity Discard Ack (ADA) SPDU..... | 30 |
| A.8.35 | Activity End (AE) SPDU..... | 30 |
| A.8.36 | Activity End Ack (AEA) SPDU | 30 |
| Annex B – List of conditional statements | | 32 |
| Annex C – List of mnemonics used in the conditional and optional statements | | 36 |

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 8327-2 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open Systems Interconnection, data management and open distributed processing*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.245.

ISO/IEC 8327 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — Connection-oriented Session protocol*:

- *Part 1: Protocol specification*
- *Part 2: Protocol Implementation Conformance Statement (PICS) proforma*

Annex A forms an integral part of this part of ISO/IEC 8327. Annexes B and C are for information only.

IECNORM.COM : Click to view the full PDF of ISO/IEC 8327-2:1996

Introduction

This Recommendation | International Standard is one of a set of Recommendations | International Standards produced to facilitate the interconnection of information processing systems. It is related to other Recommendations and International Standards in the set as defined by the Reference Model for Open Systems Interconnection (see ITU-T Rec. X.200 | ISO/IEC 7498-1). The Reference Model subdivides the area of standardization for interconnection into a series of layers of specification, each of manageable size.

The goal of Open Systems Interconnection is to allow, with a minimum of technical agreement outside the interconnection standards, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different technologies.

ITU-T Rec. X.225 | ISO/IEC 8327-1 specifies the Connection-Oriented Session Protocol.

To evaluate the conformance of a particular implementation, it is necessary to have a description of the capabilities and options which have been implemented. Such a description is called a Protocol Implementation Conformance Statement (PICS).

This Recommendation | International Standard includes the PICS proforma for the Connection-Oriented Session Protocol as defined in ITU-T Rec. X.225 | ISO/IEC 8327-1.

IECNORM.COM : Click to view the full PDF of ISO/IEC 8327-2:1996

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
CONNECTION-ORIENTED SESSION PROTOCOL: PROTOCOL IMPLEMENTATION
CONFORMANCE STATEMENT (PICS) PROFORMA**

1 Scope

This Recommendation | International Standard provides the Protocol Implementation Conformance Statement (PICS) proforma for the connection-oriented Session protocol specification ITU-T Rec. X.225 | ISO/IEC 8327-1. This PICS proforma is in compliance with the relevant requirements, and in accordance with the relevant guidance for a PICS proforma, given in ITU-T Rec. X.296 | ISO/IEC 9646-7. Detail of the use of this proforma is provided in this Recommendation | International Standard.

The supplier of an implementation which is claimed to conform to ITU-T Rec. X.225 | ISO/IEC 8327-1 is required to complete a copy of the PICS proforma provided in Annex A, and is required to provide the information necessary to uniquely identify both the supplier and the implementation.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and the parties to agreement based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunications Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.214 (1993) | ISO/IEC 8072:1994, *Information technology – Open Systems Interconnection – Transport service definition.*
- ITU-T Recommendation X.215 (1995) | ISO/IEC 8326:1996, *Information technology – Open Systems Interconnection – Session service definition.*
- ITU-T Recommendation X.225 (1995) | ISO/IEC 8327-1:1996, *Information technology – Open Systems Interconnection – Connection-oriented Session protocol – Protocol specification.*

2.2 Paired Recommendations | International Standards equivalent in technical content

- ITU-T Recommendation X.290 (1995), *OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications – General concepts.*
- ISO/IEC 9646-1:1994, *Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 1: General concepts.*

- ITU-T Recommendation X.296 (1995), *OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications – Implementation conformance statements.*
ISO/IEC 9646-7:1995, *Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 7: Implementation Conformance Statements.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

- 3.1 Terms defined in ITU-T Rec. X.225 | ISO/IEC 8327-1.
- 3.2 The following terms defined in ITU-T Rec. X.290 | ISO/IEC 9646-1:
- a) Protocol Implementation Conformance Statement (PICS);
 - b) PICS proforma.
- 3.3 Additional terms:
- Requestor: the SPM that initiates a particular action;
 - Acceptor: the SPM that accepts a particular action.

4 Abbreviations

- 4.1 Abbreviations are given in ITU-T Rec. X.225 | ISO/IEC 8327-1 and in clause 8.
- 4.2 This Recommendation | International Standard makes use of the following abbreviation given in ITU-T Rec. X.290 | ISO/IEC 9646-1:
- PICS.
- 4.3 For the purposes of this Recommendation | International Standard, the following abbreviations also apply:
- | | |
|------------|----------------|
| Sts | Status column |
| Spt | Support column |
| Sdr | Sender |
| Rcv | Receiver |

5 Conformance

A conforming PICS shall be technically equivalent to the ITU | ISO/IEC published PICS proforma and shall preserve the numbering and ordering of the items in the ITU | ISO/IEC PICS proforma.

A PICS which conforms to this Recommendation | International Standard shall:

- a) describe an implementation which conforms to ITU-T Rec. X.225 | ISO/IEC 8327-1;
- b) be a conforming PICS proforma, which has been completed in accordance with the instructions for completion given in A.2;
- c) include the information necessary to uniquely identify both the supplier and the implementation.

Annex A

Protocol Implementation Conformance Statement (PICS) Proforma for the Connection-Oriented Session Protocol¹⁾

(This annex forms an integral part of this Recommendation | International Standard)

A.1 Identification of PICS proforma corrigenda

The supplier of the PICS proforma shall identify any corrigenda (i.e. Technical Corrigenda or equivalent) to the published proforma that have been applied. Suppliers of the proforma should modify the proforma, or attach relevant additional pages in order to apply the corrigenda, and then record the application of the corrigenda in the table below.

| | |
|--|--|
| Identification of corrigenda applied to this PICS proforma | ITU-T Rec. X.245 (1995) ISO/IEC 8327-2:1996 Corr: Corr: Corr: |
|--|--|

A.2 Instructions

A.2.1 Purpose and structure of the proforma

The purpose of this PICS proforma is to provide suppliers of implementation of ITU-T Rec. X.225 | ISO/IEC 8327-1 with a consistent means of stating which capabilities have been implemented.

The proforma is in form of a questionnaire and consists of a set of items. An item is provided for each capability for which an implementation choice is allowed. Items are also provided for major mandatory capabilities for which no implementation choice is allowed. Each item includes an item number, an item description, a status value specifying the support requirement, and room for a support answer to be provided by the supplier.

This clause provides general information and instructions for completion of the proforma.

Subclause A.3 is for identification of the implementation.

Subclause A.4 contains the means of specifying, at high level, the protocol and corrigenda that have been implemented.

Subclause A.5 contains the global statement of conformance.

Subclauses A.6 onwards contain tables in which the supplier specifies details of the implementation options chosen.

NOTE – Throughout the PICS proforma, tables specifying Requestor and Acceptor roles are inserted as required for precise definition of the status of SPDUs and SPDU parameters, but these tables shall not be used for static conformance review nor for test case selection.

A.2.2 Symbols, terms and abbreviations

A.2.2.1 Introduction

Notations have been introduced in order to reduce the size of tables in the PICS proforma. These have allowed the use of multi-column layout where the columns are headed 'Status', 'Support', 'Value', 'Mnemonic' and 'Length'. The definition of each are given below.

Additionally, the following definitions apply.

A.2.2.1.1 (PICS) item: A row in a PICS proforma table.

¹⁾ Copyright release for PICS proformas: Users of this Recommendation | International Standard may freely reproduce the PICS proforma in this annex so that it can be used for its intended purpose and may further publish the completed PICS.

A.2.2.1.2 (PICS) question: The question to be answered in the intersection of a PICS item and either a support column (i.e. "Is this item supported in the context applying to this table and column") or supported values column (i.e. "What values are supported for this item in the context applying to this table and column") in a PICS proforma table.

A.2.2.1.3 status (value): An allowed entry in the status column for an item in a PICS proforma table.

A.2.2.1.4 (support) answer: An allowed entry in the support or supported values columns for an item in a PICS, in answer to a PICS question.

A.2.2.2 Item numbering

Each line within the PICS proforma which requires implementation detail to be entered is given an item number in the first column. The item number column provides a means of uniquely referencing each possible answer within the PICS proforma. Such referencing is necessary for specifying predicates, conditional expressions, test suite parameters, and test suite selection expressions.

The means of referencing individual answers is to specify the following sequence:

- a) if, and only if, the reference is being made from another Specification, then start with an unambiguous identifier for the relevant ICS proforma specification, enclosed in parentheses – this identifier is stated in the PICS proforma specification and is updated whenever the PICS proforma is updated – it is recommended that this identifier should be relevant Specification number and year of publication, as is used in a Normative References clause, and this is the default for such identifiers;
- b) the number of the relevant table or, if the tables are not numbered, of the smallest subclause enclosing the relevant table;
- c) a solidus character, "/";
- d) the item number or mnemonic reference to the item, to identify the row in which the answer appears;
- e) if, and only if, more than one question occurs in the row identified by the item number or mnemonic reference, then each possible answer is implicitly labelled a, b, c, etc., from left to right, and this letter is appended to the sequence, prefixed by a solidus character ("/") if a mnemonic reference is used.

If mnemonic references are specified and each uniquely identify an item in the PICS proforma, then entries b) and c) in the above sequence may be omitted.

A.2.2.3 Status column

This column indicates the level of support required for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1, the given values are taken from the Session Protocol Specification (see ITU-T Rec. X.225 | ISO/IEC 8327-1).

A.2.2.3.1 Definitions applying to the tables in clauses A.4 to A.6

The values are as follows:

- 'm' Mandatory support is required. The implementation shall support the functionalities described in ITU-T Rec. X.225 | ISO/IEC 8327-1 for the specified item.
- 'o' Optional support is permitted for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1. According to some specific reason, the implementation is not obliged to support the specified item. If implemented, it shall conform to the specifications and restrictions contained in ITU-T Rec. X.225 | ISO/IEC 8327-1. Therefore the constraints described for the mandatory support above also apply.
- 'o.n' Selectable options among a set of items (where n is the number which identifies the group of optionals which are linked together). The implementation shall support at least one of the given items. [For the selected item(s), the constraints described for the mandatory support above also apply.]
- 'cn' The item is conditional (where n is the number which identifies the condition which is applicable). The definitions for the conditional statements used in Annex A are written under the table where they are used, and indexed in Annex B.
- 'n/a' The item is not applicable.

A.2.2.3.2 Definitions applying to the tables in clause A.7 (Supported SPDUs)

The values are as follows:

Sender item:

- 'm' Mandatory support is required. The implementation shall be able:
 - to build the SPDU (i.e. to build correctly the heading and all the mandatory parameters within the SPDU) in the situations required by the Protocol Machine; and
 - to encode the SPDU into the TSDU, according to a valid encoding format.
- 'o' Optional support is permitted for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1. According to some specific reason, the implementation is not obliged to be able to build the SPDU. If implemented, it shall conform to the specifications and restrictions contained in ITU-T Rec. X.225 | ISO/IEC 8327-1. Therefore the constraints described for the mandatory support above also apply.
- 'o.n' Selectable options among a set of items (where *n* is the number which identifies the group of optionals which are linked together). The implementation shall support at least one of the given items. [For the selected item(s), the constraints described for the mandatory support above also apply.]
- 'cn' The item is conditional (where *n* is the number which identifies the condition which is applicable). The definitions for the conditional statements used in Annex A are written under the table where they are used, and indexed in Annex B. Resolution of the condition (e.g. depending on protocol version, protocol mechanism, etc.) yields to 'm', 'o' or 'n/a'.
- 'n/a' The item is not applicable.

Receiver item:

- 'm' Mandatory support is required. The implementation shall be able:
 - to syntactically identify the SPDU [i.e. to decode the heading and all of the parameters which are present (Type and Length in TLV coding scheme)]; and
 - to process it correctly.
- 'o' Optional support is permitted for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1. If implemented, it shall conform to the specifications and restrictions contained in ITU-T Rec. X.225 | ISO/IEC 8327-1. Therefore the constraints described for the mandatory support above also apply.
- 'o.n' Selectable options among a set of items (where *n* is the number which identifies the group of optionals which are linked together). The implementation shall support at least one of the given items. [For the selected item(s), the constraints described for the mandatory support above also apply.]
- 'cn' The item is conditional (where *n* is the number which identifies the condition which is applicable). The definitions for the conditional statements used in Annex A are written under the table where they are used, and indexed in Annex B. Resolution of the condition (e.g. depending on protocol version, protocol mechanism, etc.) yields to 'm', 'o' or 'n/a'.
- 'n/a' The item is not applicable.

A.2.2.3.3 Definitions applying to the tables in clause A.8 (Supported SPDU parameters)

NOTE – The status indicated for the parameters reflects static conformance requirements. The details about the use of these parameters in specific instances of communications (i.e. dynamic conformance) are to be found in the Session protocol standard (ITU-T Rec. X.225 | ISO/IEC 8327-1). It is reminded that a parameter with the Length equal to zero shall be considered as absent.

The values are as follows:

Sender item:

- 'm' Mandatory support is required. The implementation shall be able to build and to encode this parameter within the appropriate SPDU.
- 'o' Optional support is permitted for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1. According to some specific reason, the implementation is not obliged to be able to build the parameter. If implemented, it shall conform to the specifications and restrictions contained in ITU-T Rec. X.225 | ISO/IEC 8327-1. Therefore the constraints described for the mandatory support above also apply.

- 'cn' The item is conditional (where n is the number which identifies the condition which is applicable). The definitions for the conditional statements used in Annex A are written under the table where they are used, and indexed in Annex B. Resolution of the condition (e.g. depending on protocol version, protocol mechanism, etc.) yields to 'm', 'o' or 'n/a'.
- 'n/a' The item is not applicable.

Receiver item:

- 'm' Mandatory support is required. The implementation shall be able to syntactically and semantically identify the SPDU parameter and to process it correctly.
- 'o' Optional support is permitted for conformance to ITU-T Rec. X.225 | ISO/IEC 8327-1. If implemented, it shall conform to the specifications and restrictions contained in ITU-T Rec. X.225 | ISO/IEC 8327-1. Therefore the constraints described for the mandatory support above also apply.
- 'cn' The item is conditional (where n is the number which identifies the condition which is applicable). The definitions for the conditional statements used in Annex A are written under the table where they are used, and indexed in Annex B. Resolution of the condition (e.g. depending on protocol version, protocol mechanism, etc.) yields to 'm', 'o' or 'n/a'.
- 'n/a' The item is not applicable.

A.2.2.4 Support column

The 'Support' column shall be completed by the supplier or implementor to indicate the level of implementation of each feature. The proforma has been designed such that the only entries required in the 'Support' column are:

If the Status column yields to 'm' or 'o', the following answers are valid:

- 'Y' Yes, the feature has been implemented.
- 'N' No, the feature has not been implemented.

If the Status column yields to 'n/a', the unique following answer is valid:

- '-' Not applicable.

A.2.2.5 Value column

The 'Value' column requires the specification of the range of values implemented for a feature, where relevant.

A.2.2.6 Mnemonic column

The 'Mnemonic' column is given to facilitate the interpretation of the conditional statements throughout the PICS proforma.

The mnemonics are designed so that the implementor should easily understand their contents. Their names are generated as follows:

- a) a character identifying the Session layer (S);
- b) an hyphen character;
- c) a sequence of character which is derived, where possible, from the abbreviations used in the Session protocol specification.

A full alphanumerical list of all the defined 'Mnemonics' is given in Annex C.

A.2.2.7 Length column

The 'Length' column is given for information only in A.8, in order to indicate a specific length requirement for a parameter. Otherwise, it is recommended not to fill in this column.

If values are given in the 'Support' columns (Sender and/or Receiver), they shall conform to the value(s) given in the 'Status' column.

The values are as follows:

- 'x' A specific number of octets is given in ITU-T Rec. X.225 | ISO/IEC 8327-1.
- '0-y' A range of number of octets is given in ITU-T Rec. X.225 | ISO/IEC 8327-1.
- 'see Ref.' For a specific reason (total length of the SPDU), an explicit range of number of octets can not be given in the PICS proforma. For more details, the implementor shall refer to ITU-T Rec. X.225 | ISO/IEC 8327-1.

A.2.3 Instructions for completion

The supplier shall complete all entries in the column marked 'Support'. In certain clauses of the PICS proforma further guidance for completion may be necessary. Such guidance shall supplement the guidance given in this clause and shall have a scope restricted to the clause in which it appears. In addition, other specifically identified information shall be provided by the implementor where requested. No changes shall be made to the proforma except the completion as required. Recognising that the level of detail required may, in some instances, exceed the space available for responses a number of responses specifically allow for the addition of appendices to the PICS.

A.3 Identification of the implementation

A.3.1 Date of statement

| | |
|---|-------------------------------|
| 1 | Date of statement? (yy-mm-dd) |
|---|-------------------------------|

A.3.2 Implementation details

The supplier of the protocol implementation shall specify the information necessary to uniquely identify the implementation and the system in which it may reside. This may include details of:

- a) supplier, implementation name, operating system, suitable hardware;
- b) system supplier and/or client of the test laboratory that is to test the implementation;
- c) information on whom to contact if there are queries concerning the content of the PICS.

| | |
|---|--|
| 1 | |
|---|--|

A.4 Protocol Identification

A.4.1 ITU-T Rec. X.225 | ISO/IEC 8327-1 protocol details

| | Identification of Protocol Specification | Support | Comment |
|---|---|---------|---------|
| - | ITU-T Rec. X.225 (1994) ISO/IEC 8327-1:1996 | | |
| 1 | | | |
| 2 | | | |
| 3 | | | |

A.4.2 ITU-T Rec. X.225 | ISO/IEC 8327-1 protocol versions

Which version of the Session Protocol is described in this PICS?

| | Status | Support | Mnemonic | Comment |
|---|-----------|---------|----------|---------|
| 1 | Version 1 | o.1 | S-V1 | |
| 2 | Version 2 | o.1 | | |

o.1: the implementation of one, and only one, version of the protocol shall be described in this proforma (see below).

An implementation shall be described by completing a separate PICS proforma for each supported protocol version. PICS document for all versions of the protocol for which conformance is claimed should be attached to each other, and used together.

Which other versions of the Session Protocol does the implementation support?

| | Status | Support | Comment |
|---|-----------|---------|---------|
| 3 | Version 1 | o | |
| 4 | Version 2 | o | |

A.4.3 ITU-T Rec. X.225 | ISO/IEC 8327-1 technical corrigenda implemented

| | |
|--|--|
| Identification of corrigenda applied to the implementation | ITU-T Rec. X.225 (1994) ISO/IEC 8327-1:1996 Corr: Corr: Corr: Corr: Corr: |
|--|--|

A.5 Global statement of conformance

| | |
|--|---|
| 1 | Are all mandatory features implemented? (yes or no) |
| NOTE – If a positive response is not given to this box, then the implementation does not conform to ITU-T Rec. X.225 ISO/IEC 8327-1. | |

A.6 Supported functional units and protocol mechanisms

A.6.1 Functional units

| | Functional Unit | Status | Support | Mnemonic | Comment |
|----|--------------------------|--------|---------|-------------|---------|
| 1 | Kernel | m | | | |
| 2 | Negotiated Release | o | | S-FU(NR) | |
| 3 | Half Duplex | o.2 | | S-FU(HD) | |
| 4 | Duplex | o.2 | | S-FU(FD) | |
| 5 | Expedited Data (Note) | o | | S-FU(EX) | |
| 6 | Typed Data | o | | S-FU(TD) | |
| 7 | Capability Data Exchange | c1 | | S-FU(CD) | |
| 8 | Minor Synchronize | o | | S-FU(SY) | |
| 9 | Symmetric Synchronize | o | | S-FU(SS) | |
| 10 | Data Separation | c2 | | S-FU(DS) | |
| 11 | Major Synchronize | o | | S-FU(MA) | |
| 12 | Resynchronize | o | | S-FU(RESYN) | |
| 13 | Exceptions | c3 | | S-FU(EXCEP) | |
| 14 | Activity management | o | | S-FU(ACT) | |

o.2: at least one of the functional units Duplex and Half Duplex shall be implemented.
c1: if [S-FU(ACT)] then o else n/a.
c2: if [S-FU(SY) or S-FU(SS)] then o else n/a.
c3: if [S-FU(HD)] then o else n/a.
NOTE – The TRANSPORT Expedited data service is required to support the SESSION Expedited data functional unit.

A.6.2 Protocol mechanisms

| | Mechanism | Status | Support | Range of values | Mnemonic | Comment |
|----|---|--------|---------|-----------------|-----------------|---------|
| 1 | Use of transport expedited data (Extended control Quality of Service) | c4 | | – | S-EXP_T | |
| 2 | Reuse of transport connection | o | | – | S-REUSE_T | |
| 3 | Basic concatenation | m | | – | | |
| 4 | Extended concatenation (sending) | o | | – | | |
| 5 | Extended concatenation (receiving) | o | | – | S-XCONC_RCV | |
| 6 | Segmenting (sending) | o | | | S-SEG_SDR | |
| 7 | Segmenting (receiving) | o | | | S-SEG_RCV | |
| 8 | Max size of SS-user-data (S-CONNECT) > 512 | o | | | S-MAXSIZE_512 | |
| 9 | Max size of SS-user-data (S-CONNECT) > 10240 | o | | | S-MAXSIZE_10240 | |
| 10 | Max size of SS-user-data (S-ABORT) > 9 | o | | | S-MAXSIZE_9 | |

c4: if [S-FU(EX)] then m else o.

NOTES

1 The use of the TRANSPORT Expedited data service is mandatory in order to support the SESSION Expedited data functional unit, but is also related to the Extended Control of Quality of Service.

2 Two kinds of segmentation exist in the Session protocol. Lines 6 and 7 address the segmentation of SPDUs into several TSDUs. Lines 8, 9 and 10 address Session Version 2 (Unlimited User Data and Enclosure Item) with segmentation of an SSDU into several SPDUs.

A.7 Supported SPDUs

A.7.1 Kernel functional unit

A.7.1.1 Supported roles

A.7.1.1.1 Session Connection

Does the implementation support the Session Connection as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-----------------|---------|
| 1 | Initiator | o.3 | | S-CON_initiator | |
| 2 | Responder | o.3 | | S-CON_responder | |
| o.3: a conforming implementation shall support at least one of the above roles. | | | | | |

A.7.1.1.2 Orderly Release

Does the implementation support the Orderly Release as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-----------------|---------|
| 1 | Requestor | o.4 | | S-REL_requestor | |
| 2 | Acceptor | o.4 | | S-REL_acceptor | |
| o.4: a conforming implementation shall support at least one of the above roles. | | | | | |

A.7.1.1.3 Normal Data Transfer

Does the implementation support the Normal Data Transfer as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.5 | | S-DATA_requestor | |
| 2 | Acceptor | o.5 | | S-DATA_acceptor | |
| o.5: a conforming implementation shall support at least one of the above roles. | | | | | |

A.7.1.2 Support for the SPDUs associated with the Kernel functional unit

| | SPDU | Sender | | Receiver | | Mnemonics | | Comment |
|--|-----------------------------|--------|---------|----------|---------|-----------|-----------|---------|
| | | Status | Support | Status | Support | Sender | Receiver | |
| 1 | Connect (CN) | c5 | | c6 | | | | |
| 2 | Overflow Accept (OA) | c7 | | c8 | | S-OA_SDR | S-OA_RCV | |
| 3 | Connect Data Overflow (CDO) | c9 | | c10 | | S-CDO_SDR | S-CDO_RCV | |
| 4 | Accept (AC) | c6 | | c5 | | | | |
| 5 | Refuse (RF) | c6 | | c5 | | | | |
| 6 | Finish (FN) | c11 | | c12 | | | | |
| 7 | Disconnect (DN) | c12 | | c11 | | | | |
| 8 | Abort (AB) | m | | m | | | | |
| 9 | Abort Accept (AA) | o | | m | | | | |
| 10 | Data Transfer (DT) | c13 | | c14 | | | | |
| 11 | Prepare (PR) | c15 | | c15 | | S-PR_SDR | S-PR_RCV | |
| c5: if [S-CON_initiator] then m else n/a. c6: if [S-CON_responder] then m else n/a. c7: if [S-V1 or NOT S-CON_responder] then n/a else if [S-MAXSIZE_10240] then m else o. c8: if [NOT S-V1 and S-CON_initiator and S-MAXSIZE_10240] then m else n/a. c9: if [S-V1 or NOT S-CON_initiator] then n/a else if [S-MAXSIZE_10240] then m else o. c10: if [NOT S-V1 and S-CON_responder and S-MAXSIZE_10240] then m else n/a. c11: if [S-REL_requestor] then m else n/a. c12: if [S-REL_acceptor] then m else n/a. c13: if [S-DATA_requestor] then m else n/a. c14: if [S-DATA_acceptor] then m else n/a. c15: if [NOT S-V1 and S-MAXSIZE_9 and S-EXP_T] then m else n/a. | | | | | | | | |

A.7.1.3 Support for the SPDUs associated with Token Exchange

| | SPDU | Sender | | Receiver | | Comment |
|--|--------------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Give Tokens (GT) | m | | m | | |
| 2 | Please Tokens (PT) | m | | m | | |
| NOTE – These two SPDUs are used for Token Exchange, but they are also used as category 0 SPDUs in basic concatenation. Therefore, their implementation is mandatory even if no token is supported. (Reference to ISO/IEC 8327-1, 7.16 and 7.17.) | | | | | | |

A.7.2 Negotiated Release functional unit

A.7.2.1 Supported roles

The roles supported by the implementation for the Negotiated Release functional unit are the same as for the Orderly Release (see clause A.7.1.1.2).

A.7.2.2 Support for the SPDUs associated with the Negotiated Release functional unit

| | SPDU | Sender | | Receiver | | Comment |
|---|--------------------|----------------------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Not Finished (NF) | c16 | | c17 | | |
| 2 | Give Tokens (GT) | ------(A.7.1.3)----- | | | | |
| 3 | Please Tokens (PT) | ------(A.7.1.3)----- | | | | |
| c16: if [S-FU(NR) and S-REL_acceptor] then m else n/a. c17: if [S-FU(NR) and S-REL_requestor] then m else n/a. | | | | | | |

A.7.3 Half Duplex functional unit

A.7.3.1 Supported roles

Does the implementation support the Half Duplex functional unit as:

| | Role | Status | Support | Comment |
|---------------------------------------|-----------|--------|---------|---------|
| 1 | Requestor | c18 | | |
| 2 | Acceptor | c18 | | |
| c18: if [S-FU(HD)] then m else n/a. | | | | |

A.7.3.2 Support for the SPDUs associated with the Half Duplex functional unit

| | SPDU | Sender | | Receiver | | Comment |
|---|--------------------|-----------------------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Give Tokens (GT) | ----- (A.7.1.3) ----- | | | | |
| 2 | Please Tokens (PT) | ----- (A.7.1.3) ----- | | | | |

A.7.4 Duplex functional unit

No additional SPDUs (*this clause is present for completeness*).

A.7.5 Expedited Data functional unit

A.7.5.1 Supported roles

Does the implementation support the Expedited Data functional unit as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-------------------|---------|
| 1 | Requestor | o.6 | | S-XDATA_requestor | |
| 2 | Acceptor | o.6 | | S-XDATA_acceptor | |
| o.6: if [S-FU(EX)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.5.2 Support for the SPDU associated with the Expedited Data functional unit

| | SPDU | Sender | | Receiver | | Comment |
|--|---------------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Expedited Data (EX) | c19 | | c20 | | |
| c19: if [S-XDATA_requestor] then m else n/a. | | | | | | |
| c20: if [S-XDATA_acceptor] then m else n/a. | | | | | | |

A.7.6 Typed Data functional unit

A.7.6.1 Supported roles

Does the implementation support the Typed Data functional unit as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-------------------|---------|
| 1 | Requestor | o.7 | | S-TDATA_requestor | |
| 2 | Acceptor | o.7 | | S-TDATA_acceptor | |
| o.7: if [S-FU(TD)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.6.2 Support for the SPDU associated with the Typed Data functional unit

| | SPDU | Sender | | Receiver | | Comment |
|---|-----------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Typed Data (TD) | c21 | | c22 | | |
| c21: if [S-TDATA_requestor] then m else n/a. c22: if [S-TDATA_acceptor] then m else n/a. | | | | | | |

A.7.7 Capability Data functional unit**A.7.7.1 Supported roles**

Does the implementation support the Capability Data functional unit as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-----------------|---------|
| 1 | Requestor | o.8 | | S-CAP_requestor | |
| 2 | Acceptor | o.8 | | S-CAP_acceptor | |
| o.8: if [S-FU(CD)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.7.2 Support for the SPDUs associated with the Capability Data functional unit

| | SPDU | Sender | | Receiver | | Comment |
|---|---------------------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Capability Data (CD) | c23 | | c24 | | |
| 2 | Capability Data Ack (CDA) | c24 | | c23 | | |
| c23: if [S-CAP_requestor] then m else n/a. c24: if [S-CAP_acceptor] then m else n/a. | | | | | | |

A.7.8 Minor synchronize functional unit**A.7.8.1 Supported roles**

Does the implementation support the Minor synchronize functional unit as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|-----------------|---------|
| 1 | Requestor | o.9 | | S-MIN_requestor | |
| 2 | Acceptor | o.9 | | S-MIN_acceptor | |
| o.9: if [S-FU(SY)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.8.2 Support for the SPDUs associated with the Minor synchronize functional unit

| | SPDU | Sender | | Receiver | | Comment |
|--|------------------------|-----------------------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Minor Sync Point (MIP) | c25 | | c26 | | |
| 2 | Minor Sync Ack (MIA) | c27 | | c25 | | |
| 3 | Give Tokens (GT) | ----- (A.7.1.3) ----- | | | | |
| 4 | Please Tokens (PT) | ----- (A.7.1.3) ----- | | | | |
| c25: if [S-MIN_requestor] then m else n/a. c26: if [S-MIN_acceptor] then m else n/a. c27: if [S-MIN_acceptor] then o else n/a. | | | | | | |

A.7.9 Symmetric synchronize functional unit

A.7.9.1 Supported roles

Does the implementation support the Symmetric synchronize functional unit as:

| | Role | Status | Support | Comment |
|---------------------------------------|-----------|--------|---------|---------|
| 1 | Requestor | c28 | | |
| 2 | Acceptor | c28 | | |
| c28: if [S-FU(SS)] then m else n/a. | | | | |

A.7.9.2 Support for the SPDUs associated with the Symmetric synchronize functional unit

| | SPDU | Sender | | Receiver | | Comment |
|--|------------------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Minor Sync Point (MIP) | c28 | | c28 | | |
| 2 | Minor Sync Ack (MIA) | c29 | | c28 | | |
| c28: if [S-FU(SS)] then m else n/a. c29: if [S-FU(SS)] then o else n/a. | | | | | | |

A.7.10 Data separation functional unit

No additional SPDUs (*this clause is present for completeness*).

A.7.11 Major synchronize functional unit

A.7.11.1 Supported roles

Does the implementation support the Major synchronize functional unit as:

| | Role | Status | Support | Mnemonic | Comment |
|--|-----------|--------|---------|-----------------|---------|
| 1 | Requestor | o.10 | | S-MAJ_requestor | |
| 2 | Acceptor | o.10 | | S-MAJ_acceptor | |
| o.10: if [S-FU(MA)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.11.2 Support for the SPDUs associated with the Major synchronize functional unit

| | SPDU | Sender | | Receiver | | Comment |
|--|------------------------|----------------------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Major Sync Point (MAP) | c30 | | c31 | | |
| 2 | Major Sync Ack (MAA) | c31 | | c30 | | |
| 3 | Give Tokens (GT) | ------(A.7.1.3)----- | | | | |
| 4 | Please Tokens (PT) | ------(A.7.1.3)----- | | | | |
| 5 | Prepare (PR) | c32 | | c33 | | |
| c30: if [S-MAJ_requestor] then m else n/a. c31: if [S-MAJ_acceptor] then m else n/a. c32: if [S-MAJ_acceptor and S-EXP_T] then m else n/a. c33: if [S-MAJ_requestor and S-EXP_T] then m else n/a. | | | | | | |

A.7.12 Resynchronize functional unit**A.7.12.1 Supported roles**

Does the implementation support the Resynchronize functional unit as:

| | Role | Status | Support | Comment |
|---|-----------|--------|---------|---------|
| 1 | Requestor | c34 | | |
| 2 | Acceptor | c34 | | |

c34: if [S-FU(RESYN)] then m else n/a.
 NOTE – The Resynchronize functional unit provides an emergency service. Therefore, if the functional unit is supported, a conforming implementation shall support both roles (requestor and acceptor).

A.7.12.2 Supported resynchronize types

Does the implementation support the following Resynchronize types:

| | Type | Status | Support | Comment |
|---|---------|--------|---------|---------|
| 1 | Abandon | o.11 | | |
| 2 | Set | o.11 | | |
| 3 | Restart | o.11 | | |

o.11: if [S-FU(RESYN)] then a conforming implementation shall support at least one of the above roles else n/a.

A.7.12.3 Support for the SPDUs associated with the Resynchronize functional unit

| | SPDU | Sender | | Receiver | | Comment |
|---|------------------------|--------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Resynchronize (RS) | c34 | | c34 | | |
| 2 | Resynchronize Ack (RA) | c34 | | c34 | | |
| 3 | Prepare (PR) | c35 | | c35 | | |

c34: if [S-FU(RESYN)] then m else n/a.
 c35: if [S-FU(RESYN) and S-EXP_T] then m else n/a.

A.7.13 Exceptions functional unit**A.7.13.1 Supported roles**

Does the implementation support the Exceptions functional unit as:

| | Role | Status | Support | Comment |
|---|-----------|--------|---------|---------|
| 1 | Requestor | c36 | | |
| 2 | Acceptor | c36 | | |

c36: if [S-FU(EXCEP)] then m else n/a.
 NOTE – The Exceptions functional unit provides an emergency service. Therefore, if the functional unit is supported, a conforming implementation shall support both roles (requestor and acceptor).

A.7.13.2 Support for the SPDUs associated with the Exceptions functional unit

| | SPDU | Sender | | Receiver | | Mnemonic (Sender side only) | Comment |
|---|-----------------------|--------|---------|----------|---------|--------------------------------|---------|
| | | Status | Support | Status | Support | | |
| 1 | Exception Report (ER) | c37 | | c36 | | S-ER_SDR | |
| 2 | Exception Data (ED) | c36 | | c36 | | | |

c36: if [S-FU(EXCEP)] then m else n/a.
c37: if [S-FU(EXCEP)] then o else n/a.

A.7.14 Activity management functional unit

A.7.14.1 Supported roles

A.7.14.1.1 Activity start

Does the implementation support the Activity start as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.12 | | S-ACTS_requestor | |
| 2 | Acceptor | o.12 | | S-ACTS_acceptor | |

o.12: if [S-FU(ACT)] then a conforming implementation shall support at least one of the above roles else n/a.

A.7.14.1.2 Activity resume

Does the implementation support the Activity resume as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.13 | | S-ACTR_requestor | |
| 2 | Acceptor | o.13 | | S-ACTR_acceptor | |

o.13: if [S-FU(ACT)] then a conforming implementation shall support at least one of the above roles else n/a.

A.7.14.1.3 Activity interrupt

Does the implementation support the Activity interrupt as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.14 | | S-ACTI_requestor | |
| 2 | Acceptor | o.14 | | S-ACTI_acceptor | |

o.14: if [S-FU(ACT)] then a conforming implementation shall support at least one of the above roles else n/a.

A.7.14.1.4 Activity discard

Does the implementation support the Activity discard unit as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.15 | | S-ACTD_requestor | |
| 2 | Acceptor | o.15 | | S-ACTD_acceptor | |

o.15: if [S-FU(ACT)] then a conforming implementation shall support at least one of the above roles else n/a.

A.7.14.1.5 Activity end

Does the implementation support the Activity end as:

| | Role | Status | Support | Mnemonic | Comment |
|---|-----------|--------|---------|------------------|---------|
| 1 | Requestor | o.16 | | S-ACTE_requestor | |
| 2 | Acceptor | o.16 | | S-ACTE_acceptor | |
| o.16: if [S-FU(ACT)] then a conforming implementation shall support at least one of the above roles else n/a. | | | | | |

A.7.14.1.6 Give Tokens Confirm

Does the implementation support the Give Tokens Confirm as:

| | Role | Status | Support | Mnemonic | Comment |
|---------------------------------------|-----------|--------|---------|-----------------|---------|
| 1 | Requestor | c1 | | S-GTC_requestor | |
| 2 | Acceptor | c1 | | S-GTC_acceptor | |
| c1: if [S-FU(ACT)] then o else n/a. | | | | | |

A.7.14.2 Support for the SPDUs associated with the Activity management functional unit

| | SPDU | Sender | | Receiver | | Comment |
|--|------------------------------|----------------------|---------|----------|---------|---------|
| | | Status | Support | Status | Support | |
| 1 | Activity Start (AS) | c38 | | c39 | | |
| 2 | Activity Resume (AR) | c40 | | c41 | | |
| 3 | Activity Interrupt (AI) | c42 | | c43 | | |
| 4 | Activity Interrupt Ack (AIA) | c43 | | c42 | | |
| 5 | Activity Discard (AD) | c44 | | c45 | | |
| 6 | Activity Discard Ack (ADA) | c45 | | c44 | | |
| 7 | Activity End (AE) | c46 | | c47 | | |
| 8 | Activity End Ack (AEA) | c47 | | c46 | | |
| 9 | Prepare (PR) | c48 | | c48 | | |
| 10 | Give Tokens (GT) | ------(A.7.1.3)----- | | | | |
| 11 | Please Tokens (PT) | ------(A.7.1.3)----- | | | | |
| 12 | Give Tokens Confirm (GTC) | c49 | | c50 | | |
| 13 | Give Tokens Ack (GTA) | c50 | | c49 | | |
| c38: if [S-ACTS_requestor] then m else n/a. c39: if [S-ACTS_acceptor] then m else n/a. c40: if [S-ACTR_requestor] then m else n/a. c41: if [S-ACTR_acceptor] then m else n/a. c42: if [S-ACTI_requestor] then m else n/a. c43: if [S-ACTI_acceptor] then m else n/a. c44: if [S-ACTD_requestor] then m else n/a. c45: if [S-ACTD_acceptor] then m else n/a. c46: if [S-ACTE_requestor] then m else n/a. c47: if [S-ACTE_acceptor] then m else n/a. c48: if [S-FU(ACT) and S-EXP_T] then m else n/a. c49: if [S-GTC_requestor] then m else n/a. c50: if [S-GTC_acceptor] then m else n/a. | | | | | | |

A.8 Supported SPDU-parameters

A.8.1 Connect (CN) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.1, Table 11)

A.8.1.1 Connection Identifier

| | PGI "Connection Identifier" | Sender | | Receiver | | Length | | | Comment |
|---|----------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Calling SS-user Reference | c51 | | c6 | | 0-64 | | | |
| 2 | Common Reference | c51 | | c6 | | 0-64 | | | |
| 3 | Additional Reference Information | c51 | | c6 | | 0-4 | | | |

c6: if [S-CON_responder] then m else n/a.
c51: if [S-CON_initiator] then o else n/a.

A.8.1.2 Connect/Accept Item

A.8.1.2.1 Connect/Accept Item parameters

NOTE – If presence of the PGI "Connect/accept Item" is supported (see A.8.1.2.2) then presence of Protocol Options and Version Number parameters shall be supported.

| | PGI "Connect/Accept Item" | Sender | | Receiver | | Length | | | Comment |
|---|------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Protocol Options | c52 | | c53 | | 1 | | | |
| 2 | TSDU maximum size | c54 | | c55 | | 4 | | | |
| 3 | Version Number | c56 | | c57 | | 1 | | | |
| 4 | Initial Serial Number | c58 | | c59 | | 0-6 | | | |
| 5 | Token Setting Item | c51 | | c60 | | 1 | | | |
| 6 | Second Initial Serial Number | c61 | | c62 | | 0-6 | | | |

c51: if [S-CON_initiator] then o else n/a.
c52: if [NOT S-CON_initiator] then n/a else if [S-XCONC_RCV] then m else o.
c53: if [NOT S-CON_responder] then n/a else if [S-XCONC_RCV] then m else o.
c54: if [NOT S-CON_initiator] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o.
c55: if [NOT S-CON_responder] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o.
c56: if [NOT S-CON_initiator] then n/a else if [NOT S-V1] then m else o.
c57: if [NOT S-CON_responder] then n/a else if [NOT S-V1] then m else o.
c58: if [NOT S-CON_initiator] then n/a else if [{S-FU(SY) or S-FU(MA) or S-FU(SS) or S-FU(RESYN)} and NOT S-FU(ACT)] then m else o.
c59: if [NOT S-CON_responder] then n/a else if [{S-FU(SY) or s-FU(MA) or S-FU(SS) or S-FU(RESYN)} and NOT S-FU(ACT)] then m else o.
c60: if [S-CON_responder] then o else n/a.
c61: if [NOT S-CON_initiator] then n/a else if [S-FU(SS) and NOT S-FU(ACT)] then m else o.
c62: if [NOT S-CON_responder] then n/a else if [S-FU(SS) and NOT S-FU(ACT)] then m else o.

A.8.1.2.2 Presence of Connect/Accept Item

| | Status | Support | Comment |
|---|----------|---------|---------|
| 1 | Sender | c63 | |
| 2 | Receiver | c6 | |

c6: if [S-CON_responder] then m else n/a.
c63: if [NOT S-CON_initiator] then n/a else if [A.8.1.2.1/1a or A.8.1.2.1/2a or A.8.1.2.1/3a or A.8.1.2.1/4a or A.8.1.2.1/5a or A.8.1.2.1/6a] then m else o.

A.8.1.3 Single Items

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|--|-----------------------------|--------|---------|----------|---------|---------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Session User Requirements | c64 | | c65 | | 2 | | | |
| 2 | Calling Session Selector | c51 | | c6 | | 0-16 | | | |
| 3 | Called Session Selector | c5 | | c6 | | 0-16 | | | |
| 4 | Data Overflow | c9 | | c7 | | 1 | | | |
| 5 | User Data | c5 | | c6 | | 0-512 | | | |
| 6 | Extended User Data | c66 | | c67 | | 0-10240 | | | |
| 7 | Upper Limit Serial Number | c51 | | c60 | | | | | |
| 8 | Large Initial Serial Number | c68 | | c69 | | | | | |
| c5: if [S-CON_initiator] then m else n/a. c6: if [S-CON_responder] then m else n/a. c7: if [S-V1 or NOT S-CON_responder] then n/a else if [S-MAXSIZE_10240] then m else o. c9: if [S-V1 or NOT S-CON_initiator] then n/a else if [S-MAXSIZE_10240] then m else o. c51: if [S-CON_initiator] then o else n/a. c64: if [NOT S-CON_initiator] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m. c65: if [NOT S-CON_responder] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m. c66: if [NOT S-V1 and S-CON_initiator and S-MAXSIZE_512] then m else n/a. c67: if [NOT S-V1 and S-CON_responder and S-MAXSIZE_512] then m else n/a. c68: if [A.8.1.3/7a] then o else n/a. c69: if [A.8.1.3/7b] then o else n/a. | | | | | | | | | |

A.8.2 Overflow Accept (OA) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.2, Table 12)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|--|-------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | TSDU Maximum Size | c70 | | c71 | | 4 | | | |
| 2 | Version Number | c72 | | c73 | | 1 | | | |
| c70: if [NOT S-OA_SDR] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o. c71: if [NOT S-OA_RCV] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o. c72: if [S-OA_SDR] then m else n/a. c73: if [S-OA_RCV] then m else n/a. | | | | | | | | | |

A.8.3 Connect Data Overflow (CDO) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.3, Table 13)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|--|----------------|--------|---------|----------|---------|---------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c74 | | c75 | | 1 | | | |
| 2 | User Data | c74 | | c75 | | 0-65528 | | | |
| c74: if [S-CDO_SDR] then m else n/a. c75: if [S-CDO_RCV] then m else n/a. | | | | | | | | | |

A.8.4 Accept (AC) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.4, Table 14)

A.8.4.1 Connection Identifier

| | PGI "Connection Identifier" | Sender | | Receiver | | Length | | | Comment |
|---|----------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Called SS-user Reference | c60 | | c5 | | 0-64 | | | |
| 2 | Common Reference | c60 | | c5 | | 0-64 | | | |
| 3 | Additional Reference Information | c60 | | c5 | | 0-4 | | | |

c5: if [S-CON_initiator] then m else n/a.
c60: if [S-CON_responder] then o else n/a.

A.8.4.2 Connect/Accept Item

A.8.4.2.1 Connect/Accept Item parameters

NOTE – If presence of the PGI "Connect/accept Item" is supported (see A.8.4.2.2) then presence of Protocol Options and Version Number parameters shall be supported.

| | PGI "Connect/Accept Item" | Sender | | Receiver | | Length | | | Comment |
|---|------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Protocol Options | c53 | | c52 | | 1 | | | |
| 2 | TSDU maximum size | c55 | | c54 | | 4 | | | |
| 3 | Version Number | c57 | | c56 | | 1 | | | |
| 4 | Initial Serial Number | c59 | | c58 | | 0-6 | | | |
| 5 | Token Setting Item | c60 | | c51 | | 1 | | | |
| 6 | Second Initial Serial Number | c62 | | c61 | | 0-6 | | | |

c51: if [S-CON_initiator] then o else n/a.
c52: if [NOT S-CON_initiator] then n/a else if [S-XCONC_RCV] then m else o.
c53: if [NOT S-CON_responder] then n/a else if [S-XCONC_RCV] then m else o.
c54: if [NOT S-CON_initiator] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o.
c55: if [NOT S-CON_responder] then n/a else if [S-SEG_SDR or S-SEG_RCV] then m else o.
c56: if [NOT S-CON_initiator] then n/a else if [NOT S-V1] then m else o.
c57: if [NOT S-CON_responder] then n/a else if [NOT S-V1] then m else o.
c58: if [NOT S-CON_initiator] then n/a else if [{S-FU(SY) or s-FU(MA) or S-FU(SS) or S-FU(RESYN)} and NOT S-FU(ACT)] then m else o.
c59: if [NOT S-CON_responder] then n/a else if [{S-FU(SY) or s-FU(MA) or S-FU(SS) or S-FU(RESYN)} and NOT S-FU(ACT)] then m else o.
c60: if [S-CON_responder] then o else n/a.
c61: if [NOT S-CON_initiator] then n/a else if [S-FU(SS) and NOT S-FU(ACT)] then m else o.
c62: if [NOT S-CON_responder] then n/a else if [S-FU(SS) and NOT S-FU(ACT)] then m else o.

A.8.4.2.2 Presence of Connect/Accept Item

| | | Status | Support | Comment |
|---|----------|--------|---------|---------|
| 1 | Sender | c76 | | |
| 2 | Receiver | c5 | | |

c5: if [S-CON_initiator] then m else n/a.
c76: if [NOT S-CON_responder] then n/a else if [A.8.4.2.1/1a or A.8.4.2.1/2a or A.8.4.2.1/3a or A.8.4.2.1/4a or A.8.4.2.1/5a or A.8.4.2.1/6a] then m else o.

A.8.4.3 Single Items

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|-----------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Token Item | c60 | | c5 | | 1 | | | |
| 2 | Session User Requirements | c65 | | c64 | | 2 | | | |
| 3 | Enclosure Item | c77 | | c78 | | 1 | | | |
| 4 | Calling Session Selector | c6 | | c51 | | 0-16 | | | |
| 5 | Responding Session Selector | c60 | | c5 | | 0-16 | | | |
| 6 | User Data | c6 | | c5 | | (Ref.) | | | |
| 7 | Upper Limit Serial Number | c60 | | c51 | | | | | |
| 8 | Large Initial Serial Number | c79 | | c80 | | | | | |

c5: if [S-CON_initiator] then m else n/a.
c6: if [S-CON_responder] then m else n/a.
c51: if [S-CON_initiator] then o else n/a.
c60: if [S-CON_responder] then o else n/a.
c64: if [NOT S-CON_initiator] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m.
c65: if [NOT S-CON_responder] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m.
c77: if [S-CON_responder and NOT S-V1] then m else n/a.
c78: if [S-CON_initiator and NOT S-V1] then m else n/a.
c79: if [A.8.4.3/7a] then o else n/a.
c80: if [A.8.4.3/7b] then o else n/a.

A.8.5 Refuse (RF) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.5, Table 15)

A.8.5.1 Connection Identifier

| | PGI "Connection Identifier" | Sender | | Receiver | | Length | | | Comment |
|---|----------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Called SS-user Reference | c60 | | c5 | | 0-64 | | | |
| 2 | Common Reference | c60 | | c5 | | 0-64 | | | |
| 3 | Additional Reference Information | c60 | | c5 | | 0-4 | | | |

c5: if [S-CON_initiator] then m else n/a.
c60: if [S-CON_responder] then o else n/a.

A.8.5.2 Single Items

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|---------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Transport Disconnect | c81 | | c82 | | 1 | | | |
| 2 | Session User Requirements | c65 | | c64 | | 2 | | | |
| 3 | Version Number | c57 | | c56 | | 1 | | | |
| 4 | Enclosure Item | c77 | | c78 | | 1 | | | |
| 5 | Reason Code | c6 | | c5 | | (Ref.) | | | |

c5: if [S-CON_initiator] then m else n/a.
 c6: if [S-CON_responder] then m else n/a.
 c56: if [NOT S-CON_initiator] then n/a else if [NOT S-V1] then m else o.
 c57: if [NOT S-CON_responder] then n/a else if [NOT S-V1] then m else o.
 c64: if [NOT S-CON_initiator] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m.
 c65: if [NOT S-CON_responder] then n/a else if [S-FU(HD) and S-FU(SY) and S-FU(ACT) and S-FU(CD) and S-FU(EXCEP) and NOT S-FU(NR) and NOT S-FU(FD) and NOT S-FU(EX) and NOT S-FU(TD) and NOT S-FU(SS) and NOT S-FU(MA) and NOT S-FU(RESYN) and NOT S-FU(DS)] then o else m.
 c77: if [S-CON_responder and NOT S-V1] then m else n/a.
 c78: if [S-CON_initiator and NOT S-V1] then m else n/a.
 c81: if [NOT S-CON_responder] then n/a else if [S-REUSE_T] then m else o.
 c82: if [NOT S-CON_initiator] then n/a else if [S-REUSE_T] then m else o.

A.8.6 Finish (FN) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.6, Table 16)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Transport Disconnect | c83 | | c84 | | 1 | | | |
| 2 | Enclosure Item | c85 | | c86 | | 1 | | | |
| 3 | User Data | c87 | | c12 | | (Ref.) | | | |

c12: if [S-REL_acceptor] then m else n/a.
 c83: if [NOT S-REL_requestor] then n/a else if [S-REUSE_T] then m else o.
 c84: if [NOT S-REL_acceptor] then n/a else if [S-REUSE_T] then m else o.
 c85: if [S-REL_requestor and NOT S-V1] then m else n/a.
 c86: if [S-REL_acceptor and NOT S-V1] then m else n/a.
 c87: if [S-REL_requestor] then o else n/a.

A.8.7 Disconnect (DN) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.7, Table 17)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c86 | | c85 | | 1 | | | |
| 2 | User Data | c88 | | c11 | | (Ref.) | | | |

c11: if [S-REL_requestor] then m else n/a.
 c85: if [S-REL_requestor and NOT S-V1] then m else n/a.
 c86: if [S-REL_acceptor and NOT S-V1] then m else n/a.
 c88: if [S-REL_acceptor] then o else n/a.

A.8.8 Not Finish (NF) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.8, Table 18)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c89 | | c90 | | 1 | | | |
| 2 | User Data | c91 | | c17 | | (Ref.) | | | |

c17: if [S-FU(NR) and S-REL_requestor] then m else n/a.
c89: if [S-FU(NR) and S-REL_acceptor and NOT S-V1] then m else n/a.
c90: if [S-FU(NR) and S-REL_requestor and NOT S-V1] then m else n/a.
c91: if [S-FU(NR) and S-REL_acceptor] then o else n/a.

A.8.9 Abort (AB) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.9, Table 19)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|--------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Transport Disconnect | m | | m | | 1 | | | |
| 2 | Enclosure Item | c92 | | c92 | | 1 | | | |
| 3 | Reflect Parameter Values | o | | o | | 0-9 | | | |
| 4 | User Data | o | | m | | (Ref.) | | | |

c92: if [NOT S-V1] then m else n/a.

A.8.10 Abort Accept (AA) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.10)

No parameter field.

A.8.11 Data Transfer (DT) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.11, Table 20)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|------------------------|--------|---------|----------|---------|-----------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c93 | | c94 | | 1 | | | |
| 2 | User Information Field | c13 | | c14 | | Unlimited | | | |

c13: if [S-DATA_requestor] then m else n/a.
c14: if [S-DATA_acceptor] then m else n/a.
c93: if [S-DATA_requestor and S-SEG_SDR] then m else n/a.
c94: if [S-DATA_acceptor and S-SEG_RCV] then m else n/a.

A.8.12 Expedited Data (EX) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.12, Table 21)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | User Information Field | c19 | | c20 | | 0-14 | | | |

c19: if [S-XDATA_requestor] then m else n/a.
c20: if [S-XDATA_acceptor] then m else n/a.

A.8.13 Typed Data (TD) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.13, Table 22)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|------------------------|--------|---------|----------|---------|-----------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c95 | | c96 | | 1 | | | |
| 2 | User Information Field | c21 | | c22 | | Unlimited | | | |

c21: if [S-TDATA_requestor] then m else n/a.
 c22: if [S-TDATA_acceptor] then m else n/a.
 c95: if [S-TDATA_requestor and S-SEG_SDR] then m else n/a.
 c96: if [S-TDATA_acceptor and S-SEG_RCV] then m else n/a.

A.8.14 Capability Data (CD) SPDU

(Ref. ITU-T Rec.X.225 \ ISO/IEC 8327-1, subclause 8.3.14, Table 23)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c97 | | c98 | | 1 | | | |
| 2 | User Data | c99 | | c24 | | (Ref.) | | | |

c24: if [S-CAP_acceptor] then m else n/a.
 c97: if [S-CAP_requestor and NOT S-V1] then m else n/a.
 c98: if [S-CAP_acceptor and NOT S-V1] then m else n/a.
 c99: if [S-CAP_requestor] then o else n/a.

A.8.15 Capability Data Ack (CDA) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.15, Table 24)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c98 | | c97 | | 1 | | | |
| 2 | User Data | c100 | | c23 | | (Ref.) | | | |

c23: if [S-CAP_requestor] then m else n/a.
 c97: if [S-CAP_requestor and NOT S-V1] then m else n/a.
 c98: if [S-CAP_acceptor and NOT S-V1] then m else n/a.
 c100: if [S-CAP_acceptor] then o else n/a.

A.8.16 Give Tokens (GT) SPDU

(Ref. ITU-T Rec. X.225 \ ISO/IEC 8327-1, subclause 8.3.16, Table 25)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Token Item | c101 | | c102 | | 1 | | | |
| 2 | Enclosure Item | c92 | | c92 | | 1 | | | |
| 3 | User Data | c103 | | c92 | | (Ref.) | | | |

c92: if [NOT S-V1] then m else n/a.
 c101: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then o else n/a.
 c102: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then m else n/a.
 c103: if [NOT S-V1 and A.8.16/1a] then o else n/a.

A.8.17 Please Tokens (PT) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.17, Table 26)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Token Item | c101 | | c102 | | 1 | | | |
| 2 | Enclosure Item | c92 | | c92 | | 1 | | | |
| 3 | User Data | c104 | | c105 | | (Ref.) | | | |
| c92: if [NOT S-V1] then m else n/a. c101: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then o else n/a. c102: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then m else n/a. c104: if [A.8.17/1a] then o else n/a. c105: if [A.8.17/1b] then m else n/a. | | | | | | | | | |

A.8.18 Minor Sync Point (MIP) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.20, Table 28)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Sync Type Item | c106 | | c107 | | 1 | | | |
| 2 | Enclosure Item | c108 | | c109 | | 1 | | | |
| 3 | Serial Number | c110 | | c111 | | 0-6 | | | |
| 4 | User Data | c112 | | c111 | | (Ref.) | | | |
| c106: if [(S-MIN_requestor or S-FU(SS)) and S-FU(DS)] then m else if [(S-MIN_requestor or S-FU(SS)) and NOT S-FU(DS)] then o else n/a. c107: if [S-MIN_acceptor or S-FU(SS)] then o else n/a. c108: if [{ S-MIN_requestor and NOT S-V1 } or { S-FU(SS) and NOT S-V1 }] then m else n/a. c109: if [{ S-MIN_acceptor and NOT S-V1 } or { S-FU(SS) and NOT S-V1 }] then m else n/a. c110: if [S-MIN_requestor or S-FU(SS)] then m else n/a. c111: if [S-MIN_acceptor or S-FU(SS)] then m else n/a. c112: if [S-MIN_requestor or S-FU(SS)] then o else n/a. | | | | | | | | | |

A.8.19 Minor Sync Ack (MIA) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.21, Table 29)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|--|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c109 | | c108 | | 1 | | | |
| 2 | Serial Number | c111 | | c110 | | 0-6 | | | |
| 3 | User Data | c107 | | c110 | | (Ref.) | | | |
| c107: if [S-MIN_acceptor or S-FU(SS)] then o else n/a. c108: if [{ S-MIN_requestor and NOT S-V1 } or { S-FU(SS) and NOT S-V1 }] then m else n/a. c109: if [{ S-MIN_acceptor and NOT S-V1 } or { S-FU(SS) and NOT S-V1 }] then m else n/a. c110: if [S-MIN_requestor or S-FU(SS)] then m else n/a. c111: if [S-MIN_acceptor or S-FU(SS)] then m else n/a. | | | | | | | | | |

A.8.20 Major Sync Point (MAP) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.22, Table 30)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Sync Type Item | c30 | | c31 | | 1 | | | |
| 2 | Enclosure Item | c113 | | c114 | | 1 | | | |
| 3 | Serial Number | c30 | | c31 | | 0-6 | | | |
| 4 | User Data | c115 | | c31 | | (Ref.) | | | |

c30: if [S-MAJ_requestor] then m else n/a.
 c31: if [S-MAJ_acceptor] then m else n/a.
 c113: if [S-MAJ_requestor and NOT S-V1] then m else n/a.
 c114: if [S-MAJ_acceptor and NOT S-V1] then m else n/a.
 c115: if [S-MAJ_requestor] then o else n/a.

A.8.21 Major Sync Ack (MAA) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.23, Table 31)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c114 | | c113 | | 1 | | | |
| 2 | Serial Number | c116 | | c117 | | 0-6 | | | |
| 3 | Second Serial Number | c118 | | c119 | | 0-6 | | | |
| 4 | User Data | c120 | | c30 | | (Ref.) | | | |

c30: if [S-MAJ_requestor] then m else n/a.
 c113: if [S-MAJ_requestor and NOT S-V1] then m else n/a.
 c114: if [S-MAJ_acceptor and NOT S-V1] then m else n/a.
 c116: if [NOT S-MAJ_acceptor] then n/a else if [NOT S-FU(SS)] then m else o.
 c117: if [NOT S-MAJ_requestor] then n/a else if [NOT S-FU(SS)] then m else o.
 c118: if [NOT S-MAJ_acceptor] then n/a else if [S-FU(SS)] then m else o.
 c119: if [NOT S-MAJ_requestor] then n/a else if [S-FU(SS)] then m else o.
 c120: if [S-MAJ_acceptor] then o else n/a.

A.8.22 Resynchronize (RS) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.24, Table 32)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c121 | | c121 | | 1 | | | |
| 2 | Token Setting Item | c102 | | c102 | | 1 | | | |
| 3 | Resync Type | c122 | | c122 | | 1 | | | |
| 4 | Serial Number | c122 | | c122 | | 0-6 | | | |
| 5 | Second Resync Type | c123 | | c124 | | 1 | | | |
| 6 | Second Serial Number | c123 | | c124 | | 0-6 | | | |
| 7 | User Data | c125 | | c34 | | (Ref.) | | | |

c34: if [S-FU(RESYN)] then m else n/a.
 c102: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then m else n/a.
 c121: if [S-FU(RESYN) and NOT S-V1] then m else n/a.
 c122: if [NOT S-FU(RESYN)] then n/a else if [S-FU(SY) or S-FU(MA)] then m else o.
 c123: if [S-FU(RESYN) and S-FU(SS)] then o else n/a.
 c124: if [S-FU(RESYN) and S-FU(SS)] then m else n/a.
 c125: if [S-FU(RESYN)] then o else n/a.

A.8.23 Resynchronize Ack (RA) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.25, Table 33)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c121 | | c121 | | 1 | | | |
| 2 | Token Setting Item | c102 | | c102 | | 1 | | | |
| 3 | Resync Type | c123 | | c124 | | 1 | | | |
| 4 | Serial Number | c126 | | c34 | | 0-6 | | | |
| 5 | Second Resync Type | c123 | | c124 | | 1 | | | |
| 6 | Second Serial Number | c123 | | c124 | | 0-6 | | | |
| 7 | User Data | c125 | | c34 | | (Ref.) | | | |

c34: if [S-FU(RESYN)] then m else n/a.
 c102: if [S-FU(NR) or S-FU(HD) or S-FU(SY) or S-FU(MA) or S-FU(ACT)] then m else n/a.
 c121: if [S-FU(RESYN) and NOT S-V1] then m else n/a.
 c123: if [S-FU(RESYN) and S-FU(SS)] then o else n/a.
 c124: if [S-FU(RESYN) and S-FU(SS)] then m else n/a.
 c125: if [S-FU(RESYN)] then o else n/a.
 c126: if [NOT S-FU(RESYN)] then n/a else if [NOT S-FU(SS)] then m else o.

A.8.24 Prepare (PR) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.26, Table 34)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|--------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Prepare Type | c127 | | c128 | | 1 | | | |
| 2 | Resync Type | c129 | | c129 | | 1 | | | |
| 3 | Second Resync Type | c129 | | c129 | | 1 | | | |

c127: if [{S-MAJ_acceptor and S-EXP_T} or {S-FU(RESYN) and S-EXP_T} or {S-FU(ACT) and S-EXP_T} or {S-PR_SDR}] then m else n/a.
 c128: if [{S-MAJ_requestor and S-EXP_T} or {S-FU(RESYN) and S-EXP_T} or {S-FU(ACT) and S-EXP_T} or {S-PR_RCV}] then m else n/a.
 c129: if [S-FU(SS) and S-EXP_T] then m else n/a.

A.8.25 Exception Report (ER) SPDU

(Ref. ITU-T X.225 | ISO/IEC 8327-1, subclause 8.3.27, Table 35)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|--------------------------|--------|---------|----------|---------|---------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Reflect Parameter Values | c130 | | c36 | | 0-65531 | | | |

c36: if [S-FU(EXCEP)] then m else n/a.
 c130: if [S-ER_SDR] then m else n/a.

A.8.26 Exception Data (ED) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.28, Table 36)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c131 | | c131 | | 1 | | | |
| 2 | Reason Code | c36 | | c36 | | 1 | | | |
| 3 | User Data | c132 | | c36 | | (Ref.) | | | |

c36: if [S-FU(EXCEP)] then m else n/a.
 c131: if [S-FU(EXCEP) and NOT S-V1] then m else n/a.
 c132: if [S-FU(EXCEP)] then o else n/a.

A.8.27 Give Tokens Confirm (GTC) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.18, Table 27)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c133 | | c134 | | 1 | | | |
| 2 | User Data | c135 | | c134 | | (Ref.) | | | |

c133: if [S-GTC_requestor and NOT S-V1] then m else n/a.
 c134: if [S-GTC_acceptor and NOT S-V1] then m else n/a.
 c135: if [S-GTC_requestor and NOT S-V1] then o else n/a.

A.8.28 Give Tokens Ack (GTA) SPDU

No parameter field.

A.8.29 Activity Start (AS) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.29, Table 37)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|---------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c136 | | c136 | | 1 | | | |
| 2 | Activity Identifier | c38 | | c39 | | 0-6 | | | |
| 3 | User Data | c137 | | c39 | | (Ref.) | | | |

c38: if [S-ACTS_requestor] then m else n/a.
 c39: if [S-ACTS_acceptor] then m else n/a.
 c136: if [S-ACTS_acceptor and NOT S-V1] then m else n/a.
 c137: if [S-ACTS_requestor] then o else n/a.

A.8.30 Activity Resume (AR) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.30, Table 38)

A.8.30.1 Linking Information

| | PGI "Linking Information" | Sender | | Receiver | | Length | | | Comment |
|---|----------------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Called SS-user Reference | c138 | | c41 | | 0-64 | | | |
| 2 | Calling SS-user Reference | c138 | | c41 | | 0-64 | | | |
| 3 | Common Reference | c138 | | c41 | | 0-64 | | | |
| 4 | Additional Reference Information | c138 | | c41 | | 0-4 | | | |
| 5 | Old Activity Identifier | c40 | | c41 | | 0-6 | | | |
| 6 | Serial Number | c40 | | c41 | | 0-6 | | | |
| 7 | Second Serial Number | c139 | | c140 | | 0-6 | | | |

c40: if [S-ACTR_requestor] then m else n/a.
 c41: if [S-ACTR_acceptor] then m else n/a.
 c138: if [S-ACTR_requestor] then o else n/a.
 c139: if [S-ACTR_requestor and S-FU(SS)] then m else n/a.
 c140: if [S-ACTR_acceptor and S-FU(SS)] then m else n/a.

A.8.30.2 Single Items

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|-------------------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c141 | | c142 | | 1 | | | |
| 2 | New Activity Identifier | c40 | | c41 | | 0-6 | | | |
| 3 | User Data | c138 | | c41 | | (Ref.) | | | |

c40: if [S-ACTR_requestor] then m else n/a.
c41: if [S-ACTR_acceptor] then m else n/a.
c138: if [S-ACTR_requestor] then o else n/a.
c141: if [S-ACTR_requestor and NOT S-V1] then m else n/a.
c142: if [S-ACTR_acceptor and NOT S-V1] then m else n/a.

A.8.31 Activity Interrupt (AI) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.31, Table 39)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c143 | | c144 | | 1 | | | |
| 2 | Reason Code | c42 | | c43 | | 1 | | | |
| 3 | User Data | c145 | | c144 | | (Ref.) | | | |

c42: if [S-ACTI_requestor] then m else n/a.
c43: if [S-ACTI_acceptor] then m else n/a.
c143: if [S-ACTI_requestor and NOT S-V1] then m else n/a.
c144: if [S-ACTI_acceptor and NOT S-V1] then m else n/a.
c145: if [S-ACTI_requestor and NOT S-V1] then o else n/a.

A.8.32 Activity Interrupt Ack (AIA) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.32, Table 40)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c144 | | c143 | | 1 | | | |
| 2 | User Data | c146 | | c143 | | (Ref.) | | | |

c143: if [S-ACTI_requestor and NOT S-V1] then m else n/a.
c144: if [S-ACTI_acceptor and NOT S-V1] then m else n/a.
c146: if [S-ACTI_acceptor and NOT S-V1] then o else n/a.

A.8.33 Activity Discard (AD) SPDU

(Ref. ITU-T Rec. X.225 | ISO/IEC 8327-1, subclause 8.3.33, Table 41)

| | Single Items | Sender | | Receiver | | Length | | | Comment |
|---|----------------|--------|---------|----------|---------|--------|---------|---------|---------|
| | | Status | Support | Status | Support | Status | Spt/Sdr | Spt/Rcv | |
| 1 | Enclosure Item | c147 | | c148 | | 1 | | | |
| 2 | Reason Code | c44 | | c45 | | 1 | | | |
| 3 | User Data | c149 | | c148 | | (Ref.) | | | |

c44: if [S-ACTD_requestor] then m else n/a.
c45: if [S-ACTD_acceptor] then m else n/a.
c147: if [S-ACTD_requestor and NOT S-V1] then m else n/a.
c148: if [S-ACTD_acceptor and NOT S-V1] then m else n/a.
c149: if [S-ACTD_requestor and NOT S-V1] then o else n/a.