

INTERNATIONAL
STANDARD

ISO/IEC
8650-1

Second edition
1996-10-15

**Information technology — Open Systems
Interconnection — Connection-oriented
protocol for the Association Control
Service Element: Protocol specification**

*Technologies de l'information — Interconnexion de systèmes ouverts
(OSI) — Protocole en mode orienté connexion pour l'élément de service
de contrôle d'association: Spécification du protocole*



Reference number
ISO/IEC 8650-1:1996(E)

Contents

	<i>Page</i>	
1	Scope and field of application.....	1
2	Normative references	1
2.1	Identical Recommendations International Standards	1
2.2	Paired Recommendations International Standards equivalent in technical content	2
2.3	Additional references	2
3	Definitions.....	2
3.1	Reference Model definitions.....	2
3.1.1	Basic Reference Model definitions	2
3.1.2	Security architecture definitions	3
3.1.3	Naming and addressing definitions.....	3
3.2	Service conventions definitions	3
3.3	Presentation service definitions	3
3.4	Application Layer Structure definitions.....	4
3.5	ACSE service definitions	4
3.6	Association Control protocol specification definitions.....	4
4	Abbreviations	4
4.1	Data units	4
4.2	Types of application-protocol-data-units	5
4.3	Other abbreviations	5
5	Conventions.....	5
6	Overview of the protocol	6
6.1	Service provision	6
6.2	Functional units.....	6
6.3	Use of the presentation-service.....	6
6.4	Relationship to the session-service	7
6.5	Model.....	8

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

7	Elements of procedure.....	8
7.1	Association establishment.....	9
7.1.1	Purpose	9
7.1.2	APDUs used.....	9
7.1.3	Association establishment procedure.....	9
7.1.4	Use of the AARQ APDU fields	11
7.1.5	Use of the AARE APDU fields.....	13
7.1.6	Collisions and interactions	15
7.2	Normal release of an association	16
7.2.1	Purpose	16
7.2.2	APDUs used.....	16
7.2.3	Normal release procedure	16
7.2.4	Use of the RLRQ APDU fields.....	18
7.2.5	Use of the RLRE APDU fields	18
7.2.6	Collisions and disruptions.....	18
7.3	Abnormal release of an association	19
7.3.1	Purpose	19
7.3.2	APDUs used.....	19
7.3.3	Abnormal release procedure	19
7.3.4	Use of the ABRT APDU fields.....	20
7.3.5	Collisions and interactions.....	20
7.4	Rules for extensibility	21
8	Mapping to the presentation-service	21
8.1	Association establishment (normal mode).....	21
8.1.1	Directly mapped parameters	21
8.1.2	Use of other P-CONNECT request and indication parameters.....	22
8.1.3	Use of other P-CONNECT response and confirm parameters.....	22
8.2	Normal release of an association (normal mode).....	23
8.2.1	Use of P-RELEASE request and indication parameters	23
8.2.2	Use of P-RELEASE response and confirm parameters	23
8.3	Abnormal release of an association (normal mode).....	23
8.3.1	Use of P-U-ABORT request and indication parameters	24
8.3.2	Use of P-P-ABORT indication parameter.....	24
8.4	Association establishment (X.410-1984 mode).....	24
8.4.1	Directly mapped parameters	24
8.4.2	Use of other P-CONNECT request and indication parameters.....	24
8.4.3	Use of other P-CONNECT response and confirm parameters.....	24
8.5	Normal release of an association (X.410-1984 mode).....	25
8.6	Abnormal release of an association (X.410-1984 mode).....	25
8.6.1	Use of P-U-ABORT request and indication parameters	25
8.6.2	Use of P-P-ABORT indication parameter.....	25
9	Structure and encoding of ACSE APDUs.....	25
9.1	Abstract syntax of the ACSE APDUs.....	25
9.2	Encoding rules used to reference the transfer syntax.....	29
10	Conformance	29
10.1	Statement requirements.....	30
10.2	Static requirements.....	30
10.2.1	Normal mode	30
10.2.2	X.410-1984 mode	30
10.3	Dynamic requirements	30
10.3.1	Normal mode	30
10.3.2	X.410-1984 mode	30

11	Precedence.....	30
12	Registration requirements	31
12.1	Application titles	31
12.2	Application context.....	31
12.3	Authentication-mechanism	31
Annex A	– ACPM state table	32
A.1	General.....	32
A.2	Conventions	32
A.3	Actions to be taken by the ACPM	32
A.3.1	Invalid intersections	34
A.3.2	Valid intersections	34
A.4	Relationship to Presentation and other ASEs.....	34
Annex B	– Authentication-mechanism using password.....	37
B.0	Introduction.....	37
B.1	Assigned name.....	37
B.2	Authentication-value ASN.1 datatype	37
B.3	Processing specification.....	37
B.3.1	Requesting authentication	37
B.3.2	Performing authentication.....	37

IECNORM.COM : Click to view the full PDF of ISO/IEC 8650-1:1996

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 8650-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open Systems Interconnection, data management and open distributed processing*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.227.

This second edition cancels and replaces the first edition (ISO 8650:1988), which has been technically revised. It also incorporates Amendment 1:1990 and Technical Corrigendum 1:1990.

ISO/IEC 8650 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — Connection-oriented protocol for the Association Control Service Element*:

- *Part 1: Protocol specification*
- *Part 2: Protocol Implementation Conformance Statement (PICS) proforma*

Annexes A and B form an integral part of this part of ISO/IEC 8650.

Introduction

This Protocol Specification is one of a set of Recommendations and International Standards produced to facilitate the interconnection of information processing systems. It is related to other ITU-T Recommendations and International Standards in the set as defined by the Reference Model for Open Systems Interconnection (see ITU-T Rec. X.200 | ISO/IEC 7498-1). The Reference Model subdivides the areas of standardization for interconnection into a series of layers of specification, each of manageable size.

The goal of Open Systems Interconnection is to allow, with a minimum of technical agreement outside the interconnection standards, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different technologies.

This Protocol Specification specifies the connection-oriented mode protocol for the application-service-element for application-association control: the Association Control Service Element (ACSE). The protocol for the ACSE connectionless mode service (A-UNIT-DATA) is specified in ITU-T Rec. X.237 | ISO/IEC 10035-1.

This Recommendation | International Standard specifies the protocol for the application-service-element for application-association control: the Application Control Service Element (ACSE). The ACSE provides services for establishing and releasing application-associations. The ACSE protocol includes two optional functional units. One functional unit supports the exchange of information in support of authentication during association establishment. The second functional unit supports the negotiation of application context during association establishment. The ACSE services apply to a wide range of application-process communications requirements.

This Protocol Specification includes an annex that describes the protocol machine of ACSE in terms of a state table. This protocol machine is referred to as the Association Control Protocol Machine (ACPM).

The protocol defined in this Protocol Specification is also governed by the use of the presentation-service (ITU-T Rec. X.216 | ISO/IEC 8822) and the session-service (see ITU-T Rec. X.215 | ISO/IEC 8326).

Quality of Service (QOS) is a parameter of the A-ASSOCIATE service. Work is still in progress to provide an integrated treatment of QOS across all of the layers of the OSI Reference Model and to ensure that the individual treatments in each layer service satisfy overall QOS objectives in a consistent manner. As a consequence, an addendum may be added to this Protocol Specification at a later time which reflects further QOS developments and integration.

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
CONNECTION-ORIENTED PROTOCOL FOR THE ASSOCIATION CONTROL
SERVICE ELEMENT: PROTOCOL SPECIFICATION**

1 Scope and field of application

The ACSE supports two modes of communication: connection-oriented and connectionless. The ACSE service definition (ITU-T Rec. X.217 | ISO/IEC 8649) includes both modes of communication. This Protocol Specification provides the protocol specification for the connection-oriented mode of communication. The protocol specification for the connectionless mode of communication is contained in ITU-T Rec. X.237 | ISO/IEC 10035-1.

This Protocol Specification defines procedures that are applicable to instances of communication between systems which wish to interconnect in an Open Systems Interconnection environment in a connection-oriented mode. The Protocol Specification includes the Kernel functional unit that is used to establish and release application-associations. The Authentication functional unit provides additional facilities for exchanging information in support of authentication during association establishment without adding new services. The ACSE authentication facilities can be used to support a limited class of authentication methods. The Application Context Negotiation functional unit provides additional facility for the selection of the application context during association establishment.

This Protocol Specification specifies:

- a) procedures for the transfer of information for application-association control and the authentication of application-entities;
- b) the interaction between an ACSE protocol machine and the occurrence of external presentation events; and
- c) the abstract syntax for the representation of the ACSE APDUs.

The ACSE procedures are defined in terms of:

- a) the interactions between peer ACSE protocol machines through the use of presentation-services; and
- b) the interaction between an ACSE protocol machine and its service-user.

This Protocol Specification also specifies conformance requirements for systems implementing these procedures. It does not contain tests which can be used to demonstrate conformance.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and International Standards are subject to revision, and the parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*.
- ITU-T Recommendation X.207 (1993) | ISO/IEC 9545:1994, *Information technology – Open Systems Interconnection – Application layer structure*.
- ITU-T Recommendation X.210 (1993) | ISO/IEC 10731:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: Conventions for the definition of OSI services*.

- ITU-T Recommendation X.215 (1995) | ISO/IEC 8326:1996, *Information technology – Open Systems Interconnection – Session service definition.*
- ITU-T Recommendation X.216 (1994) | ISO/IEC 8822:1994, *Information technology – Open Systems Interconnection – Presentation service definition.*
- ITU-T Recommendation X.217 (1995) | ISO/IEC 8649:1996, *Information technology – Open Systems Interconnection – Service definition for the Association Control Service Element.*
- ITU-T Recommendation X.225 (1995) | ISO/IEC 8327-1:1996, *Information technology – Open Systems Interconnection – Connection-oriented Session protocol: Protocol specification.*
- ITU-T Recommendation X.237 (1995) | ISO/IEC 10035-1:1995, *Information technology – Open Systems Interconnection – Connectionless protocol for the Association Control Service Element: Protocol specification.*
- CCITT Recommendation X.660 (1992) | ISO/IEC 9834-1:1993, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: General procedures.*
- CCITT Recommendation X.665 (1992) | ISO/IEC 9834-6:1993, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Application Processes and Application Entities.*
- ITU-T Recommendation X.690 (1994) | ISO/IEC 8825-1:1995, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.208 (1988), *Specification of Abstract Syntax Notation One (ASN.1).*
ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.650 (1992), *Open Systems Interconnection (OSI) – Reference model for naming and addressing.*
ISO 7498-3:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 3: Naming and addressing.*
- CCITT Recommendation X.800 (1991), *Security architecture for Open Systems Interconnection for CCITT applications.*
ISO 7498-2:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 2: Security Architecture.*

2.3 Additional references

- CCITT Recommendation X.410 (1984), *Message Handling Systems: Remote operation and reliable transfer server.*
- ISO 6523:1984, *Data interchange – Structures for the identification of organizations.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

3.1 Reference Model definitions

3.1.1 Basic Reference Model definitions

This Protocol Specification is based on the concepts developed in ITU-T Rec. X.200 | ISO/IEC 7498-1 and makes use of the following terms defined in it:

- a) Application Layer;
- b) application-process;
- c) application-entity;
- d) application-service-element;
- e) application-protocol-data-unit;

- f) application-protocol-control-information;
- g) presentation-service;
- h) presentation-connection;
- i) session-service;
- j) session-protocol; and
- k) session-connection.

3.1.2 Security architecture definitions

This Protocol Specification makes use of the following term defined in CCITT Rec. X.800 | ISO 7498-2:

- password.

3.1.3 Naming and addressing definitions

This Protocol Specification makes use of the following terms defined in CCITT Rec. X.650 | ISO 7498-3:

- a) application-process title;
- b) application-entity qualifier;
- c) application-entity title¹⁾;
- d) application-process invocation-identifier;
- e) application-entity invocation-identifier; and
- f) presentation address.

3.2 Service conventions definitions

This Protocol Specification makes use of the following terms defined in ITU-T Rec. X.210 | ISO/IEC 10731:

- a) service-provider;
- b) service-user;
- c) confirmed service;
- d) non-confirmed service;
- e) provider-initiated service;
- f) primitive;
- g) request (primitive);
- h) indication (primitive);
- i) response (primitive); and
- j) confirm (primitive).

3.3 Presentation service definitions

This Protocol Specification makes use of the following terms defined in ITU-T Rec. X.216 | ISO/IEC 8822:

- a) abstract syntax;
- b) abstract syntax name;
- c) default context;
- d) defined context set;
- e) functional unit (presentation);
- f) normal mode (presentation);
- g) presentation context;

¹⁾ As defined in CCITT Rec. X.650 | ISO 7498-3, an application-entity title is composed of an application-process title and an application-entity qualifier. The ACSE protocol provides for the transfer of an application-entity title value by the transfer of its component values.

ISO/IEC 8650-1 : 1996 (E)

- h) presentation data value; and
- i) X.410-1984 mode (presentation).

3.4 Application Layer Structure definitions

This Protocol Specification makes use of the following terms defined in ISO/IEC 9545:

- a) application-context;
- b) application-entity invocation;
- c) control function; and
- d) application-service object.

3.5 ACSE service definitions

This Protocol Specification makes use of the following terms defined in ITU-T Rec. X.217 | ISO/IEC 8649:

- a) application-association; association;
- b) Association Control Service Element;
- c) ACSE service-user;
- d) ACSE service-provider;
- e) requestor;
- f) acceptor;
- g) association-initiator;
- h) association-responder;
- j) authentication;
- j) authentication-function;
- k) authentication-value;
- l) authentication-mechanism;
- m) normal mode;
- n) X.410-1984 mode; and
- o) disrupt.

3.6 Association Control protocol specification definitions

The following terms are introduced in this Protocol Specification:

3.6.1 Association Control Protocol Machine: The protocol machine for the Association Control Service Element specified in ITU-T Rec. X.227 | ISO/IEC 8650-1.

3.6.2 requesting Association Control Protocol Machine: The Association Control Protocol Machine whose service-user is the requestor of a particular Association Control Service Element service.

3.6.3 accepting Association Control Protocol Machine: The Association Control Protocol Machine whose service-user is the acceptor for a particular Association Control Service Element service.

3.6.4 external event (to an ASE): A service primitive that is not directly referenced by an ASE but that may disrupt a service procedure of the ASE.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

4.1 Data units

APDU application-protocol-data-unit

4.2 Types of application-protocol-data-units

The following abbreviations have been given to the application-protocol-data-units defined in this Protocol Specification:

AARQ	A-ASSOCIATE-REQUEST APDU
AARE	A-ASSOCIATE-RESPONSE APDU
RLRQ	A-RELEASE-REQUEST APDU
RLRE	A-RELEASE-RESPONSE APDU
ABRT	A-ABORT APDU

4.3 Other abbreviations

The following abbreviations are used in this Protocol Specification:

ACPM	Association Control Protocol Machine
ACSE	Association Control Service Element
AE	application-entity
AEI	application-entity invocation
AP	application-process
APCI	application-protocol-control-information
ASE	application-service-element
ASO	application-service-object
ASN.1	Abstract Syntax Notation One
CF	Control Function
cnf	confirm primitive
ind	indication primitive
OSI	Open Systems Interconnection
req	request primitive
ROA	recognized operating agency
QOS	Quality of Service

5 Conventions

This Protocol Specification employs a tabular presentation of its APDU fields. In clause 7, tables are presented for each ACSE APDU. Each field is summarized using the following notation:

M	Presence is mandatory
O	Presence is ACPM option
U	Presence is ACSE service-user option
req	Source is related request primitive
ind	Sink is related indication primitive
rsp	Source is related response primitive
cnf	Sink is related confirm primitive
ACPM	Source or sink is the ACPM

The structure of each ACSE APDU is specified in clause 9 using the Abstract Syntax Notation of ASN.1 (see CCITT Rec. X.208:1988 and ISO/IEC 8824:1990).

6 Overview of the protocol

6.1 Service provision

The protocol in this Protocol Specification provides the connection-oriented services defined in ITU-T Rec. X.217 | ISO/IEC 8649. Both the connection-oriented and connectionless services are listed in Table 1. The protocol for the connectionless A-UNIT-DATA service is specified in ITU-T Rec. X.237 | ISO/IEC 10035-1.

For a particular association, the ACSE connection-oriented services operate either in the normal mode or in the X.410-1984 mode. The mode of operation is determined by the Mode parameter on the A-ASSOCIATE request primitive.

Table 1 – ACSE-services

Communication mode	Service	Type
Connection-oriented	A-ASSOCIATE A-RELEASE A-ABORT A-P-ABORT	Confirmed Confirmed Non-confirmed Provider-initiated
Connectionless	A-UNIT-DATA	Non-confirmed

6.2 Functional units

Functional units are used by this Protocol Specification to negotiate ACSE user requirements during association establishment. Three functional units are defined:

- a) Kernel functional unit;
- b) Authentication functional unit; and
- c) Application Context Negotiation functional unit.

The ACSE Requirements fields on the AARQ and AARE APDUs are used to select the functional units for the association.

The Kernel functional unit is always available. It is the default functional unit. To be included, the Authentication functional unit and the Application Context Name functional unit shall be explicitly requested on the AARQ APDU and accepted on the AARE APDU.

The selection of the Authentication functional unit supports additional fields on the AARQ, AARE, ABRT and RLRQ APDUs. The selection of the Application Context Negotiation functional unit supports an additional field on the AARQ and the AARE APDUs. Neither functional unit affects the elements of procedure. Table 2 shows the services, APDUs and APDU fields associated with the ACSE functional units.

6.3 Use of the presentation-service

ACSE's use of the presentation-service is determined by ACSE's mode of operation for an association as specified below:

- a) *ACSE normal mode*: The ACPM uses the normal mode of the presentation-service (see ITU-T Rec. X.216 | ISO/IEC 8822). The ACPM uses the presentation-service Kernel functional unit to exchange its APCI and, optionally, ACSE service-user information (i.e. ACSE APDUs) with its peer. The use of additional presentation-service functional units is an ACSE service-user choice. This choice does not affect the operation of the ACPM.
- b) *ACSE X.410-1984 mode*: The ACPM uses the X.410-1984 mode of the presentation-service. Only the Kernel functional unit is available when using the presentation-service X.410-1984 mode. In this mode, the ACPM does not exchange its own APCI with its peer. It simply passes through information supplied to it by the ACSE service-user or by the presentation-service.

This Protocol Specification assumes that the ACPM is the sole user of the P-CONNECT, P-RELEASE, P-U-ABORT, and P-P-ABORT services. The ACSE neither uses nor constrains the use of any other presentation service.

Table 2 – Functional unit APDUs and their fields

Functional Unit	Service	APDU	Field Name
Kernel	A-ASSOCIATE	AARQ	Protocol Version Application Context Name Calling AP Title Calling AE Qualifier Calling AP Invocation-identifier Calling AE Invocation-identifier Called AP Title Called AE Qualifier Called AP Invocation-identifier Called AE Invocation-identifier Implementation Information User Information
		AARE	Protocol Version Application Context Name Responding AP Title Responding AE Qualifier Responding AP Invocation-identifier Responding AE Invocation-identifier Result Result Source-Diagnostic Implementation Information User Information
	A-RELEASE	RLRQ	Reason User Information
		RLRE	Reason User Information
	A-ABORT	ABRT	Abort Source User Information
Authentication	A-ASSOCIATE	AARQ	ACSE Requirements Authentication-mechanism Name Authentication-value
		AARE	Ditto
		ABRT	Diagnostic
Application Context Negotiation	A-ASSOCIATE	AARQ	Application Context Name List ACSE Requirements
		AARE	Ditto

The ACPM does not use the P-RESYNCHRONIZE, P-U-EXCEPTION-REPORT, or P-P-EXCEPTION-REPORT services. However, the A-RELEASE procedure is disrupted if a primitive of one of these presentation services occurs on the association. The disruption is made visible to the ACPM by the occurrence of an external event.

When supported by Version 1 of the session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1), the presentation-service is subject to length restrictions for its user-data parameters. This Protocol Specification assumes that a local mechanism detects violations of these constraints and makes the ACSE service-user aware of them. An encoding optimization is specified for A-ABORT to mitigate this problem (see 7.3.3.1).

6.4 Relationship to the session-service

The session functional units required for the session-connection that supports the presentation-connection (that in turn supports the association) are determined by the A-ASSOCIATE service requestor and acceptor. They accomplish this using the Session Requirements parameter on the A-ASSOCIATE primitives. The session functional units are described in ITU-T Rec. X.215 | ISO/IEC 8326.

The rules of the session-service affect the operation of the ACPM and its service-user. The ACSE service-user must be aware of these constraints. This Protocol Specification assumes that a local mechanism enforces them. Some examples of session-service constraints that affect the ACSE service-user are:

- a) the availability of negotiated release; and
- b) the possibility of release collisions.

6.5 Model

The Association Control Protocol Machine (ACPM) is modeled as a finite state machine whose specification is given in this Protocol Specification. The ACPM communicates with its service-user by means of the ACSE service primitives defined in ITU-T Rec. X.217 | ISO/IEC 8649. The ACPM communicates with its presentation service-provider by means of the presentation services defined in ITU-T Rec. X.216 | ISO/IEC 8822.

NOTE 1 – An application ASE specification that references ACSE need not specify the use of ACSE service primitive parameters that are irrelevant to its operation. The Control Function (CF) that references ACSE can be modeled to pass such parameters between the ACPM and that part of the AEI to which the parameters are relevant.

The ACPM is driven by the receipt of input events from its ACSE service-user and from its presentation service-provider for the underlying presentation-connection that supports the association. The input events from the ACSE service-user are ACSE request and response primitives. The input events from its presentation service-provider are presentation indication and confirm primitives.

The ACPM responds to input events by issuing output events to its presentation service-provider and to its ACSE service-user. The output events to its presentation service-provider are presentation request and response primitives. The output events to its ACSE service-user are ACSE indication and confirm primitives.

The ACPM is aware of external events that occur on the presentation-connection that supports its association (see 6.2). The occurrence of these external events may cause the state of the ACPM to change.

The receipt of an input event, the generation of dependent actions, and the resultant output event are considered to be an indivisible action. Likewise, the occurrence of an external event and the resultant change of state is considered to be an indivisible action.

During the establishment of an association between two AEs, the existence of invocations of both the requesting and responding AEs is presumed. How they are created is outside of the scope of this Protocol Specification.

A new invocation of an ACPM is employed upon the receipt of an A-ASSOCIATE request primitive or a P-CONNECT indication primitive. Each such invocation controls exactly one association.

NOTE 2 – Each association may be identified in an end system by a local mechanism so that the ACSE service-user and the ACPM can refer to the association.

The ACPM is modeled to operate in either one of two modes for a given association: the normal mode; and the X.410-1984 mode as specified below:

- a) When operating in the normal mode, an ACPM communicates with its peer ACPM in support of an association by transferring ACSE Application Protocol Data Units (APDUs) defined in clause 9²). An ACSE APDU is transferred as a presentation data value in the User Data parameter of the presentation primitive used on the underlying presentation-connection.
- b) When operating in the X.410-1984 mode, an ACPM does not transfer ACSE APDUs with its peer. In this situation, the sending and receiving of presentation primitives are in themselves significant protocol events.

7 Elements of procedure

The ACSE protocol consists of the following procedures:

- a) association establishment;
- b) normal release of an association; and
- c) abnormal release of an association.

²) This is true with one exception. If the association is supported by Version 1 of the session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1), the requesting ACPM does not pass ACSE APCI as user data on a P-U-ABORT request primitive. The absence of ACSE APCI in this situation does not imply that the association is operating in the X.410-1984 mode (see 7.3.3.1).

In this clause, a summary of each of these elements of procedure is presented. This consists of a summary of the relevant APDUs, and a high-level overview of the relationship between the ACSE services, the APDUs involved, and the presentation service that is used. Clause 8 describes how the parameters of the presentation primitives are used. In clause 9, a detailed specification of the ACSE APDUs is given using the notation of ASN.1 (see CCITT Rec. X.208 (1988) and ISO/IEC 8824:1990). Annex A presents the state table for the ACPM.

7.1 Association establishment

7.1.1 Purpose

The association establishment procedure is used to establish an association between two AEs. It supports the A-ASSOCIATE service.

7.1.2 APDUs used

The association establishment procedure uses the A-ASSOCIATE-REQUEST (AARQ) and the A-ASSOCIATE-RESPONSE (AARE) APDUs. The fields of the AARQ APDU are listed in Table 3. The fields of the AARE APDU are listed in Table 4.

Table 3 – AARQ APDU fields

Field name	Presence	Source	Sink
Protocol Version	O	ACPM	ACPM
Application Context Name	M	req	ind
Application Context Name List	U	req	ind
Calling AP Title	U	req	ind
Calling AE Qualifier	U	req	ind
Calling AP Invocation-identifier	U	req	ind
Calling AE Invocation-identifier	U	req	ind
Called AP Title	U	req	ind
Called AE Qualifier	U	req	ind
Called AP Invocation-identifier	U	req	ind
Called AE Invocation-identifier	U	req	ind
ACSE-requirements	U	req	ind
Authentication-mechanism Name	U	req	ind
Authentication-value	U	req	ind
Implementation Information	O	ACPM	ACPM
User Information	U	req	ind

NOTES

- The Authentication-mechanism Name and Authentication-value fields are only present if the ACSE-requirements field includes the Authentication functional unit.
- The Application Context Name List field is only present if the ACSE-requirements field includes the Application Context Negotiation functional unit. The value of the Application Context Name parameter may be different from any of the names in the Application Context Name List parameter or it may be equal to one of the names in the list.

7.1.3 Association establishment procedure

This procedure is driven by the following events:

- an A-ASSOCIATE request primitive from the requestor;
- an AARQ APDU as user data on a P-CONNECT indication primitive;
- an A-ASSOCIATE response primitive from the acceptor; and
- a P-CONNECT confirm primitive (that may or may not contain an AARE APDU).

Table 4 – AARE APDU fields

Field name	Presence	Source	Sink
Protocol Version	O	ACPM	ACPM
Application Context Name	M	rsp	cnf
Application Context Name List	U	rsp	cnf
Responding AP title	U	rsp	cnf
Responding AE Qualifier	U	rsp	cnf
Responding AP-Invocation-identifier	U	rsp	cnf
Responding AE-Invocation-identifier	U	rsp	cnf
Result	M	rsp/ACPM	cnf
Result Source – Diagnostic	M	rsp/ACPM	cnf
ACSE-requirements	U	rsp	cnf
Authentication-mechanism Name	U	rsp	cnf
Authentication-value	U	rsp	cnf
Implementation Information	O	ACPM	ACPM
User Information	U	rsp	cnf

NOTES

1 The Authentication-mechanism Name and Authentication-value fields are only present if the ACSE-requirements field includes the Authentication functional unit.

2 The Application Context Name List field is only present if the ACSE-requirements field includes the Application Context Negotiation functional unit and the result = rejected. The value of the Application Context Name parameter may be different from any of the names in the Application Context Name List parameter or it may be equal to one of the names in the list.

7.1.3.1 A-ASSOCIATE request primitive

The requesting ACPM forms an AARQ APDU from parameter values of the A-ASSOCIATE request primitive and optionally, the Protocol Version and implementation information. It issues a P-CONNECT request primitive also using information from the A-ASSOCIATE request primitive. The User Data parameter of the P-CONNECT request primitive contains the AARQ APDU.

The requesting ACPM waits for a primitive from the presentation service-provider and does not accept any other primitive from the requestor other than an A-ABORT request primitive.

7.1.3.2 AARQ APDU

The accepting ACPM receives an AARQ APDU from its peer as user data on a P-CONNECT indication primitive.

The ACPM determines if the AARQ APDU is acceptable based on the rules for extensibility (see 7.4). If the AARQ APDU is not acceptable, a protocol error results (see 7.3.3.4). The association establishment procedure is disrupted. An A-ASSOCIATE indication primitive is not issued. The association is not established.

The ACPM next inspects the value of the Protocol Version field³⁾ of the AARQ APDU. If the ACPM does not support a common protocol version, it forms an AARE APDU with the following assigned fields:

- a) Protocol Version field (optional) with the value that indicates the protocol version(s) that it could support (see 7.1.5.1);
- b) Application Context Name field with the same value as on the AARQ APDU;
- c) Result field with the value “rejected (permanent)”; and source – Diagnostic field with the values “ACSE service-provider” and “no common ACSE version”.

In this case, the ACPM sends the AARE APDU as user data on a P-CONNECT response primitive with a Result parameter that has the value “user rejection”. The ACPM does not issue an A-ASSOCIATE indication primitive. The association is not established.

³⁾ If the Protocol Version field is not present in the AARQ APDU, Version 1 is assumed.

If the P-CONNECT indication primitive and its AARQ APDU are acceptable, the ACPM inspects the ACSE requirements field if it is present. It removes functional units that it does not support. The ACPM then issues an A-ASSOCIATE indication primitive to the acceptor. The A-ASSOCIATE indication primitive parameters are derived from the AARQ APDU and the P-CONNECT indication primitive. The ACPM waits for a primitive from the acceptor.

7.1.3.3 A-ASSOCIATE response primitive

When the accepting ACPM receives the A-ASSOCIATE response primitive, the Result parameter specifies whether the service-user has accepted or rejected the association. The ACPM forms an AARE APDU using the A-ASSOCIATE response primitive parameters. The ACPM sets the Result Source – Diagnostic field to “ACSE service-user” and the value derived from the Diagnostic parameter of the response primitive. The AARE APDU is sent as the User Data parameter on the P-CONNECT response primitive.

If the acceptor accepted the association request, the Result parameter on the related P-CONNECT response primitive specifies “acceptance”, and the Result field of the outgoing AARE APDU specifies “accepted”. The association is established.

If the acceptor rejected the association request, the Result parameter on the related P-CONNECT response primitive specifies “user-rejection”, and the Result field of the AARE APDU contains the appropriate rejection value. The association is not established.

7.1.3.4 P-CONNECT confirm primitive

The requesting ACPM receives a P-CONNECT confirm primitive. The following situations are possible:

- a) the association has been accepted;
- b) the accepting ACPM or the acceptor has rejected the association, or
- c) the presentation service-provider has rejected the related presentation connection.

If the association was accepted, the P-CONNECT confirm primitive Result parameter specifies “acceptance”. The User Data parameter contains an AARE APDU. The Result field of the AARE APDU specifies “accepted”. The requesting ACPM issues an A-ASSOCIATE confirm primitive to the requestor derived from parameters from the P-CONNECT confirm primitive and the AARE APDU. The A-ASSOCIATE confirm primitive Result parameter specifies “accepted”. The association is established.

If the association was rejected by either the accepting ACPM or by the acceptor, the related P-CONNECT confirm primitive Result parameter specifies “user-rejection”. The User Data parameter contains an AARE APDU.

The requesting ACPM issues an A-ASSOCIATE confirm primitive to the requestor derived from parameters from the P-CONNECT confirm primitive and the AARE APDU. The A-ASSOCIATE confirm primitive Result parameter indicates “rejected (transient)” or “rejected (permanent)”. The Result Source parameter indicates “ACSE service-user” or “ACSE service-provider”. The association is not established.

If the presentation-connection was rejected by the presentation service-provider, the P-CONNECT confirm primitive Result parameter specifies “provider-rejection.” In this situation, the User Data field is not used. The requesting ACPM issues an A-ASSOCIATE confirm primitive with the Result parameter indicating “rejected (permanent).” The Result Source parameter indicates “presentation service-provider”⁴⁾. The association is not established.

7.1.4 Use of the AARQ APDU fields

The AARQ APDU fields are used by the requesting and accepting ACPMs as specified below.

7.1.4.1 Protocol Version

- *For the requesting ACPM:* The value assigned to this field is determined within the implementation of the ACPM. It is a variable length bit string where each bit that is set to one indicates the version of ACSE protocol that this ACPM supports. Bit 0 represents Version 1; bit 1 represents Version 2; etc. Multiple bits may be set indicating support of multiple versions. No trailing bits higher than the highest version of this Protocol Specification that the requesting ACPM supports are included. That is, the last bit of the string is set to one.

⁴⁾ The presentation-service (see ITU-T Rec. X.216 | ISO/IEC 8822) currently does not define a Diagnostic parameter on the P-CONNECT response. However, work is still in progress to provide an integrated treatment of the “result” related parameters across all layers of the OSI Reference Model. As a consequence, an addendum may be added to this Protocol Specification at a later time that reflects further developments and integration.

- *For the accepting ACPM:* The ACPM ignores trailing bits of this field that are higher than the one indicating the latest version of this Protocol Specification that it supports.

7.1.4.2 Application Context Name

- *For the requesting ACPM:* This value is determined by the value of the Application Context Name parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Application Context Name parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.3 Calling AP Title

- *For the requesting ACPM:* This value is determined by the value of the Calling AP Title parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Calling AP Title parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.4 Calling AE Qualifier

- *For the requesting ACPM:* This value is determined by the value of the Calling AE Qualifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Calling AE Qualifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.5 Calling AP Invocation-identifier

- *For the requesting ACPM:* This value is determined by the value of the Calling AP Invocation-identifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to derive the value of the Calling AP Invocation-identifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.6 Calling AE Invocation-identifier

- *For the requesting ACPM:* This value is determined by the value of the Calling AE Invocation-identifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to derive the value of the Calling AE Invocation-identifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.7 Called AP Title

- *For the requesting ACPM:* This value is determined by the value of the Called AP Title parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Called AP Title parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.8 Called AE Qualifier

- *For the requesting ACPM:* This value is determined by the value of the Called AE Qualifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Called AE Qualifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.9 Called AP Invocation-identifier

- *For the requesting ACPM:* This value is determined by the value of the Called AP Invocation-identifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Called AP Invocation-identifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.10 Called AE Invocation-identifier

- *For the requesting ACPM:* This value is determined by the value of the Called AE Invocation-identifier parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Called AE Invocation-identifier parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.11 ACSE-requirements

- *For the requesting ACPM:* The value assigned to this field is determined by the value of the ACSE Requirements parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the ACSE Requirements parameter of the A-ASSOCIATE indication primitive, if issued. The ACPM inspects the ACSE-requirements field and removes any functional units not supported by the ACPM before issuing it to the service-user.

7.1.4.12 Authentication-mechanism Name

- *For the requesting ACPM:* The value assigned to this field is determined by the value of the Authentication-mechanism Name parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Authentication-mechanism Name parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.13 Authentication-value

- *For the requesting ACPM:* The value assigned to this field is determined by the value of the Authentication-value parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Authentication-value parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.14 Implementation Information

- *For the requesting ACPM:* The value assigned to this field is determined within the implementation of the ACPM. It contains information specific to the individual implementation of that ACPM. It is not used in negotiation.
- *For the accepting ACPM:* This field does not affect the operation of the ACPM. Any use depends on a common understanding between the requesting and accepting ACPMs.

7.1.4.15 User Information

- *For the requesting ACPM:* This value is determined by the value of the User Information parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the User Information parameter of the A-ASSOCIATE indication primitive, if issued.

7.1.4.16 Application Context Name List

- *For the requesting ACPM:* The values assigned to this field are determined by the values of the Application Context Name List parameter of the A-ASSOCIATE request primitive.
- *For the accepting ACPM:* The values are used to determine the values of the Application Context Name List parameter on the A-ASSOCIATE indication primitive, if issued.

7.1.5 Use of the AARE APDU fields

The AARE APDU fields are used by the accepting and requesting ACPMs as specified below.

7.1.5.1 Protocol Version

- *For the accepting ACPM:* The value of this field assigned by the ACPM depends on whether the association request is accepted or rejected by the ACPM and the acceptor, as specified below:
 - a) If the association is accepted, the value assigned by the ACPM is a variable length bit string that indicates the protocol version selected by the ACPM from those proposed in the AARQ APDU. Only the bit indicating the version selected is set to one. That bit is the last bit in the string.
 - b) If the association is rejected, the value assigned by the ACPM is a variable length bit string that indicates the protocol version(s) of this Protocol Specification that could be supported by the ACPM.
- *For the requesting ACPM:* The use of the value in this field depends on whether the association request is accepted or rejected:
 - a) If the association is accepted, this value defines the protocol version of this Protocol Specification to be used for this association.
 - b) If the association is rejected, the use of this value is a local option.

7.1.5.2 Application Context Name

- *For the accepting ACPM:* This value is determined by the value of the Application Context Name parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Application Context Name parameter of the A-ASSOCIATE confirm primitive.

7.1.5.3 Responding AP Title

- *For the accepting ACPM:* This value is determined by the value of the Responding AP Title parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Responding AP Title parameter of the A-ASSOCIATE confirm primitive, if issued.

7.1.5.4 Responding AE Qualifier

- *For the accepting ACPM:* This value is determined by the value of the Responding AE Qualifier parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Responding AE Qualifier parameter of the A-ASSOCIATE confirm primitive, if issued.

7.1.5.5 Responding AP Invocation-identifier

- *For the accepting ACPM:* This value is determined by the value of the Responding AP Invocation-identifier parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Responding AP Invocation-identifier parameter of the A-ASSOCIATE confirm primitive, if issued.

7.1.5.6 Responding AE Invocation-identifier

- *For the accepting ACPM:* This value is determined by the value of the Responding AE Invocation-identifier parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Responding AE Invocation-identifier parameter of the A-ASSOCIATE confirm primitive, if issued.

7.1.5.7 Result

- *For the accepting ACPM:* The value is determined by the ACPM or by the acceptor as specified below:
 - a) If the AARQ APDU is rejected by the ACPM (i.e. an A-ASSOCIATE indication primitive is not issued to the acceptor), the value of “rejected (permanent)” or “rejected (transient)” is assigned by the ACPM.
 - b) Otherwise, the value is determined by the Result parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Result parameter of the A-ASSOCIATE confirm primitive.

7.1.5.8 Result Source – Diagnostic

This field contains both the Result Source value and the Diagnostic value.

7.1.5.8.1 Result Source value

- *For the accepting ACPM:* This value is assigned by the ACPM as specified below:
 - a) If the AARQ APDU is rejected by the ACPM (i.e. an A-ASSOCIATE indication primitive is not issued to the acceptor), it assigns the value “ACSE service-provider.”
 - b) Otherwise, the ACPM assigns the value “ACSE service-user.”
- *For the requesting ACPM:* This value is used to determine the value of the Result Source parameter of the A-ASSOCIATE confirm primitive.

7.1.5.8.2 Diagnostic value

- *For the accepting ACPM:* This value is determined by the ACPM or by the acceptor as specified below:
 - a) If the AARQ APDU is rejected by the ACPM (i.e. an A-ASSOCIATE indication primitive is not issued to the acceptor), the appropriate value is assigned by the ACPM.

- b) Otherwise, the value is determined by the value of the Diagnostic parameter of the A-ASSOCIATE response primitive. If the Diagnostic parameter is not included on the response primitive, the ACPM assigns the value of "null."
- *For the requesting ACPM:* This value is used to determine the value of the Diagnostic parameter of the A-ASSOCIATE confirm primitive, unless it has the value of "null.". In this case, a Diagnostic value is not included.

7.1.5.9 ACSE-requirements

- *For the accepting ACPM:* The value assigned to this field is determined by the value of the ACSE Requirements parameter of the A-ASSOCIATE response primitive. This value shall only include functional units that were on the indication primitive.
- *For the requesting ACPM:* This value is used to determine the value of the ACSE Requirements parameter of the A-ASSOCIATE confirm primitive.

7.1.5.10 Authentication-mechanism Name

- *For the accepting ACPM:* The value assigned to this field is determined by the value of the Authentication-mechanism Name parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Authentication-mechanism Name parameter of the A-ASSOCIATE confirm primitive.

7.1.5.11 Authentication-value

- *For the accepting ACPM:* The value assigned to this field is determined by the value of the Authentication-value parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Authentication-value parameter of the A-ASSOCIATE confirm primitive.

7.1.5.12 Implementation Information

- *For the accepting ACPM:* The value assigned to this field is determined within the implementation of the ACPM. It contains information specific to the individual implementation of that ACPM. It is not used in negotiation.
- *For the requesting ACPM:* This field does not affect the operation of the ACPM. Any use depends on a common understanding between the accepting and requesting ACPMs.

7.1.5.13 User Information

- *For the accepting ACPM:* This value is determined by the value of the User Information parameter of the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the User Information parameter of the A-ASSOCIATE confirm primitive.

7.1.5.14 Application Context Name List

- *For the accepting ACPM:* The values assigned to this field are determined by the values of the Application Context Name List parameter on the A-ASSOCIATE response primitive.
- *For the requesting ACPM:* The values are used to determine the values of the Application Context Name List parameter on the A-ASSOCIATE confirm primitive.

7.1.6 Collisions and interactions

7.1.6.1 A-ASSOCIATE service

For a given ACPM, an A-ASSOCIATE collision cannot occur (see 6.5). For a given AE, two distinct ACPMs would be involved that represent the processing for two distinct associations:

- a) an ACPM that processes the initial A-ASSOCIATE request primitive that results in the sending of an AARQ as user data on a P-CONNECT request primitive; and
- b) an ACPM that processes the subsequently received AARQ APDU as user data on a P-CONNECT indication primitive.

7.1.6.2 A-ABORT, P-U-ABORT, or P-P-ABORT service

If an ACPM receives an A-ABORT request primitive, a P-U-ABORT indication primitive, or a P-P-ABORT indication primitive, it discontinues the normal association establishment procedure, and instead follows the abnormal release procedure.

7.2 Normal release of an association

7.2.1 Purpose

This procedure is used for the normal release of an association by an AE without loss of information in transit. It supports the A-RELEASE service.

7.2.2 APDUs used

The normal release procedure uses the A-RELEASE-REQUEST (RLRQ) APDU and the A-RELEASE-RESPONSE (RLRE) APDU. The fields of the RLRQ APDU are listed in Table 5. The fields of the RLRE APDU are listed in Table 6.

Table 5 – RLRQ APDU fields

Field name	Presence	Source	Sink
Reason	U	req	ind
User Information	U	req	ind

Table 6 – RLRE APDU fields

Field name	Presence	Source	Sink
Reason	U	rsp	cnf
User Information	U	rsp	cnf

7.2.3 Normal release procedure

This procedure is driven by the following events:

- a) A-RELEASE request primitive from the requestor;
- b) RLRQ APDU as user data on a P-RELEASE indication primitive;
- c) A-RELEASE response primitive from the acceptor;
- d) RLRE APDU as user data on a P-RELEASE confirm primitive; or
- e) disruption by an external event.

7.2.3.1 A-RELEASE request primitive

When an A-RELEASE request primitive is received, the ACPM sends an RLRQ APDU as user data on a P-RELEASE request primitive using the parameters from the A-RELEASE request primitive.

NOTE – The requestor is required to meet the presentation (and session) requirements in order to issue an A-RELEASE request primitive (see 6.3 and 6.4).

The requesting ACPM now waits for a primitive from the presentation service-provider. It does not accept any primitives from the requestor other than an A-ABORT request primitive.

7.2.3.2 RLRQ APDU

When the accepting ACPM receives the RLRQ APDU as user data on a P-RELEASE indication primitive, it issues an A-RELEASE indication primitive to the acceptor. It does not accept any ACSE primitives from its service-user other than an A-RELEASE response primitive or an A-ABORT request primitive.

7.2.3.3 A-RELEASE response primitive

The Result parameter on the A-RELEASE response primitive specifies whether the acceptor accepts or rejects the release of the association. The accepting ACPM forms an RLRE APDU from the response primitive parameters. The RLRE APDU is sent as user data on a P-RELEASE response primitive:

- a) If the acceptor accepted the release, the Result parameter of the P-RELEASE response primitive has a Result parameter value of "affirmative." The association is released.
- b) If the acceptor rejected the release, the Result parameter of the P-RELEASE response primitive has a Result parameter value of "negative." The association continues.

NOTE – To give a negative response, the acceptor is required to meet the related presentation (and session) requirements (see 6.4).

7.2.3.4 RLRE APDU

The requesting ACPM receives a P-RELEASE confirm primitive containing an RLRE APDU from its peer. The Result parameter on the P-RELEASE confirm primitive specifies either that the acceptor agrees or disagrees that the association may be released. The requesting ACPM forms an A-RELEASE confirm primitive from the RLRE APDU fields:

- a) If the Result parameter on the P-RELEASE confirm primitive specifies "affirmative", the association is released.
- b) If the Result parameter on the P-RELEASE confirm primitive specifies "negative", the association continues. The requesting ACPM again accepts primitives from its service-user.

7.2.3.5 A-RELEASE service collision

An A-RELEASE service collision occurs when an ACPM has sent out an RLRQ APDU as the user data of a P-RELEASE request primitive (as a result of receiving an A-RELEASE request primitive from its service-user). Instead of receiving the expected RLRE APDU as user data on a P-RELEASE confirm primitive from its peer, it receives an RLRQ APDU as the user data of a P-RELEASE indication primitive.

The ACPM issues an A-RELEASE indication primitive to its service-user. The procedure then followed by an ACPM depends on whether its service-user was the association-initiator or the association-responder:

- a) *For the association-initiator:*
 - 1) The ACPM waits for an A-RELEASE response primitive from its service-user. When it receives the response primitive, it forms an RLRE APDU from the response primitive's parameters. The RLRE is sent as user data on a P-RELEASE response primitive. The association continues.
 - 2) This ACPM now waits for an RLRE from its peer as user data on a P-RELEASE confirm primitive. It does not accept any primitive from its service-user other than an A-ABORT request primitive.
 - 3) When the ACPM receives the RLRE, it forms an A-RELEASE confirm primitive from the RLRE fields and issues it to its service-user. The association is released.

In summary, the sequence of events that drive the ACPM of the association-initiator are:

- A-RELEASE request primitive;
- RLRQ APDU (causing the collision);
- A-RELEASE response primitive; and finally,
- RLRE APDU.

- b) *For the association-responder:*

- 1) The ACPM waits for an RLRE from its peer as user data on a P-RELEASE confirm primitive. It does not accept a primitive from its service-user other than an A-ABORT request primitive.
- 2) When this ACPM receives the RLRE, it forms an A-RELEASE confirm primitive from the RLRE fields. The association continues.
- 3) The ACPM now waits for an A-RELEASE response primitive from its service-user. When it receives the response primitive, it forms a RLRE APDU from the response primitive's parameters. The RLRE is sent as user data on a P-RELEASE response primitive. The association is released.

In summary, the sequence of events that drive the ACPM of the association-responder are:

- A-RELEASE request primitive;
- RLRQ APDU (causing the collision);

- RLRE APDU; and finally
- A-RELEASE response primitive.

7.2.3.6 Disruption by external event

7.2.3.6.1 The normal release procedure is disrupted by the occurrence of an external event resulting from a service primitive of one of the following services:

- a) P-RESYNCHRONIZE; or
- b) P-U-EXCEPTION-REPORT; or
- c) P-P-EXCEPTION-REPORT.

7.2.3.6.2 When the normal release procedure is disrupted, the association is again available for use as though the A-RELEASE procedure had not been invoked.

7.2.4 Use of the RLRQ APDU fields

The RLRQ APDU fields are used by the requesting and accepting ACPMs as specified below.

7.2.4.1 Reason

- *For the requesting ACPM:* This value is determined by the value of the Reason parameter of the A-RELEASE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Reason parameter of the A-RELEASE indication primitive.

7.2.4.2 User Information

- *For the requesting ACPM:* This value is determined by the value of the User Information parameter of the A-RELEASE request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the User Information parameter of the A-RELEASE indication primitive.

7.2.5 Use of the RLRE APDU fields

The RLRE APDU fields are used by the accepting and requesting ACPMs as specified below.

7.2.5.1 Reason

- *For the accepting ACPM:* This value is determined by the value of the Reason parameter of the A-RELEASE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the Reason parameter of the A-RELEASE confirm primitive.

7.2.5.2 User Information

- *For the accepting ACPM:* This value is determined by the value of the User Information parameter of the A-RELEASE response primitive.
- *For the requesting ACPM:* This value is used to determine the value of the User Information parameter of the A-RELEASE confirm primitive.

7.2.6 Collisions and disruptions

7.2.6.1 A-RELEASE service collision

For a given ACPM, an A-RELEASE service collision can occur. The processing for such a collision is described in 7.2.3.5.

NOTE – An A-RELEASE service collision can only occur if no session tokens were selected for the association.

7.2.6.2 A-RELEASE disruption

The normal release procedure is disrupted when the ACPM receives an A-ABORT request primitive, a P-U-ABORT indication primitive, or a P-P-ABORT indication primitive. The processing for the ACPM follows the abnormal release procedure (see 7.3).

7.3 Abnormal release of an association

7.3.1 Purpose

The Abnormal Release procedure can be used at any time to force the abrupt release of the association by a requestor in either AE, by either ACPM or by the presentation service-provider. When the abnormal release procedure is applied during an attempt to establish an association, the association is not established. The abnormal release procedure supports the A-ABORT and A-P-ABORT services.

7.3.2 APDUs used

The abnormal release procedure uses the A-ABORT (ABRT) APDU. The fields of the ABRT APDU are listed in Table 7.

NOTE – No APDUs are defined for the A-P-ABORT service since it is directly mapped from the P-P-ABORT service.

Table 7 – ABRT APDU fields

Field name	Presence	Source	Sink
Abort Source	M	ACPM	ind
Diagnostic	U	req	ind
User Information	U	req	ind

7.3.3 Abnormal release procedure

This procedure is driven by the following events:

- a) an A-ABORT request primitive from the requestor;
- b) a P-U-ABORT indication primitive;
- c) a P-P-ABORT indication primitive; or
- d) a protocol error detected by an ACPM.

7.3.3.1 A-ABORT request primitive

When an ACPM receives an A-ABORT request primitive from its service-user, the processing that it performs depends on the version of the underlying session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1) that supports the association as specified below:

- a) For Version 1, the ACPM does not send any of its APCI to its peer. It simply issues a P-U-ABORT request primitive. If user information is included on the A-ABORT request primitive, that user information is passed as user data on the P-U-ABORT request primitive. The association is released.
- b) For other versions, the ACPM sends an ABRT APDU as user data on a P-U-ABORT request primitive. The Abort Source field is specified as “ACSE service-user.” If the User Information parameter is included on the A-ABORT request primitive, it is included in the ABRT APDU. The association is released.

7.3.3.2 P-U-ABORT indication primitive

When an ACPM receives a P-U-ABORT indication primitive, the User Data parameter may contain⁵⁾ an ABRT APDU:

- a) If the indication primitive does not contain an ABRT APDU, the ACPM issues an A-ABORT indication primitive with the Abort Source parameter specified as “ACSE service-user.” If user data is contained on the P-U-ABORT indication primitive, it is included as the User Information parameter of the A-ABORT indication primitive. The association is released.
- b) If the indication primitive does contain an ABRT APDU, the ACPM issues an A-ABORT indication primitive using the Abort Source field of the ABRT APDU. If a User Information field is contained in the ABRT APDU, it is included on the A-ABORT indication primitive. The association is released.

⁵⁾ If an association is supported by Version 1 of the session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1), the User Data parameter does not contain an ABRT APDU (see 7.3.3.1). The absence of an APDU in this situation does not imply that the application is operating in the X.410-1984 mode.

7.3.3.3 P-P-ABORT indication primitive

When an ACPM receives a P-P-ABORT indication primitive, the ACPM issues an A-P-ABORT indication primitive to the acceptor. The association is released.

7.3.3.4 Protocol errors

Two types of ACSE protocol errors are possible:

- a) for a particular ACPM state, an unexpected APDU is received; or
- b) an invalid field is encountered during the processing of an incoming APDU (see 7.4).

If an unexpected APDU is received, the abnormal release procedure is invoked. If an invalid field is detected by an ACSE procedure, that procedure is disrupted and the abnormal release procedure is invoked.

As part of the abnormal release procedure, the ACPM issues an A-ABORT indication primitive to its service-user, unless the error occurred during the association establishment procedure⁶⁾ as the result of receiving an invalid AARQ (see 7.4). If an indication primitive is issued, the value of the Abort Source is "ACSE service-provider". The User Information parameter is not used as specified below.

The subsequent ACPM processing performed depends on the version of the underlying session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1) that supports the association as specified below:

- a) For Version 1, the ACPM issues a P-U-ABORT request primitive. No user information is included.
- b) For other versions, the ACPM sends an ABRT APDU as user data on a P-U-ABORT request primitive. The Abort Source field is specified as "ACSE service-provider". The User Information field is not used.

In either case, the association is released.

7.3.4 Use of the ABRT APDU fields

The ABRT APDU fields are used by the requesting and accepting ACPMs as specified below.

7.3.4.1 Abort Source

- *For the requesting ACPM:* This value is assigned by the ACPM as specified below:
 - a) If the ACPM initiated the abort procedure, the ACPM assigns the value of "ACSE service-provider";
 - b) Otherwise, the ACPM assigns the value of "ACSE service-user".
- *For the accepting ACPM:* This value is used to determine the value of the Abort Source parameter of the A-ABORT indication primitive.

7.3.4.2 Diagnostic

- *For the requesting ACPM:* This value is determined by the value of the Diagnostic parameter of the A-ABORT request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the Diagnostic parameter of the A-ABORT indication primitive.

7.3.4.3 User Information

- *For the requesting ACPM:* This value is determined by the value of the User Information parameter of the A-ABORT request primitive.
- *For the accepting ACPM:* This value is used to determine the value of the User Information parameter of the A-ABORT indication primitive.

7.3.5 Collisions and interactions

The abnormal release procedure may be used whenever an association is established, is in the process of being established, or is being normally released. This procedure disrupts any other currently active procedure. A P-P-ABORT indication primitive can disrupt the A-ABORT procedure with loss of the A-ABORT information. Collisions of ABRT APDUs are governed by the P-U-ABORT services (see ITU-T Rec. X.216 | ISO/IEC 8822).

⁶⁾ Since an A-ASSOCIATE indication primitive will not be issued, an A-ABORT indication primitive would have no meaning, and, therefore, it is not issued.

7.4 Rules for extensibility

When processing an incoming AARQ, the accepting ACPM shall:

- a) ignore all tagged values that are not defined in the abstract syntax of this Protocol Specification; and
- b) ignore all unknown bit name assignments within a bit string.

After the association has been established or during the establishment of an association, only those ACSE APDUs and related APDU fields defined in the ASN.1 description of the negotiated version of this Protocol Specification shall be issued.

A received APDU or field within an APDU which is not defined in the ASN.1 description of the negotiated version of this Protocol Specification shall be treated as a protocol error.

8 Mapping to the presentation-service

This clause specifies how the presentation service primitives are used by the ACPM. This usage depends on the mode selected (see 6.3) for the association:

- a) *For the requesting ACPM:* The mode for the association is determined by the value of the Mode parameter of the invoking A-ASSOCIATE request primitive. If the Mode parameter is not included on the request primitive, the default value of "normal" is used.
- b) *For the accepting ACPM:* The mode is determined by the value of the Mode parameter of the incoming P-CONNECT indication primitive.

Subclauses 8.1 to 8.3 specify the usage of the presentation services for the normal mode. Subclauses 8.4 to 8.6 specify the usage for the X.410-1984 mode. Table 8 summarizes the mapping of ACSE primitives and their related APDUs to the presentation primitives used.

Table 8 – Mapping overview

ACSE primitive	APDU ^{a)}	Presentation primitive
A-ASSOCIATE request/indication A-ASSOCIATE response/confirm	AARQ AARE	P-CONNECT request/indication P-CONNECT response/confirm
A-RELEASE request/indication A-RELEASE response/confirm	RLRQ RLRE	P-RELEASE request/indication P-RELEASE response/confirm
A-ABORT request/indication A-P-ABORT indication	ABRT –	P-U-ABORT request/indication P-P-ABORT indication
a) ACSE APDUs are not used in the X.410-1984 mode.		

8.1 Association establishment (normal mode)

The association establishment procedure uses the P-CONNECT service. Association establishment takes place concurrently with the establishment of the underlying presentation-connection.

8.1.1 Directly mapped parameters

- *For the P-CONNECT primitives:* The following parameters are not referenced by the ACPM and are mapped directly onto the corresponding parameters of the A-ASSOCIATE primitives:
 - a) Calling Presentation Address;
 - b) Called Presentation Address;
 - c) Responding Presentation Address;
 - d) Presentation Context Definition List;
 - e) Presentation Context Definition Result List;
 - f) Default (Presentation) Context Name;
 - g) Default (Presentation) Context Result;

- h) Quality of Service;
- i) Presentation Requirements;
- j) Session Requirements;
- k) Initial Synchronization Point Serial Number;
- l) Initial Assignment of Tokens; and
- m) Session-connection Identifier.

8.1.2 Use of other P-CONNECT request and indication parameters

The Mode and User Data parameters of the P-CONNECT request and indication primitives are referenced by the ACPM.

8.1.2.1 Mode

- *For the P-CONNECT request primitive:* The Mode parameter is set to the value of the Mode parameter of the A-ASSOCIATE request primitive. For the normal mode of ACSE operation, this parameter has the value of “normal”. This indicates to the presentation-service that it is to operate in the normal mode for this presentation-connection.
- *For the P-CONNECT indication primitive:* This parameter has the value of “normal” for the normal mode of ACSE operation. The value indicates that the accepting ACPM is to operate in the normal mode for this association. The Mode parameter of the A-ASSOCIATE indication primitive is set to the value of “normal”.

8.1.2.2 User Data

- *For both the P-CONNECT request and indication primitives:* The User Data parameter is used to carry the AARQ APDU as specified below:
 - a) The APCI of the AARQ APDU is expressed using the ACSE abstract syntax of this Protocol Specification. This abstract syntax must be included as the value of a presentation context definition parameter specified by the requestor on the A-ASSOCIATE request primitive.
NOTE – The requesting and accepting ACPMs are aware of the presentation context that contains their abstract syntax by a local mechanism.
 - b) User information (if any) from the A-ASSOCIATE request primitive is included in the AARQ APDU and is expressed using one or more presentation contexts specified by the requestor on the A-ASSOCIATE request primitive.

8.1.3 Use of other P-CONNECT response and confirm parameters

The User Data and Result parameters of the P-CONNECT response and confirm primitive are referenced by the ACPM.

8.1.3.1 Result⁷⁾

- *For the P-CONNECT response primitive:* The Result parameter is set by the accepting ACPM as specified below:
 - a) If the accepting ACPM itself rejects the association, it is set as “user-rejection”.
 - b) If the accepting ACPM accepts the request, the value is set as “acceptance”, or “user-rejection” as determined by the value of the corresponding Result parameter on the A-ASSOCIATE response primitive.
- *For the P-CONNECT confirm primitive:* The Result parameter is used by the requesting ACPM to determine if the P-CONNECT confirm primitive User Data parameter contains an AARE APDU as specified below:
 - a) If the Result parameter has the value “provider-rejection”, the request is rejected by the presentation service-provider. The intended accepting ACPM never received the AARQ APDU. The User Data parameter does not contain an AARE APDU.
 - b) Otherwise, the Result parameter has the value of “acceptance” or “user rejection.” The accepting ACPM received the AARQ APDU and has returned an AARE APDU that is contained in the User Data parameter.

⁷⁾ The AARE APDU also has a Result field that must correspond to the value of this presentation parameter. The Result parameter of the A-ASSOCIATE confirm primitive is determined by the Result field of the AARE APDU.

8.1.3.2 User Data

The User Data field only has relevance if the P-CONNECT request primitive was not rejected by the presentation service-provider (see 8.1.3.1).

- *For both the P-CONNECT response and confirm primitives:* The User Data parameter is used to carry the AARE APDU as specified below:
 - a) The APCI of the AARE APDU is expressed using the ACSE abstract syntax of this Protocol Specification. This abstract syntax must be included as the value of a presentation context definition parameter selected by the acceptor on the A-ASSOCIATE response primitive.
 - b) User information (if any) from the A-ASSOCIATE response primitive is included in the AARE APDU and is expressed using one or more presentation contexts selected by the acceptor on the A-ASSOCIATE response primitive.

8.2 Normal release of an association (normal mode)

The normal release procedure uses the P-RELEASE service. The normal release of an association takes place simultaneously with the normal release of the underlying presentation-connection.

8.2.1 Use of P-RELEASE request and indication parameters

The User Data parameter of the P-RELEASE request and indication primitives is referenced by the ACPM.

- *For both the P-RELEASE request and indication primitives:* The User Data parameter is used to carry the RLRQ APDU as specified below:
 - a) The APCI of the RLRQ APDU is expressed using the ACSE abstract syntax of this Protocol Specification. This abstract syntax must be one of the available presentation contexts.
 - b) User information (if any) from the A-RELEASE request primitive is included in the RLRQ APDU and is expressed using one or more available presentation contexts.

8.2.2 Use of P-RELEASE response and confirm parameters

The Result and User Data parameters of the P-RELEASE response and confirm primitives are referenced by the ACPM.

8.2.2.1 Result

- *For the P-RELEASE response primitive:* The Result parameter is set to the value of the Result parameter of the A-RELEASE response primitive (i.e. “affirmative” or “negative”). This value indicates to the presentation service-provider whether the underlying presentation-connection is to be released or if it is to be continued.
- *For the P-RELEASE confirm primitive:* The value of the Result parameter on the A-ASSOCIATE confirm primitive is set to the value of the Result parameter. This value indicates to the requesting ACPM whether the association is released or if it continues.

8.2.2.2 User Data

- *For both the P-RELEASE response and confirm primitives:* The User Data parameter is used to carry the RLRE APDU as specified below:
 - a) The APCI of the RLRE APDU is expressed using the ACSE abstract syntax of this Protocol Specification. This abstract syntax must be one of the available presentation contexts.
 - b) User information (if any) from the A-RELEASE response primitive is included in the RLRE APDU and is expressed using one or more available presentation contexts.

8.3 Abnormal release of an association (normal mode)

The abnormal release procedure uses the P-U-ABORT and P-P-ABORT services. The abnormal release of an association takes place simultaneously with the abnormal release of the underlying presentation-connection.

8.3.1 Use of P-U-ABORT request and indication parameters

The User Data parameter of the P-U-ABORT request and indication primitives is referenced⁸⁾ by the ACPM.

- *For both the P-U-ABORT request and indication primitives:* The User Data parameter is used to carry the ABRT APDU as specified below:
 - a) The APCI of the ABRT APDU is expressed using the ACSE abstract syntax of this Protocol Specification. This abstract syntax must be one of the available presentation contexts.
 - b) User information (if any) from the A-ABORT request primitive is expressed using one or more available presentation contexts.

8.3.2 Use of P-P-ABORT indication parameter

The Reason parameter of the provider-initiated P-P-ABORT indication primitive is mapped directly to the corresponding parameter of the A-P-ABORT indication.

8.4 Association establishment (X.410-1984 mode)

The association establishment procedure uses the P-CONNECT service.

8.4.1 Directly mapped parameters

The following parameters are not referenced by the ACPM and are mapped directly onto corresponding parameters of the A-ASSOCIATE primitives:

- a) User data⁹⁾;
- b) Calling Presentation Address;
- c) Called Presentation Address;
- d) Responding Presentation Address;
- e) Quality of Service;
- f) Session Requirements;
- g) Initial Synchronization Point Serial Number;
- h) Initial Assignment of Tokens; and
- i) Session-connection identifier.

8.4.2 Use of other P-CONNECT request and indication parameters

The Mode parameter of the P-CONNECT request and indication primitives is referenced by the ACPM.

- *For the P-CONNECT request primitive:* The Mode parameter is set to the value of the Mode parameter of the A-ASSOCIATE request primitive. For the X.410-1984 mode of ACSE operation, this parameter has the value of "X.410-1984". This indicates to the presentation-service that it is to operate in the X.410-1984 mode for this presentation-connection.
- *For the P-CONNECT indication primitive:* This parameter has the value of "X.410-1984" for the X.410-1984 mode of ACSE operation. This value indicates that the accepting ACPM is to operate in the X.410-1984 mode for this association. The Mode parameter of the A-ASSOCIATE indication primitive is set to the value of "X.410-1984."

8.4.3 Use of other P-CONNECT response and confirm parameters

The Result parameter of the P-CONNECT response and confirm primitives is used by the ACPM when operating in the X.410-1984 mode.

- *For the P-CONNECT response primitive:* The value of the Result parameter is mapped from the Result parameter of the A-ASSOCIATE Result parameter as shown in Table 9.

⁸⁾ If an association is supported by Version 1 of the session-protocol (see ITU-T Rec. X.225 | ISO/IEC 8327-1), the User Data parameter is not referenced by the ACPM (because of length constraints) and is mapped directly onto the User Information parameter of the A-ABORT primitives (see 7.3.3.1).

⁹⁾ User Data is mapped directly onto the A-ASSOCIATE User Information parameter. No explicit presentation context is available for it.

- For the P-CONNECT confirm primitive: The Result and Result Source parameters of the A-ASSOCIATE confirm primitive are mapped from the Result parameter as shown in Table 10.

Table 9 – Mapping ACSE's result (X.410-1984 mode)

A-ASSOCIATE rsp [from]	P-CONNECT rsp [to]
accepted	acceptance
rejected (permanent)	user-rejection
rejected (transient)	user-rejection

Table 10 – Mapping Presentation's result (X.410-1984 mode)

P-CONNECTcnf [from]	A-ASSOCIATE cnf [to]	A-ASSOCIATE cnf [to]
acceptance	accepted	ACSE service user
user-rejection	rejected (permanent)	ACSE service-user
provider-rejection	rejected (permanent)	presentation service provider

8.5 Normal release of an association (X.410-1984 mode)

The normal release procedure uses the P-RELEASE service. The following parameters are not referenced by the ACPM and are mapped directly onto corresponding parameters of the A-RELEASE primitives:

- Result; and
- User Data.

8.6 Abnormal release of an association (X.410-1984 mode)

The abnormal release procedure uses the P-U-ABORT and P-P-ABORT services.

8.6.1 Use of P-U-ABORT request and indication parameters

- For both the P-U-ABORT request and indication primitives: The User Data parameter is not referenced by the ACPM and is mapped directly onto the User Information parameter of the corresponding A-ABORT primitives.

8.6.2 Use of P-P-ABORT indication parameter

- For the P-P-ABORT indication primitive: The Reason parameter is not referenced by the ACPM and is mapped directly onto the corresponding parameter of the A-P-ABORT indication primitive.

9 Structure and encoding of ACSE APDUs

9.1 Abstract syntax of the ACSE APDUs

The abstract syntax of each of the ACSE APDUs is specified in this clause using ASN.1 (see CCITT Rec. X.208 and ISO/IEC 8824:1990).

```
ACSE-1 { joint-iso-itu-t association-control(2) modules(0) apdus(0) version1(1) }
-- ACSE-1 refers to ACSE version 1
```

DEFINITIONS ::=

BEGIN

EXPORTS

acse-as-id, ACSE-apdu,
aCSE-id, Application-context-name,
AP-title, AE-qualifier,
AE-title, AP-invocation-identifier
AE-invocation-identifier,
Mechanism-name, Authentication-value;

-- The data types Name and RelativeDistinguishedName are imported from ISO/IEC9594-2.
-- object identifier assignments.

IMPORTS Name, RelativeDistinguishedName
FROM InformationFramework
{ joint-iso-ccitt ds(5) modules(1) informationFramework(1)
};

-- The following data type may be used to reference the abstract syntax of the ACSE APDUs.

acse-as-id OBJECT IDENTIFIER ::= { joint-iso-itu-t association-control(2) abstract-syntax(1) apdus(0) version1(1) }

-- The following data type may be used to identify the Association Control ASE.

aCSE-id OBJECT IDENTIFIER ::= { joint-iso-itu-t association-control(2) as-id(3) acse-ase(1) version(1) }

-- top level CHOICE

ACSE-apdu ::= CHOICE

{ aarq AARQ-apdu,
aare AARE-apdu,
rlrq RLRQ-apdu,
rlre RLRE-apdu,
abrt ABRT-apdu
}

AARQ-apdu ::= [APPLICATION 0] IMPLICIT SEQUENCE

protocol-version	[0]	IMPLICIT BIT STRING { version1 (0) } DEFAULT { version1 },
application-context-name called-AP-title	[1] [2]	Application-context-name, AP-title
called-AE-qualifier	[3]	OPTIONAL, AE-qualifier
called-AP-invocation-identifier	[4]	OPTIONAL, AP-invocation-identifier
called-AE-invocation-identifier	[5]	OPTIONAL, AE-invocation-identifier
calling-AP-title	[6]	OPTIONAL, AP-title
calling-AE-qualifier	[7]	OPTIONAL, AE-qualifier
calling-AP-invocation-identifier	[8]	OPTIONAL, AP-invocation-identifier
calling-AE-invocation-identifier	[9]	OPTIONAL, AE-invocation-identifier

-- The following field shall not be present if only the Kernel is used.

sender-acse-requirements [10] IMPLICIT ACSE-requirements
OPTIONAL,

-- The following field shall only be present if the Authentication functional unit is selected.

mechanism-name [11] IMPLICIT Mechanism-name
OPTIONAL,

-- The following field shall only be present if the Authentication functional unit is selected.

calling-authentication-value [12] EXPLICIT Authentication-value
OPTIONAL,

-- The following field shall only be present if the Application Context Negotiation functional unit is selected

application-context-name-list	[13]	IMPLICIT Application-context-name-list
		OPTIONAL,
implementation-information	[29]	IMPLICIT Implementation-data
		OPTIONAL,
user-information	[30]	IMPLICIT Association-information
		OPTIONAL
}		
AARE-apdu ::= [APPLICATION 1] IMPLICIT SEQUENCE		
{ protocol-version	[0]	IMPLICIT BIT STRING
		{ version1 (0) }
		DEFAULT { version1 },
application-context-name	[1]	Application-context-name,
result	[2]	Associate-result,
result-source-diagnostic	[3]	Associate-source-diagnostic,
responding-AP-title	[4]	AP-title
		OPTIONAL,
responding-AE-qualifier	[5]	AE-qualifier
		OPTIONAL,
responding-AP-invocation-identifier	[6]	AP-invocation-identifier
		OPTIONAL,
responding-AE-invocation-identifier	[7]	AE-invocation-identifier
		OPTIONAL,
-- <i>The following field shall not be present if only the Kernel is used.</i>		
responder-acse-requirements	[8]	IMPLICIT ACSE-requirements
		OPTIONAL,
-- <i>The following field shall only be present if the Authentication functional unit is selected.</i>		
mechanism-name	[9]	IMPLICIT Mechanism-name
		OPTIONAL,
-- <i>The following field shall only be present if the Authentication functional unit is selected.</i>		
responding-authentication-value	[10]	EXPLICIT Authentication-value
		OPTIONAL,
-- <i>The following field shall only be present if the Application Context Negotiation functional unit is selected</i>		
application-context-name-list	[11]	IMPLICIT Application-context-name-list
		OPTIONAL,
implementation-information	[29]	IMPLICIT Implementation-data
		OPTIONAL,
user-information	[30]	IMPLICIT Association-information
		OPTIONAL
}		
RLRQ-apdu ::= [APPLICATION 2] IMPLICIT SEQUENCE		
{ reason	[0]	IMPLICIT Release-request-reason
		OPTIONAL,
user-information	[30]	IMPLICIT Association-information
		OPTIONAL
}		
RLRE-apdu ::= [APPLICATION 3] IMPLICIT SEQUENCE		
{ reason	[0]	IMPLICIT Release-response-reason
		OPTIONAL,
user-information	[30]	IMPLICIT Association-information
		OPTIONAL
}		
ABRT-apdu ::= [APPLICATION 4] IMPLICIT SEQUENCE		
{ abort-source	[0]	IMPLICIT ABRT-source,
-- <i>The following field shall not be present if only the Kernel is used.</i>		
abort-diagnostic	[1]	IMPLICIT ABRT-diagnostic
		OPTIONAL,
user-information	[30]	IMPLICIT Association-information
		OPTIONAL
}		
ABRT-diagnostic ::= ENUMERATED		
{ no-reason-given (1),		
protocol-error (2),		
authentication-mechanism-name-not-recognized (3),		
authentication-mechanism-name-required (4),		
authentication-failure (5),		
authentication-required (6)		
}		
ABRT-source ::= INTEGER		
{ acse-service-user	(0),	
acse-service-provider	(1)	
}		

ACSE-requirements ::= BIT STRING
 { authentication (0), application-context-negotiation(1) }

Application-context-name-list ::= SEQUENCE OF Application-context-name

Application-context-name ::= OBJECT IDENTIFIER

-- ***** Application-entity title productions follow (not in alphabetical order)*****

AP-title ::= CHOICE { AP-title-form1, AP-title-form2 }

AE-qualifier ::= CHOICE { AE-qualifier-form1, AE-qualifier-form2 }

-- When both AP-title and AE-qualifier data values are present in an AARQ or AARE APDU, both must have
 -- the same form to allow the construction of an AE-title as discussed in CCITT Rec. X.665 | ISO/IEC 9834-6.

AP-title-form1 ::= Name

-- The value assigned to AP-title-form1 is The Directory Name of an application-process title.

AE-qualifier-form1 ::= RelativeDistinguishedName

-- The value assigned to AE-qualifier-form1 is the relative distinguished name of a particular
 -- application-entity of the application-process identified by AP-title-form1.

AP-title-form2 ::= OBJECT IDENTIFIER

AE-qualifier-form2 ::= INTEGER

-- As defined in CCITT Rec. X.650 | ISO 7498-3, an application-entity title is composed of an
 -- application-process title and an application-entity qualifier. The ACSE protocol provides for the transfer of
 -- an application-entity title value by the transfer of its component values. However, the following data type is
 -- provided for International Standards that reference a single syntactic structure for AE titles.

AE-title ::= CHOICE { AE-title-form1, AE-title-form2 }

AE-title-form1 ::= Name

-- For access to The Directory (ITU-T Rec. X.500-Series | ISO/IEC 9594), an AE title
 -- has AE-title-form1. This value can be constructed from AP-title-form1 and AE-qualifier-form1 values
 -- contained in an AARQ or AARE APDU. A discussion of forming an AE-title-form1 from AP-title-form1 and
 -- AE-qualifier-form1 may be found in CCITT Rec. X.665 | ISO/IEC 9834-6.

AE-title-form2 ::= OBJECT IDENTIFIER

-- A discussion of forming an AE-title-form2 from AP-title-form2 and AE-qualifier-form2 may be found in
 -- CCITT Rec. X.665 | ISO/IEC 9834-6.

AE-invocation-identifier ::= INTEGER

AP-invocation-identifier ::= INTEGER

-- **** End of Application-entity title productions****

Associate-result ::= INTEGER

{ accepted (0),
 rejected-permanent (1),
 rejected-transient (2)
 }

Associate-source-diagnostic ::= CHOICE

{ acse-service-user [1] INTEGER
 { null (0),
 no-reason-given (1),
 application-context-name-not-supported (2),
 calling-AP-title-not-recognized (3),
 calling-AP-invocation-identifier-not-recognized (4),
 calling-AE-qualifier-not-recognized (5),
 calling-AE-invocation-identifier-not-recognized (6),
 called-AP-title-not-recognized (7),
 called-AP-invocation-identifier-not-recognized (8),
 called-AE-qualifier-not-recognized (9),
 called-AE-invocation-identifier-not-recognized (10),
 authentication-mechanism-name-not-recognized (11),

```

authentication-mechanism-name-required (12),
authentication-failure (13),
authentication-required (14)
},
acse-service-provider [2] INTEGER
{ null (0),
  no-reason-given (1),
  no-common-acse-version (2)
}
}

```

Association-information ::= SEQUENCE OF EXTERNAL

Authentication-value ::= CHOICE

```

{ charstring      [0] IMPLICIT GraphicString,
  bitstring       [1] IMPLICIT BIT STRING,
  external        [2] IMPLICIT EXTERNAL,
  other           [3] IMPLICIT SEQUENCE {
                        other-mechanism-name      Mechanism-name,
                        other-mechanism-value      ANY DEFINED BY
                                                    other-mechanism-name
                      }
}

```

-- The abstract syntax of authentication-value is determined by the authentication-mechanism used during association establishment. The authentication-mechanism is either explicitly denoted by the OBJECT IDENTIFIER value for mechanism-name, or it is known implicitly by prior agreement between the communicating partners. If "other" is chosen, then "mechanism-name" must be present in accordance with CCITT Rec. X.208 and ISO/IEC 8824:1990. If the value "mechanism-name" occurs in the AARQ-apdu or the AARE-apdu, then that value must be the same as the value for "other-mechanism-name"

Implementation-data ::= GraphicString

-- The following field shall be present if authentication-value is of type ANY DEFINED BY.

Mechanism-name ::= OBJECT IDENTIFIER

Release-request-reason ::= INTEGER

```

{ normal      (0),
  urgent      (1),
  user-defined (30)
}

```

Release-response-reason ::= INTEGER

```

{ normal      (0),
  not-finished (1),
  user-defined (30)
}

```

END

9.2 Encoding rules used to reference the transfer syntax

The set of encoding rules named

```
{ joint-iso-itu-t asn1(1) basic-encoding(1) }
```

and specified in ITU-T Rec. X.690 | ISO/IEC 8825-1 is used to reference the transfer syntax of the ACSE APDUs in the context of the ACSE abstract syntax definition.

10 Conformance

A system claiming to implement the procedures specified in this Protocol Specification shall comply with the requirements in 10.1 through 10.3.

Two modes of conformance are recognized:

- a) normal mode; and
- b) X.410-1984 mode.

The X.410-1984 mode exists to allow claims of conformance to allow compatibility with message handling systems implementing the protocol specified in Recommendation X.410-1984.

10.1 Statement requirements

The following shall be stated by the implementor:

- a) whether the system is capable of acting in the role of association-initiator, or association-responder, or both;
- b) that the system supports Version 1 of this protocol; and
- c) whether the system implements:
 - 1) the normal mode of ACSE protocol;
 - 2) the X.410-1984 mode of ACSE protocol to support a message handling system; or
 - 3) both the normal mode and the X.410-1984 mode for the reason given in item 2) above.

10.2 Static requirements

The use of the Association Control Service Element is required for an application-entity to meet the minimum requirements for establishing and releasing communication with a peer entity.

10.2.1 Normal mode

If the normal mode is implemented, the system shall:

- a) act in the role of an association-initiator (by sending an AARQ APDU), or in the role of an association-acceptor (by responding properly to an AARQ APDU with an appropriate AARE APDU), or act in both roles; and
- b) support (as a minimum) that encoding which results from applying the basic ASN.1 encoding rules to the ASN.1 specified in clause 9 for the purpose of exchanging ACSE APCI.

10.2.2 X.410-1984 mode

If the X.410-1984 mode is implemented, the system shall act in the role of an initiator, or acceptor, or both.

10.3 Dynamic requirements

10.3.1 Normal mode

If the normal mode is implemented, the system shall:

- a) follow all the procedures specified in clause 7 (including the rules for extensibility) and Annex A; and
- b) support the mapping onto the Presentation Service defined in 8.1 to 8.3.

The requesting AE may choose to send either form 1 or form 2 for AP title and AE qualifier. The accepting AE may respond with either form. Thus, both the requesting and responding AE must be capable of receiving both forms.

10.3.2 X.410-1984 mode

If the X.410-1984 mode is implemented, the system shall support the direct mapping of parameters of presentation-service primitives onto the ACSE primitives as specified in 8.4 to 8.6.

11 Precedence

The aspects of the protocol for ACSE are specified in several clauses in this Protocol Specification. This clause states the rules of precedence for possible situations where the same aspect may be specified in more than one place in an apparently inconsistent manner. The relevant aspects of protocol specification covered are:

- a) sequencing rules;
- b) mapping to the presentation-service; and
- c) structure and encoding of ACSE APDUs.

Annex A and clause 7 of this Recommendation | International Standard specify the elements of procedure which govern the behaviour of the ACPM. Annex A takes precedence over any other clause in this Protocol Specification which may state or imply apparently inconsistent sequencing rules.

How the presentation service primitives are used by the ACPM is specified in clause 8 which takes precedence over any other part of this Protocol Specification which may state or imply mapping to the presentation-service.

The structure and encoding of ACSE APDUs are specified in clause 9 which takes precedence over any other part of this Protocol Specification which may state or imply structure and encoding of ACSE APDUs.

NOTE – Any person encountering an inaccuracy or ambiguity in this Protocol Specification is requested to notify their National Body of ISO/IEC or the Telecommunication Standardization Bureau of the ITU without delay in order that the matter may be investigated and appropriate action taken.

12 Registration requirements

This Protocol Specification identifies the requirement to register three types of information objects:

- application titles;
- application contexts; and
- authentication-mechanisms.

Each is discussed below.

No International Registration Authority is currently planned for the registration of any of the above objects. The assignment of a name to any of these objects shall be in accordance with the general provisions of ITU-T Rec. X.660 | ISO/IEC 9834-1, except as specified below.

In accordance with CCITT Rec. X.660 | ISO/IEC 9834-1, an organization that wishes to assign names to objects shall find an appropriate superior of the naming tree. The superior assigns an arc of the naming tree to the organization. The organization can then assign names below that arc.

NOTE – Appropriate superiors in the registration tree include ISO/IEC national bodies, organizations with International Code Designators assigned in accordance with ISO/IEC 6523, as well as ITU-T network administrations, and recognized operating agencies (ROAs).

12.1 Application titles

The application titles requiring registration are application-process title, application-entity qualifier, and application-entity title. The registration requirements for these information objects are contained in ISO/IEC 9545, clause 9. CCITT Rec. X.665 | ISO/IEC 9834-6 specifies both the relationship between these information objects and the procedures to register them.

12.2 Application context

The registration requirements for an application context is contained in ISO/IEC 9545, clause 9. CCITT Rec. X.660 | ISO/IEC 9834-1 specifies the procedures to register it.

12.3 Authentication-mechanism

An authentication-mechanism may be specified as part of an ITU-T Recommendation or ISO/IEC International Standard. For example, Annex B includes an authentication-mechanism based on AE title and password. Such an authentication-mechanism is, in effect, specified and registered within this Protocol Specification.

An authentication-mechanism may also be specified outside of ITU-T Recommendations and ISO/IEC International Standards. In this situation, CCITT Rec. X.660 | ISO/IEC 9834-1 specifies the procedures to register such an authentication-mechanism.

Annex A

ACPM state table

(This annex forms an integral part of this Recommendation | International Standard)

A.1 General

This annex defines a single Association Control Protocol Machine (ACPM) in terms of a state table. The state table shows the interrelationship between the state of an ACPM, the incoming events that occur in the protocol, the actions taken, and, finally, the resultant state of the ACPM.

The ACPM state table does not constitute a formal definition of the ACPM. It is included to provide a more precise specification of the elements of procedure defined in clause 7.

This annex contains the following tables:

- a) Table A.1 specifies the abbreviated name, source, and name/description of each incoming event. The sources are:
 - 1) ACSE service-user (AC-user);
 - 2) Peer ACPM (AC-peer); and
 - 3) presentation service-provider (PS-provider).
- b) Table A.2 specifies the abbreviated name of each state.
- c) Table A.3 specifies the abbreviated name, target, and name/description of each outgoing event. The targets are:
 - 1) ACSE service-user (AC-user); and
 - 2) peer ACPM (AC-peer).
- d) Table A.4 specifies the predicates.
- e) Table A.5 specifies the ACPM state table using the abbreviations of the above tables.

A.2 Conventions

The intersection of an incoming event (row) and a state (column) forms a cell.

In the state table, a blank cell represents the combination of an incoming event and a state that is not defined for the ACPM (see A.3.1).

A non-blank cell represents an incoming event and state that is defined for the ACPM. Such a cell contains one or more action lists. An action list may be either mandatory or conditional. If a cell contains a mandatory action list, it is the only action list in the cell.

A mandatory action list contains:

- a) an outgoing event; and
- b) a resultant state.

A conditional action list contains:

- a) a predicate expression comprising predicates and Boolean operators (^ represents the Boolean NOT); and
- b) a mandatory action list (this mandatory action list is used only if the predicate expression is true).

A.3 Actions to be taken by the ACPM

The ACPM state table defines the action to be taken by the ACPM in terms of an outgoing event and the resultant state of the ACPM.