
**Information technology — Database
languages SQL —**

**Part 14:
XML-Related Specifications (SQL/
XML)**

*Technologies de l'information — Langages de base de données SQL —
Partie 14: Spécifications relatives au XML (SQL/XML)*

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023



IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents	Page
Foreword.....	ix
Introduction.....	xi
1 Scope.....	1
2 Normative references.....	2
3 Terms and definitions.....	4
4 Concepts.....	14
4.1 Notations and conventions.....	14
4.1.1 Notations.....	14
4.1.2 XML-related notations.....	14
4.2 Data types.....	15
4.2.1 Naming of predefined types.....	15
4.2.2 Data type terminology.....	16
4.3 XML.....	16
4.3.1 Introduction.....	16
4.3.2 XML types.....	16
4.3.3 Characteristics of XML values.....	17
4.3.4 XML comparison and assignment.....	18
4.3.5 Operations involving XML values.....	18
4.3.6 Registered XML schemas.....	20
4.4 Data conversions.....	21
4.5 Data analysis operations.....	22
4.5.1 Aggregate functions.....	22
4.6 SQL-invoked routines.....	22
4.6.1 Routine descriptors.....	22
4.7 SQL-statements.....	23
4.7.1 SQL-statements classified by function.....	23
4.7.1.1 SQL-session statements.....	23
4.8 Basic security model.....	23
4.8.1 Privileges.....	23
4.9 SQL-sessions.....	23
4.9.1 SQL-session properties.....	23
4.10 XML namespaces.....	24
4.11 Overview of mappings.....	24
4.11.1 Introduction to mappings.....	24
4.11.2 Mapping SQL character sets to Unicode.....	25
4.11.3 Mapping Unicode to SQL character sets.....	25
4.11.4 Mapping SQL <identifier>s to XML.....	25
4.11.5 Mapping XML names to SQL.....	25

4.11.6	Mapping SQL data types to XML	26
4.11.7	Mapping values of SQL data types to XML	27
4.11.8	Mapping XQuery atomic values to SQL values	28
4.11.9	Visibility of columns, tables, and schemas in mappings from SQL to XML	29
4.11.10	Mapping an SQL table to XML	29
4.11.11	Mapping an SQL schema to XML	30
4.11.12	Mapping an SQL catalog to XML	30
5	Lexical elements	32
5.1	<token> and <separator>	32
5.2	<literal>	34
5.3	Names and identifiers	35
6	Scalar expressions	36
6.1	<data type>	36
6.2	<field definition>	39
6.3	<value expression primary>	40
6.4	<value specification> and <target specification>	41
6.5	<case expression>	42
6.6	<cast specification>	43
6.7	<XML cast specification>	46
6.8	<value expression>	54
6.9	<string value function>	55
6.10	<XML value expression>	60
6.11	<XML value function>	61
6.12	<XML comment>	62
6.13	<XML concatenation>	64
6.14	<XML document>	66
6.15	<XML element>	68
6.16	<XML forest>	72
6.17	<XML parse>	75
6.18	<XML PI>	77
6.19	<XML query>	80
6.20	<XML text>	86
6.21	<XML validate>	88
7	Query expressions	93
7.1	<table reference>	93
7.2	<query expression>	97
8	Predicates	98
8.1	<predicate>	98
8.2	<XML content predicate>	99
8.3	<XML document predicate>	100
8.4	<XML exists predicate>	102
8.5	<XML valid predicate>	103
9	Mappings	108
9.1	Mapping SQL <identifier>s to XML names	108
9.2	Mapping a multi-part SQL name to an XML name	111
9.3	Mapping XML names to SQL <identifier>s	113

9.4	Mapping an SQL data type to an XML name.	115
9.5	Mapping SQL data types to XML schema data types.	120
9.6	Mapping an SQL data type to a named XML schema data type.	139
9.7	Mapping a collection of SQL data types to XML schema data types.	142
9.8	Mapping values of SQL data types to values of XML schema data types.	144
9.9	Mapping an SQL table to XML schema data types.	150
9.10	Mapping an SQL table to an XML element or a sequence of XML elements.	154
9.11	Mapping an SQL table to XML and an XML schema document.	158
9.12	Mapping an SQL schema to XML schema data types.	163
9.13	Mapping an SQL schema to an XML element.	166
9.14	Mapping an SQL schema to an XML document and an XML schema document.	169
9.15	Mapping an SQL catalog to XML schema data types.	174
9.16	Mapping an SQL catalog to an XML element.	176
9.17	Mapping an SQL catalog to an XML document and an XML schema document.	179
10	Additional common rules.	184
10.1	Retrieval assignment.	184
10.2	Store assignment.	186
10.3	Result of data type combinations.	188
10.4	Type precedence list determination.	190
10.5	Type name determination.	191
10.6	Determination of identical values.	192
10.7	Determination of equivalent XML values.	193
10.8	Equality operations.	196
10.9	Grouping operations.	197
10.10	Multiset element grouping operations.	198
10.11	Ordering operations.	199
10.12	Potential sources of non-determinism.	200
10.13	Invoking an SQL-invoked routine.	202
10.14	Determination of namespace URI.	205
10.15	Construction of an XML element.	207
10.16	Concatenation of two XML values.	210
10.17	Serialization of an XML value.	211
10.18	Parsing a string as an XML value.	216
10.19	Removing XQuery document nodes from an XQuery sequence.	220
10.20	Constructing a copy of an XML value.	222
10.21	Constructing an unvalidated XQuery document node.	223
10.22	Creation of an XQuery expression context.	224
10.23	Determination of an XQuery formal type notation.	227
10.24	Validating an XQuery document or element node.	230
11	Additional common elements.	232
11.1	<aggregate function>.	232
11.2	<XML lexically scoped options>.	235
11.3	<XML returning clause>.	237
11.4	<XML passing mechanism>.	238
11.5	<XML valid according to clause>.	239
12	Schema definition and manipulation.	242

12.1	<column definition>.....	242
12.2	<check constraint definition>.....	244
12.3	<alter column data type clause>.....	245
12.4	<view definition>.....	246
12.5	<assertion definition>.....	248
12.6	<user-defined type definition>.....	249
12.7	<attribute definition>.....	250
12.8	<SQL-invoked routine>.....	251
12.9	<user-defined cast definition>.....	255
13	SQL-client modules.....	256
13.1	<externally-invoked procedure>.....	256
13.2	<SQL procedure statement>.....	258
13.3	Data type correspondences.....	259
14	Data manipulation.....	261
14.1	<fetch statement>.....	261
14.2	<select statement: single row>.....	263
14.3	<delete statement: searched>.....	265
14.4	<insert statement>.....	266
14.5	<merge statement>.....	267
14.6	<update statement: positioned>.....	268
14.7	<update statement: searched>.....	269
15	Control statements.....	270
15.1	<compound statement>.....	270
15.2	<assignment statement>.....	272
16	Session management.....	274
16.1	<set XML option statement>.....	274
17	Dynamic SQL.....	275
17.1	Description of SQL descriptor areas.....	275
17.2	<input using clause>.....	276
17.3	<output using clause>.....	277
17.4	<prepare statement>.....	278
18	Embedded SQL.....	279
18.1	<embedded SQL host program>.....	279
18.2	<embedded SQL Ada program>.....	284
18.3	<embedded SQL C program>.....	287
18.4	<embedded SQL COBOL program>.....	291
18.5	<embedded SQL Fortran program>.....	294
18.6	<embedded SQL Pascal program>.....	297
18.7	<embedded SQL PL/I program>.....	300
19	Call-Level Interface specifications.....	304
19.1	SQL/CLI data type correspondences.....	304
20	Diagnostics management.....	306
20.1	<get diagnostics statement>.....	306
21	Information Schema.....	307
21.1	Information Schema digital artifact.....	307

21.2	NCNAME domain.....	307
21.3	URI domain.....	308
21.4	ATTRIBUTES view.....	309
21.5	COLUMNS view.....	310
21.6	DOMAINS view.....	311
21.7	ELEMENT_TYPES view.....	312
21.8	FIELDS view.....	313
21.9	METHOD_SPECIFICATION_PARAMETERS view.....	314
21.10	METHOD_SPECIFICATIONS view.....	315
21.11	PARAMETERS view.....	316
21.12	ROUTINES view.....	318
21.13	XML_SCHEMA_ELEMENTS view.....	320
21.14	XML_SCHEMA_NAMESPACES view.....	321
21.15	XML_SCHEMAS view.....	322
21.16	Short name views.....	323
22	Definition Schema.....	333
22.1	Definition Schema digital artifact.....	333
22.2	DATA_TYPE_DESCRIPTOR base table.....	333
22.3	PARAMETERS base table.....	339
22.4	ROUTINES base table.....	341
22.5	USAGE_PRIVILEGES base table.....	343
22.6	XML_SCHEMA_ELEMENTS base table.....	344
22.7	XML_SCHEMA_NAMESPACES base table.....	346
22.8	XML_SCHEMAS base table.....	347
23	SQL/XML XML schema.....	349
24	Status codes.....	353
24.1	SQLSTATE.....	353
25	Conformance.....	355
25.1	Claims of conformance to SQL/XML.....	355
25.2	Additional conformance requirements for SQL/XML.....	356
25.3	Implied feature relationships of SQL/XML.....	357
Annex A	(informative) SQL conformance summary.....	365
Annex B	(informative) Implementation-defined elements.....	402
Annex C	(informative) Implementation-dependent elements.....	417
Annex D	(informative) SQL optional feature taxonomy.....	419
Annex E	(informative) Deprecated features.....	425
Annex F	(informative) Incompatibilities with ISO/IEC 9075:2016.....	426
Annex G	(informative) Defect Reports not addressed in this document.....	427
Bibliography	428
Index	429

Tables

Table	Page	
1	Permanently registered XML schemas.	21
2	XML namespace prefixes and their URIs.	24
3	Constraining facets of XML schema integer types.	126
4	XQuery node properties.	194
5	Data type correspondences for Ada.	259
6	Data type correspondences for C.	259
7	Data type correspondences for COBOL.	259
8	Data type correspondences for Fortran.	259
9	Data type correspondences for M.	260
10	Data type correspondences for Pascal.	260
11	Data type correspondences for PL/I.	260
12	Codes used for SQL data types in Dynamic SQL.	275
13	SQL/CLI data type correspondences for Ada.	304
14	SQL/CLI data type correspondences for C.	304
15	SQL/CLI data type correspondences for COBOL.	304
16	SQL/CLI data type correspondences for Fortran.	305
17	SQL/CLI data type correspondences for M.	305
18	SQL/CLI data type correspondences for Pascal.	305
19	SQL/CLI data type correspondences for PL/I.	305
20	SQL-statement codes.	306
21	SQLSTATE class and subclass codes.	353
22	Implied feature relationships of SQL/XML.	357
A.1	Feature definitions outside of Conformance Rules.	365
D.1	Feature taxonomy for optional features.	419

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC have not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 32, *Data management and interchange*.

This sixth edition cancels and replaces the fifth edition (ISO/IEC 9075-14:2016), which has been technically revised. It also incorporates the Technical Corrigenda ISO/IEC 9075-14:2016/Cor.1:2019 and ISO/IEC 9075-14:2016/Cor.2:2022.

The main changes are as follows:

- improve the presentation and accuracy of the summaries of implementation-defined and implementation-dependent aspects of this document;
- introduction of several digital artifacts;
- alignment with updated ISO house style and other guidelines for creating standards.

ISO/IEC 9075-14:2023(E)

This sixth edition of ISO/IEC 9075-14 is designed to be used in conjunction with the following editions of other parts of the ISO/IEC 9075 series, all published in 2023:

- ISO/IEC 9075-1, sixth edition;
- ISO/IEC 9075-2, sixth edition;
- ISO/IEC 9075-3, sixth edition;
- ISO/IEC 9075-4, seventh edition;
- ISO/IEC 9075-9, fifth edition;
- ISO/IEC 9075-10, fifth edition;
- ISO/IEC 9075-11, fifth edition;
- ISO/IEC 9075-13, fifth edition;
- ISO/IEC 9075-15, second edition;
- ISO/IEC 9075-16, first edition.

A list of all parts in the ISO/IEC 9075 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

Introduction

The organization of this document is as follows:

- 1) Clause 1, “Scope”, specifies the scope of this document.
- 2) Clause 2, “Normative references”, identifies additional standards that, through reference in this document, constitute provisions of this document.
- 3) Clause 3, “Terms and definitions”, defines the terms and definitions used in this document.
- 4) Clause 4, “Concepts”, presents concepts related to this document.
- 5) Clause 5, “Lexical elements”, defines the lexical elements of the language.
- 6) Clause 6, “Scalar expressions”, defines the elements of the language that produce scalar values.
- 7) Clause 7, “Query expressions”, defines the elements of the language that produce rows and tables of data.
- 8) Clause 8, “Predicates”, defines the predicates of the language.
- 9) Clause 9, “Mappings”, defines the ways in which certain SQL information can be mapped into XML and certain XML information can be mapped into SQL.
- 10) Clause 10, “Additional common rules”, specifies the rules for assignments that retrieve data from or store data into SQL-data, and formation rules for set operations.
- 11) Clause 11, “Additional common elements”, defines additional language elements that are used in various parts of the language.
- 12) Clause 12, “Schema definition and manipulation”, defines facilities for creating and managing a schema.
- 13) Clause 13, “SQL-client modules”, defines SQL-client modules and externally-invoked procedures.
- 14) Clause 14, “Data manipulation”, defines the data manipulation statements.
- 15) Clause 15, “Control statements”, defines the SQL-control statements.
- 16) Clause 16, “Session management”, defines the SQL-session management statements.
- 17) Clause 17, “Dynamic SQL”, defines the SQL dynamic statements.
- 18) Clause 18, “Embedded SQL”, defines the host language embeddings.
- 19) Clause 19, “Call-Level Interface specifications”,
- 20) Clause 20, “Diagnostics management”, defines the diagnostics management facilities.
- 21) Clause 21, “Information Schema”, defines viewed tables that contain schema information.
- 22) Clause 22, “Definition Schema”, defines base tables on which the viewed tables containing schema information depend.
- 23) Clause 23, “SQL/XML XML schema”, defines the content of an XML namespace that is used when SQL and XML are utilized together.
- 24) Clause 24, “Status codes”, defines values that identify the status of the execution of SQL-statements and the mechanisms by which those values are returned.
- 25) Clause 25, “Conformance”, specifies the way in which conformance to this document may be claimed.

- 26) [Annex A, “SQL conformance summary”](#), is an informative Annex. It summarizes the conformance requirements of the SQL language.
- 27) [Annex B, “Implementation-defined elements”](#), is an informative Annex. It lists those features for which the body of this document states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or other aspect is partly or wholly implementation-defined.
- 28) [Annex C, “Implementation-dependent elements”](#), is an informative Annex. It lists those features for which the body of this document states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or other aspect is partly or wholly implementation-dependent.
- 29) [Annex D, “SQL optional feature taxonomy”](#), is an informative Annex. It identifies the optional features of the SQL language specified in this document by an identifier and a short descriptive name. This taxonomy is used to specify conformance.
- 30) [Annex E, “Deprecated features”](#), is an informative Annex. It lists features that the responsible Technical Committee intends not to include in a future edition of this document.
- 31) [Annex F, “Incompatibilities with ISO/IEC 9075:2016”](#), is an informative Annex. It lists incompatibilities with the previous edition of this document.
- 32) [Annex G, “Defect Reports not addressed in this document”](#), is an informative Annex. It describes the Defect Reports that were known at the time of publication of this document. Each of these problems is a problem carried forward from the previous edition of the ISO/IEC 9075 series. No new problems have been created in the drafting of this edition of this document.

In the text of this document, in [Clause 5, “Lexical elements”](#) through [Clause 25, “Conformance”](#), Subclauses begin new pages. Any resulting blank space is not significant.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

Information technology — Database language SQL —

Part 14:

XML-Related Specifications (SQL/XML)

1 Scope

This document defines ways in which Database Language SQL can be used in conjunction with XML.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.^{1 2}

ISO/IEC 9075-1, *Information technology — Database languages — SQL — Part 1: Framework (SQL/Framework)*

ISO/IEC 9075-2, *Information technology — Database languages — SQL — Part 2: Foundation (SQL/Foundation)*

ISO/IEC 9075-3, *Information technology — Database languages — SQL — Part 3: Call-Level Interface (SQL/CLI)*

ISO/IEC 9075-4, *Information technology — Database languages — SQL — Part 4: Persistent Stored Modules (SQL/PSM)*

ISO/IEC 9075-11, *Information technology — Database languages — SQL — Part 11: Information and Definition Schemas (SQL/Schemata)*

W3C Canonical XML 1.1 *Canonical XML, W3C Recommendation*. Edited by: Boyer, John; Marcy, Glenn
2 May 2008

Available at: <https://www.w3.org/TR/xml-c14n>

W3C XML Information Set *XML Information Set, W3C Recommendation*. Edited by: Cowan, John; Tobin, Richard
4 February 2004

Available at: <https://www.w3.org/TR/xml-infoset>

W3C XML Namespaces *XML Namespaces is used to reference either Namespaces in XML 1.0 or Namespaces in XML 1.1 when there is no significant difference between the two for the purposes of a given citation*

W3C Namespaces in XML 1.0 *Namespaces in XML 1.0, W3C Recommendation*. Edited by: Bray, Tim, et al.
8 December 2009

Available at: <https://www.w3.org/TR/xml-names>

W3C Namespaces in XML 1.1 *Namespaces in XML 1.1, W3C Recommendation*. Edited by: Bray, Tim, et al.
16 August 2006

Available at: <https://www.w3.org/TR/xml-names11>

Internet Engineering Task Force (IETF) RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*. Edited by: Berners-Lee, T., Fielding, R., Masinter, L.
January 2005

Available at: <https://www.ietf.org/rfc/rfc3986.txt>

W3C XML Schema Part 1: Structures *XML Schema Part 1: Structures, W3C Recommendation*. Edited by: Thompson, Henry S et al.
28 October 2004

Available at: <https://www.w3.org/TR/xmlschema-1/>

W3C XML Schema Part 2: Datatypes *XML Schema Part 2: Datatypes, W3C Recommendation*. Edited by: Biron, Paul V.; Malhotra, Ashok
28 October 2004

Available at: <https://www.w3.org/TR/xmlschema-2/>

¹ XML Namespaces is used to reference either *Namespaces in XML 1.0* or *Namespaces in XML 1.1* when there is no significant difference between the two for the purposes of a given citation.

² XML is used to reference either *XML 1.0* or *XML 1.1* when there is no significant difference between the two for the purposes of a given citation.

W3C XSLT and XQuery Serialization 3.1 *XSLT and XQuery Serialization 3.1, W3C Recommendation*. Edited by: Coleman Andrew; Sperberg-McQueen, C M. 21 March 2017
Available at: <https://www.w3.org/TR/xslt-xquery-serialization-31/>

The Unicode Consortium. *The Unicode Standard (Information about the latest version of the Unicode standard can be found by using the "Latest Version" link on the "Enumerated Versions of The Unicode Standard" page.)* [online]. Mountain View, California, USA: The Unicode Consortium, Available at <https://www.unicode.org/versions/enumeratedversions.html>

W3C Unicode in XML and Other Markup Languages *Unicode in XML and Other Markup Languages, W3C Working Group Note*. Edited by: Phillips, Addison 13 July 2017
Available at: <https://www.w3.org/TR/unicode-xml/>

XML is used to reference either XML 1.0 or XML 1.1 when there is no significant difference between the two for the purposes of a given citation . [Place of publication unknown]:

W3C XML 1.0 *Extensible Markup Language (XML) Version 1.0, W3C Recommendation*. Edited by: Bray, Tim et al. 26 November 2008, revised 7 February 2013
Available at: <https://www.w3.org/TR/xml>

W3C XML 1.1 *Extensible Markup Language (XML) Version 1.1, W3C Recommendation*. Edited by: Bray, Tim et al. 16 August 2006, revised 29 September 2006
Available at: <https://www.w3.org/TR/xml11>

W3C XML Path Language (XPath) 3.1 *XML Path Language (XPath) 3.1, W3C Recommendation*. Edited by: Robie, J; Dyck, M; & Spiegel, J. 21 March 2017
Available at: <https://www.w3.org/TR/xpath-31/>

W3C XQuery 3.1: an XML Query Language *XQuery 3.1: an XML Query Language, W3C Recommendation*. Edited by: Robie, J; Dyck, M; & Spiegel, J. 21 March 2017
Available at: <https://www.w3.org/TR/xquery-31/>

W3C XQuery and XPath Data Model 3.1 *XQuery and XPath Data Model 3.1, W3C Recommendation*. Edited by: Walsh, N.; Snelson, J.; & Coleman, A. 21 March 2017
Available at: <https://www.w3.org/TR/xpath-datamodel/>

W3C XQuery and XPath Functions and Operators 3.1 *XQuery and XPath Functions and Operators 3.1, W3C Recommendation*. Edited by: Malhotra, Ashok et al. 21 March 2017
Available at: <https://www.w3.org/TR/xpath-functions/>

W3C XQuery 1.0 and XPath 2.0 Formal Semantics *XQuery 1.0 and XPath 2.0 Formal Semantics, W3C Recommendation*. Edited by: Draper, Denise, et al. 14 December 2010, revised 7 September 2015
Available at: <https://www.w3.org/TR/xquery-semantics/>

W3C XQuery Update Facility 1.0 *XQuery Update Facility 1.0, W3C Recommendation*. Edited by: Robie, Jonathan et al. 17 March 2011
Available at: <https://www.w3.org/TR/xquery-update-10/>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 9075-1, ISO/IEC 9075-2, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

DTD

XML 1.0 document type declaration (3.2) or *XML 1.1 document type declaration* (3.3)

3.2

XML 1.0 document type declaration

declaration that contains or points to markup declarations that provide a grammar for a class of documents as defined in *XML 1.0*

[SOURCE: *XML 1.0*, 2.8]

3.3

XML 1.1 document type declaration

declaration that contains or points to markup declarations that provide a grammar for a class of documents as defined in *XML 1.1*

[SOURCE: *XML 1.1*, 2.8]

3.4

XML document

XML 1.0 document (3.5) or *XML 1.1 document* (3.6)

3.5

XML 1.0 document

well-formed XML document, as defined in *XML 1.0*

[SOURCE: *XML 1.0*, 2.1]

3.6

XML 1.1 document

well-formed XML document, as defined in *XML 1.1*

[SOURCE: *XML 1.1*, 2.1]

3.7

annotation

annotation schema component, as defined in *XML Schema Part 1: Structures*

[SOURCE: *XML Schema Part 1: Structures*, 3.13]

3.8

facet

facet, as defined in *XML Schema Part 2: Datatypes*

[SOURCE: *XML Schema Part 2: Datatypes*, 2.4]

3.9

wildcard schema component

wildcard schema component, as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 3.10.2]

3.10

XML schema

XML Schema, as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 2.1]

3.11

all group content model

content model of an XML schema complex type described with **xs:all** as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 3.8]

3.12

canonical XML schema literal

canonical lexical representation for an XML schema type **xst**, as defined in XML Schema Part 2: Datatypes, based on Canonical XML 1.1

Note 1 to entry: There is a unique canonical XML schema literal for each value in the value space of **xst**.

[SOURCE: XML Schema Part 2: Datatypes, 2.3.1]

3.13

empty XQuery sequence

empty sequence, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.5]

3.14

global element declaration schema component

element declaration schema component of a global element declaration, as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 3.3.2]

3.15

metadata

data about data

Note 1 to entry: In this document, metadata is included in table descriptors, column descriptors, and so forth, as defined in ISO/IEC 9075-2

3.16

sequence content model

content model of an XML schema complex type described with **xs:sequence** as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 3.3.2]

3.17

SQL value space

set of all values for a particular SQL <data type>

3.18

URI

Uniform Resource Identifier as defined in RFC 3986

3.19

valid XML character

if Feature X211, “XML 1.1 support”, is supported, then a *valid XML 1.1 character* (3.21); otherwise, a *valid XML 1.0 character* (3.20)

3.20

valid XML 1.0 character

valid character as defined in XML 1.0, rule [2], “Char”

[SOURCE: XML 1.0, 2.2]

3.21

valid XML 1.1 character

valid character as defined in XML 1.1, rule [2], “Char”

[SOURCE: XML 1.1, 2.2]

3.22

XML attribute

XML 1.0 attribute (3.23) or *XML 1.1 attribute* (3.24)

3.23

XML 1.0 attribute

attribute, as defined in XML 1.0

[SOURCE: XML 1.0, 3.3]

3.24

XML 1.1 attribute

attribute, as defined in XML 1.1

[SOURCE: XML 1.1, 3.3]

3.25

XML attribute information item

attribute information item, as defined in XML Information Set

[SOURCE: XML Information Set, 2.3]

3.26

XML character information item

character information item, as defined in XML Information Set

[SOURCE: XML Information Set, 2.6]

3.27

XML declaration

XML 1.0 declaration (3.28) or *XML 1.1 declaration* (3.29)

3.28

XML 1.0 declaration

XMLDecl, as defined in XML 1.0

[SOURCE: XML 1.0, 2.8]

3.29

XML 1.1 declaration

XMLDecl, as defined in XML 1.1

[SOURCE: XML 1.1, 2.8]

3.30

XML document information item

document information item, as defined in XML Information Set

[SOURCE: XML Information Set, 2.1]

3.31

XML element

XML 1.0 element (3.32) or *XML 1.1 element* (3.33)

3.32

XML 1.0 element

element, as defined in XML 1.0

[SOURCE: XML 1.0, 3.2]

3.33

XML 1.1 element

element, as defined in XML 1.1

[SOURCE: XML 1.1, 3.2]

3.34

XML element information item

element information item, as defined in XML Information Set

[SOURCE: XML Information Set, 2.2]

3.35

XML information item

information item, as defined in XML Information Set

[SOURCE: XML Information Set, 2]

3.36

XML 1.0 Name

Name as defined by XML 1.0

[SOURCE: XML 1.0, 2.3]

3.37

XML 1.1 Name

Name as defined by XML 1.1

[SOURCE: XML 1.1, 2.3]

3.38

XML 1.0 NameChar

NameChar as defined by XML 1.0

[SOURCE: XML 1.0, 2.3]

3.39

XML 1.1 NameChar

NameChar as defined by XML 1.1

[SOURCE: XML 1.1, 2.3]

3.40

XML 1.1 NameStartChar

NameStartChar as defined by XML 1.1

[SOURCE: XML 1.1, 2.3]

3.41

XML namespace

XML 1.0 namespace (3.42) or *XML 1.1 namespace* (3.43)

3.42

XML 1.0 namespace

XML namespace, as defined in Namespaces in XML 1.0

[SOURCE: Namespaces in XML 1.0, 2]

3.43

XML 1.1 namespace

XML namespace, as defined in Namespaces in XML 1.1

[SOURCE: Namespaces in XML 1.1, 2]

3.44

XML namespace prefix

XML 1.0 namespace prefix (3.45) or *XML 1.1 namespace prefix* (3.46)

3.45

XML 1.0 namespace prefix

XML namespace prefix, as defined in Namespaces in XML 1.0

[SOURCE: Namespaces in XML 1.0, 3]

3.46

XML 1.1 namespace prefix

XML namespace prefix, as defined in Namespaces in XML 1.1

[SOURCE: Namespaces in XML 1.1, 3]

3.47

XML 1.0 NCName

NCName, as defined by rule [4] in Namespaces in XML 1.0

[SOURCE: Namespaces in XML 1.0, 3]

3.48

XML 1.1 NCName

NCName, as defined by rule [4] in Namespaces in XML 1.1

[SOURCE: Namespaces in XML 1.1, 3]

3.49

XML 1.0 QName

QName, as defined by rule [7] of Namespaces in XML 1.0

[SOURCE: XML 1.0, 4]

3.50

XML 1.1 QName

QName, as defined by rule [7] of Namespaces in XML 1.1

[SOURCE: XML 1.1, 4]

3.51

XML QName prefix

XML 1.0 QName prefix (3.52) or *XML 1.1 QName prefix* (3.53)

3.52

XML 1.0 QName prefix

Prefix, as defined by rule [10] of Namespaces in XML 1.0

[SOURCE: Namespaces in XML 1.0, 4]

3.53

XML 1.1 QName prefix

Prefix, as defined by rule [10] of Namespaces in XML 1.1

[SOURCE: Namespaces in XML 1.1, 4]

3.54

XML 1.0 QName local part

LocalPart, as defined by rule [11] of Namespaces in XML 1.0

[SOURCE: Namespaces in XML 1.0, 4]

3.55

XML 1.1 QName local part

LocalPart, as defined by rule [11] of Namespaces in XML 1.1

[SOURCE: Namespaces in XML 1.1, 4]

3.56

XML schema built-in data type

built-in datatype, as defined in XML Schema Part 2: Datatypes

[SOURCE: XML Schema Part 2: Datatypes, 3]

3.57

XML schema complex type

complex type defined by a complex type definition, as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 3.4]

3.58

XML schema data type

datatype, as defined in XML Schema Part 2: Datatypes

[SOURCE: XML Schema Part 2: Datatypes, A]

3.59

XML schema document

schema document, as defined in XML Schema Part 1: Structures

[SOURCE: XML Schema Part 1: Structures, 4.2]

3.60

XML schema primitive type

primitive type, as defined in XML Schema Part 2: Datatypes

[SOURCE: XML Schema Part 2: Datatypes, 4.1.1]

3.61

XML schema simple type

simple type defined by a simple type definition, as defined in XML Schema Part 2: Datatypes

[SOURCE: XML Schema Part 2: Datatypes, 4.1.2]

3.62

XML schema type

term used to collectively refer to *XML schema built-in data types* (3.56), *XML schema complex types* (3.57), *XML schema data types* (3.58), and *XML schema simple types* (3.61), when it is not necessary to distinguish among those terms

3.63

XML target namespace

target namespace as defined by XML Schema Part 1: Structures

3.64

XML target namespace URI

URI (3.18) of an *XML target namespace* (3.63)

3.65

XML text

character string that is a substring of a textual XML 1.0 content or a textual XML 1.1 content, as defined in Subclause 10.18, "Parsing a string as an XML value"

3.66

XML value space

value space, as defined by XML Schema Part 2: Datatypes

[SOURCE: XML Schema Part 2: Datatypes, 2.2]

3.67

XQuery accessor

accessor, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 5]

3.68

XQuery atomic type

atomic type, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.1]

3.69

XQuery atomic value

atomic value, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.7.5]

3.70

XQuery attribute node

attribute node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 3.3.1.1]

3.71

XQuery comment node

comment node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6.6]

3.72

XQuery datetime normalized value

normalized value of a value of XML schema types `xs:dateTime`, `xs:date`, `xs:time`, or any type derived from these types, as this term is used in [XQuery and XPath Functions and Operators 3.1](#), and implicitly defined in [XQuery and XPath Data Model 3.1](#), section 3.3.2 “Dates and Times”

[SOURCE: [XQuery and XPath Data Model 3.1](#), 3.3.2]

3.73

XQuery datetime time zone component

time zone component of a value of XML schema types `xs:dateTime`, `xs:date`, `xs:time`, or any type derived from these types, as this term is used in [XQuery and XPath Functions and Operators 3.1](#) and implicitly defined in [XQuery and XPath Data Model 3.1](#), section 3.3.2, “Dates and Times”

[SOURCE: [XQuery and XPath Data Model 3.1](#), 3.3.2]

3.74

XQuery document node

document node, as defined in [XQuery and XPath Data Model 3.1](#)

[SOURCE: [XQuery and XPath Data Model 3.1](#), 6.1]

3.75

XQuery dynamic context

dynamic context, as defined in [XQuery 3.1: an XML Query Language](#)

[SOURCE: [XQuery 3.1: an XML Query Language](#), 2.1.2]

3.76

XQuery element node

element node, as defined in [XQuery and XPath Data Model 3.1](#)

[SOURCE: [XQuery and XPath Data Model 3.1](#), 6.2]

3.77

XQuery error

static error, type error or dynamic error, as defined in [XQuery 3.1: an XML Query Language](#)

[SOURCE: [XQuery 3.1: an XML Query Language](#), 2.3]

3.78

XQuery evaluation with XML 1.0 lexical rules

process of determining the value of an XQuery expression with XML 1.0 lexical rules, as defined in [XQuery 3.1: an XML Query Language](#)

[SOURCE: [XQuery 3.1: an XML Query Language](#), 2.2]

3.79

XQuery evaluation with XML 1.1 lexical rules

process of determining the value of an XQuery expression with XML 1.1 lexical rules, as defined in [XQuery 3.1: an XML Query Language](#)

[SOURCE: [XQuery 3.1: an XML Query Language](#), 2.2]

3.80

XQuery expression

XQuery expression with XML 1.0 lexical rules, or an XQuery expression with XML 1.1 lexical rules

3.81

XQuery expression context

expression context, consisting of a static context and a dynamic context, as defined in XQuery 3.1: an XML Query Language

[SOURCE: XQuery 3.1: an XML Query Language, 2.1]

3.82

XQuery expression with XML 1.0 lexical rules

expression, as defined by rule [31], “Expr”, in XQuery 3.1: an XML Query Language, with rules [4], “NCName”, and [7], “QName”, interpreted to reference Namespaces in XML 1.0

[SOURCE: XQuery 3.1: an XML Query Language, 4.17]

3.83

XQuery expression with XML 1.1 lexical rules

expression, as defined by rule [31], “Expr”, in XQuery 3.1: an XML Query Language, with rules [4], “NCName”, and [7], “QName”, interpreted to reference Namespaces in XML 1.1

[SOURCE: XQuery 3.1: an XML Query Language, 4.17]

3.84

XQuery formal type notation

formal type notation, as defined by rule [24 (Formal)] “Type”, in XQuery 1.0 and XPath 2.0 Formal Semantics

3.85

XQuery item

item, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.8]

3.86

XQuery namespace node

namespace node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6.4]

3.87

XQuery node

node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6]

3.88

XQuery node identity

node identity, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.3]

3.89

XQuery node property

property of a node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6]

3.90

XQuery processing instruction node

processing instruction node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6.5]

3.91

XQuery sequence

sequence, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.5]

3.92

XQuery static context

static context, as defined in XQuery 3.1: an XML Query Language

[SOURCE: XQuery 3.1: an XML Query Language, 2.1.1]

3.93

XQuery text node

text node, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 6.7]

3.94

XQuery tree

tree, as defined in XQuery and XPath Data Model 3.1

[SOURCE: XQuery and XPath Data Model 3.1, 2.1]

3.95

XQuery variable

variable, as defined in XQuery 3.1: an XML Query Language

[SOURCE: XQuery 3.1: an XML Query Language, 4.13]

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

4 Concepts

This Clause modifies Clause 4, “Concepts”, in ISO/IEC 9075-2.

4.1 Notations and conventions

This Subclause modifies Subclause 4.1, “Notations and conventions”, in ISO/IEC 9075-2.

4.1.1 Notations

This Subclause modifies Subclause 4.1.1, “Notations”, in ISO/IEC 9075-2.

The notations used in this document are defined in ISO/IEC 9075-1.

The syntax defined in this document is available from the ISO website as a “digital artifact”. See <https://standards.iso.org/iso-iec/9075/-14/ed-6/en/> to download digital artifacts for this document. To download the syntax defined in a plain-text format, select the file named `ISO_IEC_9075-14(E)_XML.bnf.txt`. To download the syntax defined in an XML format, select the file named `ISO_IEC_9075-14(E)_XML.bnf.xml`.

4.1.2 XML-related notations

Many of the standards referenced in Clause 2, “Normative references”, are produced and maintained by the World Wide Web Consortium, including XML, XML Path Language (XPath) 3.1, XML Namespaces, XML Schema Part 1: Structures, XML Schema Part 2: Datatypes, XML Information Set, XQuery 3.1: an XML Query Language. W3C calls these international standards “Recommendations”, and places them on its web site (<https://www.w3.org>). Whenever this document mentions a value, type, or other object (broadly conceived) that is specified by a W3C Recommendation, then that object is indicated using bold monospace font (for example, `<xs:element>`).

Similarly, when a textual variable in a Rule denotes an object that is specified by a W3C Recommendation, then the variable is written in italicized bold monospace font (for example, `FACETP`).

The following list enumerates many, but not necessarily all, of the kinds of objects that are specified by W3C Recommendations.

- XML text;
- XML values;
- XML namespaces and XML namespace prefixes;
- XML schema types;
- XQuery types;
- XQuery nodes;
- XQuery node properties;
- XQuery expressions;
- XQuery functions;
- XQuery variables;
- XQuery formal type notations;

- XQuery static and dynamic contexts.

On the other hand, an object that has some feature or aspect that is not specified by W3C is not in bold. For example, W3C objects do not have the ability to be null. Since a value of XML type may be null, it is not represented in bold. As another example, a registered XML schema has an SQL privilege associated with it. In addition, non-bold variables are used for SQL BNF non-terminals, even when they are used to identify W3C objects.

This document specifies an interface between SQL and objects specified by W3C. As such, some values may be both W3C objects and also SQL objects. Therefore no notational convention can be totally consistent. In particular, it is permitted to assign a bold value to a non-bold variable, or to assign a non-bold value to a bold variable (provided the non-bold value has been determined to have no SQL-only feature, such as being a null). It is also permitted to compare a bold value and a non-bold value.

Whenever XML text is presented, an SQL/XML implementation may substitute equivalent XML text, for example, through insertion or deletion of insignificant blanks or new lines.

In this document, <left bracket>/<right bracket> pairs occur in five contexts.

- As part of BNF productions, in which a pair of brackets surrounds one or more non-terminal and/or terminal symbols that are, treated as a single group, optional.
- In code examples, in which the brackets are literal characters that represent themselves as part of the code.
- In ordinary text, in which a pair of brackets enclose a word or phrase that identifies a publication referenced in [Clause 2, “Normative references”](#).
- In ordinary text, in which a pair of brackets enclose a number that identifies the number of a BNF production specified in the publication whose reference appears nearby.
- In ordinary text, in which a pair of brackets enclose a word or phrase that identifies the name of a property defined in [XML Information Set](#).

In this document, <left brace>/<right brace> pairs occur in three contexts.

- As part of BNF productions, in which a pair of braces surrounds one or more non-terminal and/or terminal symbols that are to be handled as a single group.
- In code examples, in which the braces are literal characters that represent themselves as part of the code.
- In ordinary text, in which the braces enclose a word or phrase that identifies the name of a property defined in [XML Schema Part 1: Structures](#).

4.2 Data types

This Subclause modifies [Subclause 4.2, “Data types”](#), in [ISO/IEC 9075-2](#).

4.2.1 Naming of predefined types

This Subclause modifies [Subclause 4.2.2, “Naming of predefined types”](#), in [ISO/IEC 9075-2](#).

Insert after the 1st paragraph: SQL defines a predefined data type named by the following <key word>: XML.

Insert after the 3rd paragraph: The data types XML(DOCUMENT(UNTYPED)), XML(DOCUMENT(ANY)), XML(DOCUMENT(XMLSCHEMA)), XML(CONTENT(UNTYPED)), XML(CONTENT(ANY)), XML(CONTENT(XMLSCHEMA)), and XML(SEQUENCE) are referred to as the *XML types*. Values of XML types are called *XML values*.

4.2.2 Data type terminology

This Subclause modifies Subclause 4.2.4, “Data type terminology”, in ISO/IEC 9075-2.

Insert into the 11th paragraph, after the last list item:

- A type *T* is *XML-ordered* if *T* is *S-ordered*, where *S* is the set consisting of the XML types.

4.3 XML

4.3.1 Introduction

Fuller descriptions of XML concepts can be found in the documents about XML included in Clause 2, “Normative references”.

4.3.2 XML types

An XML type is described by an XML type descriptor. An XML type descriptor contains the following items.

- The name of the data type (XML).
- The primary XML type modifier described by the <primary XML type modifier> (DOCUMENT, CONTENT, or SEQUENCE).
- The secondary XML type modifier described by the <secondary XML type modifier> (UNTYPED, ANY, or XMLSCHEMA), if any.
- The registered XML schema descriptor of the indicated registered XML schema, if any.
- The XML namespace URI of the indicated XML namespace, if any.
- The XML NCName of the indicated global element declaration schema component, if any.

NOTE 1 — “Indicated registered XML schema”, “indicated XML namespace”, and “indicated global element declaration schema component” are defined in Subclause 11.5, “<XML valid according to clause>”.

An XML type whose primary XML type modifier is DOCUMENT and whose secondary XML type modifier is UNTYPED is called an XML(DOCUMENT(UNTYPED)) type.

An XML type whose primary XML type modifier is DOCUMENT and whose secondary XML type modifier is ANY is called an XML(DOCUMENT(ANY)) type.

An XML type whose primary XML type modifier is DOCUMENT and whose secondary XML type modifier is XMLSCHEMA is called an XML(DOCUMENT(XMLSCHEMA)) type.

NOTE 2 — The number of XML(DOCUMENT(XMLSCHEMA)) types is determined by the number of registered XML schemas, the number of XML namespaces in those XML schemas, and the number of global element declaration schema components in those XML schemas.

An XML type whose primary XML type modifier is CONTENT and whose secondary XML type modifier is UNTYPED is called an XML(CONTENT(UNTYPED)) type.

An XML type whose primary XML type modifier is CONTENT and whose secondary XML type modifier is ANY is called an XML(CONTENT(ANY)) type.

An XML type whose primary XML type modifier is CONTENT and whose secondary XML type modifier is XMLSCHEMA is called an XML(CONTENT(XMLSCHEMA)) type.

NOTE 3 — The number of XML(CONTENT(XMLSCHEMA)) types is determined by the number of registered XML schemas, the number of XML namespaces in those XML schemas, and the number of global element declaration schema components in those XML schemas.

An XML type whose primary XML type modifier is SEQUENCE is called an XML(SEQUENCE) type.

When determining the declared type of an <XML value expression>, an SQL-implementation is permitted to use the XML(DOCUMENT(ANY)) type in place of XML(DOCUMENT(UNTYPED)) and XML(DOCUMENT(XMLSCHEMA)) types, the XML(CONTENT(ANY)) type in place of XML(CONTENT(UNTYPED)), XML(CONTENT(XMLSCHEMA)), and XML(DOCUMENT(ANY)) types, and the XML(SEQUENCE) type in place of the XML(CONTENT(ANY)) type.

NOTE 4 — The above substitutions can be applied transitively. For instance, an SQL-implementation is permitted to use the XML(SEQUENCE) type in place of the XML(DOCUMENT(UNTYPED)) type.

4.3.3 Characteristics of XML values

An *XML value* is either the null value or an XQuery sequence.

Every XML value is a value of type XML(SEQUENCE).

Every XML value that is either the null value or an XQuery document node is a value of type XML(CONTENT(ANY)).

Every XML value that is either:

- the null value;
- a non-null value of type XML(CONTENT(ANY)) that is an XQuery document node *D* such that all of the following are true:
 - for every XQuery element node that is contained in the XQuery tree *T* rooted in *D*, the **type-name** property is **xs:untyped** and the **nilled** property is **false**,
 - for every XQuery attribute node that is contained in *T*, the **type-name** property is **xs:untypedAtomic**.

is a value of type XML(CONTENT(UNTYPED)).

Every XML value that is either:

- the null value;
- a non-null value of type XML(CONTENT(ANY)) that is an XQuery document node *D* such that every XQuery element node that is contained in the XQuery tree *T* rooted in *D* is valid according to at least one of the following:
 - an XML schema *S*,
 - an XML namespace *N* in an XML schema *S*,
 - a global element declaration schema component *E* in an XML schema *S*.

is a value of type XML(CONTENT(XMLSCHEMA)) whose type descriptor includes the registered XML schema descriptor of *S* and, if *N* is specified, the XML namespace URI of *N* or, if *E* is specified, the XML namespace URI of *E* and the XML NCName of *E*.

Every XML value that is either:

- the null value;
- a non-null value of type XML(CONTENT(ANY)) that is an XQuery document node whose **children** property has exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes.

is a value of type XML(DOCUMENT(ANY)).

Every XML value that is either:

4.3 XML

- the null value;
- a non-null value of type XML(CONTENT(UNTYPED)) that is an XQuery document node whose **children** property has exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes.

is a value of type XML(DOCUMENT(UNTYPED)).

Every XML value that is either:

- the null value;
- a non-null value of type XML(DOCUMENT(ANY)) that is valid according to at least one of the following:
 - an XML schema *S*,
 - an XML namespace *N* in an XML schema *S*,
 - a global element declaration schema component *E* in an XML schema *S*.

is a value of type XML(DOCUMENT(XMLSCHEMA)) whose type descriptor includes the registered XML schema descriptor of *S* and, if *N* is specified, the XML namespace URI of *N*, or, if *E* is specified, the XML namespace URI of *E* and the XML NCName of *E*.

Two XML values are regarded as equivalent as specified in [Subclause 10.7](#), “Determination of equivalent XML values”.

4.3.4 XML comparison and assignment

A value of an XML type *S* is assignable to a site of an XML type *T* if exactly one of the following is true.

- *T* is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)) and *S* is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)).
- *T* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and *S* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) such that the registered XML schema descriptors included in the XML type descriptors of both *T* and *S* identify identical XML schemas, the XML namespace URI included in the XML type descriptor of *T*, if any, is identical to the XML namespace URI included in the XML type descriptor of *S*, as defined by [XML Namespaces](#), and the XML NCName of the global element declaration schema component included in the XML type descriptor of *T*, if any, is identical to the XML NCName of the global element declaration schema component included in the XML type descriptor of *S*.

NOTE 5 — The notion of identical XML schemas is defined in [Subclause 4.3.6](#), “Registered XML schemas”.

- *T* is either XML(DOCUMENT(ANY)), XML(CONTENT(ANY)), or XML(SEQUENCE) and *S* is an XML type.

Operations that involve assignment of XML values use the keywords BY REF to indicate that the assignment preserves XQuery node identity, and BY VALUE to indicate that the assignment loses XQuery node identity.

XML values are not comparable.

4.3.5 Operations involving XML values

<XML document> is an operator that returns an XML value, given another XML value. The new XML value consists of an XQuery document node that is constructed according to the rules of the computed document constructor in [XQuery 3.1: an XML Query Language](#).

<XML element> is an operator that returns an XML value, given an XML element name, an optional list of XML namespaces, an optional list of XML attributes, and an optional list of values as the content of the

new element. The value of <XML element content> can be any value that has a mapping to an XML value. The result, an XQuery element node, may optionally be placed as the sole child of an XQuery document node.

<XML forest> is an operator that returns an XML value, given an optional list of XML namespaces and a list of <forest element>s. An XQuery element node is produced from each <forest element>, using the column name or, if provided, the <forest element name> as the XML element name and the <forest element value> as the element content. The value of <forest element value> can be any value that has a mapping to an XML value. The result, an XQuery sequence, may optionally be placed in an XQuery document node.

<XML concatenation> is an operator that returns an XML value by concatenating a list of XML values, as defined in Subclause 6.13, “<XML concatenation>”. The result, an XQuery sequence, may optionally be placed in an XQuery document node.

<XML comment> is an operator that returns an XML value, given a character string *CS*. The XML value consists of an XQuery comment node whose **content** property is *CS*, mapped to Unicode. This XQuery comment node may optionally be placed as the sole child of an XQuery document node.

<XML PI> is an operator that returns an XML value, given an <identifier> and an optional character string *CS*. The XML value consists of an XQuery processing instruction node whose **target** property is the <identifier>, and whose **content** property is *CS*, trimmed of leading blanks and mapped to Unicode. This XQuery processing instruction node may optionally be placed as the sole child of an XQuery document node.

<XML text> is an operator that returns an XML value, given a character string *CS*. The XML value consists of an XQuery text node whose **content** property is *CS*, mapped to Unicode. The XQuery text node may optionally be placed as the sole child of an XQuery document node.

<XML query> is an operator that evaluates an XQuery expression, which may be parameterized with any number of input parameters. The result, an XQuery sequence, may optionally be placed in an XQuery document node.

<XML table> is a kind of <derived table>, which may be used to query an XML value as a table. The result is specified by means of <XML table row pattern>, <XML table argument list>, and <XML table column definitions>. The result is computed in the following steps.

- The <XML table row pattern> is an XQuery expression that is evaluated, with <XML table argument list> as the (optional) input arguments. This produces an intermediate result, an XQuery sequence.
- Each XQuery item in the intermediate result is used to create a row of the final result.
- The columns of the result are specified by <XML table column definitions>, which is a collection of <XML table column definition>s modeled on a <table definition>. Thus, each result column has a <data type>, and, optionally, a <default clause>. Each <XML table column definition> also specifies, explicitly or implicitly, an <XML table column pattern> *XTCP*, which is an XQuery expression.
- To generate the value for a particular row and column of the final result, the column pattern (i.e., the XQuery expression *XTCP*) is evaluated using a particular XQuery item of the intermediate result as the input parameter, and then cast to the <data type> of the result column. If *XTCP* evaluates to the empty XQuery sequence, then the column’s <default clause>, if any, determines the column’s default value.

<XML character string serialization> is an operator that returns a character string, given an XML value, using the algorithm in [XSLT and XQuery Serialization 3.1](#). Optionally, the input XML value may be checked to ensure that it is an XQuery document node whose **children** property has exactly one XQuery element node. Other options may be used to specify the version of XML text that is produced (i.e., either a textual XML 1.0 content or a textual XML 1.1 content); and whether an XML declaration is produced or not.

<XML binary string serialization> is an operator that returns a binary string, given an XML value, using the algorithm in [XSLT and XQuery Serialization 3.1](#). <XML binary string serialization> supports the same

options as <XML character string serialization>, plus the ability to specify the encoding (character set) of the result.

<XML parse> is an operator that parses a character string or binary string value, i.e., converts XML text to a set of XML information items, according to the rules of [XML Information Set](#), and then converts that set of XML information items into an XQuery document node, according to the rules of [XQuery and XPath Data Model 3.1](#).

<XML validate> is an operator that validates an XML value according to a registered XML schema. Optionally, the registered XML schema against which to validate may be chosen on the basis of the contents of the data value, or it may be specified directly in the <XML validate>. In the latter case, additional options allow the validation to be confined to a particular namespace of the designated registered XML schema, or to a particular global element declaration schema component. Upon successful validation, <XML validate> returns a copy of the input XML value augmented with default values and type annotations. If validation fails, <XML validate> raises an exception.

<XML content predicate> is a predicate that determines if an XML value is an XQuery document node.

<XML document predicate> is a predicate that determines if an XML value is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes.

<XML exists predicate> is a predicate that evaluates an XQuery expression and determines if the result is a null value, an empty XQuery sequence, or a non-empty XQuery sequence.

<XML valid predicate> is a predicate that determines if an XML value is valid according to a registered XML schema. Optionally, the registered XML schema to validate against may be chosen on the basis of the contents of the data value, or it may be specified directly in the <XML valid predicate>. In the latter case, additional options allow the validation to be confined to a particular namespace of the designated registered XML schema, or to a particular global element declaration schema component.

4.3.6 Registered XML schemas

A *registered XML schema* is an XML schema that has been made known to the SQL-server. The means by which an XML schema is registered is implementation-defined (IW200).

A global element declaration schema component of a registered XML schema is *non-deterministic* if it contains or references a wildcard schema component whose **{namespace constraint}** property is either **not** together with a namespace name, or **any**, and whose **{process contents}** property is either **strict** or **lax** (as defined in [XML Schema Part 1: Structures](#) section 3.10.1, “The Wildcard Schema Component”).

NOTE 6 — The elements of an XML schema Document corresponding to such wildcard schema components are elements <xs:any> or <xs:anyAttribute> in which the **namespace** attribute is either missing or has the value “##any” or “##other”, and the **processContents** attribute is either missing or has either the value “strict” or the value “lax”.

An XML namespace *NS* contained in a registered XML schema is *non-deterministic* if *NS* contains a global element declaration schema component that is non-deterministic.

A registered XML schema is *non-deterministic* if it contains a non-deterministic XML namespace.

A registered XML schema is described by a registered XML schema descriptor. A registered XML schema descriptor includes the following.

- The target namespace URI of the registered XML schema.
- The schema location URI of the registered XML schema.
- The <registered XML schema name> of the registered XML schema.
- An indication of whether the registered XML schema is permanently registered.
- An indication of whether the registered XML schema is non-deterministic.

- An unordered collection of the namespaces defined by the registered XML schema (the target namespace is one of these namespaces).
- For each namespace defined by the registered XML schema, an unordered collection of the global element declaration schema components in that namespace, with an indication for each global element declaration schema component whether that global element declaration schema component is non-deterministic.

NOTE 7 — Without Feature X161, “Advanced Information Schema for registered XML schemas”, information whether an XML schema is deterministic, information about the collection of namespaces defined in that XML schema, and, for each such namespace information about the global element declaration schema components in that namespace, is not available in the XML_SCHEMAS, XML_SCHEMA_NAMESPACES, and XML_SCHEMA_ELEMENTS views.

A registered XML schema is identified by its <registered XML schema name>.

Two registered XML schemas are considered *identical* if both are identified by the same <registered XML schema name>.

Certain XML schemas, defined by either this document or by some normative reference, are always registered. These XML schemas are enumerated in Table 1, “Permanently registered XML schemas”.

Table 1 — Permanently registered XML schemas

Common prefix (non-normative)	Target namespace URI ¹
xs	http://www.w3.org/2001/XMLSchema
xsi	http://www.w3.org/2001/XMLSchema-instance
sqlxml	http://standards.iso.org/iso/9075/2003/sqlxml

¹ The schema location URIs and <registered XML schema name>s of these XML schemas are implementation-defined (IV200).

NOTE 8 — The “common prefix” column in the preceding table indicates the prefix(es) commonly associated with the target namespaces of these XML schemas, but there is no requirement to refer to them by these prefixes.

If a <data type>, an <XML validate>, or an <XML valid predicate> that contains an <XML valid according to what> *XVACC* is contained in a <query expression> of a view, a check constraint, or an assertion, the <triggered action> of a trigger, or in an <SQL-invoked routine>, then the registered XML schema that is referenced by *XVACC* is determined at the time the view is created, the check constraint is defined, the assertion is created, the trigger is created, or the SQL-invoked routine is created. The same registered XML schema is referenced whenever the view is used, or the check constraint or assertion is evaluated, the trigger is executed, or the SQL-invoked routine is invoked.

4.4 Data conversions

This Subclause modifies Subclause 4.13, “Data conversions”, in ISO/IEC 9075-2.

Insert before the 3rd paragraph: Data conversions between the predefined data types defined in ISO/IEC 9075-2 and the XML types can be specified by an <XML cast specification>.

A conversion from an XML type to a non-XML type is computed as follows:

- 1) XQuery document nodes are removed from the source value.
- 2) The result is converted to an XQuery sequence of XQuery atomic values **AV** using the XQuery function **fn:data()**.

4.4 Data conversions

- 3) An XML schema data type ***XT*** is chosen to correspond to the target <data type>. For example, if the target <data type> is INTEGER then ***XT*** is ***xs:integer***.
- 4) ***AV*** is converted to ***XT*** using the rules of XQuery 3.1: an XML Query Language, producing ***BV***.
- 5) ***BV*** is a value of an XML schema data type, which is either an XML schema primitive type, or derived from an XML schema primitive type. For example, ***BV*** might be a value of XML schema type ***xs:short***, which is derived from ***xs:decimal***. The value spaces of most XML schema primitive types are identified with an SQL value space. For example, the XML value space of ***xs:decimal*** is identified with the SQL value space of exact numeric values. If, say, ***BV*** has the value **9075.14** in the XML value space of ***xs:decimal***, then ***BV*** is also regarded as being the value **9075.14** in the SQL value space of exact numeric values. These value space identifications are defined in Subclause 4.11.8, "Mapping XQuery atomic values to SQL values".
- 6) ***BV***, regarded now as a value of an SQL value space, is converted to the target <data type>, using a <cast specification>.

A conversion from a non-XML type to an XML type is computed as follows:

- 1) The source value is converted to a <character string literal> whose value is the result of applying the General Rules of Subclause 9.8, "Mapping values of SQL data types to values of XML schema data types".
- 2) The <character string literal> is parsed using <XML parse>, producing an XQuery document node ***D***.
- 3) If the target <data type> is XML(CONTENT(UNTYPED)) or XML(CONTENT(ANY)), then ***D*** is the result.
- 4) If the target <data type> is XML(SEQUENCE), then ***D*** is converted to an XQuery atomic value by evaluating an XQuery cast expression. The XQuery type to convert to is chosen based on the declared type of the source value. For example, if the declared type of the source is exact numeric, then the XQuery type of the result is ***xs:decimal***.

4.5 Data analysis operations

This Subclause modifies Subclause 4.18, "Data analysis operations", in ISO/IEC 9075-2.

4.5.1 Aggregate functions

This Subclause modifies Subclause 4.18.4, "Aggregate functions", in ISO/IEC 9075-2.

Insert into the 7th paragraph, after the last list item:

- If XMLAGG is specified, then an XML value formed from the <XML value expression> evaluated for each row that qualifies.

4.6 SQL-invoked routines

This Subclause modifies Subclause 4.35, "SQL-invoked routines", in ISO/IEC 9075-2.

4.6.1 Routine descriptors

This Subclause modifies Subclause 4.35.5, "Routine descriptors", in ISO/IEC 9075-2.

Insert into the 1st paragraph, in the 6th list item, after the last list item:

- For every SQL parameter whose declared type is an XML type or a distinct type whose source type is an XML type, an indication of the <XML passing mechanism>.

Insert into the 1st paragraph, in the 11th list item, after the last list item:

- If the <returns clause> contains an <XML passing mechanism>, then that <XML passing mechanism>.

Insert into the 1st paragraph, in the 15th list item, after the last list item:

- For every SQL parameter that has an associated string type, the character string type descriptor of the associated string type.
- For every SQL parameter that has an associated XML option, an indication of the associated XML option.

4.7 SQL-statements

This Subclause modifies Subclause 4.41, “SQL-statements”, in ISO/IEC 9075-2.

4.7.1 SQL-statements classified by function

This Subclause modifies Subclause 4.41.2, “SQL-statements classified by function”, in ISO/IEC 9075-2.

4.7.1.1 SQL-session statements

This Subclause modifies Subclause 4.41.2.7, “SQL-session statements”, in ISO/IEC 9075-2.

Insert into the 1st paragraph, after the last list item:

- <set XML option statement>

4.8 Basic security model

This Subclause modifies Subclause 4.42, “Basic security model”, in ISO/IEC 9075-2.

4.8.1 Privileges

This Subclause modifies Subclause 4.42.2, “Privileges”, in ISO/IEC 9075-2.

Insert into the 1st paragraph, after the last list item:

- registered XML schema

Insert into the 11th paragraph, after the last list item:

- registered XML schema

Insert after the 11th paragraph: USAGE privileges on registered XML schemas are granted or revoked by implementation-defined (IW201) means.

4.9 SQL-sessions

This Subclause modifies Subclause 4.45, “SQL-sessions”, in ISO/IEC 9075-2.

4.9.1 SQL-session properties

This Subclause modifies Subclause 4.45.3, “SQL-session properties”, in ISO/IEC 9075-2.

Insert after the 6th paragraph: An SQL-session has an XML option that is used to identify the <document or content> option needed in the implicit invocation of XMLSERIALIZE and XMLPARSE operators during the execution of <preparable statement>s that are prepared in the current SQL-session by either an <execute immediate statement> or a <prepare statement>. The XML option is initially set to an imple-

mentation-defined (ID200) value, but can subsequently be changed by the successful execution of a <set XML option statement>.

Insert into the 13th paragraph, after the last list item:

- The current XML option.

4.10 XML namespaces

This document references certain XML namespaces that are defined by the World-Wide Web Consortium or by this document. Each XML namespace is referenced using an XML namespace prefix. The XML namespace prefixes and their definitions are shown in Table 2, “XML namespace prefixes and their URIs”.

Table 2 — XML namespace prefixes and their URIs

XML namespace prefix	XML namespace URI
xs	http://www.w3.org/2001/XMLSchema
xsi	http://www.w3.org/2001/XMLSchema-instance
sqlxml	http://standards.iso.org/iso/9075/2003/sqlxml

A conforming SQL/XML implementation is not required to use the XML namespace prefixes **xs**, **xsi**, or **sqlxml** to reference these XML namespaces, but whatever XML namespace prefix it uses shall be associated with the proper URI.

The XML namespace identified by the XML namespace prefix “**sqlxml**” is normatively defined in Clause 23, “SQL/XML XML schema”.

A resource containing the XML schema definition of the XML namespace identified by the XML namespace prefix “**sqlxml**” (that is, a file containing an XML schema document) has been made available on the World Wide Web. The URI of that resource is:

<http://standards.iso.org/iso/9075/2003/sqlxml.xsd>

It is intended that the contents of that file be identical to the contents of Clause 23, “SQL/XML XML schema”. This file has been created for the convenience of the implementors of this document.

4.11 Overview of mappings

4.11.1 Introduction to mappings

This document defines mappings from SQL to XML, and from XML to SQL. The mappings from SQL to XML include the following,

- Mapping SQL character sets to Unicode.
- Mapping SQL <identifier>s to XML names.
- Mapping SQL data types (as used in SQL-schemas to define SQL-schema objects such as columns) to XML schema data types.
- Mapping values of SQL data types to values of XML schema data types.
- Mapping an SQL table to an XML document and an XML schema document.
- Mapping an SQL schema to an XML document and an XML schema document.

- Mapping an SQL catalog to an XML document and an XML schema document.

The mappings from XML to SQL include the following.

- Mapping Unicode to SQL character sets.
- Mapping XML names to SQL <identifier>s.

4.11.2 Mapping SQL character sets to Unicode

For each character set *SQLCS* in the SQL-environment, there shall be a mapping *CSM* of strings of *SQLCS* to strings of Unicode, as defined in [The Unicode® Standard](#). In this document, “Unicode” refers to the character repertoire named “UCS”. The mapping *CSM* is called *homomorphic* if for each non-negative integer *N*, there exists a non-negative integer *M* such that all strings of length *N* in *SQLCS* are mapped to strings of length *M* in Unicode. *CSM* is implementation-defined ([IA091](#)). However, if any Unicode code point is mapped to a character that is not a valid XML character, an exception condition is raised.

NOTE 9 — The entity references `<`, `&`, `>`, `'`, and `"`, as well as character references, as defined by XML are regarded as each representing a single character in XML, and do not pose an obstacle to defining homomorphic mappings.

4.11.3 Mapping Unicode to SQL character sets

For each character set *SQLCS* in the SQL-environment, there shall be an implementation-defined ([IA092](#)) mapping *CSM* of strings of Unicode to strings of *SQLCS*.

4.11.4 Mapping SQL <identifier>s to XML

Since not every SQL <identifier> is an acceptable XML name, it is necessary to define a mapping of SQL <identifier>s to XML names. This mapping is defined in [Subclause 9.1, “Mapping SQL <identifier>s to XML names”](#). The basic idea of this mapping is that characters that are not valid in XML names are converted to a sequence of hexadecimal digits derived from the Unicode encoding of the character, bracketed by an introductory underscore and lower-case *x* and a trailing underscore.

There are two variants of the mapping, known as *partially escaped* and *fully escaped*. The two differences are in the treatment of non-initial <colon> and the treatment of an <identifier> beginning with the letters `xml` in any combination of upper or lower-case. The fully escaped variant maps a non-initial <colon> to `_x003A_`, whereas the partially escaped variant maps non-initial <colon> to `..`. Also, the fully escaped variant maps initial `xml` and `XML` to `_x0078_ml` and `_x0058_ML`, respectively, whereas the partially escaped does not.

NOTE 10 — This document specifies no syntax for invoking the partially escaped mapping specified in [Subclause 9.1, “Mapping SQL <identifier>s to XML names”](#). This specification is intended to be used by applications and referenced by other standards.

4.11.5 Mapping XML names to SQL

A single algorithm suffices to reverse both the partially escaped and the fully escaped variants of the mapping of SQL <identifier>s to XML names. This algorithm is found in [Subclause 9.3, “Mapping XML names to SQL <identifier>s”](#). The basic idea is to scan the XML name from left to right, looking for escape sequences of the form `_xNNNN_` or `_xNNNNNN_` where *N* denotes a hexadecimal digit. Such sequences are converted to the character of SQL_TEXT that corresponds to the Unicode code point U+0000NNNN or U+00NNNNNN, respectively.

NOTE 11 — This document specifies no syntax for invoking the mapping specified in [Subclause 9.3, “Mapping XML names to SQL <identifier>s”](#). This specification is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

NOTE 12 — The sequence of mappings from SQL <identifier> to XML name (using either the fully escaped mapping or the partially escaped mapping) to SQL <identifier> restores the original SQL <identifier> (assuming that every character in the source SQL-implementation’s SQL <identifier> is a character of SQL_TEXT in the target SQL-implementation). However,

4.11 Overview of mappings

the sequence of mappings from XML name to SQL <identifier> to XML Name does not necessarily restore the XML name. Also, more than one XML name can be mapped to the same SQL <identifier>.

4.11.6 Mapping SQL data types to XML

For each SQL type or domain that is not unmappable, there is a corresponding XML schema type. The mapping is fully specified in Subclause 9.5, “Mapping SQL data types to XML schema data types”. The following is a conceptual description of this mapping.

In general, each SQL predefined type, distinct type, or domain *SQLT* is mapped to the XML schema type *XMLT* that is the closest analog to *SQLT*. Since the value space of *XMLT* is frequently richer than the set of values that can be represented by *SQLT*, facets are used to restrict *XMLT* in order to capture the restrictions on *SQLT* as much as possible.

In addition, many of the distinctions in the SQL type system (for example, CHARACTER VARYING versus CHARACTER LARGE OBJECT) have no corresponding distinction in the XML schema type system. In order to represent these distinctions, XML schema annotations are defined. The content of the annotations is defined by this document; however, whether such annotations are actually generated is implementation-defined (IA100). Elements from the XML namespace identified by the XML namespace prefix “**sqlxml**” are used to populate these annotations.

The SQL character string types are mapped to the XML schema type **xs:string**. For the SQL type CHARACTER, if the mapping of the SQL character set to Unicode is homomorphic, then fixed length strings are mapped to fixed length strings, and the facet **xs:length** is used. Otherwise (i.e., CHARACTER when the mapping is not homomorphic, as well as CHARACTER VARYING and CHARACTER LARGE OBJECT), the facet **xs:maxLength** is used. Annotations optionally indicate the precise SQL type (CHARACTER, CHARACTER VARYING, or CHARACTER LARGE OBJECT), the length or maximum length of the SQL type, the character set, and the default collation.

The SQL binary string types are mapped to either the XML schema type **xs:hexBinary** or the XML schema type **xs:base64Binary**. The **xs:maxLength** facet is set to the maximum length of the binary string in octets. Annotations optionally indicate the SQL type (BINARY, BINARY VARYING, BINARY LARGE OBJECT) and the maximum length in octets. For <XML element> and <XML forest>, the choice of whether to map to **xs:hexBinary** or **xs:base64Binary** is governed by the innermost <XML binary encoding> whose scope includes the <XML element> or <XML forest>; the default is implementation-defined (ID201). When mapping an SQL table, schema or catalog to XML, the choice is governed by a parameter, as specified in Subclause 9.11, “Mapping an SQL table to XML and an XML schema document”, Subclause 9.14, “Mapping an SQL schema to an XML document and an XML schema document”, and Subclause 9.17, “Mapping an SQL catalog to an XML document and an XML schema document”.

The exact numeric SQL types NUMERIC and DECIMAL are mapped to the XML schema type **xs:decimal** using the facets **xs:precision** and **xs:scale**. It is implementation-defined (IA093) whether the SQL types INTEGER, SMALLINT, and BIGINT are mapped to the XML schema type **xs:integer** using the facets **xs:maxInclusive** and **xs:minInclusive** or to the closest XML schema type that is a subtype of **xs:integer**, using the facets **xs:maxInclusive** and **xs:minInclusive** if the range of the SQL type does not exactly match the range of the XML schema type to which it is mapped. Annotations optionally indicate the SQL type (NUMERIC, DECIMAL, INTEGER, SMALLINT, or BIGINT), precision of NUMERIC, user-specified precision of DECIMAL (which may be less than the actual precision), and scale of NUMERIC and DECIMAL.

The approximate numeric SQL types are mapped to either the XML schema type **xs:float**, if the binary precision is less than or equal to 24 binary digits (bits) and the range of the binary exponent lies between -149 and 104, inclusive; otherwise, the XML schema type **xs:double** is used. Annotations optionally indicate the SQL type (REAL, DOUBLE PRECISION, or FLOAT), the binary precision, the minimum and maximum values of the range of binary exponents, and, for FLOAT, the user-specified binary precision (which may be less than the actual precision).

The SQL type BOOLEAN is mapped to the XML schema type **xs:boolean**. Optionally, an annotation indicates the SQL type (BOOLEAN).

The SQL type DATE is mapped to the XML schema type **xs:date**. The **xs:pattern** facet is used to exclude the possibility of a time zone displacement. Optionally, an annotation indicates the SQL type, DATE.

The SQL types TIME WITHOUT TIME ZONE and TIME WITH TIME ZONE are mapped to the XML schema type **xs:time**. The **xs:pattern** facet is used to exclude the possibility of a time zone displacement, in the case of TIME WITHOUT TIME ZONE, or to require a time zone displacement, in the case of TIME WITH TIME ZONE. The **xs:pattern** facet also reflects the fractional seconds precision of the SQL type. Annotations optionally indicate the SQL type (TIME or TIME WITH TIME ZONE) and the fractional seconds precision.

The SQL types TIMESTAMP WITHOUT TIME ZONE and TIMESTAMP WITH TIME ZONE are mapped to the XML schema type **xs:dateTime**. The **xs:pattern** facet is used to exclude the possibility of a time zone displacement, in the case of TIMESTAMP WITHOUT TIME ZONE, or to require a time zone displacement, in the case of TIMESTAMP WITH TIME ZONE. The **xs:pattern** facet also reflects the fractional seconds precision of the SQL type. Annotations optionally indicate the SQL type (TIMESTAMP or TIMESTAMP WITH TIME ZONE) and the fractional seconds precision.

The SQL interval types are mapped to the XML schema types **xs:yearMonthDuration** and **xs:dayTimeDuration**. The **xs:pattern** facet is used to require precisely the year, month, day, hour, minute and second fields indicated by the SQL type. The **xs:pattern** facet also reflects the leading field precision and the fractional seconds precision (when applicable). Annotations optionally indicate the SQL type, leading field precision and (when applicable) the fractional seconds precision.

An SQL row type is mapped to an XML schema complex type that consists of one element for each field of the SQL row type. For each field *F* of the SQL row type, the name of the corresponding XML element is obtained by mapping the field name of *F* using the fully escaped variant, and the XML schema type of the element is obtained by mapping the field type of *F*.

An SQL domain is mapped to XML by mapping the domain's data type to XML and then optionally applying to the generated XML schema type an annotation that identifies the name of the domain.

An SQL distinct type is mapped to an XML schema simple type by mapping the source type of the distinct type. Optionally, an annotation specifying the name of the distinct type is applied to the generated XML schema type.

An SQL collection type is mapped to an XML schema complex type having a single XML element named **element** whose XML schema type is obtained by mapping the element type of the SQL collection type. This XML element is defined using **minOccurs="0"**. For an SQL array type, **maxOccurs** is the maximum cardinality of the array, whereas for an SQL multiset type, **maxOccurs="unbounded"**.

An SQL XML type is mapped to an XML schema complex type that allows mixed content and an unvalidated **any** section. Optionally, an annotation indicates the SQL type, XML.

4.11.7 Mapping values of SQL data types to XML

For each SQL type or domain *SQLT*, with the exception of structured types and reference types, there is also a mapping of values of type *SQLT* to the value space of the corresponding XML schema type. The mappings of values are largely determined by the data type mappings. The precise rules for non-null values are found in [Subclause 9.8, "Mapping values of SQL data types to values of XML schema data types"](#). The mappings for values of predefined types are designed to exploit `<cast specification>` as much as possible. As for null values, there is generally a choice of whether to represent nulls using absence or **xsi:nil="true"** . However, for elements of a collection type, null values are always represented by **xsi:nil="true"** .

4.11.8 Mapping XQuery atomic values to SQL values

As defined in [XQuery and XPath Data Model 3.1](#), an XQuery atomic type is either an XML schema primitive type, or derived from an XML schema primitive type by restriction (and not by union or list).

Let **AV** be an XQuery atomic value. Let **AT** be the XQuery atomic type of **AV**. Let **PT** be given by

Case:

- If **AT** is an XML schema primitive type, then **AT**.
- If **AT** is **xs:yearMonthDuration**, or derived from **xs:yearMonthDuration**, then **xs:yearMonthDuration**.
- If **AT** is **xs:dayTimeDuration**, or derived from **xs:dayTimeDuration**, then **xs:dayTimeDuration**.
- Otherwise, the XML schema primitive type from which **AT** is derived.

This document (notably, in [Subclause 6.7](#), “<XML cast specification>”) regards **AV** as being a value belonging to some category of SQL predefined type, as follows.

Case:

- If **PT** is **xs:string**, then **AV** is regarded as being a character string whose character repertoire is Unicode.
- If **PT** is **xs:hexBinary** or **xs:base64Binary**, then **AV** is regarded as being a binary string.
- If **PT** is **xs:decimal**, then **AV** is regarded as being an exact numeric value.
- If **PT** is **xs:float** or **xs:double**, then **AV** is regarded as being an approximate numeric value.
- If **PT** is **xs:time** and the XQuery datetime time zone component of **AV** is an empty XQuery sequence, then the XQuery datetime normalized value of **AV** is regarded as being a value of type TIME WITHOUT TIME ZONE.
- If **PT** is **xs:time** and the XQuery datetime time zone component of **AV** is not an empty XQuery sequence, then **AV** is regarded as being a value of type TIME WITH TIME ZONE, in which the XQuery datetime time zone component of **AV** is the time zone component, and the XQuery datetime normalized value is the UTC component.
- If **PT** is **xs:dateTime**, the XQuery datetime normalized value **XDNV** of **AV** is positive, and the XQuery datetime time zone component of **AV** is an empty XQuery sequence, then **XDNV** is regarded as being a value of type TIMESTAMP WITHOUT TIME ZONE. If **XDNV** would have a SECOND field greater than 59 in a minute of UTC that has exactly 59 seconds, then it is implementation-defined ([IA055](#)) whether an implementation-defined ([IV125](#)) value of type TIMESTAMP WITHOUT TIME ZONE is identified with **XDNV**, or whether an exception condition is raised: *data exception — datetime field overflow (22008)*.
- If **PT** is **xs:dateTime**, the XQuery datetime normalized value of **AV** is positive, and the XQuery datetime time zone component of **AV** is not an empty XQuery sequence, then **AV** is regarded as being a value of type TIMESTAMP WITH TIME ZONE, in which the XQuery datetime time zone component of **AV** is the time zone component, and the XQuery datetime normalized value is the UTC component. If **AV** denotes a minute of UTC that has exactly 59 seconds and the SECOND field of **AV** is greater than 59, then it is implementation-defined ([IA055](#)) whether an implementation-defined ([IV125](#)) value of type TIMESTAMP WITHOUT TIME ZONE is identified with **AV**, or whether an exception condition is raised: *data exception — datetime field overflow (22008)*.

- If *PT* is **xs:date**, the XQuery datetime normalized value of *AV* is positive, and the XQuery datetime time zone component of *AV* is an empty XQuery sequence, then the XQuery datetime normalized value of *AV* is regarded as being a value of type DATE.
- If *PT* is **xs:yearMonthDuration**, then *AV* is regarded as being a year-month interval.
- If *PT* is **xs:dayTimeDuration**, then *AV* is regarded as being a day-time interval.
- If *PT* is **xs:boolean**, then *AV* is regarded as being a value of type BOOLEAN.

4.11.9 Visibility of columns, tables, and schemas in mappings from SQL to XML

An *XML unmappable data type* is a data type that is one of the following: a JSON type, a structured type, a reference type, XML(SEQUENCE), or a type defined in some part of the ISO/IEC 9075 series other than ISO/IEC 9075-2 and this document. An *XML unmappable column* is a column that has a declared type that is one of the XML unmappable data types or has a declared type that is based on an XML unmappable data type.

A column *C* of table *T* is a *visible column* of *T* for authorization identifier *U* if the applicable privileges for *U* include the SELECT privilege on *C* and, if the declared type of *C* is a distinct type, the applicable privileges for *U* include EXECUTE on the user-defined cast function identified by the Syntax Rules of Subclause 6.6, “<cast specification>”. A column *C* of table *T* is an *XML visible column* of *T* for authorization identifier *U* if *C* is a visible column of *T* for authorization identifier *U* and the declared type of *C* is not an XML unmappable data type.

A table *T* of schema *S* is a *visible table* of *S* for authorization identifier *U* if *T* is either a base table or a viewed table that contains a column *C* that is a visible column for *U*. A table *T* of schema *S* is an *XML visible table* of *S* for authorization identifier *U* if *T* is either a base table or a viewed table that contains a column *C* that is an XML visible column for *U*.

A schema *S* of catalog *C* is a *visible schema* of *C* for authorization identifier *U* if *S* contains a table *T* that is a visible table for *U*. A schema *S* of catalog *C* is an *XML visible schema* of *C* for authorization identifier *U* if *S* contains a table *T* that is an XML visible table for *U*.

4.11.10 Mapping an SQL table to XML

Subclause 9.11, “Mapping an SQL table to XML and an XML schema document”, defines a mapping of an SQL table to one or both of two documents: an XML schema document that describes the structure of the mapped XML and either an XML document or a sequence of XML elements. Only base tables and viewed tables may be the source of this mapping.

NOTE 13 — This document specifies no syntax for invoking the mapping specified in Subclause 9.11, “Mapping an SQL table to XML and an XML schema document”. This specification is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Only the XML visible columns of this table for the user that invokes this mapping will be represented in the generated XML.

This mapping allows the invoker to specify the following.

- Whether to map the table to a sequence of XML elements where the name of each top-level element is derived from the table name and represents a row in the table, or to map the table to an XML document with a single root element whose name is derived from the table name and to map each row to an element named <row>.
- The XML target namespace URI of the XML schema and data to be mapped (if the XML target namespace URI is specified as a zero-length string, then no XML namespace is added).
- Whether to map null values to absent elements, or whether to map them to elements that are marked with **xsi:nil="true"** .

4.11 Overview of mappings

- Whether to map the table into XML data, to map the table into an XML schema document, or both.

Some of the XML schema type definitions and element declarations may contain annotations to represent SQL metadata that is not directly relevant to XML. It is implementation-defined (IA100) whether these annotations are generated.

The rules of Subclause 9.11, “Mapping an SQL table to XML and an XML schema document”, are supported by the rules of Subclause 9.9, “Mapping an SQL table to XML schema data types”, and Subclause 9.10, “Mapping an SQL table to an XML element or a sequence of XML elements”.

4.11.11 Mapping an SQL schema to XML

Subclause 9.14, “Mapping an SQL schema to an XML document and an XML schema document”, defines a mapping between the tables of an SQL-schema and either or both of two documents: an XML document that represents the data in these tables, and an XML schema document that describes the first document.

NOTE 14 — This document specifies no syntax for invoking the mapping specified in Subclause 9.14, “Mapping an SQL schema to an XML document and an XML schema document”. This specification is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Only the XML visible tables of the schema for the user that invokes this mapping will be represented in these two XML documents. Only the XML visible columns of these tables for the user that invokes this mapping will be represented in these two XML documents.

This mapping allows the invoker to specify the following.

- Whether to map each table to a sequence of XML elements where the name of each top-level element is derived from the table name and represents a row in the table, or to map each table to a single XML element whose name is derived from the table name and to map each row to an element named `<row>`.
- The XML target namespace URI of the XML schema and data to be mapped (if the XML target namespace URI is specified as a zero-length string, then no XML namespace is added).
- Whether to map null values to absent elements, or whether to map them to elements that are marked with `xsi:nil="true"`.
- Whether to map the schema into XML data, to map the schema into an XML schema document, or both.

Some of the XML schema type definitions and element declarations may contain annotations to represent SQL metadata that is not directly relevant to XML. It is implementation-defined (IA100) whether these annotations are generated.

The SQL-schema mapping assumes an implementation-dependent (UA031) *repeatable ordering* when iterating over the XML visible tables in the SQL-schema. This allows generating the correct alignment of the table data with the element declarations in situations where the generated XML schema uses a sequence content model instead of an all group content model.

The rules of Subclause 9.14, “Mapping an SQL schema to an XML document and an XML schema document”, are supported by the rules of Subclause 9.12, “Mapping an SQL schema to XML schema data types”, and Subclause 9.13, “Mapping an SQL schema to an XML element”.

4.11.12 Mapping an SQL catalog to XML

Subclause 9.17, “Mapping an SQL catalog to an XML document and an XML schema document”, defines a mapping between the tables of an SQL catalog and either or both of two documents: an XML document that represents the data in these tables, and an XML schema document that describes the first document.

NOTE 15 — This document specifies no syntax for invoking the mapping specified in Subclause 9.17, “Mapping an SQL catalog to an XML document and an XML schema document”. This specification is intended to be used by applications and

referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Only the XML visible schemas of this catalog for the user that invokes this mapping will be represented in these two XML documents. Only the XML visible tables of these schemas for the user that invokes this mapping will be represented in these two XML documents. Only the XML visible columns of these tables for the user that invokes this mapping will be represented in these two XML documents.

This mapping allows the user that invokes this mapping to specify the following.

- Whether to map each table to a sequence of XML elements where the name of each top-level element is derived from the table name and represents a row in the table, or to map each table to a single XML element whose name is derived from the table name and each row is mapped to an element names `<row>`.
- The XML target namespace URI of the XML schema and data to be mapped (if the XML target namespace URI is specified as a zero-length string, then no XML namespace is added).
- Whether to map null values to absent elements, or whether to map them to elements that are marked with `xsi:nil="true"`.
- Whether to map the catalog into XML data, to map the catalog into an XML schema document, or both.

Some of the XML schema type definitions and element declarations may contain annotations to represent SQL metadata that is not directly relevant to XML. It is implementation-defined (IA100) whether these annotations are generated.

The rules of Subclause 9.17, “Mapping an SQL catalog to an XML document and an XML schema document”, are supported by the rules of Subclause 9.15, “Mapping an SQL catalog to XML schema data types”, and Subclause 9.16, “Mapping an SQL catalog to an XML element”.

5 Lexical elements

This Clause modifies Clause 5, “Lexical elements”, in ISO/IEC 9075-2.

5.1 <token> and <separator>

This Subclause modifies Subclause 5.2, “<token> and <separator>”, in ISO/IEC 9075-2.

Function

Specify lexical units (tokens and separators) that participate in SQL language.

Format

```

<reserved word> ::=
    !! All alternatives from ISO/IEC 9075-2

    | XML | XMLAGG | XMLATTRIBUTES | XMLBINARY | XMLCAST | XMLCOMMENT | XMLCONCAT
    | XMLDOCUMENT | XMLELEMENT | XMLEXISTS | XMLFOREST | XMLITERATE | XMLNAMESPACES
    | XMLPARSE | XMLPI | XMLQUERY | XMLSERIALIZE | XMLTABLE | XMLTEXT | XMLVALIDATE

<non-reserved word> ::=
    !! All alternatives from ISO/IEC 9075-2

    | ACCORDING
    | BASE64 | BOM
    | COLUMNS | CONTENT
    | DOCUMENT
    | ENCODING
    | HEX
    | ID | INDENT
    | LOCATION
    | NAMESPACE | NIL
    | PATH | PRESERVE
    | SEQUENCE | STRIP
    | UNTYPED | URI
    | VALID | VERSION
    | WHITESPACE
    | XMLDECLARATION | XMLSCHEMA
    
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

5.2 <literal>

This Subclause modifies Subclause 5.3, “<literal>”, in ISO/IEC 9075-2.

Function

Specify a non-null value.

Format

```
<upper-case hexit> ::=  
  <digit> | A | B | C | D | E | F
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

5.3 Names and identifiers

This Subclause modifies Subclause 5.4, “Names and identifiers”, in ISO/IEC 9075-2.

Function

Specify names.

Format

```
<registered XML schema name> ::=  
  <schema qualified name>
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after the last GR: A <registered XML schema name> identifies a registered XML schema.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6 Scalar expressions

This Clause modifies Clause 6, “Scalar expressions”, in ISO/IEC 9075-2.

6.1 <data type>

This Subclause modifies Subclause 6.1, “<data type>”, in ISO/IEC 9075-2.

Function

Specify a data type.

Format

```

<predefined type> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <XML type>

<XML type> ::=
    XML [ <left paren> <XML type modifier> <right paren> ]

<XML type modifier> ::=
    <primary XML type modifier>
    [ <left paren> <secondary XML type modifier> <right paren> ]

<primary XML type modifier> ::=
    DOCUMENT
    | CONTENT
    | SEQUENCE

<secondary XML type modifier> ::=
    ANY
    | UNTYPED
    | XMLSCHEMA <XML valid according to what> [ <XML valid element clause> ]
  
```

Syntax Rules

- 1) Insert after the last SR: XML specifies an XML data type.
- 2) Insert after the last SR: If an <XML type> does not specify <XML type modifier>, then it is implementation-defined (ID202) whether SEQUENCE, CONTENT(ANY), or CONTENT(UNTYPED) is implicit.
- 3) Insert after the last SR: Case:
 - a) If <primary XML type modifier> specifies SEQUENCE, then <secondary XML type modifier> shall not be specified.
 - b) Otherwise, if <secondary XML type modifier> is not specified, then it is implementation-defined (ID203) whether UNTYPED or ANY is implicit.

- 4) **Insert after the last SR:** If <secondary XML type modifier> specifies XMLSCHEMA, then let *RXS* be the indicated registered XML schema, let *ENSURI* be the indicated XML namespace, if any, and let *GEDSC* be the indicated global element declaration schema component, if any.

NOTE 16 — Indicated registered XML schema, indicated XML namespace, and indicated global element declaration schema component are defined in Subclause 11.5, “<XML valid according to clause>”.

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert after GR 24):** If <data type> is an <XML type>, then an XML type descriptor is created, including the following:
- The name of the data type (XML).
 - The primary XML type modifier described by the <primary XML type modifier> (DOCUMENT, CONTENT, or SEQUENCE).
 - The secondary XML type modifier described by the <secondary XML type modifier> (UNTYPED, ANY, or XMLSCHEMA), if any.
 - The registered XML schema descriptor of the indicated registered XML schema, if any.
 - The XML namespace URI of the indicated XML namespace, if any.
 - The XML NCName of the indicated global element declaration schema component, if any.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X010, “XML type”, conforming SQL language shall not contain an <XML type>.
- 2) **Insert after the last CR:** Without Feature X011, “Arrays of XML type”, conforming SQL language shall not contain an <array type> that is based on a <data type> that is either an XML type or a distinct type whose source type is an XML type.
- 3) **Insert after the last CR:** Without Feature X012, “Multisets of XML type”, conforming SQL language shall not contain a <multiset type> that is based on a <data type> that is either an XML type or a distinct type whose source type is an XML type.
- 4) **Insert after the last CR:** Without Feature X181, “XML(DOCUMENT(UNTYPED)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is DOCUMENT and <secondary XML type modifier> is UNTYPED.
- 5) **Insert after the last CR:** Without Feature X182, “XML(DOCUMENT(ANY)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is DOCUMENT and <secondary XML type modifier> is ANY.
- 6) **Insert after the last CR:** Without Feature X231, “XML(CONTENT(UNTYPED)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is CONTENT and <secondary XML type modifier> is UNTYPED.
- 7) **Insert after the last CR:** Without Feature X232, “XML(CONTENT(ANY)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is CONTENT and <secondary XML type modifier> is ANY.

6.1 <data type>

- 8) Insert after the last CR: Without Feature X191, “XML(DOCUMENT(XMLSCHEMA)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is DOCUMENT and <secondary XML type modifier> specifies XMLSCHEMA.
- 9) Insert after the last CR: Without Feature X192, “XML(CONTENT(XMLSCHEMA)) type”, conforming SQL language shall not contain an <XML type> whose <primary XML type modifier> is CONTENT and <secondary XML type modifier> specifies XMLSCHEMA.
- 10) Insert after the last CR: Without Feature X260, “XML type: ELEMENT clause”, conforming SQL language shall not contain an <XML type> that contains <XML valid element clause>.
- 11) Insert after the last CR: Without Feature X261, “XML type: NAMESPACE without ELEMENT clause”, conforming SQL language shall not contain an <XML type> that contains an <XML valid element clause> that does not contain an <XML valid element name specification>.
- 12) Insert after the last CR: Without Feature X263, “XML type: NO NAMESPACE with ELEMENT clause”, conforming SQL language shall not contain an <XML type> that contains an <XML valid element namespace specification> that contains NO NAMESPACE.
- 13) Insert after the last CR: Without Feature X264, “XML type: schema location”, conforming SQL language shall not contain an <XML type> that contains <XML valid schema location>.
- 14) Insert after the last CR: Without Feature X190, “XML(SEQUENCE) type”, conforming SQL language shall not contain an <XML type> whose <XML type modifier> is SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.2 <field definition>

This Subclause modifies Subclause 6.2, “<field definition>”, in ISO/IEC 9075-2.

Function

Define a field of a row type.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X015, “Fields of XML type”, conforming SQL language shall not contain a <field definition> that contains a <data type> that is based on either an XML type or a distinct type whose source type is an XML type.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.3 <value expression primary>

This Subclause modifies Subclause 6.3, “<value expression primary>”, in ISO/IEC 9075-2.

Function

Specify a value that is syntactically self-delimited.

Format

```
<non-parenthesized value expression primary> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <XML cast specification>
```

Syntax Rules

- 1) **Augment SR 1)** by adding “<XML cast specification>” to the list of simply contained BNF non-terminals.

Access Rules

No additional Access Rules.

General Rules

- 1) **Augment GR 1)** by adding “<XML cast specification>” to the list of simply contained BNF non-terminals.

Conformance Rules

No additional Conformance Rules.

6.4 <value specification> and <target specification>

This Subclause modifies Subclause 6.4, “<value specification> and <target specification>”, in ISO/IEC 9075-2.

Function

Specify one or more values, host parameters, SQL parameters, dynamic parameters, or host variables.

Format

```
<target specification> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <SQL parameter reference> <XML passing mechanism>  
    | <column reference> <XML passing mechanism>  
    | <target array element specification> <XML passing mechanism>
```

Syntax Rules

- 1) **Insert after the last SR:** If <target specification> *TS* contains <XML passing mechanism>, then the declared type of *TS* shall be an XML type.
- 2) **Insert after the last SR:** If the declared type of *TS* is an XML type and *TS* is not a <host parameter specification>, an <embedded variable specification>, or a <dynamic parameter specification>, and *TS* does not contain an <XML passing mechanism>, then it is implementation-defined (IA102) whether an <XML passing mechanism> of BY REF or BY VALUE is implicit.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

6.5 <case expression>

This Subclause modifies Subclause 6.12, “<case expression>”, in ISO/IEC 9075-2.

Function

Specify a conditional value.

Format

```
<when operand> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <XML content predicate part 2>  
    | <XML document predicate part 2>  
    | <XML valid predicate part 2>
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.6 <cast specification>

This Subclause modifies Subclause 6.13, “<cast specification>”, in ISO/IEC 9075-2.

Function

Specify a data conversion.

Format

```
<cast specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | CAST <left paren> <cast operand> AS <cast target>
      [ FORMAT <cast template> ]
      <XML passing mechanism>
      <right paren>
```

Syntax Rules

- 1) **Insert after SR 3):** If <XML passing mechanism> is specified, then <cast operand> shall be a <value expression> and both *SD* and *TD* shall be XML types.
- 2) **Insert after SR 3):** If *SD* and *TD* are both XML types and <XML passing mechanism> is not specified, then it is implementation-defined (ID204) whether BY REF or BY VALUE is implicit.
- 3) **Augment SR 7)** by adding “a new rightmost column” to the table in SR 7).

<i>SD</i>	<i>TD</i>
	XML
EN	N
AN	N
C	N
D	N
T	N
TS	N
YM	N
DT	N
BO	N
UDT	N
B	N
RT	N
CT	N
RW	N
JS	N

- 4) **Augment SR 7)** by adding “a new row” to the table in SR 7).

XML N N N N N N N N N N N N N N N M

Where:
XML = XML type

- 5) **Insert before SR 16):** If BY REF is specified or implied, then

Case:

- a) If *TD* is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then *SD* shall be either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)).
- b) If *TD* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then

Case:

- i) If the type descriptor of *TD* includes an XML namespace URI *N* and an XML NCName *EN* of a global element declaration schema component, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) such that the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* is identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD* and the type descriptor of *SD* includes an XML namespace URI that is identical to *N*, as defined by XML Namespaces, and an XML NCName that is equivalent to *EN*.
- ii) If the type descriptor of *TD* includes an XML namespace URI *N*, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) such that the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* is identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD* and the type descriptor of *SD* includes an XML namespace URI that is identical to *N*, as defined by XML Namespaces.
- iii) Otherwise, *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) such that the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* is identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert before GR 3: If *SD* and *TD* are both XML types, then:
 - a) Case:
 - i) If *TD* is XML(DOCUMENT(UNTYPED)), XML(DOCUMENT(ANY)), or XML(DOCUMENT(XMLSCHEMA)), and *SV* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, zero or more XQuery processing instruction nodes, then an exception condition is raised: *data exception — not an XML document (2200L)*.
 - ii) If *TD* is XML(CONTENT(UNTYPED)), XML(CONTENT(ANY)), or XML(CONTENT(XMLSCHEMA)), and *SV* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then an exception condition is raised: *data exception — not an XQuery document node (2200U)*.
 - b) Case:
 - i) If BY VALUE is specified or implied, then

Case:

 - 1) If *TD* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then let *S* be the <secondary XML type modifier> contained in <cast target>.
 - A) Case:
 - I) If *TD* is XML(DOCUMENT(XMLSCHEMA)), then let *DCS* be DOCUMENT.

- II) Otherwise, let *DCS* be CONTENT.
 - B) *TV* is the result of

```
XMLVALIDATE( DCS VE ACCORDING TO S )
```
 - 2) If *TD* is either XML(DOCUMENT(ANY)), XML(CONTENT(ANY)), or XML(SEQUENCE), then the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with *SV* as *VALUE*; let *TV* be the *COPY* returned from the application of those General Rules.
 - 3) Otherwise, the General Rules of Subclause 10.21, “Constructing an unvalidated XQuery document node”, are applied with *SV* as *XQUERYDOCNODE*; let *TV* be the *UNVALIDATEDDOCNODE* returned from the application of those General Rules.
- ii) Otherwise, *TV* is *SV*.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.7 <XML cast specification>

Function

Specify a data conversion whose source or target type is an XML type.

Format

```
<XML cast specification> ::=  
  XMLCAST <left paren> <XML cast operand> AS  
    <XML cast target> [ <XML passing mechanism> ] <right paren>  
  
<XML cast operand> ::=  
  <value expression>  
  | <implicitly typed value specification>  
  
<XML cast target> ::=  
  <domain name>  
  | <data type>
```

Syntax Rules

- 1) Case:
 - a) If the <XML cast specification> is contained within the scope of an <XML binary encoding>, then let *XBE* be the <XML binary encoding> with innermost scope that contains the <XML cast specification>.
 - b) Otherwise, let *XBE* be an implementation-defined (ID201) <XML binary encoding>.
- 2) Case:
 - a) If *XBE* specifies BASE64, then let *ENC* be an indication that binary strings are to be encoded in base64.
 - b) Otherwise, let *ENC* be an indication that binary strings are to be encoded in hex.
- 3) Case:
 - a) If <XML cast target> is <domain name>, then let *TD* be the data type of the specified domain.
 - b) Otherwise, let *TD* be the data type identified by <data type>. <data type> shall not contain a <collate clause>.
- 4) At least one of the following shall be true:
 - a) *TD* is an XML type.
 - b) The <XML cast operand> is a <value expression> whose declared type is an XML type.
- 5) *TD* shall not be a collection type, a distinct type whose source type is a collection type, a row type, a structured type or a reference type.
- 6) The declared type of the result of the <XML cast specification> is *TD*.
- 7) If *TD* is XML(DOCUMENT(UNTYPED)), XML(DOCUMENT(ANY)), XML(DOCUMENT(XMLSCHEMA)), or XML(CONTENT(XMLSCHEMA)), then the <XML cast operand> shall be either NULL or a <value expression> whose declared type is an XML type.

- 8) If the <XML cast operand> is a <value expression> *VE*, then let *SD* be the declared type of *VE*.
- 9) If <XML passing mechanism> is specified, then:
- <XML cast operand> shall be a <value expression>.
 - SD* and *TD* shall both be XML types.
- 10) If the <XML cast operand> is a <value expression> *VE*, then
Case:
- If *VE* simply contains a <dynamic parameter specification> *DPS*, then the <XML cast specification> is equivalent to

```
CAST ( DPS AS TD )
```
 - Otherwise:
 - SD* shall not be a collection type, a distinct type whose source type is a collection type, a row type, a structured type or a reference type.
 - If *SD* and *TD* are both XML types, then:
 - If <XML passing mechanism> is not specified, then it is implementation-defined (ID204) whether BY REF or BY VALUE is implicit.
 - Let *XPM* be the implicit or explicit <XML passing mechanism>.
 - The <XML cast specification> is equivalent to

```
CAST ( VE AS TD XPM )
```
- 11) If <XML cast operand> is an <implicitly typed value specification> *ITVS*, then the <XML cast specification> is equivalent to

```
CAST ( ITVS AS TD )
```
- 12) If *TD* is character string type, then the declared type collation of the <XML cast specification> is the character set collation of the character set of *TD* and its collation derivation is *implicit*.
- 13) If <XML cast target> is <domain name>, then let *D* be the domain identified by the <domain name>. The schema identified by the explicit or implicit qualifier of the <domain name> shall include the descriptor of *D*.
- 14) Case:
- If the <XML cast target> is a <domain name>, then let *SQLT* be the <data type> of the identified domain.
 - If the <XML cast target> identifies a distinct type, then let *SQLT* be the source type of the distinct type.
 - Otherwise, let *SQLT* be <data type>.
- 15) Case:
- If *SQLT* is a character string type, then let *XT* be **xs:string**.
 - If *SQLT* is a binary string type, then
Case:

6.7 <XML cast specification>

- i) If *XBE* specifies BASE64, then let *XT* be **xs:base64Binary**.
 - ii) Otherwise, let *XT* be **xs:hexBinary**.
- c) If *SQLT* is an exact numeric type, then
- Case:
- i) If the type designator of *SQLT* is DECIMAL or NUMERIC, then let *XT* be **xs:decimal**.
 - ii) If the type designator of *SQLT* is SMALLINT, INTEGER, or BIGINT, then let *XT* be **xs:integer**.
- d) If *SQLT* is an approximate numeric type, then let *XT* be **xs:double**.
- e) If *SQLT* is a datetime type, then
- Case:
- i) If the type designator of *SQLT* is DATE, then let *XT* be **xs:date**.
 - ii) If the type designator of *SQLT* is TIME WITH TIME ZONE, then let *XT* be **xs:time**.
 - iii) If the type designator of *SQLT* is TIME WITHOUT TIME ZONE, then let *XT* be **xs:time**.
 - iv) If the type designator of *SQLT* is TIMESTAMP WITH TIME ZONE, then let *XT* be **xs:dateTime**.
 - v) If the type designator of *SQLT* is TIMESTAMP WITHOUT TIME ZONE, then let *XT* be **xs:dateTime**.
- f) Otherwise, the General Rules of Subclause 9.5, “Mapping SQL data types to XML schema data types”, are applied with *SQLT* as *SQLTYPE*, *ENC* as *ENCODING*, and “absent” as *NULLS*; let *XT* be the *SCHEMA TYPE* returned from the application of those General Rules.

Access Rules

- 1) If *TD* is a distinct type, then let *STD* be the source type of *TD*, and let *AVE* be an arbitrary <value expression> of declared type *STD*. The following shall be valid according to the Syntax Rules of Subclause 6.6, “<cast specification>”:

CAST (*AVE* AS *TD*)

NOTE 17 — As specified in ISO/IEC 9075-1, Subclause 6.3.3.3, “Rule evaluation order”, evaluation of Syntax Rules, Access Rules, and Conformance Rules is all performed concurrently.

- 2) If *SD* is a distinct type, then let *SSD* be the source type of *SD*. The following shall be valid according to the Syntax Rules of Subclause 6.6, “<cast specification>”:

CAST (*VE* AS *SSD*)

- 3) If <XML cast target> is a <domain name>, then

Case:

- a) If the <XML cast specification> is contained, without an intervening <SQL routine spec> that specifies SQL SECURITY INVOKER, in an <SQL schema statement>, then the applicable privileges of the <authorization identifier> that owns the containing SQL-schema shall include USAGE on the domain identified by the <domain name>.
- b) Otherwise, the current privileges shall include USAGE on the domain identified by the <domain name>.

General Rules

- 1) Let V be the value of the <XML cast operand> simply contained in the <XML cast specification>.
- 2) If V is the null value, then the result of the <XML cast specification> is the null value, and no further General Rules of this Subclause are applied.
- 3) If TD is an XML type, then:

a) The General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with V as $SQLVALUE$, ENC as $ENCODING$, “absent” as $NULLS$, and $True$ as $CHARMAPPING$; let $XMLV$ be the $XMLVALUE$ returned from the application of those General Rules.

b) Let $TEMPV$ be the result of

```
XMLPARSE (CONTENT XMLV PRESERVE WHITESPACE)
```

c) If TD is XML(CONTENT(UNTYPED)) or XML(CONTENT(ANY)), then let TV be $TEMPV$.

d) If TD is XML(SEQUENCE), then:

i) The General Rules of Subclause 9.5, “Mapping SQL data types to XML schema data types”, are applied with SD as $SQLTYPE$, ENC as $ENCODING$, and “absent” as $NULLS$; let XST be the $SCHEMA TYPE$ returned from the application of those General Rules.

ii) Case:

1) If SD is a year-month interval type, then let $XSBT$ be the XQuery simple type **xs:yearMonthDuration**.

2) If SD is a day-time interval type, then let $XSBT$ be the XQuery simple type **xs:dayTimeDuration**.

3) If XST is an XML schema built-in data type, then let $XSBT$ be XST .

4) If XST is an XML schema atomic type, then let $XSBT$ be the XML schema built-in data type from which XST is derived.

iii) Let $XSBTN$ be an XML 1.1 QName for $XSBT$.

iv) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the null value as $NONTERMINAL$; let XSC be the $STATICCONTEXT$ returned from the application of those Syntax Rules. The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let XDC be the $DYNAMICCONTEXT$ returned from the application of those General Rules.

NOTE 18 — XSC is an XQuery static context. XDC is an XQuery dynamic context.

v) Let XSC and XDC be augmented with an XQuery variable $\$TEMP$, whose XQuery formal type notation is “document { text ? }”, and whose value is $TEMPV$.

vi) Case:

1) If the SQL-implementation supports Feature X211, “XML 1.1 support”, then let TV be the result of the XQuery evaluation with XML 1.1 lexical rules, using XSC and XDC as the XQuery expression context, of the XQuery expression

```
 $\$TEMP$  cast as  $XSBTN$ 
```

If this XQuery evaluation raises an XQuery error, then an exception condition is raised: *XQuery error (10000)*.

- 2) Otherwise, let *TV* be the result of the XQuery evaluation with XML 1.0 lexical rules, using *XSC* and *XDC* as the XQuery expression context, of the XQuery expression

```
$TEMP cast as XSBTN
```

If this XQuery evaluation raises an XQuery error, then an exception condition is raised: *XQuery error (10000)*.

- e) The result of the <XML cast specification> is *TV*.

- 4) If *SD* is an XML type and *TD* is not an XML type, then:

- a) The General Rules of Subclause 10.19, “Removing XQuery document nodes from an XQuery sequence”, are applied with *v* as *SEQUENCE*; let *xv* be the *RESULT* returned from the application of those General Rules.

- b) Let *AV* be the result of applying the XQuery function `fn:data()` to *xv*.

- c) If *AV* is the empty sequence, then the result is the null value and no further General Rules of this Subclause are applied.

- d) Let *XMLT* be an XML 1.1 QName for *XT*.

NOTE 19 — *XMLT* can be in one of the built-in namespaces denoted by the prefix *xs*, or it can be in an implementation-dependent (UV014) namespace, not necessarily available to the user.

- e) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the null value as *NONTERMINAL*; let *XSC* be the *STATICCONTEXT* returned from the application of those Syntax Rules.

NOTE 20 — *XSC* is an XQuery static context.

- f) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *XDC* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 21 — *XDC* is an XQuery dynamic context.

- g) Let *XSC* and *XDC* be augmented with an XQuery variable *\$TEMP* whose XQuery formal type notation is “*xs:anyAtomicType+*” and whose value is *AV*.

- h) Let *BV* be the result of the XQuery evaluation with XML 1.1 lexical rules, using *XSC* and *XDC* as the XQuery expression context, of the XQuery expression

Case:

- i) If *SQLT* is *TIMESTAMP WITHOUT TIME ZONE*, then

```
fn:adjust-dateTime-to-timezone(
  fn:adjust-dateTime-to-timezone( $TEMP cast as xs:dateTime,
    xs:dayTimeDuration("PT0H")
  ), ( ) cast as XMLT
```

- ii) If *SQLT* is *TIME WITHOUT TIME ZONE*, then

```
fn:adjust-time-to-timezone(
  fn:adjust-time-to-timezone( $TEMP cast as xs:time,
    xs:dayTimeDuration("PT0H")
  ), ( ) cast as XMLT
```

- iii) If *SQLT* is *DATE*, then

```
fn:adjust-date-to-timezone(  
  fn:adjust-date-to-timezone( $TEMP cast as xs:date,  
    xs:dayTimeDuration("PT0H")  
  ), ( ) ) cast as XMLT
```

iv) Otherwise,

\$TEMP cast as XMLT

If this XQuery evaluation raises an XQuery error, then an exception condition is raised: *XQuery error (10000)*.

i) **BV** is an XQuery atomic value.

NOTE 22 — The following rules are based on the fact that the value space of XQuery atomic types is the same as the value space of corresponding SQL types. That is, it is possible to treat **BV** as a value of an SQL type. For example, if **BV** is of type **xs:integer**, then **BV** is a (mathematical) integer, and, as such, it can also be the value of an exact numeric type with scale 0 (zero). See Subclause 4.11.8, "Mapping XQuery atomic values to SQL values".

Case:

- i) If **XT** is **xs:string** or derived from **xs:string**, then let *A* be an arbitrary <literal> of character string type whose character repertoire is Unicode and whose value is **BV**.
- ii) If **XT** is **xs:hexBinary** or derived from **xs:hexBinary**, then let *A* be an arbitrary <literal> of binary string type whose value is **BV** decoded as hex.
- iii) If **XT** is **xs:base64Binary** or is derived from **xs:base64Binary**, then let *A* be an arbitrary <literal> of binary string type whose value is **BV** decoded as base64.
- iv) If **XT** is **xs:decimal** or derived from **xs:decimal**, then let *A* be an arbitrary <literal> of exact numeric type whose value is **BV**.
- v) If **XT** is **xs:float** or **xs:double**, or derived from **xs:float** or **xs:double**, then:
 - 1) If **AV** is INF, -INF, or NaN, then an exception condition is raised: *data exception — numeric value out of range (22003)*.
 - 2) Let *A* be an arbitrary <literal> of approximate numeric type whose value is **BV**.
- vi) If **XT** is **xs:date** or derived from **xs:date**, then:
 - 1) If the XQuery datetime normalized value component of **AV** is not positive, then an exception condition is raised: *data exception — invalid datetime format (22007)*.
 - 2) Let *A* be an arbitrary <literal> of declared type *SQLT* whose value is **BV**.
- vii) If **XT** is **xs:dateTime** or derived from **xs:dateTime**, then:
 - 1) If the XQuery datetime normalized value component of **AV** is not positive, then an exception condition is raised: *data exception — invalid datetime format (22007)*.
 - 2) If *SQLT* is **TIMESTAMP WITHOUT TIME ZONE**, then let *A* be an arbitrary <literal> of declared type **TIMESTAMP WITHOUT TIME ZONE** whose value is **BV**.
 - 3) If *SQLT* is **TIMESTAMP WITH TIME ZONE**, then

Case:

- A) If the XQuery datetime time zone component of **AV** is the empty XQuery sequence, then:

- I) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the null value as *NONTERMINAL*; let *xsc2* be the *STATICCONTEXT* returned from the application of those Syntax Rules.

NOTE 23 — *xsc2* is an XQuery static context.

- II) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *xdc2* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 24 — *xdc2* is an XQuery dynamic context.

- III) Let *XSC2* and *XDC2* be augmented with an XQuery variable \$TEMP whose XQuery formal type notation is “*xs:anyAtomicType*” and whose value is *BV*.

- IV) Let *CV* be the result of the XQuery evaluation with XML 1.1 lexical rules, using *XSC2* and *XDC2* as the XQuery expression context, of the XQuery expression

```
fn:adjust-dateTime-to-timezone(  
  $TEMP cast as xs:dateTime,  
  xs:dayTimeDuration("PT0H") ) cast as XMLT
```

- V) Let *A* be an arbitrary <literal> of declared type *TIMESTAMP WITH TIME ZONE* whose value is *CV*.

- B) Otherwise, let *A* be an arbitrary <literal> of declared type *TIMESTAMP WITH TIME ZONE* whose value is *BV*.

- viii) If *XT* is *xs:time* or derived from *xs:time*, then

Case:

- 1) If *SQLT* is *TIME WITHOUT TIME ZONE*, then let *A* be an arbitrary <literal> of declared type *TIME WITHOUT TIME ZONE* whose value is the XQuery datetime normalized value of *BV*.
- 2) If *SQLT* is *TIME WITH TIME ZONE*, then

Case:

- A) If the XQuery datetime time zone component of *AV* is the empty XQuery sequence, then:

- I) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the null value as *NONTERMINAL*; let *xsc3* be the *STATICCONTEXT* returned from the application of those Syntax Rules.

NOTE 25 — *xsc3* is an XQuery static context.

- II) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *xdc3* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 26 — *xdc3* is an XQuery dynamic context.

- III) Let *XSC3* and *XDC3* be augmented with an XQuery variable \$TEMP whose XQuery formal type notation is “*xs:anyAtomicType*” and whose value is *BV*.

- IV) Let **CV** be the result of the XQuery evaluation with XML 1.1 lexical rules, using *XSC3* and *XDC3* as the XQuery expression context, of the XQuery expression

```
fn:adjust-time-to-timezone(  
  $TEMP cast as xs:time,  
  xs:dayTimeDuration("PT0H") ) cast as XMLT
```

- V) Let *A* be an arbitrary <literal> of declared type TIME WITH TIME ZONE whose value is **CV** (more precisely, whose UTC component is the XQuery datetime normalized value of **CV** and whose time zone component is the XQuery datetime time zone component of **CV**).
- B) Otherwise, let *A* be an arbitrary <literal> of declared type TIME WITH TIME ZONE whose value is **BV** (more precisely, whose UTC component is the XQuery datetime normalized value of **BV** and whose time zone component is the XQuery datetime time zone component of **BV**).
- ix) If **XT** is **xs:yearMonthDuration** or derived from **xs:yearMonthDuration**, then let *A* be an arbitrary <literal> of year-month interval type whose value is **BV**.
- x) If **XT** is **xs:dayTimeDuration** or derived from **xs:dayTimeDuration**, then let *A* be an arbitrary <literal> of day-time interval type whose value is **BV**.
- xi) If **XT** is **xs:boolean** or derived from **xs:boolean**, then let *A* be an arbitrary <literal> of declared type BOOLEAN whose value is **BV**.
- j) The result of the <XML cast specification> is the result of

CAST (*A* AS *SQLT*)

NOTE 27 — This can raise a warning or an exception condition if the value of *A* does not conform to constraints of *SQLT*. It can also perform rounding or truncation, and so forth, in order to produce a value of type *SQLT*.

Conformance Rules

- 1) Without Feature X025, "XMLCast", conforming SQL language shall not contain an <XML cast specification>.

6.8 <value expression>

This Subclause modifies Subclause 6.29, “<value expression>”, in ISO/IEC 9075-2.

Function

Specify a value.

Format

```
<common value expression> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <XML value expression>
```

Syntax Rules

- 1) [Augment SR 2\)](#) by adding “<XML value expression>” to the list of BNF non-terminals.

Access Rules

No additional Access Rules.

General Rules

- 1) [Augment GR 2\)](#) by adding “<XML value expression>” to the list of immediately contained BNF non-terminals.

Conformance Rules

No additional Conformance Rules.

6.9 <string value function>

This Subclause modifies Subclause 6.33, “<string value function>”, in ISO/IEC 9075-2.

Function

Specify a function yielding a value of type character string or binary string.

Format

```
<character value function> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <XML character string serialization>  
  
<XML character string serialization> ::=  
    XMLSERIALIZE <left paren> [ <document or content> ]  
    <XML value expression> AS <data type>  
    [ <XML serialize bom> ]  
    [ <XML serialize version> ]  
    [ <XML declaration option> ]  
    [ <XML serialize indent> ]  
    <right paren>  
  
<XML serialize version> ::=  
    VERSION <character string literal>  
  
<XML serialize bom> ::=  
    WITH [ NO ] BOM  
  
<XML declaration option> ::=  
    INCLUDING XMLDECLARATION  
    | EXCLUDING XMLDECLARATION  
  
<XML serialize indent> ::=  
    [ NO ] INDENT  
  
<document or content> ::=  
    DOCUMENT  
    | CONTENT  
  
<binary value function> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <XML binary string serialization>  
  
<XML binary string serialization> ::=  
    XMLSERIALIZE <left paren> [ <document or content> ]  
    <XML value expression> AS <data type>  
    [ ENCODING <XML encoding specification> ]  
    [ <XML serialize bom> ]  
    [ <XML serialize version> ]  
    [ <XML declaration option> ]  
    [ <XML serialize indent> ]  
    <right paren>  
  
<XML encoding specification> ::=  
    <XML encoding name>  
  
<XML encoding name> ::=  
    <SQL language identifier>
```

Syntax Rules

- 1) **Augment SR 2)** by adding “<XML character string serialization>” to the list of immediately contained BNF non-terminals.
- 2) **Insert after the last SR:** If <XML character string serialization> is specified, then:
 - a) If <document or content> is not specified, then a <document or content> that specifies CONTENT is implicit.
 - b) The <data type> shall be a character string type. The declared type of <XML character string serialization> is <data type>.
 - c) The <character string literal> immediately contained in <XML serialize version> shall be '1.0' or '1.1', or it shall identify some successor to XML 1.0 and XML 1.1.
 - d) If <XML serialize version> is not specified, then an implementation-defined (ID205) <XML serialize version> is implicit.
- 3) **Augment SR 20)** by adding “<XML binary string serialization>” to the list of immediately contained BNF non-terminals.
- 4) **Insert after the last SR:** If <XML binary string serialization> is specified, then:
 - a) If <document or content> is not specified, then a <document or content> that specifies CONTENT is implicit.
 - b) The <data type> shall be a binary string type.
 - c) The declared type of <XML binary string serialization> is <data type>.
 - d) If <XML encoding specification> is not specified, then an implementation-defined (ID206) <XML encoding name> is implicit.
 - e) The supported <XML encoding name>s are implementation-defined (IA101).
 - f) The <character string literal> immediately contained in <XML serialize version> shall be '1.0' or '1.1', or it shall identify some successor to XML 1.0 and XML 1.1.
 - g) If <XML serialize version> is not specified, then an implementation-defined (ID205) <XML serialize version> is implicit.

Access Rules

No additional Access Rules.

General Rules

- 1) **Augment GR 2)** by adding “<XML character string serialization>” to the list of immediately contained BNF non-terminals.
- 2) **Insert after the last GR:** If <XML character string serialization> is specified, then:
 - a) Let *DCS* be the explicit or implicit <document or content>.
 - b) Let *XMLV* be the value of the <XML value expression>.
 - c) Let *DT* be the <data type>.
 - d) Let *CS* be the character set of *DT*.

- e) Case:
- i) If <XML serialize bom> is specified, then
Case:
 - 1) If WITH BOM is specified, then let *B* be True.
 - 2) Otherwise, let *B* be False.
 - ii) Otherwise, let *B* be Unknown.
- f) Let *VER* be the <string value expression> simply contained in the explicit or implicit <XML serialize version>.
- g) Case:
- i) If <XML declaration option> is specified and specifies INCLUDING XMLDECLARATION, then let *DECL* be True.
 - ii) If <XML declaration option> is specified and specifies EXCLUDING XMLDECLARATION, then let *DECL* be False.
 - iii) Otherwise, let *DECL* be Unknown.
- h) Case:
- i) If <XML serialize indent> is specified and does not contain NO, then let *IND* be True.
 - ii) Otherwise, let *IND* be False.
- i) The General Rules of Subclause 10.17, “Serialization of an XML value”, are applied with *XMLV* as *VALUE*, *DCS* as *SYNTAX*, *DT* as *TYPE*, *CS* as *ENCODING*, *B* as *BOM*, *VER* as *VERSION*, *DECL* as *XMLDECLARATION*, and *IND* as *INDENT*; let result of <XML character string serialization> be the *SERIALIZATION* returned from the application of those General Rules
- 3) **Augment GR 16)** by adding “<XML binary string serialization>” to the list of immediately contained BNF non-terminals.
- 4) **Insert after the last GR:** If <XML binary string serialization> is specified, then:
- a) Let *DCS* be the explicit or implicit <document or content>.
 - b) Let *XMLV* be the value of the <XML value expression>.
 - c) Let *DT* be the <data type>.
 - d) Let *XEN* be the <XML encoding name>.
 - e) Case:
 - i) If <XML serialize bom> is specified, then
Case:
 - 1) If WITH BOM is specified, then let *B* be True.
 - 2) Otherwise, let *B* be False.
 - ii) Otherwise, let *B* be Unknown.
 - f) Let *VER* be the <string value expression> simply contained in the explicit or implicit <XML serialize version>.
 - g) Case:

6.9 <string value function>

- i) If <XML declaration option> is specified and specifies INCLUDING XMLDECLARATION, then let *DECL* be *True*.
 - ii) If <XML declaration option> is specified and specifies EXCLUDING XMLDECLARATION, then let *DECL* be *False*.
 - iii) Otherwise, let *DECL* be *Unknown*.
- h) Case:
- i) If <XML serialize indent> is specified and does not contain NO, then let *IND* be *True*.
 - ii) Otherwise, let *IND* be *False*.
- i) The General Rules of Subclause 10.17, “Serialization of an XML value”, are applied with *XMLV* as *VALUE*, *DCS* as *SYNTAX*, *DT* as *TYPE*, *XEN* as *ENCODING*, *B* as *BOM*, *VER* as *VERSION*, *DECL* as *XMLDECLARATION*, and *IND* as *INDENT*; let result of <XML binary string serialization> be the *SERIALIZATION* returned from the application of those General Rules

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X070, “XMLSerialize: character string serialization and CONTENT option”, conforming SQL language shall not contain an <XML character string serialization> that immediately contains a <document or content> that is CONTENT.
- 2) **Insert after the last CR:** Without Feature X071, “XMLSerialize: character string serialization and DOCUMENT option”, conforming SQL language shall not contain an <XML character string serialization> that immediately contains a <document or content> that is DOCUMENT.
- 3) **Insert after the last CR:** Without Feature X072, “XMLSerialize: character string serialization”, conforming SQL language shall not contain an <XML character string serialization>.
- 4) **Insert after the last CR:** Without Feature X073, “XMLSerialize: binary string serialization and CONTENT option”, conforming SQL language shall not contain an <XML binary string serialization> that immediately contains a <document or content> that is CONTENT.
- 5) **Insert after the last CR:** Without Feature X074, “XMLSerialize: binary string serialization and DOCUMENT option”, conforming SQL language shall not contain an <XML binary string serialization> that immediately contains a <document or content> that is DOCUMENT.
- 6) **Insert after the last CR:** Without Feature X075, “XMLSerialize: binary string serialization”, conforming SQL language shall not contain an <XML binary string serialization>.
- 7) **Insert after the last CR:** Without Feature X076, “XMLSerialize: VERSION”, in conforming SQL language, <XML character string serialization> shall not contain VERSION.
- 8) **Insert after the last CR:** Without Feature X076, “XMLSerialize: VERSION”, in conforming SQL language, <XML binary string serialization> shall not contain VERSION.
- 9) **Insert after the last CR:** Without Feature X077, “XMLSerialize: explicit ENCODING option”, conforming SQL language shall not contain an <XML binary string serialization> that contains ENCODING.
- 10) **Insert after the last CR:** Without Feature X078, “XMLSerialize: explicit XML declaration”, in conforming SQL language, <XML character string serialization> shall not contain XMLDECLARATION.
- 11) **Insert after the last CR:** Without Feature X078, “XMLSerialize: explicit XML declaration”, in conforming SQL language, <XML binary string serialization> shall not contain XMLDECLARATION.
- 12) **Insert after the last CR:** Without Feature X068, “XMLSerialize: BOM”, in conforming SQL language, <XML serialize bom> shall not be specified.

- 13) Insert after the last CR: Without Feature X069, “XMLSerialize: INDENT”, in conforming SQL language, <XML serialize indent> shall not be specified.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.10 <XML value expression>

Function

Specify an XML value.

Format

```
<XML value expression> ::=  
  <XML primary>
```

```
<XML primary> ::=  
  <value expression primary>  
  | <XML value function>
```

Syntax Rules

- 1) The declared type of the <value expression primary> immediately contained in <XML primary> shall be an XML type.
- 2) The declared type of <XML value expression> is the declared type of the simply contained <value expression primary> or <XML value function>.

Access Rules

None.

General Rules

- 1) The value of <XML value expression> is the value of the simply contained <value expression primary> or <XML value function>.

Conformance Rules

- 1) Without Feature X010, "XML type", conforming SQL language shall not contain an <XML value expression>.

6.11 <XML value function>

Function

Specify a function that yields a value of type XML.

Format

```
<XML value function> ::=  
  <XML comment>  
  | <XML concatenation>  
  | <XML document>  
  | <XML element>  
  | <XML forest>  
  | <XML parse>  
  | <XML PI>  
  | <XML query>  
  | <XML text>  
  | <XML validate>
```

Syntax Rules

- 1) The declared type of <XML value function> is the declared type of the immediately contained <XML comment>, <XML concatenation>, <XML document>, <XML element>, <XML forest>, <XML parse>, <XML PI>, <XML query>, <XML text>, or <XML validate>.

Access Rules

None.

General Rules

- 1) The result of an <XML value function> is the XML value of the immediately contained <XML comment>, <XML concatenation>, <XML document>, <XML element>, <XML forest>, <XML parse>, <XML PI>, <XML query>, <XML text>, or <XML validate>.

Conformance Rules

- 1) Without Feature X010, “XML type”, conforming SQL language shall not contain an <XML value function>.

6.12 <XML comment>

Function

Generate an XML value with a single XQuery comment node, possibly as a child of an XQuery document node.

Format

```
<XML comment> ::=  
  XMLCOMMENT <left paren> <character value expression>  
    [ <XML returning clause> ] <right paren>
```

Syntax Rules

- 1) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 2) Let *SVE* be the <character value expression>.
- 3) Case:

- a) If RETURNING CONTENT is specified or implied, then <XML comment> is equivalent to

```
XMLDOCUMENT ( XMLCOMMENT ( SVE RETURNING SEQUENCE ) RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML comment> is XML(SEQUENCE).

NOTE 28 — If RETURNING CONTENT is specified or implied, then the declared type of <XML comment> is effectively established by the Syntax Rules of Subclause 6.14, “<XML document>”.

Access Rules

None.

General Rules

- 1) Let *SV* be the value of *SVE*.
- 2) If *SV* is the null value, then the result of <XML comment> is the null value and no further General Rules of this Subclause are applied.
- 3) If the value of

```
'<!--' || SV || '-->'
```

does not conform to rule [15], “comment”, of XML, then an exception condition is raised: *data exception — invalid comment (2200S)*.

- 4) Let *xcti* be an XQuery comment node with the following properties:
 - a) The value of the **content** property is the value of *SV*, converted to Unicode using the implementation-defined (IA091) mapping from the character set of *SV* to Unicode.
 - b) The value of the **parent** property is set to **empty**.
- 5) The result of the <XML comment> is the XQuery sequence consisting of one node, *xcti*.

Conformance Rules

- 1) Without Feature X036, “XMLComment”, conforming SQL language shall not contain an <XML comment>.
- 2) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML comment> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 3) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML comment> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.13 <XML concatenation>

Function

Concatenate a list of XML values.

Format

```
<XML concatenation> ::=  
  XMLCONCAT <left paren> <XML value expression>  
    { <comma> <XML value expression> }...  
  [ <XML returning clause> ] <right paren>
```

Syntax Rules

- 1) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 2) Let N be the number of <XML value expression>s simply contained in <XML concatenation>. Let XVE_i , $1 \text{ (one)} \leq i \leq N$, be the i -th <XML value expression> and let T_i be the declared type of XVE_i .
- 3) Case:
 - a) If RETURNING CONTENT is specified or implied, then the declared type of <XML concatenation> is
Case:
 - i) If, for all i , $1 \text{ (one)} \leq i \leq N$, T_i is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then XML(CONTENT(UNTYPED)).
 - ii) If there exists a registered XML schema S and a global element declaration schema component E such that, for all i , $1 \text{ (one)} \leq i < N$, T_i is XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI NS that is identical to the XML namespace URI of E , as defined by XML Namespaces, and an XML NCName EN that is equivalent to the XML NCName of E , then XML(CONTENT(XMLSCHEMA)), whose XML type descriptor includes the registered XML schema descriptor of S and the XML namespace URI NS and the XML NCName EN .
 - iii) If there exists a registered XML schema S and an XML namespace URI NS such that, for all i , $1 \text{ (one)} \leq i < N$, T_i is XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI that is identical to NS , as defined by XML Namespaces, then XML(CONTENT(XMLSCHEMA)), whose XML type descriptor includes the registered XML schema descriptor of S and the XML namespace URI NS .
 - iv) If there exists a registered XML schema S such that, for all i , $1 \text{ (one)} \leq i < N$, T_i is XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S , then XML(CONTENT(XMLSCHEMA)), whose XML type descriptor includes the registered XML schema descriptor of S .
 - v) Otherwise, XML(CONTENT(ANY)).

- b) Otherwise, the declared type of <XML concatenation> is XML(SEQUENCE).
- 4) If RETURNING CONTENT is specified or implied, then:
 - a) Let RT be the declared type of <XML concatenation>.
 - b) <XML concatenation> is equivalent to

```
CAST (  
  XMLDOCUMENT (  
    XMLCONCAT (  $XVE_1$ ,  $XVE_2$ , . . . ,  $XVE_N$  RETURNING SEQUENCE )  
    RETURNING CONTENT )  
  AS  $RT$  )
```

Access Rules

None.

General Rules

- 1) For all i , $1 \text{ (one)} \leq i \leq N$, let XV_i be the results of XVE_i .
- 2) Let R_0 be the null value.
- 3) For all i , $1 \text{ (one)} \leq i \leq N$, the General Rules of Subclause 10.16, “Concatenation of two XML values”, are applied with R_{i-1} as *FIRSTVAL* and XV_i as *SECONDVAL*; let R_i be the *CONCAT* returned from the application of those General Rules.
- 4) The result of <XML concatenation> is R_N .

Conformance Rules

- 1) Without Feature X020, “XMLConcat”, conforming SQL language shall not contain an <XML concatenation>.
- 2) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML concatenation> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 3) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML concatenation> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

6.14 <XML document>

Function

Generate an XML value with a single XQuery document node.

Format

```
<XML document> ::=
  XMLDOCUMENT <left paren> <XML value expression>
  [ <XML returning clause> ] <right paren>
```

Syntax Rules

- 1) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 2) Let *XVE* be the <XML value expression> simply contained in the <XML document>.
- 3) Case:
 - a) If RETURNING CONTENT is specified or implied, then it is implementation-defined (IA107) whether the declared type of <XML document> is XML(CONTENT(UNTYPED)) or XML(CONTENT(ANY)).
 - b) Otherwise, the declared type of <XML document> is XML(SEQUENCE).

Access Rules

None.

General Rules

- 1) Let *XV* be the value of *XVE*.
- 2) If *XV* is the null value, then the result of <XML document> is the null value and no further General Rules of this Subclause are applied.
- 3) The Syntax Rules of Subclause 10.23, "Determination of an XQuery formal type notation", are applied with *XV* as *SOURCE* and *False* as *CONTEXT*; let *xvft* be the *FORMALTYPE* returned from the application of those Syntax Rules.
- 4) The Syntax Rules of Subclause 10.22, "Creation of an XQuery expression context", are applied with the null value as *NONTERMINAL*; let *xsc* be the *STATICCONTEXT* returned from the application of those Syntax Rules.

NOTE 29 — *xsc* is an XQuery static context.

- 5) The **construction mode** component of *xsc* is set to **preserve**.
- 6) The General Rules of Subclause 10.22, "Creation of an XQuery expression context", are applied; let *xdc* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 30 — *xdc* is an XQuery dynamic context.

- 7) Let ***xsc*** and ***xdc*** be augmented with an XQuery variable ***\$EXPR***, whose XQuery formal type notation is ***xvft***, and whose value is *XV*.
- 8) Case:
- a) If Feature X211, “XML 1.1 support” is supported, then let *DN* be the result of an XQuery evaluation with XML 1.1 lexical rules, using ***xsc*** and ***xdc*** as the XQuery expression context of the XQuery expression
- ```
document { $EXPR }
```
- If an XQuery error occurs during the evaluation, then an exception condition is raised: *XQuery error (10000)*.
- b) Otherwise, let *DN* be the result of an XQuery evaluation with XML 1.0 lexical rules, using ***xsc*** and ***xdc*** as the XQuery expression context of the XQuery expression
- ```
document { $EXPR }
```
- If an XQuery error occurs during the evaluation, then an exception condition is raised: *XQuery error (10000)*.
- 9) Case:
- a) If the declared type of the <XML document> is XML(CONTENT(UNTYPED)), then the General Rules of Subclause 10.21, “Constructing an unvalidated XQuery document node”, are applied with *DN* as *XQUERYDOCNODE*; let result of the <XML document> be the *UNVALIDATEDDOCNODE* returned from the application of those General Rules.
- b) Otherwise, the result of the <XML document> is *DN*.

Conformance Rules

- 1) Without Feature X030, “XMLDocument”, conforming SQL language shall not contain an <XML document>.
- 2) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML document> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 3) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML document> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

6.15 <XML element>

Function

Generate an XML value with a single XQuery element node, possibly as a child of an XQuery document node.

Format

```
<XML element> ::=
  XMLELEMENT <left paren> NAME <XML element name>
    [ <comma> <XML namespace declaration> ] [ <comma> <XML attributes> ]
    [ { <comma> <XML element content> }... ]
    [ OPTION <XML content option> ] ]
  [ <XML returning clause> ] <right paren>

<XML element name> ::=
  <identifier>

<XML attributes> ::=
  XMLATTRIBUTES <left paren> <XML attribute list> <right paren>

<XML attribute list> ::=
  <XML attribute> [ { <comma> <XML attribute> }... ]

<XML attribute> ::=
  <XML attribute value> [ AS <XML attribute name> ]

<XML attribute value> ::=
  <value expression>

<XML attribute name> ::=
  <identifier>

<XML element content> ::=
  <value expression>

<XML content option> ::=
  NULL ON NULL
  | EMPTY ON NULL
  | ABSENT ON NULL
  | NIL ON NULL
  | NIL ON NO CONTENT
```

Syntax Rules

- 1) The scope of the <XML namespace declaration> is the <XML element>.
- 2) Let n be the number of occurrences of <XML attribute> in <XML attribute list>.
- 3) For i ranging from 1 (one) to n .
 - a) Let A_i be the i -th <XML attribute> contained in <XML attribute list>.
 - b) Let AV_i be the <XML attribute value> of A_i .
 - c) The declared type of AV_i shall be either a predefined type other than XML or a distinct type whose source type is neither an XML type nor a collection type.

- d) Case:
- i) If A_i contains an <XML attribute name> AN_i , then let ANC_i be AN_i .
 - ii) Otherwise, AV_i shall be a <column reference>. Let CN_i be the <column name> of the column designated by the <column reference> that is AV_i . The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with CN_i as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let ANC_i be the *XMLNAME* returned from the application of those General Rules.
- e) ANC_i shall be an XML 1.1 QName.
- f) ANC_i shall not be equivalent to 'xmlns', and ANC_i shall not have an XML QName prefix that is equivalent to 'xmlns'.
- g) The Syntax Rules of Subclause 10.14, “Determination of namespace URI”, are applied with ANC_i as *QNAME* and the <XML element> as *BNFTERM*; let $NSURI_i$ be the *NSURI* returned from the application of those Syntax Rules.
- 4) There shall not be two <XML attribute>s A_i and A_j such that i does not equal j , $NSURI_i$ is identical as defined in XML Namespaces to $NSURI_j$, and the XML QName local part of ANC_i equals the XML QName local part of ANC_j .
- 5) Let EN be the character representation of <XML element name>. EN shall be an XML 1.1 QName.
- 6) The Syntax Rules of Subclause 10.14, “Determination of namespace URI”, are applied with EN as *QNAME* and the <XML element> as *BNFTERM*; let $ENSURI$ be the *NSURI* returned from the application of those Syntax Rules.
- 7) For each <XML element content> XEC , the declared type of XEC shall be a predefined type, a collection type that is not based on an XML unmappable data type, or a distinct type.
- 8) Case:
- a) If <XML element content> is specified, then:
 - i) If <XML content option> is not specified, then EMPTY ON NULL is implicit.
 - ii) Let OPT be the explicit or implicit <XML content option>.
 - b) Otherwise, let OPT be the zero-length string.
- 9) If <XML element content> is specified, then there shall not be an <XML attribute> A_i such that $NSURI_i$ is the XML namespace URI given in Table 2, “XML namespace prefixes and their URIs”, corresponding to the XML namespace prefix xsi , and the XML QName local part of ANC_i is *nil*.
- 10) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 11) Let XEN be the <XML element name>.
- 12) If <XML namespace declaration> is specified, then let XND be “<comma> <XML namespace declaration>”; otherwise, let XND be a zero-length string.
- 13) If <XML attributes> is specified, then let XAT be “<comma> <XML attributes>”; otherwise, let XAT be the zero-length string.

6.15 <XML element>

- 14) Let k be the number of <XML element content>s immediately contained in <XML element>. For each such <XML element content> in order of its position in <XML element> from left to right, let $XMLEC_l$, $1 \text{ (one)} \leq l \leq k$, be “<comma> <XML element content>”.
- 15) Let XCO be the specified or implied <XML content option>.
- 16) Case:
 - a) If RETURNING CONTENT is specified or implied, then <XML element> is equivalent to

```
XMLDOCUMENT (
  XMLELEMENT (
    NAME XEN XND XAT XMLEC1 XMLEC2 ... XMLECk XCO
    RETURNING SEQUENCE )
  RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML element> is XML(SEQUENCE).

NOTE 31 — If RETURNING CONTENT is specified or implied, then the declared type of <XML element> is effectively established by the Syntax Rules of Subclause 6.14, “<XML document>”.

Access Rules

- 1) If the declared type DT of the <value expression> VE immediately contained in an <XML attribute value> or an <XML element content> is a distinct type, then let ST be the source type of DT . The following shall be valid according to the Syntax Rules of Subclause 6.6, “<cast specification>”:

```
CAST ( VE AS ST )
```

NOTE 32 — As specified in ISO/IEC 9075-1, Subclause 6.3.3.3, “Rule evaluation order”, evaluation of Syntax Rules, Access Rules, and Conformance Rules is all performed concurrently.

General Rules

- 1) Case:
 - a) If the <XML element> is contained within the scope of an <XML binary encoding>, then let XBE be the <XML binary encoding> with innermost scope that contains the <XML element>.
 - b) Otherwise, let XBE be an implementation-defined (ID201) <XML binary encoding>.
- 2) Case:
 - a) If XBE specifies BASE64, then let ENC be an indication that binary strings are to be encoded in base64.
 - b) Otherwise, let ENC be an indication that binary strings are to be encoded in hex.
- 3) For i range from 1 (one) to n , if the value of AV_i is not the null value, then:
 - a) The General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with AV_i as $SQLVALUE$, ENC as $ENCODING$, “absent” as $NULLS$, and $False$ as $CHARMAPPING$; let CAV_i be the $XMLVALUE$ returned from the application of those General Rules. CAV_i is a character string of Unicode characters.
 - b) Let ATI_i be an XQuery attribute node having the following properties:
 - i) The **node-name** is an XQuery atomic value of XQuery atomic type $xs:QName$, whose local name is the XML 1.1 QName local part of ANC_i and whose namespace URI is $NSURI_i$.

- ii) The **string-value** property is *CAV_i*.
 - iii) The **type-name** property is *xs:untypedAtomic*.
 - iv) The **parent** property is initially unknown.
- 4) Let *ATTRS* be the XQuery sequence of XQuery attribute nodes *ATI_i*, $1 \leq i \leq n$, such that *AV_i* is not the null value.
 - 5) Let *N* be the number of <XML element content>s. Let *V_j* be an enumeration of the values of the <XML element content>s, $1 \leq j \leq N$. Let *CON* be the list of values *V₁, ..., V_N*.
 - 6) The General Rules of Subclause 10.15, “Construction of an XML element”, are applied with *EN* as *QNAME*, *ENSURI* as *NAMESPACE*, *ATTRS* as *ATTRIBUTES*, *CON* as *CONTENTS*, *OPT* as *OPTION*, and *ENC* as *ENCODING*; let result of <XML element> be the *XMLELEM* returned from the application of those General Rules.

Conformance Rules

- 1) Without Feature X031, “XMLElement”, conforming SQL language shall not contain an <XML element>.
- 2) Without Feature X080, “Namespaces in XML publishing”, in conforming SQL language, <XML element> shall not immediately contain <XML namespace declaration>.
- 3) Without Feature X170, “XML null handling options”, conforming SQL language shall not specify <XML content option>.
- 4) Without Feature X171, “NIL ON NO CONTENT option”, conforming SQL language shall not specify NIL ON NO CONTENT.
- 5) Without Feature X211, “XML 1.1 support”, in conforming SQL language, an <XML element name> shall be an XML 1.0 QName.
- 6) Without Feature X211, “XML 1.1 support”, in conforming SQL language, an <XML attribute name> shall be an XML 1.0 QName.
- 7) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML element> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 8) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML element> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.
- 9) Without Feature X085, “Predefined namespace prefixes”, conforming SQL language shall not contain an <XML element name> *E* that has an XML QName prefix that is not equivalent to an <XML namespace prefix> contained in one or more <XML namespace declaration>s that are the scope of the <XML element> that contains *E*.
- 10) Without Feature X085, “Predefined namespace prefixes”, conforming SQL language shall not contain an explicit or implicit <XML attribute name> *A* that has an XML QName prefix other than 'xml' that is not equivalent to an <XML namespace prefix> contained in one or more <XML namespace declaration>s that are the scope of the <XML element> that contains *A*.

6.16 <XML forest>

Function

Generate an XML value with a sequence of XQuery element nodes, possibly as the children of an XQuery document node.

Format

```
<XML forest> ::=
  XMLFOREST <left paren> [ <XML namespace declaration> <comma> ]
  <forest element list>
  [ OPTION <XML content option> ]
  [ <XML returning clause> ]
  <right paren>

<forest element list> ::=
  <forest element> [ { <comma> <forest element> }... ]

<forest element> ::=
  <forest element value> [ AS <forest element name> ]

<forest element value> ::=
  <value expression>

<forest element name> ::=
  <identifier>
```

Syntax Rules

- 1) The scope of the <XML namespace declaration> is the <XML forest>.
- 2) Let n be the number of occurrences of <forest element> in <forest element list>. For each i between 1 (one) and n :
 - a) Let F_i be the i -th <forest element> contained in <forest element list>.
 - b) Let FV_i be the <forest element value> immediately contained in F_i . The declared type of FV_i shall be a predefined type, a collection type that is not based on an XML unmappable data type, or a distinct type.
 - c) Case:
 - i) If F_i contains a <forest element name> FEN_i , then let FNC_i be FEN_i .
 - ii) Otherwise, FV_i shall be a column reference. Let CN_i be the <column name> of the column designated by FV_i . The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with FN_i as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let ANC_i be the *XMLNAME* returned from the application of those General Rules.
 - d) FNC_i shall be an XML 1.1 QName.
 - e) The Syntax Rules of Subclause 10.14, "Determination of namespace URI", are applied with FNC_i as *QNAME* and the <XML forest> as *BNFTERM*; let $NSURI_i$ be the *NSURI* returned from the application of those Syntax Rules.
- 3) If <XML content option> is not specified, then NULL ON NULL is implicit.

- 4) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 5) If <XML namespace declaration> is specified, then let *XND* be “<XML namespace declaration> <comma>”; otherwise, let *XND* be a zero-length string.
- 6) Let *FEL* be the <forest element list>.
- 7) Let *XCO* be the specified or implied <XML content option>.
- 8) Case:
 - a) If RETURNING CONTENT is specified or implied, then <XML forest> is equivalent to

```
XMLDOCUMENT (
  XMLFOREST (
    XND FEL XCO
    RETURNING SEQUENCE )
  RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML forest> is XML(SEQUENCE).

NOTE 33 — If RETURNING CONTENT is specified or implied, then the declared type of <XML forest> is effectively established by the Syntax Rules of Subclause 6.14, “<XML document>”.

Access Rules

- 1) If the declared type *DT* of the <value expression> *VE* immediately contained in a <forest element value> is a distinct type, then let *ST* be the source type of *DT*. The following shall be valid according to the Syntax Rules of Subclause 6.6, “<cast specification>”:

```
CAST ( VE AS ST )
```

NOTE 34 — As specified in ISO/IEC 9075-1, Subclause 6.3.3.3, “Rule evaluation order”, evaluation of Syntax Rules, Access Rules, and Conformance Rules is all performed concurrently.

General Rules

- 1) Case:
 - a) If the <XML forest> is contained within the scope of an <XML binary encoding>, then let *XBE* be the <XML binary encoding> with innermost scope that contains the <XML forest>.
 - b) Otherwise, let *XBE* be an implementation-defined (ID201) <XML binary encoding>.
- 2) Case:
 - a) If *XBE* specifies BASE64, then let *ENC* be an indication that binary strings are to be encoded in base64.
 - b) Otherwise, let *ENC* be an indication that binary strings are to be encoded in hex.
- 3) For each *i* between 1 (one) and *n*, let *V_i* be the value of the *i*-th <forest element> contained in <forest element list>.
- 4) For each *i* between 1 (one) and *n*, let *CON_i* be the list of values consisting of the single value *V_i*.
- 5) For each *i* between 1 (one) and *n*, the General Rules of Subclause 10.15, “Construction of an XML element”, are applied with *FNC_i* as *QNAME*, *NSURI_i* as *NAMESPACE*, the empty XQuery sequence as *ATTRIBUTES*, *CON_i* as *CONTENTS*, the explicit or implicit <XML content option> as *OPTION*, and *ENC* as *ENCODING*; let *XV_i* be the *XMLELEM* returned from the application of those General Rules.

6.16 <XML forest>

- 6) Let R_1 be XV_1 . For all i , $2 \leq i \leq n$, the General Rules of Subclause 10.16, “Concatenation of two XML values”, are applied with R_{i-1} as *FIRSTVAL* and XV_i as *SECONDVAL*; let R_i be the *CONCAT* returned from the application of those General Rules.
- 7) The result of <XML forest> is R_n .

Conformance Rules

- 1) Without Feature X032, “XMLForest”, conforming SQL language shall not contain an <XML forest>.
- 2) Without Feature X080, “Namespaces in XML publishing”, in conforming SQL language, <XML forest> shall not immediately contain <XML namespace declaration>.
- 3) Without Feature X211, “XML 1.1 support”, in conforming SQL language, a <forest element name> shall be an XML 1.0 QName.
- 4) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML forest> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 5) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML forest> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.
- 6) Without Feature X085, “Predefined namespace prefixes”, conforming SQL language shall not contain an explicit or implicit <forest element name> F that has an XML QName prefix that is not equivalent to an <XML namespace prefix> contained in one or more <XML namespace declaration>s that are the scope of the <XML forest> that contains F .

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.17 <XML parse>

Function

Perform a non-validating parse of a string to produce an XML value.

Format

```
<XML parse> ::=  
  XMLPARSE <left paren> <document or content> <string value expression>  
    <XML whitespace option> <right paren>  
  
<XML whitespace option> ::=  
  { PRESERVE | STRIP } WHITESPACE
```

Syntax Rules

- 1) Case:
 - a) If <document or content> is DOCUMENT, then it is implementation-defined (IV205) whether the declared type of <XML parse> is XML(DOCUMENT(UNTYPED)) or XML(DOCUMENT(ANY)).
 - b) Otherwise, it is implementation-defined (IV206) whether the declared type of <XML parse> is XML(CONTENT(UNTYPED)) or XML(CONTENT(ANY)).

Access Rules

None.

General Rules

- 1) Let *DC* be <document or content>.
- 2) Let *V* be the value of <string value expression>.
- 3) Let *WO* be the <XML whitespace option>.
- 4) Case:
 - a) If *V* is the null value, then let *PARSE* be the null value.
 - b) Otherwise, the General Rules of Subclause 10.18, “Parsing a string as an XML value”, are applied with *DC* as *SYNTAX*, *V* as *TEXT*, and *WO* as *OPTION*; let *PARSE* be the *XMLPARSE* returned from the application of those General Rules.
- 5) The result of <XML parse> is *PARSE*.

Conformance Rules

- 1) Without Feature X060, “XMLParse: character string input and CONTENT option”, in conforming SQL language, the declared type of the <string value expression> immediately contained in <XML parse> shall not be a character string type and <XML parse> shall not immediately contain a <document or content> that is CONTENT.

6.17 <XML parse>

- 2) Without Feature X061, “XMLParse: character string input and DOCUMENT option”, in conforming SQL language, the declared type of the <string value expression> immediately contained in <XML parse> shall not be a character string type and <XML parse> shall not immediately contain a <document or content> that is DOCUMENT.
- 3) Without Feature X065, “XMLParse: binary string input and CONTENT option”, in conforming SQL language, the declared type of the <string value expression> immediately contained in <XML parse> shall not be a binary string type and <XML parse> shall not immediately contain a <document or content> that is CONTENT.
- 4) Without Feature X066, “XMLParse: binary string input and DOCUMENT option”, in conforming SQL language, the declared type of the <string value expression> immediately contained in <XML parse> shall not be a binary string type and <XML parse> shall not immediately contain a <document or content> that is DOCUMENT.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.18 <XML PI>

Function

Generate an XML value with a single XQuery processing instruction node, possibly as a child of an XQuery document node.

Format

```
<XML PI> ::=
  XMLPI <left paren> NAME <XML PI target>
    [ <comma> <character value expression> ]
    [ <XML returning clause> ]
  <right paren>

<XML PI target> ::=
  <identifier>
```

Syntax Rules

- 1) Let *I* be the result of mapping the <identifier> contained in the <XML PI target> to Unicode.
- 2) *I* shall be an XML 1.1 NCName.
- 3) *I* shall not consist of three characters, the first being 'X' or 'x', the second being 'M' or 'm', and the third being 'L' or 'l'.
- 4) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 5) Let *XPT* be the <XML PI target>.
- 6) If <character value expression> is specified, then let *CSVE* be "<comma> <character value expression>"; otherwise, let *CSVE* be the zero-length string.
- 7) Case:
 - a) If RETURNING CONTENT is specified or implied, then <XML PI> is equivalent to:

```
XMLDOCUMENT (
  XMLPI (
    NAME XPT CSVE
    RETURNING SEQUENCE )
  RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML PI> is XML(SEQUENCE).

NOTE 35 — If RETURNING CONTENT is specified or implied, then the declared type of <XML PI> is effectively established by the Syntax Rules of Subclause 6.14, "<XML document>".

Access Rules

None.

General Rules

- 1) If the value of the <string value expression> is the null value, then the result of <XML PI> is the null value and no further General Rules of this Subclause are applied.
- 2) If <character value expression> is not specified, then let *SVE* be ' ' (the <character string literal> for the zero-length string); otherwise, let *SVE* be the <string value expression>.
- 3) The General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with *SVE* as *SQLVALUE*, an indication that binary strings are to be encoded in hex as *ENCODING*, “absent” as *NULLS*, and *False* as *CHARMAPPING*; let *USV* be the *XMLVALUE* returned from the application of those General Rules. *USV* is a character string of Unicode characters.

- 4) If the value of

'<?' I || ' ' || *USV* || '?>'

does not conform to rule [16], “PI”, of XML 1.1, then an exception condition is raised: *data exception — invalid processing instruction (2200T)*.

NOTE 36 — If the SQL/XML implementation does not support XML 1.1, then the processing instruction target *I* is subject to a Conformance Rule limiting it to be an XML 1.0 Name. Under that assumption, if the proposed processing instruction conforms to rule [16] of XML 1.1, then it also conforms to rule [16] of XML 1.0.

- 5) The Syntax Rules of Subclause 10.23, “Determination of an XQuery formal type notation”, are applied with *USV* as *SOURCE* and *False* as *CONTEXT*; let *xvft* be the *FORMALTYPE* returned from the application of those Syntax Rules.
- 6) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the null value as *NONTERMINAL*; let *xsc* be the *STATICCONTEXT* returned from the application of those Syntax Rules.

NOTE 37 — *xsc* is an XQuery static context.

- 7) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *xdc* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 38 — *xdc* is an XQuery dynamic context.

- 8) Let *XSC* and *XDC* be augmented with an XQuery variable *\$EXPR*, whose XQuery formal type notation is *xvft*, and whose value is *USV*.

- 9) Case:

- a) If Feature X211, “XML 1.1 support” is supported, then let *PN* be the result of an XQuery evaluation with XML 1.1 lexical rules, using *xsc* and *xdc* as the XQuery expression context of the XQuery expression

`processing-instruction I { $EXPR }`

- b) Otherwise, let *PN* be the result of an XQuery evaluation with XML 1.0 lexical rules, using *xsc* and *xdc* as the XQuery expression context of the XQuery expression

`processing-instruction I { $EXPR }`

- 10) The result of the <XML PI> is *PN*.

Conformance Rules

- 1) Without Feature X037, “XMLPI”, conforming SQL language shall not contain an <XML PI>.

- 2) Without Feature X211, “XML 1.1 support”, in conforming SQL language, an <identifier> contained in an <XML PI target>, when mapped to Unicode, shall be an XML 1.0 NCName.

NOTE 39 — The set of XML 1.0 NCNames is a proper subset of the set of XML 1.1 NCNames. That is, all XML 1.0 NCNames are also XML 1.1 NCNames, but not all XML 1.1 NCNames are also XML 1.0 NCNames.

- 3) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML PI> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 4) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML PI> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.19 <XML query>

Function

Evaluate an XQuery expression.

Format

```

<XML query> ::=
  XMLQUERY <left paren>
    <XQuery expression>
      [ <XML query argument list> ]
      [ <XML returning clause>
        [ <XML query returning mechanism> ] ]
    <XML query empty handling option>
  <right paren>

<XQuery expression> ::=
  <character string literal>

<XML query argument list> ::=
  PASSING <XML query default passing mechanism>
    <XML query argument>
    [ { <comma> <XML query argument> }... ]

<XML query default passing mechanism> ::=
  <XML passing mechanism>

<XML query argument> ::=
  <XML query context item>
  | <XML query variable>

<XML query context item> ::=
  <value expression> [ <XML passing mechanism> ]

<XML query variable> ::=
  <value expression> AS <identifier>
  [ <XML passing mechanism> ]

<XML query returning mechanism> ::=
  <XML passing mechanism>

<XML query empty handling option> ::=
  NULL ON EMPTY
  | EMPTY ON EMPTY

```

Syntax Rules

- 1) Let *XMQ* be the <XML query>.
- 2) If *XMQ* contains <XML query argument list>, then let *DPM* be the <XML query default passing mechanism> immediately contained in the <XML query argument list>.
- 3) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 4) Case:

- a) If the implicit or explicit <XML returning clause> is RETURNING CONTENT, then <XML query returning mechanism> shall not be specified. Let *XQRM* be BY VALUE.
 - b) If *XMQ* contains <XML query returning mechanism>, then let *XQRM* be that <XML query returning mechanism>.
 - c) Otherwise, *XMQ* shall contain <XML query argument list>. Let *XQRM* be *DPM*.
- 5) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the <XML query> as *NONTERMINAL*; let *xsc* be the *STATICCONTEXT* returned from the application of those Syntax Rules, modifying the **in-scope variables** component of *xsc* as follows:

NOTE 40 — *xsc* is an XQuery static context.

- a) For each <XML query variable> *XQV*:
 - i) The <identifier> *I* contained in *XQV* shall be an XML 1.1 NCName.
 - ii) *I* shall not be equivalent to the name of any implementation-defined (IV097) XQuery variable, or to the <identifier> of any other <XML query variable>.
 - iii) Let *VVE* be the <value expression> simply contained in *XQV*.
 - iv) The declared type of *VVE* shall be convertible to XML(SEQUENCE) according to the Syntax Rules of Subclause 6.7, “<XML cast specification>”.
 - v) If the declared type of *VVE* is not an XML type, then *XQV* shall not contain an <XML passing mechanism>.
 - vi) If *XQV* contains an <XML passing mechanism>, then let *VPM* be that <XML passing mechanism>; otherwise, let *VPM* be *DPM*.
 - vii) The Syntax Rules of Subclause 10.23, “Determination of an XQuery formal type notation”, are applied with *VVE* as *SOURCE* and *False* as *CONTEXT*; let *VFT* be the *FORMALTYPE* returned from the application of those Syntax Rules.
 - viii) The pair (*I*, *VFT*) is placed in the **in-scope variables** component of *xsc*.
- b) If *XMQ* contains <XML query context item>, then:
 - i) *XMQ* shall contain exactly one <XML query context item> *XQCI*.
 - ii) Let *CVE* be the <value expression> simply contained in *XQCI*.
 - iii) The declared type of *CVE* shall be convertible to XML(SEQUENCE) according to the Syntax Rules of Subclause 6.7, “<XML cast specification>”.
 - iv) If the declared type of *CVE* is not an XML type, then *XQCI* shall not contain an <XML passing mechanism>.
 - v) If *XQCI* contains an <XML passing mechanism>, then let *CPM* be that <XML passing mechanism>; otherwise, let *CPM* be *DPM*.
 - vi) The Syntax Rules of Subclause 10.23, “Determination of an XQuery formal type notation”, are applied with *CVE* as *SOURCE* and *True* as *CONTEXT*; let *CFT* be the *FORMALTYPE* returned from the application of those Syntax Rules.
 - vii) Let *\$fs:dot* be the XQuery variable in the fictitious namespace associated with the prefix *fs* as posited in XQuery 1.0 and XPath 2.0 Formal Semantics, section 3.1.2, “Dynamic context”, corresponding to the context item in *xsc*. The pair (*fs:dot*, *CFT*) is placed in the **in-scope variables** component of *xsc*.

6.19 <XML query>

NOTE 41 — Initialization of the XQuery static context *xsc* can in many cases be overridden by the prolog of the <XQuery expression>.

- 6) <XQuery expression> shall conform to an implementation-defined (IA108) subset of the normative rules of XQuery expressions that are found in XQuery 3.1: an XML Query Language, XQuery and XPath Functions and Operators 3.1, XQuery 1.0 and XPath 2.0 Formal Semantics, and XQuery Update Facility 1.0, and that define the analysis phase, using the XQuery static context *XSC* and XML 1.1 lexical rules, without raising an XQuery static error, type error, or statically-detected dynamic error.

NOTE 42 — The subset of mandatory and optional features of XQuery supported by an SQL/XML implementation is implementation-defined (IA103). This includes each of the following.

- What subset of the BNF in XQuery 3.1: an XML Query Language and XQuery Update Facility 1.0 is supported.
- For the supported BNF, which of the normative rules in XQuery 3.1: an XML Query Language and XQuery 1.0 and XPath 2.0 Formal Semantics are supported.
- Which of the functions in XQuery and XPath Functions and Operators 3.1 are supported.
- Which of the features described in the XQuery 3.1: an XML Query Language section titled “Optional Features” are supported, and to what extent.

NOTE 43 — XQuery permits an SQL/XML implementation to postpone some or all type checking to the evaluation phase (i.e., until the General Rules of this Subclause are performed).

- 7) <XQuery expression> shall not contain an updating expression, except as part of a transform expression, as defined by XQuery Update Facility 1.0.
- 8) Let *XQE* be the <XQuery expression>.
- 9) If <XML query argument list> is specified, then let *XQAL* be that <XML query argument list>; otherwise, let *XQAL* be the zero-length string.
- 10) Let *XQEHO* be the <XML query empty handling option>.
- 11) Case:
- a) If RETURNING CONTENT is specified or implied, then <XML query> is equivalent to

```
XMLDOCUMENT (
  XMLQUERY (
    XQE XQAL
    RETURNING SEQUENCE XQRM XQEHO )
  RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML query> is XML(SEQUENCE).

NOTE 44 — If RETURNING CONTENT is specified or implied, then the declared type of <XML query> is effectively established by the Syntax Rules of Subclause 6.14, “<XML document>”.

Access Rules

None.

General Rules

- 1) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *xdc* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 45 — *xdc* is an XQuery dynamic context.

- a) Case:
- i) If there is no <XML query context item>, then there is no context item in *xdc*.

- ii) Otherwise,
Case:
- 1) If the value of *CVE* is the null value, then the result of the <XML query> is the null value, and no further General Rules of this Subclause are applied.
 - 2) Otherwise:
 - A) Case:
 - I) If the declared type of *CVE* is an XML type, then
Case:
 - 1) If *CPM* is BY REF, then let *CI* be the value of *CVE*.
 - 2) Otherwise, the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with *CVE* as *VALUE*; let *CI* be the *COPY* returned from the application of those General Rules.
 - II) Otherwise, let *CI* be the result of the <XML cast specification>:
`XMLCAST (CVE AS XML (SEQUENCE))`
 - B) Case:
 - I) If *CI* is the empty XQuery sequence, then there is no context item in *XDC*.
 - II) If *CI* is an XQuery sequence of length 1 (one), then the context item, context position, and context size of *XDC* are set by initializing *\$fs:dot* to reference *CI*, *\$fs:position* to 1 (one), and *\$fs:last* to 1 (one).
 - III) Otherwise, an exception condition is raised: *data exception — invalid XQuery context item (2200V)*.
- b) For each <XML query variable> *XQV*:
- i) Let *VVE* be the <value expression> simply contained in *XQV*, and let *V* be the value of *VVE*.
Case:
 - 1) If *V* is the null value, then let *VV* be the empty sequence.
 - 2) If *V* is a value of an XML type, then
Case:
 - A) If *VPM* is BY REF, then let *VV* be *V*.
 - B) Otherwise, the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with *V* as *VALUE*; let *VV* be the *COPY* returned from the application of those General Rules.
 - 3) Otherwise, let *VV* be the result of
`XMLCAST (VVE AS XML (SEQUENCE))`

6.19 <XML query>

- ii) The XQuery variable whose QName is equivalent to the <identifier> simply contained in *XQV* is set to *VV*.
- 2) Case:
- a) If the SQL/XML implementation supports Feature X211, “XML 1.1 support”, then the <XQuery expression> is evaluated as an XQuery expression with XML 1.1 lexical rules, using **xSC** and **xDC** as the XQuery expression context, yielding a value *X1* of an XML type.
 - b) Otherwise, the <XQuery expression> is evaluated as an XQuery expression with XML 1.0 lexical rules, using **xSC** and **xDC** as the XQuery expression context, yielding a value *X1* of an XML type.
- 3) If the result of the XQuery evaluation is an XQuery error, then an exception condition is raised: *XQuery error (10000)*.
- 4) Case:
- a) If *X1* is an empty sequence and the <XML query empty handling option> is NULL ON EMPTY, then let *X2* be the null value.
 - b) Otherwise,

Case:

 - i) If *XQRM* is BY REF, then let *X2* be *X1*.
 - ii) Otherwise, the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with **x1** as *VALUE*; let **x2** be the *COPY* returned from the application of those General Rules.
- 5) *X2* is the result of the <XML query>.

Conformance Rules

- 1) Without Feature X200, “XMLQuery”, conforming SQL language shall not contain an <XML query>.
- 2) Without Feature X201, “XMLQuery: RETURNING CONTENT”, conforming SQL language shall not contain an <XML query> that contains RETURNING CONTENT.
- 3) Without Feature X202, “XMLQuery: RETURNING SEQUENCE”, conforming SQL language shall not contain an <XML query> that contains RETURNING SEQUENCE.
- 4) Without Feature X203, “XMLQuery: passing a context item”, in conforming SQL language, an <XML query> shall not contain an <XML query context item>.
- 5) Without Feature X204, “XMLQuery: initializing an XQuery variable”, in conforming SQL language, an <XML query> shall not contain an <XML query variable>.
- 6) Without Feature X205, “XMLQuery: EMPTY ON EMPTY option”, conforming SQL language shall not contain an <XML query> that contains an <XML query empty handling option> that specifies EMPTY ON EMPTY.
- 7) Without Feature X206, “XMLQuery: NULL ON EMPTY option”, conforming SQL language shall not contain an <XML query> that contains an <XML query empty handling option> that specifies NULL ON EMPTY.
- 8) Without Feature X211, “XML 1.1 support”, in conforming SQL language, the value of the <XQuery expression> shall be an XQuery expression with XML 1.0 lexical rules.

- 9) Without Feature X211, “XML 1.1 support”, in conforming SQL language, the <identifier> contained in an <XML query variable> shall be an XML 1.0 NCName.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.20 <XML text>

Function

Generate an XML value with a single XQuery text node, possibly as a child of an XQuery document node.

Format

```
<XML text> ::=
  XMLTEXT <left paren> <character value expression>
    [ <XML returning clause> ] <right paren>
```

Syntax Rules

- 1) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
- 2) Let *SVE* be the <character value expression>.
- 3) Case:
 - a) If RETURNING CONTENT is specified or implied, then <XML text> is equivalent to

```
XMLDOCUMENT (
  XMLTEXT ( SVE RETURNING SEQUENCE )
  RETURNING CONTENT )
```

- b) Otherwise, the declared type of <XML text> is XML(SEQUENCE).

NOTE 46 — If RETURNING CONTENT is specified or implied, then the declared type of <XML text> is effectively established by the Syntax Rules of Subclause 6.14, "<XML document>".

Access Rules

None.

General Rules

- 1) Let *SV* be the value of *SVE*.
- 2) If *SV* is the null value, then the result of <XML text> is the null value and no further General Rules of this Subclause are applied.
- 3) Case:
 - a) If <XML text> is contained within the scope of an <XML binary encoding>, then let *XBE* be the <XML binary encoding> with innermost scope that contains the <XML text>.
 - b) Otherwise, let *XBE* be an implementation-defined (ID201) <XML binary encoding>.
- 4) Case:
 - a) If *XBE* specifies `BASE64`, then let *ENC* be an indication that binary strings are to be encoded in base64.
 - b) Otherwise, let *ENC* be an indication that binary strings are to be encoded in hex.

- 5) The General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with *SV* as *SQLVALUE*, *ENC* as *ENCODING*, “absent” as *NULLS*, and *False* as *CHARMAPPING*; let *USV* be the *XMLVALUE* returned from the application of those General Rules. *USV* is a character string of Unicode characters.
- 6) Let *XTN* be an XQuery text node with the following properties:
 - a) The value of the **content** property is the value of *USV*.
 - b) The value of the **parent** property is set to **empty**.
- 7) The result of <XML text> is the XQuery sequence consisting of one node, *XTN*.

Conformance Rules

- 1) Without Feature X038, “XMLText”, conforming SQL language shall not contain an <XML text>.
- 2) Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML text> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 3) Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML text> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

6.21 <XML validate>

Function

Validate an XML value.

Format

```
<XML validate> ::=
  XMLVALIDATE <left paren>
    <document or content or sequence>
    <XML value expression>
    [ <XML valid according to clause> ]
    <right paren>

<document or content or sequence> ::=
  <document or content>
  | SEQUENCE
```

Syntax Rules

- 1) Let *XVE* be the <XML value expression>. Let *DCS* be the <document or content or sequence>.
- 2) If <XML valid according to clause> is specified, then let *RXS* be the indicated registered XML schema, let *ENSURI* be the indicated XML namespace, if any, and let *EN* be the XML NCName of the indicated global element declaration schema component, if any.

NOTE 47 — Indicated registered XML schema, indicated XML namespace, and indicated global element declaration schema component are defined in Subclause 11.5, “<XML valid according to clause>”.

- 3) Let *XVT* be the declared type of *XVE*. The declared type of <XML validate> is

Case:

- a) If *XVT* is XML(DOCUMENT(ANY)), XML(DOCUMENT(UNTYPED)), or XML(DOCUMENT(XMLSCHEMA)), then

Case:

- i) If <XML valid according to clause> is specified, then

Case:

- 1) If <XML valid element name specification> is specified, then XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS*, the XML namespace *ENSURI*, and XML NCName *EN*.
- 2) If <XML valid element namespace specification> is specified, then XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS* and the XML namespace *ENSURI*.
- 3) Otherwise, XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS*.

- ii) Otherwise, XML(DOCUMENT(ANY)).

- b) If *XVT* is XML(CONTENT(ANY)), XML(CONTENT(UNTYPED)), or XML(CONTENT(XMLSCHEMA)), then

Case:

i) If <XML valid according to clause> is specified, then

Case:

- 1) If <XML valid element name specification> is specified, then XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS*, the XML namespace *ENSURI*, and XML NCName *EN*.
- 2) If <XML valid element namespace specification> is specified, then XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS* and the XML namespace *ENSURI*.
- 3) Otherwise, XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of *RXS*.

ii) Otherwise, XML(CONTENT(ANY)).

c) If *XVT* is XML(SEQUENCE), then XML(SEQUENCE).

Access Rules

None.

General Rules

- 1) Let *V* be the value of *XVE*.
- 2) If *V* is the null value, then the result of the <XML validate> is the null value and no further General Rules of this Subclause are applied.
- 3) Case:
 - a) If *DCS* is DOCUMENT and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then an exception condition is raised: *data exception — invalid XML document (2200M)*.
 - b) If *DCS* is CONTENT and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then an exception condition is raised: *data exception — invalid XML content (2200N)*.
 - c) Otherwise, if any XQuery item contained in *V* is an XQuery atomic value, XQuery attribute node, XQuery namespace node, or an XQuery text node, then an exception condition is raised: *data exception — XQuery sequence cannot be validated (2201)*.
- 4) If *V* is an empty XQuery sequence, then the result of <XML validate> is an empty XQuery sequence and no further General Rules of this Subclause are applied.
- 5) Let *N* be the number of XQuery items in *V*. Let \mathcal{I}_j , $1 \text{ (one)} \leq j \leq N$, be an enumeration in order of the XQuery items in *V*.
- 6) For each *j*, $1 \text{ (one)} \leq j \leq N$,

Case:

a) If \mathcal{I}_j is an XQuery document node *D*, then:

- i) Let M be the number of XQuery nodes in the **children** property of \mathcal{D} .
- ii) Let \mathcal{C}_k , $1 \text{ (one)} \leq k \leq M$, be an enumeration in order of the XQuery nodes in the **children** property of \mathcal{D} .
- iii) For each k , $1 \text{ (one)} \leq k \leq M$,

Case:

- 1) If \mathcal{C}_k is not an XQuery element node, an XQuery comment node, or an XQuery processing instruction node, then an exception condition is raised: *data exception — XQuery document node cannot be validated (2201K)*.

- 2) If \mathcal{C}_k is an XQuery element node, then:

A) Case:

- I) If <XML valid according to clause> is specified, then let XS_k be RXS .

II) Otherwise:

- 1) Let NS be the XML namespace of \mathcal{C}_k .
- 2) Let XS_k be a registered XML schema for which the current user has USAGE privilege and whose target namespace is identical to NS , as defined by XML Namespaces, chosen according to a deterministic implementation-defined (IW062) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user and the same value V , then the same registered XML schema will be chosen. If no XS_k is found, then an exception condition is raised: *data exception — no XML schema found (2201L)*.

- B) If <XML valid element clause> is specified, then let **ENAME** be the **node-name** property of \mathcal{C}_k .

Case:

- I) If <XML valid element name specification> is specified, and either the XML NCName of **ENAME** is not equivalent to EN , or the XML namespace of **ENAME** is not identical to $ENSURI$, as defined by XML Namespaces, then an exception condition is raised: *data exception — no XML element with the specified QName (2201P)*.

- II) Otherwise, if <XML valid element namespace specification> is specified, and the XML namespace of **ENAME** is not identical to $ENSURI$, as defined by XML Namespaces, then an exception condition is raised: *data exception — no XML element with the specified namespace (2201Q)*.

C) Case:

- I) If DCS is DOCUMENT, then the General Rules of Subclause 10.24, “Validating an XQuery document or element node”, are applied with \mathcal{I}_j as *ITEM* and XS_k as *SCHEMA*; let $STAT$ be the *STATUS* and let **RES** be the *RESULT* returned from the application of those General Rules.

- II) Otherwise, the General Rules of Subclause 10.24, “Validating an XQuery document or element node”, are applied with C_k as *ITEM* and XS_k as *SCHEMA*; let *STAT* be the *STATUS* and let *RES* be the *RESULT* returned from the application of those General Rules.
 - D) If *STAT* is FAILURE, then an exception condition is raised: *data exception — validation failure (2201R)*.
 - E) Case:
 - I) If *DCS* is DOCUMENT, then let O_k be the XQuery element node that is the **child** of *RES*.
 - II) Otherwise, let O_k be *RES*.
 - 3) Otherwise, the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with C_k as *VALUE*; let O_k be the *COPY* returned from the application of those General Rules.
 - iv) Let R_j be an XQuery document node whose **children** property is replaced by an enumeration of O_k , $1 \text{ (one)} \leq k \leq M$.
- b) If I_j is an XQuery element node *E*, then:
- i) Case:
 - 1) If <XML valid according to clause> is specified, then let *XS* be *RXS*.
 - 2) Otherwise, let *NS* be the XML namespace of *E*. Let *XS* be a registered XML schema for which the current user has USAGE privilege and whose target namespace is identical to *NS*, as defined by XML Namespaces, chosen according to a deterministic implementation-defined (IW062) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user and the same value *V*, then the same registered XML schema will be chosen. If no *XS* is found, then an exception condition is raised: *data exception — no XML schema found (2201L)*.
 - ii) If <XML valid element clause> is specified, then let *ENAME* be the **node-name** property of *E*.

Case:

 - 1) If <XML valid element name specification> is specified, and either the XML NCName of *ENAME* is not equivalent to *EN* or the XML namespace of *ENAME* is not identical to *ENSURI*, as defined by XML Namespaces, then an exception condition is raised: *data exception — no XML element with the specified QName (2201P)*.
 - 2) Otherwise, if <XML valid element namespace specification> is specified and the XML namespace of *ENAME* is not identical to *ENSURI*, as defined by XML Namespaces, then an exception condition is raised: *data exception — no XML element with the specified namespace (2201Q)*.
 - iii) The General Rules of Subclause 10.24, “Validating an XQuery document or element node”, are applied with I_j as *ITEM* and *XS* as *SCHEMA*; let *STAT* be the *STATUS* and let *RES* be the *RESULT* returned from the application of those General Rules.
 - iv) If *STAT* is FAILURE, then an exception condition is raised: *data exception — validation failure (2201R)*.

- v) Let R_j be *RES*.
 - c) Otherwise, I_j is an XQuery comment node or an XQuery processing instruction node. The General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with I_j as *VALUE*; let R_j be the *COPY* returned from the application of those General Rules.
- 7) Let R be an XQuery sequence enumerated by R_j , $1 \text{ (one)} \leq j \leq N$.
 - 8) The result of <XML validate> is R .

Conformance Rules

- 1) Without Feature X271, “XMLValidate: data-driven case”, conforming SQL language shall not contain an <XML validate> that does not contain <XML valid according to clause>.
- 2) Without Feature X272, “XMLValidate: ACCORDING TO clause”, conforming SQL language shall not contain an <XML validate> that contains <XML valid according to clause>.
- 3) Without Feature X273, “XMLValidate: ELEMENT clause”, conforming SQL language shall not contain an <XML validate> that contains <XML valid element clause>.
- 4) Without Feature X284, “XMLValidate: NAMESPACE without ELEMENT clause”, conforming SQL language shall not contain an <XML validate> that contains an <XML valid element clause> that does not contain an <XML valid element name specification>.
- 5) Without Feature X286, “XMLValidate: NO NAMESPACE with ELEMENT clause”, conforming SQL language shall not contain an <XML validate> that contains an <XML valid element namespace specification> that contains NO NAMESPACE.
- 6) Without Feature X274, “XMLValidate: schema location”, conforming SQL language shall not contain an <XML validate> that contains <XML valid schema location>.
- 7) Without Feature X281, “XMLValidate with DOCUMENT option”, conforming SQL language shall not contain an <XML validate> that immediately contains a <document or content or sequence> that is DOCUMENT.
- 8) Without Feature X282, “XMLValidate with CONTENT option”, conforming SQL language shall not contain an <XML validate> that immediately contains a <document or content or sequence> that is CONTENT.
- 9) Without Feature X283, “XMLValidate with SEQUENCE option”, conforming SQL language shall not contain an <XML validate> that immediately contains a <document or content or sequence> that is SEQUENCE.

7 Query expressions

This Clause modifies Clause 7, “Query expressions”, in ISO/IEC 9075-2.

7.1 <table reference>

This Subclause modifies Subclause 7.6, “<table reference>”, in ISO/IEC 9075-2.

Function

Reference a table.

Format

```

<table primary> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <XML iterate> [ AS ] <correlation name>
      <left paren> <derived column list> <right paren>
    | <XML table> [ AS ] <correlation name>
      [ <left paren> <derived column list> <right paren> ]

<XML iterate> ::=
    XMLITERATE <left paren> <XML value expression> <right paren>

<XML table> ::=
    XMLTABLE <left paren>
      [ <XML namespace declaration> <comma> ]
      <XML table row pattern>
      [ <XML table argument list> ]
      COLUMNS <XML table column definitions> <right paren>

<XML table row pattern> ::=
    <character string literal>

<XML table argument list> ::=
    PASSING <XML table argument passing mechanism>
      <XML query argument>
      [ { <comma> <XML query argument> }... ]

<XML table argument passing mechanism> ::=
    <XML passing mechanism>

<XML table column definitions> ::=
    <XML table column definition>
      [ { <comma> <XML table column definition> }... ]

<XML table column definition> ::=
    <XML table ordinality column definition>
    | <XML table regular column definition>

<XML table ordinality column definition> ::=
    <column name> FOR ORDINALITY

<XML table regular column definition> ::=
    <column name> <data type> [ <XML passing mechanism> ]
      [ <default clause> ]

```

7.1 <table reference>

[PATH <XML table column pattern>]

<XML table column pattern> ::=
<character string literal>

Syntax Rules

- 1) **Augment SR 5)** by adding “<XML table>” to the list of <table primary>s that support lateral join..
- 2) **Insert after SR 21)a):** If <table primary> specifies <XML table> or <XML iterate>, then the <table primary> is not generally updatable, not simply updatable, not effectively updatable, and not insertable-into.
- 3) **Insert after the last SR:** If <table primary> contains <XML iterate>, then the <derived column list> shall contain exactly two <column name>s *CN1* and *CN2*, which shall not be equivalent. The declared type of <XML iterate> is a row type consisting of two fields, the first of which has a <field name> that is equivalent to *CN1* and a data type that is XML(SEQUENCE), and the second of which has a <field name> that is equivalent to *CN2* and a data type that is exact numeric with scale 0 (zero).
- 4) **Insert after the last SR:** If <XML table> is specified, then:
 - a) Case:
 - i) If <XML namespace declaration> *XND* is specified, then let *XNDC* be
WITH *XND*
 - ii) Otherwise, let *XNDC* be the zero-length string.
 - b) Let *XTRP* be the <XML table row pattern>.
 - c) Case:
 - i) If <XML table argument list> is specified, then let *XTTPM* be the <XML table argument passing mechanism>, let *NA* be the number of <XML query argument>s, let *XQA_i*, 1 (one) ≤ *i* ≤ *NA*, be an enumeration of the <XML query argument>s, and let *XQAL* be
PASSING *XTTPM* *XQA₁*,, *XQA_{NA}*
 - ii) Otherwise, let *XTTPM* be BY REF, and let *XQAL* be the zero-length string.
 - d) Let *NC* be the number of <XML table column definition>s. Let *XTCD_j*, 1 (one) ≤ *j* ≤ *NC*, be an enumeration of the <XML table column definition>s, in order from left to right. There shall be at most one *XTCD_j* that is <XML table ordinality column definition>.
 - e) For each *j* between 1 (one) and *NC*, inclusive, let *CN_j* be the <column name> contained in *XTCD_j*.
Case:
 - i) If *XTCD_j* is an <XML table ordinality column definition>, then let *SLI_j* be
I.N
 - ii) Otherwise:
 - 1) Let *DT_j* be the <data type> contained in *XTCD_j*.
 - 2) Case:
 - A) If *DT_j* is XML(SEQUENCE) then:

- I) If <XML table argument list> is not specified, then $XTCD_j$ shall contain <XML passing mechanism>.
- II) If $XTCD_j$ contains <XML passing mechanism>, then let XPM_j be this <XML passing mechanism>; otherwise, let XPM_j be $XTTPM$.
- III) Let XRM_j be RETURNING SEQUENCE XPM_j .
- B) Otherwise, <XML passing mechanism> shall not be specified. Let XRM_j be RETURNING CONTENT.
- 3) If $XTCD_j$ contains a <default option>, then let DEF_j be that <default option>; otherwise, let DEF_j be NULL.
- 4) If $XTCD_j$ contains an <XML table column pattern>, then let $PATH_j$ be that <XML table column pattern>; otherwise, let $PATH_j$ be a <character string literal> whose value is equivalent to the column name of the column identified by CN_j .
- 5) Let XQC_j be
- ```
XMLQUERY (PATH_j PASSING BY REF I.V XRM_j EMPTY ON EMPTY)
```
- 6) Let  $XE_j$  be
- ```
XML EXISTS ( PATH_j PASSING BY REF I.V )
```
- 7) Case:
- A) If DT_j is XML(SEQUENCE), then let CPM_j be XPM_j .
- B) If DT_j is an XML type, then let CPM_j be BY VALUE.
- C) Otherwise, let CPM_j be a zero-length string.
- 8) Let SLI_j be
- ```
CASE WHEN XE_j
THEN XMLCAST(XQC_j AS DT_j CPM_j)
ELSE DEF_j
END
```
- f) Let  $CORR$  be the <correlation name>.
- g) Case:
- i) If <derived column list> is specified, then let  $DCL$  be that <derived column list> and let  $DCLP$  be
- ```
( DCL )
```
- ii) Otherwise, let $DCLP$ be the zero-length string.
- h) TP is equivalent to the <table primary>

```
LATERAL
( XNDC
SELECT SLI_1 AS CN_1, SLI_2 AS CN_2, ..., SLI_NC AS CN_NC
FROM XMLITERATE ( XMLQUERY ( XTRP XQAL
RETURNING SEQUENCE BY REF EMPTY ON EMPTY ) )
```

AS I (V, N)
) AS CORR DCLP

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert after GR 3):** If a <table primary> *TP* simply contains an <XML iterate>, then let *V* be the value of the <XML value expression>.

Case:

- a) If *V* is the null value or the empty XQuery sequence, then the result of *TP* is an empty table.
- b) Otherwise, the result of *TP* is a table consisting of one row for each XQuery item in *V*. The value of the first column of each row is the corresponding XQuery item in *V*. The value of the second column is the sequential number of the XQuery item in *V*.

Conformance Rules

- 1) **Insert after the last CR:** Conforming SQL language shall not contain <XML iterate>.

NOTE 48 — This Conformance Rule ensures that <XML iterate> exists purely as a specification device within this document and cannot be used by conforming SQL language. Conforming SQL language can achieve the same effect by use of <XML table>.
- 2) **Insert after the last CR:** Without Feature X300, “XMLTable”, conforming SQL language shall not contain <XML table>.
- 3) **Insert after the last CR:** Without Feature X301, “XMLTable: derived column list option”, in conforming SQL language, a <table primary> that is an <XML table> shall not contain a <derived column list>.
- 4) **Insert after the last CR:** Without Feature X302, “XMLTable: ordinality column option”, in conforming SQL language, an <XML table> shall not contain an <XML table ordinality column definition>.
- 5) **Insert after the last CR:** Without Feature X303, “XMLTable: column default option”, in conforming SQL language, an <XML table regular column definition> shall not contain a <default clause>.
- 6) **Insert after the last CR:** Without Feature X304, “XMLTable: passing a context item”, in conforming SQL language, an <XML table argument list> shall not contain an <XML query context item>.
- 7) **Insert after the last CR:** Without Feature X305, “XMLTable: initializing an XQuery variable”, in conforming SQL language, an <XML table argument list> shall not contain an <XML query variable>.
- 8) **Insert after the last CR:** Without Feature X086, “XML namespace declarations in XMLTable”, in conforming SQL language, an <XML table> shall not contain an <XML namespace declaration>.

7.2 <query expression>

This Subclause modifies Subclause 7.17, “<query expression>”, in ISO/IEC 9075-2.

Function

Specify a table.

Format

```
<with clause> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | WITH <XML lexically scoped options> [ <comma> [ RECURSIVE ] <with list> ]
```

Syntax Rules

- 1) **Insert after the last SR:** A <with clause> shall contain an <XML lexically scoped option> or a <with list> or both.
- 2) **Insert after the last SR:** The scope of an <XML namespace declaration> contained in an <XML lexically scoped options> immediately contained in a <with clause> is the <query expression>.
- 3) **Insert after the last SR:** The scope of an <XML binary encoding> contained in an <XML lexically scoped options> immediately contained in a <with clause> is the <query expression>.

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert after GR 3)b)ii)1):** If the declared type of the i -th column of T is an XML type, then let $DDTC_i$ be the declared type of the i -th column of T and let DTC_i be

$DDTC_i$ BY REF

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X081, “Query-level XML namespace declarations”, in conforming SQL language, <with clause> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X131, “Query-level XMLBINARY clause”, in conforming SQL language, a <with clause> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.
- 3) **Insert after the last CR:** Without Feature X135, “XMLBINARY clause in subqueries”, in conforming SQL language, a <query expression> that is contained in another <query expression> shall not contain an <XML lexically scoped options> that contains an <XML binary encoding>.

8 Predicates

This Clause modifies Clause 8, “Predicates”, in ISO/IEC 9075-2.

8.1 <predicate>

This Subclause modifies Subclause 8.1, “<predicate>”, in ISO/IEC 9075-2.

Function

Specify a condition that can be evaluated to give a Boolean value.

Format

```
<predicate> ::=  
  !! All alternatives from ISO/IEC 9075-2  
  | <XML content predicate>  
  | <XML document predicate>  
  | <XML exists predicate>  
  | <XML valid predicate>
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Augment GR 1) by adding “<XML content predicate>, <XML document predicate>, <XML exists predicate>, and <XML valid predicate>” to the list of predicates.

Conformance Rules

No additional Conformance Rules.

8.2 <XML content predicate>

Function

Determine whether an XML value is an XQuery document node.

Format

```
<XML content predicate> ::=  
  <row value predicand> <XML content predicate part 2>  
  
<XML content predicate part 2> ::=  
  IS [ NOT ] CONTENT
```

Syntax Rules

- 1) The <row value predicand> shall be a <row value constructor predicand> that is a <common value expression> that is an <XML value expression> *XVE*.
- 2) The expression
XVE IS NOT CONTENT
is equivalent to
NOT (XVE IS CONTENT)

Access Rules

None.

General Rules

- 1) Let *V* be the value of *XVE*.
- 2) The result of
XVE IS CONTENT
is determined as follows.
Case:
 - a) If *V* is the null value, then the result is *Unknown*.
 - b) If *V* is an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then the result is *True*.
 - c) Otherwise, the result is *False*.

Conformance Rules

- 1) Without Feature X091, "XML content predicate", conforming SQL language shall not contain <XML content predicate>.

8.3 <XML document predicate>

Function

Determine whether an XML value is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes.

Format

```
<XML document predicate> ::=  
  <row value predicand> <XML document predicate part 2>  
  
<XML document predicate part 2> ::=  
  IS [ NOT ] DOCUMENT
```

Syntax Rules

1) The <row value predicand> shall be a <row value constructor predicand> that is a <common value expression> that is an <XML value expression> *XVE*.

2) The expression

XVE IS NOT DOCUMENT

is equivalent to

NOT (*XVE* IS DOCUMENT)

Access Rules

None.

General Rules

1) Let *V* be the value of *XVE*.

2) The result of

XVE IS DOCUMENT

is determined as follows.

Case:

a) If *V* is the null value, then the result is *Unknown*.

b) If *V* is an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then the result is *True*.

c) Otherwise, the result is *False*.

Conformance Rules

- 1) Without Feature X090, “XML document predicate”, conforming SQL language shall not contain <XML document predicate>.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

8.4 <XML exists predicate>

Function

Specify a test for a non-empty XQuery sequence.

Format

```
<XML exists predicate> ::=  
  XML EXISTS <left paren> <XQuery expression>  
    [ <XML query argument list> ] <right paren>
```

Syntax Rules

- 1) Let *XQE* be the <XQuery expression>.
- 2) If <XML query argument list> is specified, then let *XQP* be that <XML query argument list>; otherwise, let *XQP* be the zero-length string.
- 3) The following shall be valid according to the Syntax Rules of Subclause 6.19, “<XML query>”:

```
XMLQUERY ( XQE XQP RETURNING SEQUENCE EMPTY ON EMPTY )
```

NOTE 49 — As specified in ISO/IEC 9075-1, Subclause 6.3.3.3, “Rule evaluation order”, evaluation of Syntax Rules, Access Rules, and Conformance Rules is all performed concurrently.

Access Rules

None.

General Rules

- 1) Let *V* be the result of evaluating:

```
XMLQUERY ( XQE XQP RETURNING SEQUENCE EMPTY ON EMPTY )
```

- 2) The value of <XML exists predicate> is

Case:

- a) If *V* is the null value, then *Unknown*.
- b) If *V* is an empty XQuery sequence, then *False*.
- c) Otherwise, *True*.

Conformance Rules

- 1) Without Feature X096, “XMLExists”, conforming SQL language shall not contain <XML exists predicate>.

8.5 <XML valid predicate>

Function

Specify a test to determine whether an XML value is valid according to a registered XML schema.

Format

```
<XML valid predicate> ::=
  <row value predicand> <XML valid predicate part 2>

<XML valid predicate part 2> ::=
  IS [ NOT ] VALID
    <document or content or sequence>
    [ <XML valid according to clause> ]
```

Syntax Rules

- 1) The <row value predicand> shall be a <row value constructor predicand> that is a <common value expression> that is an <XML value expression> *XVE*.
- 2) Let *DCS* be the <document or content or sequence>. Let *XVACC* be the <XML valid according to clause>, if any; otherwise, let *XVACC* be the zero-length string.
- 3) If <XML valid predicate> immediately contains NOT, then the <XML valid predicate> is equivalent to

$$\text{NOT} (XVE \text{ IS VALID } DCS \text{ XVACC })$$
- 4) If <XML valid according to clause> is specified, then let *RXS* be the indicated registered XML schema, let *ENSURI* be the indicated XML namespace, if any, and let *EN* be the XML NCName of the indicated global element declaration schema component, if any.

NOTE 50 — Indicated registered XML schema, indicated XML namespace, and indicated global element declaration schema component are defined in Subclause 11.5, “<XML valid according to clause>”.

Access Rules

None.

General Rules

- 1) Let *V* be the value of *XVE*.
- 2) If *V* is the null value, then the result of the <XML valid predicate> is *Unknown* and no further General Rules of this Subclause are applied.
- 3) If *DCS* is DOCUMENT and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.

ISO/IEC 9075-14:2023(E)
8.5 <XML valid predicate>

- 4) If *DCS* is CONTENT and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
- 5) If *DCS* is SEQUENCE, then
Case:
 - a) If *V* is an empty XQuery sequence, then the result of the <XML valid predicate> is *True* and no further General Rules of this Subclause are applied.
 - b) Otherwise, if any XQuery item contained in *V* is an XQuery atomic value, XQuery attribute node, XQuery namespace node, or an XQuery text node, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
- 6) Let *N* be the number of XQuery items in *V*. Let \mathcal{I}_j , $1 \text{ (one)} \leq j \leq N$, be an enumeration in order of the XQuery items in *V*. Let $ITV_0 \text{ (zero)}$ be *True*.
- 7) For each *j*, $1 \text{ (one)} \leq j \leq N$,
Case:
 - a) If \mathcal{I}_j is an XQuery document node *D*, then:
 - i) Let *M* be the number of XQuery nodes in the **children** property of *D*.
 - ii) Let \mathcal{C}_k , $1 \text{ (one)} \leq k \leq M$, be an enumeration in order of the XQuery nodes in the **children** property of *D*. Let $ITV_0 \text{ (zero)}$ be *True*.
 - iii) For each *k*, $1 \text{ (one)} \leq k \leq M$,
Case:
 - 1) If \mathcal{C}_k is not an XQuery element node, XQuery comment node, or an XQuery processing instruction node, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
 - 2) If \mathcal{C}_k is an XQuery comment node or an XQuery processing instruction node, then let ITV_k be ITV_{k-1} .
 - 3) Otherwise, \mathcal{C}_k is an XQuery element node.
 - A) Case:
 - I) If <XML valid according to clause> is specified, then let XS_k be *RXS* and let *FOUND* be *True*.
 - II) Otherwise:
 - 1) Let *NS* be the XML namespace of \mathcal{C}_k .
 - 2) Let XS_k be a registered XML schema for which the current user has USAGE privilege and whose target namespace is identical to *NS*, as defined by XML Namespaces, chosen according to a deterministic implementation-defined (IW062) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user and the same value *V*, then the same registered XML schema will be chosen. If there is no XS_k , then let *FOUND* be *False*; otherwise, let *FOUND* be *True*.

B) Case:

I) If *FOUND* is *False*, then let ITV_k be the result of

ITV_{k-1} AND *Unknown*

II) Otherwise:

1) If <XML valid element clause> is specified, then let **ENAME** be the **node-name** property of C_k .

Case:

a) If <XML valid element name specification> is specified, and if either the XML NCName of **ENAME** is not equivalent to *EN* or the XML namespace of **ENAME** is not identical to *ENSURI*, as defined by *XML Namespaces*, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.

b) Otherwise, if <XML valid element namespace specification> is specified, and the XML namespace of **ENAME** is not identical to *ENSURI*, as defined by *XML Namespaces*, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.

2) Case:

a) If *DCS* is DOCUMENT, then the General Rules of Subclause 10.24, "Validating an XQuery document or element node", are applied with I_j as *ITEM* and XS_k as *SCHEMA*; let *STAT* be the *STATUS* and let **RES** be the *RESULT* returned from the application of those General Rules.

b) Otherwise, the General Rules of Subclause 10.24, "Validating an XQuery document or element node", are applied with C_k as *ITEM* and XS_k as *SCHEMA*; let *STAT* be the *STATUS* and let **RES** be the *RESULT* returned from the application of those General Rules.

3) Case:

a) If *STAT* is FAILURE, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.

b) Otherwise, let ITV_k be ITV_{k-1} .

iv) Let TV_j be the result of

TV_{j-1} AND ITV_M

b) If I_j is an XQuery element node **E**, then:

i) Case:

1) If <XML valid according to clause> is specified, then let *XS* be *RXS*, and let *FOUND* be *True*.

- 2) Otherwise, let **NS** be the XML namespace of **E**. Let **XS** be a registered XML schema for which the current user has USAGE privilege and whose target namespace is identical to **NS**, as defined by XML Namespaces, chosen according to a deterministic implementation-defined (IW062) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user and the same value *V*, then the same registered XML schema will be chosen. If there is no **XS**, then let **FOUND** be *False*; otherwise, let **FOUND** be *True*.
- ii) Case:
- 1) If **FOUND** is *False*, then let **TV_j** be the result of
- TV_{j-1}* AND *Unknown*
- 2) Otherwise:
- A) If <XML valid element clause> is specified, then let **ENAME** be the **node-name** property of **E**.
- Case:
- I) If <XML valid element name specification> is specified, and if either the XML NCName of **ENAME** is not equivalent to **EN**, or the XML namespace of **ENAME** is not identical to **ENSURI**, as defined by XML Namespaces, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
- II) Otherwise, if <XML valid element namespace specification> is specified, and the XML namespace of **ENAME** is not identical to **ENSURI**, as defined by XML Namespaces, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
- B) The General Rules of Subclause 10.24, “Validating an XQuery document or element node”, are applied with **I_j** as **ITEM** and **XS** as **SCHEMA**; let **STAT** be the **STATUS** and let **RES** be the **RESULT** returned from the application of those General Rules.
- C) Case:
- I) If **STAT** is FAILURE, then the result of the <XML valid predicate> is *False* and no further General Rules of this Subclause are applied.
- II) Otherwise, let **TV_j** be **TV_{j-1}**.
- c) Otherwise, **I_j** is an XQuery comment node or an XQuery processing instruction node. Let **TV_j** be **TV_{j-1}**.
- 8) The result of <XML valid predicate> is **TV_N**.

Conformance Rules

- 1) Without Feature X141, “IS VALID predicate: data-driven case”, conforming SQL language shall not contain an <XML valid predicate> that does not contain <XML valid according to clause>.

- 2) Without Feature X155, “IS VALID predicate: NAMESPACE without ELEMENT clause”, conforming SQL language shall not contain an <XML valid predicate> that contains an <XML valid element clause> that does not contain an <XML valid element name specification>.
- 3) Without Feature X157, “IS VALID predicate: NO NAMESPACE with ELEMENT clause”, conforming SQL language shall not contain an <XML valid predicate> that contains an <XML valid element namespace specification> that contains NO NAMESPACE.
- 4) Without Feature X142, “IS VALID predicate: ACCORDING TO clause”, conforming SQL language shall not contain an <XML valid predicate> that contains <XML valid according to clause>.
- 5) Without Feature X143, “IS VALID predicate: ELEMENT clause”, conforming SQL language shall not contain an <XML valid predicate> that contains <XML valid element clause>.
- 6) Without Feature X144, “IS VALID predicate: schema location”, conforming SQL language shall not contain an <XML valid predicate> that contains <XML valid schema location>.
- 7) Without Feature X145, “IS VALID predicate outside check constraints”, conforming SQL language shall not contain an <XML valid predicate> that is not directly contained in the <search condition> of a <check constraint definition>.
- 8) Without Feature X151, “IS VALID predicate: with DOCUMENT option”, conforming SQL language shall not contain an <XML valid predicate> that immediately contains a <document or content or sequence> that is DOCUMENT.
- 9) Without Feature X152, “IS VALID predicate: with CONTENT option”, conforming SQL language shall not contain an <XML valid predicate> that immediately contains a <document or content or sequence> that is CONTENT.
- 10) Without Feature X153, “IS VALID predicate: with SEQUENCE option”, conforming SQL language shall not contain an <XML valid predicate> that immediately contains a <document or content or sequence> that is SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9 Mappings

9.1 Mapping SQL <identifier>s to XML names

Function

Define the mapping of SQL <identifier>s to XML names.

Subclause Signature

"Mapping SQL <identifier>s to XML names" [General Rules] (
 Parameter: "IDENT",
 Parameter: "ESCAPE VARIANT"
) Returns: "XMLNAME"

IDENT — an <identifier>.

ESCAPE VARIANT — either *partially escaped* or *fully escaped*.

XMLNAME — the XML name created by the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *SQLI* be the *IDENT* and let *EV* be the *ESCAPE VARIANT* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLNAME*.
- 2) Let *N* be the number of characters in *SQLI*. Let S_1, S_2, \dots, S_N be the characters of *SQLI*, in order from left to right.
- 3) Let *TM* be the implementation-defined (IA091) mapping of the characters of SQL_TEXT to characters of Unicode.

NOTE 51 — Unicode scalar values in the ranges U+0000 through U+001F (inclusive), sometimes called the "C0 controls", and U+007F through U+009F (inclusive), sometimes called "delete" (U+007F) and the "C1 controls" (the remainder of that latter range) are not encoding of abstract characters in Unicode. Programs that conform to the Unicode Standard can treat these Unicode scalar values in exactly the same way as they treat the 7- and 8-bit equivalents in other protocols. Such usage constitutes a higher-level protocol and is beyond the scope of the Unicode standard. These Unicode scalar values do not occur in XML names, but can appear in other places in XML text.

- 4) For each *i* between 1 (one) and *N*, let T_i be the mapping of S_i to Unicode using *TM* and let X_i be the Unicode character string defined by the following rules.

Case:

- a) If S_i has no mapping to Unicode (i.e., $TM(S_i)$ is undefined), then X_i is implementation-defined (IA109).
- b) If S_i is <colon>, then
 Case:
 i) If $i = 1$ (one), then let X_i be `_x003A_`.
 ii) If EV is fully escaped, then let X_i be `_x003A_`.
 iii) Otherwise, let X_i be T_i .
- c) If $i \leq N-1$, S_i is <underscore>, and S_{i+1} is the lower-case letter “x”, then let X_i be `_x005F_`.
- d) If EV is fully escaped, $i = 1$ (one), $N \geq 3$, S_1 is either the upper-case letter “X” or the lower-case letter “x”, S_2 is either the upper-case letter “M” or the lower-case letter “m”, and S_3 is either the upper-case letter “L” or the lower-case letter “l”, then
 Case:
 i) If S_1 is the lower-case letter “x”, then let \mathbf{x}_1 be `_x0078_`.
 ii) If S_1 is the upper-case letter “X”, then let \mathbf{x}_1 be `_x0058_`.
- e) If exactly one of the following is true:
 — the SQL-implementation supports Feature X211, “XML 1.1 support”, and either T_i is not a valid XML 1.1 NameChar, or $i = 1$ (one) and T_1 is not a valid XML 1.1 NameStartChar;
 — the SQL-implementation does not support Feature X211, “XML 1.1 support”, and either T_i is not a valid XML 1.0 NameChar, or $i = 1$ (one) and T_1 is not a valid XML 1.0 NameStartChar.
 then:
 i) Let U_1, U_2, \dots, U_8 be the eight <upper-case hexit>s such that T_i is $U+U_1U_2\dots U_8$ in the UCS-4 encoding.
 ii) Case:
 1) If $U_1 = 0$ (zero), $U_2 = 0$ (zero), $U_3 = 0$ (zero), and $U_4 = 0$ (zero), then let X_i be `_xU5U6U7U8_`.
 NOTE 52 — This case implies that T_i has a UCS-2 encoding, which is $U+U_5U_6U_7U_8$.
 2) Otherwise, let \mathbf{x}_i be `_xU3U4U5U6U7U8_`.
- f) Otherwise, let X_i be T_i .
 NOTE 53 — That is, any character in *SQL* that does not occasion a problem as a character in an XML 1.0 NCName or XML 1.1 NCName is simply copied into the result.
- 5) Let ***XMLN*** be the XML name that is the character string concatenation of X_1, X_2, \dots , and X_N in order from left to right.
- 6) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives ***XMLN*** as *XMLNAME*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.2 Mapping a multi-part SQL name to an XML name

Function

Define the mapping of a sequence of SQL <identifier>s to an XML name.

Subclause Signature

"Mapping a multi-part SQL name to an XML name" [General Rules] (
Parameter: "SEQUENCE OF SQL IDENTIFIERS"
) Returns: "XMLNAME"

SEQUENCE OF SQL IDENTIFIERS — a sequence of <identifier>s.

XMLNAME — the XML name created by the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *SQLIS* be the *SEQUENCE OF SQL IDENTIFIERS* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLNAME*.
- 2) Let *n* be the number of SQL <identifier>s in *SQLIS*. Let *SQLI_i*, 1 (one) ≤ *i* ≤ *n* be an SQL <identifier> equivalent to the *i*-th element of *SQLIS*.
- 3) Let NP(*S*) be the mapping of a string *S* to a result string defined as follows:
 - a) Let *m* be the number of characters in *S*. For each character *S_j*, 1 (one) ≤ *j* ≤ *m*, in *S*, let *NPS_j* be defined as follows.
Case:
 - i) If *S_j* is <period>, then *NPS_j* is `_x002E_`.
 - ii) Otherwise, *NPS_j* is *S_j*.
 - b) NP(*S*) is the concatenation of *NPS_j*, 1 (one) ≤ *j* ≤ *m*.
- 4) For each *i* between 1 (one) and *n*, the General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *SQLI_i* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLN_i* be the *XMLNAME* returned from the application of those General Rules.
- 5) Let *XMLR* be the result of:

NP(*XMLN₁*) || '.' || NP(*XMLN₂*) || '.' || ... || NP(*XMLN_n*)

9.2 Mapping a multi-part SQL name to an XML name

- 6) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives ***XMLR*** as *XMLNAME*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.3 Mapping XML names to SQL <identifier>s

Function

Define the mapping of XML names to SQL <identifier>s.

NOTE 54 — This document specifies no syntax for invoking the mapping specified in this Subclause, which is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Subclause Signature

"Mapping XML names to SQL <identifier>s" [General Rules] (
Parameter: "XMLNAME"
) Returns: "SQLIDENT"

XMLNAME — an XML name; a sequence of Unicode characters.

SQLIDENT — the SQL identifier that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let **XMLN** be the *XMLNAME* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SQLIDENT*.
- 2) **XMLN** is a sequence of Unicode characters. Let *N* be the number of characters in **XMLN**. Let X_1, X_2, \dots, X_N be the characters of **XMLN** in order from left to right.
- 3) Let the *N* Unicode character strings U_1, U_2, \dots, U_N be defined as follows.

If U_i , $1 \text{ (one)} \leq i \leq N$, has not yet been determined, then

Case:

- a) If $X_i = \text{'_'} (an <underscore>)$, and $X_{i+1} = \text{'x'}$, and each of $X_{i+2}, X_{i+3}, X_{i+4}$, and X_{i+5} are all <hexit>s, and $X_{i+6} = \text{'_'} (an <underscore>)$, then

Case:

- i) If the Unicode code point $U+X_{i+2}X_{i+3}X_{i+4}X_{i+5}$ is a Unicode assigned character *UC*, then let U_i be the character string of length 1 (one) whose character is *UC* and let $U_{i+1}, U_{i+2}, U_{i+3}, U_{i+4}, U_{i+5}$, and U_{i+6} be the zero-length string.
- ii) Otherwise, $U_i, U_{i+1}, U_{i+2}, U_{i+3}, U_{i+4}, U_{i+5}$, and U_{i+6} are implementation-defined (IA110).

9.3 Mapping XML names to SQL <identifier>s

- b) If $X_i = \text{'_'} (an <underscore>)$, and $X_{i+1} = \text{'x'}$, and each of $X_{i+2}, X_{i+3}, X_{i+4}, X_{i+5}, X_{i+6}$, and X_{i+7} , are all <hexit>s, and $X_{i+8} = \text{'_'} (an <underscore>)$, then

Case:

- i) If the Unicode code point $U+X_{i+2}X_{i+3}X_{i+4}X_{i+5}X_{i+6}X_{i+7}$ is a Unicode assigned character UC , then let U_i be the character string of length 1 (one) whose character is UC and let $U_{i+1}, U_{i+2}, U_{i+3}, U_{i+4}, U_{i+5}, U_{i+6}, U_{i+7}$, and U_{i+8} be the zero-length string.
 - ii) Otherwise, $U_i, U_{i+1}, U_{i+2}, U_{i+3}, U_{i+4}, U_{i+5}, U_{i+6}, U_{i+7}$, and U_{i+8} are implementation-defined (IA110).
- c) Otherwise, let U_i be the character string of length 1 (one) whose character is X_i .
- 4) Let U be the Unicode character string constructed by concatenating every $U_i, 1 (one) \leq i \leq N$, in order by i .
 - 5) Let $SQLI$ be the SQL_TEXT character string obtained by mapping the Unicode character string U to SQL_TEXT using the implementation-defined (IA091) mapping of Unicode to SQL_TEXT. If $SQLI$ can not be mapped to SQL_TEXT, then an exception condition is raised: *SQL/XML mapping error — unmappable XML Name (ON001)*.
 - 6) Let the SQL <identifier> $SQLID$ that is the result of the mapping of $SQLI$ to SQL_IDENTIFIER be the <delimited identifier> " $SQLI$ ".
 - 7) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives $SQLID$ as $SQLIDENT$.

Conformance Rules

- 1) Without Feature X400, "Name and identifier mapping", a conforming application shall not invoke this Subclause of this document.

9.4 Mapping an SQL data type to an XML name

Function

Define the mapping of an SQL data type or domain to an XML name.

Subclause Signature

"Mapping an SQL data type to an XML name" [General Rules] (
Parameter: "DATA TYPE"
) Returns: "XML NAME"

DATA TYPE — an SQL data type or the underlying data type of a domain.

XML NAME — the XML name that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *D* be the *DATA TYPE* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XML NAME*.
- 2) If *D* is a character string type, then:
 - a) Let *SQLCS* be the character set of *D*.
 - b) Let *N* be the length or maximum length of *D*.
 - c) Let *CSM* be the implementation-defined (IA091) mapping of strings of *SQLCS* to strings of Unicode. Let *MAXCSL* be the maximum length in characters of *CSM(S)*, for all strings *S* of length *N* characters.
 - d) Let *MLIT* be the canonical XML schema literal of the XML schema type **xs:integer** denoting *MAXCSL*.
 - e) Let *NLIT* be the canonical XML schema literal denoting *N* in the lexical representation of XML schema type **xs:integer**.
 - f) Case:
 - i) If *CSM* is homomorphic, and *N* equals *MAXCSL*, then
Case:
 - 1) If the type designator of *D* is CHARACTER, then let **XMLN** be the following:
CHAR_MLIT

9.4 Mapping an SQL data type to an XML name

- 2) If the type designator of D is CHARACTER VARYING, then let \mathbf{XMLN} be the following:

$\mathbf{VARCHAR_MLIT}$

- 3) If the type designator of D is CHARACTER LARGE OBJECT, then let \mathbf{XMLN} be the following:

$\mathbf{CLOB_MLIT}$

- ii) If CSM is homomorphic, and N does not equal $MAXCSL$, then

Case:

- 1) If the type designator of D is CHARACTER, then let \mathbf{XMLN} be the following:

$\mathbf{CHAR_NLIT_MLIT}$

- 2) If the type designator of D is CHARACTER VARYING, then let \mathbf{XMLN} be the following:

$\mathbf{VARCHAR_NLIT_MLIT}$

- 3) If the type designator of D is CHARACTER LARGE OBJECT, then let \mathbf{XMLN} be the following:

$\mathbf{CLOB_NLIT_MLIT}$

- iii) Otherwise,

Case:

- 1) If the type designator of D is CHARACTER or CHARACTER VARYING, then let \mathbf{XMLN} be the following:

$\mathbf{VARCHAR_NLIT_MLIT}$

- 2) If the type designator of D is CHARACTER LARGE OBJECT, then let \mathbf{XMLN} be the following:

$\mathbf{CLOB_NLIT_MLIT}$

- 3) If the type designator of D is BINARY LARGE OBJECT, then:

- a) Let N be the maximum length of D . Let \mathbf{XN} be the canonical XML schema literal denoting N in the lexical representation of XML schema type $\mathbf{xs:integer}$.

- b) Let \mathbf{XMLN} be the following:

$\mathbf{BLOB_XN}$

- 4) If the type designator of D is NUMERIC, then:

- a) Let P be the precision of D . Let \mathbf{XP} be the canonical XML schema literal denoting P in the lexical representation of XML schema type $\mathbf{xs:integer}$.

- b) Let S be the scale of D . Let \mathbf{XS} be the canonical XML schema literal denoting S in the lexical representation of XML schema type $\mathbf{xs:integer}$.

- c) Let \mathbf{XMLN} be the following:

NUMERIC_XP_XS

- 5) If the type designator of D is DECIMAL, then:
- Let P be the precision of D . Let XP be the canonical XML schema literal denoting P in the lexical representation of XML schema type **xs:integer**.
 - Let S be the scale of D . Let XS be the canonical XML schema literal denoting S in the lexical representation of XML schema type **xs:integer**.
 - Let **XMLN** be the following:

DECIMAL_XP_XS

- 6) If the type designator of D is INTEGER, then let **XMLN** be the following:

INTEGER

- 7) If the type designator of D is SMALLINT, then let **XMLN** be the following:

SMALLINT

- 8) If the type designator of D is BIGINT, then let **XMLN** be the following:

BIGINT

- 9) If the type designator of D is FLOAT, then:

- Let P be the precision of D . Let XP be the canonical XML schema literal denoting P in the lexical representation of XML schema type **xs:integer**.
- Let **XMLN** be the following:

FLOAT_XP

- 10) If the type designator of D is REAL, then let **XMLN** be the following:

REAL

- 11) If the type designator of D is DOUBLE PRECISION, then let **XMLN** be the following:

DOUBLE

- 12) If the type designator of D is BOOLEAN, then let **XMLN** be the following:

BOOLEAN

- 13) If the type designator of D is TIME WITHOUT TIME ZONE, then:

- Let TP be the time precision of D . Let XTP be the canonical XML schema literal denoting TP in the lexical representation of XML schema type **xs:integer**.
- Let **XMLN** be the following:

TIME_XTP

- 14) If the type designator of D is TIME WITH TIME ZONE, then:

9.4 Mapping an SQL data type to an XML name

a) Let *TP* be the time precision of *D*. Let ***XTP*** be the canonical XML schema literal denoting *TP* in the lexical representation of XML schema type ***xs:integer***.

b) Let ***XMLN*** be the following:

TIME_WTZ_XTP

15) If the type designator of *D* is **TIMESTAMP WITHOUT TIME ZONE**, then:

a) Let *TSP* be the timestamp precision of *D*. Let ***XTSP*** be the canonical XML schema literal denoting *TSP* in the lexical representation of XML schema type ***xs:integer***.

b) Let ***XMLN*** be the following:

TIMESTAMP_XTSP

16) If the type designator of *D* is **TIMESTAMP WITH TIME ZONE**, then:

a) Let *TSP* be the timestamp precision of *D*. Let ***XTSP*** be the canonical XML schema literal denoting *TSP* in the lexical representation of XML schema type ***xs:integer***.

b) Let ***XMLN*** be the following:

TIMESTAMP_WTZ_XTSP

17) If the type designator of *D* is **DATE**, then let ***XMLN*** be the following:

DATE

18) If *D* is a domain, then let *C*, *S*, and *N* be the catalog name, schema name, and domain name of *D*, respectively. The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “Domain”, *C*, *S*, and *N* as **SEQUENCE OF SQL IDENTIFIERS**; let ***XMLN*** be the ***XMLNAME*** returned from the application of those General Rules.

19) If *D* is a row type, then let the XML name ***IDI*** be an implementation-dependent (UA031) identifier for the row type. Two row types that have different numbers of fields, different field names, or different declared types in corresponding fields shall have different values of ***IDI***. It is implementation-dependent (UA031) whether the types of two sites of row type, having the same number of fields, and having corresponding fields of the same name and declared type, receive the same row type identifier. Let ***XMLN*** be **Row.*IDI***.

20) If *D* is a distinct type, then let *C*, *S*, and *N* be the catalog name, schema name, and type name of *D*, respectively. The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “UDT”, *C*, *S*, and *N* as **SEQUENCE OF SQL IDENTIFIERS**; let ***XMLN*** be the ***XMLNAME*** returned from the application of those General Rules.

21) If *D* is an array type, then let *ET* be the element type of *D* and let *M* be the maximum cardinality of *D*. The General Rules of this Subclause are applied with *ET* as **DATA TYPE**; let ***XMLET*** be the ***XML NAME*** returned from the application of those General Rules. Let ***MLIT*** be the canonical XML schema literal denoting *M* in the lexical representation of XML schema type ***xs:integer***. Let ***XMLN*** be **Array_*MLIT*.*XMLET***.

22) If *D* is a multiset type, then let *ET* be the element type of *D*. The General Rules of this Subclause are applied with *ET* as **DATA TYPE**; let ***XMLET*** be the ***XML NAME*** returned from the application of those General Rules. Let ***XMLN*** be **Multiset.*XMLET***.

23) If *D* is an XML type, then let ***XMLN*** be **XML**.

- 24) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives ***XMLN*** as *XML NAME*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.5 Mapping SQL data types to XML schema data types

Function

Define the mapping of SQL data types and domains to XML schema data types.

Subclause Signature

"Mapping SQL data types to XML schema data types" [General Rules] (
 Parameter: "SQLTYPE",
 Parameter: "ENCODING",
 Parameter: "NULLS"
) Returns: "SCHEMA TYPE"

SQLTYPE — an SQL data type or a domain.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

SCHEMA TYPE — the XML schema type that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *SQLT* be the *SQLTYPE*, let *ENCODING* be the *ENCODING*, and let *NULLS* be the *NULLS* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMA TYPE*.
- 2) Case:
 - a) If *NULLS* is "absent", then let the XML text *XMLNULLS* be `minOccurs="0"` .
 - b) If *NULLS* is "nil", then let the XML text *XMLNULLS* be `nillable="true"` .
- 3) Let *TM* be the implementation-defined (IA091) mapping of character strings of *SQL_TEXT* to character strings of Unicode.
- 4) Let *xs* be the XML namespace prefix to be used to identify the XML schema namespace as shown in Table 2, "XML namespace prefixes and their URIs".
- 5) Let *sqlxml* be the XML namespace prefix to be used to identify the XML namespace as shown in Table 2, "XML namespace prefixes and their URIs".
- 6) Let *XMLT* denote the representation of the XML schema data type that is the mapping of *SQLT* into XML. *XMLT* is defined by the following rules.

7) Case:

a) If *SQLT* is a character string type, then:

- i) Let *SQLCS* be the character set of *SQLT*. Let *SQLCSN* be the name of *SQLCS*. Let *N* be the length or maximum length of *SQLT*.
- ii) Let *CSM* be the implementation-defined (IA091) mapping of strings of *SQLCS* to strings of Unicode. Let *MAXCSL* be the maximum length in characters of *CSM(S)*, for all strings *S* of length *N* characters.
- iii) Let *NLIT* and *MLIT* be canonical XML schema literals of the XML schema type **xs:integer** denoting *N* and *MAXCSL*, respectively.

iv) Case:

1) If the type designator of *SQLT* is CHARACTER, then:

A) Case:

I) If *CSM* is homomorphic, then let **FACET** be the XML text:

```
<xs:length value="MLIT">
```

II) Otherwise, let **FACET** be the XML text:

```
<xs:maxLength value="MLIT">
```

B) It is implementation-defined (IA100) whether the XML text **ANNNT** is the zero-length string or given by:

```
name="CHAR"
```

C) It is implementation-defined (IA100) whether the XML text **ANNL** is the zero-length string or given by:

```
length="NLIT"
```

2) If the type designator of *SQLT* is CHARACTER VARYING, then:

A) Let **FACET** be the XML text:

```
<xs:maxLength value="MLIT">
```

B) It is implementation-defined (IA100) whether the XML text **ANNNT** is the zero-length string or given by:

```
name="VARCHAR"
```

C) It is implementation-defined (IA100) whether the XML text **ANNL** is the zero-length string or given by:

```
maxLength="NLIT"
```

3) If the type designator of *SQLT* is CHARACTER LARGE OBJECT, then:

A) Let **FACET** be the XML text:

```
<xs:maxLength value="MLIT">
```

9.5 Mapping SQL data types to XML schema data types

- B) It is implementation-defined (IA100) whether the XML text **ANNNT** is the zero-length string or given by:

```
name="CLOB"
```

- C) It is implementation-defined (IA100) whether the XML text **ANNL** is the zero-length string or given by:

```
maxLength="NLIT"
```

- v) Let the XML text **SQLCSNLIT** be the result of mapping *SQLCSN* to Unicode using *TM*. It is implementation-defined (IA100) whether the XML text **ANNCS** is the zero-length string or given by:

```
characterSetName="SQLCSNLIT"
```

- vi) Let *SQLCON* be the name of the collation of *SQLT*. Let the XML text **SQLCONLIT** be the result of mapping *SQLCON* to Unicode using *TM*. It is implementation-defined (IA100) whether the XML text **ANNCO** is the zero-length string or given by:

```
collation="SQLCONLIT"
```

- vii) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                   ANNNT ANNL ANNCS ANNCO/>
  </xs:appinfo>
</xs:annotation>
```

- viii) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:string">
    FACET
  </xs:restriction>
</xs:simpleType>
```

- b) If *SQLT* is a binary string type, then:

- i) Let *N* be the length or maximum length of *SQLT*. Let **NLIT** be the canonical XML schema literal denoting *N* in the lexical representation of the XML schema type **xs:integer**.

- ii) Case:

- 1) If *ENCODING* indicates that binary strings are to be encoded in hex, then let **EN** be the XML text **hexBinary**.

- 2) Otherwise, let **EN** be the XML text **base64Binary**.

- iii) Case:

- 1) If the type designator of *SQLT* is **BINARY**, then let **FACET** be the XML text:

```
<xs:length value="NLIT">
```

- 2) Otherwise, let **FACET** be the XML text:

`<xs:maxLength value="NLIT">`

iv) Case:

- 1) If the type designator of *SQLT* is BINARY, then it is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or given by:

`name="BINARY"`

- 2) If the type designator of *SQLT* is VARBINARY, then it is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or given by:

`name="VARBINARY"`

- 3) Otherwise, it is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or given by:

`name="BLOB"`

v) Case:

- 1) If the type designator of *XQLT* is BINARY, then it is implementation-dependent (UA040) whether the XML text **ANNL** is the zero-length string or given by:

`length="NLIT"`

- 2) Otherwise, it is implementation-defined (IA100) whether the XML text **ANNL** is the zero-length string or given by:

`maxLength="NLIT"`

vi) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
      ANN ANNL/>
  </xs:appinfo>
</xs:annotation>
```

vii) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:EN">
    FACET
  </xs:restriction>
</xs:simpleType>
```

c) If the type designator of *SQLT* is NUMERIC or DECIMAL, then:

- i) Let *P* be the precision of *SQLT*. Let **PLIT** be the canonical XML schema literal denoting *P* in the lexical representation of the XML schema type **xs:integer**. Let **FACETP** be the XML text:

`<xs:totalDigits value="PLIT"/>`

9.5 Mapping SQL data types to XML schema data types

- ii) Let S be the scale of $SQLT$. Let $SLIT$ be the canonical XML schema literal denoting S in the lexical representation of the XML schema type $xs:integer$. Let $FACETS$ be the XML text:

```
<xs:fractionDigits value="SLIT"/>
```

- iii) Case:

- 1) If the type designator of $SQLT$ is NUMERIC, then:

- A) It is implementation-defined (IA100) whether the XML text $ANNT$ is the zero-length string or

```
name="NUMERIC"
```

- B) It is implementation-defined (IA100) whether the XML text $ANNP$ is the zero-length string or:

```
precision="PLIT"
```

- 2) If the type designator of $SQLT$ is DECIMAL, then:

- A) It is implementation-defined (IA100) whether the XML text $ANNT$ is the zero-length string or:

```
name="DECIMAL"
```

- B) Let UP be the value of the $\langle precision \rangle$ specified in the $\langle data\ type \rangle$ used to create the descriptor of $SQLT$. Let $UPLIT$ be the canonical XML schema literal denoting UP in the lexical representation of the XML schema type $xs:integer$. It is implementation-defined (IA100) whether the XML text $ANNP$ is the zero-length string or:

```
userPrecision="UPLIT"
```

NOTE 55 — UP can be less than P , as specified in SR 29) of Subclause 6.1, " $\langle data\ type \rangle$ ", in ISO/IEC 9075-2.

- iv) It is implementation-defined (IA100) whether the XML text $ANNS$ is the zero-length string or:

```
scale="SLIT"
```

- v) It is implementation-defined (IA100) whether the XML text ANN is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
      ANNT ANNP ANNS/>
  </xs:appinfo>
</xs:annotation>
```

- vi) $XMLT$ is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:decimal">
    FACETP
    FACETS
```

```
</xs:restriction>
</xs:simpleType>
```

d) If the type designator of *SQLT* is INTEGER, SMALLINT, or BIGINT, then:

i) Let *MAX* be the maximum value representable by *SQLT*. Let **MAXLIT** be the canonical XML schema literal denoting *MAX* in the lexical representation of the XML schema type **xs:integer**. Let **FACETMAX** be the XML text:

```
<xs:maxInclusive value="MAXLIT"/>
```

ii) Let *MIN* be the minimum value representable by *SQLT*. Let **MINLIT** be the canonical XML schema literal denoting *MIN* in the lexical representation of the XML schema type **xs:integer**. Let **FACETMIN** be the XML text:

```
<xs:minInclusive value="MINLIT"/>
```

iii) Case:

1) If the type designator of *SQLT* is INTEGER, then it is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  name="INTEGER"/>
  </xs:appinfo>
</xs:annotation>
```

2) If the type designator of *SQLT* is SMALLINT, then it is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  name="SMALLINT"/>
  </xs:appinfo>
</xs:annotation>
```

3) If the type designator of *SQLT* is BIGINT, then it is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  name="BIGINT"/>
  </xs:appinfo>
</xs:annotation>
```

iv) It is implementation-defined (IA104) whether *REST* is

```
<xs:restriction base="xs:integer">
  FACETMAX
  FACETMIN
</xs:restriction>
```

or determined by

1) Case:

A) If there is no row in Table 3, “Constraining facets of XML schema integer types” such that *MAX* is less than or equal to the value in the “maxInclusive”

9.5 Mapping SQL data types to XML schema data types

column and *MIN* is greater than or equal to the value in the “minInclusive” column, then:

- I) Let *TYPE* be **xs:integer**.
 - II) Let *FMAX* be *FACETMAX*.
 - III) Let *FMIN* be *FACETMIN*.
- B) Otherwise:
- I) Let *TYPE* be the contents of the “Type” column, in Table 3, “Constraining facets of XML schema integer types”, taken from the first row in the table for which *MAX* is less than or equal to the value in the “maxInclusive” column and *MIN* is greater than or equal to the value in the “minInclusive” column.
 - II) If *MAX* is equal to the value of the “maxInclusive”, in the selected row of the table, then let *FMAX* be the zero-length string; otherwise, let *FMAX* be *FACETMAX*.
 - III) If *MIN* is equal to the value of the “minInclusive”, in the selected row of the table, then let *FMIN* be the zero-length string; otherwise, let *FMIN* be *FACETMIN*.
- 2) Let *REST* be:

```
<xs:restriction base="TYPE">
  FMAX
  FMIN
</xs:restriction>
```

Table 3 — Constraining facets of XML schema integer types

Type	minInclusive	maxInclusive
xs:unsignedByte	0	255
xs:byte	-128	127
xs:unsignedShort	0	$2^{16}-1$ (65 535)
xs:short	-2^{15} (-32 768)	$2^{15}-1$ (32 767)
xs:unsignedInt	0	$2^{32}-1$ (4 294 967 295)
xs:int	-2^{31} (-2 147 483 648)	$2^{31}-1$ (2 147 483 647)
xs:unsignedLong	0	$2^{64}-1$ (18 446 744 073 709 551 615)
xs:long	-2^{63} (-9 223 372 036 854 775 808)	$2^{63}-1$ (9 223 372 036 854 775 807)

- v) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
```

```
REST  
</xs:simpleType>
```

e) If *SQLT* is approximate numeric, then:

i) Let *P* be the binary precision of *SQLT*, let *MINEXP* be the minimum binary exponent supported by *SQLT*, and let *MAXEXP* be the maximum binary exponent supported by *SQLT*.

ii) Case:

1) If *P* is less than or equal to 24 binary digits (bits), *MINEXP* is greater than or equal to -149, and *MAXEXP* is less than or equal to 104, then let the XML text *TYPE* be **float**.

2) Otherwise, let the XML text *TYPE* be **double**.

iii) Case:

1) If the type designator of *SQLT* is REAL, then the XML text *ANNUP* is the zero-length string, and it is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="REAL"
```

2) If the type designator of *SQLT* is DOUBLE PRECISION, then the XML text *ANNUP* is the zero-length string, and it is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="DOUBLE PRECISION"
```

3) Otherwise:

A) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="FLOAT"
```

B) Let *UP* be the value of the <precision> specified in the <data type> used to create the descriptor of *SQLT*. Let *UPLIT* be the canonical XML schema literal denoting *UP* in the lexical representation of the XML schema type **xs:integer**. It is implementation-defined (IA100) whether the XML text *ANNUP* is the zero-length string or:

```
userPrecision="UPLIT"
```

NOTE 56 — *UP* can be less than *P*, as specified in SR 31) of Subclause 6.1, "<data type>", in ISO/IEC 9075-2.

iv) Let *PLIT* be the canonical XML schema literal denoting *P* in the lexical representation of the XML schema type **xs:integer**. It is implementation-defined (IA100) whether the XML text *ANNP* is the zero-length string or:

```
precision="PLIT"
```

v) Let *MINLIT* be the canonical XML schema literal denoting *MINEXP* in the lexical representation of the XML schema type **xs:integer**. It is implementation-defined (IA100) whether the XML text *ANNMIN* is the zero-length string or:

```
minExponent="MINLIT"
```

9.5 Mapping SQL data types to XML schema data types

- vi) Let **MAXLIT** be the canonical XML schema literal denoting *MAXEXP* in the lexical representation of the XML schema type **xs:integer**. It is implementation-defined (IA100) whether the XML text **ANNMAX** is the zero-length string or:

```
maxExponent="MAXLIT"
```

- vii) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  ANNT ANNP ANNUP ANNMAX ANNMIN/>
  </xs:appinfo>
</xs:annotation>
```

- viii) It is implementation-defined (IA106) whether **XMLT** is **xs:TYPE** or the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:TYPE">
  </xs:restriction>
</xs:simpleType>
```

- f) If the type designator of *SQLT* is BOOLEAN, then it is implementation-defined (IA105) whether **XMLT** is **xs:boolean** or the XML schema type defined by:

```
<xs:simpleType>
  <xs:annotation>
    <xs:appinfo>
      <sqlxml:sqltype kind="PREDEFINED"
                    name="BOOLEAN"/>
    </xs:appinfo>
  </xs:annotation>
  <xs:restriction base="xs:boolean"/>
</xs:simpleType>
```

- g) If the type designator of *SQLT* is DATE, then:

- i) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  name="DATE"/>
  </xs:appinfo>
</xs:annotation>
```

- ii) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:date">
    <xs:pattern
      value="\p{Nd}{4}-\p{Nd}{2}-\p{Nd}{2}"/>
  </xs:restriction>
</xs:simpleType>
```

- h) If *SQLT* is TIME WITHOUT TIME ZONE, then:

9.5 Mapping SQL data types to XML schema data types

- i) Let S be the <time fractional seconds precision> of $SQLT$. Let $SLIT$ be the canonical XML schema literal denoting S in the lexical representation of XML schema type $xs:integer$.
- ii) Case:
- 1) If S is greater than 0 (zero), then let the XML text $FACETP$ be:


```
<xs:pattern value=
  "\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}.\p{Nd}{SLIT}"/>
```
 - 2) Otherwise, let the XML text $FACETP$ be:


```
<xs:pattern value=
  "\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}"/>
```
- iii) It is implementation-defined (IA100) whether the XML text $ANNT$ is the zero-length string or:
- ```
name="TIME"
```
- iv) It is implementation-defined (IA100) whether the XML text  $ANNS$  is the zero-length string or:
- ```
scale="SLIT"
```
- v) It is implementation-defined (IA100) whether the XML text ANN is the zero-length string or:
- ```
<xs:annotation>
 <xs:appinfo>
 <sqlxml:sqltype kind="PREDEFINED"
 ANNT ANNS/>
 </xs:appinfo>
</xs:annotation>
```
- vi)  $XMLT$  is the XML schema type defined by:
- ```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:time">
    FACETP
  </xs:restriction>
</xs:simpleType>
```
- i) If $SQLT$ is TIME WITH TIME ZONE, then:
- i) Let S be the <time fractional seconds precision> of $SQLT$. Let $SLIT$ be the canonical XML schema literal denoting S in the lexical representation of XML schema type $xs:integer$.
 - ii) Let the XML text TZ be:


```
(\+|-)\p{Nd}{2}:\p{Nd}{2}
```
 - iii) Case:
 - 1) If S is greater than 0 (zero), then let the XML text $FACETP$ be:


```
<xs:pattern value=
            "\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}.\p{Nd}{SLIT}TZ"/>
```

9.5 Mapping SQL data types to XML schema data types

2) Otherwise, let the XML text *FACETP* be:

```
<xs:pattern value=
  "\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}TZ"/>
```

iv) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="TIME WITH TIME ZONE"
```

v) It is implementation-defined (IA100) whether the XML text *ANNS* is the zero-length string or:

```
scale="SLIT"
```

vi) It is implementation-defined (IA100) whether the XML text *ANN* is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
      ANNT ANNS/>
  </xs:appinfo>
</xs:annotation>
```

vii) *XMLT* is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:time">
    FACETP
  </xs:restriction>
</xs:simpleType>
```

j) If *SQTL* is *TIMESTAMP WITHOUT TIME ZONE*, then:

i) Let *S* be the <time fractional seconds precision> of *SQTL*. Let *SLIT* be the canonical XML schema literal denoting *S* in the lexical representation of XML schema type *xs:integer*.

ii) Let the XML text *DATETIME* be:

```
\p{Nd}{4}-\p{Nd}{2}-\p{Nd}{2}T\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}
```

iii) Case:

1) If *S* is greater than 0 (zero), then let the XML text *FACETP* be:

```
<xs:pattern value=
  "DATETIME.\p{Nd}{SLIT}"/>
```

2) Otherwise, let the XML text *FACETP* be:

```
<xs:pattern value=
  "DATETIME"/>
```

iv) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="TIMESTAMP"
```

- v) It is implementation-defined (IA100) whether the XML text **ANNS** is the zero-length string or:

```
scale="SLIT"
```

- vi) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
      ANNT ANNS/>
  </xs:appinfo>
</xs:annotation>
```

- vii) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:dateTime">
    FACETP
  </xs:restriction>
</xs:simpleType>
```

- k) If *SQLT* is **TIMESTAMP WITH TIME ZONE**, then:

- i) Let *S* be the <time fractional seconds precision> of *SQLT*. Let **SLIT** be the canonical XML schema literal denoting *S* in the lexical representation of XML schema type **xs:integer**.

- ii) Let the XML text **DATETIME** be:

```
\p{Nd}{4}-\p{Nd}{2}-\p{Nd}{2}T\p{Nd}{2}:\p{Nd}{2}:\p{Nd}{2}
```

- iii) Let the XML text **TZ** be:

```
(\+|-)\p{Nd}{2}:\p{Nd}{2}
```

- iv) Case:

- 1) If *S* is greater than 0 (zero), then let the XML text **FACETP** be:

```
<xs:pattern value=
  "DATETIME.\p{Nd}{SLIT}TZ"/>
```

- 2) Otherwise, let the XML text **FACETP** be:

```
<xs:pattern value="DATETIMETZ"/>
```

- v) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

```
name="TIMESTAMP WITH TIME ZONE"
```

- vi) It is implementation-defined (IA100) whether the XML text **ANNS** is the zero-length string or:

```
scale="SLIT"
```

9.5 Mapping SQL data types to XML schema data types

- vii) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                  ANNT ANNS/>
  </xs:appinfo>
</xs:annotation>
```

- viii) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="xs:dateTime">
    FACETP
  </xs:restriction>
</xs:simpleType>
```

- l) If the type designator of *SQLT* is INTERVAL, then:

- i) Let *P* be the <interval leading field precision> of *SQLT*. Let **PLIT** be the canonical XML schema literal for *P* in the XML schema type **xs:integer**. It is implementation-defined (IA100) whether the XML text **ANNP** is the zero-length string or:

```
leadingPrecision="PLIT"
```

- ii) Case:

- 1) If the <end field> or <single datetime field> of *SQLT* specifies SECOND, then let *S* be the <interval fractional seconds precision> of *SQLT*, and let **SLIT** be the canonical XML schema literal for *S* in the XML schema type **xs:integer**. Let the XML text **SECS** be:

```
\p{Nd}{2}.\p{Nd}{SLIT}s
```

It is implementation-defined (IA100) whether the XML text **ANNS** is the zero-length string or:

```
scale="SLIT"
```

- 2) Otherwise, let the XML text **ANNS** be the zero-length string, and let the XML text **SECS** be:

```
\p{Nd}{2}s
```

- iii) Case:

- 1) If *SQLT* is INTERVAL YEAR then:

- A) Let the XML text **FACETP** be:

```
<xs:pattern value="-?P\p{Nd}{PLIT}Y"/>
```

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

```
name="INTERVAL YEAR"
```

- 2) If *SQLT* is INTERVAL YEAR TO MONTH then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="-?P\p{Nd}{PLIT}Y\p{Nd}{2}M"/>
```

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="INTERVAL YEAR TO MONTH"
```

3) If *SQLT* is INTERVAL MONTH then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="-?P\p{Nd}{PLIT}M"/>
```

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="INTERVAL MONTH"
```

4) If *SQLT* is INTERVAL DAY then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="-?P\p{Nd}{PLIT}D"/>
```

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="INTERVAL DAY"
```

5) If *SQLT* is INTERVAL DAY TO HOUR then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="-?P\p{Nd}{PLIT}DT\p{Nd}{2}H"/>
```

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="INTERVAL DAY TO HOUR"
```

6) If *SQLT* is INTERVAL DAY TO MINUTE then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="
  "-?P\p{Nd}{PLIT}DT\p{Nd}{2}H\p{Nd}{2}M"/>
```

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

```
name="INTERVAL DAY TO MINUTE"
```

7) If *SQLT* is INTERVAL DAY TO SECOND then:

A) Let the XML text *FACETP* be:

```
<xs:pattern value="
  "-?P\p{Nd}{PLIT}DT\p{Nd}{2}H\p{Nd}{2}MSECS"/>
```

9.5 Mapping SQL data types to XML schema data types

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL DAY TO SECOND"`

- 8) If *SQLT* is INTERVAL HOUR then:

- A) Let the XML text **FACETP** be:

`<xs:pattern value="-?PT\p{Nd}{PLIT}H"/>`

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL HOUR"`

- 9) If *SQLT* is INTERVAL HOUR TO MINUTE then:

- A) Let the XML text **FACETP** be:

`<xs:pattern value="
 "-?PT\p{Nd}{PLIT}H\p{Nd}{2}M"/>`

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL HOUR TO MINUTE"`

- 10) If *SQLT* is INTERVAL HOUR TO SECOND then:

- A) Let the XML text **FACETP** be:

`<xs:pattern value="
 "-?PT\p{Nd}{PLIT}H\p{Nd}{2}MSECS"/>`

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL HOUR TO SECOND"`

- 11) If *SQLT* is INTERVAL MINUTE then:

- A) Let the XML text **FACETP** be:

`<xs:pattern value="-?PT\p{Nd}{PLIT}M"/>`

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL MINUTE"`

- 12) If *SQLT* is INTERVAL MINUTE TO SECOND then:

- A) Let the XML text **FACETP** be:

`<xs:pattern value="-?PT\p{Nd}{PLIT}MSECS"/>`

- B) It is implementation-defined (IA100) whether the XML text **ANNT** is the zero-length string or:

`name="INTERVAL MINUTE TO SECOND"`

13) If *SQLT* is INTERVAL SECOND then:

A) Let the XML text *FACETP* be:

`<xs:pattern value="-?PTSECS"/>`

B) It is implementation-defined (IA100) whether the XML text *ANNT* is the zero-length string or:

`name="INTERVAL SECOND"`

iv) It is implementation-defined (IA100) whether the XML text *ANN* is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
      ANNT ANNP ANNS/>
  </xs:appinfo>
</xs:annotation>
```

v) Case:

1) If *SQLT* is a year-month interval, then let *DTYPE* be `xs:yearMonthDuration`.

2) If *SQLT* is a day-time interval, then let *DTYPE* be `xs:dayTimeDuration`.

vi) *XMLT* is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="DTYPE">
    FACETP
  </xs:restriction>
</xs:simpleType>
```

m) If *SQLT* is a domain, then:

i) Let *DT* be the data type of *SQLT*.

ii) The General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with *DT* as *DATA TYPE*; let *XMLN* be the *XML NAME* returned from the application of those General Rules.

iii) Let *DC*, *DS*, and *DN* be the domain's catalog name, schema name, and domain name, respectively.

iv) Let *DCLIT*, *DSLIT*, and *DNLIT* be the result of mapping *DC*, *DS*, and *DN* to Unicode using *TM*.

v) It is implementation-defined (IA100) whether the XML text *ANN* is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="DOMAIN"
      catalogName="DCLIT" schemaName="DSLIT"
      typeName="DNLIT" mappedType="XMLN"/>
  </xs:appinfo>
</xs:annotation>
```

9.5 Mapping SQL data types to XML schema data types

```

    </xs:appinfo>
  </xs:annotation>

```

- vi) **XMLT** is the XML schema type defined by:

```

<xs:simpleType>
  ANN
  <xs:restriction base="XMLN"/>
</xs:simpleType>

```

- n) If *SQLT* is a row type, then:

- i) Let N_{sym} be the number of fields of *SQLT*. Let FT_i and FN_i be the declared type and name of the i -th field of *SQLT*, respectively, for i between 1 (one) and N .
- ii) For i between 1 (one) and N , the General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with FT_i as *DATA TYPE*; let XMLMT_i be the *XML NAME* returned from the application of those General Rules.
- iii) For each i between 1 (one) and N , the General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with FN_i as *IDENT* and fully escaped as *ESCAPE VARIANT*; let XMLFN_i be the *XMLNAME* returned from the application of those General Rules.
- iv) Let FNLIT_i be the result of mapping FN_i to Unicode using *TM*, for i between 1 (one) and N .
- v) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or given by:

```

<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="ROW">
      <sqlxml:field name="FNLIT1"
        mappedType="XMLMT1" />
      ...
      <sqlxml:field name="FNLITN"
        mappedType="XMLMTN" />
    </sqlxml:sqltype>
  </xs:appinfo>
</xs:annotation>

```

- vi) **XMLT** is the XML schema type defined by:

```

<xs:complexType>
  ANN
  <xs:sequence>
    <xs:element name="XMLFN1" type="XMLMT1" XMLNULLS />
    ...
    <xs:element name="XMLFNN" type="XMLMTN" XMLNULLS />
  </xs:sequence>
</xs:complexType>

```

- o) If *SQLT* is a distinct type, then:

- i) Let *ST* be the source type of *SQLT*.
- ii) The General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with *ST* as *DATA TYPE*; let **XMLN** be the *XML NAME* returned from the application of those General Rules.

9.5 Mapping SQL data types to XML schema data types

- iii) Let *DTC*, *DTS*, and *DTN* be the catalog name, schema name, and type name, respectively, of *SQLT*.
- iv) Let *DTCLIT*, *DTSLIT*, and *DTNLIT* be the result of mapping *DTC*, *DTS*, and *DTN* to Unicode using *TM*.
- v) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="DISTINCT"
                    catalogName="DTCLIT" schemaName="DTSLIT"
                    typeName="DTNLIT" mappedType="XMLN"
                    final="true" />
  </xs:appinfo>
</xs:annotation>
```

- vi) **XMLT** is the XML schema type defined by:

```
<xs:simpleType>
  ANN
  <xs:restriction base="XMLN" />
</xs:simpleType>
```

- p) If *SQLT* is an array type, then:

- i) Let *ET* be the element type of *SQLT*, and let *M* be the maximum cardinality of *SQLT*.
- ii) The General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with *ET* as *DATA TYPE*; let **XMLN** be the *XML NAME* returned from the application of those General Rules.
- iii) Let **MLIT** be the canonical XML schema literal for *M* in the XML schema type **xs:integer**.
- iv) It is implementation-defined (IA100) whether the XML text **ANN** is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="ARRAY"
                    maxElements="MLIT"
                    mappedElementType="XMLN" />
  </xs:appinfo>
</xs:annotation>
```

- v) **XMLT** is the XML schema type defined by:

```
<xs:complexType>
  ANN
  <xs:sequence>
    <xs:element name="element" minOccurs="0"
                maxOccurs="MLIT" nillable="true"
                type="XMLN" />
  </xs:sequence>
</xs:complexType>
```

- q) If *SQLT* is a multiset type, then:

- i) Let *ET* be the element type of *SQLT*.

9.5 Mapping SQL data types to XML schema data types

- ii) The General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with *ET* as *DATA TYPE*; let *XMLN* be the *XML NAME* returned from the application of those General Rules.
- iii) It is implementation-defined (IA100) whether the XML text *ANN* is the zero-length string or given by:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="MULTISET"
                    mappedElementType="XMLN" />
  </xs:appinfo>
</xs:annotation>
```

- iv) *XMLT* is the XML schema type defined by:

```
<xs:complexType>
  ANN
  <xs:sequence>
    <xs:element name="element" minOccurs="0"
                maxOccurs="unbounded" nillable="true"
                type="XMLN" />
  </xs:sequence>
</xs:complexType>
```

- r) If *SQLT* is an XML type other than XML(SEQUENCE), then:

- i) It is implementation-defined (IA100) whether the XML text *ANN* is the zero-length string or:

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqltype kind="PREDEFINED"
                    name="XML" />
  </xs:appinfo>
</xs:annotation>
```

- ii) *XMLT* is the XML schema type defined by:

```
<xs:complexType mixed="true">
  ANN
  <xs:sequence>
    <xs:any name="element" minOccurs="0" maxOccurs="unbounded"
            processContents="skip" />
  </xs:sequence>
</xs:complexType>
```

- 8) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XMLT* as *SCHEMA TYPE*.

Conformance Rules

None.

9.6 Mapping an SQL data type to a named XML schema data type

Function

Define the mapping of an SQL data type or domain to an XML schema data type.

Subclause Signature

"Mapping an SQL data type to a named XML schema data type" [General Rules] (
 Parameter: "SQLTYPE",
 Parameter: "ENCODING",
 Parameter: "NULLS"
) Returns: "SCHEMA TYPE"

SQLTYPE — an SQL data type or domain.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

SCHEMA TYPE — the XML schema type that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *D* be the *SQLTYPE*, let *ENCODING* be the *ENCODING*, and let *NULLS* be the *NULLS* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMA TYPE*.
- 2) The General Rules of Subclause 9.4, "Mapping an SQL data type to an XML name", are applied with *D* as *DATA TYPE*; let *XMLN* be the *XML NAME* returned from the application of those General Rules.
- 3) If *D* is a character string type, then:
 - a) Let *SQLCS* be the character set of *D*.
 - b) Let *N* be the length or maximum length of *D*.
 - c) Let *CSM* be the implementation-defined (IA091) mapping of strings of *SQLCS* to strings of Unicode. Let *MAXCSL* be the maximum length in characters of *CSM(S)*, for all strings *S* of length *N* characters.
 - d) Let *MLIT* be the canonical XML schema literal of the XML schema type `xs:integer` denoting *MAXCSL*.
 - e) Case:

9.6 Mapping an SQL data type to a named XML schema data type

- i) If *CSM* is homomorphic, *N* equals *MAXCSL*, and the type designator of *D* is CHARACTER, then let *SQLCDT* be the following:

```
<xs:simpleType name="XMLN">
  <xs:restriction base="xs:string">
    <xs:length value="MLIT" />
  </xs:restriction>
</xs:simpleType>
```

- ii) Otherwise, let *SQLCDT* be the following:

```
<xs:simpleType name="XMLN">
  <xs:restriction base="xs:string">
    <xs:maxLength value="MLIT" />
  </xs:restriction>
</xs:simpleType>
```

- 4) If *D* is a domain or a data type that is not a character string type, then:

- a) Let *ENC* be the choice of whether to encode binary strings in base64 or in hex and let *NC* be the choice of whether to map null values to absent elements or elements that are marked with **xsi:nil="true"**.

- b) The General Rules of Subclause 9.5, "Mapping SQL data types to XML schema data types", are applied with *D* as *SQLTYPE*, *ENC* as *ENCODING*, and *NC* as *NULLS*; let *XMLT* be the *SCHEMA TYPE* returned from the application of those General Rules.

- c) Case:

- i) If *D* is an XML type, then *XMLT* is of the form

```
<xs:complexType MIXED>
  XMLTC
</xs:complexType>
```

where *XMLTC* is the string comprising the element content and *MIXED* is the string comprising the attribute of the element. Let *SQLDT* be the following:

```
<xs:complexType name="XMLN" MIXED>
  XMLTC
</xs:complexType>
```

- ii) If *XMLT* is of the form **<xs:complexType>XMLTC</xs:complexType>**, where *XMLTC* is the string comprising the element content, then let *SQLCDT* be the following:

```
<xs:complexType name="XMLN">
  XMLTC
</xs:complexType>
```

- iii) If *XMLT* is of the form **<xs:simpleType>XMLTC</xs:simpleType>**, where *XMLTC* is the string comprising the element content, then let *SQLCDT* be the following:

```
<xs:simpleType name="XMLN">
  XMLTC
</xs:simpleType>
```

- iv) Otherwise, let *SQLCDT* be the following:

```
<xs:simpleType name="XMLN">
  <xs:restriction base="XMLT" />
</xs:simpleType>
```

9.6 Mapping an SQL data type to a named XML schema data type

- 5) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *SQLCDT* as *SCHEMA TYPE*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.7 Mapping a collection of SQL data types to XML schema data types

Function

Define the mapping of a collection of SQL data types and domains to XML schema data types.

Subclause Signature

"Mapping a collection of SQL data types to XML schema data types" [General Rules] (
 Parameter: "SQLTYPES",
 Parameter: "ENCODING",
 Parameter: "NULLS"
) Returns: "SCHEMA TYPE"

SQLTYPES — a collection of SQL data types and domains.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

SCHEMA TYPE — the XML schema type that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *C* be the *SQLTYPES*, let *ENCODING* be the *ENCODING*, and let *NULLS* be the *NULLS* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMA TYPE*.
- 2) *C* is augmented recursively as follows, until no more data types are added to *C*:
 - a) If *DO* is a domain contained in *C* and the data type of *DO* is not contained in *C*, then the data type of *DO* is added to *C*.
 - b) If *RT* is a row type contained in *C* and *F* is a field of *RT* whose declared type is not contained in *C*, then the declared type of *F* is added to *C*.
 - c) If *DT* is a distinct type contained in *C* whose source type is not in *C*, then the source type of *DT* is added to *C*.
 - d) If *CT* is a collection type contained in *C* whose element type is not in *C*, then the element type of *CT* is added to *C*.
- 3) Let *n* be the number of SQL data types and domains in *C*.
- 4) Let *XMLD* be the zero-length string. Let *XMLTL* be an empty list of XML names.

9.7 Mapping a collection of SQL data types to XML schema data types

- 5) For i ranging from 1 (one) to n :
- a) Let D_i be the i -th SQL data type or domain in C .
 - b) The General Rules of Subclause 9.4, “Mapping an SQL data type to an XML name”, are applied with D_i as *DATA TYPE*; let \mathbf{XMLN}_i be the *XML NAME* returned from the application of those General Rules.
 - c) The General Rules of Subclause 9.6, “Mapping an SQL data type to a named XML schema data type”, are applied with D_i as *SQLTYPE*, *ENCODING* as *ENCODING*, and *NULLS* as *NULLS*; let \mathbf{XMLT}_i be the *SCHEMA TYPE* returned from the application of those General Rules.
 - d) Two XML names are considered to be equivalent to each other if they have the same number of characters and the Unicode values of all corresponding characters are equal.
 - e) If \mathbf{XMLN}_i is not equivalent to the value of any XML name in \mathbf{XMLTTL} , then:
 - i) Let \mathbf{XMLD} be:

$$\mathbf{XMLD} \ || \ \mathbf{XMLT}_i$$
 - ii) Append \mathbf{XMLN}_i to \mathbf{XMLTTL} .
- 6) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives \mathbf{XMLD} as *SCHEMA TYPE*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.8 Mapping values of SQL data types to values of XML schema data types

Function

Define the mapping of non-null values of SQL data types to XML.

Subclause Signature

"Mapping values of SQL data types to values of XML schema data types" [General Rules]
(

Parameter: "SQLVALUE",
Parameter: "ENCODING",
Parameter: "NULLS",
Parameter: "CHARMAPPING"

) Returns: "XMLVALUE"

SQLVALUE — a value of an SQL type.

ENCODING — the choice of whether to encode binary strings in base64 or hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

CHARMAPPING — the choice of whether to replace certain characters ("&" (U+0026), "<" (U+003C), ">" (U+003E), and Carriage Return (U+000D)) with their character references (*True*) or not (*False*).

XMLVALUE — the XML value that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *DV* be the *SQLVALUE*, let *ENC* be the *ENCODING*, let *NL* be the *NULLS*, and let *CHARMAPPING* be the *CHARMAPPING* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLVALUE*.
- 2) Case:
 - a) If *DV* is a value of a distinct type, then let *SQLT* be the source type of the distinct type, and let *SQLV* be the result of:


```
CAST (DV AS SQLT)
```
 - b) Otherwise, let *SQLT* be the most specific type of *DV* and let *SQLV* be *DV*.
- 3) The General Rules of Subclause 9.5, "Mapping SQL data types to XML schema data types", are applied with *SQLT* as *SQLTYPE*, *ENC* as *ENCODING*, and *NL* as *NULLS*; let *XMLT* be the *SCHEMA TYPE* returned from the application of those General Rules.

9.8 Mapping values of SQL data types to values of XML schema data types

- 4) Let *M* be the implementation-defined (IL006) maximum length of variable-length character strings.
- 5) If *SQLT* is not a binary string type, a character string type, a row type, a collection type, an interval type, or the XML type, then let *CV* be the result of

```
CAST ( SQLV AS CHARACTER VARYING(M) )
```

- 6) Let *CSM* be the implementation-defined (IA091) mapping of the default character set of CHARACTER VARYING to Unicode.

- 7) Case:

- a) If *SQLT* is a character string type, then:

- i) Let *CS* be the character set of *SQLT*. Let *XMLVRAW* be the XML text that is the result of mapping *SQLV* to Unicode using the implementation-defined (IA091) mapping of character strings of *CS* to Unicode.

- ii) Case:

- 1) If the SQL-implementation supports Feature X211, “XML 1.1 support”, then if any Unicode code point in *XMLVRAW* does not represent a valid XML 1.1 character, then an exception condition is raised: *SQL/XML mapping error — invalid XML character (ON002)*.
- 2) Otherwise, if any Unicode code point in *XMLVRAW* does not represent a valid XML 1.0 character, then an exception condition is raised: *SQL/XML mapping error — invalid XML character (ON002)*.

- iii) Case:

- 1) If *CHARMAPPING* is *True*, then let *XMLV* be *XMLVRAW*, with each instance of “&” (U+0026) replaced by “&”, each instance of “<” (U+003C) replaced by “<”, each instance of “>” (U+003E) replaced by “>”, and each instance of Carriage Return (U+000D) replaced by “”.
- 2) Otherwise, let *XMLV* be *XMLVRAW*.

- b) If *SQLT* is a binary string type, then

Case:

- i) If *ENCODING* indicates that binary strings are to be encoded in hex, then let *XMLV* be the hex encoding as defined by XML Schema Part 2: Datatypes of *SQLV*.

- ii) Otherwise, let *XMLV* be the base64 encoding as defined by XML Schema Part 2: Datatypes of *SQLV*.

- c) If *SQLT* is a numeric type, then let *XMLV* be the result of mapping *CV* to Unicode using *CSM*.

- d) If *SQLT* is a BOOLEAN, then let *TEMP* be the result of:

```
LOWER ( CV )
```

Let *XMLV* be the result of mapping *TEMP* to Unicode using *CSM*.

- e) If *SQLT* is DATE, then let *TEMP* be the result of:

```
SUBSTRING ( CV FROM 6 FOR 10 )
```

Let *XMLV* be the result of mapping *TEMP* to Unicode using *CSM*.

- f) If *SQLT* specifies TIME, then:

9.8 Mapping values of SQL data types to values of XML schema data types

- i) Let P be the <time fractional seconds precision> of $SQLT$.
- ii) If P is 0 (zero), then let Q be 0 (zero); otherwise, let Q be $P + 1$ (one).
- iii) If $SQLT$ specifies WITH TIME ZONE, then let Z be 6; otherwise, let Z be 0 (zero).
- iv) Case:
 - 1) If the SECOND field of CV is greater than or equal to 60, then it is implementation-defined (IA111) whether an implementation-defined (IA112) value is assigned to $TEMP$, or whether to raise an exception condition: *data exception — datetime field overflow (22008)*.
 - 2) Otherwise, let $TEMP$ be the result of:


```
SUBSTRING ( CV FROM 6 FOR 8 + Q + Z )
```
- v) Let $XMLV$ be the result of mapping $TEMP$ to Unicode using CSM .
- g) If $SQLT$ specifies TIMESTAMP, then:
 - i) Let P be the <time fractional seconds precision> of $SQLT$.
 - ii) If P is 0 (zero), then let Q be 0 (zero); otherwise, let Q be $P + 1$ (one).
 - iii) If $SQLT$ specifies WITH TIME ZONE, then let Z be 6; otherwise, let Z be 0 (zero).
 - iv) Case:
 - 1) If the SECOND field of CV is greater than or equal to 60, then it is implementation-defined (IA111) whether an implementation-defined (IA112) value is assigned to $TEMP$, or whether to raise an exception condition: *data exception — datetime field overflow (22008)*.
 - 2) Otherwise, let $TEMP$ be the result of:


```
SUBSTRING ( CV FROM 11 FOR 10 )
              || 'T'
              || SUBSTRING ( CV FROM 22 FOR 8 + Q + Z )
```
 - v) Let $XMLV$ be the result of mapping $TEMP$ to Unicode using CSM .
- h) If $SQLT$ specifies INTERVAL, then:
 - i) If $SQLV$ is negative, then let $SIGN$ be '-' (a character string of length 1 (one) consisting of <minus sign>); otherwise, let $SIGN$ be the zero-length string.
 - ii) Let $SQLVA$ be $ABS(SQLV)$.
 - iii) Let CVA be the result of:


```
CAST ( SQLVA AS CHARACTER VARYING(M) )
```
 - iv) Let L be the <interval leading field precision> of $SQLT$.
 - v) Let P be the <interval fractional seconds precision> of $SQLT$, if any.
 - vi) If P is 0 (zero), then let Q be 0 (zero); otherwise, let Q be $P + 1$ (one).
 - vii) Case:
 - 1) If $SQLT$ is INTERVAL YEAR, then let $TEMP$ be the result of:


```
SIGN || 'P' || SUBSTRING ( CVA FROM 10 FOR L ) || 'Y'
```

9.8 Mapping values of SQL data types to values of XML schema data types

- 2) If *SQLT* is INTERVAL YEAR TO MONTH, then let *TEMP* be the result of

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'Y'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'M'
```

- 3) If *SQLT* is INTERVAL MONTH, then let *TEMP* be the result of:

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'M'
```

- 4) If *SQLT* is INTERVAL DAY, then let *TEMP* be the result of:

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'D'
```

- 5) If *SQLT* is INTERVAL DAY TO HOUR, then let *TEMP* be the result of:

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'DT'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'H'
```

- 6) If *SQLT* is INTERVAL DAY TO MINUTE, then let *TEMP* be the result of:

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'DT'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'H'
|| SUBSTRING (CVA FROM 14 + L FOR 2) || 'M'
```

- 7) If *SQLT* is INTERVAL DAY TO SECOND, then let *TEMP* be the result of:

```
SIGN || 'P'
|| SUBSTRING (CVA FROM 10 FOR L) || 'DT'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'H'
|| SUBSTRING (CVA FROM 14 + L FOR 2) || 'M'
|| SUBSTRING (CVA FROM 17 + L FOR 2 + Q) || 'S'
```

- 8) If *SQLT* is INTERVAL HOUR, then let *TEMP* be the result of:

```
SIGN || 'PT'
|| SUBSTRING (CVA FROM 10 FOR L) || 'H'
```

- 9) If *SQLT* is INTERVAL HOUR TO MINUTE, then let *TEMP* be the result of:

```
SIGN || 'PT'
|| SUBSTRING (CVA FROM 10 FOR L) || 'H'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'M'
```

- 10) If *SQLT* is INTERVAL HOUR TO SECOND, then let *TEMP* be the result of:

```
SIGN || 'PT'
|| SUBSTRING (CVA FROM 10 FOR L) || 'H'
|| SUBSTRING (CVA FROM 11 + L FOR 2) || 'M'
|| SUBSTRING (CVA FROM 14 + L FOR 2 + Q) || 'S'
```

- 11) If *SQLT* is INTERVAL MINUTE, then let *TEMP* be the result of:

```
SIGN || 'PT'
|| SUBSTRING (CVA FROM 10 FOR L) || 'M'
```

- 12) If *SQLT* is INTERVAL MINUTE TO SECOND, then let *TEMP* be the result of:

```
SIGN || 'PT'
```

9.8 Mapping values of SQL data types to values of XML schema data types

```

|| SUBSTRING (CVA FROM 10 FOR L) || 'M'
|| SUBSTRING (CVA FROM 11 + L FOR 2 + Q) || 'S'

```

13) If *SQLT* is INTERVAL SECOND, then let *TEMP* be the result of:

```

SIGN || 'PT'
|| SUBSTRING (CVA FROM 10 FOR L + Q) || 'S'

```

viii) Let *XMLV* be the result of mapping *TEMP* to Unicode using *CSM*.

i) If *SQLT* is a row type, then:

i) Let *N* be the number of fields of *SQLT*. For *i* between 1 (one) and *N*, let *FT_i*, *FN_i*, and *FV_i* be the declared type, name, and value of the *i*-th field, respectively.

ii) For each *i* between 1 (one) and *N*:

1) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *FN_i* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLFN_i* be the *XMLNAME* returned from the application of those General Rules.

2) Case:

A) If *FV_i* is the null value and *NULLS* is “absent”, then let *XMLE_i* be the zero-length string.

B) If *FV_i* is the null value and *NULLS* is “nil”, then let *XMLE_i* be the XML element:

```
<XMLFNi xsi:nil="true"/>
```

C) Otherwise, let the XML text *XMLV_i* be the result of applying the mapping defined in this Subclause to *FV_i*. Let *XMLE_i* be the XML element:

```
<XMLFNi>XMLVi</XMLFNi>
```

iii) Let *XMLV* be:

```
XMLE1 XMLE2 . . . XMLEN
```

j) If *SQLV* is an array value or a multiset value, then:

i) Let *N* be the number of elements in *SQLV*.

ii) Let *ET* be the element type of *SQLV*.

iii) For *i* between 1 (one) and *N*:

1) Let *E_i* be the value of the *i*-th element of *SQLV*. (If *SQLV* is a multiset value, then the ordering of the elements is implementation-dependent (US054).)

2) Case:

A) If *E_i* is the null value, then let the XML text *XMLE_i* be `<element xsi:nil="true"/>`.

B) Otherwise, The General Rules of this Subclause are applied with *E_i* as *SQL-VALUE*, *ENC* as *ENCODING*, *NL* as *NULLS*, and *CHARMAPPING* as *CHARMAP-PING*; let *X_i* be the *XMLVALUE* returned from the application of those General Rules. Let the XML text *XMLE_i* be:

9.8 Mapping values of SQL data types to values of XML schema data types

`<element>Xi</element>`

iv) Let ***XMLV*** be:

XML_{E1} XML_{E2} ... XML_N

k) If *SQLT* is an XML type, then let ***XMLV*** be the serialized value of the XML value in *SQLV*:

`XMLSERIALIZE (CONTENT SQLV AS CLOB)`

8) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives ***XMLV*** as *XMLVALUE*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.9 Mapping an SQL table to XML schema data types

Function

Define the mapping of an SQL table to XML schema data types.

Subclause Signature

"Mapping an SQL table to XML schema data types" [General Rules] (
 Parameter: "TABLE",
 Parameter: "NULLS",
 Parameter: "TABLEFOREST",
 Parameter: "AUTHID"
) Returns: "SCHEMATYPES"

TABLE — an SQL table.

NULLS — the choice of whether to map null values to absent elements ("absent"), or whether to map them to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map the table to a sequence of XML elements (*True*) or to map the table to an XML document with a single root element (*False*).

AUTHID — the authorization identifier that is invoking this mapping.

SCHEMATYPES — a collection of XML schema types that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *T* be the *TABLE*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMATYPES*.
- 2) Let *TC*, *TS*, and *TN* be the <catalog name>, <unqualified schema name>, and <qualified identifier> of the <table name> of *T*, respectively.
- 3) Let *n* be the number of XML visible columns of *T* for *U*.
NOTE 57 — "XML visible column" is defined in Subclause 4.11.9, "Visibility of columns, tables, and schemas in mappings from SQL to XML".
- 4) For *i* ranging from 1 (one) to *n*:
 - a) Let *C_i* be the *i*-th XML visible column of *T* for *U* in order of its ordinal position within *T*.
 - b) Let *CN* be the <column name> of *C_i*. Let *D* be the data type of *C_i*.

9.9 Mapping an SQL table to XML schema data types

- c) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCN* be the *XMLNAME* returned from the application of those General Rules.
- d) The General Rules of Subclause 9.4, “Mapping an SQL data type to an XML name”, are applied with *D* as *DATA TYPE*; let *XMLCTN* be the *XML NAME* returned from the application of those General Rules.
- e) Case:
- i) If C_i is known not nullable, then let *XMLNULLS* be the zero-length string.
 - ii) Otherwise,

Case:

 - 1) If *NULLS* is “absent”, then let *XMLNULLS* be
`minOccurs="0"`
 - 2) If *NULLS* is nil, then let *XMLNULLS* be
`nullable="true"`
- f) Case:
- i) If *D* is a character string type, then:
 - 1) Let *CS* be the character set of *D*.
 - 2) Let *CSC*, *CSS*, and *CSN* be the <catalog name>, <unqualified schema name>, and <SQL language identifier> of the <character set name> of *CS*, respectively.
 - 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CSC* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCSCN* be the *XMLNAME* returned from the application of those General Rules.
 - 4) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CSS* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCSSN* be the *XMLNAME* returned from the application of those General Rules.
 - 5) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CSN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCSN* be the *XMLNAME* returned from the application of those General Rules.
 - 6) Let *CO* be the collation of *D*.
 - 7) Let *COC*, *COS*, and *CON* be the <catalog name>, <unqualified schema name>, and <qualified identifier> of the <collation name> of *CO*, respectively.
 - 8) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *COC* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCOCN* be the *XMLNAME* returned from the application of those General Rules. The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *COS* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCOSN* be the *XMLNAME* returned from the application of those General Rules. The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CON* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCON* be the *XMLNAME* returned from the application of those General Rules.

9.9 Mapping an SQL table to XML schema data types

- 9) It is implementation-defined (IA100) whether **COLANN** is the zero-length string or

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqlname
      type="CHARACTER SET"
      catalogName="XMLCSCN"
      schemaName="XMLCSSN"
      localName="XMLCSN" />
    <sqlxml:sqlname
      type="COLLATION"
      catalogName="XMLCOCN"
      schemaName="XMLCOSN"
      localName="XMLCON" />
  </xs:appinfo>
</xs:annotation>
```

- ii) Otherwise, let **COLANN** be the zero-length string.

- g) Let **XMLCE_i** be

```
<xs:element name="XMLCN" type="XMLCTN" XMLNULLS>
  COLANN
</xs:element>
```

- 5) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "TableType", *TC*, *TS*, and *TN* as *SEQUENCE OF SQL IDENTIFIERS*; let **XMLTYPEN** be the *XMLNAME* returned from the application of those General Rules.
- 6) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "RowType", *TC*, *TS*, and *TN* as *SEQUENCE OF SQL IDENTIFIERS*; let **XMLROWN** be the *XMLNAME* returned from the application of those General Rules.
- 7) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *TC* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let **XMLCAT** be the *XMLNAME* returned from the application of those General Rules. The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *TS* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let **XMLSN** be the *XMLNAME* returned from the application of those General Rules. The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *TN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let **XMLTN** be the *XMLNAME* returned from the application of those General Rules.
- 8) If *T* is a base table, then let **TYPE** be **BASE TABLE**; otherwise, let **TYPE** be **VIEWED TABLE**. It is implementation-defined (IA100) whether **SQLANN** is the zero-length string or

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqlname
      type="TYPE"
      catalogName="XMLCAT"
      schemaName="XMLSN"
      localName="XMLTN" />
  </xs:appinfo>
</xs:annotation>
```

- 9) Case:

- a) If *TABLEFOREST* is *False*, then let **XMLTYPMAP** be:

```
<xs:complexType name="XMLROWN">
```

```
<xs:sequence>
  XMLCE1
  ...
  XMLCEn
</xs:sequence>
</xs:complexType>
<xs:complexType name="XMLTYPEN">
  SQLANN
  <xs:sequence>
    <xs:element name="row"
      type="XMLROWN"
      minOccurs="0"
      maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

- b) If *TABLEFOREST* is *True*, then let *XMLTYPMAP* be:

```
<xs:complexType name="XMLROWN">
  <xs:sequence>
    XMLCE1
    ...
    XMLCEn
  </xs:sequence>
</xs:complexType>
```

- 10) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XMLTYPMAP* as *SCHEMATYPES*.

Conformance Rules

None.

9.10 Mapping an SQL table to an XML element or a sequence of XML elements

Function

Define the mapping of an SQL table to XML.

Subclause Signature

"Mapping an SQL table to an XML element or a sequence of XML elements" [General Rules]
 (
 Parameter: "TABLE" ,
 Parameter: "ENCODING" ,
 Parameter: "NULLS" ,
 Parameter: "TABLEFOREST" ,
 Parameter: "TARGETNS" ,
 Parameter: "SCHEMALOCATION" ,
 Parameter: "AUTHID"
) Returns: "XMLELEMS"

TABLE — an SQL table.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map the table to a sequence of XML elements (*True*) or to an XML document with a single root element (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added.

SCHEMALOCATION — the URI of the XML schema describing the result of the data mapping, if any.

AUTHID — the authorization identifier that is invoking this mapping.

XMLELEMS — the XML elements that are the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *T* be the *TABLE*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let *TARGETNS* be the *TARGETNS*, let *XSL* be the *SCHEMALOCATION*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLELEMS*.
- 2) Let *TN* be the <qualified identifier> of the <table name> of *T*.

9.10 Mapping an SQL table to an XML element or a sequence of XML elements

- 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *TN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLTN* be the *XMLNAME* returned from the application of those General Rules.
- 4) Let *n* be the number of rows of *T* and let *m* be the number of XML visible columns of *T* for *U*.
NOTE 58 — “XML visible column” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.
- 5) Case:
- a) If *XSL* is not the zero-length string, then
Case:
- i) If *TARGETNS* is the zero-length string, then let *XSLA* be:
`xsi:noNamespaceSchemaLocation="XSL"`
- ii) Otherwise, let *XSLA* be:
`xsi:schemaLocation="TARGETNS XSL"`
- b) Otherwise, let *XSLA* be the zero-length string.
- 6) Let *XSINS* be the value of the XML namespace URI provided for the XML namespace prefix *xsi* in Table 2, “XML namespace prefixes and their URIs”.
Case:
- a) If *NULLS* is “absent” and *XSLA* is the zero-length string, then let *XSI* be the zero-length string.
- b) Otherwise, let *XSI* be
`xmlns:xsi="XSINS"`
- 7) For *i* ranging from 1 (one) to *n*:
- a) Let *R_i* be the *i*-th row of *T*, in the implementation-dependent (US057) repeatable ordering of *T*.
- b) For *j* ranging from 1 (one) to *m*:
- i) Let *C_j* be the *j*-th XML visible column of *T* for *U*.
- ii) Let *CN_j* be the <column name> of *C_j*.
- iii) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CN_j* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCN_j* be the *XMLNAME* returned from the application of those General Rules.
- iv) Let *V_j* be the value of *C_j* for *R_i*.
- v) Case:
- 1) If *V_j* is the null value and *NULLS* is “absent”, then *XMLC_j* is the zero-length string.
- 2) If *V_j* is the null value and *NULLS* is “nil”, then *XMLC_j* is
`<XMLCNj xsi:nil="true" />`
- 3) Otherwise:

9.10 Mapping an SQL table to an XML element or a sequence of XML elements

A) The General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with V_j as *SQLVALUE*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, and *True* as *CHARMAPPING*; let $XMLV_j$ be the *XMLVALUE* returned from the application of those General Rules.

B) $XMLC_j$ is

`<XMLCNj>XMLVj</XMLCNj>`

c) Case:

i) If *TABLEFOREST* is *False*, then let $XMLR_i$ be

`<row>
XMLC1
...
XMLCm
</row>`

ii) If *TABLEFOREST* is *True* and *TARGETNS* is the zero-length string, then let $XMLR_i$ be

`<XMLTN XSI XSLA>
XMLC1
...
XMLCm
</XMLTN>`

iii) If *TABLEFOREST* is *True* and *TARGETNS* is not the zero-length string, then let $XMLR_i$ be

`<XMLTN XSI xmlns="TARGETNS" XSLA>
XMLC1
...
XMLCm
</XMLTN>`

8) Case:

a) If *TABLEFOREST* is *False* and *TARGETNS* is the zero-length string, then let $XMLTE$ be:

`<XMLTN XSI XSLA>
XMLR1
...
XMLRn
</XMLTN>`

b) If *TABLEFOREST* is *False* and *TARGETNS* is not the zero-length string, then let $XMLTE$ be:

`<XMLTN XSI xmlns="TARGETNS" XSLA>
XMLR1
...
XMLRn
</XMLTN>`

c) If *TABLEFOREST* is *True*, then let $XMLTE$ be:

`XMLR1`

9.10 Mapping an SQL table to an XML element or a sequence of XML elements

...
XMLR_n

- 9) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XMLTE* as *XMLELEMS*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.11 Mapping an SQL table to XML and an XML schema document

Function

Define the mapping of an SQL table to an XML schema document that describes the structure of the mapped XML, and either an XML document or a sequence of XML elements.

NOTE 59 — This document specifies no syntax for invoking the mapping specified in this Subclause, which is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Subclause Signature

"Mapping an SQL table to XML and an XML schema document" [General Rules] (
 Parameter: "TABLE" ,
 Parameter: "ENCODING" ,
 Parameter: "NULLS" ,
 Parameter: "TABLEFOREST" ,
 Parameter: "TARGETNS" ,
 Parameter: "RETURN" ,
 Parameter: "AUTHID"
) Returns: "RESULT"

TABLE — an SQL table.

ENCODING — the choice of whether binary strings are to be encoded in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map the table to a sequence of XML elements (*True*) or to an XML document with a single XML element (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added.

RETURN — the choice of whether the mapping results in an XML representation of the data of *T*, an XML schema document that describes the XML representation of the data of *T*, or both.

AUTHID — the authorization identifier that is invoking this mapping.

RESULT — the XML schema document that describes the structure of the mapped XML, and either an XML document or a sequence of XML elements that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *T* be the *TABLE*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let *TARGETNS* be the *TARGETNS*, let *RETURN* be the *RETURN*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *RESULT*.
- 2) Let *TC*, *TS*, and *TN* be the <catalog name>, <unqualified schema name>, and <qualified identifier> of the <table name> of *T*, respectively.
- 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *TN* as *IDENT* and fully escaped as *ESCAPE VARIANT*; let *XMLTN* be the *XMLNAME* returned from the application of those General Rules.
- 4) If any of the visible columns of *T* is an XML unmappable column, then a completion condition is raised: *warning — column cannot be mapped to XML (01010)*.
- 5) The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “TableType”, *TC*, *TS*, and *TN* as *SEQUENCE OF SQL IDENTIFIERS*; let *XMLTYPEN* be the *XMLNAME* returned from the application of those General Rules.
- 6) The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “RowType”, *TC*, *TS*, and *TN* as *SEQUENCE OF SQL IDENTIFIERS*; let *XMLROWN* be the *XMLNAME* returned from the application of those General Rules.
- 7) Let *CT* be the XML visible columns of *T* for *U*.
- 8) The General Rules of Subclause 9.7, “Mapping a collection of SQL data types to XML schema data types”, are applied with the data types and domains of the columns of *CT* as *SQLTYPES*, *ENCODING* as *ENCODING*, and *NULLS* as *NULLS*; let *XSCT* be the *SCHEMA TYPE* returned from the application of those General Rules.

NOTE 60 — “XML visible column” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.

- 9) The General Rules of Subclause 9.9, “Mapping an SQL table to XML schema data types”, are applied with *T* as *TABLE*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, and *U* as *AUTHID*; let *XST* be the *SCHEMATYPES* returned from the application of those General Rules.
- 10) Case:
 - a) If either *XSCT* or *XST* contains an XML 1.1 QName that is not an XML 1.0 QName, then let *VER* be 1.1.
 - b) Otherwise, it is implementation-defined (IA113) whether *VER* is 1.1 or 1.0.
- 11) The character encoding to use for the result(s) of this mapping is implementation-defined (IV234). If this encoding is not UTF-8 or UTF-16, then let *CHARENC* be the name of the character encoding, and let *ENC* be

`encoding = 'CHARENC'`

Otherwise, let *ENC* be the zero-length string.

- 12) If *VER* is not 1.0 or *ENC* is not the zero-length string, then let *XMLDECL* be

`<?xml version='VER' ENC ?>`

Otherwise, let *XMLDECL* be the zero-length string.

- 13) If *RETURN* is not “data only”, then:

9.11 Mapping an SQL table to XML and an XML schema document

- a) Let **SQLXMLNS** be the value of the XML namespace URI provided for the XML namespace prefix **sqlxml** in Table 2, "XML namespace prefixes and their URIs".
- b) Let **XSDNS** be the value of the XML namespace URI provided for the XML namespace prefix **xs** in Table 2, "XML namespace prefixes and their URIs".
- c) Let **SLOCVAL** be an implementation-defined (IV111) URI that references the XML schema document describing the XML namespace **SQLXMLNS**. It is implementation-defined (IV111) whether **SLOC** is the zero-length string or

```
schemaLocation="SLOCVAL"
```

Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be

```
<xs:import namespace="SQLXMLNS" SLOC />
```

d) Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be

```
xmlns:sqlxml="SQLXMLNS"
```

e) Case:

- i) If **TABLEFOREST** is *False* and **TARGETNS** is not the zero-length string, then **XS** has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL
  targetNamespace="TARGETNS"
  xmlns="TARGETNS"
  elementFormDefault="qualified">
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLTN" type="XMLTYPEN" />
</xs:schema>
```

- ii) If **TABLEFOREST** is *False* and **TARGETNS** is the zero-length string, then **XS** has the following content:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL>
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLTN" type="XMLTYPEN" />
</xs:schema>
```

9.11 Mapping an SQL table to XML and an XML schema document

- iii) If *TABLEFOREST* is *True* and *TARGETNS* is not the zero-length string, then *XS* has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL
  targetNamespace="TARGETNS"
  xmlns="TARGETNS"
  elementFormDefault="qualified">
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLTN" type="XMLROWN"/>
</xs:schema>
```

- iv) If *TABLEFOREST* is *True* and *TARGETNS* is the zero-length string, then *XS* has the following content:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL>
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLTN" type="XMLROWN"/>
</xs:schema>
```

- f) Let *XSR* be:

```
XMLSERIALIZE ( DOCUMENT
  XMLPARSE ( DOCUMENT 'XS' PRESERVE WHITESPACE )
  AS CLOB )
```

- 14) Case:

- a) If *RETURN* is not “data only”, then let *XSL* be the URI that identifies *XSR*.
 b) Otherwise, let *XSL* be the zero-length string.

- 15) If *RETURN* is not “metadata only”, then:

- a) The General Rules of Subclause 9.10, “Mapping an SQL table to an XML element or a sequence of XML elements”, are applied with *T* as *TABLE*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, *TARGETNS* as *TARGETNS*, *XSL* as *SCHEMALOCATION*, and *U* as *AUTHID*; let *XDROWS* be the *XMLELEMS* returned from the application of those General Rules.

- b) Case:

- i) If *TABLEFOREST* is *False*, then *XD* has the following contents:

```
XMLDECL
  XDROWS
```

- ii) If *TABLEFOREST* is *True*, then *XD* is *XDROWS*.

- c) Case:

- i) If *TABLEFOREST* is *True*, then let *XDR* be:

```
XMLSERIALIZE ( CONTENT
```

9.11 Mapping an SQL table to XML and an XML schema document

```
XMLPARSE ( CONTENT 'XD' PRESERVE WHITESPACE )
AS CLOB )
```

ii) If *TABLEFOREST* is *False*, then let *XDR* be:

```
XMLSERIALIZE ( DOCUMENT
XMLPARSE ( DOCUMENT 'XD' PRESERVE WHITESPACE )
AS CLOB )
```

16) Case:

- a) If *RETURN* is “metadata only”, then let *XRET* be *XSR* (the character large object value containing the XML schema document that describes the XML representation of the data of T).
- b) If *RETURN* is “data only”, then let *XRET* be *XDR* (the character large object value containing the XML document or forest of XML elements that is the XML representation of the data of T).
- c) Otherwise, let *XRET* be:

```
XSR || '&&' || XDR
```

17) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XRET* as *RESULT*.

Conformance Rules

- 1) Without Feature X040, “Basic table mapping”, a conforming application shall not invoke this Subclause of this document.
- 2) Without Feature X041, “Basic table mapping: null absent”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked to absent elements.
- 3) Without Feature X042, “Basic table mapping: null as nil”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked with *xsi:nil="true"*.
- 4) Without Feature X043, “Basic table mapping: table as forest”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *True*.
- 5) Without Feature X044, “Basic table mapping: table as element”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *False*.
- 6) Without Feature X045, “Basic table mapping: with target namespace”, a conforming application shall not invoke this Subclause of this document with *TARGETNS* that is not a zero-length string.
- 7) Without Feature X046, “Basic table mapping: data mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “metadata only”.
- 8) Without Feature X047, “Basic table mapping: metadata mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “data only”.
- 9) Without Feature X048, “Basic table mapping: base64 encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using base64.
- 10) Without Feature X049, “Basic table mapping: hex encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using hex.

9.12 Mapping an SQL schema to XML schema data types

Function

Define the mapping of an SQL-schema to XML schema data types.

Subclause Signature

"Mapping an SQL schema to XML schema data types" [General Rules] (
Parameter: "SCHEMA",
Parameter: "NULLS",
Parameter: "TABLEFOREST",
Parameter: "AUTHID"
) Returns: "SCHEMATYPES"

SCHEMA — an SQL schema.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of the schema to a sequence of XML elements, one for each row of the table (*True*) or to map the table to a single XML element that contains an element for each row of the table (*False*).

AUTHID — the authorization identifier that is invoking this mapping.

SCHEMATYPES — the collection of XML schema types that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *S* be the *SCHEMA*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMATYPES*.
- 2) Let *SC*, and *SN* be the <catalog name> and <unqualified schema name> of the <schema name> of *S*, respectively.
- 3) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *SN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLS_N* be the *XMLNAME* returned from the application of those General Rules.
- 4) Let *n* be the number of XML visible tables of *S* for *U*.
NOTE 61 — "XML visible table" is defined in Subclause 4.11.9, "Visibility of columns, tables, and schemas in mappings from SQL to XML".
- 5) For *i* ranging from 1 (one) to *n*:

9.12 Mapping an SQL schema to XML schema data types

- a) Let T_i be the i -th XML visible table of S for U in the implementation-dependent (US055) repeatable ordering of S .
- b) Let TN be the <qualified identifier> of the <table name> of T_i .
- c) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with TN as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let $XMLTN$ be the *XMLNAME* returned from the application of those General Rules.
- d) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "TableType", SC , SN , and TN as *SEQUENCE OF SQL IDENTIFIERS*; let $XMLTTN$ be the *XMLNAME* returned from the application of those General Rules.
- e) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "RowType", SC , SN , and TN as *SEQUENCE OF SQL IDENTIFIERS*; let $XMLROWN$ be the *XMLNAME* returned from the application of those General Rules.
- f) The General Rules of Subclause 9.9, "Mapping an SQL table to XML schema data types", are applied with T_i as *TABLE*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, and U as *AUTHID*; let $XMLTTYE_i$ be the *SCHEMATYPES* returned from the application of those General Rules

g) Case:

- i) If *TABLEFOREST* is *False*, then let $XMLTE_i$ be

```
<xs:element name="XMLTN" type="XMLTN" />
```

- ii) If *TABLEFOREST* is *True*, then let $XMLTE_i$ be

```
<xs:element name="XMLTN" type="XMLROWN"
  minOccurs="0" maxOccurs="unbounded" />
```

- 6) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "SchemaType", SC , and SN as *SEQUENCE OF SQL IDENTIFIERS*; let $XMLTYPEN$ be the *XMLNAME* returned from the application of those General Rules.
- 7) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with SC as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let $XMLSC$ be the *XMLNAME* returned from the application of those General Rules.
- 8) It is implementation-defined (IA100) whether *SQLANN* is the zero-length string or

```
<xs:annotation>
  <xs:appinfo>
    <sql.xml:sqlname
      type="SCHEMA"
      catalogName="XMLSC"
      schemaName="XMLSN" />
  </xs:appinfo>
</xs:annotation>
```

9) Case:

- a) If *TABLEFOREST* is *False*, then let $XMLSCHEMAT$ be:

```
XMLTTYE1
...
XMLTTYEn
<xs:complexType name="XMLTYPEN">
  SQLANN
```

```
<xs:all>  
  XMLTE1  
  ...  
  XMLTEn  
</xs:all>  
</xs:complexType>
```

- b) If *TABLEFOREST* is *True*, then let *XMLSCHEMAT* be:

```
XMLTTYPE1  
...  
XMLTTYPEn  
<xs:complexType name="XMLTYPEN">  
  SQLANN  
  <xs:sequence>  
    XMLTE1  
    ...  
    XMLTEn  
  </xs:sequence>  
</xs:complexType>
```

- 10) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XMLSCHEMAT* as *SCHEMATYPES*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.13 Mapping an SQL schema to an XML element

Function

Define the mapping of an SQL-schema to an XML element.

Subclause Signature

"Mapping an SQL schema to an XML element" [General Rules] (
 Parameter: "SCHEMA",
 Parameter: "ENCODING",
 Parameter: "NULLS",
 Parameter: "TABLEFOREST",
 Parameter: "TARGETNS",
 Parameter: "SCHEMALOCATION",
 Parameter: "AUTHID"
) Returns: "XMLELEMENT"

SCHEMA — an SQL schema.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of the schema to a sequence of XML elements, one for each row of the table (*True*), or to a single XML element that contains an element for each row of the table (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added. *U* is the authorization identifier that is invoking this mapping, if any.

SCHEMALOCATION — the URI of the XML schema describing the result of the data mapping, if any.

AUTHID — the authorization identifier that is invoking this mapping.

XMLELEMENT — the XML element that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *S* be the *SCHEMA*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let **TARGETNS** be the *TARGETNS*, let *XSL* be the *SCHEMALOCATION*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLELEMENT*.

- 2) Let *SN* be the <unqualified schema name> of *S*.
- 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *SN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLSN* be the *XMLNAME* returned from the application of those General Rules.
- 4) Let *n* be the number of XML visible tables of *S* for *U*.
NOTE 62 — “XML visible table” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.
- 5) For *i* ranging from 1 (one) to *n*:
 - a) Let *T_i* be the *i*-th XML visible table of *S* for *U* in the implementation-dependent (ISO57) repeatable ordering of *S*.
 - b) The General Rules of Subclause 9.10, “Mapping an SQL table to an XML element or a sequence of XML elements”, are applied with *T_i* as *TABLE*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, *TARGETNS* as *TARGETNS*, *XSL* as *SCHEMALOCATION*, and *U* as *AUTHID*; let *XMLT_i* be the *XMLELEMS* returned from the application of those General Rules.
- 6) Case:
 - a) If *XSL* is not the zero-length string, then
Case:
 - i) If *TARGETNS* is the zero-length string, then let *XSLA* be:
`xsi:noNamespaceSchemaLocation="XSL"`
 - ii) Otherwise, let *XSLA* be:
`xsi:schemaLocation="TARGETNS XSI"`
 - b) Otherwise, let *XSLA* be the zero-length string.
- 7) Let *XSINS* be the value of the XML namespace URI provided for the XML namespace prefix *xsi* in Table 2, “XML namespace prefixes and their URIs”.
Case:
 - a) If *NULLS* is “absent” and *XSLA* is the zero-length string, then let *XSI* be the zero-length string.
 - b) Otherwise, let *XSI* be:
`xmlns:xsi="XSINS"`
- 8) Case:
 - a) If *TARGETNS* is the zero-length string, then let *XMLSE* be:
`<XMLSN XSI XSLA>`
`XMLT1`
`...`
`XMLTn`
`</XMLSN>`
 - b) If *TARGETNS* is not the zero-length string, then let *XMLSE* be:
`<XMLSN XSI xmlns="TARGETNS" XSLA>`
`XMLT1`

9.13 Mapping an SQL schema to an XML element

```
...  
XMLTn  
</XMLSN>
```

- 9) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives **XMLSE** as **XMLELEMENT**.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.14 Mapping an SQL schema to an XML document and an XML schema document

Function

Define the mapping of an SQL-schema to an XML document and an XML schema document that describes this XML document.

NOTE 63 — This document specifies no syntax for invoking the mapping specified in this Subclause, which is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Subclause Signature

"Mapping an SQL schema to an XML document and an XML schema document" [General Rules]

```
(
  Parameter: "SCHEMA" ,
  Parameter: "ENCODING" ,
  Parameter: "NULLS" ,
  Parameter: "TABLEFOREST" ,
  Parameter: "TARGETNS" ,
  Parameter: "RETURN" ,
  Parameter: "AUTHID"
) Returns: "RESULT"
```

SCHEMA — an SQL schema.

ENCODING — the choice of whether binary strings are to be encoded in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of the schema to a sequence of XML elements, one for each row of the table (*True*), or to a single XML element that contains an element for each row of the table (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added.

RETURN — the choice of whether the mapping results in an XML representation of the data of *T*, an XML schema document that describes the XML representation of the data of *T*, or both.

AUTHID — the authorization identifier that is invoking this mapping.

RESULT — the XML schema document that describes the structure of the mapped XML, and either an XML document or a sequence of XML elements that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *S* be the *SCHEMA*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let *TARGETNS* be the *TARGETNS*, let *RETURN* be the *RETURN*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *RESULT*.
- 2) Let *SC* and *SN* be the <catalog name> and <unqualified schema name> of *S*, respectively.
- 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *SN* as *IDENT* and fully escaped as *ESCAPE VARIANT*; let *XMLSNS* be the *XMLNAME* returned from the application of those General Rules.
- 4) If any of the visible columns of the viewed and base tables contained in *S* for *U* is an XML unmappable column, then a completion condition is raised: *warning — column cannot be mapped to XML (01010)*.
NOTE 64 — “visible column” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.
- 5) Let *CT* be the XML visible columns of the viewed and base tables contained in *S* for *U*.
- 6) The General Rules of Subclause 9.7, “Mapping a collection of SQL data types to XML schema data types”, are applied with the data types and domains of the columns of *CT* as *SQLTYPES*, *ENCODING* as *ENCODING*, and *NULLS* as *NULLS*; let *XSCT* be the *SCHEMA TYPE* returned from the application of those General Rules.
- 7) The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “SchemaType”, *SC* and *SN* as *SEQUENCE OF SQL IDENTIFIERS*; let *XMLTYPEN* be the *XMLNAME* returned from the application of those General Rules.
- 8) The General Rules of Subclause 9.12, “Mapping an SQL schema to XML schema data types”, are applied with *S* as *SCHEMA*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, and *U* as *AUTHID*; let *XST* be the *SCHEMATYPES* returned from the application of those General Rules.
- 9) Case:
 - a) If either *XSCT* or *XST* contains an XML 1.1 QName that is not an XML 1.0 QName, then let *VER* be 1.1.
 - b) Otherwise, it is implementation-defined (IA113) whether *VER* is 1.1 or 1.0.
- 10) The character encoding to use for the result(s) of this mapping is implementation-defined (IV234). If this character encoding is not UTF-8 or UTF-16, then let *CHARENC* be the name of the character encoding, and let *ENC* be

```
encoding = 'CHARENC'
```

 Otherwise, let *ENC* be the zero-length string.
- 11) If *VER* is not 1.0 or *ENC* is not the zero-length string, then let *XMLDECL* be

```
<?xml version='VER' ENC ?>
```

 Otherwise, let *XMLDECL* be the zero-length string.
- 12) If *RETURN* is not “data only”, then:
 - a) Let *SQLXMLNS* be the value of the XML namespace URI provided for the XML namespace prefix *sqlxml* in Table 2, “XML namespace prefixes and their URIs”.
 - b) Let *XSDNS* be the value of the XML namespace URI provided for the XML namespace prefix *xs* in Table 2, “XML namespace prefixes and their URIs”.

9.14 Mapping an SQL schema to an XML document and an XML schema document

- c) Let **SLOCVAL** be an implementation-defined (IA100) URI that references the XML schema document describing the XML namespace **SQLXMLNS**. It is implementation-defined (IA100) whether **SLOC** is the zero-length string or

```
schemaLocation="SLOCVAL"
```

Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be

```
<xs:import
  namespace="SQLXMLNS" SLOC />
```

d) Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be

```
xmlns:sqlxml="SQLXMLNS"
```

e) Case:

- i) If **TARGETNS** is the zero-length string, then **XS** has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL>
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLSN" type="XMLTYPEN" />
</xs:schema>
```

- ii) If **TARGETNS** is not the zero-length string, then **XS** has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL
  targetNamespace="TARGETNS"
  xmlns="TARGETNS"
  elementFormDefault="qualified">
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLSN" type="XMLTYPEN" />
</xs:schema>
```

f) Let **XSR** be:

```
XMLSERIALIZE ( DOCUMENT
  XMLPARSE ( DOCUMENT 'XS' PRESERVE WHITESPACE )
  AS CLOB )
```

9.14 Mapping an SQL schema to an XML document and an XML schema document

13) Case:

- a) If *RETURN* is not “data only”, then let *XSL* be the URI that identifies *XSR*.
- b) Otherwise, let *XSL* be the zero-length string.

14) If *RETURN* is not “metadata only”, then:

- a) The General Rules of Subclause 9.13, “Mapping an SQL schema to an XML element”, are applied with *S* as *SCHEMA*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, *TARGETNS* as *TARGETNS*, *XSL* as *SCHEMALOCATION*, and *U* as *AUTHID*; let *XDSHEMA* be the *XMLLEMENT* returned from the application of those General Rules.
- b) *XD* has the following contents:

```
XMLDECL
  XDSHEMA
```

- c) Let *XDR* be:

```
XMLSERIALIZE ( DOCUMENT
                XMLPARSE ( DOCUMENT 'XD' PRESERVE WHITESPACE )
                AS CLOB )
```

15) Case:

- a) If *RETURN* is “metadata only”, then let *XRET* be *XSR* (the character large object value containing the XML schema document that describes the XML representation of the data of *S*).
- b) If *RETURN* is “data only”, then let *XRET* be *XDR* (the character large object value containing the XML document or forest of XML elements that is the XML representation of the data of *S*).
- c) Otherwise, let *XRET* be:

```
XSR || '&&' || XDR
```

16) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XRET* as *RESULT*.

Conformance Rules

- 1) Without Feature X050, “Advanced table mapping”, a conforming application shall not invoke this Subclause of this document.
- 2) Without Feature X051, “Advanced table mapping: null absent”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked to absent elements.
- 3) Without Feature X052, “Advanced table mapping: null as nil”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked with *xsi:nil="true"*.
- 4) Without Feature X053, “Advanced table mapping: table as forest”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *True*.
- 5) Without Feature X054, “Advanced table mapping: table as element”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *False*.
- 6) Without Feature X055, “Advanced table mapping: with target namespace”, a conforming application shall not invoke this Subclause of this document with *TARGETNS* that is not a zero-length string.

9.14 Mapping an SQL schema to an XML document and an XML schema document

- 7) Without Feature X056, “Advanced table mapping: data mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “metadata only”.
- 8) Without Feature X057, “Advanced table mapping: metadata mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “data only”.
- 9) Without Feature X058, “Advanced table mapping: base64 encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using base64.
- 10) Without Feature X059, “Advanced table mapping: hex encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using hex.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.15 Mapping an SQL catalog to XML schema data types

Function

Define the mapping of an SQL catalog to XML schema data types.

Subclause Signature

"Mapping an SQL catalog to XML schema data types" [General Rules] (
 Parameter: "CATALOG",
 Parameter: "NULLS",
 Parameter: "TABLEFOREST",
 Parameter: "AUTHID"
) Returns: "SCHEMATYPES"

CATALOG — an SQL catalog.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of the schema to a sequence of XML elements, one for each row of the table (*True*) or to map the table to a single XML element that contains an element for each row of the table (*False*).

AUTHID — the authorization identifier that is invoking this mapping.

SCHEMATYPES — the collection of XML schema types that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *C* be the *CATALOG*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SCHEMATYPES*.
- 2) Let *CN* be the <catalog name> of *C*.
- 3) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with *CN* as *IDENT* and fully escaped as *ESCAPE VARIANT*; let *XMLCN* be the *XMLNAME* returned from the application of those General Rules.
- 4) Let *n* be the number of XML visible schemas of *C* for *U*.
NOTE 65 — "XML visible schema" is defined in Subclause 4.11.9, "Visibility of columns, tables, and schemas in mappings from SQL to XML".
- 5) For *i* ranging from 1 (one) to *n*:

9.15 Mapping an SQL catalog to XML schema data types

- a) Let S_i be the i -th XML visible schema of C .
- b) Let SN be the <unqualified schema name> of the <schema name> of S_i .
- c) The General Rules of Subclause 9.1, "Mapping SQL <identifier>s to XML names", are applied with SN as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let $XMLSN$ be the *XMLNAME* returned from the application of those General Rules.
- d) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "SchemaType", CN and SN as *SEQUENCE OF SQL IDENTIFIERS*; let $XMLSTN$ be the *XMLNAME* returned from the application of those General Rules.
- e) The General Rules of Subclause 9.12, "Mapping an SQL schema to XML schema data types", are applied with S_i as *SCHEMA*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, and U as *AUTHID*; let $XMLSTYPE_i$ be the *SCHEMATYPES* returned from the application of those General Rules
- f) Let $XMLSE_i$ be

```
<xs:element name="XMLSN" type="XMLSTN" />
```

- 6) The General Rules of Subclause 9.2, "Mapping a multi-part SQL name to an XML name", are applied with "CatalogType" and CN as *SEQUENCE OF SQL IDENTIFIERS*; let $XMLTYPEN$ be the *XMLNAME* returned from the application of those General Rules.
- 7) It is implementation-defined (IA100) whether $SQLANN$ is the zero-length string or

```
<xs:annotation>
  <xs:appinfo>
    <sqlxml:sqlname
      type="CATALOG"
      catalogName="XMLCN" />
    </xs:appinfo>
  </xs:annotation>
```

- 8) Let $XMLCATT$ be:

```
XMLSTYPE1
...
XMLSTYPEn
<xs:complexType name="XMLTYPEN">
  SQLANN
  <xs:all>
    XMLSE1
    ...
    XMLSEn
  </xs:all>
</xs:complexType>
```

- 9) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives $XMLCATT$ as *SCHEMATYPES*.

Conformance Rules

None.

9.16 Mapping an SQL catalog to an XML element

Function

Define the mapping of an SQL catalog to an XML element.

Subclause Signature

"Mapping an SQL catalog to an XML element" [General Rules] (
 Parameter: "CATALOG" ,
 Parameter: "ENCODING" ,
 Parameter: "NULLS" ,
 Parameter: "TABLEFOREST" ,
 Parameter: "TARGETNS" ,
 Parameter: "SCHEMALOCATION" ,
 Parameter: "AUTHID"
) Returns: "XMLELEMENT"

CATALOG — an SQL catalog.

ENCODING — the choice of whether to encode binary strings in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of each schema in the catalog to a sequence of XML elements, one for each row of the table (*True*), or to a single XML element that contains an element for each row of the table (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added.

SCHEMALOCATION — the URI of the XML schema describing the result of the data mapping, if any.

AUTHID — the authorization identifier that is invoking this mapping.

XMLELEMENT — the XML element that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *C* be the *CATALOG*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let **TARGETNS** be the *TARGETNS*, let *XSL* be the *SCHEMALOCATION*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLELEMENT*.
- 2) Let *CN* be the <catalog name> of *C*.

3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CN* as *IDENT* and *fully escaped* as *ESCAPE VARIANT*; let *XMLCN* be the *XMLNAME* returned from the application of those General Rules.

4) Let *n* be the number of XML visible schemas of *C* for *U*.

NOTE 66 — “XML visible schema” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.

5) For *i* ranging from 1 (one) to *n*:

a) Let *S_i* be the *i*-th XML visible schema of *C* for *U* in the implementation-dependent (US055) repeatable ordering of *C*.

b) The General Rules of Subclause 9.13, “Mapping an SQL schema to an XML element”, are applied with *S_i* as *SCHEMA*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, *TARGETNS* as *TARGETNS*, *XSL* as *SCHEMALOCATION*, and *U* as *AUTHID*; let *XMLS_i* be the *XMLELEMENT* returned from the application of those General Rules.

6) Case:

a) If *XSL* is not the zero-length string, then

Case:

i) If *TARGETNS* is the zero-length string, then let *XSLA* be:

`xsi:noNamespaceSchemaLocation="XSL"`

ii) Otherwise, let *XSLA* be:

`xsi:schemaLocation="TARGETNS XSL"`

b) Otherwise, let *XSLA* be the zero-length string.

7) Let *XSINS* be the value of the XML namespace URI provided for the XML namespace prefix *xsi* in Table 2, “XML namespace prefixes and their URIs”.

Case:

a) If *NULLS* is “absent” and *XSLA* is the zero-length string, then let *XSI* be the zero-length string.

b) Otherwise, let *XSI* be:

`xmlns:xsi="XSINS"`

8) Case:

a) If *TARGETNS* is the zero-length string, then let *XMLCE* be:

```
<XMLCN XSI XSLA>
  XMLS1
  ...
  XMLSn
</XMLCN>
```

b) If *TARGETNS* is not the zero-length string, then let *XMLCE* be:

```
<XMLCN XSI xmlns="TARGETNS" XSLA>
  XMLS1
  ...
```

9.16 Mapping an SQL catalog to an XML element

XMLS_n
</XMLCN>

- 9) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XMLCE* as *XMLEMENT*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

9.17 Mapping an SQL catalog to an XML document and an XML schema document

Function

Define the mapping of an SQL catalog to an XML document and an XML schema document that describes this XML document.

NOTE 67 — This document specifies no syntax for invoking the mapping specified in this Subclause, which is intended to be used by applications and referenced by other standards. It is the responsibility of any such application or other standard to ensure that the correct number of arguments as well as a valid value for each argument are supplied for this mapping.

Subclause Signature

```
"Mapping an SQL catalog to an XML document and an XML schema document" [General Rules]
(
  Parameter: "CATALOG" ,
  Parameter: "ENCODING" ,
  Parameter: "NULLS" ,
  Parameter: "TABLEFOREST" ,
  Parameter: "TARGETNS" ,
  Parameter: "RETURN" ,
  Parameter: "AUTHID"
) Returns: "RESULT"
```

CATALOG — an SQL catalog.

ENCODING — the choice of whether binary strings are to be encoded in base64 or in hex.

NULLS — the choice of whether to map null values to absent elements ("absent") or to elements that are marked with `xsi:nil="true"` ("nil").

TABLEFOREST — the choice of whether to map each table of each schema in the catalog to a sequence of XML elements, one for each row of the table (*True*), or to a single XML element that contains an element for each row of the table (*False*).

TARGETNS — the XML target namespace URI of the XML schema and data to be mapped. If TARGETNS is the zero-length string, then no XML namespace is added.

RETURN — the choice of whether the mapping results in an XML representation of the data of *T*, an XML schema document that describes the XML representation of the data of *T*, or both.

AUTHID — the authorization identifier that is invoking this mapping.

RESULT — the XML schema document that describes the structure of the mapped XML, and either an XML document or a sequence of XML elements that is the result of the mapping.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *C* be the *CATALOG*, let *ENCODING* be the *ENCODING*, let *NULLS* be the *NULLS*, let *TABLEFOREST* be the *TABLEFOREST*, let *TARGETNS* be the *TARGETNS*, let *RETURN* be the *RETURN*, and let *U* be the *AUTHID* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *RESULT*.
- 2) Let *CN* be the <catalog name> of *C*.
- 3) The General Rules of Subclause 9.1, “Mapping SQL <identifier>s to XML names”, are applied with *CN* as *IDENT* and fully escaped as *ESCAPE VARIANT*; let *XMLCN* be the *XMLNAME* returned from the application of those General Rules.
- 4) If any of the visible columns of the viewed and base tables contained in *C* for *U* is an XML unmappable column, then a completion condition is raised: *warning — column cannot be mapped to XML (01010)*.
NOTE 68 — “visible column” is defined in Subclause 4.11.9, “Visibility of columns, tables, and schemas in mappings from SQL to XML”.
- 5) Let *CT* be the XML visible columns of the viewed and base tables contained in *C* for *U*.
- 6) The General Rules of Subclause 9.7, “Mapping a collection of SQL data types to XML schema data types”, are applied with the data types and domains of the columns of *CT* as *SQLTYPES*, *ENCODING* as *ENCODING*, and *NULLS* as *NULLS*; let *XSCT* be the *SCHEMA TYPE* returned from the application of those General Rules.
- 7) The General Rules of Subclause 9.2, “Mapping a multi-part SQL name to an XML name”, are applied with “CatalogType” and *CN* as *SEQUENCE OF SQL IDENTIFIERS*; let *XMLTYPEN* be the *XMLNAME* returned from the application of those General Rules.
- 8) The General Rules of Subclause 9.15, “Mapping an SQL catalog to XML schema data types”, are applied with *C* as *CATALOG*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, and *U* as *AUTHID*; let *XST* be the *SCHEMATYPES* returned from the application of those General Rules.
- 9) Case:
 - a) If either *XSCT* or *XST* contains an XML 1.1 QName that is not an XML 1.0 QName, then let *VER* be 1.1.
 - b) Otherwise, it is implementation-defined (IA113) whether *VER* is 1.1 or 1.0.
- 10) The character encoding to use for the result(s) of this mapping is implementation-defined (IV234). If this character encoding is not UTF-8 or UTF-16, then let *CHARENC* be the name of the character encoding, and let *ENC* be

```
encoding = 'CHARENC'
```

 Otherwise, let *ENC* be the zero-length string.
- 11) If *VER* is not 1.0 or *ENC* is not the zero-length string, then let *XMLDECL* be

```
<?xml version='VER' ENC ?>
```

 Otherwise, let *XMLDECL* be the zero-length string.
- 12) If *RETURN* is not “data only”, then:
 - a) Let *SQLXMLNS* be the value of the XML namespace URI provided for the XML namespace prefix *sqlxml* in Table 2, “XML namespace prefixes and their URIs”.
 - b) Let *XSDNS* be the value of the XML namespace URI provided for the XML namespace prefix *xs* in Table 2, “XML namespace prefixes and their URIs”.

9.17 Mapping an SQL catalog to an XML document and an XML schema document

- c) Let **SLOCVAL** be an implementation-defined (IA100) URI that references the XML schema document describing the XML namespace **SQLXMLNS**. It is implementation-defined (IA100) whether **SLOC** is the zero-length string or

```
schemaLocation="SLOCVAL"
```

Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDIMP** be

```
<xs:import
  namespace="SQLXMLNS" SLOC />
```

d) Case:

- i) If neither **XSCT** nor **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be the zero-length string.
- ii) If at least one of **XSCT** and **XST** uses the XML namespace that corresponds to the **sqlxml** XML namespace prefix, then let **XSDECL** be

```
xmlns:sqlxml="SQLXMLNS"
```

e) Case:

- i) If **TARGETNS** is the zero-length string, then **XS** has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL>
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLCN" type="XMLTYPEN" />
</xs:schema>
```

- ii) If **TARGETNS** is not the zero-length string, then **XS** has the following contents:

```
XMLDECL
<xs:schema
  xmlns:xs="XSDNS"
  XSDECL
  targetNamespace="TARGETNS"
  xmlns="TARGETNS"
  elementFormDefault="qualified">
  XSDIMP
  XSCT
  XST
  <xs:element name="XMLCN" type="XMLTYPEN" />
</xs:schema>
```

f) Let **XSR** be:

```
XMLSERIALIZE ( DOCUMENT
  XMLPARSE ( DOCUMENT 'XS' PRESERVE WHITESPACE )
  AS CLOB )
```

9.17 Mapping an SQL catalog to an XML document and an XML schema document

13) Case:

- a) If *RETURN* is not “data only”, then let *XSL* be the URI that identifies *XSR*.
- b) Otherwise, let *XSL* be the zero-length string.

14) If *RETURN* is not “metadata only”, then:

- a) The General Rules of Subclause 9.16, “Mapping an SQL catalog to an XML element”, are applied with *C* as *CATALOG*, *ENCODING* as *ENCODING*, *NULLS* as *NULLS*, *TABLEFOREST* as *TABLEFOREST*, *TARGETNS* as *TARGETNS*, *XSL* as *SCHEMALOCATION*, and *U* as *AUTHID*; let *XDCATALOG* be the *XMLELEMENT* returned from the application of those General Rules.
- b) *XD* has the following contents:

```
XMLDECL
  XDCATALOG
```

- c) Let *XDR* be:

```
XMLSERIALIZE ( DOCUMENT
               XMLPARSE ( DOCUMENT 'XD' PRESERVE WHITESPACE )
               AS CLOB )
```

15) Case:

- a) If *RETURN* is “metadata only”, then let *XRET* be *XSR* (the character large object value containing the XML schema document that describes the XML representation of the data of *C*).
- b) If *RETURN* is “data only”, then let *XRET* be *XDR* (the character large object value containing the XML document or forest of XML elements that is the XML representation of the data of *C*).
- c) Otherwise, let *XRET* be:

```
XSR || '&&' || XDR
```

16) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XRET* as *RESULT*.

Conformance Rules

- 1) Without Feature X050, “Advanced table mapping”, a conforming application shall not invoke this Subclause of this document.
- 2) Without Feature X051, “Advanced table mapping: null absent”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked to absent elements.
- 3) Without Feature X052, “Advanced table mapping: null as nil”, a conforming application shall not invoke this Subclause of this document with *NULLS* set to indicate that nulls are mapped to elements that are marked with *xsi:nil="true"*.
- 4) Without Feature X053, “Advanced table mapping: table as forest”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *True*.
- 5) Without Feature X054, “Advanced table mapping: table as element”, a conforming application shall not invoke this Subclause of this document with *TABLEFOREST* set to *False*.
- 6) Without Feature X055, “Advanced table mapping: with target namespace”, a conforming application shall not invoke this Subclause of this document with *TARGETNS* that is not a zero-length string.

9.17 Mapping an SQL catalog to an XML document and an XML schema document

- 7) Without Feature X056, “Advanced table mapping: data mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “metadata only”.
- 8) Without Feature X057, “Advanced table mapping: metadata mapping”, a conforming application shall not invoke this Subclause of this document with *RETURN* not set to “data only”.
- 9) Without Feature X058, “Advanced table mapping: base64 encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using base64.
- 10) Without Feature X059, “Advanced table mapping: hex encoding of binary strings”, a conforming application shall not invoke this Subclause of this document with *ENCODING* set to indicate that binary strings are to be encoded using hex.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10 Additional common rules

This Clause modifies Clause 9, “Additional common rules”, in ISO/IEC 9075-2.

10.1 Retrieval assignment

This Subclause modifies Subclause 9.1, “Retrieval assignment”, in ISO/IEC 9075-2.

Function

Specify rules for assignments to targets that do not support null values or that support null values with indicator parameters (e.g., assigning SQL-data to host parameters or host variables).

Syntax Rules

- 1) Insert after the last SR: If *TD* is an XML type, then

Case:

- a) If *TD* is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then *SD* shall be either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)).

- b) If *TD* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then

Case:

- i) If the type descriptor of *TD* includes the XML namespace URI *N* and the XML NCName *EN* of a global element declaration schema component, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*, and the type descriptor of *SD* shall include an XML namespace URI that is identical to *N*, as defined by XML Namespaces and an XML NCName that is equivalent to *EN*.

- ii) If the type descriptor of *TD* includes the XML namespace URI *N*, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*, and the type descriptor of *SD* shall include an XML namespace URI that is identical to *N*, as defined by XML Namespaces.

- iii) Otherwise, *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*.

- c) Otherwise, *SD* shall be an XML type.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR 7)x: If the declared type of T is an XML type, then:
 - a) Case:
 - i) If the declared type of T is XML(DOCUMENT(UNTYPED)), XML(DOCUMENT(ANY)), or XML(DOCUMENT(XMLSCHEMA)), and V is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then an exception condition is raised: *data exception — not an XML document (2200L)*.
 - ii) If the declared type of T is XML(CONTENT(UNTYPED)), XML(CONTENT(ANY)), or XML(CONTENT(XMLSCHEMA)), and V is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then an exception condition is raised: *data exception — not an XQuery document node (2200U)*.
 - b) The value of T is set to V .

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.2 Store assignment

This Subclause modifies Subclause 9.2, “Store assignment”, in ISO/IEC 9075-2.

Function

Specify rules for assignments where the target permits null without the use of indicator parameters or indicator variables, such as storing SQL-data or setting the value of SQL parameters.

Subclause Signature

```
“Store assignment” [General Rules] (  
  Parameter: “TARGET” ,  
  Parameter: “VALUE” ,  
  Parameter: “PASSING”  
)
```

TARGET — a site that is the target of a store assignment operation.

VALUE — a value that is to be assigned to TARGET.

PASSING — an <XML passing mechanism> (BY VALUE or BY REF).

Syntax Rules

- 1) Insert after the last SR: If *TD* is an XML type, then
Case:
 - a) If *TD* is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then *SD* shall be either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)).
 - b) If *TD* is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then
Case:
 - i) If the type descriptor of *TD* includes the XML namespace URI *N* and the XML NCName *EN* of a global element declaration schema component, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*, and the type descriptor of *SD* shall include an XML namespace URI that is identical to *N*, as defined by XML Namespaces, and an XML NCName that is equivalent to *EN*.
 - ii) If the type descriptor of *TD* includes the XML namespace URI *N*, then *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*, and the type descriptor of *SD* shall include an XML namespace URI that is identical to *N*, as defined by XML Namespaces.
 - iii) Otherwise, *SD* shall be either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML schema identified by the registered XML schema descriptor included in the type descriptor of *TD* shall be identical to the XML schema identified by the registered XML schema descriptor included in the type descriptor of *SD*.

- c) Otherwise, *SD* shall be an XML type.

Access Rules

No additional Access Rules.

General Rules

- 1) **Replicate GR 1):** Let *T* be the *TARGET*, let *V* be the *VALUE*, and let *P* be the *PASSING* in an application of the General Rules of this Subclause.
- 2) **Insert after GR 3)b)xxiv):** If the declared type of *T* is the XML type, then:
 - a) Case:
 - i) If the declared type of *T* is XML(DOCUMENT(UNTYPED)), XML(DOCUMENT(ANY)), or XML(DOCUMENT(XMLSCHEMA)), and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then an exception condition is raised: *data exception — not an XML document (2200L)*.
 - ii) If the declared type of *T* is XML(CONTENT(UNTYPED)), XML(CONTENT(ANY)), or XML(CONTENT(XMLSCHEMA)), and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node, then an exception condition is raised: *data exception — not an XQuery document node (2200U)*.
 - b) Case:
 - i) If *T* is a <column reference> or a <target array element specification> whose <target array reference> is a <column reference>, or *P* is BY VALUE, then the General Rules of Subclause 10.20, “Constructing a copy of an XML value”, are applied with **v** as *VALUE*; let **v1** be the *COPY* returned from the application of those General Rules.
 - ii) Otherwise, let *V1* be *V*.
 - c) The value of *T* is set to *V1*.

Conformance Rules

No additional Conformance Rules.

10.3 Result of data type combinations

This Subclause modifies Subclause 9.5, “Result of data type combinations”, in ISO/IEC 9075-2.

Function

Specify the declared type of the result of certain combinations of values of compatible data types, such as <case expression>s, <collection value expression>s, or a column in the result of a <query expression>.

Syntax Rules

- 1) Insert after SR 3)f) If any data type in *DTS* is an XML type, then:
 - a) Each data type in *DTS* shall be an XML type.
 - b) Case:
 - i) If any of the data types in *DTS* is XML(SEQUENCE), then the declared type of the result is XML(SEQUENCE).
 - ii) Otherwise:
 - 1) Let N be the number of data types in *DTS*. Let T_i , $1 \text{ (one)} \leq i \leq N$, be the i -th data type in *DTS*.
 - 2) Case:
 - A) If $N = 1 \text{ (one)}$, then the declared type of the result is T_1 .
 - B) Otherwise,
 - Case:
 - I) If T_i , for all i , $1 \text{ (one)} \leq i \leq N$, is XML(DOCUMENT(UNTYPED)), then the declared type of the result is XML(DOCUMENT(UNTYPED)).
 - II) If T_i , for all i , $1 \text{ (one)} \leq i \leq N$, is either XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then the declared type of the result is XML(CONTENT(UNTYPED)).
 - III) If there exists a registered XML schema S and a global element declaration schema component E such that, for all i , $1 \text{ (one)} \leq i \leq N$, T_i is XML(DOCUMENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI NS that is identical to the XML namespace URI of E , as defined by XML Namespaces, and an XML NCName EN that is equivalent to the XML NCName of E , then the declared type of the result is XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S , the XML namespace URI NS , and the XML NCName EN .
 - IV) If there exists a registered XML schema S and an XML namespace NS such that, for all i , $1 \text{ (one)} \leq i \leq N$, T_i is XML(DOCUMENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI that is identical to NS , as defined by XML Namespaces, then the declared

type of the result is XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S and the XML namespace URI NS .

- V) If there exists a registered XML schema S such that, for all i , 1 (one) $\leq i \leq N$, T_i is XML(DOCUMENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S , then the declared type of the result is XML(DOCUMENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S .
- VI) If there exists a registered XML schema S and a global element declaration schema component E such that, for all i , 1 (one) $\leq i \leq N$, T_i is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI NS that is identical to the XML namespace URI of E , as defined by XML Namespaces, and an XML NCName EN that is equivalent to the XML NCName of E , then the declared type of the result is XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S , the XML namespace URI NS , and the XML NCName EN .
- VII) If there exists a registered XML schema S and an XML namespace NS such that, for all i , 1 (one) $\leq i \leq N$, T_i is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S and an XML namespace URI that is identical to NS , as defined by XML Namespaces, then the declared type of the result is XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S and the XML namespace URI NS .
- VIII) If there exists a registered XML schema S such that, for all i , 1 (one) $\leq i \leq N$, T_i is either XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)) and the XML type descriptor of T_i includes the registered XML schema descriptor of S , then the declared type of the result is XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes the registered XML schema descriptor of S .
- IX) Otherwise, the declared type of the result is XML(CONTENT(ANY)).

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

10.4 Type precedence list determination

This Subclause modifies Subclause 9.7, “Type precedence list determination”, in ISO/IEC 9075-2.

Function

Determine the type precedence list of a given type.

Syntax Rules

- 1) Insert after the last SR: If *DT* is an XML type, then *TPL* is XML.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.5 Type name determination

This Subclause modifies Subclause 9.9, “Type name determination”, in ISO/IEC 9075-2.

Function

Determine an <identifier> given the name of a predefined or collection type.

Syntax Rules

- 1) Insert after SR 2)w): If *DT* specifies XML, then let *FNSDT* be “XML”.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.6 Determination of identical values

This Subclause modifies Subclause 9.10, “Determination of identical values”, in ISO/IEC 9075-2.

Function

Determine whether two instances of values are identical, that is to say, are occurrences of the same value.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

1) Insert before GR 2)d): If *V1* and *V2* are both of the XML type, then

Case:

- a) If *V1* and *V2* are both XQuery sequences, then *V1* and *V2* are identical if they have the same number of XQuery items and their corresponding XQuery items are identical.
- b) If *V1* and *V2* are both XQuery atomic values, then *V1* and *V2* are identical if they are labeled with the same XQuery atomic type *XQAT* and

Case:

- i) If *XQAT* is *xs:duration*, or an XML schema type derived from *xs:duration*, then *YM1* equals *YM2* and *DT1* equals *DT2* where *YM1* and *YM2* are XQuery atomic values of type *xs:yearMonthDuration* whose year and month components equal the year and month components of *V1* and *V2*, respectively, and *DT1* and *DT2* are XQuery atomic values of type *xs:dayTimeDuration* whose day, hour, minute, and second components equal the day, hour, minute, and second components of *V1* and *V2*, respectively.
- ii) Otherwise, the result of comparing *V1* and *V2* using the XQuery “eq” operation is *True*.
- c) If *V1* and *V2* are both XQuery nodes, then *V1* and *V2* are identical if the XQuery node identity of *V1* is the same as the XQuery node identity of *V2*.

NOTE 69 — This definition is equivalent to the XQuery expression “*v1 is v2*”.

- d) Otherwise, *V1* and *V2* are not identical.

Conformance Rules

No additional Conformance Rules.

10.7 Determination of equivalent XML values

Function

Determine whether two instances of XML values are equivalent.

NOTE 70 — This Subclause is implicitly invoked whenever the word *equivalent* is used with respect to XML values.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *V1* and *V2* be two XML values specified in an application of this Subclause.
- 2) Whether *V1* and *V2* are equivalent or not equivalent is defined as follows:

NOTE 71 — This definition involves the simultaneous recursive definition of equivalent XQuery items and identical properties of XQuery nodes, as well as equivalent XML values.

- a) Two XQuery sequences are equivalent if they have the same number of XQuery items and their corresponding XQuery items are equivalent.
- b) Two XQuery atomic values are equivalent if they are identical.
- c) Two XQuery nodes ***xn1*** and ***xn2*** are defined to be equivalent if and only if all of the following are true:
 - i) ***xn1*** and ***xn2*** are the same kind of XQuery node (both are an XQuery document node, an XQuery element node, an XQuery attribute node, an XQuery processing instruction node, an XQuery text node, an XQuery comment node, or an XQuery namespace node).
 - ii) If ***xn1*** is not a document node, then exactly one of the following is true:
 - 1) The **parent** property of ***xn1*** and the **parent** property of ***xn2*** are both empty.
 - 2) The XQuery node ***p1*** that is the **parent** property of ***xn1*** is equivalent to the XQuery node ***p2*** that is the **parent** property of ***xn2***, and if ***xn1*** and ***xn2*** are not XQuery attribute nodes or XQuery namespace nodes, then ***xn1*** and ***xn2*** have the same ordinal position in the **children** property of ***p1*** and ***p2***, respectively.
 - iii) Every significant property ***P*** of ***xn1*** is identical to the corresponding property ***P*** of ***xn2***. The significant and insignificant properties of XQuery nodes are shown in Table 4, “XQuery node properties”.

Table 4 — XQuery node properties

XQuery Node Type	Significant Properties	Insignificant Properties
document	children unparsed-entities	base-uri document-uri
element	node-name parent type-name children attributes nilled	namespaces base-uri
attribute	node-name string-value parent type	
processing instruction	target content parent	base-uri
text	content parent	
comment	content parent	
namespace	uri parent	prefix

- d) A property P of an XQuery node $XN1$ is identical to the same property P of another XQuery node $XN2$ if

Case:

- i) If P is the **children** property or the **parent** property, then the XQuery sequences that are returned by the XQuery accessor of property P applied to $XN1$ and $XN2$ are identical.
- ii) If P is the **unparsed-entities** property or the **attributes** property, then the number of XQuery items returned by the XQuery accessor of property P applied to $XN1$ equals the number of XQuery items returned by the XQuery accessor of property P applied to $XN2$, and there exists a one-to-one mapping of the XQuery items returned by the XQuery accessor of property P applied to $XN1$ to the XQuery items returned by the XQuery accessor of property P applied to $XN2$ such that corresponding XQuery items are identical.
- iii) If P is the **node-name** property, **type-name** property, **nilled** property, **string-value** property, **uri** property, **target** property, or **content** property, then the XQuery atomic value that is returned by the XQuery accessor of property P applied to $XN1$ is identical to the XQuery atomic value that is returned by the XQuery accessor of property P applied to $XN2$.

NOTE 72 — The **content** and **uri** properties are accessed by the **dm:string-value** XQuery accessor, and the **target** property is accessed by the **dm:node-name** XQuery accessor. Otherwise, the name of the XQuery accessor is the same as the name of the property.

- e) An XQuery atomic value and an XQuery node are not equivalent.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.8 Equality operations

This Subclause modifies Subclause 9.11, “Equality operations”, in ISO/IEC 9075-2.

Function

Specify the prohibitions and restrictions by data type on operations that involve testing for equality.

Syntax Rules

- 1) Insert after the last SR: The declared type of an operand of an equality operation shall not be XML-ordered.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.9 Grouping operations

This Subclause modifies Subclause 9.12, "Grouping operations", in ISO/IEC 9075-2.

Function

Specify the prohibitions and restrictions by data type on operations that involve grouping of data.

Syntax Rules

- 1) Insert after the last SR: The declared type of an operand of a grouping operation shall not be XML-ordered.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.10 Multiset element grouping operations

This Subclause modifies Subclause 9.13, “Multiset element grouping operations”, in ISO/IEC 9075-2.

Function

Specify the prohibitions and restrictions by data type on the declared element type of a multiset for operations that involve grouping the elements of a multiset.

Syntax Rules

- 1) Insert after the last SR: The declared element type of a multiset operand of a multiset element grouping operation shall not be XML-ordered.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.11 Ordering operations

This Subclause modifies Subclause 9.14, "Ordering operations", in ISO/IEC 9075-2.

Function

Specify the prohibitions and restrictions by data type on operations that involve ordering of data.

Syntax Rules

- 1) Insert after the last SR: The declared type of an operand of an ordering operation shall not be XML-ordered.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.12 Potential sources of non-determinism

This Subclause modifies Subclause 9.16, “Potential sources of non-determinism”, in ISO/IEC 9075-2.

Function

Define the potential sources of non-determinism.

Syntax Rules

- 1) **Insert after SR 1)as):** An <XML cast specification> whose <XML cast target> is an XML type, whose <XML cast operand> has a declared type that is an XML type, and whose <XML passing mechanism> specifies or implies BY VALUE.
- 2) **Insert after SR 1)as):** An <XML cast specification> whose <XML cast target> is either XML(CONTENT(ANY)) or XML(CONTENT(UNTYPED)) type and whose <XML cast operand> has a declared type that is not an XML type.
- 3) **Insert after SR 1)as):** An <XML character string serialization> or an <XML binary string serialization>.
- 4) **Insert after SR 1)as):** A <cast specification> whose result type is an XML type and whose <cast operand> has a declared type that is an XML type and whose <XML passing mechanism> specifies or implies BY VALUE.
- 5) **Insert after SR 1)as):** An <XML value function> other than <XML query> and <XML concatenation>.
- 6) **Insert after SR 1)as):** An <XML concatenation> that does not implicitly or explicitly specify RETURNING SEQUENCE.
- 7) **Insert after SR 1)as):** An <XML query> that does not conform to implementation-defined (IA115) rules enabling the SQL-implementation to deduce that the result of the <XML query> is deterministic.
- 8) **Insert after SR 1)as):** An <XML table> that does not conform to implementation-defined (IA116) rules enabling the SQL-implementation to deduce that the result of the <XML table> is deterministic.
- 9) **Insert after SR 1)as):** An <XML exists predicate> that does not conform to implementation-defined (IA117) rules enabling the SQL-implementation to deduce that the result of the <XML exists predicate> is deterministic.
- 10) **Insert after SR 1)as):** An <XML valid predicate> *XVP* for which exactly one of the following is true:
 - a) *XVP* does not specify <XML valid according to clause>.
 - b) *XVP* specifies an <XML valid according to clause> that identifies a non-deterministic registered XML schema and *XVP* does not specify an <XML valid element name specification> of an <XML valid element namespace specification>.
 - c) *XVP* specifies an <XML valid according to clause> that identifies a non-deterministic XML namespace and *XVP* does not specify an <XML valid element name specification>.
 - d) *XVP* specifies an <XML valid element clause> that identifies a non-deterministic global element declaration schema component of a registered XML schema.

NOTE 73 — This implies that an <XML valid predicate> that is used in a <check constraint definition> or an <assertion definition> has to contain an <XML valid according to clause> that either identifies a deterministic registered XML schema, or contains an <XML valid element namespace specification> that identifies a deterministic XML namespace of a registered XML schema, or contains an <XML valid element name specification> that identifies a deterministic global element declaration schema component of a registered XML schema.

- 11) Insert after SR 1)as): An <XML aggregate>.

Access Rules

None.

General Rules

None.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.13 Invoking an SQL-invoked routine

This Subclause modifies Subclause 9.18, “Invoking an SQL-invoked routine”, in ISO/IEC 9075-2.

Function

Execute the invocation of an SQL-invoked routine.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

NOTE 74 — The General Rules of this Subclause as defined in GR 2) of Subclause 9.18, “Invoking an SQL-invoked routine”, in ISO/IEC 9075-2 are not always terminated when an exception condition is raised.

- 1) Insert before GR 4)c):
Case:
 - a) If T_i is an XML type, then let $PTEMP$ be the <XML passing mechanism> of P_i
 - b) Otherwise let $PTEMP$ be the null value.
- 2) Augment GR 4)c)i) by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 3) Insert after GR 5)b)1): If T_i is an XML type, then:
 - a) Let XDT_i be the associated string type of P_i .
 - b) Let XO_i be the associated XML option of P_i .
 - c) It is implementation-defined (IA118) whether XDO_i is INCLUDING XMLDECLARATION or EXCLUDING XMLDECLARATION.
 - d) Case:
 - i) If the character set of XDT_i is UTF16, then let BOM_i be $U\&' \backslash FEFF '$.
 - ii) Otherwise, let BOM_i be the zero-length string of type XDT_i .
 - e) CPV_i is replaced by the result of

$BOM_i \ || \ XMLSERIALIZE (XO_i \ CPV_i \ AS \ XDT_i \ XDO_i)$

- 4) Insert after GR 5)b)ii)1): If T_i is an XML type, then:
- a) Let XDT_i be the associated string type of P_i .
 - b) CPV_i is replaced by an implementation-defined (IV235) value of type XDT_i .
- 5) Insert before GR 9)j)ii)4)B)II)2)b): If CRT is an XML type, then:
- a) Let XO be the associated XML option of the result of R .
 - b) It is implementation-defined (IA119) whether XWO is STRIP WHITESPACE or PRESERVE WHITESPACE.
 - c) Let RDI be the result of

$$\text{XMLPARSE} (XO \ ERDI \ XWO)$$
- 6) Insert before GR 9)j)iii)2)C): If T_i is an XML type, then:
- a) Let XO_i be the associated XML option of P_i .
 - b) It is implementation-defined (IA120) whether XWO_i is STRIP WHITESPACE or PRESERVE WHITESPACE.
 - c) CPV_i is set to the result of

$$\text{XMLPARSE} (XO_i \ EV_i \ XWO_i)$$
- 7) Insert before GR 10)a)iii):
Case:
- a) If $ERDT$ is an XML type, then let $PTEMP$ be the <XML passing mechanism> of the <returns clause> of R
 - b) Otherwise let $PTEMP$ be the null value.
- 8) Augment GR 10)a)iii) by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 9) Insert before GR 10)b)ii)1)B)V)1)b):
Case:
- a) If EDT is an XML type, then let $PTEMP$ be the <XML passing mechanism> of P_i
 - b) Otherwise let $PTEMP$ be the null value.
- 10) Augment GR 10)b)ii)1)B)V)1)b) by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 11) Insert before GR 10)b)ii)1)B)V)2)c):
Case:
- a) If EDT is an XML type, then let $PTEMP$ be the <XML passing mechanism> of P_i
 - b) Otherwise let $PTEMP$ be the null value.
- 12) Augment GR 10)b)ii)1)B)V)2)c) by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.

10.13 Invoking an SQL-invoked routine

- 13) Insert before GR 10)b)ii)2)B): If the declared type of P_i is an XML type, then let PTEMP be the <XML passing mechanism> of P_i
- 14) Augment GR 10)b)ii)2)B) by adding “PTEMP as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.14 Determination of namespace URI

Function

Determine the XML namespace URI of an XML QName.

Subclause Signature

"Determination of namespace URI" [Syntax Rules] (
Parameter: "QNAME",
Parameter: "BNFTERM"
) Returns: "NSURI"

QNAME — an XML QName.

BNFTERM — a context non-terminal, either <XML element> or <XML forest>

NSURI — the XML namespace URI that is associated with the XML namespace of QNAME.

Syntax Rules

- 1) Let *QN* be the *QNAME* and let *B* be the *BNFTERM* in an application of the Syntax Rules of this Subclause. The result of the application of this Subclause is returned as *NSURI*.
- 2) Case:
 - a) If *QN* has an XML QName prefix, then:
 - i) Let *P* be the XML QName prefix of *QN*.
 - ii) Case:
 - 1) If *P* is equivalent to 'xml', then let *NSURI* be
`http://www.w3.org/XML/1998/namespace`
 - 2) Otherwise, *B* shall be within the scope of one or more <XML namespace declaration>s that contain an <XML namespace prefix> equivalent to *P* or *P* shall be equivalent to one of 'sqlxml', 'xs', or 'xsi'.
 - Case:
 - A) If *B* is within the scope of one or more <XML namespace declaration>s that contain an <XML namespace prefix> equivalent to *P*, then:
 - I) Let *XND* be the <XML namespace declaration> that contains an <XML namespace prefix> equivalent to *P* with innermost scope that includes *B*.
 - II) Let *XNDI* be the <XML namespace declaration item> of *XND* that contains an <XML namespace prefix> equivalent to *P*.
 - III) Let *NSURI* be the <XML namespace URI> contained in *XNDI*.
 - B) Otherwise,
Case:

10.14 Determination of namespace URI

- I) If P is equivalent to '`sqlxml`', then let $NSURI$ be
`http://standards.iso.org/iso/9075/2003/sqlxml`
- II) If P is equivalent to '`xs`', then let $NSURI$ be
`http://www.w3.org/2001/XMLSchema`
- III) If P is equivalent to '`xsi`', then let $NSURI$ be
`http://www.w3.org/2001/XMLSchema-instance`

NOTE 75 — The XML namespace prefixes `fn`, `xs`, and `local`, which are predeclared in *XQuery 3.1: an XML Query Language*, if present in an <XML element name> or an <XML attribute name>, need to be in the scope of one or more <XML namespace declaration>s.

b) Otherwise,

Case:

- i) If B is contained within the scope of one or more <XML namespace declaration>s that contain an <XML default namespace declaration item>, then:
 - 1) Let $XDNDI$ be the <XML default namespace declaration item> with innermost scope that includes B .
 - 2) Case:
 - A) If $XDNDI$ contains an <XML namespace URI>, then let $NSURI$ be that <XML namespace URI>.
 - B) Otherwise, let $NSURI$ be the zero-length string.
 - ii) Otherwise, let $NSURI$ be the zero-length string.
- 3) Let CS be the character set of the declared type of $NSURI$. Let CSM be the implementation-defined (IA091) mapping of strings of CS to strings of Unicode. Let R be the result of mapping $NSURI$ to a string of Unicode using CSM .
- 4) Evaluation of the Syntax Rules is terminated and control is returned to the invoking Subclause, which receives R as $NSURI$.

Access Rules

None.

General Rules

None.

Conformance Rules

None.

10.15 Construction of an XML element

Function

Construct an XML value consisting of a single XQuery element node.

Subclause Signature

"Construction of an XML element" [General Rules] (
Parameter: "QNAME" ,
Parameter: "ENCODING" ,
Parameter: "NAMESPACE" ,
Parameter: "ATTRIBUTES" ,
Parameter: "CONTENTS" ,
Parameter: "OPTION"
) Returns: "XMLELEM"

QNAME — an XML 1.1 QName.

ENCODING — an indication of whether binary strings are to be encoded in base64 or hex.

NAMESPACE — an XML namespace URI.

ATTRIBUTES — a set of XQuery attribute nodes.

CONTENT — a list of values.

OPTION — either NIL ON NULL or NIL ON NO CONTENT.

XMLELEM — the XML element that is constructed in this Subclause.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let **QN** be the *QNAME*, let **ENC** be the *ENCODING*, let **NSURI** be the *NAMESPACE*, let **ATTRS** be the *ATTRIBUTES*, let **CON** be the *CONTENTS*, and let **OPT** be the *OPTION* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLELEM*.
- 2) Let *N* be the number of values in *CON*. Let V_1, \dots, V_N be an enumeration of the values in *CON*.
- 3) Case:
 - a) If $N > 0$ (zero) and, for every *i* between 1 (one) and *N*, V_i is the null value, then let *ALLNULL* be *True*.
 - b) Otherwise, let *ALLNULL* be *False*.
- 4) Case:

10.15 Construction of an XML element

- a) If *ALLNULL* is *True* and *OPT* is NULL ON NULL, then the result is the null value.
- b) If *ALLNULL* is *True* and *OPT* is ABSENT ON NULL, then the result is an empty XQuery sequence.
- c) Otherwise:
- i) For each j , $1 \text{ (one)} \leq j \leq N$, such that V_j is not the null value:
 - 1) Case:
 - A) If the most specific type of V_j is an XML type, then let **CEC_j** be a variable whose value is identical to V_j .
 - B) Otherwise, the General Rules of Subclause 9.8, “Mapping values of SQL data types to values of XML schema data types”, are applied with V_j as *SQLVALUE*, *ENC* as *ENCODING*, “absent” as *NULLS*, and *True* as *CHARMAPPING*; let *XMLV_j* be the *XMLVALUE* returned from the application of those General Rules. **XMLV_j** is a character string of Unicode characters. Let **CEC_j** be the result of

```
XMLPARSE (CONTENT XMLVj PRESERVE WHITESPACE)
```
 - 2) The General Rules of Subclause 10.19, “Removing XQuery document nodes from an XQuery sequence”, are applied with **CEC_j** as *SEQUENCE*; let **S_j** be the *RESULT* returned from the application of those General Rules.
 - ii) Let *NILLED* be defined as follows.

Case:

 - 1) If *OPT* is NIL ON NULL and *ALLNULL* is *True*, then *NILLED* is *True*.
 - 2) If *OPT* is NIL ON NO CONTENT and there does not exist at least one j , $1 \text{ (one)} \leq j \leq N$, such that V_j is an XQuery element node or an XQuery text node, then *NILLED* is *True*.
 - 3) Otherwise, *NILLED* is *False*.
 - iii) Case:
 - 1) If *NILLED* is *True*, then:
 - A) Let **XSIURI** be the XML namespace URI given in Table 2, “XML namespace prefixes and their URIs”, corresponding to the XML namespace prefix **xsi** .
 - B) Let **NILLAI** be an XQuery attribute node whose properties are set as follows:
 - I) The **node-name** property is an XQuery atomic value of XQuery atomic type **xs:QName**, whose local name is **nil** and whose namespace URI is **XSIURI**.
 - II) The **string-value** property is **true**.
 - III) The **type-name** property is **xs:untypedAtomic**.
 - IV) The **parent** property is empty.
 - 2) Otherwise, let **NILLAI** be the empty XQuery sequence.
 - iv) Let **S** be the XQuery sequence formed by concatenating **ATTRS**, **NILLAI**, and the **S_j** in order from $j = 1 \text{ (one)}$ through $j = N$.

- v) The Syntax Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied with the <XML element> or <XML forest> that invoked the current Subclause as *NONTERMINAL*; let *xsc* be the *STATICCONTEXT* returned from the application of those Syntax Rules. The validation mode of *xsc* is set to an implementation-defined (IV236) value.

NOTE 76 — *xsc* is an XQuery static context.

- vi) The General Rules of Subclause 10.22, “Creation of an XQuery expression context”, are applied; let *xdc* be the *DYNAMICCONTEXT* returned from the application of those General Rules.

NOTE 77 — *xdc* is an XQuery dynamic context.

- vii) Let *xsc* and *xdc* be augmented with the following XQuery variables:

- 1) An XQuery variable *\$QNAME* whose XQuery formal type notation is *xs:QName* and whose value is a QName whose local name is the XML 1.1 QName local part of *QN* and whose namespace URI is *NSURI*.
- 2) An XQuery variable *\$SEQ*, whose XQuery formal type notation is (*element of type xs:anyType | attribute of type xs:anySimpleType | text | comment | processing-instruction | xs:anyAtomic-Type | document { (element of type xs:anyType | comment | processing-instruction | text) * }) ** and whose value is *S*.

NOTE 78 — If the SQL/XML implementation does not support Feature X211, “XML 1.1 support”, then any Names, NCNames, and QNames found in either *\$QNAME* or *\$SEQ* will already be XML 1.0 Names, NCNames, and QNames.

- viii) Case:

- 1) If the SQL-implementation supports Feature X211, “XML 1.1 support”, then let *EI* be the result of an XQuery evaluation with XML 1.1 lexical rules, using *xsc* and *xdc* as the XQuery expression context, of the XQuery expression


```
element { $QNAME } { $SEQ }
```

If an XQuery error occurs during the evaluation, then an exception condition is raised: *XQuery error (10000)*.
- 2) Otherwise, let *EI* be the result of an XQuery evaluation with XML 1.0 lexical rules, using *xsc* and *xdc* as the XQuery expression context, of the XQuery expression

```
element { $QNAME } { $SEQ }
```

If an XQuery error occurs during the evaluation, then an exception condition is raised: *XQuery error (10000)*.

- ix) Let *xQEN* be an XQuery element node that is equivalent to *EI*.
- x) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *xQEN* as *XMLELEM*.

Conformance Rules

None.

10.16 Concatenation of two XML values

Function

Specify the result of the concatenation of two XML values.

Subclause Signature

"Concatenation of two XML values" [General Rules] (
Parameter: "FIRSTVAL",
Parameter: "SECONDVAL"
) Returns: "CONCAT"

FIRSTVAL — an XML value.

SECONDVAL — an XML value.

CONCAT — an XML value resulting from the concatenation of the first and second XML values.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let x be the *FIRSTVAL* and let y be the *SECONDVAL* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *CONCAT*.
- 2) Case:
 - a) If x is the null value, then let c be y .
 - b) If y is the null value, then let c be x .
 - c) Otherwise, let c be the XQuery sequence consisting of every XQuery item of x , in order, followed by every XQuery item of y , in order.
- 3) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives c as *CONCAT*.

Conformance Rules

None.

10.17 Serialization of an XML value

Function

Specify the serialization of an XML value.

Subclause Signature

"Serialization of an XML value" [General Rules] (

Parameter: "VALUE" ,
Parameter: "SYNTAX" ,
Parameter: "TYPE" ,
Parameter: "ENCODING" ,
Parameter: "BOM" ,
Parameter: "VERSION" ,
Parameter: "XMLDECLARATION" ,
Parameter: "INDENT"

) Returns: "SERIALIZATION"

VALUE — an XML value.

SYNTAX — either DOCUMENT or CONTENT.

TYPE — an SQL string type.

ENCODING — an XML encoding, either UTF8 or UTF16.

BOM — the choice of whether to generate an XML byte-order mark, either *True*, *False*, or *Unknown*.

VERSION — an XML version number, either "1.0" or another XML version number.

XMLDECLARATION — the choice of whether to generate an XML declaration, either *True*, *False*, or *Unknown*.

INDENT — the choice of whether to "pretty-print" the serialized XML by means of indentation, either *True* or *False*.

SERIALIZATION — the character-string serialization of the XML value.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let v be the *VALUE*, let *DC* be the *SYNTAX*, let *DT* be the *TYPE*, let *CS* be the *ENCODING*, let *B* be the *BOM*, let *VP* be the *VERSION*, let *DECL* be the *XMLDECLARATION*, and let *INDENT* be the *INDENT* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *SERIALIZATION*.

10.17 Serialization of an XML value

NOTE 79 — *V* is an XML value. *DC* is either DOCUMENT or CONTENT. *DT* is a string type. *B* is either *True*, *False*, or *Unknown*. *DECL* is either *True*, *False*, or *Unknown*. *INDENT* is either *True* or *False*.

- 2) If *V* is the null value, then *RES* is the null value and no further General Rules are applied.
- 3) If *DC* is DOCUMENT and *V* is not an XQuery sequence of length 1 (one) whose sole XQuery item is an XQuery document node whose **children** property contains exactly one XQuery element node, zero or more XQuery comment nodes, and zero or more XQuery processing instruction nodes, then an exception condition is raised: *data exception — not an XML document (2200L)*.
- 4) Case:
 - a) If *B* is *True*, then let **BOM** be **yes**.
 - b) If *B* is *False*, then let **BOM** be **no**.
 - c) Otherwise, *B* is *Unknown*, and

Case:

- i) If *DT* is a binary string type, then

Case:

- 1) If *CS* is UTF16, then let **BOM** be **yes**.
- 2) Otherwise, it is implementation-defined (ID212) whether **BOM** is **yes** or **no**.

NOTE 80 — The purpose of the previous rule is to ensure that a Byte Order Mark (BOM) can be prefixed to the serialized value when needed because of the specified encoding.

- ii) Otherwise, let **BOM** be **no**.

- 5) Case:
 - a) If *INDENT* is *True*, then let **IND** be “yes”.
 - b) Otherwise, let **IND** be “no”.
- 6) Let **METH** be an XML 1.0 QName whose XML 1.0 QName prefix is the zero-length string and whose XML 1.0 QName local part is “xml”.
- 7) It is implementation-defined (IV237) whether **SA** is **yes**, **no**, or **none**.
- 8) Case:
 - a) If *DECL* is *True*, then let **OXD** be **no**.
 - b) If *DECL* is *False*, then let **OXD** be **yes**.
 - c) Otherwise, (*DECL* is *Unknown*),

Case:

- i) If *DC* is DOCUMENT and at least one of the following is true:
 - 1) *CS* is neither UTF8 nor UTF16.
 - 2) **SA** is not **none**.
 - 3) *VP* is not “1.0”.

then let **OXD** be **no**.

- ii) If *DC* is DOCUMENT and all of the following are true:

- 1) *CS* is either UTF8 or UTF16.
- 2) *SA* is **none**.
- 3) *VP* is “1.0”.

then it is implementation-defined (IA122) whether *OXD* is **yes** or **no**.

iii) Otherwise, let *OXD* be **yes**.

9) Case:

a) If *VP* is “1.0”, then let *UN* be **no**.

b) Otherwise, it is implementation-defined (IA123) whether *UN* is **yes** or **no**.

10) Let *CSE*, *DP*, *DS*, *EUA*, *ICT*, *MT*, *NF*, and *UCM* be implementation-dependent (UV009) values that are permitted values for the *cdata-section-elements*, *doctype-public*, *doctype-system*, *escape-uri-attributes*, *include-content-type*, *media-type*, *normalization-form*, and *use-character-maps* serialization parameters, respectively, as defined in Section 3, “Serialization Parameters”, of XSLT and XQuery Serialization 3.1.

11) Case:

a) If *DT* is a character string type, then:

i) Let *CV* be the result of applying Section 5, “XML output method”, of XSLT and XQuery Serialization 3.1 to *V* with the following values for the serialization parameters:

- 1) *BOM* as the byte-order-mark.
- 2) *CSE* as the *cdata-section-elements*.
- 3) *DP* as the *doctype-public*.
- 4) *DS* as the *doctype-system*.
- 5) *CS* as the encoding.
- 6) *EUA* as the *escape-uri-attributes*.
- 7) *ICT* as the *include-content-type*.
- 8) *IND* as the indent.
- 9) *MT* as the *media-type*.
- 10) *METH* as the method.
- 11) *NF* as the *normalization-form*.
- 12) *OXD* as the *omit-xml-declaration*.
- 13) *SA* as the *standalone*.
- 14) *UN* as the *undeclare-prefixes*.
- 15) *UCM* as the *use-character-maps*.
- 16) *VP* as the version.

If an XQuery serialization error occurs during the application of Section 5, “XML output method”, of XSLT and XQuery Serialization 3.1 to *V*, then an exception condition is raised: *data exception — XQuery serialization error (2200W)*.

10.17 Serialization of an XML value

- ii) The General Rules of Subclause 10.2, “Store assignment”, are applied with a temporary site *TS* whose declared type is *DT* as *TARGET*, *CV* as *VALUE*, and the null value as *PASSING*.
 - iii) Let *RES* be the value of *TS*.
 - iv) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *RES* as *SERIALIZATION*.
- b) Otherwise (*DT* is a binary string type):
- i) Let *CV* be a binary string equivalent to the result of applying Section 5, “XML output method”, of XSLT and XQuery Serialization 3.1 to *V* with the following values for the serialization parameters:
 - 1) *BOM* as the byte-order-mark.
 - 2) *CSE* as the cdata-section-elements.
 - 3) *DP* as the doctype-public.
 - 4) *DS* as the doctype-system.
 - 5) *CS* as the encoding.
 - 6) *EUA* as the escape-uri-attributes.
 - 7) *ICT* as the include-content-type.
 - 8) *IND* as the indent.
 - 9) *MT* as the media-type.
 - 10) *METH* as the method.
 - 11) *NF* as the normalization-form.
 - 12) *OXD* as the omit-xml-declaration.
 - 13) *SA* as the standalone.
 - 14) *UN* as the undeclare-prefixes.
 - 15) *UCM* as the use-character-maps.
 - 16) *VP* as the version.

If an XQuery serialization error occurs during the application of Section 5, “XML output method”, of XSLT and XQuery Serialization 3.1 to *V*, then an exception condition is raised: *data exception — XQuery serialization error (2200W)*.
 - ii) The General Rules of Subclause 10.2, “Store assignment”, are applied with a temporary site *TS* whose declared type is *DT* as *TARGET*, *CV* as *VALUE*, and the null value as *PASSING*.
 - iii) Let *RES* be the value of *TS*.
 - iv) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *RES* as *SERIALIZATION*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.18 Parsing a string as an XML value

Function

Parse a character string or a binary string to obtain an XML value.

Subclause Signature

"Parsing a string as an XML value" [General Rules] (

Parameter: "SYNTAX",

Parameter: "TEXT",

Parameter: "OPTION"

) Returns: "XMLPARSE"

SYNTAX — either DOCUMENT or CONTENT.

TEXT — a character string representation ("serialization") of an XML document or a sequence of XML elements.

OPTION — PRESERVE WHITESPACE or STRIP WHITESPACE.

XMLPARSE — the XML value resulting from parsing the character string representation.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let *DC* be the *SYNTAX*, let *V* be the *TEXT*, and let *WO* be the *OPTION* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *XMLPARSE*.
- 2) A string is called a *textual XML 1.0 document* if the string conforms to the definition of a well-formed XML document as defined in [XML 1.0](#), as modified by [Namespaces in XML 1.0](#).
- 3) A string is called a *textual XML 1.1 document* if the string conforms to the definition of a well-formed XML document as defined in [XML 1.1](#), as modified by [Namespaces in XML 1.1](#).
- 4) A string is called a *textual XML 1.0 content* if any of the following is true:
 - a) The character string is a textual XML 1.0 document.
 - b) The character string conforms to the definition of a well-formed external parsed entity as defined in [XML 1.0](#), as modified by [Namespaces in XML 1.0](#).
- 5) A string is called a *textual XML 1.1 content* if any of the following is true:
 - a) The character string is a textual XML 1.1 document.
 - b) The character string conforms to the definition of a well-formed external parsed entity as defined in [XML 1.1](#), as modified by [Namespaces in XML 1.1](#).

- 6) Case:
- a) If the SQL-implementation supports Feature X211, “XML 1.1 support”, then
Case:
 - i) If *DC* is DOCUMENT and *V* is neither a textual XML 1.0 document nor a textual XML 1.1 document, then an exception condition is raised: *data exception — invalid XML document (2200M)*.
 - ii) If *DC* is CONTENT and *V* is neither a textual XML 1.0 content nor a textual XML 1.1 content, then an exception condition is raised: *data exception — invalid XML content (2200N)*.
 - b) Otherwise,
Case:
 - i) If *DC* is DOCUMENT and *V* is not a textual XML 1.0 document, then an exception condition is raised: *data exception — invalid XML document (2200M)*.
 - ii) If *DC* is CONTENT and *V* is not a textual XML 1.0 content, then an exception condition is raised: *data exception — invalid XML content (2200N)*.
- 7) *V* is parsed and a collection *C* of XML information items is produced according to the rules of [XML Information Set](#), with the following modifications:
- a) The generation of the XML document information item *XRII* is modified as follows:
 - i) If *DC* is CONTENT, then the **[children]** property of the XML document information item consists of the list of XML information items that would be produced using the rules of [XML Information Set](#) corresponding to the BNF non-terminal content defined in rule [43] of [XML 1.0](#) or of [XML 1.1](#).
NOTE 81 — It is not an error for the XML document information item to contain zero or more than one XML element information item in this case, or for it to contain XML character information items.
 - ii) The **[notations]** property is implementation-defined ([IA124](#)).
 - iii) The **[unparsed entities]** property is implementation-defined ([IA124](#)).
 - b) The **[base URI]** property of any XML information item is implementation-dependent ([UV012](#)).
 - c) References to entities that are defined in an internal DTD are replaced by their expanded form.
 - d) Default values defined by an internal DTD are applied.
 - e) Support for an external DTD is implementation-defined ([IA089](#)).
- 8) If *WO* is STRIP WHITESPACE, then:
- a) An XML element information item *EII* contained in *C* is *potentially whitespace-strippable* if at least one of the following is true:
 - i) *EII* is contained in the **[children]** property of *XRII* and *EII* does not have an **[attributes]** property that contains an XML attribute information item for which all of the following are true:
 - 1) The **[local name]** property is **space**.
 - 2) The **[namespace name]** property is **http://www.w3.org/XML/1998/namespace**.

- 3) The **[normalized value]** property is **preserve**.
- ii) **EII** has an **[attributes]** property that contains an XML attribute information item for which all of the following are true:
 - 1) The **[local name]** property is **space**.
 - 2) The **[namespace name]** property is **http://www.w3.org/XML/1998/namespace**.
 - 3) The **[normalized value]** property is **default**.
- iii) **EII** is contained in the **[children]** property of a potentially whitespace-strippable XML element information item and **EII** does not have an **[attributes]** property that contains an XML attribute information item for which all of the following are true:
 - 1) The **[local name]** property is **space**.
 - 2) The **[namespace name]** property is **http://www.w3.org/XML/1998/namespace**.
 - 3) The **[normalized value]** property is **preserve**.
- b) For every potentially whitespace-strippable XML element information item **PWSEII** contained in **C**:
 - i) Let N be the cardinality of the **[children]** property of **PWSEII**. Let XII_i , $1 \text{ (one)} \leq i \leq N$, be the list of XML information items that is the **[children]** property of **PWSEII**.
 - ii) For every i between 1 (one) and N , if XII_i is an XML character information item, then:
 - 1) Let j be the least subscript less than or equal to i such that for all q between j and i , XII_q is an XML character information item.
 - 2) Let k be the greatest subscript greater than or equal to i such that for all q between i and k , XII_q is an XML character information item.

NOTE 82 — Thus the list XII_j, \dots, XII_k is the maximal sublist of XII_1, \dots, XII_N containing XII_i and consisting entirely of XML character information items. Such a maximal list of XML character information items is commonly called a “text node”.
 - 3) If for all q between j and k , XII_q is an XML character information item whose **[character code]** property is a whitespace character, then XII_q is marked for removal from **C**.
 - iii) For every i between 1 (one) and N , if XII_i is marked for removal from **C**, then XII_i is removed from **C**.
- c) Let N be the cardinality of the **[children]** property of **XRII**. Let XII_i , $1 \text{ (one)} \leq i \leq N$, be the list of XML information items that is the **[children]** property of **XRII**.
 - i) For every i between 1 (one) and N , if XII_i is an XML character information item, then:
 - 1) Let j be the least subscript less than or equal to i such that for all q between j and i , XII_q is an XML character information item.
 - 2) Let k be the greatest subscript greater than or equal to i such that for all q between i and k , XII_q is an XML character information item.

- 3) If for all q between j and k , XII_q is an XML character information item whose **[character code]** property is a whitespace character, then XII_q is marked for removal from C .
 - ii) For every i between 1 (one) and N , if XII_i is marked for removal from C , then XII_i is removed from C .
- 9) C is converted to an XQuery document node D (and its children) according to the rules of XQuery and XPath Data Model 3.1 section 6, "Nodes".
- 10) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives D as *XMLPARSE*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.19 Removing XQuery document nodes from an XQuery sequence

Function

Replace each XQuery document node in a sequence by the sequence of children of the XQuery document node.

Subclause Signature

"Removing XQuery document nodes from an XQuery sequence" [General Rules] (

Parameter: "SEQUENCE"

) Returns: "RESULT"

SEQUENCE — a sequence of XML document nodes.

RESULT — a sequence of XML element nodes resulting from the removal of XML document nodes.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let S be the *SEQUENCE* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *RESULT*.
- 2) Case:
 - a) If S is the null value, then let R be the null value.
 - b) Otherwise:
 - i) Let N be the number of XQuery items in S .
 - ii) Let I_j , 1 (one) $\leq j \leq N$, be an enumeration in order of the XQuery items in S .
 - iii) For each j , 1 (one) $\leq j \leq N$,
 - Case:
 - 1) If I_j is an XQuery document node, then let C_j be the XQuery sequence that is the **children** property of I_j .
 - 2) Otherwise, let C_j be I_j .
 - iv) Let R be the concatenation of the XQuery sequences C_j in order from $j = 1$ (one) through $j = N$.
- 3) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives R as *RESULT*.

10.19 Removing XQuery document nodes from an XQuery sequence

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.20 Constructing a copy of an XML value

Function

Construct a copy of an XML value.

Subclause Signature

"Constructing a copy of an XML value" [General Rules] (
 Parameter: "VALUE"
) Returns: "COPY"

VALUE — a value of an XML type.

COPY — a value of an XML type that is a copy of the original value.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let V be the *VALUE* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *COPY*.
- 2) Let N be the number of XQuery items in V .
- 3) Let I_j , $1 \text{ (one)} \leq j \leq N$, be an enumeration in order of the XQuery items in V .
- 4) For each j , $1 \text{ (one)} \leq j \leq N$, let C_j be defined as follows.
 Case:
 - a) If I_j is an XQuery atomic value, then let C_j be I_j .
 - b) Otherwise, let C_j be a value of XML type that is equivalent to I_j except that the **parent** property (if any) of C_j is **empty** and the XQuery node identity of C_j is different from the XQuery node identity of I_j .
- 5) Let R be the XQuery sequence enumerated by C_j , $1 \text{ (one)} \leq j \leq N$.
- 6) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives R as *COPY*.

Conformance Rules

None.

10.21 Constructing an unvalidated XQuery document node

Function

Convert an XQuery document node to a value of type XML(CONTENT(UNTYPED)).

Subclause Signature

"Constructing an unvalidated XQuery document node" [General Rules] (
 Parameter: "XQUERYDOCNODE"
) Returns: "UNVALIDATEDDOCNODE"

XQUERYDOCNODE — an XML document node.

UNVALIDATEDDOCNODE — an unvalidated XML document node.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let ***XDN*** be the *XQUERYDOCNODE* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *UNVALIDATEDDOCNODE*.
- 2) Let ***R*** be an XQuery document node that is equivalent to ***XDN*** except:
 - a) The XQuery node identity of ***R*** is different from the XQuery node identity of ***XDN***.
 - b) The **type-name** property of every XQuery element node in the XQuery tree rooted by ***R*** is ***xs:untyped***.
 - c) The **nilled** property of every XQuery element node in the XQuery tree rooted by ***R*** is **false**.
 - d) The **type-name** property of every XQuery attribute node in the XQuery tree rooted by ***R*** is ***xs:untypedAtomic***.
- 3) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives ***R*** as *UNVALIDATEDDOCNODE*.

Conformance Rules

None.

10.22 Creation of an XQuery expression context

Function

Create an XQuery expression context.

Subclause Signature

"Creation of an XQuery expression context" [Syntax Rules] (
 Parameter: "NONTERMINAL"
) Returns: "STATICCONTEXT"

NONTERMINAL — the SQL null value or a BNF non-terminal symbol that is either an <XML query>, <XML element>, or <XML forest>.

STATICCONTEXT — an XML Query static context.

"Creation of an XQuery expression context" [General Rules] () Returns: "DYNAMICCONTEXT"

DYNAMICCONTEXT — an XQuery dynamic context.

Syntax Rules

- 1) Let *BNF* be the *NONTERMINAL* in an application of the Syntax Rules of this Subclause. The result of the application of this Subclause is returned as *STATICCONTEXT*.
- 2) Let *xsc* be an XQuery static context, created as follows:
 - a) *xsc* is initially created as defined by XQuery 3.1: an XML Query Language Appendix C.1, "Static context components", as specified in the table titled "Static context components" in the column headed "Default initial value".
 - b) The **statically known namespaces** component of *xsc* is augmented with the XML namespace prefix/URL pair consisting of


```
('sqlxml', "http://standards.iso.org/iso/9075/2003/sqlxml")
```
 - c) *xsc* is modified with implementation-defined (IV238) values, as permitted by XQuery 3.1: an XML Query Language Appendix C.1, "Static context components", in the table titled "Static context components", in the column headed "Can be overwritten or augmented by implementation?".
 - d) If *BNF* is specified, then:
 - i) The **statically known namespaces** component of *xsc* is overwritten or augmented with certain namespaces, as follows:
 - 1) For each <XML namespace prefix> *XNP* contained in an <XML namespace declaration> whose scope contains *BNF*, let *XND* be the <XML namespace declaration> with innermost scope containing *BNF*, and let *XNURI* be the <XML namespace URI> of the <XML regular namespace declaration item> containing *XNP* in *XND*.
 - 2) The pair (*XNP*, *XNURI*) is placed in the **statically known namespaces** component of *xsc*, either,

Case:

- A) If *XNP* is previously defined, then overwriting the previously defined namespace.
- B) Otherwise, augmenting the **statically known namespaces** component of ***XSC***.

NOTE 83 — The scope of <XML namespace declaration>s is defined in the various Subclauses that reference that non-terminal symbol, such as Subclause 6.15, “<XML element>”, and Subclause 7.2, “<query expression>”.

- ii) If there is an <XML namespace declaration> whose scope includes *BNF* and that contains an <XML default namespace declaration item>, then let *XND* be the innermost such <XML namespace declaration>.

Case:

- 1) If *XND* contains an <XML default namespace declaration item> of the form “DEFAULT <XML namespace URI>”, then let *XNURI* be that <XML namespace URI>.

Case:

- A) If *XNURI* is the zero-length string, then the **default element/type namespace** component of ***XSC*** is set to empty.
- B) Otherwise, the **default element/type namespace** component of ***XSC*** is set to *XNURI*.

- 2) If *XND* contains an <XML default namespace declaration item> of the form “NO DEFAULT”, then the **default element/type namespace** component of ***XSC*** is set to empty.

- e) The in-scope schema definitions component of ***XSC*** (i.e., the in-scope schema types, the in-scope element declarations, and the in-scope attribute declarations) consists of an implementation-defined (IV204) collection of registered XML schemas for which the current user has USAGE privilege.

- 3) Evaluation of the Syntax Rules is terminated and control is returned to the invoking Subclause, which receives ***XSC*** as *STATICCONTEXT*.

Access Rules

None.

General Rules

- 1) The General Rules of this Subclause are applied without any symbolic arguments. The result of the application of this Subclause is returned as *DYNAMICCONTEXT*.
- 2) Let ***XDC*** be an XQuery dynamic context, created as follows:
 - a) ***XDC*** is initially created as defined by XQuery 3.1: an XML Query Language Appendix C.2, “Dynamic context components”, as specified in the table titled “Dynamic context components”, in the column headed “Default initial value”.
 - b) ***XDC*** is modified with implementation-defined (IV238) values, as permitted by XQuery 3.1: an XML Query Language Appendix C.2, “Dynamic context components”, in the table titled

10.22 Creation of an XQuery expression context

“Dynamic context components”, in the column headed “Can be overwritten or augmented by implementation?”.

- 3) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *XDC* as *DYNAMICCONTEXT*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

10.23 Determination of an XQuery formal type notation

Function

Determine the XQuery formal type notation of an XQuery variable in the XQuery static context.

Subclause Signature

"Determination of an XQuery formal type notation" [Syntax Rules] (
Parameter: "SOURCE",
Parameter: "CONTEXT"
) Returns: "FORMALTYPE"

SOURCE — an SQL site (such as a column reference or value expression)

CONTEXT — a Boolean value, either *True* or *False*.

FORMALTYPE — an XQuery formal type notation.

Syntax Rules

- 1) Let *S* be the *SOURCE* and let *C* be the *CONTEXT* in an application of the Syntax Rules of this Subclause. The result of the application of this Subclause is returned as *FORMALTYPE*.
- 2) Let *SD* be the declared type of *S*.
- 3) Case:
 - a) If *C* is *True*, then let **SUFFIX** be the zero-length string.
 - b) If *SD* is XML(SEQUENCE), then let **SUFFIX** be "*".
 - c) If *S* is a column reference that references a known not null column or a <value expression> for which the SQL-implementation can deduce via an implementation-defined (IE013) rule that the value of *S* cannot be null, then let **SUFFIX** be the zero-length string.
 - d) Otherwise, let **SUFFIX** be "?".
- 4) If *SD* is XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then:
 - a) Let **XS** be the XML schema identified by the registered XML schema descriptor included in the XML type descriptor of *SD*.
 - b) Case:
 - i) If the XML type descriptor of *SD* includes the XML namespace URI and the XML NCName of a global element declaration schema component **GE**, then let **ET** be the XML QName of **GE**.
 - ii) If the XML type descriptor of *SD* includes the XML namespace URI **NS**, then let *N* be the number of global element declaration schema components included in **NS** and let **ET_{*i*}**, 1 (one) ≤ *i* ≤ *N*, be the XML QNames of those global element declaration schema components.
 - iii) Otherwise, let *N* be the number of global element declaration schema components included in **XS** and let **ET_{*i*}**, 1 (one) ≤ *i* ≤ *N*, be the XML QNames of those global element declaration schema components.

10.23 Determination of an XQuery formal type notation

5) Let **XFTN** be the XQuery formal type notation determined as follows.

Case:

a) If *SD* is XML(DOCUMENT(UNTYPED)), then let **XFTN** be

```
document { (comment | processing-instruction)*,
           element * of type xs:untyped,
           (comment | processing-instruction)* } SUFFIX
```

b) If *SD* is XML(DOCUMENT(ANY)), then let **XFTN** be

```
document { (comment | processing-instruction)*,
           element * of type xs:anyType,
           (comment | processing-instruction)* } SUFFIX
```

c) If *SD* is XML(DOCUMENT(XMLSCHEMA)), then

Case:

i) If the type descriptor of *SD* includes the XML namespace URI and the XML NCName of a global element declaration schema component, then let **XFTN** be

```
document { (comment | processing-instruction)*,
           element * of type ET,
           (comment | processing-instruction)* } SUFFIX
```

ii) Otherwise, let **XFTN** be

```
document { (comment | processing-instruction)*,
           (element * of type ET1 | element * of type ET2 | ... |
           element * of type ETN,
           (comment | processing-instruction)* } SUFFIX
```

d) If *SD* is XML(CONTENT(UNTYPED)), then let **XFTN** be

```
document { ( element * of type xs:untyped | comment
           | processing-instruction | text)* } SUFFIX
```

e) If *SD* is XML(CONTENT(ANY)), then let **XFTN** be

```
document { ( element * of type xs:anyType | comment
           | processing-instruction | text)* } SUFFIX
```

f) If *SD* is XML(CONTENT(XMLSCHEMA)), then

Case:

i) If the type descriptor of *SD* includes the XML namespace URI and the XML NCName of a global element declaration schema component, then let **XFTN** be

```
document { ( element * of type ET |
           comment | processing-instruction)* } SUFFIX
```

ii) Otherwise, let **XFTN** be

```
document { ( element * of type ET1 | element * of type ET2 | ... | element
           * of type ETN |
           comment | processing-instruction)* } SUFFIX
```

g) If *SD* is XML(SEQUENCE), then let **XFTN** be

```
( element * of type xs:anyType | attribute of type xs:anySimpleType |  
text | comment | processing-instruction | xs:anyAtomicType |  
document { ( element * of type xs:anyType | comment |  
processing-instruction | text )* } ) SUFFIX
```

- h) If *SD* is an SQL predefined type, then let *ENC* be an indication that the binary strings are to be encoded in hex; the General Rules of Subclause 9.5, “Mapping SQL data types to XML schema data types”, are applied with *SD* as *SQLTYPE*, *ENC* as *ENCODING*, and “absent” as *NULLS*; let *XMLT* be the *SCHEMA TYPE* returned from the application of those General Rules. Let *PT* be the XML schema primitive type from which *XMLT* is derived.

Case:

- i) If *SD* is a year-month interval, then let *XFTN* be “*xs:yearMonthDuration SUFFIX*”.
 - ii) If *SD* is a day-time interval, then let *XFTN* be “*xs:dayTimeDuration SUFFIX*”.
 - iii) If *SD* is an exact numeric type with scale 0 (zero), then let *XFTN* be “*xs:integer SUFFIX*”.
 - iv) Otherwise, let *XFTN* be “*PT SUFFIX*”.
- 6) Let *XFT* be *XFTN* or an implementation-defined (IV207) XML schema subtype of *XFTN* that describes *S*
- 7) Evaluation of the Syntax Rules is terminated and control is returned to the invoking Subclause, which receives *XFT* as *FORMALTYPE*.

Access Rules

None.

General Rules

None.

Conformance Rules

None.

10.24 Validating an XQuery document or element node

Function

Validate an XQuery document or an XQuery element node.

Subclause Signature

"Validating an XQuery document or element node" [General Rules] (
 Parameter: "ITEM",
 Parameter: "SCHEMA"
) Returns: "STATUS" and "RESULT"

ITEM — an XQuery item.

SCHEMA — an XML schema.

STATUS — either SUCCESS or FAILURE.

RESULT — either the SQL null value or a strictly validated XQuery sequence.

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Let v be the *ITEM* and let *SXS* be the *SCHEMA* in an application of the General Rules of this Subclause. The result of the application of this Subclause is returned as *STATUS* and *RESULT*.
- 2) The Syntax Rules of Subclause 10.22, "Creation of an XQuery expression context", are applied with the null value as *NONTERMINAL*; let *xsc* be the *STATICCONTEXT* returned from the application of those Syntax Rules.
 NOTE 84 — *xsc* is an XQuery static context.
- 3) The General Rules of Subclause 10.22, "Creation of an XQuery expression context", are applied; let *xdc* be the *DYNAMICCONTEXT* returned from the application of those General Rules.
 NOTE 85 — *xdc* is an XQuery dynamic context.
- 4) *SXS* is included in the in-scope schema definitions component of *xsc*.
- 5) *xsc* and *xdc* are augmented with an XQuery variable $\$SEQ$, whose XQuery formal type notation is

```
(element of type xs:anyType | attribute of type xs:anySimpleType |
text | comment | processing-instruction | xs:anyAtomicType |
document-node { ( element of type xs:anyType | comment |
processing-instruction | text )* } )*
```

and whose value is v .

10.24 Validating an XQuery document or element node

- 6) Case:
- a) If the SQL-implementation supports Feature X211, “XML 1.1 support”, then let **ET** be the result of an XQuery evaluation with XML 1.1 lexical rules, using **XSC** and **XDC** as the XQuery expression context, of the XQuery expression
- ```
validate strict { $SEQ }
```
- If an XQuery error occurs during the evaluation, then let *STAT* be FAILURE; otherwise, let *STAT* be SUCCESS.
- b) Otherwise, let **ET** be the result of an XQuery evaluation with XML 1.0 lexical rules, using **XSC** and **XDC** as the XQuery expression context, of the XQuery expression
- ```
validate strict { $SEQ }
```
- If an XQuery error occurs during the evaluation, then let *STAT* be FAILURE; otherwise, let *STAT* be SUCCESS.
- 7) If *STAT* is FAILURE, then let **ET** be the null value.
- 8) Evaluation of the General Rules is terminated and control is returned to the invoking Subclause, which receives *STAT* as *STATUS* and **ET** as *RESULT*.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

11 Additional common elements

This Clause modifies Clause 10, “Additional common elements”, in ISO/IEC 9075-2.

11.1 <aggregate function>

This Subclause modifies Subclause 10.9, “<aggregate function>”, in ISO/IEC 9075-2.

Function

Specify a value computed from a collection of rows.

Format

```
<aggregate function> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <XML aggregate>

<XML aggregate> ::=
    XMLAGG <left paren> <XML value expression>
        [ ORDER BY <sort specification list> ]
        [ <XML returning clause> ]
    <right paren>
```

Syntax Rules

- 1) Insert after the last SR: If <XML aggregate> is specified, then:
 - a) If <XML returning clause> is not specified, then it is implementation-defined (ID208) whether RETURNING CONTENT or RETURNING SEQUENCE is implicit.
 - b) Case:
 - i) If RETURNING CONTENT is specified or implied, then

Case:

 - 1) If the declared type of the <XML value expression> is XML(DOCUMENT(UNTYPED)) or XML(CONTENT(UNTYPED)), then the declared type of <XML aggregate> is XML(CONTENT(UNTYPED)).
 - 2) If the declared type of the <XML value expression> is XML(DOCUMENT(XMLSCHEMA)) or XML(CONTENT(XMLSCHEMA)), then let *XVT* be the declared type of <XML value expression>, let *XS* be the registered XML schema descriptor included in the XML type descriptor of *XVT*, let *NS* be the XML namespace URI included in the XML type descriptor of *XVT*, if any, and let *EN* be the XML NCName of a global element declaration schema component included in the XML type descriptor of *XVT*, if any. The declared type of <XML aggregate> is XML(CONTENT(XMLSCHEMA)) whose XML type descriptor includes *XS*, if *NS* is defined, then *NS*, and, if *EN* is defined, then *EN*.
 - 3) Otherwise, the declared type of <XML aggregate> is XML(CONTENT(ANY)).

- ii) Otherwise, the declared type of <XML aggregate> is XML(SEQUENCE).
- c) Let *XVE* be the <XML value expression>.
- d) If <sort specification list> is specified, then let *SSL* be “ORDER BY <sort specification list>”; otherwise, let *SSL* be the zero-length string.
- e) If RETURNING CONTENT is specified or implied, then
 - i) Let *RT* be the declared type of <XML aggregate>.
 - ii) <XML aggregate> is equivalent to

```
CAST (
  XMLDOCUMENT (
    XMLAGG (
      XVE SSL
      RETURNING SEQUENCE )
    RETURNING CONTENT )
  AS RT )
```

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR 3)b): If the most specific type of the result of *AF* is an XML type, then an exception condition is raised: *data exception — XML value overflow (2200R)*.
- 2) Insert after the last GR: If <XML aggregate> is specified, then:
 - a) If <sort specification list> is specified, then let *K* be the number of <sort key>s; otherwise, let *K* be 0 (zero).
 - b) Let *TXA* be the table of *K+1* columns obtained by applying <XML value expression> to each row of *T1* to obtain the first column of *TXA*, and, for all *i* between 1 (one) and *K*, applying the <value expression> simply contained in the *i*-th <sort key> to each row of *T1* to obtain the (*i+1*)-th column of *TXA*.
 - c) Every row of *TXA* in which the value of the first column is the null value is removed from *TXA*.
 - d) Let *TXA* be ordered according to the values of the <sort key>s found in the second through (*K+1*)-th columns of *TXA*. If *K* is 0 (zero), then the ordering of *TXA* is implementation-dependent (UA032). Let *N* be the number of rows in *TXA*. Let *R_i*, 1 (one) ≤ *i* ≤ *N*, be the rows of *TXA* according to the ordering of *TXA*.
 - e) Case:
 - i) If *TXA* is empty, then the result of <XML aggregate> is the null value.
 - ii) Otherwise:
 - 1) Let *V₁* be the value of the first column of *R₁*.
 - 2) For all *i*, 2 ≤ *i* ≤ *N*, the General Rules of Subclause 10.16, “Concatenation of two XML values”, are applied with *V_{i-1}* as *FIRSTVAL* and the value of the first column of *R_i* as *SECONDDVAL*; let *V_i* be the *CONCAT* returned from the application of those General Rules.

- 3) The result is V_N .

Conformance Rules

- 1) Insert after [the last CR](#): Without Feature X034, “XMLAgg”, conforming SQL language shall not contain an <XML aggregate>.
- 2) Insert after [the last CR](#): Without Feature X035, “XMLAgg: ORDER BY option”, conforming SQL language shall not contain an <XML aggregate> that contains a <sort specification list>.
- 3) Insert after [the last CR](#): Without Feature X241, “RETURNING CONTENT in XML publishing”, in conforming SQL language, an <XML aggregate> shall not specify an <XML returning clause> that is RETURNING CONTENT.
- 4) Insert after [the last CR](#): Without Feature X242, “RETURNING SEQUENCE in XML publishing”, in conforming SQL language, an <XML aggregate> shall not specify an <XML returning clause> that is RETURNING SEQUENCE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

11.2 <XML lexically scoped options>

Function

Declare one or more XML namespaces and the encoding to use for binary strings.

Format

```
<XML lexically scoped options> ::=
  <XML lexically scoped option> [ <comma> <XML lexically scoped option> ]

<XML lexically scoped option> ::=
  <XML namespace declaration>
  | <XML binary encoding>

<XML namespace declaration> ::=
  XMLNAMESPACES <left paren> <XML namespace declaration item>
  [ { <comma> <XML namespace declaration item> }... ] <right paren>

<XML namespace declaration item> ::=
  <XML regular namespace declaration item>
  | <XML default namespace declaration item>

<XML namespace prefix> ::=
  <identifier>

<XML namespace URI> ::=
  <character string literal>

<XML regular namespace declaration item> ::=
  <XML namespace URI> AS <XML namespace prefix>

<XML default namespace declaration item> ::=
  DEFAULT <XML namespace URI>
  | NO DEFAULT

<XML binary encoding> ::=
  XMLBINARY [ USING ] { BASE64 | HEX }
```

Syntax Rules

- 1) An <XML lexically scoped options> shall contain at most one <XML namespace declaration>, and at most one <XML binary encoding>.
- 2) <XML namespace declaration> shall contain at most one <XML default namespace declaration item>.
- 3) Each <XML namespace prefix> shall be an XML 1.1 NCName.
- 4) No two <XML namespace prefix>es shall be equivalent.
- 5) No <XML namespace prefix> shall be equivalent to `xml` or `xmlns`.
- 6) No <XML namespace URI> shall be identical, as defined in [XML Namespaces](#), to `http://www.w3.org/2000/xmlns/` or to `http://www.w3.org/XML/1998/namespace`.
- 7) The value of an <XML namespace URI> contained in an <XML regular namespace declaration item> shall not be a zero-length string.

Access Rules

None.

General Rules

None.

Conformance Rules

- 1) Without Feature X211, “XML 1.1 support”, in conforming SQL language, each <XML namespace prefix> shall be an XML 1.0 NCName.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

11.3 <XML returning clause>

Function

Specify whether the declared type of certain <XML value function>s is XML(SEQUENCE) or some other XML type.

Format

```
<XML returning clause> ::=  
  RETURNING { CONTENT | SEQUENCE }
```

Syntax Rules

None.

Access Rules

None.

General Rules

None.

Conformance Rules

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

11.4 <XML passing mechanism>

Function

Specify the semantics for assigning or casting an XML value.

Format

```
<XML passing mechanism> ::=  
  BY REF  
  | BY VALUE
```

Syntax Rules

None.

Access Rules

None.

General Rules

None.

Conformance Rules

- 1) Without Feature X221, “XML passing mechanism BY VALUE”, conforming SQL language shall not contain an <XML passing mechanism> that is BY VALUE.
- 2) Without Feature X222, “XML passing mechanism BY REF”, conforming SQL language shall not contain an <XML passing mechanism> that is BY REF.

11.5 <XML valid according to clause>

Function

Indicate a registered XML schema, and (optionally) an XML namespace of that registered XML schema, and (optionally) a global element declaration schema component of that registered XML schema.

Format

```
<XML valid according to clause> ::=
  ACCORDING TO XMLSCHEMA <XML valid according to what>
    [ <XML valid element clause> ]

<XML valid according to what> ::=
  <XML valid according to URI>
  | <XML valid according to identifier>

<XML valid according to URI> ::=
  URI <XML valid target namespace URI> [ <XML valid schema location> ]
  | NO NAMESPACE [ <XML valid schema location> ]

<XML valid target namespace URI> ::=
  <XML URI>

<XML URI> ::=
  <character string literal>

<XML valid schema location> ::=
  LOCATION <XML valid schema location URI>

<XML valid schema location URI> ::=
  <XML URI>

<XML valid according to identifier> ::=
  ID <registered XML schema name>

<XML valid element clause> ::=
  <XML valid element name specification>
  | <XML valid element namespace specification>
    [ <XML valid element name specification> ]

<XML valid element name specification> ::=
  ELEMENT <XML valid element name>

<XML valid element namespace specification> ::=
  NO NAMESPACE
  | NAMESPACE <XML valid element namespace URI>

<XML valid element namespace URI> ::=
  <XML URI>

<XML valid element name> ::=
  <identifier>
```

Syntax Rules

- 1) If <XML valid according to identifier> is specified, then the <registered XML schema name> shall identify a registered XML schema *RXS*. Let *NSURI* be the target namespace URI of *RXS*.
- 2) If <XML valid according to URI> is specified, then:

11.5 <XML valid according to clause>

- a) Case:
- i) If NO NAMESPACE is specified, then let *NSURI* be the zero-length string.
 - ii) Otherwise, let *NSURI* be the <XML valid target namespace URI>.
- b) Case:
- i) If the SQL-implementation identifies registered XML schemas by the combination of their target namespace URIs and schema location URIs, then

Case:

 - 1) If <XML valid schema location> is specified, then there shall exist a registered XML schema whose target namespace URI is identical to *NSURI*, as defined by [XML Namespaces](#), and whose schema location URI equals <XML valid schema location URI> *XVSL* according to the UCS_BASIC collation.

Case:

 - A) If there exists more than one such registered XML schema, then let *XSDN* be a <registered XML schema name> chosen using a deterministic implementation-defined ([IW062](#)) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user, the same <registered XML schema name> will be chosen.
 - B) Otherwise, let *XSD* be the registered XML schema descriptor that includes *NSURI* as its target namespace URI and *XVSL* as its schema location URI. Let *XSDN* be the <registered XML schema name> included in *XSD*.
 - 2) Otherwise, a <registered XML schema name> *XSDN* is chosen using a deterministic implementation-defined ([IW062](#)) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user, the same <registered XML schema name> will be chosen.

NOTE 86 — This does not say that the algorithm must choose a <registered XML schema name> that identifies a registered XML schema. One possibility for the implementation-defined algorithm is to choose a <registered XML schema name> that does not identify a registered XML schema, resulting in a syntax error.
 - ii) Otherwise, there shall exist a registered XML schema whose target namespace URI is *NSURI*.

Case:

 - 1) If there exists more than one such registered XML schema, then let *XSDN* be a <registered XML schema name> chosen using a deterministic implementation-defined ([IW062](#)) algorithm that is repeatable, in the sense that if the algorithm is re-evaluated with the same collection of registered XML schemas that are accessible to the user, the same <registered XML schema name> will be chosen.
 - 2) Otherwise, let *XSD* be the registered XML schema descriptor that includes *NSURI* as its target namespace URI. Let *XSDN* be the <registered XML schema name> included in *XSD*.
- c) *XSDN* shall identify a registered XML schema *RXS*.
- 3) *RXS* is the *indicated registered XML schema*.
 - 4) If <XML valid element clause> is specified, then:

- a) Case:
 - i) If <XML valid element namespace specification> is specified, then
Case:
 - 1) If NO NAMESPACE is specified, then let *ENSURI* be the zero-length string.
 - 2) Otherwise, let *ENSURI* be <XML valid element namespace URI>.
 - ii) Otherwise, let *ENSURI* be *NSURI*.
- b) It is implementation-defined (IA126) whether *RXS* shall have a namespace, among its unordered collection of namespaces, whose namespace URI is identical to *ENSURI*, as defined by XML Namespaces.
- c) *ENSURI* is the indicated XML namespace.
- d) If <XML valid element name specification> is specified, then:
 - i) Let *EN* be the <XML valid element name>.
 - ii) Let *GEDSC* be the global element declaration schema component whose namespace URI is identical to *ENSURI*, as defined by XML Namespaces, and whose XML NCName is *EN*. *GEDSC* is the indicated global element declaration schema component.
 - iii) It is implementation-defined (IA127) whether *RXS* shall have a global element declaration schema component whose namespace URI is identical to *ENSURI*, as defined by XML Namespaces, and whose XML NCName is *EN*.

Access Rules

- 1) Case:
 - a) If the <XML valid according to clause> is contained, without an intervening <SQL routine spec> that specifies SQL SECURITY INVOKER, in an <SQL schema statement>, then the applicable privileges of the <authorization identifier> that owns the containing schema shall include USAGE on *RXS*.
 - b) Otherwise, the current privileges shall include USAGE on *RXS*.

General Rules

- 1) If <XML valid element clause> is specified, then:
 - a) If *RXS* does not have a namespace, among its unordered collection of namespaces, whose namespace URI is identical to *ENSURI*, as defined by XML Namespaces, then an exception condition is raised: *data exception — element namespace not declared (2201M)*.
 - b) If <XML valid element name specification> is specified and *RXS* does not have a global element declaration schema component whose namespace URI is identical to *ENSURI*, as defined by XML Namespaces, and whose XML NCName is *EN*, then an exception condition is raised: *data exception — global element not declared (2201N)*.

Conformance Rules

None.

12 Schema definition and manipulation

This Clause modifies Clause 11, “Schema definition and manipulation”, in ISO/IEC 9075-2.

12.1 <column definition>

This Subclause modifies Subclause 11.4, “<column definition>”, in ISO/IEC 9075-2.

Function

Define a column of a base table.

Format

```
<generation expression> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <left paren> WITH <XML lexically scoped options>
      <value expression> <right paren>
```

Syntax Rules

- 1) Insert after the last SR: The scope of each <XML namespace declaration item> contained in the <XML lexically scoped options> is the <generation expression>.
- 2) Insert after the last SR: The scope of an <XML binary encoding> contained in the <XML lexically scoped options> is the <generation expression>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X083, “XML namespace declarations in DDL”, in conforming SQL language, a <generation expression> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) Insert after the last CR: Without Feature X133, “XMLBINARY clause in DDL”, in conforming SQL language, a <generation expression> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.
- 3) Insert after the last CR: Without Feature X016, “Persistent XML values”, conforming SQL language shall not contain a <column definition> whose declared type is based on either an XML type or a distinct type whose source type is an XML type.

- 4) **Insert after the last CR:** Without Feature X251, “Persistent XML values of XML(DOCUMENT(UNTYPED)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(DOCUMENT(UNTYPED)) type or a distinct type whose source type is the XML(DOCUMENT(UNTYPED)) type.
- 5) **Insert after the last CR:** Without Feature X252, “Persistent XML values of XML(DOCUMENT(ANY)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(DOCUMENT(ANY)) type or a distinct type whose source type is the XML(DOCUMENT(ANY)) type.
- 6) **Insert after the last CR:** Without Feature X256, “Persistent XML values of XML(DOCUMENT(XMLSCHEMA)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(DOCUMENT(XMLSCHEMA)) type or a distinct type whose source type is the XML(DOCUMENT(XMLSCHEMA)) type.
- 7) **Insert after the last CR:** Without Feature X253, “Persistent XML values of XML(CONTENT(UNTYPED)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(CONTENT(UNTYPED)) type or a distinct type whose source type is the XML(CONTENT(UNTYPED)) type.
- 8) **Insert after the last CR:** Without Feature X254, “Persistent XML values of XML(CONTENT(ANY)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(CONTENT(ANY)) type or a distinct type whose source type is the XML(CONTENT(ANY)) type.
- 9) **Insert after the last CR:** Without Feature X257, “Persistent XML values of XML(CONTENT(XMLSCHEMA)) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(CONTENT(XMLSCHEMA)) type or a distinct type whose source type is the XML(CONTENT(XMLSCHEMA)) type.
- 10) **Insert after the last CR:** Without Feature X255, “Persistent XML values of XML(SEQUENCE) type”, conforming SQL language shall not contain a <column definition> whose declared type is based on either the XML(SEQUENCE) type or a distinct type whose source type is the XML(SEQUENCE) type.

12.2 <check constraint definition>

This Subclause modifies Subclause 11.9, “<check constraint definition>”, in ISO/IEC 9075-2.

Function

Specify a condition for the SQL-data.

Format

```
<check constraint definition> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | CHECK <left paren> WITH <XML lexically scoped options>  
      <search condition> <right paren>
```

Syntax Rules

- 1) **Insert after the last SR:** The scope of each <XML namespace declaration item> contained in the <XML lexically scoped options> is the <check constraint definition>.
- 2) **Insert after the last SR:** The scope of an <XML binary encoding> contained in the <XML lexically scoped options> is the <check constraint definition>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X083, “XML namespace declarations in DDL”, in conforming SQL language, a <check constraint definition> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X133, “XMLBINARY clause in DDL”, in conforming SQL language, a <check constraint definition> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

12.3 <alter column data type clause>

This Subclause modifies Subclause 11.19, “<alter column data type clause>”, in ISO/IEC 9075-2.

Function

Change the declared type of a column.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR 15)j): If *DTC* is an XML type, then:
 - a) Let *PDTC* be the primary XML type modifier of *DTC*, let *SDTC* be the secondary XML type modifier of *DTC* (if any), let *SCHDTC* be the registered XML schema of *DTC* (if any), let *NSDTC* be the XML namespace URI of *DTC* (if any), and let *EDTC* be the XML NCName of the global element of *DTC* (if any).
 - b) Let *PD* be the primary XML type modifier of *D*, let *SD* be the secondary XML type modifier of *D* (if any), let *SCHD* be the registered XML schema of *D* (if any), let *NSD* be the XML namespace URI of *D* (if any), and let *ED* be the XML NCName of the global element of *D* (if any).
 - c) If *PDTC* is CONTENT, then *PD* shall be CONTENT or SEQUENCE.
 - d) If *SDTC* is UNTYPED, then *SD* shall be UNTYPED or ANY.
 - e) If *SDTC* is XMLSCHEMA, then *SD* shall be XMLSCHEMA or ANY.
 - f) If *SCHDTC* is defined, then *SCHD* shall be either identical to *SCHDTC* or not defined.
 - g) If *NSDTC* is defined, then *NSD* shall be either identical to *NSDTC* as defined by XML Namespaces or not defined.
 - h) If *EDTC* is defined, then *ED* shall be either equivalent to *EDTC* or not defined.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after CR 1): Without Feature X410, “Alter column data type: XML type”, conforming SQL language shall not specify an <alter column data type clause> that contains a <data type> that specifies an XML type.

12.4 <view definition>

This Subclause modifies Subclause 11.32, “<view definition>”, in ISO/IEC 9075-2.

Function

Define a viewed table.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X016, “Persistent XML values”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either an XML type or a distinct type whose source type is an XML type.
- 2) **Insert after the last CR:** Without Feature X251, “Persistent XML values of XML(DOCUMENT(UNTYPED)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(DOCUMENT(UNTYPED)) type or a distinct type whose source type is the XML(DOCUMENT(UNTYPED)) type.
- 3) **Insert after the last CR:** Without Feature X252, “Persistent XML values of XML(DOCUMENT(ANY)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(DOCUMENT(ANY)) type or a distinct type whose source type is the XML(DOCUMENT(ANY)) type.
- 4) **Insert after the last CR:** Without Feature X256, “Persistent XML values of XML(DOCUMENT(XMLSCHEMA)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(DOCUMENT(XMLSCHEMA)) type or a distinct type whose source type is the XML(DOCUMENT(XMLSCHEMA)) type.
- 5) **Insert after the last CR:** Without Feature X253, “Persistent XML values of XML(CONTENT(UNTYPED)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(CONTENT(UNTYPED)) type or a distinct type whose source type is the XML(CONTENT(UNTYPED)) type.
- 6) **Insert after the last CR:** Without Feature X254, “Persistent XML values of XML(CONTENT(ANY)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose

declared type is based on either the XML(CONTENT(ANY)) type or a distinct type whose source type is the XML(CONTENT(ANY)) type.

- 7) Insert after [the last CR](#): Without Feature X257, “Persistent XML values of XML(CONTENT(XMLSCHEMA)) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(CONTENT(XMLSCHEMA)) type or a distinct type whose source type is the XML(CONTENT(XMLSCHEMA)) type.
- 8) Insert after [the last CR](#): Without Feature X255, “Persistent XML values of XML(SEQUENCE) type”, conforming SQL language shall not contain a <view definition> that defines a column whose declared type is based on either the XML(SEQUENCE) type or a distinct type whose source type is the XML(SEQUENCE) type.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

12.5 <assertion definition>

This Subclause modifies Subclause 11.47, “<assertion definition>”, in ISO/IEC 9075-2.

Function

Specify an integrity constraint.

Format

```
<assertion definition> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | CREATE ASSERTION <constraint name>  
        CHECK <left paren> WITH <XML lexically scoped options>  
        <search condition> <right paren>  
        [ <constraint characteristics> ]
```

Syntax Rules

- 1) **Insert after the last SR:** The scope of each <XML namespace declaration item> contained in the <XML lexically scoped options> is the <assertion definition>.
- 2) **Insert after the last SR:** The scope of an <XML binary encoding> contained in the <XML lexically scoped options> is the <assertion definition>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X083, “XML namespace declarations in DDL”, in conforming SQL language, an <assertion definition> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X133, “XMLBINARY clause in DDL”, in conforming SQL language, an <assertion definition> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

12.6 <user-defined type definition>

This Subclause modifies Subclause 11.51, “<user-defined type definition>”, in ISO/IEC 9075-2.

Function

Define a user-defined type.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X013, “Distinct types of XML type”, conforming SQL language shall not contain a <representation> that is a <predefined type> that is an XML type.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

12.7 <attribute definition>

This Subclause modifies Subclause 11.52, “<attribute definition>”, in ISO/IEC 9075-2.

Function

Define an attribute of a structured type.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X014, “Attributes of XML type”, conforming SQL language shall not contain an <attribute definition> that contains a <data type> that is based on either an XML type or a distinct type whose source type is an XML type.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

12.8 <SQL-invoked routine>

This Subclause modifies Subclause 11.60, “<SQL-invoked routine>”, in ISO/IEC 9075-2.

Function

Define an SQL-invoked routine.

Format

```
<SQL parameter declaration> ::=
    !! All alternatives from ISO/IEC 9075-2
    [ [ <parameter mode> ]
      [ <SQL parameter name> ]
      <parameter type>
      [ RESULT ]
      [ DEFAULT <parameter default> ]
      <XML passing mechanism>

<parameter type> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <data type>
      <document or content> <string type option>

<returns clause> ::=
    !! All alternatives from ISO/IEC 9075-2
    | RETURNS <returns type> <XML passing mechanism>

<returns data type> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <data type>
      <document or content> <string type option>

<string type option> ::=
    AS <character string type>
```

Syntax Rules

- 1) **Insert before SR 9)y):** Case:
 - a) If the <data type> immediately contained in a <parameter type> or <returns data type> is an XML type and R is an external routine, then <document or content> and <string type option> shall be specified.
 - b) Otherwise, <document or content> and <string type option> shall not be specified.
- 2) **Insert before SR 9)y):** If the <data type> immediately contained in a <returns data type> that is immediately contained in a <returns type> RT is an XML type, then RT shall not contain a <result cast>.
- 3) **Insert after SR 24)d)iii)1)A):** If the <parameter type> T_i simply contained in the i -th <SQL parameter declaration> is an XML type, then:
 - a) Let XDT be the data type identified by the <character string type> contained in <string type option> immediately contained in T_i . XDT is the *associated string type* of P_i .
 - b) Let XO be the <document or content> immediately contained in T_i . XO is the *associated XML option* of P_i .

- c) The i -th effective SQL parameter list entry is the i -th <SQL parameter declaration> with the <parameter type> replaced by XDT .
- 4) **Insert after SR 24)d)iii)2)A)II)1):** If RT is an XML type, then:
- a) Let XDT be the data type identified by the <character string type> contained in <string type option> immediately contained in RT . XDT is the *associated string type* of the result of R .
- b) Let XO be the <document or content> immediately contained in RT . XO is the *associated XML option* of the result of R .
- c) PT is XDT .
- 5) **Insert before SR 24)d)iii)2)B)II)2):** If RFT_{i-PN} is an XML type, then:
- a) Let XDT be the data type identified by the <character string type> contained in <string type option> immediately contained in RFT_{i-PN} . XDT is the *associated string type* of the result of R .
- b) Let XO be the <document or content> immediately contained in RFT_{i-PN} . XO is the *associated XML option* of the result of R .
- c) PT_i is XDT .
- 6) **Insert after SR 24)d)iv)1)A):** If the <parameter type> T_i simply contained in the i -th <SQL parameter declaration> is an XML type, then:
- a) Let XDT be the data type identified by the <character string type> contained in <string type option> immediately contained in T_i . XDT is the *associated string type* of T_i .
- b) Let XO be the <document or content> immediately contained in T_i . XO is the *associated XML option* of T_i .
- c) The i -th effective SQL parameter list entry is the i -th <SQL parameter declaration> with the <parameter type> replaced by XDT .
- 7) **Insert after SR 24)e)i):** If the <parameter type> T_i simply contained in the i -th <SQL parameter declaration> is an XML type, then:
- a) Let XDT be the data type identified by the <character string type> contained in <string type option> immediately contained in T_i . XDT is the *associated string type* of T_i .
- b) Let XO be the <document or content> immediately contained in T_i . XO is the *associated XML option* of T_i .
- c) The i -th effective SQL parameter list entry is the i -th <SQL parameter declaration> with the <parameter type> replaced by XDT .
- 8) **Insert after the last SR:** Case:
- a) If R is an external routine, then <SQL parameter declaration> and <returns clause> shall not contain an <XML passing mechanism>.
- b) Otherwise:
- i) If the declared type of an <SQL parameter declaration> is an XML type or a distinct type whose source type is an XML type, and the <SQL parameter declaration> does not contain an <XML passing mechanism>, then it is implementation-defined (IA128) whether BY REF or BY VALUE is implicit.

- ii) If the declared type of an <SQL parameter declaration> is not an XML type or a distinct type whose source type is an XML type, then the <SQL parameter declaration> shall not contain an <XML passing mechanism>.
- iii) If *R* is an SQL-invoked function, the declared type of the <returns type> is an XML type or a distinct type whose source type is an XML type, and the <returns clause> does not contain an <XML passing mechanism>, then it is implementation-defined (IA129) whether BY REF or BY VALUE is implicit.
- iv) If *R* is an SQL-invoked function and the declared type of the <returns type> is not an XML type or a distinct type whose source type is an XML type, then the <returns clause> shall not contain an <XML passing mechanism>.

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert after GR 3)r):** For every SQL parameter that has an associated string type, the routine descriptor includes the character string type descriptor of the associated string type.
- 2) **Insert after GR 3)r):** For every SQL parameter that has an associated XML option, the routine descriptor includes an indication of the associated XML option.
- 3) **Insert after GR 3)r):** For every SQL parameter whose <SQL parameter declaration> contains an explicit or implicit <XML passing mechanism>, the routine descriptor includes an indication of that <XML passing mechanism>.
- 4) **Insert after GR 3)s):** If *R* is an SQL function, then the routine descriptor includes an indication of the explicit or implicit <XML passing mechanism> contained in the <returns clause>.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X120, “XML parameters in SQL routines”, conforming SQL language shall not contain an <SQL-invoked routine> that simply contains a <language clause> that contains SQL and that simply contains a <parameter type> or a <returns data type> that contains a <data type> that is based on either an XML type or a distinct type whose source type is an XML type.
- 2) **Insert after the last CR:** Without Feature X121, “XML parameters in external routines”, conforming SQL language shall not contain an <SQL-invoked routine> that simply contains a <language clause> that contains ADA, C, COBOL, FORTRAN, MUMPS, PASCAL, or PLI and that simply contains a <parameter type> or a <returns data type> that contains a <data type> that is based on either an XML type or a distinct type whose source type is an XML type.
- 3) **Insert after the last CR:** Without Feature X110, “Host language support for XML: VARCHAR mapping”, conforming SQL language shall not contain a <string type option> that contains CHARACTER VARYING, CHAR VARYING, or VARCHAR.
- 4) **Insert after the last CR:** Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <string type option> that contains CHARACTER LARGE OBJECT, CHAR LARGE OBJECT, or CLOB.
- 5) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, conforming SQL language shall not contain a <document or content> that is CONTENT.

- 6) Insert after [the last CR:](#) Without Feature X101, “Host language support for XML: DOCUMENT option”, conforming SQL language shall not contain a <document or content> that is DOCUMENT.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

12.9 <user-defined cast definition>

This Subclause modifies Subclause 11.63, “<user-defined cast definition>”, in ISO/IEC 9075-2.

Function

Define a user-defined cast.

Format

No additional Format items.

Syntax Rules

- 1) Insert after the last SR: Neither *SDT* nor *TDT* shall be a distinct type whose source type is an XML type.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

13 SQL-client modules

This Clause modifies Clause 13, “SQL-client modules”, in ISO/IEC 9075-2.

13.1 <externally-invoked procedure>

This Subclause modifies Subclause 13.3, “<externally-invoked procedure>”, in ISO/IEC 9075-2.

Function

Define an externally-invoked procedure.

Format

No additional Format items.

Syntax Rules

- 1) Insert into SR 10)e after

```
package SQLSTATE_CODES is
```

the code:

```
WARNING_NO_SUBCLASS:
  constant SQLSTATE_TYPE := "01000";
WARNING_COLUMN_CANNOT_BE_MAPPED_TO_XML:
  constant SQLSTATE_TYPE := "01010";
SQL_XML_MAPPING_ERROR_NO_SUBCLASS:
  constant SQLSTATE_TYPE := "0N000";
SQL_XML_MAPPING_ERROR_UNMAPPABLE_XML_NAME:
  constant SQLSTATE_TYPE := "0N001";
SQL_XML_MAPPING_ERROR_INVALID_XML_CHARACTER:
  constant SQLSTATE_TYPE := "0N002";
XQUERY_ERROR_NO_SUBCLASS:
  constant SQLSTATE_TYPE := "10000";
DATA_EXCEPTION_NO_SUBCLASS:
  constant SQLSTATE_TYPE := "22000";
DATA_EXCEPTION_NOT_AN_XML_DOCUMENT:
  constant SQLSTATE_TYPE := "2200L";
DATA_EXCEPTION_INVALID_XML_DOCUMENT:
  constant SQLSTATE_TYPE := "2200M";
DATA_EXCEPTION_INVALID_XML_CONTENT:
  constant SQLSTATE_TYPE := "2200N";
DATA_EXCEPTION_XML_VALUE_OVERFLOW:
  constant SQLSTATE_TYPE := "2200R";
DATA_EXCEPTION_INVALID_COMMENT:
  constant SQLSTATE_TYPE := "2200S";
DATA_EXCEPTION_INVALID_PROCESSING_INSTRUCTION:
  constant SQLSTATE_TYPE := "2200T";
DATA_EXCEPTION_NOT_AN_XQUERY_DOCUMENT_NODE:
  constant SQLSTATE_TYPE := "2200U";
DATA_EXCEPTION_INVALID_XQUERY_CONTEXT_ITEM:
  constant SQLSTATE_TYPE := "2200V";
DATA_EXCEPTION_XQUERY_SERIALIZATION_ERROR:
  constant SQLSTATE_TYPE := "2200W";
```

```
DATA_EXCEPTION_XQUERY_SEQUENCE_CANNOT_BE_VALIDATED:  
  constant SQLSTATE_TYPE := "2201J";  
DATA_EXCEPTION_XQUERY_DOCUMENT_NODE_CANNOT_BE_VALIDATED:  
  constant SQLSTATE_TYPE := "2201K";  
DATA_EXCEPTION_NO_XML_SCHEMA_FOUND:  
  constant SQLSTATE_TYPE := "2201L";  
DATA_EXCEPTION_ELEMENT_NAMESPACE_NOT_DECLARED:  
  constant SQLSTATE_TYPE := "2201M";  
DATA_EXCEPTION_GLOBAL_ELEMENT_NOT_DECLARED:  
  constant SQLSTATE_TYPE := "2201N";  
DATA_EXCEPTION_NO_XML_ELEMENT_WITH_THE_SPECIFIED_QNAME:  
  constant SQLSTATE_TYPE := "2201P";  
DATA_EXCEPTION_NO_XML_ELEMENT_WITH_THE_SPECIFIED_NAMESPACE:  
  constant SQLSTATE_TYPE := "2201Q";  
DATA_EXCEPTION_VALIDATION_FAILURE:  
  constant SQLSTATE_TYPE := "2201R";
```

The text of library unit package `Interfaces.SQL` is also available in a “digital artifact”. Please see The text of the Ada library unit package `Interfaces.SQL` is also available from the ISO website as a “digital artifact”. See <https://standards.iso.org/iso-iec/9075/-14/ed-6/en/> to download digital artifacts for this document. To download the library unit package, select the file named `ISO_IEC_9075-14(E)_XML-Interfaces.SQL.ada`.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

13.2 <SQL procedure statement>

This Subclause modifies Subclause 13.4, “<SQL procedure statement>”, in ISO/IEC 9075-2.

Function

Define all of the SQL-statements that are <SQL procedure statement>s.

Format

```
<SQL session statement> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <set XML option statement>
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

13.3 Data type correspondences

This Subclause modifies Subclause 13.5, “Data type correspondences”, in ISO/IEC 9075-2.

Function

Specify the data type correspondences for SQL data types and host language types.

Tables

Insert into Table 21, “Data type correspondences for Ada” the rows of Table 5, “Data type correspondences for Ada”.

Table 5 — Data type correspondences for Ada

SQL Data Type	Ada Data Type
XML	<i>None</i>

Insert into Table 22, “Data type correspondences for C” the rows of Table 6, “Data type correspondences for C”.

Table 6 — Data type correspondences for C

SQL Data Type	C Data Type
XML	<i>None</i>

Insert into Table 23, “Data type correspondences for COBOL” the rows of Table 7, “Data type correspondences for COBOL”.

Table 7 — Data type correspondences for COBOL

SQL Data Type	COBOL Data Type
XML	<i>None</i>

Insert into Table 24, “Data type correspondences for Fortran” the rows of Table 8, “Data type correspondences for Fortran”.

Table 8 — Data type correspondences for Fortran

SQL Data Type	Fortran Data Type
XML	<i>None</i>

Insert into Table 25, “Data type correspondences for M” the rows of Table 9, “Data type correspondences for M”.

Table 9 — Data type correspondences for M

SQL Data Type	M Data Type
XML	<i>None</i>

Insert into Table 26, “Data type correspondences for Pascal” the rows of Table 10, “Data type correspondences for Pascal”.

Table 10 — Data type correspondences for Pascal

SQL Data Type	Pascal Data Type
XML	<i>None</i>

Insert into Table 27, “Data type correspondences for PL/I” the rows of Table 11, “Data type correspondences for PL/I”.

Table 11 — Data type correspondences for PL/I

SQL Data Type	PL/I Data Type
XML	<i>None</i>

Conformance Rules

No additional Conformance Rules.

14 Data manipulation

This Clause modifies Clause 14, “Data manipulation”, in ISO/IEC 9075-2.

14.1 <fetch statement>

This Subclause modifies Subclause 14.5, “<fetch statement>”, in ISO/IEC 9075-2.

Function

Position a standing cursor on a specified row of the standing cursor’s result set and retrieve values from that row.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert before GR 5)a)i)2): If the declared type of *TS* is an XML type, then let *PTEMP* be the <XML passing mechanism> of *TS*
- 2) Augment GR 5)a)i)2) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 3) Insert before GR 5)b)i)1)B)V)1)b):
Case:
 - a) If *EDT* is an XML type, then let *PTEMP* be the <XML passing mechanism> of *TV_i*
 - b) Otherwise let *PTEMP* be the null value.
- 4) Augment GR 5)b)i)1)B)V)1)b) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 5) Insert before GR 5)b)i)1)B)V)2)c):
Case:
 - a) If *EDT* is an XML type, then let *PTEMP* be the <XML passing mechanism> of *TV_i*

14.1 <fetch statement>

- b) Otherwise let *PTEMP* be the null value.
- 6) Augment GR 5)b)i)1)B)V)2)c) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 7) Insert before GR 5)b)i)2)B): If the declared type of TV_i is an XML type, then let *PTEMP* be the <XML passing mechanism> of TV_i
- 8) Augment GR 5)b)i)2)B) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

14.2 <select statement: single row>

This Subclause modifies Subclause 14.7, “<select statement: single row>”, in ISO/IEC 9075-2.

Function

Retrieve values from a specified row of a table.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert before GR 4)a)i)2):** If the declared type of TS is an XML type, then let $PTEMP$ be the <XML passing mechanism> of TS
- 2) **Augment GR 4)a)i)2)** by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 3) **Insert before GR 4)b)ii)1)B)V)1)b):**
Case:
 - a) If EDT is an XML type, then let $PTEMP$ be the <XML passing mechanism> of TS_i
 - b) Otherwise let $PTEMP$ be the null value.
- 4) **Augment GR 4)b)ii)1)B)V)1)b)** by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 5) **Insert before GR 4)b)ii)1)B)V)2)c):**
Case:
 - a) If EDT is an XML type, then let $PTEMP$ be the <XML passing mechanism> of TS_i
 - b) Otherwise let $PTEMP$ be the null value.
- 6) **Augment GR 4)b)ii)1)B)V)2)c)** by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 7) **Insert before GR 4)b)ii)2)B):** If the declared type of TS_i is an XML type, then let $PTEMP$ be the <XML passing mechanism> of TS_i .
- 8) **Augment GR 4)b)ii)2)B)** by adding “ $PTEMP$ as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

14.3 <delete statement: searched>

This Subclause modifies Subclause 14.9, “<delete statement: searched>”, in ISO/IEC 9075-2.

Function

Delete rows of a table.

Format

```
<delete statement: searched> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | DELETE WITH <XML lexically scoped options> FROM <target table>  
      [ FOR PORTION OF <application time period name>  
        FROM <point in time 1> TO <point in time 2> ]  
      [ [ AS ] <correlation name> ]  
      [ WHERE <search condition> ]
```

Syntax Rules

- 1) **Insert after the last SR:** The scope of each <XML namespace declaration item> contained in the <XML lexically scoped options> is the <delete statement: searched>.
- 2) **Insert after the last SR:** The scope of an <XML binary encoding> contained in the <XML lexically scoped options> is the <delete statement: searched>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X082, “XML namespace declarations in DML”, in conforming SQL language, a <delete statement: searched> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X132, “XMLBINARY clause in DML”, in conforming SQL language, a <delete statement: searched> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

14.4 <insert statement>

This Subclause modifies Subclause 14.11, “<insert statement>”, in ISO/IEC 9075-2.

Function

Create new rows in a table.

Format

```
<insert statement> ::=
    !! All alternatives from ISO/IEC 9075-2
    | INSERT WITH <XML lexically scoped options> INTO <insertion target>
      <insert columns and source>
```

Syntax Rules

- 1) Insert after the last SR: The scope of each <XML namespace declaration item> contained in <XML lexically scoped options> is the <insert statement>.
- 2) Insert after the last SR: The scope of an <XML binary encoding> contained in <XML lexically scoped options> is the <insert statement>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X082, “XML namespace declarations in DML”, in conforming SQL language, an <insert statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) Insert after the last CR: Without Feature X132, “XMLBINARY clause in DML”, in conforming SQL language, an <insert statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

14.5 <merge statement>

This Subclause modifies Subclause 14.12, “<merge statement>”, in ISO/IEC 9075-2.

Function

Conditionally update and/or delete rows of a table and/or insert new rows into a table.

Format

```
<merge statement> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | MERGE WITH <XML lexically scoped options> INTO <target table>  
      [ [ AS ] <merge correlation name> ]  
      USING <table reference> ON <search condition>  
      <merge operation specification>
```

Syntax Rules

- 1) **Insert after the last SR:** The scope of each <XML namespace declaration item> contained in <XML lexically scoped options> is the <merge statement>.
- 2) **Insert after the last SR:** The scope of an <XML binary encoding> contained in <XML lexically scoped options> is the <merge statement>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X082, “XML namespace declarations in DML”, in conforming SQL language, a <merge statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X132, “XMLBINARY clause in DML”, in conforming SQL language, a <merge statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

14.6 <update statement: positioned>

This Subclause modifies Subclause 14.13, “<update statement: positioned>”, in ISO/IEC 9075-2.

Function

Update a row of a table.

Format

```
<update statement: positioned> ::=
  !! All alternatives from ISO/IEC 9075-2
  | UPDATE WITH <XML lexically scoped options>
    <target table> [ [ AS ] <correlation name> ]
    SET <set clause list> WHERE CURRENT OF <cursor name>
```

Syntax Rules

- 1) Insert after the last SR: The scope of each <XML namespace declaration item> contained in <XML lexically scoped options> is the <update statement: positioned>.
- 2) Insert after the last SR: The scope of an <XML binary encoding> contained in <XML lexically scoped options> is the <update statement: positioned>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X082, “XML namespace declarations in DML”, in conforming SQL language, an <update statement: positioned> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) Insert after the last CR: Without Feature X132, “XMLBINARY clause in DML”, in conforming SQL language, an <update statement: positioned> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

14.7 <update statement: searched>

This Subclause modifies Subclause 14.14, “<update statement: searched>”, in ISO/IEC 9075-2.

Function

Update rows of a table.

Format

```
<update statement: searched> ::=  
  !! All alternatives from ISO/IEC 9075-2  
  | UPDATE WITH <XML lexically scoped options> <target table>  
    [ FOR PORTION OF <application time period name>  
      FROM <point in time 1> TO <point in time 2> ]  
    [ [ AS ] <correlation name> ]  
    SET <set clause list>  
    [ WHERE <search condition> ]
```

Syntax Rules

- 1) **Insert after the last SR:** The scope of each <XML namespace declaration item> contained in <XML lexically scoped options> is the <update statement: searched>.
- 2) **Insert after the last SR:** The scope of an <XML binary encoding> contained in <XML lexically scoped options> is the <update statement: searched>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X082, “XML namespace declarations in DML”, in conforming SQL language, an <update statement: searched> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.
- 2) **Insert after the last CR:** Without Feature X132, “XMLBINARY clause in DML”, in conforming SQL language, an <update statement: searched> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

15 Control statements

This Clause modifies Clause 15, “Control statements”, in ISO/IEC 9075-4.

15.1 <compound statement>

This Subclause modifies Subclause 15.1, “<compound statement>”, in ISO/IEC 9075-4.

Function

Specify a statement that groups other statements together.

Format

```
<compound statement> ::=
  !! All alternatives from ISO/IEC 9075-2
  | [ <beginning label> <colon> ]
    BEGIN [ [ NOT ] ATOMIC ]
    DECLARE <XML lexically scoped options> <semicolon>
    [ <local declaration list> ]
    [ <local cursor declaration list> ]
    [ <local handler declaration list> ]
    [ <SQL statement list> ]
    END [ <ending label> ]
```

Syntax Rules

- 1) Insert after the last SR: The scope of each <XML namespace declaration item> contained in <XML lexically scoped options> is the <compound statement>.
- 2) Insert after the last SR: The scope of an <XML binary encoding> contained in <XML lexically scoped options> is the <compound statement>.

Access Rules

No additional Access Rules.

General Rules

NOTE 87 — The General Rules of this Subclause as defined in GR 2) of Subclause 8.3, “Executing a <compound statement>”, in ISO/IEC 9075-4 are not always terminated when an exception condition is raised.

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X084, “XML namespace declarations in compound statements”, in conforming SQL language, a <compound statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML namespace declaration>.

- 2) Insert after [the last CR:](#) Without Feature X134, “XMLBINARY clause in compound statements”, in conforming SQL language, a <compound statement> shall not immediately contain an <XML lexically scoped options> that contains an <XML binary encoding>.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

15.2 <assignment statement>

This Subclause modifies Subclause 15.5, “<assignment statement>”, in ISO/IEC 9075-4.

Function

Assign a value to an SQL variable, SQL parameter, host parameter, or host variable.

Format

```
<singleton variable assignment> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | SET <assignment target> <equals operator> <assignment source>  
      <XML passing mechanism>
```

Syntax Rules

- 1) **Insert after the last SR:** If a <singleton variable assignment> *SVA* contains an <XML passing mechanism>, then:
 - a) The declared type of the <assignment target> *AT* contained in *SVA* shall be an XML type.
 - b) *AT* shall not be a <host parameter specification>, an <embedded variable specification>, or a <dynamic parameter specification>.
- 2) **Insert after the last SR:** If the declared type of the <assignment target> *AT* contained in a <singleton variable assignment> *SVA* is an XML type, *AT* is not a <host parameter specification>, an <embedded variable specification>, or a <dynamic parameter specification>, and *SVA* does not contain an <XML passing mechanism>, then it is implementation-defined (ID204) whether an <XML passing mechanism> of BY REF or BY VALUE is implicit.

Access Rules

No additional Access Rules.

General Rules

- 1) **Insert before GR 1)b):** If the declared type of *T* is an XML type, then let *PTEMP* be the <XML passing mechanism>
- 2) **Augment GR 1)b):** by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 3) **Insert before GR 4)b)ii):** If the declared type of *FT* is an XML type, then let *PTEMP* be the <XML passing mechanism>
- 4) **Augment GR 4)b)ii):** by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 5) **Insert before GR 5)b)v)1)B):**

Case:

 - a) If *EDT* is an XML type, then let *PTEMP* be the <XML passing mechanism>

- b) Otherwise let *PTEMP* be the null value.
- 6) Augment GR 5)b)v)1)B) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.
- 7) Insert before GR 5)b)v)2)C):
Case:
 - a) If *EDT* is an XML type, then let *PTEMP* be the <XML passing mechanism>
 - b) Otherwise let *PTEMP* be the null value.
- 8) Augment GR 5)b)v)2)C) by adding “*PTEMP* as PASSING” to the list of parameter assignments in the call to Subclause 10.2, “Store assignment”.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

16 Session management

This Clause modifies Clause 19, "Session management", in ISO/IEC 9075-2.

16.1 <set XML option statement>

Function

Set the XML option of the current SQL-session.

Format

```
<set XML option statement> ::=  
  SET XML OPTION <document or content>
```

Syntax Rules

None.

Access Rules

None.

General Rules

- 1) Case:
 - a) If DOCUMENT is specified, then the XML option of the current SQL-session is set to DOCUMENT.
 - b) Otherwise, the XML option of the current SQL-session is set to CONTENT.

Conformance Rules

- 1) Without Feature F761, "Session management", conforming SQL language shall not contain a <set XML option statement>.
- 2) Without Feature X100, "Host language support for XML: CONTENT option", conforming SQL language shall not contain a <set XML option statement> that contains CONTENT.
- 3) Without Feature X101, "Host language support for XML: DOCUMENT option", conforming SQL language shall not contain a <set XML option statement> that contains DOCUMENT.

17 Dynamic SQL

This Clause modifies Clause 20, “Dynamic SQL”, in ISO/IEC 9075-2.

17.1 Description of SQL descriptor areas

This Subclause modifies Subclause 20.1, “Description of SQL descriptor areas”, in ISO/IEC 9075-2.

Function

Specify the identifiers, data types, and codes used in SQL item descriptor areas.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert into Table 30, “Codes used for SQL data types in Dynamic SQL” the rows of Table 12, “Codes used for SQL data types in Dynamic SQL”.

Table 12 – Codes used for SQL data types in Dynamic SQL

Data Type	Code
XML	137

Conformance Rules

No additional Conformance Rules.

17.2 <input using clause>

This Subclause modifies Subclause 20.11, “<input using clause>”, in ISO/IEC 9075-2.

Function

Supply input values for an <SQL dynamic statement>.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert before GR 6)c)ii): If *SDT* is a character string type and *TDT* is an XML type, then:
 - a) Let *XO* be the XML option of the current SQL-session.
 - b) It is implementation-defined (IA121) whether *XWO* is STRIP WHITESPACE or PRESERVE WHITESPACE.
 - c) If the <XML parse>
`XMLPARSE (XO SV XWO)`
does not conform to the Syntax Rules of Subclause 6.17, “<XML parse>”, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation (07006)*.
 - d) The <XML parse>
`XMLPARSE (XO SV XWO)`
is effectively performed and is the value of the *i*-th input dynamic parameter.
NOTE 88 — The effective performance of the <XML parse> includes the raising of exceptions as specified in the General Rules of that Subclause.

Conformance Rules

No additional Conformance Rules.

17.3 <output using clause>

This Subclause modifies Subclause 20.12, “<output using clause>”, in ISO/IEC 9075-2.

Function

Supply output values for an <SQL dynamic statement>.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR 5)d)ii): If *SDT* is the XML type and *TDT* is a character string type, then:
 - a) Let *XO* be the XML option of the current SQL-session.
 - b) It is implementation-defined (IA118) whether *XDO* is INCLUDING XMLDECLARATION or EXCLUDING XMLDECLARATION.
 - c) Case:
 - i) If the character set of *TDT* is UTF16, then let *BOM* be U&' \FEFF '.
 - ii) Otherwise, let *BOM* be the zero-length string of type *TDT*.
 - d) If the <string value function>
`XMLSERIALIZE (XO SV AS TDT XDO)`
does not conform to the Syntax Rules of Subclause 6.9, “<string value function>”, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation (07006)*.
 - e) The <string value function>
`BOM || XMLSERIALIZE (XO SV AS TDT XDO)`
is effectively performed and is the value *TV* of the *i*-th <target specification>.

NOTE 89 — The effective performance of the <XML character string serialization> includes the raising of exceptions as specified in the General Rules of that Subclause.

Conformance Rules

No additional Conformance Rules.

17.4 <prepare statement>

This Subclause modifies Subclause 20.7, “<prepare statement>”, in ISO/IEC 9075-2.

Function

Prepare a statement for execution.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR 5)a)xxviii)1)E):
NOTE 90 — The following “part 2” predicates do not have any value expressions with declared type information: <XML content predicate part 2>, <XML document predicate part 2>, <XML valid predicate part 2>.
- 2) Insert after GR 5)a)xxxvii): If *DP* is an <XML value expression> simply contained in <XML character string serialization>, <XML binary string serialization>, <XML concatenation>, <XML document>, or <XML validate>, then *DT* is an implementation-defined (IV239) XML type.
- 3) Insert after GR 5)a)xxxvii): If *DP* is a <row value predicand> simply contained in <XML content predicate>, <XML document predicate>, or <XML valid predicate>, then *DT* is an implementation-defined (IV239) XML type.
- 4) Insert after GR 5)a)xxxvii): If *DP* is a <character value expression> simply contained in <XML comment>, <XML PI>, or <XML text>, then *DT* is CHARACTER VARYING (*ML*).

Conformance Rules

No additional Conformance Rules.

18 Embedded SQL

This Clause modifies Clause 21, “Embedded SQL”, in ISO/IEC 9075-2.

18.1 <embedded SQL host program>

This Subclause modifies Subclause 21.1, “<embedded SQL host program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL host program>.

Format

No additional Format items.

Syntax Rules

- 1) Insert before SR 22)h)ii)2): If *EVN* identifies an XML VARCHAR host variable, an XML CLOB host variable, or an XML BLOB host variable, then:
 - a) Let *XO* be the XML option of *EVN*.
 - b) Let *XWO* be the XML whitespace option of *EVN*.
 - c) *EVN* is replaced by


```
XMLPARSE (XO PN XWO)
```
- 2) Insert before SR 22)l)j)7): For each *HVN_i*, 1 (one) ≤ *i* ≤ *n*, that identifies some *HV_i* that is either an XML VARCHAR host variable, an XML CLOB host variable, or an XML BLOB host variable, the Syntax Rules of Subclause 9.8 “Host parameter mode determination”, in ISO/IEC 9075-2, are applied with the *PD_i* corresponding to *HVN_i* as *HOST PARAM DECL* and *ES* as *SQL PROC STMT*; let *PMODE_i* be the *PARAMETER MODE* returned from the application of those Syntax Rules, to determine whether the corresponding *XP_i* is an input host parameter, an output host parameter, or both an input host parameter and an output host parameter.
 - a) Among *XP_i*, 1 (one) ≤ *i* ≤ *n*, let *d* be the number of host parameters, where *PMODE_i* is equal to “IN”, *e* be the number of host parameters, where *PMODE_i* is equal to “OUT”, and *f* be the number of host parameters, where *PMODE_i* is equal to “INOUT”.
 - b) Among *XP_i*, 1 (one) ≤ *i* ≤ *n*, let *XPI_j*, 1 (one) ≤ *j* ≤ *d*, be the host parameters, where *PMODE_i* is equal to “IN”, let *XPO_k*, 1 (one) ≤ *k* ≤ *e*, be the host parameters, where *PMODE_i* is equal to “OUT”, and let *XPIO_l*, 1 (one) ≤ *l* ≤ *f*, be the host parameters, where *PMODE_i* is equal to “INOUT”.
 - c) For 1 (one) ≤ *j* ≤ *d*:
 - i) Let *XPNI_j* be the <host parameter name> of *XPI_j*.
 - ii) Let *XHVI_j* be the host variable corresponding to *XPI_j*.

18.1 <embedded SQL host program>

- iii) Let $XDOCI_j$ be the XML option of $XHVI_j$.
 - iv) Let $XSPWI_j$ be the XML whitespace option of $XHVI_j$.
 - v) It is implementation-defined (IA118) whether $XDOI_j$ is INCLUDING XMLDECLARATION or EXCLUDING XMLDECLARATION.
- d) For $1 \text{ (one)} \leq k \leq e$:
- i) Let $XPNO_k$ be the <host parameter name> of XPO_k .
 - ii) Let $XHVO_k$ be the host variable corresponding to XPO_k .
 - iii) Let $XDOCO_k$ be the XML option of $XHVO_k$.
 - iv) Let $XSPWO_k$ be the XML whitespace option of $XHVO_k$.
 - v) It is implementation-defined (IA118) whether $XDOO_k$ is INCLUDING XMLDECLARATION or EXCLUDING XMLDECLARATION.
 - vi) Let XLO_k be the length of $XHVO_k$.
 - vii) If $XHVO_k$ is an XML VARCHAR host variable or XML CLOB host variable, then let $XCSO_k$ be the character set of $XHVO_k$.
 - viii) Case:
 - 1) If $XHVO_k$ is an XML VARCHAR host variable, then let XTO_k be
`VARCHAR(XLO_k) CHARACTER SET $XCSO_k$`
 - 2) If $XHVO_k$ is an XML BLOB host variable, then let XTO_k be
`BLOB(XLO_k)`
 - 3) Otherwise, let XTO_k be
`CLOB(XLO_k) CHARACTER SET $XCSO_k$`
 - ix) Case:
 - 1) If $XCSO_k$ is UTF16, then let $OBOM_k$ be `U&' \FEFF'`.
 - 2) Otherwise, let $OBOM_k$ be the zero-length string of type XTO_k .
- e) For $1 \text{ (one)} \leq l \leq f$:
- i) Let $XPNIOL$ be the <host parameter name> of $XPIOL$.
 - ii) Let $XHVIO_l$ be the host variable corresponding to $XPIOL$.
 - iii) Let $XDOCIO_l$ be the XML option of $XHVIO_l$.
 - iv) Let $XSPWIO_l$ be the XML whitespace option of $XHVIO_l$.
 - v) It is implementation-defined (IA118) whether $XDOIO_l$ is INCLUDING XMLDECLARATION or EXCLUDING XMLDECLARATION.
 - vi) Let $XLIO_l$ be the length of $XHVIO_l$.

vii) If $XHVIO_l$ is an XML VARCHAR host variable or XML CLOB host variable, then let $XCSIO_l$ be the character set of $XHVIO_l$.

viii) Case:

1) If $XHVIO_l$ is an XML VARCHAR host variable, then let $XTIO_l$ be

`VARCHAR($XLIO_l$) CHARACTER SET $XCSIO_l$`

2) If $XHVIO_l$ is an XML BLOB host variable, then let $XTIO_l$ be

`BLOB($XLIO_l$)`

3) Otherwise, let $XTIO_l$ be

`CLOB($XLIO_l$) CHARACTER SET $XCSIO_l$`

ix) Case:

1) If $XCSIO_l$ is UTF16, then let $IOBOM_l$ be `U&' \FEFF'`

2) Otherwise, let $IOBOM_l$ be the zero-length string of type $XTIO_l$.

f) Let XVI_j , $1 \text{ (one)} \leq j \leq d$, XVO_k , $1 \text{ (one)} \leq k \leq e$, and $XVIO_l$, $1 \text{ (one)} \leq l \leq f$, be implementation-dependent (UV013) <SQL variable name>s, each of which is not equivalent to any other <SQL variable name> contained in ES , to any <SQL parameter name> contained in ES , or to any <column name> contained in ES .

3) **Insert before SR 22)l)i)7)B):** If HV_i identifies an XML VARCHAR host variable, an XML CLOB host variable, or an XML BLOB variable, then

Case:

a) If $PMODE_i$ is equal to "IN", then let $PXNI_j$, $1 \text{ (one)} \leq j \leq d$, be the <host parameter name> of the input host parameter that corresponds to P_i . HVN_i is replaced by XVI_j .

b) If $PMODE_i$ is equal to "OUT", then let $PXNO_k$, $1 \text{ (one)} \leq k \leq e$, be the <host parameter name> of the output host parameter that corresponds to P_i . HVN_i is replaced by XVO_k .

c) Otherwise, let $PXNIO_l$, $1 \text{ (one)} \leq l \leq f$, be the <host parameter name> of the host parameter that corresponds to P_i . HVN_i is replaced by $XVIO_l$.

4) **Insert into SR 22)l)i)8)** after

`DECLARE SVI_a TUI_a ;`

the code:

`DECLARE XVI_1 XML;`

`...`

`DECLARE XVI_d XML;`

5) **Insert into SR 22)l)i)8)** after

`DECLARE SVO_b TUO_b ;`

the code:

`DECLARE XVO_1 XML;`

18.1 <embedded SQL host program>

```
...
DECLARE XVOe XML;
```

- 6) [Insert into SR 22\)l\)i\)8\)](#) after

```
DECLARE SVIOc TTIOc;
```

the code:

```
DECLARE XVIO1 XML;
...
DECLARE XVIOf XML;
```

- 7) [Insert into SR 22\)l\)i\)8\)](#) after

```
SET SVIa = TSINa (CAST (PNIa AS TTIa));
```

the code:

```
SET XVI1 = XMLPARSE (XDOCI1 XPNI1 XSPWI1);
...
SET XVId = XMLPARSE (XDOCId XPNId XSPWId);
```

- 8) [Insert into SR 22\)l\)i\)8\)](#) after

```
SET SVIOc = TSIONc (CAST (PNIOc AS TTIOc));
```

the code:

```
SET XVIO1 = XMLPARSE (XDOCIO1 XPNIO1 XSPWIO1);
...
SET XVIOf = XMLPARSE (XDOCIOf XPNIOf XSPWIOf);
```

- 9) [Insert into SR 22\)l\)i\)8\)](#) after

```
SET PNOb = CAST ( FSONb (SVOb) AS TSOb);
```

the code:

```
SET XPNO1 = IOBOM1 || XMLSERIALIZE ( XDOCO1 XVO1 AS XTO1 XDOO1 );
...
SET XPNOe = IOBOMe || XMLSERIALIZE ( XDOCOe XVOe AS XTOe XDOOe );
```

- 10) [Insert into SR 22\)l\)i\)8\)](#) after

```
SET PNIOc = CAST ( FSIONc (SVIOc) AS TSIOc);
```

the code:

```
SET XPNIO1 = IOBOM1 || XMLSERIALIZE ( XDOCIO1 XVIO1 AS XTIO1 XDOIO1 );
...
SET XPNIOf = IOBOMf || XMLSERIALIZE ( XDOCIOf XVIOf AS XTIOf XDOIOf );
```

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

No additional Conformance Rules.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

18.2 <embedded SQL Ada program>

This Subclause modifies Subclause 21.3, “<embedded SQL Ada program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL Ada program>.

Format

```
<Ada derived type specification> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <Ada XML CLOB variable>  
    | <Ada XML BLOB variable>  
  
<Ada XML BLOB variable> ::=  
    SQL TYPE IS XML [ <document or content> ]  
    [ <XML whitespace option> ]  
    AS BLOB <left paren> <large object length> <right paren>  
  
<Ada XML CLOB variable> ::=  
    SQL TYPE IS XML [ <document or content> ]  
    [ <XML whitespace option> ]  
    AS CLOB <left paren> <character large object length> <right paren>  
    [ CHARACTER SET [ IS ] <character set specification> ]
```

Syntax Rules

- 1) **Insert after SR 4)c)xi):** If *ATS* is <Ada XML CLOB variable>, then the <host parameter data type> of *HV* is CHARACTER LARGE OBJECT with maximum length specified by the <character large object length> contained in *ATS* and character set specified by the <character set specification> contained in *ATS*. If <character set specification> is not specified, then the character set is implementation-defined (ID217).
- 2) **Insert after SR 4)c)xi):** If *ATS* is <Ada XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT with maximum length specified by the <large object length> contained in *ATS*.
- 3) **Insert after SR 5)f):** The syntax

```
SQL TYPE IS XML XO XWO AS CLOB (L)  
CHARACTER SET IS CS
```

for a given <Ada host identifier> *HVN* shall be replaced by

```
TYPE HVN IS RECORD  
    HVN_RESERVED : Interfaces.SQL.INT ;  
    HVN_LENGTH : Interfaces.SQL.INT ;  
    HVN_DATA : Interfaces.SQL.CHAR (1..LL) ;  
END RECORD;
```

in any <Ada XML CLOB variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”.
- b) The value of *LL* is $NV * k$.
- c) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.

- d) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- e) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML CLOB host variable. *L* is the length of XML CLOB host variable. *CS* is the character set of XML CLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise *XO* is the XML option of XML CLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise, *XWO* is the XML whitespace option of the XML CLOB host variable.

NOTE 91 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 4) Insert after SR 5)f) The syntax

```
SQL TYPE IS XML XO XWO AS BLOB (L)
```

for a given <Ada host identifier> *HVN* shall be replaced by

```
TYPE HVN IS RECORD
  HVN_RESERVED : Interfaces.SQL.INT ;
  HVN_LENGTH : Interfaces.SQL.INT ;
  HVN_DATA : Interfaces.SQL.CHAR (1..L);
END RECORD;
```

in any <Ada XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

HVN is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise, *XWO* is the XML whitespace option of the XML BLOB host variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain an <Ada XML CLOB variable>.

- 2) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Ada XML CLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 3) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Ada XML CLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 4) **Insert after the last CR:** Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain an <Ada XML BLOB variable>.
- 5) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Ada XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 6) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Ada XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 7) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Ada XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Ada XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Ada XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Ada XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

18.3 <embedded SQL C program>

This Subclause modifies Subclause 21.4, “<embedded SQL C program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL C program>.

Format

```
<C derived variable> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <C XML VARCHAR variable>
    | <C XML CLOB variable>
    | <C XML BLOB variable>

<C XML VARCHAR variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS VARCHAR
    [ CHARACTER SET [ IS ] <character set specification> ]
    <C host identifier> <C array specification> [ <C initial value> ]
    [ { <comma> <C host identifier> <C array specification> [ <C initial value> ] }...
    ]

<C XML CLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS CLOB <left paren> <character large object length> <right paren>
    [ CHARACTER SET [ IS ] <character set specification> ]
    <C host identifier> [ <C initial value> ]
    [ { <comma> <C host identifier> [ <C initial value> ] }... ]

<C XML BLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS BLOB <left paren> <large object length> <right paren>
    <C host identifier> [ <C initial value> ]
    [ { <comma> <C host identifier> [ <C initial value> ] }... ]
```

Syntax Rules

- 1) **Insert after SR 4)c)x):** If CVS contains <C XML VARCHAR variable>, then the <host parameter data type> of HV is CHARACTER VARYING, with maximum length specified by the <character length> of the <C array specification>, measured in the units specified by the explicit or implicit <char length units>. The character set is specified by the <character set specification>; if omitted, the character set is implementation-defined (ID217). The value in HV is terminated by a null character and the position occupied by this null character is included in the maximum length of HV. The SQL data type of the character string resulting from the invocation of the XMLSERIALIZE operator on a value of XML type is CHARACTER VARYING whose maximum length is 1 (one) less than the <character length> of the <C array specification> and whose value does not include the terminating null character. The <length> shall be greater than 1 (one).
- 2) **Insert after SR 4)c)x):** If CVS contains <C XML CLOB variable>, then the <host parameter data type> of HV is CHARACTER LARGE OBJECT, with maximum length specified by the <character large object length>, and with character set specified by the <character set specification>. If there is no <character set specification>, then the character set is implementation-defined (ID217). The SQL data

ISO/IEC 9075-14:2023(E)
18.3 <embedded SQL C program>

type of the character string resulting from the invocation of the XMLSERIALIZE operator on a value of XML type is CHARACTER LARGE OBJECT with maximum length and character set of the <host parameter data type> of *HV*.

- 3) **Insert after SR 4)c)x):** If *CVS* contains <C XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT, with maximum length specified by the <large object length>.
- 4) **Augment the lead text of SR 5)a)** by adding “<C XML VARCHAR variable> and <C XML CLOB variable>” to the list of variables.
- 5) **Insert after SR 5)f):** The syntax

```
SQL TYPE IS XML XO XWO AS VARCHAR  
CHARACTER SET IS CS hvn[L]
```

for a given <C host identifier> *hvn* shall be replaced by:

```
char hvn [LL]
```

in any <C XML VARCHAR variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”, and the value of *LL* is $NV * k$.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

hvn is an XML VARCHAR host variable. *L* is the length of XML VARCHAR host variable. *CS* is the character set of XML VARCHAR host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML VARCHAR host variable; otherwise *XO* is the XML option of XML VARCHAR host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML VARCHAR host variable; otherwise *XWO* is the XML whitespace option of the XML VARCHAR host variable.

NOTE 92 — The length of the XML VARCHAR host variable contains an implicit or explicit <char length units>.

- 6) **Insert after SR 5)f):** The syntax

```
SQL TYPE IS XML XO XWO AS CLOB(L)  
CHARACTER SET IS CS hvn
```

for a given <C host identifier> *hvn* shall be replaced by:

```
struct {  
    long          hvn_reserved;  
    unsigned long hvn_length;  
    char          hvn_data[LL];  
} hvn
```

in any <C XML CLOB variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”, and the value of *LL* is $NV * k$.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.

- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

hvn is an XML CLOB host variable. *L* is the length of XML CLOB host variable. *CS* is the character set of XML CLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise *XO* is the XML option of XML CLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise *XWO* is the XML whitespace option of the XML CLOB host variable.

NOTE 93 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 7) Insert after SR 5)f) The syntax

SQL TYPE IS XML *XO* *XWO* AS BLOB(*L*)

for a given <C host identifier> *hvn* shall be replaced by:

```
struct {
    long          hvn_reserved;
    unsigned long hvn_length;
    char          hvn_data[L];
} hvn
```

in any <C XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

hvn is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise *XWO* is the XML whitespace option of the XML BLOB host variable.

- 8) Augment SR 7) by adding “XML” to the list of words.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X110, “Host language support for XML: VARCHAR mapping”, conforming SQL language shall not contain a <C XML VARCHAR variable>.

18.3 <embedded SQL C program>

- 2) **Insert after the last CR:** Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <C XML CLOB variable>.
- 3) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, neither <C XML VARCHAR variable> nor <C XML CLOB variable> shall immediately contain a <document or content> that is CONTENT.
- 4) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, neither <C XML VARCHAR variable> nor <C XML CLOB variable> shall immediately contain a <document or content> that is DOCUMENT.
- 5) **Insert after the last CR:** Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain a <C XML BLOB variable>.
- 6) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <C XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 7) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <C XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <C XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <C XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <C XML VARCHAR variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 11) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <C XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 12) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <C XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 13) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <C XML VARCHAR variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

18.4 <embedded SQL COBOL program>

This Subclause modifies Subclause 21.5, “<embedded SQL COBOL program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL COBOL program>.

Format

```
<COBOL derived type specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <COBOL XML CLOB variable>
    | <COBOL XML BLOB variable>

<COBOL XML BLOB variable> ::=
    [ USAGE [ IS ] ] SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS BLOB <left paren> <large object length> <right paren>

<COBOL XML CLOB variable> ::=
    [ USAGE [ IS ] ] SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS CLOB <left paren> <character large object length> <right paren>
    [ CHARACTER SET [ IS ] <character set specification> ]
```

Syntax Rules

- 1) **Insert after SR 4)d)x):** If *CTS* contains <COBOL XML CLOB variable>, then the <host parameter data type> of *HV* is CHARACTER LARGE OBJECT with the maximum length specified by <character large object length> and character set specified by <character set specification>. If <character set specification> is not specified, then an implementation-defined (ID217) <character set specification> is implicit.
- 2) **Insert after SR 4)d)x):** If *CTS* contains <COBOL XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT with maximum length specified by <large object length> contained in *CTS*.
- 3) **Insert after SR 5)d):** The syntax

```
SQL TYPE IS XML XO XWO AS CLOB ( L )
CHARACTER SET IS CS
```

for a given <COBOL host identifier> *HVN* shall be replaced by:

```
49 HVN-RESERVED PIC S9(9) USAGE IS BINARY.
49 HVN-LENGTH PIC S9(9) USAGE IS BINARY.
49 HVN-DATA PIC X(LL).
```

in any <COBOL XML CLOB variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”, and the value of *LL* is *NV***k*.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

- d) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML CLOB host variable. *L* is the length of XML CLOB host variable. *CS* is the character set of XML CLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise *XO* is the XML option of XML CLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise *XWO* is the XML whitespace option of the XML CLOB host variable.

NOTE 94 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 4) Insert after SR 5)d): The syntax

```
SQL TYPE IS XML XO XWO AS BLOB ( L )
```

for a given <COBOL host identifier> *HVN* shall be replaced by:

```
49 HVN-RESERVED PIC S9(9) USAGE IS BINARY.
49 HVN-LENGTH PIC S9(9) USAGE IS BINARY.
49 HVN-DATA PIC X(L).
```

in any <COBOL XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

HVN is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise *XWO* is the XML whitespace option of the XML BLOB host variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <COBOL XML CLOB variable>.
- 2) Insert after the last CR: Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <COBOL XML CLOB variable> shall not immediately contain a <document or content> that is CONTENT.

- 3) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <COBOL XML CLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 4) **Insert after the last CR:** Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain a <COBOL XML BLOB variable>.
- 5) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <COBOL XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 6) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <COBOL XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 7) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <COBOL XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <COBOL XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <COBOL XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <COBOL XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

18.5 <embedded SQL Fortran program>

This Subclause modifies Subclause 21.6, “<embedded SQL Fortran program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL Fortran program>.

Format

```
<Fortran derived type specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <Fortran XML CLOB variable>
    | <Fortran XML BLOB variable>

<Fortran XML BLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS BLOB <left paren> <large object length> <right paren>

<Fortran XML CLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS CLOB <left paren> <character large object length> <right paren>
    [ CHARACTER SET [ IS ] <character set specification> ]
```

Syntax Rules

- 1) **Insert after SR 5)g)xi):** If *FTS* contains <Fortran XML CLOB variable>, then the <host parameter data type> of *HV* is CHARACTER LARGE OBJECT with the maximum length specified by the <character large object length> and character set specified by <character set specification>. If <character set specification> is not specified, then an implementation-defined (ID217) <character set specification> is implicit.
- 2) **Insert after SR 5)g)xi):** If *FTS* contains <Fortran XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT with the maximum length specified by the <large object length> contained in *FTS*.
- 3) **Insert after SR 6)d):** The syntax

```
SQL TYPE IS XML XO XWO AS CLOB ( L )
CHARACTER SET IS CS
```

for a given <Fortran host identifier> *HVN* shall be replaced by

```
CHARACTER HVN (L+8)
INTEGER*4 HVN_RESERVED
INTEGER*4 HVN_LENGTH
CHARACTER HVN_DATA * LL
EQUIVALENCE (HVN(1), HVN_RESERVED)
EQUIVALENCE (HVN(5), HVN_LENGTH)
EQUIVALENCE (HVN(9), HVN_DATA)
```

in any <Fortran XML CLOB variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”, and the value of *LL* is $NV \cdot k$.

- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML CLOB host variable. *L* is the length of XML CLOB host variable. *CS* is the character set of XML CLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise *XO* is the XML option of XML CLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise *XWO* is the XML whitespace option of the XML CLOB host variable.

NOTE 95 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 4) Insert after SR 6)d): The syntax

```
SQL TYPE IS XML XO XWO AS BLOB ( L )
```

for a given <Fortran host identifier> *HVN* shall be replaced by

```
CHARACTER HVN ( L+8 )
INTEGER*4 HVN_RESERVED
INTEGER*4 HVN_LENGTH
CHARACTER HVN_DATA * L
EQUIVALENCE ( HVN(1), HVN_RESERVED )
EQUIVALENCE ( HVN(5), HVN_LENGTH )
EQUIVALENCE ( HVN(9), HVN_DATA )
```

in any <Fortran XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

HVN is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise *XWO* is the XML whitespace option of the XML BLOB host variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <Fortran XML CLOB variable>.
- 2) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Fortran XML CLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 3) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Fortran XML CLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 4) **Insert after the last CR:** Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain a <Fortran XML BLOB variable>.
- 5) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Fortran XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 6) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Fortran XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 7) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Fortran XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Fortran XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Fortran XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Fortran XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

18.6 <embedded SQL Pascal program>

This Subclause modifies Subclause 21.8, “<embedded SQL Pascal program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL Pascal program>.

Format

```
<Pascal derived type specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <Pascal XML CLOB variable>
    | <Pascal XML BLOB variable>

<Pascal XML CLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS CLOB <left paren> <character large object length> <right paren>
    [ CHARACTER SET [ IS ] <character set specification> ]

<Pascal XML BLOB variable> ::=
    SQL TYPE IS XML [ <document or content> ]
    [ <XML whitespace option> ]
    AS BLOB <left paren> <large object length> <right paren>
```

Syntax Rules

- 1) Insert after SR 4)f)x): If *PTS* is <Pascal XML CLOB variable>, then the <host parameter data type> of *HV* is CHARACTER LARGE OBJECT with maximum length specified by the <character large object length> contained in *PTS* and character set specified by the <character set specification> contained in *PTS*. If <character set specification> is not specified, then the character set is implementation-defined (ID217).
- 2) Insert after SR 4)f)x): If *PTS* is <Pascal XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT with maximum length specified by the <large object length> contained in *PTS*.
- 3) Insert after SR 5)f): The syntax

```
SQL TYPE IS XML XO XWO AS CLOB ( L )
CHARACTER SET IS CS
```

for a given <Pascal host identifier> *HVN* shall be replaced by

```
VAR HVN = RECORD
    HVN_RESERVED : INTEGER ;
    HVN_LENGTH : INTEGER ;
    HVN_DATA : PACKED ARRAY [ 1..LL ] OF CHAR ;
END ;
```

in any <Pascal XML CLOB variable>, where:

- a) *NV* is the numeric value of *L* as specified in Subclause 6.1, “<data type>”, and the value of *LL* is $NV \cdot k$.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.

- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) *CS* is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML CLOB host variable. *L* is the length of XML CLOB host variable. *CS* is the character set of XML CLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise *XO* is the XML option of XML CLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise *XWO* is the XML whitespace option of the XML CLOB host variable.

NOTE 96 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 4) Insert after SR 5)f) The syntax

```
SQL TYPE IS XML XO XWO AS BLOB
( L )
```

for a given <Pascal host identifier> *HVN* shall be replaced by

```
VAR HVN = RECORD
  HVN_RESERVED : INTEGER ;
  HVN_LENGTH : INTEGER ;
  HVN_DATA : PACKED ARRAY [ 1..L ] OF CHAR ;
END ;
```

in any <Pascal XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

HVN is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise *XWO* is the XML whitespace option of the XML BLOB host variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <Pascal XML CLOB variable>.

- 2) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Pascal XML CLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 3) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Pascal XML CLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 4) **Insert after the last CR:** Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain a <Pascal XML BLOB variable>.
- 5) **Insert after the last CR:** Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <Pascal XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 6) **Insert after the last CR:** Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <Pascal XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.
- 7) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Pascal XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <Pascal XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Pascal XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <Pascal XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

18.7 <embedded SQL PL/I program>

This Subclause modifies Subclause 21.9, “<embedded SQL PL/I program>”, in ISO/IEC 9075-2.

Function

Specify an <embedded SQL PL/I program>.

Format

```
<PL/I derived type specification> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <PL/I XML VARCHAR variable>  
    | <PL/I XML CLOB variable>  
    | <PL/I XML BLOB variable>  
  
<PL/I XML VARCHAR variable> ::=  
    SQL TYPE IS XML [ <document or content> ]  
    [ <XML whitespace option> ]  
    AS VARCHAR <left paren> <character length> <right paren>  
    [ CHARACTER SET [ IS ] <character set specification> ]  
  
<PL/I XML CLOB variable> ::=  
    SQL TYPE IS XML [ <document or content> ]  
    [ <XML whitespace option> ]  
    AS CLOB <left paren> <character large object length> <right paren>  
    [ CHARACTER SET [ IS ] <character set specification> ]  
  
<PL/I XML BLOB variable> ::=  
    SQL TYPE IS XML [ <document or content> ]  
    [ <XML whitespace option> ]  
    AS BLOB <left paren> <large object length> <right paren>
```

Syntax Rules

- 1) **Insert after SR 4)e)xi):** If *PTS* contains <PL/I XML VARCHAR variable>, then the <host parameter data type> of *HV* is CHARACTER VARYING with maximum length specified by the <character length> contained in *PTS* and character set is specified by the <character set specification> contained in *PTS*. If <character set specification> is not specified, then an implementation-defined (ID217) <character set specification> is implicit.
- 2) **Insert after SR 4)e)xi):** If *PTS* contains <PL/I XML CLOB variable>, then the <host parameter data type> of *HV* is CHARACTER LARGE OBJECT with maximum length specified by the <character large object length> contained in *PTS* and with character set set specified by the <character set specification>. If <character set specification> is not specified, then an implementation-defined (ID217) <character set specification> is implicit.
- 3) **Insert after SR 4)e)xi):** If *PTS* contains <PL/I XML BLOB variable>, then the <host parameter data type> of *HV* is BINARY LARGE OBJECT with maximum length specified by the <large object length> contained in *PTS*.
- 4) **Insert after SR 5)d):** The syntax

```
SQL TYPE IS XML XO XWO AS VARCHAR (L)  
    CHARACTER SET IS CS
```

for a given <PL/I host identifier> *HVN* shall be replaced by:

CHARACTER VARYING (LL)

in any <PL/I XML VARCHAR variable>, where:

- a) NV is the numeric value of L as specified in Subclause 6.1, “<data type>”, and the value of LL is NV*k.
- b) XO is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) XWO is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) CS is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML VARCHAR host variable. L is the length of XML VARCHAR host variable. CS is the character set of XML VARCHAR host variable. If XO is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML VARCHAR host variable; otherwise XO is the XML option of XML VARCHAR host variable. If XWO is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML VARCHAR host variable; otherwise XWO is the XML whitespace option of the XML VARCHAR host variable.

NOTE 97 — The length of the XML VARCHAR host variable contains an implicit or explicit <char length units>.

- 5) Insert after SR 5)d): The syntax

```
SQL TYPE IS XML XO XWO AS CLOB ( L )
CHARACTER SET IS CS
```

for a given <PL/I host identifier> HVN shall be replaced by:

```
DCL 1 HVN
2 HVN_RESERVED FIXED BINARY (31),
2 HVN_LENGTH    FIXED BINARY (31),
2 HVN_DATA      CHARACTER ( LL );
```

in any <PL/I XML CLOB variable>, where:

- a) NV is the numeric value of L as specified in Subclause 6.1, “<data type>”, and the value of LL is NV*k.
- b) XO is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) XWO is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.
- d) CS is a <character set name> as specified in Subclause 5.3, “Names and identifiers”.

HVN is an XML CLOB host variable. L is the length of XML CLOB host variable. CS is the character set of XML CLOB host variable. If XO is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML CLOB host variable; otherwise XO is the XML option of XML CLOB host variable. If XWO is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML CLOB host variable; otherwise XWO is the XML whitespace option of the XML CLOB host variable.

NOTE 98 — The length of the XML CLOB host variable contains an implicit or explicit <char length units>.

- 6) Insert after SR 5)d): The syntax

```
SQL TYPE IS XML XO XWO AS BLOB ( L )
```

for a given <PL/I host identifier> *HVN* shall be replaced by:

```
DCL 1 HVN
  2 HVN_RESERVED FIXED BINARY (31),
  2 HVN_LENGTH   FIXED BINARY (31),
  2 HVN_DATA     CHARACTER ( L );
```

in any <PL/I XML BLOB variable>, where:

- a) *L* is the numeric value of <large object length> as specified in Subclause 6.1, “<data type>”.
- b) *XO* is either <document or content> as specified in Subclause 6.9, “<string value function>”, or the zero-length string.
- c) *XWO* is either <XML whitespace option> as specified in Subclause 6.17, “<XML parse>”, or the zero-length string.

HVN is an XML BLOB host variable. *L* is the length of XML BLOB host variable. If *XO* is the zero-length string, then it is implementation-defined (ID218) whether DOCUMENT or CONTENT is the XML option of XML BLOB host variable; otherwise *XO* is the XML option of XML BLOB host variable. If *XWO* is the zero-length string, then it is implementation-defined (IA131) whether STRIP WHITESPACE or PRESERVE WHITESPACE is the XML whitespace option of the XML BLOB host variable; otherwise *XWO* is the XML whitespace option of the XML BLOB host variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Insert after the last CR: Without Feature X110, “Host language support for XML: VARCHAR mapping”, conforming SQL language shall not contain a <PL/I XML VARCHAR variable>.
- 2) Insert after the last CR: Without Feature X111, “Host language support for XML: CLOB mapping”, conforming SQL language shall not contain a <PL/I XML CLOB variable>.
- 3) Insert after the last CR: Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, neither <PL/I XML VARCHAR variable> nor <PL/I XML CLOB variable> shall immediately contain a <document or content> that is CONTENT.
- 4) Insert after the last CR: Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, neither <PL/I XML VARCHAR variable> nor <PL/I XML CLOB variable> shall immediately contain a <document or content> that is DOCUMENT.
- 5) Insert after the last CR: Without Feature X112, “Host language support for XML: BLOB mapping”, conforming SQL language shall not contain a <PL/I XML BLOB variable>.
- 6) Insert after the last CR: Without Feature X100, “Host language support for XML: CONTENT option”, in conforming SQL language, <PL/I XML BLOB variable> shall not immediately contain a <document or content> that is CONTENT.
- 7) Insert after the last CR: Without Feature X101, “Host language support for XML: DOCUMENT option”, in conforming SQL language, <PL/I XML BLOB variable> shall not immediately contain a <document or content> that is DOCUMENT.

- 8) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <PL/I XML CLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 9) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <PL/I XML BLOB variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 10) **Insert after the last CR:** Without Feature X113, “Host language support for XML: STRIP WHITESPACE option”, in conforming SQL language, <PL/I XML VARCHAR variable> shall not immediately contain an <XML whitespace option> that is STRIP WHITESPACE.
- 11) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <PL/I XML CLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 12) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <PL/I XML BLOB variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.
- 13) **Insert after the last CR:** Without Feature X114, “Host language support for XML: PRESERVE WHITESPACE option”, in conforming SQL language, <PL/I XML VARCHAR variable> shall not immediately contain an <XML whitespace option> that is PRESERVE WHITESPACE.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

19 Call-Level Interface specifications

This Clause modifies Clause 6, “Call-Level Interface specifications”, in ISO/IEC 9075-3.

19.1 SQL/CLI data type correspondences

This Subclause modifies Subclause 6.19, “SQL/CLI data type correspondences”, in ISO/IEC 9075-3.

Function

Specify the SQL/CLI data type correspondences for SQL data types and host language types associated with the required parameter mechanisms, as shown in Table 3, “Supported calling conventions of SQL/CLI routines by language”, in ISO/IEC 9075-3.

Tables

Insert into Table 39, “SQL/CLI data type correspondences for Ada” the rows of Table 13, “SQL/CLI data type correspondences for Ada”.

Table 13 — SQL/CLI data type correspondences for Ada

SQL Data Type	Ada Data Type
XML	None

Insert into Table 40, “SQL/CLI data type correspondences for C” the rows of Table 14, “SQL/CLI data type correspondences for C”.

Table 14 — SQL/CLI data type correspondences for C

SQL Data Type	C Data Type
XML	None

Insert into Table 41, “SQL/CLI data type correspondences for COBOL” the rows of Table 15, “SQL/CLI data type correspondences for COBOL”.

Table 15 — SQL/CLI data type correspondences for COBOL

SQL Data Type	COBOL Data Type
XML	None

Insert into Table 42, “SQL/CLI data type correspondences for Fortran” the rows of Table 16, “SQL/CLI data type correspondences for Fortran”.

Table 16 — SQL/CLI data type correspondences for Fortran

SQL Data Type	Fortran Data Type
XML	<i>None</i>

Insert into Table 43, “SQL/CLI data type correspondences for M” the rows of Table 17, “SQL/CLI data type correspondences for M”.

Table 17 — SQL/CLI data type correspondences for M

SQL Data Type	MUMPS Data Type
XML	<i>None</i>

Insert into Table 44, “SQL/CLI data type correspondences for Pascal” the rows of Table 18, “SQL/CLI data type correspondences for Pascal”.

Table 18 — SQL/CLI data type correspondences for Pascal

SQL Data Type	Pascal Data Type
XML	<i>None</i>

Insert into Table 45, “SQL/CLI data type correspondences for PL/I” the rows of Table 19, “SQL/CLI data type correspondences for PL/I”.

Table 19 — SQL/CLI data type correspondences for PL/I

SQL Data Type	PL/I Data Type
XML	<i>None</i>

20 Diagnostics management

This Clause modifies Clause 23, “Diagnostics management”, in ISO/IEC 9075-2.

20.1 <get diagnostics statement>

This Subclause modifies Subclause 23.1, “<get diagnostics statement>”, in ISO/IEC 9075-2.

Function

Get exception or completion condition information from the diagnostics area.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert into Table 39, “SQL-statement codes” the rows of Table 20, “SQL-statement codes”.

Table 20 — SQL-statement codes

SQL-statement	Identifier	Code
<set XML option statement>	SET XML OPTION	138

Conformance Rules

No additional Conformance Rules.

21 Information Schema

This Clause modifies Clause 6, “Information Schema”, in ISO/IEC 9075-11.

21.1 Information Schema digital artifact

This Subclause modifies Subclause 6.1, “Information Schema digital artifact”, in ISO/IEC 9075-11.

Insert after the 1st paragraph: These schema definition and manipulation statements are also available from the ISO website as a “digital artifact”. See <https://standards.iso.org/iso-iec/9075/-14/ed-6/en/> to download digital artifacts for this document. To download the schema definition and manipulation statements, select the file named `ISO_IEC_9075-14(E)_XML-schema-definition.sql`.

21.2 NCNAME domain

Function

Define a domain that contains an NCNAME.

Definition

```
CREATE DOMAIN NCNAME AS
  CHARACTER VARYING(L)
  CHARACTER SET CS;
GRANT USAGE ON NCNAME
  TO PUBLIC WITH GRANT OPTION;
```

Description

- 1) It is implementation-defined (IA130) whether this domain specifies all variable-length character string values that conform to the rules for formation and representation of an XML 1.0 NCName or an XML 1.1 NCName.

NOTE 99 — There is no way in SQL to specify a <domain constraint> that would be true for an XML 1.0 NCName or an XML 1.1 NCName and false for all other character string values.

- 2) *L* is the implementation-defined (IL200) maximum length of an XML 1.0 NCName or XML 1.1 NCName.
- 3) *CS* is an implementation-defined (IV233) character set whose character repertoire is UCS.

Conformance Rules

- 1) Without Feature F251, “Domain support”, conforming SQL language shall not reference the domain `INFORMATION_SCHEMA.NCNAME`.

21.3 URI domain

Function

Define a domain that contains a URI.

Definition

```
CREATE DOMAIN URI AS  
  CHARACTER VARYING(L)  
  CHARACTER SET CS;  
GRANT USAGE ON URI  
  TO PUBLIC WITH GRANT OPTION;
```

Description

- 1) This domain specifies all variable-length character string values that conform to the rules for formation and representation of an <XML URI>.
- 2) *L* is the implementation-defined (IL201) maximum length of an <XML URI>.
- 3) *CS* is an implementation-defined (IV233) character set whose character repertoire is UCS.

Conformance Rules

- 1) Without Feature F251, "Domain support", conforming SQL language shall not reference the domain INFORMATION_SCHEMA.URI.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

21.4 ATTRIBUTES view

This Subclause modifies Subclause 6.12, “ATTRIBUTES view”, in ISO/IEC 9075-11.

Function

Identify the attributes of user-defined types defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
DECLARED_DATA_TYPE, DECLARED_NUMERIC_PRECISION,  
DECLARED_NUMERIC_SCALE
```

the code:

```
,  
D1.XML_PRIMARY_MODIFIER, D1.XML_SECONDARY_MODIFIER,  
D1.XML_SCHEMA_CATALOG, D1.XML_SCHEMA_SCHEMA, D1.XML_SCHEMA_NAME,  
D1.XML_SCHEMA_NAMESPACE, D1.XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ATTRIBUTES:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ATTRIBUTES:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.5 COLUMNS view

This Subclause modifies Subclause 6.22, “COLUMNS view”, in ISO/IEC 9075-11.

Function

Identify the columns of tables defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
COALESCE (D1.DECLARED_NUMERIC_PRECISION, D2.DECLARED_NUMERIC_PRECISION)  
AS DECLARED_NUMERIC_PRECISION,  
COALESCE (D1.DECLARED_NUMERIC_SCALE, D2.DECLARED_NUMERIC_SCALE)  
AS DECLARED_NUMERIC_SCALE
```

the code:

```
,  
COALESCE (D1.XML_PRIMARY_MODIFIER, D2.XML_PRIMARY_MODIFIER) AS  
XML_PRIMARY_MODIFIER,  
COALESCE (D1.XML_SECONDARY_MODIFIER, D2.XML_SECONDARY_MODIFIER) AS  
XML_SECONDARY_MODIFIER,  
COALESCE (D1.XML_SCHEMA_CATALOG, D2.XML_SCHEMA_CATALOG) AS  
XML_SCHEMA_CATALOG,  
COALESCE (D1.XML_SCHEMA_SCHEMA, D2.XML_SCHEMA_SCHEMA) AS  
XML_SCHEMA_SCHEMA,  
COALESCE (D1.XML_SCHEMA_NAME, D2.XML_SCHEMA_NAME) AS  
XML_SCHEMA_NAME,  
COALESCE (D1.XML_SCHEMA_NAMESPACE, D2.XML_SCHEMA_NAMESPACE) AS  
XML_SCHEMA_NAMESPACE,  
COALESCE (D1.XML_SCHEMA_ELEMENT, D2.XML_SCHEMA_ELEMENT) AS  
XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.COLUMNS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.COLUMNS:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.6 DOMAINS view

This Subclause modifies Subclause 6.30, “DOMAINS view”, in ISO/IEC 9075-11.

Function

Identify the domains defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
DTD.DECLARED_DATA_TYPE, DTD.DECLARED_NUMERIC_PRECISION,  
DTD.DECLARED_NUMERIC_SCALE
```

the code:

```
,  
DTD.XML_PRIMARY_MODIFIER, DTD.XML_SECONDARY_MODIFIER,  
DTD.XML_SCHEMA_CATALOG, DTD.XML_SCHEMA_SCHEMA, DTD.XML_SCHEMA_NAME,  
DTD.XML_SCHEMA_NAMESPACE, DTD.XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.DOMAINS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.DOMAINS:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.7 ELEMENT_TYPES view

This Subclause modifies Subclause 6.31, “ELEMENT_TYPES view”, in ISO/IEC 9075-11.

Function

Identify the element types defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
DTD.DECLARED_DATA_TYPE, DTD.DECLARED_NUMERIC_PRECISION,  
DTD.DECLARED_NUMERIC_SCALE
```

the code:

```
,  
DTD.XML_PRIMARY_MODIFIER, DTD.XML_SECONDARY_MODIFIER,  
DTD.XML_SCHEMA_CATALOG, DTD.XML_SCHEMA_SCHEMA, DTD.XML_SCHEMA_NAME,  
DTD.XML_SCHEMA_NAMESPACE, DTD.XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ELEMENT_TYPES:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ELEMENT_TYPES:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.8 FIELDS view

This Subclause modifies Subclause 6.33, “FIELDS view”, in ISO/IEC 9075-11.

Function

Identify the field types defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
DTD.DECLARED_DATA_TYPE, DTD.DECLARED_NUMERIC_PRECISION,  
DTD.DECLARED_NUMERIC_SCALE
```

the code:

```
,  
DTD.XML_PRIMARY_MODIFIER, DTD.XML_SECONDARY_MODIFIER,  
DTD.XML_SCHEMA_CATALOG, DTD.XML_SCHEMA_SCHEMA, DTD.XML_SCHEMA_NAME,  
DTD.XML_SCHEMA_NAMESPACE, DTD.XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.FIELDS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.FIELDS:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.9 METHOD_SPECIFICATION_PARAMETERS view

This Subclause modifies Subclause 6.36, “METHOD_SPECIFICATION_PARAMETERS view”, in ISO/IEC 9075-11.

Function

Identify the SQL parameters of method specifications described in the METHOD_SPECIFICATIONS view that are accessible to a given user or role.

Definition

Insert into the Definition after

```
D.DECLARED_DATA_TYPE, D.DECLARED_NUMERIC_PRECISION,
D.DECLARED_NUMERIC_SCALE
```

the code:

```
,
D.XML_PRIMARY_MODIFIER, D.XML_SECONDARY_MODIFIER,
D.XML_SCHEMA_CATALOG, D.XML_SCHEMA_SCHEMA, D.XML_SCHEMA_NAME,
D.XML_SCHEMA_NAMESPACE, D.XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECIFICATION_PARAMETERS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECIFICATION_PARAMETERS:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

21.10 METHOD_SPECIFICATIONS view

This Subclause modifies Subclause 6.37, “METHOD_SPECIFICATIONS view”, in ISO/IEC 9075-11.

Function

Identify the SQL-invoked methods in the catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
D.DECLARED_DATA_TYPE, D.DECLARED_NUMERIC_PRECISION,  
D.DECLARED_NUMERIC_SCALE
```

the code:

```
,  
D.XML_PRIMARY_MODIFIER, D.XML_SECONDARY_MODIFIER,  
D.XML_SCHEMA_CATALOG, D.XML_SCHEMA_SCHEMA, D.XML_SCHEMA_NAME,  
D.XML_SCHEMA_NAMESPACE, D.XML_SCHEMA_ELEMENT,  
DT.XML_PRIMARY_MODIFIER AS RESULT_CAST_XML_PRIMARY_MODIFIER,  
DT.XML_SECONDARY_MODIFIER AS RESULT_CAST_XML_SECONDARY_MODIFIER,  
DT.XML_SCHEMA_CATALOG AS RESULT_CAST_XML_SCHEMA_CATALOG,  
DT.XML_SCHEMA_SCHEMA AS RESULT_CAST_XML_SCHEMA_SCHEMA,  
DT.XML_SCHEMA_NAME AS RESULT_CAST_XML_SCHEMA_NAME,  
DT.XML_SCHEMA_NAMESPACE AS RESULT_CAST_XML_SCHEMA_NAMESPACE,  
DT.XML_SCHEMA_ELEMENT AS RESULT_CAST_XML_SCHEMA_ELEMENT
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECIFICATIONS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
 - d) RESULT_CAST_XML_SCHEMA_CATALOG.
 - e) RESULT_CAST_XML_SCHEMA_SCHEMA.
 - f) RESULT_CAST_XML_SCHEMA_NAME.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECIFICATIONS:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.
 - c) RESULT_CAST_XML_SCHEMA_NAMESPACE.
 - d) RESULT_CAST_XML_SCHEMA_ELEMENT.

21.11 PARAMETERS view

This Subclause modifies Subclause 6.38, “PARAMETERS view”, in ISO/IEC 9075-11.

Function

Identify the SQL parameters of SQL-invoked routines defined in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
END AS PARAMETER_DEFAULT,  
DTD.TABLE_SEMANTICS, DTD.IS_PRUNABLE, DTD.HAS_PASS_THROUGH_COLUMNS
```

the code:

```
,  
DTD.XML_PRIMARY_MODIFIER, DTD.XML_SECONDARY_MODIFIER,  
DTD.XML_SCHEMA_CATALOG, DTD.XML_SCHEMA_SCHEMA, DTD.XML_SCHEMA_NAME,  
DTD.XML_SCHEMA_NAMESPACE, DTD.XML_SCHEMA_ELEMENT,  
DTD2.DATA_TYPE AS XML_CHAR_TYPE,  
DTD2.CHARACTER_MAXIMUM_LENGTH AS XML_CHAR_MAX_LEN,  
DTD2.CHARACTER_OCTET_LENGTH AS XML_CHAR_OCT_LEN,  
DTD2.CHARACTER_SET_CATALOG AS XML_CHAR_SET_CAT,  
DTD2.CHARACTER_SET_SCHEMA AS XML_CHAR_SET_SCH,  
DTD2.CHARACTER_SET_NAME AS XML_CHAR_SET_NAME,  
DTD2.COLLATION_CATALOG AS XML_CHAR_COLL_CAT,  
DTD2.COLLATION_SCHEMA AS XML_CHAR_COLL_SCH,  
DTD2.COLLATION_NAME AS XML_CHAR_COLL_NAME,  
DTD2.DTD_IDENTIFIER AS XML_CHAR_DTD_ID,  
P.XML_OPTION, P.XML_PASSING_MECHANISM
```

Insert into the Definition after

```
= ( DTD.OBJECT_CATALOG, DTD.OBJECT_SCHEMA, DTD.OBJECT_NAME,  
DTD.OBJECT_TYPE, DTD.DTD_IDENTIFIER )
```

the code:

```
LEFT JOIN  
DEFINITION_SCHEMA.DATA_TYPE_DESCRIPTOR DTD2  
ON ( P.SPECIFIC_CATALOG, P.SPECIFIC_SCHEMA, P.SPECIFIC_NAME,  
'ROUTINE', P.XML_STRING_DTD_IDENTIFIER )  
= ( DTD2.OBJECT_CATALOG, DTD2.OBJECT_SCHEMA, DTD2.OBJECT_NAME,  
DTD2.OBJECT_TYPE, DTD2.DTD_IDENTIFIER )
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.PARAMETERS:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.

- 2) Insert after [the last CR:](#) Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.PARAMETERS:
- a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

21.12 ROUTINES view

This Subclause modifies Subclause 6.55, “ROUTINES view”, in ISO/IEC 9075-11.

Function

Identify the SQL-invoked routines in this catalog that are accessible to a given user or role.

Definition

Insert into the Definition after

```
D.SCOPE_CATALOG, D.SCOPE_SCHEMA, D.SCOPE_NAME,  
D.MAXIMUM_CARDINALITY, D.DTD_IDENTIFIER,
```

the code:

```
D.XML_PRIMARY_MODIFIER, D.XML_SECONDARY_MODIFIER,  
D.XML_SCHEMA_CATALOG, D.XML_SCHEMA_SCHEMA, D.XML_SCHEMA_NAME,  
D.XML_SCHEMA_NAMESPACE, D.XML_SCHEMA_ELEMENT,
```

Insert into the Definition after

```
DT.MAXIMUM_CARDINALITY AS RESULT_CAST_MAX_CARDINALITY,  
DT.DTD_IDENTIFIER AS RESULT_CAST_DTD_IDENTIFIER,
```

the code:

```
DT.XML_PRIMARY_MODIFIER AS RESULT_CAST_XML_PRIMARY_MODIFIER,  
DT.XML_SECONDARY_MODIFIER AS RESULT_CAST_XML_SECONDARY_MODIFIER,  
DT.XML_SCHEMA_CATALOG AS RESULT_CAST_XML_SCHEMA_CATALOG,  
DT.XML_SCHEMA_SCHEMA AS RESULT_CAST_XML_SCHEMA_SCHEMA,  
DT.XML_SCHEMA_NAME AS RESULT_CAST_XML_SCHEMA_NAME,  
DT.XML_SCHEMA_NAMESPACE AS RESULT_CAST_XML_SCHEMA_NAMESPACE,  
DT.XML_SCHEMA_ELEMENT AS RESULT_CAST_XML_SCHEMA_ELEMENT,  
D2.DATA_TYPE AS XML_CHAR_TYPE,  
D2.CHARACTER_MAXIMUM_LENGTH AS XML_CHAR_MAX_LEN,  
D2.CHARACTER_OCTET_LENGTH AS XML_CHAR_OCT_LEN,  
D2.CHARACTER_SET_CATALOG AS XML_CHAR_SET_CAT,  
D2.CHARACTER_SET_SCHEMA AS XML_CHAR_SET_SCH,  
D2.CHARACTER_SET_NAME AS XML_CHAR_SET_NAME,  
D2.COLLATION_CATALOG AS XML_CHAR_COLL_CAT,  
D2.COLLATION_SCHEMA AS XML_CHAR_COLL_SCH,  
D2.COLLATION_NAME AS XML_CHAR_COLL_NAME,  
D2.DTD_IDENTIFIER AS XML_CHAR_DTD_ID,  
R.XML_OPTION, R.XML_RETURN_MECHANISM,
```

Insert into the Definition before

```
( ( DEFINITION_SCHEMA.ROUTINES AS R
```

the code:

```
(
```

Insert into the Definition before

```
WHERE ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME ) IS NULL
```

the code:

```
LEFT JOIN  
DEFINITION_SCHEMA.DATA_TYPE_DESCRIPTOR AS D2  
ON ( SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME,  
'ROUTINE', R.XML_STRING_DTD_IDENTIFIER )
```

= (D2.OBJECT_CATALOG, D2.OBJECT_SCHEMA, D2.OBJECT_NAME,
D2.OBJECT_TYPE, D2.DTD_IDENTIFIER))

NOTE 100 — The ROUTINES view contains three sets of columns that each describe a data type. The set of columns that are prefixed with “XML_” describes the associated string type, if any, of the result of the <SQL-invoked routine>, if its declared type is XML. The set of columns that are prefixed with “RESULT_CAST_” describes the data type specified in the <result cast>, if any, contained in the <SQL-invoked routine>. The third set of columns describes the data type specified in the <returns data type> contained in the <SQL-invoked routine>.

Conformance Rules

- 1) Insert after the last CR: Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ROUTINES:
 - a) XML_SCHEMA_CATALOG.
 - b) XML_SCHEMA_SCHEMA.
 - c) XML_SCHEMA_NAME.
 - d) RESULT_CAST_XML_SCHEMA_CATALOG.
 - e) RESULT_CAST_XML_SCHEMA_SCHEMA.
 - f) RESULT_CAST_XML_SCHEMA_NAME.
- 2) Insert after the last CR: Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ROUTINES:
 - a) XML_SCHEMA_NAMESPACE.
 - b) XML_SCHEMA_ELEMENT.
 - c) RESULT_CAST_XML_SCHEMA_NAMESPACE.
 - d) RESULT_CAST_XML_SCHEMA_ELEMENT.

21.13 XML_SCHEMA_ELEMENTS view

Function

Identify the global element declaration schema components defined in registered XML schemas that are accessible to a given user or role.

Definition

```
CREATE VIEW XML_SCHEMA_ELEMENTS AS
  SELECT XS.XML_SCHEMA_TARGET_NAMESPACE, XS.XML_SCHEMA_LOCATION,
         XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
         XE.XML_SCHEMA_NAMESPACE, XE.XML_SCHEMA_ELEMENT,
         XE.XML_SCHEMA_ELEMENT_IS_DETERMINISTIC
  FROM DEFINITION_SCHEMA.XML_SCHEMA_ELEMENTS AS XE
  JOIN DEFINITION_SCHEMA.XML_SCHEMAS AS XS
  USING ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME )
  WHERE ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
         XML_SCHEMA_NAME, 'XML_SCHEMA' )
        IN ( SELECT UP.OBJECT_CATALOG, UP.OBJECT_SCHEMA,
                 UP.OBJECT_NAME, UP.OBJECT_TYPE
             FROM DEFINITION_SCHEMA.USAGE_PRIVILEGES AS UP
             WHERE ( UP.GRANTEE IN ( 'PUBLIC', CURRENT_USER )
                   OR
                   UP.GRANTEE IN ( SELECT ROLE_NAME
                                   FROM ENABLED_ROLES ) ) )
        AND XML_SCHEMA_CATALOG =
        ( SELECT CATALOG_NAME
          FROM INFORMATION_SCHEMA_CATALOG_NAME );

GRANT SELECT ON TABLE XML_SCHEMA_ELEMENTS
  TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMA_ELEMENTS.
- 2) Without Feature F391 “Long identifiers”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMA_ELEMENTS.

21.14 XML_SCHEMA_NAMESPACES view

Function

Identify the namespaces that are defined in registered XML schemas that are accessible to a given user or role.

Definition

```
CREATE VIEW XML_SCHEMA_NAMESPACES AS
  SELECT XS.XML_SCHEMA_TARGET_NAMESPACE, XS.XML_SCHEMA_LOCATION,
         XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
         XSN.XML_SCHEMA_NAMESPACE,
         XSN.XML_SCHEMA_NAMESPACE_IS_DETERMINISTIC
  FROM DEFINITION_SCHEMA.XML_SCHEMA_NAMESPACES AS XSN
  JOIN DEFINITION_SCHEMA.XML_SCHEMAS AS XS
  USING ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME )
  WHERE ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
         XML_SCHEMA_NAME, 'XML SCHEMA' )
        IN ( SELECT UP.OBJECT_CATALOG, UP.OBJECT_SCHEMA,
                 UP.OBJECT_NAME, UP.OBJECT_TYPE
             FROM DEFINITION_SCHEMA.USAGE_PRIVILEGES AS UP
             WHERE ( UP.GRANTEE IN ( 'PUBLIC', CURRENT_USER )
                   OR
                     UP.GRANTEE IN ( SELECT ROLE_NAME
                                     FROM ENABLED_ROLES ) ) )
        AND XML_SCHEMA_CATALOG =
        ( SELECT CATALOG_NAME
          FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE XML_SCHEMA_NAMESPACES
  TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMA_NAMESPACES.
- 2) Without Feature F391 “Long identifiers”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMA_NAMESPACES.

21.15 XML_SCHEMAS view

Function

Identify the registered XML schemas that are accessible to a given user or role.

Definition

```
CREATE VIEW XML_SCHEMAS AS
  SELECT XML_SCHEMA_TARGET_NAMESPACE, XML_SCHEMA_LOCATION,
         XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
         XML_SCHEMA_IS_DETERMINISTIC, XML_SCHEMA_IS_PERMANENT
FROM DEFINITION_SCHEMA.XML_SCHEMAS
WHERE ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
        XML_SCHEMA_NAME, 'XML SCHEMA' )
IN ( SELECT UP.OBJECT_CATALOG, UP.OBJECT_SCHEMA,
          UP.OBJECT_NAME, UP.OBJECT_TYPE
      FROM DEFINITION_SCHEMA.USAGE_PRIVILEGES AS UP
      WHERE ( UP.GRANTEE IN ( 'PUBLIC', CURRENT_USER )
            OR
              UP.GRANTEE IN ( SELECT ROLE_NAME
                             FROM ENABLED_ROLES ) ) )
AND XML_SCHEMA_CATALOG =
  ( SELECT CATALOG_NAME
    FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE XML_SCHEMAS
TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMAS.
- 2) Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.XML_SCHEMAS:
 - a) SCHEMA_IS_DETERMINISTIC.
- 3) Without Feature F391, “Long identifiers”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMAS.

21.16 Short name views

This Subclause modifies Subclause 6.83, “Short name views”, in ISO/IEC 9075-11.

Function

Provide alternative views that use only identifiers that do not require Feature F391, “Long identifiers”.

Definition

Insert into the Definition after

```
CREATE VIEW ATTRIBUTES_S
( UDT_CATALOG,          UDT_SCHEMA,          UDT_NAME,
  ATTRIBUTE_NAME,      ORDINAL_POSITION,    ATTRIBUTE_DEFAULT,
  DATA_TYPE,          CHAR_MAX_LENGTH,     CHAR_OCTET_LENGTH,
  CHAR_SET_CATALOG,   CHAR_SET_SCHEMA,     CHARACTER_SET_NAME,
  COLLATION_CATALOG,  COLLATION_SCHEMA,    COLLATION_NAME,
  NUMERIC_PRECISION,  NUMERIC_PREC_RADIX,  NUMERIC_SCALE,
  DATETIME_PRECISION, INTERVAL_TYPE,        INTERVAL_PRECISION,
  ATT_UDT_CAT,        ATT_UDT_SCHEMA,      ATT_UDT_NAME,
  SCOPE_CATALOG,     SCOPE_SCHEMA,        SCOPE_NAME,
  MAX_CARDINALITY,   DTD_IDENTIFIER,      IS_DERIVED_REF_ATT,
  DECLARED_DATA_TYPE, DECLARED_NUM_PREC,   DECLARED_NUM_SCALE
```

the code:

```
,
XML_PRIMARY_MOD,      XML_SECONDARY_MOD,    XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA,   XML_SCHEMA_NAME,      XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.ATTRIBUTES;
```

the code:

```
,
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW COLUMNS_S
( TABLE_CATALOG,      TABLE_SCHEMA,        TABLE_NAME,
  COLUMN_NAME,         ORDINAL_POSITION,    COLUMN_DEFAULT,
  IS_NULLABLE,         DATA_TYPE,           CHAR_MAX_LENGTH,
  CHAR_OCTET_LENGTH,   NUMERIC_PRECISION,    NUMERIC_PREC_RADIX,
  NUMERIC_SCALE,       DATETIME_PRECISION,  INTERVAL_TYPE,
  INTERVAL_PRECISION, CHAR_SET_CATALOG,     CHAR_SET_SCHEMA,
  CHARACTER_SET_NAME,  COLLATION_CATALOG,    COLLATION_SCHEMA,
  COLLATION_NAME,      DOMAIN_CATALOG,       DOMAIN_SCHEMA,
  DOMAIN_NAME,         UDT_CATALOG,          UDT_SCHEMA,
  UDT_NAME,            SCOPE_CATALOG,        SCOPE_SCHEMA,
  SCOPE_NAME,          MAX_CARDINALITY,      DTD_IDENTIFIER,
  IS_SELF_REF,         IS_IDENTITY,           ID_GENERATION,
  ID_START,            ID_INCREMENT,         ID_MAXIMUM,
  ID_MINIMUM,          ID_CYCLE,              IS_GENERATED,
  GENERATION_EXPR,     IS_SYSPER_START,     IS_SYSPER_END,
  SYSPER_TSTMP_GEN,    IS_UPDATABLE,         DECLARED_DATA_TYPE,
  DECLARED_NUM_PREC,   DECLARED_NUM_SCALE
```

the code:

ISO/IEC 9075-14:2023(E)
21.16 Short name views

```
,  
XML_PRIMARY_MOD, XML_SECONDARY_MOD, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.COLUMNS;
```

the code:

```
,  
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW DOMAINS_S  
( DOMAIN_CATALOG, DOMAIN_SCHEMA, DOMAIN_NAME,  
DATA_TYPE, CHAR_MAX_LENGTH, CHAR_OCTET_LENGTH,  
CHAR_SET_CATALOG, CHAR_SET_SCHEMA, CHARACTER_SET_NAME,  
COLLATION_CATALOG, COLLATION_SCHEMA, COLLATION_NAME,  
NUMERIC_PRECISION, NUMERIC_PREC_RADIX, NUMERIC_SCALE,  
DATETIME_PRECISION, INTERVAL_TYPE, INTERVAL_PRECISION,  
DOMAIN_DEFAULT, MAX_CARDINALITY, DTD_IDENTIFIER,  
DECLARED_DATA_TYPE, DECLARED_NUM_PREC, DECLARED_NUM_SCALE
```

the code:

```
,  
XML_PRIMARY_MOD, XML_SECONDARY_MOD, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.DOMAINS;
```

the code:

```
,  
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW ELEMENT_TYPES_S  
( OBJECT_CATALOG, OBJECT_SCHEMA, OBJECT_NAME,  
OBJECT_TYPE, COLLECTION_TYPE_ID, DATA_TYPE,  
CHAR_MAX_LENGTH, CHAR_OCTET_LENGTH, CHAR_SET_CATALOG,  
CHAR_SET_SCHEMA, CHARACTER_SET_NAME, COLLATION_CATALOG,  
COLLATION_SCHEMA, COLLATION_NAME, NUMERIC_PRECISION,  
NUMERIC_PREC_RADIX, NUMERIC_SCALE, DATETIME_PRECISION,  
INTERVAL_TYPE, INTERVAL_PRECISION, UDT_CATALOG,  
UDT_SCHEMA, UDT_NAME, SCOPE_CATALOG,  
SCOPE_SCHEMA, SCOPE_NAME, MAX_CARDINALITY,  
DTD_IDENTIFIER, SCOPE_NAME, MAX_CARDINALITY,  
DECLARED_DATA_TYPE, DECLARED_NUM_PREC, DECLARED_NUM_SCALE
```

the code:

```
,  
XML_PRIMARY_MOD, XML_SECONDARY_MOD, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

FROM INFORMATION_SCHEMA.ELEMENT_TYPES;

the code:

```
,
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW FIELDS_S
( OBJECT_CATALOG,          OBJECT_SCHEMA,          OBJECT_NAME,
  OBJECT_TYPE,            ROW_IDENTIFIER,         FIELD_NAME,
  ORDINAL_POSITION,      DATA_TYPE,             CHAR_MAX_LENGTH,
  CHAR_OCTET_LENGTH,     CHAR_SET_CATALOG,      CHAR_SET_SCHEMA,
  CHARACTER_SET_NAME,    COLLATION_CATALOG,     COLLATION_SCHEMA,
  COLLATION_NAME,        NUMERIC_PRECISION,     NUMERIC_PREC_RADIX,
  NUMERIC_SCALE,         DATETIME_PRECISION,    INTERVAL_TYPE,
  INTERVAL_PRECISION,   UDT_CATALOG,           UDT_SCHEMA,
  UDT_NAME,              SCOPE_CATALOG,         SCOPE_SCHEMA,
  SCOPE_NAME,            MAX_CARDINALITY,      DTD_IDENTIFIER,
  DECLARED_DATA_TYPE,   DECLARED_NUM_PREC,    DECLARED_NUM_SCALE
```

the code:

```
,
XML_PRIMARY_MOD,        XML_SECONDARY_MOD,     XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA,     XML_SCHEMA_NAME,      XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

FROM INFORMATION_SCHEMA.FIELDS;

the code:

```
,
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW METHOD_SPECS
( SPECIFIC_CATALOG,      SPECIFIC_SCHEMA,       SPECIFIC_NAME,
  UDT_CATALOG,          UDT_SCHEMA,           UDT_NAME,
  METHOD_NAME,          IS_STATIC,             IS_OVERRIDING,
  IS_CONSTRUCTOR,      DATA_TYPE,           CHAR_MAX_LENGTH,
  CHAR_OCTET_LENGTH,   CHAR_SET_CATALOG,     CHAR_SET_SCHEMA,
  CHARACTER_SET_NAME,  COLLATION_CATALOG,    COLLATION_SCHEMA,
  COLLATION_NAME,      NUMERIC_PRECISION,    NUMERIC_PREC_RADIX,
  NUMERIC_SCALE,       DATETIME_PRECISION,   INTERVAL_TYPE,
  INTERVAL_PRECISION,  RETURN_UDT_CATALOG,   RETURN_UDT_SCHEMA,
  RETURN_UDT_NAME,     SCOPE_CATALOG,        SCOPE_SCHEMA,
  SCOPE_NAME,          MAX_CARDINALITY,     DTD_IDENTIFIER,
  METHOD_LANGUAGE,      PARAMETER_STYLE,      IS_DETERMINISTIC,
  SQL_DATA_ACCESS,     IS_NULL_CALL,         TO_SQL_SPEC_CAT,
  TO_SQL_SPEC_SCHEMA,  TO_SQL_SPEC_NAME,     AS_LOCATOR,
  CREATED,             RC_FROM_DATA_TYPE,    RC_AS_LOCATOR,
  RC_CHAR_MAX_LENGTH,  RC_CHAR_OCT_LENGTH,   RC_CHAR_SET_CAT,
  RC_CHAR_SET_SCHEMA,  RC_CHAR_SET_NAME,     RC_COLLATION_CAT,
  RC_COLLATION_SCH,    RC_COLLATION_NAME,    RC_NUMERIC_PREC,
  RC_NUMERIC_RADIX,    RC_NUMERIC_SCALE,     RC_DATETIME_PREC,
  RC_INTERVAL_TYPE,   RC_INTERVAL_PREC,     RC_TYPE_UDT_CAT,
  RC_TYPE_UDT_SCHEMA,  RC_TYPE_UDT_NAME,     RC_SCOPE_CATALOG,
  RC_SCOPE_SCHEMA,     RC_SCOPE_NAME,        RC_MAX_CARDINALITY,
  RC_DTD_IDENTIFIER,   DECLARED_DATA_TYPE,   DECLARED_NUM_PREC,
  DECLARED_NUM_SCALE
```

ISO/IEC 9075-14:2023(E) 21.16 Short name views

the code:

```
,  
XML_PRIMARY_MOD, XML_SECONDARY_MOD, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT, RC_XML_PRIMARY_MOD, RC_XML_SECOND_MOD,  
RC_XML_SCHEMA_CAT, RC_XML_SCH_SCH, RC_XML_SCH_NAME,  
RC_XML_SCH_NAMESPACE, RC_XML_SCH_ELEMENT
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.METHOD_SPECIFICATIONS;
```

the code:

```
,  
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT, RESULT_CAST_XML_PRIMARY_MODIFIER,  
RESULT_CAST_XML_SECONDARY_MODIFIER,  
RESULT_CAST_XML_SCHEMA_CATALOG, RESULT_CAST_XML_SCHEMA_SCHEMA,  
RESULT_CAST_XML_SCHEMA_NAME, RESULT_CAST_XML_SCHEMA_NAMESPACE,  
RESULT_CAST_XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW METHOD_SPEC_PARAMS  
( SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME,  
ORDINAL_POSITION, PARAMETER_MODE, IS_RESULT,  
AS_LOCATOR, PARAMETER_NAME, FROM_SQL_SPEC_CAT,  
FROM_SQL_SPEC_SCH, FROM_SQL_SPEC_NAME, DATA_TYPE,  
CHAR_MAX_LENGTH, CHAR_OCTET_LENGTH, CHAR_SET_CATALOG,  
CHAR_SET_SCHEMA, CHARACTER_SET_NAME, COLLATION_CATALOG,  
COLLATION_SCHEMA, COLLATION_NAME, NUMERIC_PRECISION,  
NUMERIC_PREC_RADIX, NUMERIC_SCALE, DATETIME_PRECISION,  
INTERVAL_TYPE, INTERVAL_PRECISION, PARM_UDT_CATALOG,  
PARM_UDT_SCHEMA, PARM_UDT_NAME, SCOPE_CATALOG,  
SCOPE_SCHEMA, SCOPE_NAME, MAX_CARDINALITY,  
DTD_IDENTIFIER,  
DECLARED_DATA_TYPE, DECLARED_NUM_PREC, DECLARED_NUM_SCALE
```

the code:

```
,  
XML_PRIMARY_MOD, XML_SECONDARY_MOD, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.METHOD_SPECIFICATION_PARAMETERS;
```

the code:

```
,  
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT
```

Insert into the Definition after

```
CREATE VIEW PARAMETERS_S  
( SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME,  
ORDINAL_POSITION, PARAMETER_MODE, IS_RESULT,  
AS_LOCATOR, PARAMETER_NAME, FROM_SQL_SPEC_CAT,  
FROM_SQL_SPEC_SCH, FROM_SQL_SPEC_NAME, TO_SQL_SPEC_CAT,  
TO_SQL_SPEC_SCHEMA, TO_SQL_SPEC_NAME, DATA_TYPE,  
CHAR_MAX_LENGTH, CHAR_OCTET_LENGTH, CHAR_SET_CATALOG,  
CHAR_SET_SCHEMA, CHARACTER_SET_NAME, COLLATION_CATALOG,
```

```
COLLATION_SCHEMA, COLLATION_NAME, NUMERIC_PRECISION,
NUMERIC_PREC_RADIX, NUMERIC_SCALE, DATETIME_PRECISION,
INTERVAL_TYPE, INTERVAL_PRECISION, UDT_CATALOG,
UDT_SCHEMA, UDT_NAME, SCOPE_CATALOG,
SCOPE_SCHEMA, SCOPE_NAME, MAX_CARDINALITY,
DTD_IDENTIFIER, DECLARED_DATA_TYPE, DECLARED_NUM_PREC,
DECLARED_NUM_SCALE, PARAMETER_DEFAULT, TABLE_SEMANTICS,
IS_PRUNABLE, HAS_PASS_THRU_COLS
```

the code:

```
, XML_PRIMARY_MOD, XML_SECONDARY_MOD,
XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
XML_SCHEMA_NAMESPACE, XML_SCHEMA_ELEMENT, XML_CHAR_TYPE,
XML_CHAR_MAX_LEN, XML_CHAR_OCT_LEN, XML_CHAR_SET_CAT,
XML_CHAR_SET_SCH, XML_CHAR_SET_NAME, XML_CHAR_COLL_CAT,
XML_CHAR_COLL_SCH, XML_CHAR_COLL_NAME, XML_CHAR_DTD_ID,
XML_OPTION, XML_PASSING_MECH
```

Insert into the Definition before

```
FROM INFORMATION_SCHEMA.PARAMETERS;
```

the code:

```
,
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER,
XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
XML_SCHEMA_NAMESPACE, XML_SCHEMA_ELEMENT, XML_CHAR_TYPE,
XML_CHAR_MAX_LEN, XML_CHAR_OCT_LEN, XML_CHAR_SET_CAT,
XML_CHAR_SET_SCH, XML_CHAR_SET_NAME, XML_CHAR_COLL_CAT,
XML_CHAR_COLL_SCH, XML_CHAR_COLL_NAME, XML_CHAR_DTD_ID,
XML_OPTION, XML_PASSING_MECHANISM
```

Insert into the Definition after

```
CREATE VIEW ROUTINES_S
( SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME,
ROUTINE_CATALOG, ROUTINE_SCHEMA, ROUTINE_NAME,
ROUTINE_TYPE, MODULE_CATALOG, MODULE_SCHEMA,
MODULE_NAME, UDT_CATALOG, UDT_SCHEMA,
UDT_NAME, DATA_TYPE, CHAR_MAX_LENGTH,
CHAR_OCTET_LENGTH, CHAR_SET_CATALOG, CHAR_SET_SCHEMA,
CHARACTER_SET_NAME, COLLATION_CATALOG, COLLATION_SCHEMA,
COLLATION_NAME, NUMERIC_PRECISION, NUMERIC_PREC_RADIX,
NUMERIC_SCALE, DATETIME_PRECISION, INTERVAL_TYPE,
INTERVAL_PRECISION, TYPE_UDT_CATALOG, TYPE_UDT_SCHEMA,
TYPE_UDT_NAME, SCOPE_CATALOG, SCOPE_SCHEMA,
SCOPE_NAME, MAX_CARDINALITY, DTD_IDENTIFIER,
```

the code:

```
XML_PRIMARY_MOD, XML_SECONDD_MOD,
XML_SCHEMA_CAT, XML_SCH_SCH, XML_SCH_NAME,
XML_SCH_NAMESPACE, XML_SCH_ELEMENT,
```

Insert into the Definition after

```
IS_UDT_DEPENDENT, RC_FROM_DATA_TYPE, RC_AS_LOCATOR,
RC_CHAR_MAX_LENGTH, RC_CHAR_OCT_LENGTH, RC_CHAR_SET_CAT,
RC_CHAR_SET_SCHEMA, RC_CHAR_SET_NAME, RC_COLLATION_CAT,
RC_COLLATION_SCH, RC_COLLATION_NAME, RC_NUM_PREC,
RC_NUMERIC_RADIX, RC_NUMERIC_SCALE, RC_DATETIME_PREC,
RC_INTERVAL_TYPE, RC_INTERVAL_PREC, RC_TYPE_UDT_CAT,
RC_TYPE_UDT_SCHEMA, RC_TYPE_UDT_NAME, RC_SCOPE_CATALOG,
RC_SCOPE_SCHEMA, RC_SCOPE_NAME, RC_MAX_CARDINALITY,
RC_DTD_IDENTIFIER,
```

the code:

ISO/IEC 9075-14:2023(E) 21.16 Short name views

```
RC_XML_PRIMARY_MOD, RC_XML_SECOND_MOD, RC_XML_SCHEMA_CAT,  
RC_XML_SCH_SCH, RC_XML_SCH_NAME, RC_XML_SCH_NAMESPACE,  
RC_XML_SCH_ELEMENT, XML_CHAR_TYPE, XML_CHAR_MAX_LEN,  
XML_CHAR_OCT_LEN, XML_CHAR_SET_CAT, XML_CHAR_SET_SCH,  
XML_CHAR_SET_NAME, XML_CHAR_COLL_CAT, XML_CHAR_COLL_SCH,  
XML_CHAR_COLL_NAME, XML_CHAR_DTD_ID, XML_OPTION,  
XML_RETURN_MECH,
```

Insert into the Definition after

```
SCOPE_NAME, MAXIMUM_CARDINALITY,  
DTD_IDENTIFIER,
```

the code:

```
XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER,  
XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,  
XML_SCHEMA_NAMESPACE, XML_SCHEMA_ELEMENT,
```

Insert into the Definition after

```
RESULT_CAST_SCOPE_SCHEMA, RESULT_CAST_SCOPE_NAME,  
RESULT_CAST_MAX_CARDINALITY,  
RESULT_CAST_DTD_IDENTIFIER,
```

the code:

```
RESULT_CAST_XML_PRIMARY_MODIFIER,  
RESULT_CAST_XML_SECONDARY_MODIFIER,  
RESULT_CAST_XML_SCHEMA_CATALOG, RESULT_CAST_XML_SCHEMA_SCHEMA,  
RESULT_CAST_XML_SCHEMA_NAME, RESULT_CAST_XML_SCHEMA_NAMESPACE,  
RESULT_CAST_XML_SCHEMA_ELEMENT, XML_CHAR_TYPE, XML_CHAR_MAX_LEN,  
XML_CHAR_OCT_LEN, XML_CHAR_SET_CAT, XML_CHAR_SET_SCH,  
XML_CHAR_SET_NAME, XML_CHAR_COLL_CAT, XML_CHAR_COLL_SCH,  
XML_CHAR_COLL_NAME, XML_CHAR_DTD_ID, XML_OPTION,  
XML_RETURN_MECHANISM,
```

Insert into the Definition after

```
GRANT SELECT ON TABLE VIEWS_S  
TO PUBLIC WITH GRANT OPTION;
```

the code:

```
CREATE VIEW XML_SCH_ELEMENTS_S  
( XML_SCH_TGT_NAMESPACE, XML_SCH_LOCATION, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCH_NAMESPACE,  
XML_SCHEMA_ELEMENT, XML_SCH_EL_IS_DET ) AS  
SELECT XML_SCHEMA_TARGET_NAMESPACE, XML_SCHEMA_LOCATION, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT, XML_SCHEMA_ELEMENT_IS_DETERMINISTIC  
FROM INFORMATION_SCHEMA.XML_SCHEMA_ELEMENTS;
```

```
GRANT SELECT ON TABLE XML_SCH_ELEMENTS_S  
TO PUBLIC WITH GRANT OPTION;
```

```
CREATE VIEW XML_SCH_NAMESPACES_S  
( XML_SCH_TGT_NAMESPACE, XML_SCH_LOCATION, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCH_NAMESPACE,  
XML_SCH_NSP_IS_DET ) AS  
SELECT XML_SCHEMA_TARGET_NAMESPACE, XML_SCHEMA_LOCATION, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_NAMESPACE_IS_DETERMINISTIC  
FROM INFORMATION_SCHEMA.XML_SCHEMA_NAMESPACES;
```

```
GRANT SELECT ON TABLE XML_SCH_NAMESPACES_S  
TO PUBLIC WITH GRANT OPTION;
```

```
CREATE VIEW XML_SCHEMAS_S
( XML_SCH_TGT_NAMESPACE, XML_SCH_LOCATION, XML_SCHEMA_CATALOG,
  XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_IS_DET,
  XML_SCHEMA_IS_PERM ) AS
SELECT XML_SCHEMA_TARGET_NAMESPACE, XML_SCHEMA_LOCATION, XML_SCHEMA_CATALOG,
  XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_IS_DETERMINISTIC,
  XML_SCHEMA_IS_PERMANENT
FROM INFORMATION_SCHEMA.XML_SCHEMAS;

GRANT SELECT ON TABLE XML_SCHEMAS_S
TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCHEMAS_S.
- 2) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCH_ELEMENTS_S.
- 3) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the view INFORMATION_SCHEMA.XML_SCH_NAMESPACES_S.
- 4) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.XML_SCHEMAS_S:
 - a) XML_SCHEMA_IS_DET.
- 5) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ATTRIBUTES_S:
 - a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME
- 6) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ATTRIBUTES_S:
 - a) XML_SCHEMA_NAMESPACE
 - b) XML_SCHEMA_ELEMENT
- 7) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.COLUMNS_S:
 - a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME

- 8) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.COLUMNS_S:
- XML_SCHEMA_NAMESPACE
 - XML_SCHEMA_ELEMENT
- 9) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.DOMAINS_S:
- XML_SCHEMA_CATALOG
 - XML_SCHEMA_SCHEMA
 - XML_SCHEMA_NAME
- 10) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.DOMAINS_S:
- XML_SCHEMA_NAMESPACE
 - XML_SCHEMA_ELEMENT
- 11) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ELEMENT_TYPES_S:
- XML_SCHEMA_CATALOG
 - XML_SCHEMA_SCHEMA
 - XML_SCHEMA_NAME
- 12) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ELEMENT_TYPES_S:
- XML_SCHEMA_NAMESPACE
 - XML_SCHEMA_ELEMENT
- 13) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.FIELDS_S:
- XML_SCHEMA_CATALOG
 - XML_SCHEMA_SCHEMA
 - XML_SCHEMA_NAME
- 14) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.FIELDS_S:
- XML_SCHEMA_NAMESPACE
 - XML_SCHEMA_ELEMENT

- 15) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPEC_PARAMS_S:
- a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME
- 16) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPEC_PARAMS_S:
- a) XML_SCHEMA_NAMESPACE
 - b) XML_SCHEMA_ELEMENT
- 17) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECS_S:
- a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME
 - d) RESULT_CAST_XML_SCHEMA_CATALOG
 - e) RESULT_CAST_XML_SCHEMA_SCHEMA
 - f) RESULT_CAST_XML_SCHEMA_NAME
- 18) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.METHOD_SPECS_S:
- a) XML_SCHEMA_NAMESPACE
 - b) XML_SCHEMA_ELEMENT
 - c) RESULT_CAST_XML_SCHEMA_NAMESPACE
 - d) RESULT_CAST_XML_SCHEMA_ELEMENT
- 19) **Insert after the last CR:** Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.PARAMETERS_S:
- a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME
- 20) **Insert after the last CR:** Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.PARAMETERS_S:
- a) XML_SCHEMA_NAMESPACE
 - b) XML_SCHEMA_ELEMENT

21.16 Short name views

- 21) Insert after the last CR: Without Feature X160, “Basic Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ROUTINES_S:
- a) XML_SCHEMA_CATALOG
 - b) XML_SCHEMA_SCHEMA
 - c) XML_SCHEMA_NAME
 - d) RESULT_CAST_XML_SCHEMA_CATALOG
 - e) RESULT_CAST_XML_SCHEMA_SCHEMA
 - f) RESULT_CAST_XML_SCHEMA_NAME
- 22) Insert after the last CR: Without Feature X161, “Advanced Information Schema for registered XML schemas”, conforming SQL language shall not reference the following columns in the view INFORMATION_SCHEMA.ROUTINES_S:
- a) XML_SCHEMA_NAMESPACE
 - b) XML_SCHEMA_ELEMENT
 - c) RESULT_CAST_XML_SCHEMA_NAMESPACE
 - d) RESULT_CAST_XML_SCHEMA_ELEMENT

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

22 Definition Schema

This Clause modifies Clause 7, “Definition Schema”, in ISO/IEC 9075-11.

22.1 Definition Schema digital artifact

This Subclause modifies Subclause 7.1, “Definition Schema digital artifact”, in ISO/IEC 9075-11.

Insert after the 1st paragraph: These schema definition and manipulation statements are also available from the ISO website as a “digital artifact”. See <https://standards.iso.org/iso-iec/9075/-14/ed-6/en/> to download digital artifacts for this document. To download the schema definition and manipulation statements, select the file named ISO_IEC_9075-14(E)_XML-schema-definition.sql.

22.2 DATA_TYPE_DESCRIPTOR base table

This Subclause modifies Subclause 7.23, “DATA_TYPE_DESCRIPTOR base table”, in ISO/IEC 9075-11.

Function

The DATA_TYPE_DESCRIPTOR table has one row for each usage of a datatype as identified by the ISO/IEC 9075 series. It effectively contains a representation of the data type descriptors.

Definition

Insert into the Definition before

```
CONSTRAINT DATA_TYPE_DESCRIPTOR_DATA_TYPE_CHECK_COMBINATIONS
```

the code:

XML_PRIMARY_MODIFIER	INFORMATION_SCHEMA.CHARACTER_DATA,
XML_SECONDARY_MODIFIER	INFORMATION_SCHEMA.CHARACTER_DATA,
XML_SCHEMA_CATALOG	INFORMATION_SCHEMA.SQL_IDENTIFIER,
XML_SCHEMA_SCHEMA	INFORMATION_SCHEMA.SQL_IDENTIFIER,
XML_SCHEMA_NAME	INFORMATION_SCHEMA.SQL_IDENTIFIER,
XML_SCHEMA_NAMESPACE	INFORMATION_SCHEMA.URI,
XML_SCHEMA_ELEMENT	INFORMATION_SCHEMA.NCNAME,

Insert into the Definition before

```
)
OR
( DATA_TYPE IN
( 'BINARY', 'BINARY VARYING', 'BINARY LARGE OBJECT' )
```

the code:

```
AND
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
)
```

ISO/IEC 9075-14:2023(E)
22.2 DATA_TYPE_DESCRIPTOR base table

```
OR  
  ( DATA_TYPE IN  
    ( 'SMALLINT', 'INTEGER', 'BIGINT' )
```

the code:

```
AND  
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
  ( DATA_TYPE IN  
    ( 'NUMERIC', 'DECIMAL' )
```

the code:

```
AND  
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
  ( DATA_TYPE IN  
    ( 'REAL', 'DOUBLE PRECISION', 'FLOAT' )
```

the code:

```
AND  
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
  ( DATA_TYPE = 'DECFLOAT'
```

the code:

```
AND  
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
  ( DATA_TYPE IN  
    ( 'DATE', 'TIME', 'TIMESTAMP',  
      'TIME WITH TIME ZONE', 'TIMESTAMP WITH TIME ZONE' )
```

the code:

```
AND  
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'INTERVAL'
```

the code:

```
AND  
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'BOOLEAN'
```

the code:

```
AND  
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'USER-DEFINED'
```

the code:

```
AND  
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'REF'
```

the code:

```
AND  
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'ARRAY'
```

the code:

```
AND  
( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,  
XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,  
XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

)

```
OR  
( DATA_TYPE = 'MULTISET'
```

the code:

ISO/IEC 9075-14:2023(E)

22.2 DATA_TYPE_DESCRIPTOR base table

```
AND
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
)
OR
  ( DATA_TYPE = 'ROW'
```

the code:

```
AND
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
)
OR
  ( DATA_TYPE = 'TABLE'
```

the code:

```
AND
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
)
OR
  ( DATA_TYPE = 'DESCRIPTOR'
```

the code:

```
AND
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
)
OR
  ( DATA_TYPE = 'JSON'
```

the code:

```
AND
  ( XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG,
    XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
    XML_SCHEMA_ELEMENT ) IS NULL
```

Insert into the Definition before

```
OR
  ( DATA_TYPE NOT IN
    ( 'CHARACTER', 'CHARACTER VARYING',
```

the code:

```
OR
  ( DATA_TYPE = 'XML'
  AND
    ( XML_PRIMARY_MODIFIER IN ( 'DOCUMENT', 'CONTENT', 'SEQUENCE' ) )
```

```

AND
  ( XML_SECONDARY_MODIFIER IN ( 'UNTYPED', 'ANY', 'XMLSCHEMA' ) )
AND
  XML_PRIMARY_MODIFIER IS NOT NULL
AND
  ( XML_PRIMARY_MODIFIER NOT IN ( 'DOCUMENT', 'CONTENT' )
  OR
    XML_SECONDARY_MODIFIER IS NOT NULL )
AND
  ( XML_SECONDARY_MODIFIER <> 'XMLSCHEMA'
  OR
    ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME ) IS NULL )
AND
  ( CHARACTER_SET_CATALOG, CHARACTER_SET_SCHEMA, CHARACTER_SET_NAME,
  CHARACTER_OCTET_LENGTH, CHARACTER_MAXIMUM_LENGTH,
  COLLATION_CATALOG, COLLATION_SCHEMA, COLLATION_NAME )
  IS NULL
AND
  ( NUMERIC_PRECISION, NUMERIC_PRECISION_RADIX, NUMERIC_SCALE,
  DECLARED_DATA_TYPE, DECLARED_NUMERIC_PRECISION,
  DECLARED_NUMERIC_SCALE ) IS NULL
AND
  DATETIME_PRECISION IS NULL
AND
  ( INTERVAL_TYPE, INTERVAL_PRECISION )
  IS NULL
AND
  ( USER_DEFINED_TYPE_CATALOG, USER_DEFINED_TYPE_SCHEMA,
  USER_DEFINED_TYPE_NAME ) IS NULL
AND
  ( SCOPE_CATALOG, SCOPE_SCHEMA, SCOPE_NAME ) IS NULL
AND
  MAXIMUM_CARDINALITY IS NULL )

```

Insert into the Definition after

```

'REF', 'ROW', 'ARRAY', 'MULTISET',
'TABLE', 'DESCRIPTOR'

```

the code:

```

, 'XML'

```

Insert into the Definition after

```

);

```

the code:

```

ALTER TABLE DATA_TYPE_DESCRIPTOR
  ADD CONSTRAINT
    DATA_TYPE_DESCRIPTOR_CHECK_REFERENCES_XML_SCHEMA_NAMESPACES
  CHECK ( XML_SCHEMA_CATALOG NOT IN
    ( SELECT CATALOG_NAME
      FROM SCHEMATA )
  OR
    ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
    XML_SCHEMA_NAMESPACE) IN
    ( SELECT XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
      XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE
      FROM XML_SCHEMA_NAMESPACES )
  );

```

```

ALTER TABLE DATA_TYPE_DESCRIPTOR
  ADD CONSTRAINT
    DATA_TYPE_DESCRIPTOR_CHECK_REFERENCES_XML_SCHEMA_ELEMENTS
  CHECK ( XML_SCHEMA_CATALOG NOT IN
    ( SELECT CATALOG_NAME
      FROM SCHEMATA )
  );

```

```

OR
( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,
  XML_SCHEMA_NAMESPACE, XML_SCHEMA_ELEMENT ) IN
( SELECT XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
         XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
         XML_SCHEMA_ELEMENT
  FROM XML_SCHEMA_ELEMENTS )
);

```

Description

1) Insert after the last Description: Case:

a) If DATA_TYPE is 'XML', then:

i) The value of XML_PRIMARY_MODIFIER is 'DOCUMENT', 'CONTENT', or 'SEQUENCE'.

ii) If the value of XML_PRIMARY_MODIFIER is either 'DOCUMENT' or 'CONTENT', then the value of XML_SECONDARY_MODIFIER is 'UNTYPED', 'ANY', or 'XMLSCHEMA'; otherwise, the value of XML_SECONDARY_MODIFIER is the null value.

iii) Case:

1) If the value of XML_SECONDARY_MODIFIER is 'XMLSCHEMA', then:

A) The values of XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, and XML_SCHEMA_NAME are the catalog name, the unqualified schema name, and the name of a registered XML schema, respectively, identified by the registered XML schema descriptor included in the XML type descriptor.

B) The value of XML_SCHEMA_NAMESPACE is:

Case:

I) If the XML type descriptor contains an XML namespace URI *NS*, then *NS*.

II) Otherwise, the null value.

C) The value of XML_SCHEMA_ELEMENT is:

Case:

I) If the XML type descriptor contains an XML NCName *EN*, then *EN*.

II) Otherwise, the null value.

2) Otherwise, the values of XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE, and XML_SCHEMA_ELEMENT are the null value.

b) Otherwise, the values of XML_PRIMARY_MODIFIER, XML_SECONDARY_MODIFIER, XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE and XML_SCHEMA_ELEMENT are the null value.

Initial Table Population

No additional Initial Table Population items.

22.3 PARAMETERS base table

This Subclause modifies Subclause 7.34, “PARAMETERS base table”, in ISO/IEC 9075-11.

Function

The PARAMETERS table has one row for each SQL parameter of each SQL-invoked routine described in the ROUTINES base table.

Definition

Insert into the Definition before

```
CONSTRAINT PARAMETERS_PRIMARY_KEY
```

the code:

```
XML_STRING_DTD_IDENTIFIER          INFORMATION_SCHEMA.SQL_IDENTIFIER,
XML_OPTION                          INFORMATION_SCHEMA.CHARACTER_DATA
CONSTRAINT XML_OPTION_CHECK
CHECK (XML_OPTION IN ( 'CONTENT', 'DOCUMENT' ) ),
XML_PASSING_MECHANISM              INFORMATION_SCHEMA.CHARACTER_DATA
CONSTRAINT XML_PASSING_MECHANISM_CHECK
CHECK (XML_PASSING_MECHANISM IN
      ( 'BY REF', 'BY VALUE' ) ),
```

Insert into the Definition after

```
);
```

the code:

```
ALTER TABLE PARAMETERS ADD
CONSTRAINT PARAMETERS_CHECK_XML_DATA_TYPE
CHECK (
  ( SPECIFIC_CATALOG, SPECIFIC_SCHEMA,
    SPECIFIC_NAME, 'ROUTINE', XML_STRING_DTD_IDENTIFIER ) IN
  ( SELECT OBJECT_CATALOG, OBJECT_SCHEMA,
        OBJECT_NAME, OBJECT_TYPE, DTD_IDENTIFIER
    FROM DATA_TYPE_DESCRIPTOR ) );
```

Description

- 1) **Insert after the last Description:** SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME, and XML_STRING_DTD_IDENTIFIER are the values of OBJECT_CATALOG, OBJECT_SCHEMA, OBJECT_NAME, and DTD_IDENTIFIER, respectively, of the row in DATA_TYPE_DESCRIPTOR that describes the associated string type of the parameter being described.

NOTE 101 — The meaning of the term “DTD” used in “XML_STRING_DTD_IDENTIFIER” and “DTD_IDENTIFIER” is different from the meaning of the term “DTD” defined in Clause 3, “Terms and definitions”.

- 2) **Insert after the last Description:** The value of XML_OPTION is the associated XML option of the parameter being described.

- 3) **Insert after the last Description:** The values of XML_PASSING_MECHANISM have the following meanings:

the null value The parameter has no <XML passing mechanism>.

BY REF The <XML passing mechanism> of the parameter is BY REF.

BY VALUE The <XML passing mechanism> of the parameter is BY VALUE.

Initial Table Population

No additional Initial Table Population items.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

22.4 ROUTINES base table

This Subclause modifies Subclause 7.46, “ROUTINES base table”, in ISO/IEC 9075-11.

Function

The ROUTINES base table has one row for each SQL-invoked routine.

Definition

Insert into the Definition before

```
CONSTRAINT ROUTINES_PRIMARY_KEY
```

the code:

```
XML_STRING_DTD_IDENTIFIER          INFORMATION_SCHEMA.SQL_IDENTIFIER,
XML_OPTION                          INFORMATION_SCHEMA.CHARACTER_DATA
CONSTRAINT XML_OPTION_CHECK
CHECK (XML_OPTION IN ( 'CONTENT', 'DOCUMENT' ) ),
XML_RETURN_MECHANISM                INFORMATION_SCHEMA.CHARACTER_DATA
CONSTRAINT XML_RETURN_MECHANISM_CHECK
CHECK (XML_RETURN_MECHANISM IN
      ( 'BY REF', 'BY VALUE' ) ),
```

Insert into the Definition after

```
);
```

the code:

```
ALTER TABLE ROUTINES
ADD CONSTRAINT ROUTINES_CHECK_XML_STRING_DTD_IDENTIFIER
CHECK (
  ( SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME,
    'ROUTINE', XML_STRING_DTD_IDENTIFIER ) IN
  ( SELECT OBJECT_CATALOG, OBJECT_SCHEMA, OBJECT_NAME,
        OBJECT_TYPE, DTD_IDENTIFIER
    FROM DATA_TYPE_DESCRIPTOR ) );
```

Description

- 1) **Insert after the last Description:** SPECIFIC_CATALOG, SPECIFIC_SCHEMA, SPECIFIC_NAME, and XML_STRING_DTD_IDENTIFIER are the values of OBJECT_CATALOG, OBJECT_SCHEMA, OBJECT_NAME, and DTD_IDENTIFIER, respectively, of the row in DATA_TYPE_DESCRIPTOR that describes the associated string type of the result of SQL-invoked routine being described.

NOTE 102 — The meaning of the term “DTD” used in “XML_STRING_DTD_IDENTIFIER” and “DTD_IDENTIFIER” is different from the meaning of the term “DTD” defined in Clause 3, “Terms and definitions”.

- 2) **Insert after the last Description:** The value of XML_OPTION is the associated XML option of the result of SQL-invoked routine being described.
- 3) **Insert after the last Description:** The values of XML_RETURN_MECHANISM have the following meanings:

the null value The SQL-invoked routine does not have a <returns clause>, or its <returns clause> does not have an <XML passing mechanism>.

BY REF The <XML passing mechanism> of the <returns clause> is BY REF.

BY VALUE The <XML passing mechanism> of the <returns clause> is BY VALUE.

Initial Table Population

No additional Initial Table Population items.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

22.5 USAGE_PRIVILEGES base table

This Subclause modifies Subclause 7.65, “USAGE_PRIVILEGES base table”, in ISO/IEC 9075-11.

Function

The USAGE_PRIVILEGES table has one row for each usage privilege descriptor. It effectively contains a representation of the usage privilege descriptors.

Definition

Insert into the Definition after

```
'COLLATION', 'TRANSLATION', 'SEQUENCE'
```

the code:

```
, 'XML_SCHEMA'
```

Insert into the Definition after

```
UNION  
SELECT SEQUENCE_CATALOG, SEQUENCE_SCHEMA, SEQUENCE_NAME,  
       'SEQUENCE'  
FROM SEQUENCES
```

the code:

```
UNION  
SELECT XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME,  
       'XML_SCHEMA'  
FROM XML_SCHEMAS
```

Description

1) Insert into Description 4), after the last list item:

XML_SCHEMA The object to which the privilege applies is a registered XML schema.

Initial Table Population

No additional Initial Table Population items.

22.6 XML_SCHEMA_ELEMENTS base table

Function

The XML_SCHEMA_ELEMENTS base table has one row for each global element declaration schema component of each registered XML schema.

Definition

```
CREATE TABLE XML_SCHEMA_ELEMENTS (
  XML_SCHEMA_CATALOG          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_SCHEMA          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_NAME            INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_NAMESPACE      INFORMATION_SCHEMA.URI,
  XML_SCHEMA_ELEMENT        INFORMATION_SCHEMA.NCNAME,
  XML_SCHEMA_ELEMENT_IS_DETERMINISTIC INFORMATION_SCHEMA.YES_OR_NO
  CONSTRAINT XML_SCHEMA_ELEMENT_IS_DETERMINISTIC_NOT_NULL
    NOT NULL,

  CONSTRAINT XML_SCHEMA_ELEMENTS_PRIMARY_KEY
    PRIMARY KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
                 XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE,
                 XML_SCHEMA_ELEMENT ),

  CONSTRAINT XML_SCHEMA_ELEMENTS_FOREIGN_KEY_XML_SCHEMA_NAMESPACES
    FOREIGN KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
                 XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE )
    REFERENCES XML_SCHEMA_NAMESPACES
);
```

Description

- 1) The values of XML_SCHEMA_CATALOG and XML_SCHEMA_SCHEMA are the catalog name and the unqualified schema name, respectively, of the registered XML schema containing the global element declaration schema component being described.
- 2) The value of XML_SCHEMA_NAME is the name of the registered XML schema containing the global element declaration schema component being described.
- 3) The value of XML_SCHEMA_NAMESPACE is the namespace URI of the global element declaration schema component being described.
- 4) The value of XML_SCHEMA_ELEMENT is the XML QName local part of the name of the global element declaration schema component being described.
- 5) The values of XML_SCHEMA_ELEMENT_IS_DETERMINISTIC have the following meanings:

YES	The global element declaration schema component being described is not non-deterministic.
NO	The global element declaration schema component being described is non-deterministic.

NOTE 103 — The concept of a global element declaration schema component being non-deterministic is defined in Subclause 4.3.6, “Registered XML schemas”.

Initial Table Population

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023

22.7 XML_SCHEMA_NAMESPACES base table

Function

The XML_SCHEMA_NAMESPACES base table has one row for each namespace of each registered XML schema descriptor.

Definition

```
CREATE TABLE XML_SCHEMA_NAMESPACES (
  XML_SCHEMA_CATALOG          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_SCHEMA           INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_NAME              INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_NAMESPACE        INFORMATION_SCHEMA.URI,
  XML_SCHEMA_NAMESPACE_IS_DETERMINISTIC INFORMATION_SCHEMA.YES_OR_NO
  CONSTRAINT XML_SCHEMA_NAMESPACE_IS_DETERMINISTIC_NOT_NULL
  NOT NULL,

  CONSTRAINT XML_SCHEMA_NAMESPACES_PRIMARY_KEY
  PRIMARY KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
               XML_SCHEMA_NAME, XML_SCHEMA_NAMESPACE )

  CONSTRAINT XML_SCHEMA_NAMESPACES_FOREIGN_KEY_XML_SCHEMAS
  FOREIGN KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
               XML_SCHEMA_NAME )
  REFERENCES XML_SCHEMAS
);
```

Description

- 1) The values of XML_SCHEMA_CATALOG and XML_SCHEMA_SCHEMA are the catalog name and the unqualified schema name, respectively, of the registered XML schema containing the namespace being described.
- 2) The value of XML_SCHEMA_NAME is the name of the registered XML schema containing the namespace being described.
- 3) The value of XML_SCHEMA_NAMESPACE is the namespace URI of the namespace being described.
- 4) The values of XML_SCHEMA_NAMESPACE_IS_DETERMINISTIC have the following meanings:

YES	The namespace being described is not non-deterministic.
NO	The namespace being described is non-deterministic.

NOTE 104 — The concept of an XML namespace being non-deterministic is defined in Subclause 4.3.6, “Registered XML schemas”.

Initial Table Population

None.

22.8 XML_SCHEMAS base table

Function

The XML_SCHEMAS base table has one row for each registered XML schema.

Definition

```
CREATE TABLE XML_SCHEMAS (
  XML_SCHEMA_TARGET_NAMESPACE          INFORMATION_SCHEMA.URI
  CONSTRAINT XML_SCHEMA_TARGET_NAMESPACE_NOT_NULL
  NOT NULL,
  XML_SCHEMA_LOCATION                  INFORMATION_SCHEMA.URI
  CONSTRAINT XML_SCHEMA_LOCATION_NOT_NULL
  NOT NULL,
  XML_SCHEMA_CATALOG                   INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_SCHEMA                     INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_NAME                       INFORMATION_SCHEMA.SQL_IDENTIFIER,
  XML_SCHEMA_IS_DETERMINISTIC           INFORMATION_SCHEMA.YES_OR_NO
  CONSTRAINT XML_SCHEMA_IS_DETERMINISTIC_NOT_NULL
  NOT NULL,
  XML_SCHEMA_IS_PERMANENT               INFORMATION_SCHEMA.YES_OR_NO
  CONSTRAINT XML_SCHEMA_IS_PERMANENT_NOT_NULL
  NOT NULL,

  CONSTRAINT XML_SCHEMAS_PRIMARY_KEY
  PRIMARY KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA, XML_SCHEMA_NAME ),

  CONSTRAINT XML_SCHEMA_FOREIGN_KEY_XML_SCHEMA_NAMESPACES
  FOREIGN KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA,
                XML_SCHEMA_NAME, XML_SCHEMA_TARGET_NAMESPACE )
  REFERENCES XML_SCHEMA_NAMESPACES,

  CONSTRAINT XML_SCHEMA_FOREIGN_KEY_XML_SCHEMATA
  FOREIGN KEY ( XML_SCHEMA_CATALOG, XML_SCHEMA_SCHEMA )
  REFERENCES SCHEMATA
);
```

Description

- 1) The value of XML_SCHEMA_TARGET_NAMESPACE is the target namespace URI of the registered XML schema being described.
- 2) The value of XML_SCHEMA_LOCATION is the schema location URI of the registered XML schema being described.
- 3) The values of XML_SCHEMA_CATALOG and XML_SCHEMA_SCHEMA are the catalog name and the unqualified schema name, respectively, of the registered XML schema being described.
- 4) The value of XML_SCHEMA_NAME is the name of the registered XML schema being described.
- 5) The values of XML_SCHEMA_IS_DETERMINISTIC have the following meanings:

YES	The registered XML schema being described is not non-deterministic.
NO	The registered XML schema being described is non-deterministic.

NOTE 105 — The concept of a registered XML schema being non-deterministic is defined in [Subclause 4.3.6](#), “Registered XML schemas”.
- 6) The values of XML_SCHEMA_IS_PERMANENT have the following meanings:

YES The registered XML schema being described is permanently registered.

NO The registered XML schema being described is not permanently registered.

NOTE 106 — The concept of a permanently registered XML schema being non-deterministic is defined in Subclause 4.3.6, “Registered XML schemas”.

Initial Table Population

None.

IECNORM.COM : Click to view the full PDF of ISO/IEC 9075-14:2023