

INTERNATIONAL  
STANDARDIZED  
PROFILE

**ISO/IEC**  
**ISP**  
**12059-1**

First edition  
1995-12-15

---

---

**Information technology — International  
Standardized Profiles — OSI  
Management — Common information for  
management functions —**

**Part 1:**  
Object management

*Technologies de l'information — Profils normalisés internationaux —  
Gestion OSI — Information courante pour fonctions de gestion —  
Partie 1: Gestion d'objet*



Reference number  
ISO/IEC ISP 12059-1:1995(E)

## Contents

Page

Foreword .....	iii
1 Scope .....	1
1.1 General .....	1
1.2 Position within the Taxonomy .....	1
2 Normative references .....	1
2.1 Identical CCITT Recommendations   International Standards .....	1
2.2 Paired CCIT/ITU-T Recommendations   International Standards equivalent in technical content .....	2
2.3 Additional references .....	2
3 Definitions .....	2
4 Abbreviations .....	2
5 Conventions .....	3
5.1 Common conventions .....	3
5.2 Document specific conventions .....	3
6 Conformance requirements .....	3
Annex A ISPICS Requirements List (IPRL) for Object management .....	4
A.1 Manager/Agent role .....	4
A.2 MAPDU Support .....	4
A.2.1 Object creation MAPDU support .....	5
A.2.2 Object deletion MAPDU support .....	6
A.2.3 Attribute value change MAPDU support .....	7
A.3 Managed object support .....	8
A.3.1 Introduction .....	8
A.3.2 Object creation record support .....	8
A.3.3 Object deletion record support .....	10
A.3.4 Attribute value change record support .....	12
Annex B ICS proformas for Object management function .....	14

© ISO/IEC 1995

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland.

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. In addition to developing International Standards, ISO/IEC JTC 1 has created a special group on Functional Standardization for the elaboration of International Standardized Profiles.

An International Standardized Profile is an internationally agreed, harmonized document which identifies a standard or group of standards, together with options and parameters, necessary to accomplish a function or set of functions.

Draft International Standardized Profiles are circulated to national bodies for voting. Publication as an International Standardized Profile requires approval by at least 75 % of the national bodies casting a vote.

International Standardized Profile ISO/IEC ISP 12059-1 was prepared with the collaboration of

- Asia-Oceania Workshop (AOW);
- European Workshop for Open Systems (EWOS);
- Open Systems Environment Implementors' Workshop (OIW).

ISO/IEC ISP 12059 consists of the following parts, under the general title *Information technology - International Standardized Profiles - OSI Management - Common information for management functions*:

- *Part 0: Common definitions for management function profiles*
- *Part 1: Object management*
- *Part 2: State management*
- *Part 3: Attributes for representing relationships*
- *Part 4: Alarm reporting*
- *Part 5: Event report management*
- *Part 6: Log control*

Annexes A and B form an integral part of this part of ISO/IEC ISP 12059.

This page intentionally left blank

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

# Information technology - International Standardized Profiles - OSI Management - Common information for management functions -

## Part 1:

### Object management

#### 1 Scope

##### 1.1 General

This part of ISO/IEC ISP 12059 is based on CCITT Rec. X.730 | ISO/IEC 10164-1, Object management function. Each part of ISO/IEC ISP 12059 is a building block, containing a subset of systems management function capability, and is used by ISO/IEC ISP 12060 parts to build interoperable profile specifications.

##### 1.2 Position within the Taxonomy

This part of ISO/IEC ISP 12059 may be referenced by parts of ISO/IEC ISP 12060 for the specification of management function profiles. The position of this part of ISO/IEC ISP 12059 within the taxonomy is described in ISO/IEC ISP 12059-0.

#### 2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC ISP 12059. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this part of ISO/IEC ISP 12059 are warned against automatically applying any more recent editions of the documents listed below, since the nature of references made by ISPs to such documents is that they may be specific to a particular edition. Members of IEC and ISO maintain registers of currently valid International Standards and ISPs, and ITU-T maintains published editions of its current Recommendations.

##### 2.1 Identical CCITT Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model*.
- CCITT Recommendation X.701 (1992) | ISO/IEC 10040:1992, *Information technology - Open Systems Interconnection - Systems management overview*.
- CCITT Recommendation X.720 (1992) | ISO/IEC 10165-1:1993, *Information technology - Open Systems Interconnection - Structure of management information: Management information model*.
- CCITT Recommendation X.721 (1992) | ISO/IEC 10165-2:1992, *Information technology - Open Systems Interconnection - Structure of management information: Definition of management information*.
- CCITT Recommendation X.722 (1992) | ISO/IEC 10165-4:1992, *Information technology - Open Systems Interconnection - Structure of management information: Guidelines for the definition of managed objects*.
- CCITT Recommendation X.730 (1992) | ISO/IEC 10164-1:1993, *Information technology - Open Systems Interconnection - Systems Management: Object management function*.
- CCITT Recommendation X.733 (1992) | ISO/IEC 10164-4:1992, *Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function*.

- CCITT Recommendation X.734 (1992) | ISO/IEC 10164-5:1993, *Information technology - Open Systems Interconnection - Systems Management: Event report management function.*
- CCITT Recommendation X.735 (1992) | ISO/IEC 10164-6:1993, *Information technology - Open Systems Interconnection - Systems Management: Log control function.*

## 2.2 Paired CCITT/ITU-T Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.208 (1988), *Specification of abstract syntax notation one (ASN.1).*  
ISO/IEC 8824:1990, *Information technology - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.290 (1992), *OSI conformance testing methodology and framework for protocol Recommendations for CCITT applications - General concepts.*  
ISO/IEC 9646-1:1994, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts..*
- CCITT Recommendation X.291 (1992), *OSI conformance testing methodology and framework for protocol Recommendations for CCITT applications - Abstract test suite specification.*  
ISO/IEC 9646-2:1994, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract test suite specification.*
- ITU-T Recommendation X.296<sup>1)</sup>, *OSI conformance testing methodology and framework - Implementation Conformance Statements.*  
ISO/IEC 9646-7:1995, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements.*
- CCITT Recommendation X.700 (1992), *Management Framework Definition for Open Systems Interconnection for CCITT applications.*  
ISO/IEC 7498-4:1989, *Information processing systems - Open Systems Interconnection - Basic Reference Model - Part 4: Management framework.*
- CCITT Recommendation X.710 (1991), *Common Management information Service Definition for CCITT Applications.*  
ISO/IEC 9595:1991, *Information technology - Open Systems Interconnection - Common management information service definition.*

## 2.3 Additional references

- ISO/IEC 9545:1994, *Information technology - Open Systems Interconnection - Application layer Structure.*
- ISO/IEC TR 10000-1:1992<sup>2)</sup>, *Information technology - Framework and taxonomy of International Standardized profiles - Part 1: Framework.*
- ISO/IEC TR 10000-2:1994<sup>2)</sup>, *Information technology - Framework and taxonomy of International Standardized profiles - Part 2: Principles and Taxonomy for OSI Profiles.*
- ISO/IEC ISP 12059-0:1995, *Information technology - International Standardized Profiles - OSI Management - Common information for management functions - Part 0: Common definitions for management function profiles.*

## 3 Definitions

The terms used in this part of ISO/IEC ISP 12059 are defined in the referenced base standards.

## 4 Abbreviations

The abbreviations used in this part of ISO/IEC ISP 12059 are specified in ISO/IEC ISP 12059-0.

1) Currently at the stage of Draft Recommendation.

2) Under revision.

## 5 Conventions

### 5.1 Common conventions

The common conventions and status codes for IPRL used in this part of ISO/IEC ISP 12059, including c3, are defined in ISO/IEC ISP 12059-0.

### 5.2 Document specific conventions

The following conditions are specified in the referenced base standard and used in this part of ISO/IEC ISP 12059:

1B/cn see CCITT Rec X.730 | ISO/IEC 10164-1, Annex B, condition cn

1C/cn see CCITT Rec X.730 | ISO/IEC 10164-1, Annex C, condition cn

## 6 Conformance requirements

This part of ISO/IEC ISP 12059 is referenced by parts of ISO/IEC ISP 12060. Those parts of ISO/IEC ISP 12060 that reference this part of ISO/IEC ISP 12059 each define the requirements for a particular AOM2xx profile and state the conformance requirements for that profile.

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

**Annex A**

(normative)

**ISPICS Requirements List (IPRL) for Object management**

The following clarifies, where necessary, the column headings used in the IPRL in this annex:

- Index: The row index of this item in the referenced ICS proforma.
- Constraints and values: Base standard constraints or any additional constraints defined in the common profile for this item.
- Base Std.: The status value of the item as defined in the base standard.
- Common Profile: Common profile requirements defined for this item (relevant to any profile referencing this table)..

The notation used in this annex is identified in clause 5. The parameter names are those which are specified in CCITT Rec. X.730 | ISO/IEC 10164-1 and CCITT Rec. X.721 | ISO/IEC 10165-2.

**A.1 Manager/Agent role**

Table A.1 is based on Table B.4 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.1 – Management role support**

Index	Systems management functional unit	Manager		Agent		Additional information
		Base Std.	Common Profile	Base Std.	Common Profile	
1	all Events	o	o.1	o	o.1	
2	control	o	o.2	o	o.2	
3	monitor	o	o.3	o	o.3	
4	object Events	1B/c2	o.4	1B/c2	o.4	

**A.2 MAPDU support**

Table A.2 is based on Table B.5 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.2 – Object management MAPDUs**

Index	MAPDU (agent sending)   (manager receiving)	Base Std.	Common Profile	Additional information
1	Object creation (agent sending)	1B/c3	1B/c3	
2	Object deletion (agent sending)	1B/c3	1B/c3	
3	Attribute value change (agent sending)	1B/c3	1B/c3	
4	Object creation (manager receiving)	1B/c4	1B/c4	
5	Object deletion (manager receiving)	1B/c4	1B/c4	
6	Attribute value change (manager receiving)	1B/c4	1B/c4	

### A.2.1 Object creation MAPDU support

Table A.3 is based on Table B.6 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.3 – Object creation MAPDU (Agent sending)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	o	mo	
2	attributeList <sup>3)</sup>	–	o	mo	
3	notificationIdentifier	INTEGER	1B/c5	1B/c5o	
4	correlatedNotifications	–	o	oo	
4.1	correlatedNotifications	–	c:m	c:mm	
4.2	sourceObjectInst	–	c:o	c:mo	
4.2.1	distinguishedName	–	c:o.2	c:mc3	
4.2.2	nonspecificForm	–	c:o.2	c:mc3	
4.2.3	localDistinguishedName	–	c:o.2	c:mc3	
5	additionalText	–	o	oo	
6	additionalInformation	Required for some objects	o	oo	

Table A.4 is based on Table B.7 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.4 – Object creation MAPDU (Manager receiving)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	m	mo	
2	attributeList <sup>3)</sup>	–	m	mo	
3	notificationIdentifier	INTEGER	m	mo	
4	correlatedNotifications	–	m	mo	
4.1	correlatedNotifications	–	m	mm	
4.2	sourceObjectInst	–	m	mo	
4.2.1	distinguishedName	–	m	mc3	
4.2.2	nonspecificForm	–	m	mc3	
4.2.3	localDistinguishedName	–	m	mc3	
5	additionalText	–	m	mo	
6	additionalInformation	Required for some objects	m	mo	

<sup>3)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance being created are allowed to be present.

**A.2.2 Object deletion MAPDU support**

Table A.5 is based on Table B.8 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.5 – Object deletion MAPDU (Agent sending)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	o	mo	
2	attributeList <sup>4)</sup>	–	o	mo	
3	notificationIdentifier	INTEGER	1B/c6	1B/c6o	
4	correlatedNotifications	–	o	oo	
4.1	correlatedNotifications	–	c:m	c:mm	
4.2	sourceObjectInst	–	c:o	c:mo	
4.2.1	distinguishedName	–	c:o.3	c:mc3	
4.2.2	nonspecificForm	–	c:o.3	c:mc3	
4.2.3	localDistinguishedName	–	c:o.3	c:mc3	
5	additionalText	–	o	oo	
6	additionalInformation	Required for some objects	o	oo	

Table A.6 is based on Table B.9 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.6 – Object deletion MAPDU (Manager receiving)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	m	mo	
2	attributeList <sup>4)</sup>	–	m	mo	
3	notificationIdentifier	INTEGER	m	mo	
4	correlatedNotifications	–	m	mo	
4.1	correlatedNotifications	–	m	mm	
4.2	sourceObjectInst	–	m	mo	
4.2.1	distinguishedName	–	m	mc3	
4.2.2	nonspecificForm	–	m	mc3	
4.2.3	localDistinguishedName	–	m	mc3	
5	additionalText	–	m	mo	
6	additionalInformation	Required for some objects	m	mo	

<sup>4)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance being deleted are allowed to be present.

### A.2.3 Attribute value change MAPDU support

Table A.7 is based on Table B.10 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.7 – Attribute value change MAPDU (Agent sending)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	o	mo	
2	attributeIdentifierList	–	o	mo	
3	attributeValueChangeDefinition <sup>5)</sup>	–	m	mm	
3.1	attributeId	–	m	mm	
3.2	oldAttributeValue	–	o	mo	
3.3	newAttributeValue	–	m	mm	
4	notificationIdentifier	INTEGER	1B/c7	1B/c7o	
5	correlatedNotifications	–	o	oo	
5.1	correlatedNotifications	–	c:m	c:mm	
5.2	sourceObjectInst	–	c:o	c:mo	
5.2.1	distinguishedName	–	c:o.4	c:mc3	
5.2.2	nonspecificForm	–	c:o.4	c:mc3	
5.2.3	localDistinguishedName	–	c:o.4	c:mc3	
6	additionalText	–	o	oo	
7	additionalInformation	Required for some objects	o	oo	

Table A.8 is based on Table B.11 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.8 – Attribute value change MAPDU (Manager receiving)**

Index	Parameter name	Constraints and values	Base Std.	Common Profile	Additional information
1	sourceIndicator	ENUMERATED 0 to 2	m	mo	
2	attributeIdentifierList	–	m	mo	
3	attributeValueChangeDefinition <sup>5)</sup>	–	m	mm	
3.1	attributeId	–	m	mo	
3.2	oldAttributeValue	–	m	mo	
3.3	newAttributeValue	–	m	mm	
4	notificationIdentifier	INTEGER	m	mo	
5	correlatedNotifications	–	m	mo	
5.1	correlatedNotifications	–	m	mm	
5.2	sourceObjectInst	–	m	mo	
5.2.1	distinguishedName	–	m	mc3	
5.2.2	nonspecificForm	–	m	mc3	
5.2.3	localDistinguishedName	–	m	mc3	
6	additionalText	–	m	mo	
7	additionalInformation	Required for some objects	m	mo	

<sup>5)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance undergoing value change are allowed to be present.

### A.3 Managed object support

#### A.3.1 Introduction

The following MOCS tables define the requirements for the object creation record managed object class, object deletion record managed object class and attribute value change record managed object class.

#### A.3.2 Object creation record support

##### A.3.2.1 Object creation record packages support

Table A.9 is based on Table C.3 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.9 – Object creation record packages**

Index	Package template label	Value of object identifier for package	Constraints and values	Base Std.	Common Profile	Additional information
1	topPackage	–	–	m	m	
2	packagesPackage	{dmi-pkg 16}	–	1C/c1	m	
3	allomorphicPackage	{dmi-pkg 17}	–	1C/c2	i	
4	logRecordPackage	–	–	m	m	
5	eventLogRecordPackage	–	–	m	m	
6	eventTimePackage	{dmi-pkg 11}	–	o	m	
7	notificationIdentifierPackage	{dmi-pkg 24}	–	o	m	
8	correlatedNotificationsPackage	{dmi-pkg 23}	–	o	m	
9	additionalTextPackage	{dmi-pkg 19}	–	o	m	
10	additionalInformationPackage	{dmi-pkg 18}	–	o	m	
11	objectCreationRecordPackage <sup>6)</sup>	–	–	m	m	
12	sourceIndicatorPackage	{dmi-pkg 28}	–	o	m	
13	attributeListPackage	{dmi-pkg 21}	–	o	m	

<sup>6)</sup> This package has no attributes.

## A.3.2.2 Object creation record attributes support

Table A.10 is based on Table C.4 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

Table A.10 – Object creation record attributes

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by Create		Get		Replace	
				Base Std.	Common Profile	Base Std.	Common Profile	Base Std.	Common Profile
1	objectClass	{dmi-att 65}	–	x	x	m	m	x	x
2	nameBinding	{dmi-att 63}	–	x	x	m	m	x	x
3	packages	{dmi-att 66}	–	x	x	1C/c1	m	x	x
4	allomorpha	{dmi-att 50}	–	x	x	1C/c2	i	x	x
5	logRecordId	{dmi-att 3}	–	x	x	m	m	x	x
6	loggingTime	{dmi-att 59}	–	x	x	m	m	x	x
7	managedObjectClass	{dmi-att 60}	–	x	x	m	m	x	x
8	managedObjectInstance	{dmi-att 61}	–	x	x	m	m	x	x
9	eventType	{dmi-att 14}	–	x	x	m	m	x	x
10	eventTime	{dmi-att 13}	–	x	x	1C/c3	m	x	x
11	notificationIdentifier	{dmi-att 16}	–	x	x	1C/c4	m	x	x
12	correlatedNotifications	{dmi-att 12}	–	x	x	1C/c5	m	x	x
13	additionalText	{dmi-att 7}	–	x	x	1C/c6	m	x	x
14	additionalInformation	{dmi-att 6}	–	x	x	1C/c7	m	x	x
15	sourceIndicator	{dmi-att 26}	–	x	x	1C/c8	m	x	x
16	attributeList	{dmi-att 9}	–	x	x	1C/c9	m	x	x

Table A.10 (concluded) – Object creation record attributes

Index	Add		Remove		Set To Default		Additional information
	Base Std.	Common Profile	Base Std.	Common Profile	Base Std.	Common Profile	
1	–	–	–	–	–	–	
2	–	–	–	–	–	–	
3	x	x	x	x	–	–	
4	x	x	x	x	–	–	
5	–	–	–	–	–	–	
6	–	–	–	–	–	–	
7	–	–	–	–	–	–	
8	–	–	–	–	–	–	
9	–	–	–	–	–	–	
10	–	–	–	–	–	–	
11	–	–	–	–	–	–	
12	x	x	x	x	–	–	
13	–	–	–	–	–	–	
14	x	x	x	x	–	–	
15	–	–	–	–	–	–	
16	x	x	x	x	–	–	

### A.3.3 Object deletion record support

#### A.3.3.1 Object deletion record packages support

Table A.11 is based on Table C.7 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

Table A.11 – Object deletion record packages

Index	Package name	Value of object identifier for package	Constraints and values	Base Std.	Common Profile	Additional information
1	topPackage	–	–	m	m	
2	packagesPackage	{dmi-pkg 16}	–	1C/c10	m	
3	allomorphicPackage	{dmi-pkg 17}	–	1C/c11	i	
4	logRecordPackage	–	–	m	m	
5	eventLogRecordPackage	–	–	m	m	
6	eventTimePackage	{dmi-pkg 11}	–	o	m	
7	notificationIdentifierPackage	{dmi-pkg 24}	–	o	m	
8	correlatedNotificationsPackage	{dmi-pkg 23}	–	o	m	
9	additionalTextPackage	{dmi-pkg 19}	–	o	m	
10	additionalInformationPackage	{dmi-pkg 18}	–	o	m	
11	objectDeletionRecordPackage <sup>7)</sup>	–	–	m	m	
12	sourceIndicatorPackage	{dmi-pkg 28}	–	o	m	
13	attributeListPackage	{dmi-pkg 21}	–	o	m	

<sup>7)</sup> This package has no attributes.

### A.3.3.2 Object deletion record attributes support

Table A.12 is based on Table C.8 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

Table A.12 – Object deletion record attributes

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by Create		Get		Replace	
				Base Std.	Common Profile	Base Std.	Common Profile	Base Std.	Common Profile
1	objectClass	{dmi-att 65}	–	x	x	m	m	x	x
2	name Binding	{dmi-att 63}	–	x	x	m	m	x	x
3	packages	{dmi-att 66}	–	x	x	1C/c10	m	x	x
4	allomorphs	{dmi-att 50}	–	x	x	1C/c11	i	x	x
5	logRecordId	{dmi-att 3}	–	x	x	m	m	x	x
6	loggingTime	{dmi-att 59}	–	x	x	m	m	x	x
7	managedObjectClass	{dmi-att 60}	–	x	x	m	m	x	x
8	managedObjectInstance	{dmi-att 61}	–	x	x	m	m	x	x
9	eventType	{dmi-att 14}	–	x	x	m	m	x	x
10	eventTime	{dmi-att 13}	–	x	x	1C/c12	m	x	x
11	notificationIdentifier	{dmi-att 16}	–	x	x	1C/c13	m	x	x
12	correlatedNotifications	{dmi-att 12}	–	x	x	1C/c14	m	x	x
13	additionalText	{dmi-att 7}	–	x	x	1C/c15	m	x	x
14	additionalInformation	{dmi-att 6}	–	x	x	1C/c16	m	x	x
15	sourceIndicator	{dmi-att 26}	–	x	x	1C/c17	m	x	x
16	attributeList	{dmi-att 9}	–	x	x	1C/c18	m	x	x

Table A.12 (concluded) – Object deletion record attributes

Index	Add		Remove		Set To Default		Additional information
	Status	Common Profile	Status	Common Profile	Status	Common Profile	
1	–	–	–	–	–	–	
2	–	–	–	–	–	–	
3	x	x	x	x	–	x	
4	x	x	x	x	–	x	
5	–	–	–	–	–	–	
6	–	–	–	–	–	–	
7	–	–	–	–	–	–	
8	–	–	–	–	–	–	
9	–	–	–	–	–	–	
10	–	–	–	–	–	–	
11	–	–	–	–	–	–	
12	x	x	x	x	–	x	
13	–	–	–	–	–	–	
14	x	x	x	x	–	x	
15	–	–	–	–	–	–	
16	x	x	x	x	–	x	

**A.3.4 Attribute value change record support****A.3.4.1 Attribute value change record packages support**

Table A.13 is based on Table C.11 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.13 – Attribute value change record packages**

Index	Package name	Value of object identifier for package	Constraints and values	Base Std.	Common Profile	Additional information
1	topPackage	–	–	m	m	
2	packagesPackage	{dmi-pkg 16}	–	1C/c19	m	
3	allomorphicPackage	{dmi-pkg 17}	–	1C/c20	i	
4	logRecordPackage	–	–	m	m	
5	eventLogRecordPackage	–	–	m	m	
6	eventTimePackage	{dmi-pkg 11}	–	o	m	
7	notificationIdentifierPackage	{dmi-pkg 24}	–	o	m	
8	correlatedNotificationsPackage	{dmi-pkg 23}	–	o	m	
9	additionalTextPackage	{dmi-pkg 19}	–	o	m	
10	additionalInformationPackage	{dmi-pkg 18}	–	o	m	
11	attributeValueChangeRecordPackage	–	–	m	m	
12	sourceIndicatorPackage	{dmi-pkg 28}	–	o	m	
13	attributeIdentifierListPackage	{dmi-pkg 20}	–	o	m	

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

**A.3.4.2 Attribute value change record attributes support**

Table A.14 is based on Table C.12 of CCITT Rec X.730 | ISO/IEC 10164-1 DAM 1.

**Table A.14 – Attribute value change record attributes**

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by Create		Get		Replace	
				Base Std.	Common Profile	Base Std.	Common Profile	Base Std.	Common Profile
1	objectClass	{dmi-att 65}	–	x	x	m	m	x	x
2	nameBinding	{dmi-att 63}	–	x	x	m	m	x	x
3	packages	{dmi-att 66}	–	x	x	1C/c19	m	x	x
4	allomorphs	{dmi-att 50}	–	x	x	1C/c20	i	x	x
5	logRecordId	{dmi-att 3}	–	x	x	m	m	x	x
6	loggingTime	{dmi-att 59}	–	x	x	m	m	x	x
7	managedObjectClass	{dmi-att 60}	–	x	x	m	m	x	x
8	managedObjectInstance	{dmi-att 61}	–	x	x	m	m	x	x
9	eventType	{dmi-att 14}	–	x	x	m	m	x	x
10	eventTime	{dmi-att 13}	–	x	x	1C/c21	m	x	x
11	notificationIdentifier	{dmi-att 16}	–	x	x	1C/c22	m	x	x
12	correlatedNotifications	{dmi-att 12}	–	x	x	1C/c23	m	x	x
13	additionalText	{dmi-att 7}	–	x	x	1C/c24	m	x	x
14	additionalInformation	{dmi-att 6}	–	x	x	1C/c25	m	x	x
15	attributeValueChange Definition	{dmi-att 10}	–	x	x	m	m	x	x
16	sourceIndicator	{dmi-att 26}	–	x	x	1C/c26	m	x	x
17	attributeIdentifierList	{dmi-att 8}	–	x	x	1C/c27	m	x	x

**Table A.14 (concluded) – Attribute value change record attributes**

Index	Add		Remove		Set To Default		Additional information
	Base Std.	Common Profile	Base Std.	Common Profile	Base Std.	Common Profile	
1	–	–	–	–	–	–	
2	–	–	–	–	–	–	
3	x	x	x	x	–	–	
4	x	x	x	x	–	–	
5	–	–	–	–	–	–	
6	–	–	–	–	–	–	
7	–	–	–	–	–	–	
8	–	–	–	–	–	–	
9	–	–	–	–	–	–	
10	–	–	–	–	–	–	
11	–	–	–	–	–	–	
12	x	x	x	x	–	–	
13	–	–	–	–	–	–	
14	x	x	x	x	–	–	
15	x	x	x	x	–	–	
16	–	–	–	–	–	–	
17	x	x	x	x	–	–	

**Annex B**

(normative)

**ICS proformas for Object management function**

NOTE – The ICS proforma for CCITT Rec. X.730 | ISO/IEC 10164-1 is currently at DAM stage. This part of ISO/IEC ISP 12059 is based on that DAM. The text of that DAM forms this appendix but will be removed once the DAM is approved and this part of ISO/IEC ISP 12059 is modified accordingly.

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

**INFORMATION TECHNOLOGY — OPEN SYSTEMS INTERCONNECTION —  
SYSTEMS MANAGEMENT: OBJECT MANAGEMENT FUNCTION**

**AMENDMENT 1**

**Page 2**

Add the following reference to Clause 2.1:

"

- ITU-T Recommendation X.724 | ISO/IEC 10165-6, *Information technology - Open Systems Interconnection - Structure of Management information: Requirements and guidelines for implementation conformance statement proformas associated with OSI management.*

"

Add the following reference to Clause 2.2:

"

- CCITT Recommendation X.291 (1992), *OSI conformance testing methodology and framework for protocol Recommendations for CCITT applications - Abstract test suite specification.*  
ISO/IEC 9646-2 : 1991, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract test suite specification.*
- ITU-T Recommendation X.296<sup>1)</sup>, *OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Implementation Conformance Statements.*  
ISO/IEC 9646-7<sup>1)</sup>, *Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements.*

"

**Page 4**

Add the following definitions to Clause 3.7:

"

PICS proforma;  
protocol implementation conformance statement;

"

Add the following abbreviations to Clause 4:

"

MCS	management conformance summary
MIDS	management information definition statement
MOCS	managed object conformance statement
MRCS	managed relationship conformance statement
PICS	protocol implementation conformance statement

---

<sup>1)</sup> Currently at the stage of Draft Recommendation | Draft International Standard.

"

Page 13

*Add the following new clauses:*

"

### 13.3 PICS requirements

A PICS proforma which conforms to this Recommendation | International Standard shall be textually identical to Annex B, differing only in pagination and page headers. A PICS which conforms to this Recommendation | International Standard shall

- describe an implementation which conforms to CCITT Rec. X.730 | ISO/IEC 10164-1;
- be a conforming PICS proforma which has been completed in accordance with the instructions for completion given in clause 1 of Annex B;
- include the information necessary to uniquely identify both the supplier and the implementation.

The supplier of a protocol implementation which is claimed to conform to CCITT Rec. X.730 | ISO/IEC 10164-1 shall complete a copy of the PICS proforma provided in Annex B as part of the conformance requirements, and shall provide the information necessary to identify both the supplier and the implementation.

### 13.4 Management information conformance requirements

A MCS proforma which conforms to this Recommendation | International Standard shall be textually identical to the MCS proforma specified in Annex A, differing only in indices, pagination and page headers. An object creation, object deletion, or attribute value change record object class MOCS proforma which conforms to this Recommendation | International Standard shall be textually identical to the MOCS proforma specified in Annex C, differing only in pagination and page headers. An object creation, object deletion, or attribute value change notification MIDS proforma which conforms to this Recommendation | International Standard shall be textually identical to the MIDS proforma specified in Annex D, differing only in pagination and page headers. An MCS, MIDS, MOCS, MRCS and PICS which conforms to this Recommendation | International Standard shall

- describe an implementation which conforms to this Recommendation | International Standard;
- be conforming MCS, MIDS, MOCS, MRCS and/or PICS proformas which have been completed in accordance with the instructions for completion given in ITU-T Rec. X.724 | ISO/IEC 10165-6;
- include the information necessary to uniquely identify both the supplier and the implementation.

The supplier of an implementation which is claimed to conform to this Recommendation | International Standard shall complete a copy of the management conformance summary provided in Annex A as part of the conformance requirements, and shall provide the information necessary to identify both the supplier and the implementation.

"

[Temporary NOTE — National Body comment is requested on the title and contents of Clause 13.3 and 13.4 to ensure consistency with the requirements of ISO/IEC 10165-6.]

*Add the following annexes:*

## Annex A

### MCS proforma<sup>2)</sup>

(This annex forms an integral part of this Recommendation | International Standard)

#### A.1 Introduction

##### A.1.1 Purpose and structure

The management conformance summary (MCS) is a statement by a supplier that identifies an implementation and provides information on whether the implementation claims conformance to any of the listed set of documents that specify conformance requirements to OSI management.

The MCS proforma is a document, in the form of a questionnaire that when completed by the supplier of an implementation becomes the MCS.

##### A.1.2 Instructions for completing the MCS proforma to produce an MCS<sup>3)</sup>

The supplier of the implementation shall enter an explicit statement in each of the boxes provided. Specific instruction is provided in the text which precedes each table.

##### A.1.3 Symbols, abbreviations and terms

For all annexes of this Recommendation | International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7 are used for the Status column:

- m mandatory;
- o optional;
- c conditional;
- x prohibited;
- not applicable or out of scope.

##### NOTES

1 – 'c', 'm', and 'o' are prefixed by a 'c:' when nested under a conditional or optional item of the same table;

2 – 'o' may be suffixed by 'N' (where N is a unique number) for mutually exclusive or selectable options among a set of status values. Support of at least one of the choices (from the items with the same values of N) is required.

For all annexes of this Recommendation | International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7 are used for the Support column:

- Y implemented;
- N not implemented;
- no answer required;
- Ig the item is ignored (i.e. processed syntactically but not semantically).

The following requirement is commonly used throughout this MCS proforma:

c1 : if A.1/1a then m else —

<sup>2)</sup> Users of this Recommendation | International Standard may freely reproduce the MCS proforma in this annex so that it can be used for its intended purpose, and may further publish the completed MCS.

<sup>3)</sup> Instructions for completing the MCS proforma are specified in ITU-T Rec.X.724 | ISO/IEC 10165-6 .

**A.1.4 Table format**

Some of the tables in this Recommendation | International Standard have been split because the information is too wide to fit on the page. Where this occurs, the index number of the first block of columns are the index numbers of the corresponding rows of the remaining blocks of columns. A complete table reconstructed from the constituent parts should have the following layout:

Index	First block of columns	Second block of columns	Etc.
-------	------------------------	-------------------------	------

In this Recommendation | International Standard the constituent parts of the table appear consecutively, starting with the first block of columns.

When a table with subrows is too wide to fit on a page, the continuation tables(s) have been constructed with index numbers identical to the index numbers in the corresponding rows of the first table, and with subindex numbers corresponding to the subrows within each indexed row. For example, if Table X.1 has 2 rows and the continuation of Table X.1 has 2 subrows for each row, the tables are presented as follows:

**Table X.1 — Title**

					Support		
Index	A	B	C	D	E	F	G
1	a	b	—				
2	a	b	—				

**Table X.1 (continued) — Title**

Index	Subindex	H	I	J	K	L
1	1.1	h	i	j		
	1.2	h	i	j		
2	2.1	h	i	j		
	2.2	h	i	j		

A complete table reconstructed from the constituent parts should have the following layout:

					Support								
Index	A	B	C	D	E	F	G	Subindex	H	I	J	K	L
1	a	b	—					1.1	h	i	j		
								1.2	h	i	j		
2	a	b	—					2.1	h	i	j		
								2.2	h	i	j		

References made to cells within tables shall be interpreted as references within tables shall be interpreted as references within reconstructed table. In the example, above, the reference X.1/1d corresponds with the blank cell in the column G for row with Index 1, and X.1/1.2b corresponds with the blank cell in column L for row with Subindex 1.2

**A.2 Identification of the implementation****A.2.1 Date of statement**

The supplier of the implementation shall enter the date of this statement in the box below. Use the format DD-MM-YYYY.

Date of statement
-------------------

**A.2.2 Identification of the implementation**

The supplier of the implementation shall enter information necessary to uniquely identify the implementation and the system(s) in which it may reside, in the box below.

--

**A.2.3 Contact**

The supplier of the implementation shall provide information on whom to contact if there are any queries concerning the content of the MCS, in the box below.

--

**A.3 Identification of the Recommendation | International Standard in which the management information is defined**

The supplier of the implementation shall enter the title, reference number and date of the publication of the Recommendation | International Standard which specifies the management information to which conformance is claimed, in the box below.

Recommendation   International Standard to which conformance is claimed
---

**A.3.1 Technical corrigenda implemented**

The supplier of the implementation shall enter the reference numbers of implemented technical corrigenda which modify the identified Recommendation | International Standard, in the box below.

--

**A.3.2 Amendments implemented**

The supplier of the implementation shall state the titles and reference numbers of implemented amendments to the identified Recommendation | International Standard, in the box below.

--

**A.4 Management conformance summary**

The supplier of the implementation shall provide information on whether the implementation claims conformance to any of the set of documents globally representing the implementation under claim. For each Recommendation | International Standard that the supplier of the implementation claims conformance to, the corresponding conformance statement(s) shall be completed, or referenced by, the MCS. The supplier of the implementation shall complete the Support, Table numbers and Additional information columns.

**Table A.1 — Logging of event records**

Index	Description	Status	Support	Additional Information
1	Does the implementation support logging of event records in agent role?	o		

NOTE — Conformance to this Recommendation | International Standard does not require conformance to CCITT Rec. X.735 | ISO/IEC 10164-6.

In tables A.2, A.3 and A.4, the "status" column is used to indicate whether the supplier of the implementation is required to complete the referenced tables or referenced items. Conformance requirements are as specified in the referenced tables or referenced items and are not changed by the value of the MCS "status" column. Similarly, the "support" column is used by the supplier of the implementation to indicate completion of the referenced tables or referenced items.

**Table A.2 — PICS support summary**

Index	Identification of the document that includes the PICS proforma	Table numbers of PICS proforma	Description	Constraints and values	Status	Support	Table numbers of PICS	Additional information
1	CCITT Rec X.730   ISO/IEC 10164-1	Annex B all tables	—	—	m			
2	CCITT Rec X.730   ISO/IEC, 10164-1	Annex E all tables	SM application Context	OBJECT IDENTIFIER	m			

**Table A.3 — MOCS support summary**

Index	Identification of the document that includes the MOCS proforma	Table numbers of MOCS proforma	Description	Constraints and values	Status	Support	Table numbers of MOCS	Additional information
1	CCITT Rec X.730   ISO/IEC 10164-1,	Annex C all tables	Record objects	—	cl			

**Table A.4 — MRCS support summary**

Index	Identification of the document that includes the MRCS proforma	Table numbers of MRCS proforma	Description	Constraints and values	Status	Support	Table numbers of MRCS	Additional information
1	CCITT Rec X.735   ISO/IEC 10164-6,	Item D.1/1	LogRecord-Log Name binding	—	cl			

## Annex B PICS proforma<sup>4)</sup>

(This annex forms an integral part of this Recommendation | International Standard)

### B.1 Instructions for completing the PICS proforma

#### B.1.1 Purpose and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of CCITT Rec. X.730 | ISO/IEC 10164-1 may provide information in a standard form. The PICS proforma is subdivided into clauses for the following categories of information

- protocol details;
- overall conformance claim;
- implementation capabilities.

#### B.1.2 Symbols, abbreviation and terms

The PICS proforma contained in this annex is comprised of information in a tabular form in accordance with the guidelines presented in CCITT Rec. X.291 | ISO/IEC 9646-2.

The notations used in the Status and Support columns are specified in A.1.3.

Within this PICS proforma, space has been provided for the supplier of the implementation to specify support for individual items and if appropriate provide additional information. It is recommended that references to additional specifications are included where appropriate (for example, to list the OBJECT IDENTIFIER values and/or ranges supported), and that these additional specifications be appended to the completed PICS proforma.

#### B.1.3 Nesting rules

In the "Status" column of the tables in this Recommendation | International Standard, a mandatory element contained within an optional or conditional constructor parameter is mandatory only if the option or condition is taken. The "c:" notation, specified in ITU-T Rec X.296 | ISO/IEC 9646-7 is used to express these nesting rules.

#### B.1.4 Instructions for completing the PICS

The supplier of the implementation shall enter an explicit statement in each of the boxes provided using the notation described in clause B.1.2. Specific instruction is provided in the text which precedes each table.

---

<sup>4)</sup> Users of this Recommendation | International Standard may freely reproduce the PICS proforma in this annex so that it can be used for its intended purpose, and may further publish the completed PICS.

**B.2 Global statement of conformance**

The supplier of the implementation shall state whether or not all mandatory capabilities are implemented for CCITT Rec. X.730 | ISO/IEC 10164-1, in Table B.1.

**Table B.1 — Capabilities**

Index		Status	Support	Additional information
1	Are all mandatory capabilities implemented?	m		
2	Does the implementation support the general conformance class?	o		

NOTE — Answering NO to the question in B.1/1 indicates non-conformance to the protocol standard. Non-supported mandatory capabilities are listed in the table below, explaining why the status of the implementation is abnormal.

Capability not implemented	Reason

**B.3 Capabilities**

**B.3.1 Systems management functional unit support**

The supplier of the implementation shall state the capability for supporting each functional unit, in Table B.2.

**Table B.2 — SMFU support**

Index	Functional unit name	Status	Support	MAPDU support	CMIS support	Additional information
1	allEvents	o		All notifications	M-EVENT-REPORT	
2	control	o		All management operations except notifications	M-GET, M-SET, M-CREATE, M-DELETE, M-ACTION	
3	monitor	o		All get operations	M-GET	
4	objectEvents	c1		ObjectCreation ObjectDeletion AttributeValueChange	M-EVENT-REPORT	

c1: if B.1/2a then m else o.

[Temporary NOTE - This table may be redundant (see tables B.4 and B.5) National body comment is invited.]

**B.3.2 Systems management functional unit negotiation support**

The supplier of the implementation shall state the capability for negotiating the use of the object management functional units, in Table B.3.

**Table B.3 — SMFU negotiation support**

Index	Negotiation capability	Status	Support	Additional information
1	Does the implementation support the negotiation of the object management functional units?	o		

The tables for the functional unit negotiation mechanism are specified in Annex E.

**B.3.3 Management roles**

The supplier of the implementation shall the management role(s) for which conformance is claimed, in Table B.4.

**Table B.4 — Management role support**

Index	Systems management functional unit name	Manager		Agent		Additional Information
		Status	Support	Status	Support	
1	all Events	o		o		
2	control	o		o		
3	monitor	o		o		
4	object Events	c2		c2		

c2: if B.1/2a then o.1 else o

**B.3.4 MAPDU support**

The supplier of the implementation shall state support for the MAPDU in the management role(s) for which conformance is claimed, in Table B.5.

**Table B.5 — Object management MAPDUs**

Index	MAPDU (agent sending)   (manager receiving)	Status	Support	Additional Information
1	Object creation (agent sending)	c3		
2	Object deletion (agent sending)	c3		
3	Attribute value change (agent sending)	c3		
4	Object creation (manager receiving)	c4		
5	Object deletion (manager receiving)	c4		
6	Attribute value change (manager receiving)	c4		

c3: if B4/4b then m else o

c4: if B4/4a then m else o

A standard mechanism for configuring event forwarding characteristics of an open system has been defined in CCITT Rec. X.734 | ISO/IEC 10164-5. For systems not using this mechanism, the supplier of the implementation shall state the condition under which event reports will be forwarded by the system, in the box below.

If support for the object creation MAPDU in the agent role is claimed (B.5/1a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.6.

Table B.6 — Object creation MAPDU (Agent sending)

Index	Parameter name	Constraints and values	Status	Support	Additional information
1	sourceIndicator	ENUMERATED 0 to 3	o		
2	attributeList <sup>5)</sup>	—	o		
3	notificationIdentifier	INTEGER	c5		
4	correlatedNotifications	—	o		
4.1	correlatedNotifications	—	c:m		
4.2	sourceObjectInst	—	c:o		
4.2.1	distinguishedName	—	c:o.2		
4.2.2	nonspecificForm	—	c:o.2		
4.2.3	localDistinguishedName	—	c:o.2		
5	additionalText	—	o		
6	additionalInformation	Required for some objects	o		

c5: if B.6/4a then m else o

If support for the object creation MAPDU in the manager role is claimed (B.5/4a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.7.

Table B.7 — Object creation MAPDU (Manager receiving)

Index	Parameter name	Constraints and values	Status	Support	Additional information
1	sourceIndicator	ENUMERATED 0 to 3	m		
2	attributeList <sup>5)</sup>	—	m		
3	notificationIdentifier	INTEGER	m		
4	correlatedNotifications	—	m		
4.1	correlatedNotifications	—	m		
4.2	sourceObjectInst	—	m		
4.2.1	distinguishedName	—	m		
4.2.2	nonspecificForm	—	m		
4.2.3	localDistinguishedName	—	m		
5	additionalText	—	m		
6	additionalInformation	Required for some objects	m		

<sup>5)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance being created are allowed to be present.

If support for the object deletion MAPDU in the agent role is claimed (B.5/2a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.8.

Table B.8 — Object deletion MAPDU (Agent sending)

Index	Parameter name	Constraints and values	Status	Support	Additional Information
1	sourceIndicator	ENUMERATED 0 to 3	o		
2	attributeList <sup>6)</sup>	—	o		
3	notificationIdentifier	INTEGER	m c 6		
4	correlatedNotifications	—	o		
4.1	correlatedNotifications	—	c:m		
4.2	sourceObjectInst	—	c:o		
4.2.1	distinguishedName	—	c:o.3		
4.2.2	nonspecificForm	—	c:o.3		
4.2.3	localDistinguishedName	—	c:o.3		
5	additionalText	—	o		
6	additionalInformation	Required for some objects	o		

c6: if B.8/4a then m else o

If support for the object deletion MAPDU in the manager role is claimed (B.5/5a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.9.

Table B.9 — Object deletion MAPDU (Manager receiving)

Index	Parameter name	Constraints and values	Status	Support	Additional Information
1	sourceIndicator	ENUMERATED 0 to 3	m		
2	attributeList <sup>6)</sup>	—	m		
3	notificationIdentifier	INTEGER	m		
4	correlatedNotifications	—	m		
4.1	correlatedNotifications	—	m		
4.2	sourceObjectInst	—	m		
4.2.1	distinguishedName	—	m		
4.2.2	nonspecificForm	—	m		
4.2.3	localDistinguishedName	—	m		
5	additionalText	—	m		
6	additionalInformation	Required for some objects	m		

<sup>6)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance being deleted are allowed to be present.

If support for the attribute value change MAPDU in the agent role is claimed (B.5/3a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.10.

Table B.10 — Attribute value change MAPDU (Agent sending)

Index	Parameter name	Constraints and values	Status	Support	Additional information
1	sourceIndicator	ENUMERATED 0 to 3	o		
2	attributeIdentifierList	—	o		
3	AttributeValueChangeDefinition <sup>7)</sup>	—	m		
3.1	attributeId	—	m		
3.2	oldAttributeValue	—	o		
3.3	newAttributeValue	—	m		
4	notificationIdentifier	INTEGER	c7		
5	correlatedNotifications	—	o		
5.1	correlatedNotifications	—	c:m		
5.2	sourceObjectInst	—	c:o		
5.2.1	distinguishedName	—	c:o.4		
5.2.2	nonspecificForm	—	c:o.4		
5.2.3	localDistinguishedName	—	c:o.4		
6	additionalText	—	o		
7	additionalInformation	Required for some objects	o		

c7: if B.10/5a then m else o

If support for the attribute value change MAPDU in the manager role is claimed (B.5/6a), then the supplier of the implementation shall state whether or not each parameter of the MAPDU is supported in Table B.11.

Table B.11 — Attribute value change MAPDU (Manager receiving)

Index	Parameter name	Constraints and values	Status	Support	Additional information
1	sourceIndicator	ENUMERATED 0 to 3	m		
2	attributeIdentifierList	—	m		
3	AttributeValueChangeDefinition <sup>7)</sup>	—	m		
3.1	attributeId	—	m		
3.2	oldAttributeValue	—	m		
3.3	newAttributeValue	—	m		
4	notificationIdentifier	INTEGER	m		
5	correlatedNotifications	—	m		
5.1	correlatedNotifications	—	m		
5.2	sourceObjectInst	—	m		
5.2.1	distinguishedName	—	m		
5.2.2	nonspecificForm	—	m		
5.2.3	localDistinguishedName	—	m		
6	additionalText	—	m		
7	additionalInformation	Required for some objects	m		

<sup>7)</sup> This parameter is used to carry any attribute type. However, for a particular notification only the attributes of the corresponding managed object instance undergoing value change are allowed to be present.

## Annex C

### MOCS proforma<sup>8)</sup>

(This annex forms an integral part of this Recommendation | International Standard)

#### C.1 Introduction

The purpose of this MOCS proforma is to provide a mechanism for a supplier of an implementation which claims to conform to a managed object class, to provide conformance information in a standard form.

#### C.2 Instructions for completing the MOCS proforma to produce a MOCS<sup>9)</sup>

The MOCS proforma contained in this annex is comprised of information in tabular form, in accordance with ITU-T Rec X.724 | ISO/IEC 10165-6. The supplier of the implementation shall state which items are supported in tables below and if necessary provide additional information.

#### C.3 Symbols, abbreviations and terms

The following abbreviations are used throughout the proformas:

dmi-moc	joint-iso-ccitt ms(9) smi(3) part2(2) managedobjectClass(3)
dmi-att	joint-iso-ccitt ms(9) smi(3) part2(2) attribute(7)
dmi-not	joint-iso-ccitt ms(9) smi(3) part2(2) notification(10)
dmi-pkg	joint-iso-ccitt ms(9) smi(3) part2(2) package(4)

The notations used in the Status and Support columns are specified in A.1.3.

The following requirement is commonly used throughout this MOCS proforma:

- c1: if C.3/3a or C.3/6a or C.3/7a or C.3/8a or C.3/9a or C.3/ 10a or C.3/12a or C.3/13a then m else —
- c2: if C.1/1b then — else m
- c10: if C.7/3a or C.7/6a or C.7/7a or C.7/8a or C.7/9a or C.7/ 10a or C.7/12a or C.7/13a then m else —
- c11: if C.5/1b then — else m
- c19: if C.11/3a or C.11/6a or C.11/7a or C.11/8a or C.11/9a or C.11/ 10a or C.11/12a or C.11/13a then m else —
- c20: if C.9/1b then — else m

<sup>8)</sup> Users of this Recommendation | International Standard may freely reproduce the MOCS proforma in this annex so that it can be used for its intended purpose, and may further publish the completed MOCS. Instructions for completing the MOCS proforma are specified in ITU-T Rec. X.724 | ISO/IEC 10165-6.

<sup>9)</sup> Instructions for MOCS proforma are specified in ITU-T Rec. X.724 | ISO/IEC 10165-6.

C.4 Object creation record managed object class

C.4.1 Statement of conformance to the managed object class

Table C.1 — Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	ObjectCreationRecord	{dmi-moc 8}		

If the answer to the actual class question in the managed object class support table is "NO", the supplier of the implementation shall supply the actual class support details, in Table C.2.

Table C.2 — Actual class support

Index	Actual managed object class template label	Value of object identifier for managed object class	Additional information
1			

C.4.2 Packages

Table C.3 — Object creation record packages

Index	Package template label	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	topPackage	—	—	m		
2	packagesPackage	{dmi-pkg 16}	—	c1		
3	allomorphicPackage	{dmi-pkg 17}	—	c2		
4	logRecordPackage	—	—	m		
5	eventLogRecordPackage	—	—	m		
6	eventTimePackage	{dmi-pkg 11}	—	o		
7	notificationIdentifierPackage	{dmi-pkg 24}	—	o		
8	correlatedNotificationPackage	{dmi-pkg 23}	—	o		
9	additionalTextPackage	{dmi-pkg 19}	—	o		
10	additionalInformationPackage	{dmi-pkg 18}	—	o		
11	objectCreationRecordPackage <sup>10)</sup>	—	—	m		
12	sourceIndicatorPackage	{dmi-pkg 28}	—	o		
13	attributeListPackage	{dmi-pkg 21}	—	o		

<sup>10)</sup> This package has no attributes.

## C.4.3 Attributes

Table C.4 — Object creation attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by Create		Get		Replace	
				Status	Support	Status	Support	Status	Support
1	objectClass	{dmi-att 65}	—	x		m		x	
2	nameBinding	{dmi-att 63}	—	x		m		x	
3	packages	{dmi-att 66}	—	x		c1		x	
4	allomorpha	{dmi-att 50}	—	x		c2		x	
5	logRecordId	{dmi-att 3}	—	x		m		x	
6	loggingTime	{dmi-att 59}	—	x		m		x	
7	managedObjectClass	{dmi-att 60}	—	x		m		x	
8	managedObjectInstance	{dmi-att 61}	—	x		m		x	
9	eventType	{dmi-att 14}	—	x		m		x	
10	eventTime	{dmi-att 13}	—	x		c3		x	
11	notificationIdentifier	{dmi-att 16}	—	x		c4		x	
12	correlatedNotifications	{dmi-att 12}	—	x		c5		x	
13	additionalText	{dmi-att 7}	—	x		c6		x	
14	additionalInformation	{dmi-att 6}	—	x		c7		x	
15	sourceIndicator	{dmi-att 26}	—	x		c8		x	
16	attributeList	{dmi-att 9}	—	x		c9		x	

c3: if C.3/6a then m else —

c4: if C.3/7a then m else —

c5: if C.3/8a then m else —

c6: if C.3/9a then m else —

c7: if C.3/10a then m else —

c8: if C.3/12a then m else —

c9: if C.3/13a then m else —

continued on next page

Table C.4 (concluded)—Object creation attribute support

Index	Add		Remove		Set To Default		Additional information
	Status	Support	Status	Support	Status	Support	
1	—		—		—		
2	—		—		—		
3	x		x		—		
4	x		x		—		
5	—		—		—		
6	—		—		—		
7	—		—		—		
8	—		—		—		
9	—		—		—		
10	—		—		—		
11	—		—		—		
12	x		x		—		
13	—		—		—		
14	x		x		—		
15	—		—		—		
16	x		x		—		

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

## C.5 Object deletion record managed object class

### C.5.1 Statement of conformance to the managed object class

Table C.5 — Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	Object creation record	{dmi-moc 9}		

If the answer to the actual class question in the managed object class support table is "NO", the supplier of the implementation shall supply the actual class support details, in Table C.6.

Table C.6 — Actual class support

Index	Actual managed object class template label	Value of object identifier for managed object class	Additional information
1			

### C.5.2 Object deletion record packages

Table C.7 — Object deletion record packages

Index	Package name	Value of object identifier for package	Constraints and values	Status	Support	Additional information
1	topPackage	—	—	m		
2	packagesPackage	{dmi-pkg 16}	—	c10		
3	allomorphicPackage	{dmi-pkg 17}	—	c11		
4	logRecordPackage	—	—	m		
5	eventLogRecordPackage	—	—	m		
6	eventTimePackage	{dmi-pkg 11}	—	o		
7	notificationIdentifierPackage	{dmi-pkg 24}	—	o		
8	correlatedNotificationPackage	{dmi-pkg 23}	—	o		
9	additionalTextPackage	{dmi-pkg 19}	—	o		
10	additionalInformationPackage	{dmi-pkg 18}	—	o		
11	objectDeletionRecordPackage <sup>11)</sup>	—	—	m		
12	sourceIndicatorPackage	{dmi-pkg 28}	—	o		
13	attributeListPackage	{dmi-pkg 21}	—	o		

<sup>11)</sup> This package has no attributes.

C.5.3 Attributes

Table C.8—Object deletion record attribute support

Index	Attribute template label	Value of object identifier for attribute	Constraints and values	Set by Create		Get		Replace	
				Status	Support	Status	Support	Status	Support
1	objectClass	{dmi-att 65}	—	x		m		x	
2	name Binding	{dmi-att 63}	—	x		m		x	
3	packages	{dmi-att 66}	—	x		c10		x	
4	allomorphs	{dmi-att 50}	—	x		c11		x	
5	logRecordId	{dmi-att 3}	—	x		m		x	
6	loggingTime	{dmi-att 59}	—	x		m		x	
7	managedObjectClass	{dmi-att 60}	—	x		m		x	
8	managedObjectInstance	{dmi-att 61}	—	x		m		x	
9	eventType	{dmi-att 14}	—	x		m		x	
10	eventTime	{dmi-att 13}	—	x		c12		x	
11	notificationIdentifier	{dmi-att 16}	—	x		c13		x	
12	correlatedNotifications	{dmi-att 12}	—	x		c14		x	
13	additionalText	{dmi-att 7}	—	x		c15		x	
14	additionalInformation	{dmi-att 6}	—	x		c16		x	
15	sourceIndicator	{dmi-att 26}	—	x		c17		x	
16	attributeList	{dmi-att 9}	—	x		c18		x	

c12: if C.7/6a then m else —

c13: if C.7/7a then m else —

c14: if C.7/8a then m else —

c15: if C.7/9a then m else —

c16: if C.7/10a then m else —

c17: if C.7/12a then m else —

c18: if C.7/13a then m else —

continued on next page

Table C.8 (concluded)—Object deletion record attribute support

Index	Add		Remove		Set To Default		Additional information
	Status	Support	Status	Support	Status	Support	
1	—		—		—		
2	—		—		—		
3	x		x		—		
4	x		x		—		
5	—		—		—		
6	—		—		—		
7	—		—		—		
8	—		—		—		
9	—		—		—		
10	—		—		—		
11	—		—		—		
12	x		x		—		
13	—		—		—		
14	x		x		—		
15	—		—		—		
16	x		x		—		

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 12059-1:1995

C.6 Attribute value change record managed object class

C.6.1 Statement of conformance to the managed object class

Table C.9 — Managed object class support

Index	Managed object class template label	Value of object identifier for class	Support of all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	attributeValueChangeRecord	{dmi-moc 2}		

If the answer to the actual class question in the managed object class support table is "NO", the supplier of the implementation shall supply the actual class support details, in Table C.10.

Table C.10 — Actual class support

Index	Actual managed object class template label	Value of object identifier for managed object class	Additional information
1			

C.5.2 Attribute value change record packages

Table C.11 — Attribute value change record packages

Index	Package name	Value of object identifier	Constraints and values	Status	Support	Additional information
1	topPackage	—	—	m		
2	packagesPackage	{dmi-pkg 16}	—	c19		
3	allomorphicPackage	{dmi-pkg 17}	—	c20		
4	logRecordPackage	—	—	m		
5	eventLogRecordPackage	—	—	m		
6	eventTimePackage	{dmi-pkg 11}	—	o		
7	notificationIdentifierPackage	{dmi-pkg 24}	—	o		
8	correlatedNotificationPackage	{dmi-pkg 23}	—	o		
9	additionalTextPackage	{dmi-pkg 19}	—	o		
10	additionalInformationPackage	{dmi-pkg 18}	—	o		
11	attributeValueChangeRecordPackage	—	—	m		
12	sourceIndicatorPackage	{dmi-pkg 28}	—	o		
13	attributeIdentifierListPackage	{dmi-pkg 20}	—	o		