

First edition
2006-08-01

**Information technology — Common
Language Infrastructure (CLI) —
Technical Report: Common Generics**

*Technologies de l'information — Infrastructure commune de
langage (ICL) — Rapport technique: Génériques communs*

IECNORM.COM : Click to view the full PDF of ISO/IEC TR 25438:2006

Reference number
ISO/IEC TR 25438:2006(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

IECNORM.COM : Click to view the full PDF of ISO/IEC TR 25438:2006

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction	vi
1 Scope	1
2 Rationale	1
2.1 Reference vs. value tuples.....	1
2.2 Interaction with other standard types.....	2
3 Overview	2
3.1 Tuple types	2
3.2 Function and procedure types	2
3.3 Unit	2
3.4 Optional	3
3.5 Either	3
4 Action delegates	3
4.1 System.Action delegate	3
4.2 System.Action<A, B> delegate	4
4.3 System.Action<A, B, C> delegate	5
4.4 System.Action<A, B, C, D> delegate.....	6
4.5 System.Action<A, B, C, D, E> delegate	8
5 System.DelegateCast class	9
5.1 DelegateCast.ToFunction<T, Boolean>(System.Predicate<T>) method.....	10
5.2 DelegateCast.ToPredicate<T>(System.Function<T, System.Boolean>) method.....	10
5.3 DelegateCast.ToFunction<T, U>(System.Converter<T, U>) method.....	11
5.4 DelegateCast.ToConverter<T, U>(System.Function<T, U>) method.....	12
5.5 DelegateCast.ToFunction<T, T, System.Int32>(System.Comparison<T>) method	12
5.6 DelegateCast.ToComparison<T>(System.Function<T, T, System.Int32>) method	13
6 System.Either<A, B> Structure	13
6.1 Either<A, B>.Equals(System.Object) method	15
6.2 Either<A, B>.Equals(Either<A, B>) method	16
6.3 Either<A, B>.First property	17
6.4 Either<A, B>.GetHashCode() method	17
6.5 Either<A, B>.IsFirst property	18
6.6 Either<A, B>.IsSecond property	19
6.7 Either<A, B>.op_Equality(Either<A, B>, Either<A, B>) method	19
6.8 Either<A, B>.op_Inequality(Either<A, B>, Either<A, B>) method	20
6.9 Either<A, B>.Second property	21
6.10 Either<A, B>.MakeFirst(A aValue) method.....	22
6.11 Either<A, B>.MakeSecond(B bValue) method	22
6.12 Either<A, B>.ToString() method	23
6.13 Either<A, B>(A) constructor	23
6.14 Either<A, B>(B) constructor	24
6.15 A Either<A, B>.op_Explicit(System.Either<A, B>) method	25
6.16 B Either<A, B>.op_Explicit(System.Either<A, B>) method	26
6.17 Either<A, B>.op_Implicit(A) method	27
6.18 Either<A, B>.op_Implicit(B) method	28
7 Function Delegates.....	29
7.1 System.Function<A > delegate	29
7.2 System.Function<A, B> delegate	30
7.3 System.Function<A, B, C> delegate	31

7.4	System.Function<A, B, C, D> delegate	32
7.5	System.Function<A, B, C, D, E> delegate	33
7.6	System.Function<A, B, C, D, E, F> delegate	35
8	System.Optional<T> structure	36
8.1	Optional<T>(T) constructor	38
8.2	Optional<T>.CompareTo(System.Object) method	38
8.3	Optional<T>.CompareTo(Optional<T>) method	40
8.4	Optional<T>.Equals(System.Object) method	41
8.5	Optional<T>.Equals(Optional<T>) method	42
8.6	Optional<T>.FromNullable<U>(Nullable<U>) method	43
8.7	Optional<T>.FromOptional(System.Optional<T>) method	44
8.8	Optional<T>.GetHashCode() method	45
8.9	Optional<T>.GetValueOrDefault() method	45
8.10	Optional<T>.GetValueOrDefault(T) method	46
8.11	Optional<T>.HasValue property	46
8.12	Optional<T>.op_Equality(Optional<T>, Optional<T>) method	47
8.13	Optional<T>.op_Explicit(System.Optional<T>) method	48
8.14	Optional<T>.op_Implicit(T) method	49
8.15	Optional<T>.op_Inequality(Optional<T>, Optional<T>) method	50
8.16	Optional<T>.ToNullable<U>(Optional<U>) method	51
8.17	Optional<T>.ToOptional(T) method	51
8.18	Optional<T>.ToString() method	52
8.19	Optional<T>.Value property	53
8.20	Optional<T>.NullableValue.Value property	53
9	Tuple structures System.Tuple<A, B> ... System.Tuple<A, B, ..., I, J>	54
9.1	Tuple<A, ...>() constructors	56
9.2	Tuple<A, ...>.Equals(System.Object) method	56
9.3	Tuple<A, ...>.Equals(Tuple<A, ...>) method	57
9.4	Tuple<A, ...>.ItemA, Tuple<A, B, ...>.ItemB, ... Tuple<A, B, ..., I, J>.ItemJ field	58
9.5	Tuple<A, ...>.GetHashCode() method	58
9.6	Tuple<A, ...>.op_Equality(Tuple<A, ...>, Tuple<A, ...>) method	59
9.7	Tuple<A, B>.op_Implicit(KeyValuePair<A, B>) method	60
9.8	Tuple<A, B>.op_Implicit(Tuple<A, B>) method	60
9.9	Tuple<A, ...>.op_Inequality(Tuple<A, ...>, Tuple<A, ...>) method	61
9.10	Tuple<A, ...>.ToString() method	62
10	System.Unit enum	62
10.1	Unit.Unit field	63

IECNORM.COM · Click to view the full PDF of ISO/IEC TR 25438:2006

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In exceptional circumstances, the joint technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the joint technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TR 25438 was prepared by Ecma International (as Ecma TR/89) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Introduction

This Technical Report defines a collection of types that are intended to enhance the common language nature of the CLI, by facilitating language inter-operation. The collection includes generic tuples, functions, actions, optional value representation, a type that can contain a value of one of two different types, and a utility filler type.

These types are experimental and will be considered for inclusion in a future version of the CLI International Standard. A reference implementation, written in C#, is included (see the accompanying file `CommonGenericsLibrary.cs`). This implementation source is also available from <http://kahu.zoot.net.nz/ecma>. A binary version is also available from that site, along with any updates to the proposal.

Feedback on these types is encouraged. (Please send comments to ecmacli@zoot.net.nz.)

IECNORM.COM : Click to view the full PDF of ISO/IEC TR 25438:2006

Information technology — Common Language Infrastructure (CLI) — Technical Report: Common Generics

1 Scope

The CLI standard libraries (ISO/IEC 23271) provide a collection of common types that can be used by multiple languages. With the addition of generics to the CLI, the standard libraries have been extended to include a number of common generic types, in particular, collections. However, at present, these libraries do not include many simple generic types found in a number of different languages. Any language which uses these common types must implement them rather than deferring to the CLI library, thereby reducing language interoperability. This Technical Report addresses this issue by providing a number of these common types.

Generic tuples (product types) are standard in a number of languages: C++ (`template Pair`), Ada, Haskell, and Standard ML (SML). However, languages differ in the number of pre-defined tuple sizes supported by their standard libraries; e.g. C++ provides just one (`Pair`) while Haskell provides eight (sizes 2 to 9) and SML allows any size of tuple. This Technical Report provides nine (sizes 2 to 10).

Generic programming encourages “higher order” programming where generic functions (methods) take function (delegate) type arguments that have generic types. Examples include Ada’s `with` and generic constraints, and function arguments in Haskell and SML. In the CLI, function values are provided in the form of delegates, so this proposal defines standard generic delegate types for functions (which return a value) and procedures (which do not).

Another two types that occur in a number of languages are an *optional* type, which either contains a value of some other type or an indication that such a value is not present; and an *either* type, which holds a value of one of two possible types and an indication of which one is present. This proposal provides both of these.

Note The optional type is similar to, but different from, the type `System.Nullable`.

Finally, in existing generic languages, a need has been found for a *filler* type to be used when a particular generic parameter is not required for a particular use of the generic type. A standard one-value type is often provided for this purpose, often called `Unit` or `Void`. This Technical Report includes such a type.

2 Rationale

2.1 Reference vs. value tuples

In some languages (such as C++ and Ada) tuple types can be value or reference types, while in others (such as Haskell and SML) they are always reference types. This implementation provides only value type tuples (which can contain value or reference types). Boxed versions of these types can be used when reference versions are required. Named boxed types would, of course, help greatly here, but these are not currently provided by the CLI Standard.

A simple generic type, such as `Boxed<T>`, can be written to address this issue. Such a type has been made available in the reference implementation of this proposal. However it is not being considered for standardization at this time.

2.2 Interaction with other standard types

The CLI Standard contains six types related to those in this proposal. These are:

System.Action<T>: This type is just the first member of this collection's set of action types. As it is already standardized it is not included here.

System.Comparison<T>: This type is equivalent to this collection's `Function<T, T, Int32>`. Conversion methods are provided.

System.Converter<T,U>: This type is equivalent to this collection's `Function<T, U>`. Conversion methods are provided.

System.Nullable<T>: This type is a restricted version of this collection's `Optional<T>`. The difference is that `Nullable<T>` is restricted to non-nullable value types, whereas `Optional<T>` can also wrap reference types and nullable value types. Both these choices are useful in different applications, so there is no clash between these two types. This proposal includes operators on the `Optional<T>` type to convert to/from `Nullable<T>` values.

System.Predicate<T>: This type is equivalent to this collection's `Function<T, Boolean>`. However as the CLI does not support type synonyms, these two types are (unfortunately) not equivalent. A separate static class provides methods to convert between these two types. The methods are in a separate class as additional methods cannot be declared on delegate types.

System.Collections.Generic.KeyValuePair<K,V>: This is just a differently named equivalent of this collection's `Tuple<K,V>`. Conversion operators are provided on `Tuple<K,V>` to convert to/from `KeyValuePair<K,V>`.

3 Overview

3.1 Tuple types

Tuples are provided as value types with public fields, which mirrors their typical usage in current languages. Overloading on arity is leveraged to provide eight standard tuple types.

The fields are named `ItemA`, `ItemB`, ..., `ItemI`. A single n-ary constructor is provided to easily define all fields.

An `Equals()` method is provided and defined as the component fields being equal according to their `Equals()` methods.

The corresponding `GetHashCode()` method and `op_Equality` and `op_Inequality` methods are provided.

`ToString()` is overridden to provide the typical tuple parenthesized notation.

For tuples of size 2, methods are provided to convert to/from values of type `System.Collections.Generic.KeyValuePair<K, V>`.

3.2 Function and procedure types

Standard delegates are provided for function types (`System.Function<>`) and procedures (`System.Action<>`). Delegates are defined for 0 to 5 argument functions and 0 and 2 to 5 argument procedures. (The single argument procedure is already included in the CLI Standard.)

3.3 Unit

The `Unit` type is a filler type. This is useful, for example, when an existing generic type is used, but one of its type arguments is not required for the particular application.

3.4 Optional

The `Optional<A>` type represents either a value of type A, or the lack of a value. A value of this type is immutable and provides two constructors, one providing a value, the other for providing no value. Properties are provided to test for validity and to obtain the value. An exception is thrown if an attempt to access a non-existent value.

3.5 Either

The `Either<A, B>` type represents either a value of type A, or a value of type B. A value of this type is immutable. Properties are provided to test which type of value is present and to obtain the value. An exception is thrown if an attempt to access the value of one type is made when a value of the other type is present.

4 Action delegates

4.1 System.Action delegate

```
[ILAsm]
.class public auto ansi sealed System.Action
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance void Invoke()
}

[C#]
public delegate void Action();
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - `CLSCompliantAttribute(true)`

Implements:

- `System.ICloneable`

Summary:

Represents a method that performs an action.

Parameters:

Inherits From: `System.Delegate`

Library: BCL

Description

A generic delegate type for zero-argument, methods which perform an action (return void)

4.2 System.Action<A, B> delegate

```
[ILAsm]
.class public auto ansi sealed System.Action`2<A, B>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance void Invoke(!0 argA,
                            !1 argB)
}

[C#]
public delegate void Action<A, B>
    (A argA,
     B argB
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - `CLSCompliantAttribute(true)`

Implements:

- `System.ICloneable`

Summary:

Represents a method that performs an action using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the action.
<i>argB</i>	The second argument to the action.

Inherits From: `System.Delegate`

Library: BCL

Description

A generic delegate type for two-argument methods, which perform an action (return void).

4.3 System.Action<A, B, C> delegate

```

[ILAsm]
.class public auto ansi sealed System.Action`3<A, B, C>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance void Invoke(!0 argA,
                             !1 argB,
                             !2 argC)
}

[C#]
public delegate void Action<A, B, C>
    (A argA,
     B argB,
     C argC
    );

```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*

- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs an action using the supplied arguments.

Parameters:

Parameter	Description
argA	The first argument to the action.
argB	The second argument to the action.
argC	The third argument to the action.

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for three-argument methods, which perform an action (return void).

4.4 System.Action<A, B, C, D> delegate

```

[ILAsm]
.class public auto ansi sealed System.Action`4<A, B, C, D>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance void Invoke(!0 argA,
                            !1 argB,
                            !2 argC,
                            !3 argD)
}

[C#]
public delegate void Action<A, B, C, D>
    (A argA,
     B argB,
     C argC,
     D argD
    );
    
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- `System.ICloneable`

Summary:

Represents a method that performs an action using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the action.
<i>argB</i>	The second argument to the action.
<i>argC</i>	The third argument to the action.
<i>argD</i>	The fourth argument to the action.

Inherits From: `System.Delegate`

Library: BCL

Description

A generic delegate type for four-argument methods, which perform an action (return void).

4.5 System.Action<A, B, C, D, E> delegate

```
[ILAsm]
.class public auto ansi sealed System.Action`5<A, B, C, D, E>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance void Invoke(!0 argA,
                               !1 argB,
                               !2 argC,
                               !3 argD,
                               !4 argE)
}

[C#]
public delegate void Action<A, B, C, D, E>
    (A argA,
     B argB,
     C argC,
     D argD,
     E argE
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs an action using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the action.
<i>argB</i>	The second argument to the action.
<i>argC</i>	The third argument to the action.
<i>argD</i>	The fourth argument to the action.
<i>argE</i>	The fifth argument to the action.

Inherits From: `System.Delegate`

Library: BCL

Description

A generic delegate type for five-argument methods, which perform an action (return void).

5 System.DelegateCast class

```
[ILAsm]
.class public abstract sealed beforefieldinit System.DelegateCast
    extends System.Object

[C#]
public static class DelegateCast
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - `CLSCompliantAttribute(true)`

Summary

Provides methods for converting between `System.Function<>` and corresponding `System.Predicate<T>`, `System.Converter<T, U>` and `System.Comparison<T>` delegate types.

Inherits From: `System.Object`

Library:

Thread Safety: This type is safe for multithreaded operations.

Description

5.1 DelegateCast.ToFunction<T, Boolean>(System.Predicate<T>) method

```
[ILAsm]
.method public hidebysig static class Function`2<!!0, bool>
    ToFunction<T>(class Predicate`1<!!0> pred)

[C#]
public static Function<T, bool> ToFunction<T>(Predicate<T> pred)
```

Summary

Constructs a `System.Function<T, bool>` value equivalent to the given `System.Predicate<T>` value.

Parameters

Parameter	Description
<i>pred</i>	The <code>System.Predicate<T></code> to convert.

Return Value

A `System.Function<T, bool>` value, functionally equivalent to the `System.Predicate<T>` argument.

Description

5.2 DelegateCast.ToPredicate<T>(System.Function<T, System.Boolean>) method

```
[ILAsm]
.method public hidebysig static class Predicate`1<!!0>
    ToPredicate<T>(class Function`2<!!0, bool> func)

[C#]
public static Predicate<T> ToPredicate<T>(Function<T, bool> func)
```

Summary

Constructs a `System.Predicate<T>` value equivalent to the given `System.Function<T, Boolean>` value.

Parameters

Parameter	Description
<i>Func</i>	The <code>System.Function<T, bool></code> to convert.

Return Value

A `System.Predicate<T>` value functionally equivalent to the `System.Function<T, bool>` argument.

Description

5.3 DelegateCast.ToFunction<T, U>(System.Converter<T, U>) method

```
[ILAsm]
.method public hidebysig static class Function`2<!!0, !!1>
    ToFunction<T, U>(class Converter`2<!!0, !!1> conv)

[C#]
public static Function<T, U> ToFunction<T, U>(Converter<T, U> conv)
```

Summary

Constructs a `System.Function<T, U>` value equivalent to the given `System.Converter<T, U>` value.

Parameters

Parameter	Description
<i>conv</i>	The <code>System.Converter<T, U></code> to convert.

Return Value

A `System.Function<T, U>` value functionally equivalent to the `System.Converter<T, U>` argument.

Description

5.4 DelegateCast.ToConverter<T, U>(System.Function<T, U>) method

```
[ILAsm]
.method public hidebysig static class Converter`2<!!0, !!1>
    ToConverter<T, U>(class Function`2<!!0, !!1> func)

[C#]
public static Converter<T, U> ToConverter<T, U>(Function<T, U> func)
```

Summary

Constructs a System.Converter<T, U> value equivalent to the given System.Function<T, U> value.

Parameters

Parameter	Description
<i>func</i>	The System.Function<T, U> to convert.

Return Value

A System.Converter<T, U> value functionally equivalent to the System.Function<T, U> argument.

Description

5.5 DelegateCast.ToFunction<T, T, System.Int32>(System.Comparison<T>) method

```
[ILAsm]
.method public hidebysig static class Function`3<!!0, !!1, int>
    ToFunction<T>(class Comparison`1<!!0> comp)

[C#]
public static Function<T, T, int> ToFunction<T>(Comparison<T> comp)
```

Summary

Constructs a System.Function<T, T, Int32> value equivalent to the given System.Comparison<T> value.

Parameters

Parameter	Description
<i>comp</i>	The System.Comparison<T> to convert.

Return Value

A `System.Function<T, T, System.Int32>` value functionally equivalent to the `System.Comparison<T>` argument.

Description**5.6 DelegateCast.ToComparison<T>(System.Function<T, T, System.Int32>) method**

```
[ILAsm]
.method public hidebysig static class Comparison`1<!!0>
    ToComparison<T>(class Function`3<!!0,!!1,int> func)

[C#]
public static Comparison<T> ToComparison<T>(Function<T, T, int> func)
```

Summary

Constructs a `System.Comparison<T>` value equivalent to the given `System.Function<T, T, Int32>` value.

Parameters

Parameter	Description
<i>func</i>	The <code>System.Function<T, T, Int32></code> to convert.

Return Value

A `System.Comparison<T>` value functionally equivalent to the `System.Function<T, T, Int32>` argument.

Description**6 System.Either<A, B> Structure**

```
[ILAsm]
.class public sequential serializable sealed Either`2<A, B> extends
System.ValueType implements IEquatable`1<valuetype Either`2<A, B>>

[C#]
public struct Either<A, B> : IEquatable<Either<A, B>>
```

Assembly Info:

- *Name:*
- *Public Key:*

- *Version:*

- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.IEquatable<Either<A, B>>

Summary

Contains a value of type A or a value of type B.

Inherits From: System.ValueType

Library:

Thread Safety: This type is not guaranteed to be safe for multithreaded operations.

Description

The `System.Either<A, B>` value type represents either a value of a given type A or a value of a given type B. For example, an instance of `System.Either<System.Int32, System.String>` contains either a `System.Int32` value or a `System.String` value. Instances of this type are immutable.

An instance of `System.Either<A, B>` has four key properties; `IsFirst`, `IsSecond`, `First`, and `Second`. `IsFirst` and `IsSecond` are used to determine whether the current instance has a value of type A or a value of a given B. They return `true` or `false`, and never throw an exception. `First` and `Second` return the value of the instance, provided it is of the appropriate type (i.e., `First` or `Second` are `true` respectively); otherwise, they throw an exception.

Calling `System.Either<A, B>.IsFirst` on an instance that has the default initial value returns `true` and calling `System.Either<A, B>.First` returns the default value of type A.

See the methods `System.Either<A, B>.MakeFirst` and `System.Either<A, B>.MakeSecond` for how to create new instances initialized to values of type A or type B respectively.

See also `System.Nullable<T>` (for value types T) and `System.Optional<T>` (for all types T) that represent either a value of type T or the lack of such a value.

6.1 Either<A, B>.Equals(System.Object) method

```
[ILAsm]
.method public hidebysig virtual bool Equals(object other)

[C#]
public override bool Equals(object other)
```

Summary

Determines whether the current instance and the specified System.Object represent the same type and value.

Parameters

Parameter	Description
<i>other</i>	The System.Object to compare to the current instance.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions
false	<i>other</i> is null or the current instance and <i>other</i> have different types.
false	IsFirst is false and <i>other</i> .IsFirst is true.
false	IsFirst is true and <i>other</i> .IsFirst is false.
First.Equals(<i>other</i> .First)	IsFirst is true and <i>other</i> .IsFirst is true
Second.Equals(<i>other</i> .Second)	IsFirst is false and <i>other</i> . IsFirst is false

Description

[*Note:* This method overrides System.Object.Equals.]

6.2 Either<A, B>.Equals(Either<A, B>) method

```
[ILAsm]
.method public hidebysig virtual bool Equals(valuetype Either`2<A, B> other)

[C#]
public bool Equals(Either<A, B> other)
```

Summary

Determines whether the current instance and the specified System.Either<A, B> represent the same value.

Parameters

Parameter	Description
<i>other</i>	The System.Either<A, B> to compare to the current instance.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions
false	IsFirst is false and other.IsFirst is true.
false	IsFirst is true and other.IsFirst is false.
First.Equals(other.First)	IsFirst is true and other.IsFirst is true
Second.Equals(other.Second)	IsFirst is false and other.IsFirst is false

Description

[Note: This method implicitly implements the System.IEquatable<Either<A, B>>.Equals method.]

6.3 Either<A, B>.First property

```
[ILAsm]
.property !0 First()
{
    .get instance !0 get_First()
}
.method public hidebysig specialname instance !0 get_First()

[C#]
public A First { get; }
```

Summary

Gets the value of type A, if any, of the current instance.

Property Value

The value of type A of the current instance.

Behaviors

If `System.Either<A, B>.IsFirst` is true, the instance contains a value of type A, and `System.Either<A, B>.First` returns that value. If `System.Either<A, B>.IsFirst` is false, the instance has a value of type B, and an attempt to read `System.Either<A, B>.First` results in an exception.

This property is read-only.

Exceptions

Exception	Condition
<code>System.InvalidOperationException</code>	<code>System.Either<A, B>.IsFirst</code> is false.

6.4 Either<A, B>.GetHashCode() method

```
[ILAsm]
.method public hidebysig virtual int32 GetHashCode()

[C#]
public override int GetHashCode()
```

Summary

Generates a hash code for the value of the current instance.

Return Value

A `System.Int32` containing the hash code for the value of the current instance is returned.

Description

The algorithm used to generate the hash code is unspecified.

[*Note:* This method overrides `System.Object.GetHashCode.`]

6.5 Either<A, B>.IsFirst property

```
[ILAsm]
.property bool IsFirst()
{
    .get instance bool get_IsFirst()
}
.method public hidebysig specialname instance bool get_IsFirst()

[C#]
bool IsFirst { get; }
```

Summary

Indicates whether the current instance contains a value of type A.

Property Value

true if the current instance was constructed by a call to `MakeFirst` or is the default value of `Either<A, B>`; otherwise, false.

Behaviors

If `System.Either<A, B>.IsFirst` is true, the instance contains a value of type A, `System.Either<A, B>.First` returns that value, and `System.Either<A, B>.IsSecond` returns false. If `System.Either<A, B>.IsFirst` is false, the instance contains a value of type B, `System.Either<A, B>.IsSecond` returns true, and an attempt to read `System.Either<A, B>.First` results in a `System.InvalidOperationException` exception.

This property is read-only.

6.6 Either<A, B>.IsSecond property

```
[ILAsm]
.property bool IsSecond()
{
    .get instance bool get_IsSecond()
}
.method public hidebysig specialname instance bool get_IsSecond()

[C#]
public bool IsSecond { get; }
```

Summary

Indicates whether the current instance contains a value of type B.

Property Value

true if the current instance was constructed by a call to `MakeSecond`; otherwise, false.

Behaviors

If `System.Either<A, B>.IsSecond` is true, the instance contains a value of type B, `System.Either<A, B>.Second` returns that value, and `System.Either<A, B>.IsFirst` returns false. If `System.Either<A, B>.IsSecond` is false, the instance contains a value of type A, `System.Either<A, B>.IsFirst` returns true, and an attempt to read `System.Either<A, B>.Second` results in a `System.InvalidOperationException` exception.

This property is read-only.

6.7 Either<A, B>.op_Equality(Either<A, B>, Either<A, B>) method

```
[ILAsm]
.method public hidebysig specialname static
    bool op_Equality(valuetype Either`2<!0, !1> left,
                    valuetype Either`2<!0, !1> right)

[C#]
public static bool operator==(Either<A, B> left, Either<A, B> right)
```

Summary

Determines whether the specified values are equal.

Parameters

Parameter	Description
<i>left</i>	The first <code>Either<A, B></code> value to compare.
<i>right</i>	The second <code>Either<A, B></code> value to compare.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions	
	<code>left.IsFirst</code>	<code>right.IsFirst</code>
<code>left.Second.Equals(right.Second)</code>	false	false
false	false	true
false	true	false
<code>left.First.Equals(right.First)</code>	true	true

Description

6.8 `Either<A, B>.op_Inequality(Either<A, B>, Either<A, B>)` method

```
[ILAsm]
.method public hidebysig specialname static
    bool op_Inequality(valueuetype Either`2<!0, !1> left,
        valueuetype Either`2<!0, !1> right)

[C#]
public static bool operator!=(Either<A, B> left, Either<A, B> right)
```

Summary

Determines whether the specified values are not equal.

Parameters

Parameter	Description
<i>left</i>	The first <code>Either<A, B></code> value to compare.
<i>right</i>	The second <code>Either<A, B></code> value to compare.

Return Value

The following table defines the conditions under which the return value is `true` or `false`:

Return Value	Conditions	
	left.IsFirst	right.IsFirst
Not <code>left.Second.Equals(right.Second)</code>	false	false
<code>true</code>	false	true
<code>true</code>	true	false
Not <code>left.First.Equals(right.First)</code>	true	true

Description

6.9 Either<A, B>.Second property

```
[ILAsm]
.property !1 Second()
{
    .get instance !1 get_Second()
}
.method public hidebysig specialname instance !1 get_Second()

[C#]
public B Second { get; }
```

Summary

Gets the value of type B, if any, of the current instance.

Property Value

The value of type B of the current instance.

Behaviors

If `System.Either<A, B>.IsSecond` is `true`, the instance contains a value of type B, and `System.Either<A, B>.Second` returns that value. If `System.Either<A, B>.IsSecond` is `false`, the instance has a value of type A, and an attempt to read `System.Either<A, B>.Second` results in an exception.

This property is read-only.

Exceptions

Exception	Condition
System.InvalidOperationException	System.Either<A, B>.IsSecond is false.

6.10 Either<A, B>.MakeFirst(A aValue) method

```
[ILAsm]
public hidebysig static valuetype Either`<!0, !1>MakeFirst(!0 aValue)

[C#]
public static Either<A, B> MakeFirst(A aValue)
```

Summary

Constructs and initializes a new instance of System.Either<A, B> containing the specified value of type A.

Parameters

Parameter	Description
aValue	The value for the new instance.

Description

Constructs a new instance of System.Either<A, B> containing the supplied value of type A. Once this constructor has executed, applying System.Either<A, B>.IsFirst to the new instance returns true and applying System.Either<A, B>.IsSecond to the new instance returns false.

6.11 Either<A, B>.MakeSecond(B bValue) method

```
[ILAsm]
public hidebysig static valuetype Either`<!0, !1>MakeSecond(!1 bValue)

[C#]
public static Either<A, B> MakeSecond(B bValue)
```

Summary

Constructs and initializes a new instance of System.Either<A, B> containing the specified value of type B.

Parameters

Parameter	Description
<i>bValue</i>	The value for the new instance.

Description

Constructs a new instance of `System.Either<A, B>` containing the supplied value of type B. Once this constructor has executed, applying `System.Either<A, B>.IsSecond` to the new instance returns `true`.

6.12 Either<A, B>.ToString() method

```
[ILAsm]
.method public hidebysig virtual string ToString()

[C#]
public override string ToString()
```

Summary

Returns a `System.String` representation of the value of the current instance.

Return Value

If `System.Either<A, B>.IsFirst` is `true`, `System.Either<A, B>.First.ToString()` is returned; otherwise, `System.Either<A, B>.Second.ToString()` is returned.

Description

[*Note:* This method overrides `System.Object.ToString()`.]

6.13 Either<A, B>(A) constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(A aValue)

[C#]
public Either(A aValue)
```

Attributes

- `CLSCompliantAttribute(false)`

Summary

Constructs and initializes a new instance of `System.Either<A, B>` which contains the given value of type A.

Description

Constructs a new instance of `System.Either<A, B>`. Once this constructor has executed, calling `System.Either<A, B>.IsFirst` on the new instance returns `true` and calling `System.Either<A, B>.First` returns the given value of type A.

[*Note:* If the type A is the same as the type B then this method unifies with the constructor which accepts a value of type B; therefore this method is not CLS-compliant and is marked as such.]

[*Note:* The construction implemented by this method corresponds exactly to calling the `System.Either<A, B>.MakeFirst` method.]

6.14 Either<A, B>(B) constructor

```
[ILAsm]
public rtspecialname specialname instance void ctor(B bValue)

[C#]
public Either(B bValue)
```

Attributes

- `CLSCompliantAttribute(false)`

Summary

Constructs and initializes a new instance of `System.Either<A, B>` which contains the given value of type B.

Description

Constructs a new instance of `System.Either<A, B>`. Once this constructor has executed, calling `System.Either<A, B>.IsSecond` on the new instance returns `true` and calling `System.Either<A, B>.Second` returns the given value of type B.

[*Note:* If the type A is the same as the type B then this method unifies with the constructor which accepts a value of type A; therefore this method is not CLS-compliant and is marked as such.]

[*Note:* The construction implemented by this method corresponds exactly to calling the `System.Either<A, B>.MakeSecond` method.]

6.15 A Either<A, B>.op_Explicit(System.Either<A, B>) method

```
[ILAsm]
.method public hidebysig static specialname !0 op_Explicit(valuetype
Either`2<!0, !1> abValue)

[C#]
public static explicit operator A(Either<A, B> abValue)
```

Attributes

- CLSCompliantAttribute(false)

Summary

Perform an explicit conversion of a `System.Either<A, B>` value to type `A`.

Parameters

Parameter	Description
<code>abValue</code>	The <code>System.Either<A, B></code> value to convert to type <code>A</code> .

Return Value

The value of type `A`, if any, of the specified value. Otherwise, an exception is thrown.

Description

An explicit conversion from a value of type `System.Either<A, B>` to a value of type `A`. If `System.Either<A, B>.IsFirst` is true the value is returned, otherwise an exception is thrown.

[Note: If the type `A` is the same as the type `B` then this method unifies with the `op_Explicit` which returns a value of type `B`, therefore this method is not CLS-compliant and is marked as such.]

[Note: The conversion implemented by this method corresponds exactly to obtaining the value of the `System.Either<A, B>.First` property.]

Exceptions

Exception	Condition
<code>System.InvalidOperationException</code>	<code>System.Either<A, B>.IsFirst</code> is false.

6.16 B Either<A, B>.op_Explicit(System.Either<A, B>) method

```
[ILAsm]
.method public hidebysig static specialname !1 op_Explicit(valuetype
Either`2<!0, !1> abValue)

[C#]
public static explicit operator B(Either<A, B> abValue)
```

Attributes

- CLSCompliantAttribute(false)

Summary

Perform an explicit conversion of a `System.Either<A, B>` value to type B.

Parameters

Parameter	Description
<i>abValue</i>	The <code>System.Either<A, B></code> value to convert to type B.

Return Value

The value of type B, if any, of the specified value. Otherwise, an exception is thrown.

Description

An explicit conversion from a value of type `System.Either<A, B>` to a value of type B. If `System.Either<A, B>.IsFirst` is true the value is returned otherwise an exception is thrown.

[Note: If the type A is the same as the type B then this method unifies with the `op_Explicit` which returns a value of type A, therefore this method is not CLS-compliant and is marked as such.]

[Note: The conversion implemented by this method corresponds exactly to obtaining the value of the `System.Either<A, B>.Second` property.]

Exceptions

Exception	Condition
<code>System.InvalidOperationException</code>	<code>System.Either<A, B>.IsSecond</code> is false.

6.17 Either<A, B>.op_Implicit(A) method

```
[ILAsm]
.method public hidebysig static specialname valuetype Either`2<!0, !1>
op_Implicit(!0 aValue)
```

```
[C#]
public static implicit operator Either<A, B>(A aValue)
```

Attributes

- CLSCompliantAttribute(false)

Summary

Perform an implicit conversion of a value of type *A* to a value of type `System.Either<A, B>`.

Parameters

Parameter	Description
<i>aValue</i>	The <i>A</i> value to convert to <code>System.Either<A, B></code> .

Return Value

A `System.Either<A, B>` with the specified value of type *A*.

Description

Perform a conversion from *aValue* to a value of type `System.Either<A, B>`. Calling `System.Either<A, B>.IsFirst` on the returned value returns `true`, and `System.Either<A, B>.First` returns the value.

[*Note:* If the type *A* is the same as the type *B* then this method unifies with the `op_Implicit` which takes a value of type *B*, therefore this method is not CLS-compliant and is marked as such.]

[*Note:* The conversion implemented by this method corresponds exactly to invoking the `System.Either<A, B>.MakeFirst(A)` method.]

6.18 Either<A, B>.op_Implicit(B) method

```
[ILAsm]
.method public hidebysig static specialname valuetype Either`2<!0, !1>
op_Implicit(!1 bValue)
```

```
[C#]
public static implicit operator Either<A, B>(B bValue)
```

Attributes

- CLSCompliantAttribute(false)

Summary

Perform an implicit conversion of a value of type B to a value of type `System.Either<A, B>`.

Parameters

Parameter	Description
<i>bValue</i>	The B value to convert to <code>System.Either<A, B></code> .

Return Value

A `System.Either<A, B>` with the specified value of type B.

Description

Perform a conversion from *bValue* to a value of type `System.Either<A, B>`. Calling `System.Either<A, B>.IsSecond` on the returned value returns `true`, and `System.Either<A, B>.Second` returns the value.

[Note: If the type A is the same as the type B then this method unifies with the `op_Implicit` which takes a value of type A, therefore this method is not CLS-compliant and is marked as such.]

[Note: The conversion implemented by this method corresponds exactly to invoking the `System.Either<A, B>.MakeSecond(B)` method.]

7 Function Delegates

7.1 System.Function<A> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`1<A>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !0 Invoke()
}

[C#]
public delegate A Function<A>();
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that returns a value.

Parameters:

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for zero-argument methods, which perform a function (return a value).

7.2 System.Function<A, B> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`2<A, B>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !1 Invoke(!0 argA)
}

[C#]
public delegate B Function<A, B>
    (A argA
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs a function using the supplied argument.

Parameters:

Parameter	Description
argA	The argument to the function.

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for one-argument methods, which perform a function (return a value).

7.3 System.Function<A, B, C> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`3<A, B, C>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !2 Invoke(!0 argA,
                            !1 argB)
}

[C#]
public delegate C Function<A, B, C>
    (A argA,
     B argB
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs a function using the supplied arguments.

Parameters:

Parameter	Description
argA	The first argument to the function.
argB	The second argument to the function.

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for two-argument methods, which perform a function (return a value).

7.4 System.Function<A, B, C, D> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`4<A, B, C, D>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !3 Invoke(!0 argA,
                          !1 argB,
                          !2 argC)
}

[C#]
public delegate D Function<A, B, C, D>
    (A argA,
     B argB,
     C argC
    );
```

Assembly Info:

- Name:
- Public Key:
- Version:
- Attributes:
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs a function using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the function.
<i>argB</i>	The second argument to the function.
<i>argC</i>	The third argument to the function.

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for three-argument methods, which perform a function (return a value).

7.5 System.Function<A, B, C, D, E> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`5<A, B, C, D, E>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !4 Invoke(!0 argA,
                          !1 argB,
                          !2 argC,
                          !3 argD)
}

[C#]
public delegate E Function<A, B, C, D, E>
    (A argA,
     B argB,
     C argC,
     D argD
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- `System.ICloneable`

Summary:

Represents a method that performs a function using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the function.
<i>argB</i>	The second argument to the function.
<i>argC</i>	The third argument to the function.
<i>argD</i>	The fourth argument to the function.

Inherits From: `System.Delegate`

Library: BCL

Description

A generic delegate type for four-argument methods, which perform a function (return a value).

7.6 System.Function<A, B, C, D, E, F> delegate

```
[ILAsm]
.class public auto ansi sealed System.Function`6<A, B, C, D, E, F>
    extends System.Delegate
{
    .method public hidebysig newslot virtual
        instance !5 Invoke(!0 argA,
                            !1 argB,
                            !2 argC,
                            !3 argD,
                            !4 argE)
}

[C#]
public delegate F Function<A, B, C, D, E, F>
    (A argA,
     B argB,
     C argC,
     D argD,
     E argE
    );
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- System.ICloneable

Summary:

Represents a method that performs a function using the supplied arguments.

Parameters:

Parameter	Description
<i>argA</i>	The first argument to the function.
<i>argB</i>	The second argument to the function.
<i>argC</i>	The third argument to the function.
<i>argD</i>	The fourth argument to the function.
<i>argE</i>	The fifth argument to the function.

Inherits From: System.Delegate

Library: BCL

Description

A generic delegate type for five-argument methods, which perform a function (return a value).

8 System.Optional<T> structure

```
[ILAsm]
.class public sequential serializable sealed
Optional`1<T>
extends System.ValueType
implements System.IComparable,
            System.IComparable`1<valuetype Optional`1<!0>>,
            System.IEquatable`1<valuetype Optional`1<!0>>,
            System.INullableValue

[C#]
public struct Optional<T> : IComparable,
                          IComparable<Optional<T>>,
                          IEquatable<Optional<T>>,
                          INullableValue
```

Assembly Info:

- *Name:*
- *Public Key:*
- *Version:*

- *Attributes:*
 - `CLSCompliantAttribute(true)`

Implements:

- `System.IComparable`
- `System.IComparable<System.Optional<T>>`
- `System.IEquatable<System.Optional<T>>`
- `System.INullableValue`

Summary

Represents an optional value. Similar to `System.Nullable<T>` except that the generic type parameter is not constrained in any way.

Inherits From: `System.ValueType`

Library:

Thread Safety: This type is not guaranteed to be safe for multithreaded operations.

Description

The `System.Optional<T>` value type represents a value of a given type `T` or the lack of such a value. For example an instance of `System.Optional<System.Int32>` contains a `System.Int32` value or an indication that no value is available. Instances of this type are immutable.

An instance of `System.Optional<T>` has two properties, `HasValue` and `Value`. Property `HasValue` is used to determine whether the current instance has a value of type `T`. It returns `true` or `false`, and never throws an exception. Property `Value` returns the value of the instance, provided it has one (i.e., `HasValue` is `true`); otherwise, it throws an exception.

In addition to the above properties, there is a pair of methods, both overloads of `GetValueOrDefault`. The version taking no arguments returns the instance's value of type `T`, if it has one; otherwise, it returns the default value of type `T`. The version taking a value argument of type `T` returns the instance's value of type `T`, if it has one; otherwise, it returns the value argument passed to it.

Applying `System.Optional<T>.HasValue` to an instance that has the default initial value returns `false`.

`System.Optional<T>` is similar to `System.Nullable<T>` but is not constrained to containing non-nullable value types. Conversion methods, `System.Optional<T>.FromNullable` and `System.Optional<T>.ToNullable`, are provided between the types.

See also `System.Either<A, B>` that represents either a value of type A or a value of type B.

8.1 `Optional<T>(T)` constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(!0 value)

[C#]
public Optional(T value)
```

Summary

Constructs and initializes a new instance of `System.Optional<T>` containing the specified value.

Parameters

Parameter	Description
<i>value</i>	The value for the new instance.

Description

Constructs a new instance of `System.Optional<T>` containing the supplied value of type T. Once this constructor has executed, calling `System.Optional<T>.HasValue` to the new instance returns `true` and `System.Optional<T>.Value` returns the value.

8.2 `Optional<T>.CompareTo(System.Object)` method

```
[ILAsm]
.method private final hidebysig virtual
    int32 CompareTo(object other)

[C#]
int CompareTo(object other)
```

Summary

Returns the sort order of the current instance compared to the specified `System.Object`.

Parameters

Parameter	Description
<i>other</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *other*. For non-zero values, the exact value returned by this method is unspecified. The following table defines the conditions under which the return value is a negative number, zero, or a positive number.

Return Value	Description
Any negative number	Current instance < <i>other</i> .
Zero	Current instance == <i>other</i> .
Any positive number	Current instance > <i>other</i> , or <i>other</i> is a null reference.

If *other* is null, the returned value is 0 if `System.Optional<T>.HasValue` is false, or 1 otherwise. If *other* is non-null but not an instance of `System.Optional<T>`, an exception is thrown. Otherwise, the result is computed from the `System.Optional<T>.HasValue` and `System.Optional<T>.Value` properties, as follows:

Return Value	Conditions	
	HasValue	<i>other</i> .HasValue
0	false	false or <i>other</i> is null
Some negative number	false	true
Some positive number	true	false or <i>other</i> is null
<code>Value.CompareTo(<i>other</i>.Value)</code>	true	true

Description

[*Note:* This method is implemented to support the `System.IComparable` interface.]

Exceptions

Exception	Condition
System.ArgumentException	<i>other</i> is not null and not an instance of Optional<T>. or Type T doesn't implement System.IComparable.

8.3 Optional<T>.CompareTo(Optional<T>) method

```

[ILAsm]
.method public hidebysig virtual final
    int32 CompareTo(valuetype Optional`1<!0> other)

[C#]
public int CompareTo(Optional<T> other)
    
```

Summary

Returns the sort order of the current instance compared to the specified object.

Parameters

Parameter	Description
<i>other</i>	The System.Optional<T> to compare to the current instance.

Return Value

A value that reflects the sort order of the current instance as compared to *other*. For non-zero values, the exact value returned by this method is unspecified. The following table defines the conditions under which the returned value is a negative number, zero, or a positive number.

Returned Value	Description
A negative value	The current instance is < <i>other</i> .
Zero	The current instance is == <i>other</i> .
A positive value	The current instance is > than <i>other</i> .

If either of the current instance or *other* is not an instance of `System.Optional<T>`, an exception is thrown. Otherwise, the result is computed from the `System.Optional<T>.HasValue` and `System.Optional<T>.Value` properties, as follows:

Return Value	Conditions	
	HasValue	other.HasValue
0	false	false
Some negative number	false	true
Some positive number	true	false
<code>Value.CompareTo(other.Value)</code>	true	true

Description

If `T` implements `System.IComparable<T>`, that interface's method is used. Otherwise, if `T` implements `System.IComparable`, that interface's method is used. Otherwise, an exception is thrown.

[*Note:* This method implicitly implements the `System.IComparable<Optional<T>>.CompareTo` method.]

Exceptions

Exception	Condition
<code>System.ArgumentException</code>	Type <code>T</code> doesn't implement <code>System.IComparable<T></code> or <code>System.IComparable</code> .

8.4 Optional<T>.Equals(System.Object) method

```
[ILAsm]
.method public hidebysig virtual bool Equals(object other)
```

```
[C#]
public override bool Equals(object other)
```

Summary

Determines whether the current instance and the specified `System.Object` represent the same type and value.

Parameters

Parameter	Description
<i>other</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

The following table defines the conditions under which the return value is `true` or `false`:

Return Value	Conditions	
	HasValue	other.HasValue
<code>false</code>	The current instance and <i>other</i> have different types.	
<code>true</code>	<code>false</code>	<code>false</code> or <i>other</i> is null
<code>false</code>	<code>false</code>	<code>true</code>
<code>false</code>	<code>true</code>	<code>false</code> or <i>other</i> is null
<code>Value.Equals(other.Value)</code>	<code>true</code>	<code>true</code>

Description

[*Note:* This method overrides `System.Object.Equals.`]

8.5 Optional<T>.Equals(Optional<T>) method

```
[ILAsm]
.method public hidebysig virtual final
    bool Equals(valuetype Optional`1<!0> other)

[C#]
public bool Equals(Optional<T> other)
```

Summary

Determines whether the specified object is equal to the current object.

Parameters

Parameter	Description
<i>other</i>	The <code>Optional<T></code> to compare to the current instance.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions	
	HasValue	other.HasValue
true	false	false
false	false	true
false	true	false
Value.Equals (other.Value)	true	true

Description

[*Note:* This method implicitly implements the `System.IEquatable<Optional<T>>.Equals` method.]

8.6 Optional<T>.FromNullable<U>(Nullable<U>) method

```
[ILAsm]
.method public hidebysig static valuetype Optional`1<!!0>
  FromNullable<valuetype U>
    (valuetype Nullable`1<!!0> value)

[C#]
public static Optional<U> FromNullable(Nullable<U> value)
  where U : struct
```

Summary

Perform a conversion of a `System.Nullable<U>` value to `System.Optional<U>`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Nullable<U></code> value to convert to <code>System.Optional<U></code> .

Return Value

A `System.Optional<U>` with the specified value.

Description

Perform a conversion of a `System.Nullable<U>` value to `System.Optional<U>`. The type `U` is constrained to be a value type to satisfy the requirements of `System.Nullable<U>`.

8.7 Optional<T>.FromOptional(System.Optional<T>) method

```
[ILAsm]
.method public hidebysig static !0 FromOptional(valuetype
System.Optional`1<!0> value)

[C#]
public static explicit operator T(Optional<T> value)
```

Summary

Perform a conversion of a `System.Optional<T>` value to type `T`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Optional<T></code> value to convert to type <code>T</code> .

Return Value

The value, if any, of the specified optional value. Otherwise, an exception is thrown.

Description

[*Note:* This method is provided for CLS compliance and is equivalent to `System.Optional<T>.op_explicit(T)`.]

[*Note:* The conversion implemented by this method corresponds exactly to obtaining the value of the `System.Optional<T>.Value` property.]

Exceptions

Exception	Condition
<code>System.InvalidOperationException</code>	<code>System.Optional<T>.HasValue</code> is false.

8.8 Optional<T>.GetHashCode() method

```
[ILAsm]
.method public hidebysig virtual int32 GetHashCode()

[C#]
public override int GetHashCode()
```

Summary

Generates a hash code for the value of the current instance.

Return Value

If `System.Optional<T>.HasValue` is true, a `System.Int32` containing the hash code for the value of the current instance is returned; otherwise, 0 is returned.

Description

The algorithm used to generate the hash code when `System.Optional<T>.HasValue` is true is unspecified.

[*Note:* This method overrides `System.Object.GetHashCode`.]

8.9 Optional<T>.GetValueOrDefault() method

```
[ILAsm]
.method public hidebysig !0 GetValueOrDefault()

[C#]
public T GetValueOrDefault()
```

Summary

Returns the value of the current instance, or if it has none, returns the default value for the type T.

Return Value

A value of type T, which is either the value of the current instance, or if it has none, the default value for the type T.

Description

[*Note:* Another method, `System.Optional<T>.GetValueOrDefault(T)`, allows a value other than the default value of type T to be returned if the current instance has no value.]

8.10 Optional<T>.GetValueOrDefault(T) method

```
[ILAsm]
.method public hidebysig !0 GetValueOrDefault(!0 alternateDefaultValue)

[C#]
public T GetValueOrDefault(T alternateDefaultValue)
```

Summary

Returns the value of the current instance, or if it has none, returns *alternateDefaultValue*.

Parameters

Parameter	Description
<i>alternateDefaultValue</i>	The value to be returned if the current instance has no value.

Return Value

A value of type T, which is either the value of the current instance, or if it has none, the value *alternateDefaultValue*.

Description

[*Note:* `System.Optional<T>.GetValueOrDefault()` allows the default value for type T to be returned if the current instance has no value.]

8.11 Optional<T>.HasValue property

```
[ILAsm]
.property bool HasValue()
{
    .get instance bool get_HasValue()
}
.method public hidebysig specialname instance bool get_HasValue()

[C#]
public bool HasValue { get; }
```

Summary

Indicates whether the current instance contains a value.

Property Value

true if the current instance contains a value; otherwise, false.

Behaviors

If `System.Optional<T>.HasValue` is true, the instance contains a value of type T, and `System.Optional<T>.Value` returns that value. If `System.Optional<T>.HasValue` is false, the instance contains no value of type T, and an attempt to read `System.Optional<T>.Value` results in a `System.InvalidOperationException` exception. A call to `System.Optional<T>.Value.GetValueOrDefault` returns the default value.

This property is read-only.

[*Note:* This method implicitly implements the `Optional<T>.INullableValue.HasValue` property.]

8.12 Optional<T>.op_Equality(Optional<T>, Optional<T>) method

```
[ILAsm]
.method public hidebysig specialname static
    bool op_Equality(valuetype Optional`1<!0> left,
                    valuetype Optional`1<!0> right)

[C#]
static bool operator==(Optional<T> left, Optional<T> right)
```

Summary

Determines whether the specified values are equal.

Parameters

Parameter	Description
<i>left</i>	The first <code>Optional<T></code> value to compare.
<i>right</i>	The second <code>Optional<T></code> value to compare.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions	
	left.HasValue	right.HasValue
true	false	false
false	false	true
false	true	false
left.Value.Equals(right.Value)	true	true

Description

8.13 Optional<T>.op_Explicit(System.Optional<T>) method

```
[ILAsm]
.method public hidebysig static specialname !0 op_Explicit(valuetype
Optional`1<!0> value)

[C#]
public static explicit operator T(Optional<T> value)
```

Summary

Perform an explicit conversion of a System.Optional<T> value to type T.

Parameters

Parameter	Description
value	The System.Optional<T> value to convert to type T.

Return Value

The value, if any, of the specified optional value. Otherwise, an exception is thrown.

Description

[Note: See the System.Optional<T>.FromOptional(Optional<T>) method for the CLS twin of this operator.]

[Note: The conversion implemented by this method corresponds exactly to obtaining the value of the System.Optional<T>.Value property.]

Exceptions

Exception	Condition
System.InvalidOperationException	System.Optional<T>.HasValue is false.

8.14 Optional<T>.op_Implicit(T) method

```
[ILAsm]
.method public hidebysig static specialname valuetype Optional`1<!0>
op_Implicit(!0 value)
```

```
[C#]
public static implicit operator Optional<T>(T value)
```

Summary

Perform an implicit conversion of a `T` value to `System.Optional<T>`.

Parameters

Parameter	Description
<i>value</i>	The <code>T</code> value to convert to <code>System.Optional<T></code> .

Return Value

A `System.Optional<T>` with the specified value.

Description

[*Note:* See the `System.Optional<T>.ToOptional(T)` method for the CLS twin of this operator.]

[*Note:* The conversion implemented by this method corresponds exactly to invoking the `System.Optional<T>(T)` constructor.]

8.15 Optional<T>.op_Inequality(Optional<T>, Optional<T>) method

```
[ILAsm]
.method public hidebysig specialname static
    bool op_Inequality(valuetype Optional`1<!0> left,
                      valuetype Optional`1<!0> right)

[C#]
static bool operator!=(Optional<T> left, Optional<T> right)
```

Summary

Determines whether the specified values are not equal.

Parameters

Parameter	Description
<i>left</i>	The first Optional<T> value to compare.
<i>right</i>	The second Optional<T> value to compare.

Return Value

The following table defines the conditions under which the return value is true or false:

Return Value	Conditions	
	left.HasValue	right.HasValue
false	false	false
true	false	true
true	true	false
Not left.Value.Equals(right.Value)	true	true

Description