

TECHNICAL  
REPORT

ISO/IEC  
TR 9577

Third edition  
1996-12-15

---

---

**Information technology — Protocol  
identification in the network layer**

*Technologies de l'information — Identification du protocole dans la couche  
réseau*

IECNORM.COM : Click to view the full PDF of ISO/IEC TR 9577:1996



Reference number  
ISO/IEC TR 9577:1996(E)

## Contents

	<i>Page</i>	
1	Scope.....	1
2	References.....	1
2.1	Identical Recommendations   International Standards.....	2
2.2	Paired Recommendations   International Standards equivalent in technical content.....	2
2.3	Additional references.....	2
3	Abbreviations.....	3
4	Protocol identifiers.....	4
5	Initial protocol identifier.....	4
5.1	General.....	4
5.2	Assignment structure.....	4
5.3	Values assigned to the IPI.....	5
6	Subsequent protocol identifier.....	7
6.1	General.....	7
6.2	Assignment structure.....	7
6.3	Values assigned to the SPI.....	8
	Annex A – The location and use of protocol identifiers in Recommendation X.25.....	10
	Annex B – Guidelines on the processing of protocol identifiers.....	13
	B.1 Originating systems.....	13
	B.2 Destination systems.....	13
	Annex C – Identification of two non-ISO/IEC, non-ITU-T protocols.....	15
	Annex D – Identification of protocols that are discriminated according to the IEEE-defined SNAP convention....	16

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The main task of technical committees is to prepare International Standards. In exceptional circumstances a technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/IEC TR 9577, which is a Technical Report of type 3, was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.263.

This third edition cancels and replaces the second edition (ISO/IEC TR 9577:1993), which has been technically revised.

## Introduction

Identifying protocols by information in a uniform part of the protocol control information fulfils two requirements:

- a) It enables an entity to verify that the protocol received is of the type and kind expected; and
- b) It permits an entity to discriminate among a number of different protocols (both OSI and non-OSI) that might co-exist in a common environment.

This Recommendation | Technical Report contains a description of the means used to identify protocols and where that information is located in a protocol, together with a record of those values of protocol identifiers which have been used by ITU-T and ISO/IEC, and by other authorities. This Recommendation | Technical Report does not attempt to provide any general architectural principles for the functions of protocol identification, nor does it attempt to provide judgements as to whether a protocol might have more than one value of protocol identifier.

By reference to this Recommendation | Technical Report, future protocols can be developed to include a protocol identifier and the values of such protocol identifiers can be chosen on a knowledgeable basis.

IECNORM.COM : Click to view the full PDF of ISO/IEC TR 9577:1996

**TECHNICAL REPORT****ITU-T RECOMMENDATION****INFORMATION TECHNOLOGY – PROTOCOL IDENTIFICATION  
IN THE NETWORK LAYER****1 Scope**

This Recommendation | Technical Report provides:

- a) the description of a means to permit a protocol to be identified;
- b) a record of the structure and allowable ranges of protocol identifier(s) which can be assigned by ITU-T, ISO/IEC and other authorities;
- c) a record of the values of protocol identifiers used by OSI Network layer protocols and non-OSI protocols occupying a similar position: in particular, only protocols with protocol control information commencing in octet 1 of the protocol data unit are covered; and
- d) a record of the values that are in use as protocol control information in non-Network layer protocols where they impact on Network layer protocol identification.

The application of this Recommendation | Technical Report is:

- a) in the identification of internationally standardized Network layer protocols operating directly above the Data Link service;
- b) in the identification of protocols used in conjunction with internationally standardized Network layer protocols that operate directly above the Data Link service; and
- c) to distinguish between Internationally standardized Network layer protocols, and other internationally standardized protocols used in conjunction with internationally standardized Network layer protocols.

This Recommendation | Technical Report is for use by ITU-T Study Groups, ISO/IEC Technical Committees and other authorities in applying the principles contained in clause 4, and in selecting an unused value or values from the range of values permitted in clauses 5 or 6, as appropriate. When a new value is selected, that value and its usage should be brought to the attention of ITU-T Study Group 7 or ISO/IEC JTC 1 SC6 so that this Recommendation | Technical Report can be amended.

**2 References**

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | Technical Report. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | Technical Report are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

## 2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.233 (1993) | ISO/IEC 8473-1:1994, *Information technology – Protocol for providing the connectionless-mode network service: Protocol specification.*
- ITU-T Recommendation X.273 (1994) | ISO/IEC 11577:1995, *Information technology – Open Systems Interconnection – Network layer security protocol.*
- ITU-T Recommendation X.633 (1996) | ISO/IEC 14700:1996, *Open Systems Interconnection – Network fast byte protocol.*
- ITU-T Recommendation X.634 (1996) | ISO/IEC 14699:1996, *Open Systems Interconnection – Transport fast byte protocol.*

## 2.2 Paired Recommendations | International Standards equivalent in technical content

- ITU-T Recommendation X.25 (1996), *Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit.*  
  
ISO/IEC 8208:1995, *Information technology – Data communications – X.25 Packet Layer Protocol for Data Terminal Equipment.*
- ITU-T Recommendation X.223 (1996), *Use of X.25 to provide the OSI connection-mode network service for ITU-T applications.*  
  
ISO/IEC 8878:1992, *Information technology – Telecommunications and information exchange between systems – Use of X.25 to provide the OSI Connection-mode Network Service.*
- ITU-T Recommendation X.224 (1993), *Protocol for providing the OSI connection-mode transport service.*  
  
ISO/IEC 8073:1992, *Information technology – Telecommunications and information exchange between systems – Open Systems Interconnection – Protocol for providing the connection-mode transport service.*
- ITU-T Recommendation X.264 (1993), *Transport protocol identification mechanism.*  
  
ISO/IEC 11570:1992, *Information technology – Telecommunications and information exchange between systems – Open Systems Interconnection – Transport protocol identification mechanism.*

## 2.3 Additional references

- CCITT Recommendation G.764 (1992), *Voice packetization – Packetized voice protocols.*
- ITU-T Recommendation Q.931 (1993), *Digital Subscriber Signalling System No. 1 (DSS 1) – ISDN user-network interface layer 3 specification for basic call control.*
- ITU-T Recommendation Q.932 (1993), *Digital Subscriber Signalling System No. 1 (DSS 1) – Generic procedures for the control of ISDN supplementary services.*
- ITU-T Recommendation Q.933 (1993), *Digital subscriber signalling system No. 1 (DSS 1) – Signalling specification for frame mode basic call control.*
- ITU-T Recommendation Q.2119 (1996), *B-ISDN ATM Adaptation layer protocols. Convergence function for SSCOP above the frame relay core service.*
- ITU-T Recommendation Q.2931 (1995), *Broadband Integrated Services Digital Network (B-ISDN) – Digital Subscriber Signalling System No. 2 (DSS 2) – User-Network Interface (UNI) layer 3 specification for basic call/connection control.*
- ITU-T Recommendation T.70 (1993), *Network-independent basic transport service for the telematic services.*
- ITU-T Recommendation X.29 (1993), *Procedures for the exchange of control information and user data between a Packet Assembly/Disassembly (PAD) facility and a packet mode DTE or another PAD.*

- ITU-T Recommendation X.36 (1995), *Interface between Data Terminal Equipment (DTE) and Data Circuit-Terminating Equipment (DCE) for public data networks providing frame relay data transmission service by dedicated circuit.*
- ITU-T Recommendation X.37 (1995), *Encapsulation in X.25 packets of various protocols including frame relay.*
- ITU-T Recommendation X.39 (1996), *Procedures for the exchange of control information and user data between a Facsimile Packet Assembly/Disassembly (FPAD) facility and a packet mode Data Terminal Equipment (DTE) or another FPAD.*
- ITU-T Recommendation X.48 (1996), *Procedures for the provision of a basic multicast service for Data Terminating Equipments (DTEs) using Recommendation X.25.*
- ITU-T Recommendation X.49 (1996), *Procedures for the provision of an extended multicast service for Data Terminating Equipment (DTEs) using Recommendation X.25.*
- CCITT Recommendation X.610 (1992), *Provision and support of the OSI connection-mode network service.*
- ISO/IEC 9542:1988<sup>1)</sup>, *Information processing systems – Telecommunications and information exchange between systems – End system to Intermediate system routing exchange protocol for use in conjunction with the Protocol for providing the connectionless-mode network service (ISO 8473).*
- ISO/IEC 10030:1995, *Information technology – Telecommunications and information exchange between systems – End System Routing Information Exchange Protocol for use in conjunction with ISO/IEC 8878.*
- ISO/IEC 10589:1992, *Information technology – Telecommunications and information exchange between systems – Intermediate system to Intermediate system intra-domain routing information exchange protocol for use in conjunction with the protocol for providing the connectionless-mode Network Service (ISO/IEC 8473).*
- ISO/IEC 10747:1994, *Information technology – Telecommunications and information exchange between systems – Protocol for exchange of inter-domain routing information among intermediate systems to support forwarding of ISO 8473 PDUs.*
- ISO/IEC 11572:1994<sup>2)</sup>, *Information technology – Telecommunications and information exchange between systems – Private Integrated Services Network – Circuit mode bearer services – Inter-exchange signalling procedures and protocol.*
- ISO/IEC 11582:1995, *Information technology – Telecommunications and information exchange between systems – Private Integrated Services Network – Generic functional protocol for the support of supplementary services – Inter-exchange signalling procedures and protocol.*
- ISO/IEC TR 13532:1995, *Information technology – Telecommunications and information exchange between systems – Protocol combinations to provide and support the OSI Network Service.*

### 3 Abbreviations

For the purposes of this Recommendation | Technical Report, the following abbreviations apply:

GFI	General Format Identifier
IPI	Initial Protocol Identifier
NCMS	Network Connection Management Subprotocol
OSI	Open Systems Interconnection
PDU	Protocol Data Unit
SPI	Subsequent Protocol Identifier
TPDU	Transport Protocol Data Unit

<sup>1)</sup> Currently under revision.

## 4 Protocol identifiers

The protocol operating directly over the Data Link layer is termed the initial protocol and is identified by the Initial Protocol Identifier (IPI).

The protocol carried by the initial protocol is termed the subsequent protocol and is identified by a Subsequent Protocol Identifier (SPI).

The subsequent protocol can carry further subsequent protocols, identified by further SPIs, iteratively.


For the purposes of this Recommendation | Technical Report, the octets referred to as IPI and SPI are viewed as protocol identifiers. In some cases the protocol itself gives other names to these octets, and might also view the function of the octets as being distinct from protocol identification. ITU-T Rec. X.25 and ISO/IEC 8208 provide an example (see Annex A). It is possible to identify such protocols by the means described in this Recommendation | Technical Report. It is also possible for a given protocol to be identified in more than one way, in different contexts.

NOTE – Guidelines for the processing of protocol identifiers are given in Annex B.

## 5 Initial protocol identifier

### 5.1 General

The location of the IPI is the first octet of the protocol control information; this is depicted in Figure 1. The value of the IPI unambiguously identifies the initial protocol.



TISO7040-96/d01

Figure 1 – Location of the IPI

### 5.2 Assignment structure

The structure applied to the values of the IPI is depicted in Table 1.

With the exception of protocol identifiers used by ITU-T Rec. X.25 and ISO/IEC 8208, bits 8, 7, 6, and 5 of the IPI indicate the administrative authority which is responsible for assigning a combination of the associated bits 4, 3, 2 and 1 to an initial protocol.

Table 1 – Structure of the IPI octet

Bit Pattern								Allocation Category
8	7	6	5	4	3	2	1	
0	0	0	0	0	0	0	0	Allocation by ISO/IEC
0	0	0	0	0	0	0	1	Allocation by ITU-T
through to and including								
0	0	0	0	1	1	1	1	ITU-T Rec. X.25, ISO/IEC 8208
x	x	0	1	x	x	x	x	
x	x	1	0	x	x	x	x	
0	0	1	1	x	x	x	x	
0	1	0	0	0	0	x	x	Allocation by ISO/IEC
0	1	0	0	0	1	0	0	Allocation by ITU-T
0	1	0	0	0	1	0	1	Allocation by ISO/IEC
through to and including								
0	1	0	0	1	1	1	1	Joint allocation by ITU-T and ISO/IEC
0	1	1	1	x	x	x	x	
1	0	0	0	x	x	x	x	Allocation by ISO/IEC
1	0	1	1	x	x	x	x	Allocation by ITU-T
1	1	0	0	x	x	x	x	Not categorized by this Recommendation   Technical Report (see Note)
1	1	1	1	0	0	0	0	Joint Allocation by ITU-T and ISO/IEC
through to and including								
1	1	1	1	1	1	1	0	Reserved for extension, see Table 2
1	1	1	1	1	1	1	1	

NOTE – Although not categorized by this Recommendation | Technical Report, the codepoints 1100 1100 and 1100 1111 are in widespread use (see Table 2 and Annex C).

### 5.3 Values assigned to the IPI

Table 2 records the values that have been assigned to specific protocols. Values not recorded are reserved and available for allocation by the administrative authorities specified by the structure depicted in 5.2.

A specific value is reserved to indicate the null Network layer. One value is reserved for future extension to this Recommendation | Technical Report.

Table 2 – Values assigned to the IPI octet


Bit Pattern								Protocol
8	7	6	5	4	3	2	1	
0	0	0	0	0	0	0	0	Null Network layer (see Note 1)
0	0	0	0	0	0	0	1	Rec. T.70 (Minimum Network layer functionality)
0	0	0	0	0	0	1	1	Rec. X.633 (Network layer fast-byte protocol)
0	0	0	0	1	0	0	0	Recs. Q.931, Q.932, Q.933, X.36, ISO/IEC 11572, ISO/IEC 11582
0	0	0	0	1	0	1	0	Rec. Q.2119
0	0	0	0	1	0	0	1	Rec. Q.2931 (Broadband ISDN Signalling protocol)
x	x	0	1	x	x	x	x	ITU-T Rec. X.25 and ISO/IEC 8208 – modulo 8
x	x	1	0	x	x	x	x	ITU-T Rec. X.25 and ISO/IEC 8208 – modulo 128
0	0	1	1	x	x	x	x	ITU-T Rec. X.25 and ISO/IEC 8208 – GFI extension
0	1	0	0	0	1	0	0	Rec. G.764
1	0	0	0	0	0	0	0	IEEE SNAP, see Annex D
1	0	0	0	0	0	0	1	ITU-T Rec. X.233   ISO/IEC 8473-1 (excluding the inactive subset)
1	0	0	0	0	0	1	0	ISO/IEC 9542
1	0	0	0	0	0	1	1	ISO/IEC 10589
1	0	0	0	0	1	0	1	ISO/IEC 10747 (see Note 3)
1	0	0	0	1	0	1	0	ISO/IEC 10030
1	0	0	0	1	0	1	1	ITU-T Rec. X.273   ISO/IEC 11577
1	0	1	1	0	0	0	0	Data compression protocol (see Note 4)
1	1	0	0	1	1	0	0	See Annex C
1	0	0	0	1	1	1	1	Private Network layer protocols
1	1	1	1	1	1	1	1	Reserved for extension (see Note 2).
<p>NOTES</p> <p>1 ITU-T Rec. X.233   ISO/IEC 8473-1 uses this value for the inactive subset.</p> <p>2 The extension mechanisms will be the subject of joint development between ITU-T and ISO/IEC.</p> <p>3 IPI assigned but not currently used since current usage of ISO/IEC 10747 PDUs is covered by the ITU-T Rec. X.233   ISO/IEC 8473-1 IPI.</p> <p>4 The first octet of the decompressed PDU, when the IPI indicated Data compression protocol, is itself an IPI octet.</p>								

## 6 Subsequent protocol identifier

### 6.1 General

An initial protocol can make provision for implicit or explicit mechanisms to list and/or negotiate the identity of subsequent protocols to be carried by it. In the case of an explicit mechanism, the identity of the subsequent protocol is given by the Subsequent Protocol Identifier (SPI).

For the purposes of this Recommendation | Technical Report, the SPI is the first octet of protocol control information in each instance of communication of the subsequent protocol. This is depicted in Figure 2 where a subsequent protocol is operating directly over the initial protocol.



NOTE – The term sublayer is used as defined in ITU-T Rec. X.200 | ISO/IEC 7498-1.

Figure 2 – Location of the SPI

The value of the SPI:

- a) identifies another OSI Network layer protocol;
- b) identifies some other non-OSI protocol;
- c) identifies that a set of protocols is encapsulated within the initial protocol – the method for identification of the subsequent encapsulated protocol(s) is defined by the protocol associated with the SPI; or
- d) is that which is in use by an OSI Transport layer protocol.

It should be noted that in some cases an SPI might not be present, for example see Figure A.3.

It should also be noted that in case c), for the purposes of the initial protocol, the single-octet SPI defined here can be separate from the mechanism used to identify subsequent protocols (in particular, that mechanism can use multi-octet protocol identifiers specified by the protocol associated with the SPI; for example, see Annex D).

### 6.2 Assignment structure

The structure applied to the SPI is depicted in Table 3.

Bits 8 and 7 of the SPI indicate the administrative authority (if any) which is responsible for assigning the associated bits 6, 5, 4, 3, 2, and 1 to a subsequent protocol.

**Table 3 – Structure of the SPI octet**

Bit Pattern								Allocation Category
8	7	6	5	4	3	2	1	
0	0	0	0	0	0	0	0	Joint allocation by ITU-T and ISO/IEC (see Note 1)
0	0	0	0	0	0	0	1	Allocation by ITU-T
through to and including								
0	0	1	1	1	1	1	1	Allocation by ISO/IEC National Bodies (see Note 2)
0	1	x	x	x	x	x	x	
1	0	0	x	x	x	x	x	Allocation by ISO/IEC
1	0	1	x	x	x	x	x	Allocation by ITU-T
1	1	0	0	0	0	0	0	Not categorized by this Recommendation   Technical Report (see Note 3)
through to and including								
1	1	1	1	1	1	1	0	Reserved for extension, see Table 4.
1	1	1	1	1	1	1	1	

**NOTES**

1 The general principle of bits 8 and 7 identifying the administrative authority is used by this Recommendation | Technical Report. Where bits 8 and 7 are 00 this identifies ITU-T. However, it has been necessary for ISO/IEC to use the particular value 0000 0000 as an SPI for a certain protocol. This is not expected to cause interworking problems.

2 The allocation of SPIs by ISO/IEC National Bodies should be done with extreme care as it is possible that different National Bodies could allocate the same identifier to different protocols, or different identifiers to the same protocols. In such cases interworking problems may result.

3 Although not categorized by this Recommendation | Technical Report, the codepoints 1100 1100 and 1100 1111 are in widespread use (see Table 4 and Annex C).

**6.3 Values assigned to the SPI**

Table 4 records the values that have been assigned to specific protocols which operate over the initial protocol. Values not recorded are reserved and available for allocation by the administrative authorities specified by the structure depicted in 6.2.

Table 4 – Values assigned to the SPI octet

Bit Pattern								Protocol
8	7	6	5	4	3	2	1	
0	0	0	0	0	0	0	0	ITU-T Rec. X.233   ISO/IEC 8473-1 Inactive subset, Rec. X.37 multi-protocol encapsulation (see Note 1)
0	0	0	0	0	0	0	1	Rec. X.29
0	0	0	0	0	0	1	0	Rec. T.70 Transport layer procedure (see Note 2).
0	0	0	0	0	0	1	1	
through to and including								Reserved – in use by ITU-T Rec. X.224 and ISO/IEC 8073 Annex B and ITU-T Rec. X.264 and ISO/IEC 11570 (see Notes 2 and 3)
0	0	1	1	1	1	1	1	
1	0	0	0	0	0	0	0	IEEE SNAP (see Annex D)
1	0	0	0	0	0	0	1	ITU-T Rec. X.233   ISO/IEC 8473-1 (excluding the inactive subset)
1	0	0	0	0	0	1	0	ISO/IEC 9542
1	0	0	0	0	0	1	1	ISO/IEC 10589
1	0	0	0	0	1	0	0	ISO/IEC 8878 Annex A
1	0	0	0	0	1	0	1	ISO/IEC 10747
1	0	0	0	1	0	1	0	ISO/IEC 10030
1	0	0	0	1	0	1	1	ITU-T Rec. X.273   ISO/IEC 11577
1	0	0	0	1	1	1	1	Private Network layer protocols
1	0	1	0	0	0	0	0	Rec. X.37, identification by other means
1	0	1	0	0	0	0	1	Rec. X.39
1	0	1	0	0	0	1	0	Rec. X.634 (see Note 2)
1	0	1	0	0	1	0	0	Recs. X.48 and X.49
1	0	1	0	1	0	0	0	Rec. X.37, encapsulation of frame relay
1	0	1	1	0	0	0	0	Data compression protocol
1	1	0	0	1	1	0	0	See Annex C
1	1	0	0	1	1	1	1	See Annex C
1	1	1	1	1	1	1	1	Reserved for extension (see Note 4).
NOTES								
1 No interworking problems are likely to arise from the (apparent) conflict of assignment for the SPI value 0000 0000. It is not expected that the inactive subset of Rec. X.233   ISO/IEC 8473-1 will be conveyed using Rec. X.37 in a way that would cause this SPI value identifying the inactive subset to occur.								
2 These are not Network layer protocol identifiers. The values shown are used by the respective higher layer protocol; they are not used for higher layer protocol identification.								
3 These values are not used for identification. However, the receipt of these values confirms the use of the Transport layer protocol identification mechanism as defined in ITU-T Rec. X.264 and ISO/IEC 11570 and ITU-T Rec. X.224 and ISO/IEC 8073 Annex B (known <i>a priori</i> ).								
4 The extension mechanisms will be the subject of joint development between ITU-T and ISO/IEC.								

Annex A

The location and use of protocol identifiers in X.25 Packet Layer Protocol


(This annex forms an integral part of this Recommendation)

This annex shows examples of protocol identifiers when the X.25 Packet Layer Protocol specified in ITU-T Rec. X.25 and/or ISO/IEC 8208 is used as the initial protocol in various situations. These examples assume that the systems operate in an OSI environment, and that the X.25 or ISO/IEC 8208 protocol is operating in modulo 8 or modulo 128.

NOTES

1 In modulo 8 or modulo 128 operation of ITU-T Rec. X.25 and ISO/IEC 8208, the first octet consists of the General Format Identifier (GFI) and the upper four bits of the logical channel identifier. This first octet also serves as the Initial Protocol Identifier (IPI). In modulo 32 768 operation, the first octet is an IPI and is separate from the GFI and the upper four bits of the logical channel identifier (which are in the second octet). This is not shown in the examples below.

2 In the case of ITU-T Rec. X.25 and ISO/IEC 8208 CALL REQUEST/INCOMING CALL packets, bit 8 might be set to 1 to indicate alternative address formats and bit 7 might be set to 1 to indicate desire to use the delivery confirmation procedure.




TISO7060-96/d03

NOTE – When a virtual call is set up to carry connectionless PDUs as shown above, the subsequent DATA packets may carry ITU-T Rec. X.233 | ISO/IEC 8473-1 PDUs, or ISO/IEC 9542 PDUs, each PDU being identified by its respective SPI value as indicated in Table 4.

Figure A.1 – IPI and SPI when ITU-T Rec. X.233 | ISO/IEC 8473-1 or ISO/IEC 9542 is operated over ITU-T Rec. X.25 and/or ISO/IEC 8208





TISO7080-96/d05

NOTES

- 1 In an OSI environment where default identification is used, the ITU-Rec. X.224 and ISO/IEC 8073 protocol is carried in X.25 DATA packets and an SPI does not exist.
- 2 The Transport layer is accessed by the called Network Address (N-address) conveyed in the X.25 protocol control information.
- 3 ITU-T Rec. X.224 and ISO/IEC 8073 is implicitly identified in this case and the receipt of TPDU is expected on an *a priori* basis.

**Figure A.3 – Location of IPI and SPI when ITU-T Rec. X.264 and ISO/IEC 11570 default identification is used over ITU-T Rec. X.25 and/or ISO/IEC 8208**

## Annex B

## Guidelines on the processing of protocol identifiers

(This annex forms an integral part of this Recommendation)

## B.1 Originating systems


The use of particular protocols depends upon the capabilities of both the originating and destination systems. This Recommendation | Technical Report does not provide mechanisms for the selection of specific protocols. It notes that the selection could be, for example, by *a priori* knowledge, by directories, or by some other means. It is also noted that CCITT Rec. X.610 and ISO/IEC TR 13532 define protocol combinations to support the connection-mode Network service, and ISO/IEC TR 13532 also defines protocol combinations to support the connectionless-mode Network service.

## B.2 Destination systems

This Recommendation | Technical Report describes a means by which a system can identify the protocols recorded in Tables 2 and 4. Following an examination of the IPI, PDUs can be directed to the correct protocol entity for further processing. In this regard the IPI is a pre-processing selector (see Figure B.1).


The destination system might also need to examine the SPI in order to determine what other protocols are being received. For example, ISO/IEC 8208 can support both the Connection-mode and the Connectionless-mode Network services. In an OSI environment an examination of the SPI will reveal, for example, whether the ITU-T Rec. X.233 | ISO/IEC 8473-1 protocol is in use (see Table 4). Note that if the SPI indicates a subsequent protocol that cannot be processed, ISO/IEC 8208 includes a diagnostic code (number 249) which indicates "unrecognizable protocol in user data" and this can be used in a CLEAR REQUEST packet to reject a virtual call.

Figures B.1 and B.2 show the use of the IPI and SPI respectively in their roles as protocol identifiers. The representation used in these figures is as an aid to understanding and it does not prescribe a method of implementation. Details regarding the specific operation of protocols, and their use of particular Data Link services, are excluded from Figures B.1 and B.2.



TISO7090-96/d06

Figure B.1 – Selection of the initial protocol



TISO7100-96/d07

Figure B.2 – Selection of the subsequent protocol

## Annex C

### Identification of two non-ISO/IEC, non-ITU-T protocols

(This annex forms an integral part of this Recommendation)

The Internet Engineering Steering Group (IESG) has established a set of standards for the protocols that are used in “The Internet” – the internationally distributed collection of systems and networks that follow what is customarily called the “TCP/IP protocol suite”. These standards are published as part of a series of documents called “Requests for Comments” (RFCs). The standards are widely used and non-proprietary, although they are not considered to be part of OSI; the specifications (RFCs) are freely and readily available throughout the world, although they are not distributed by ITU-T or ISO/IEC.

This Recommendation | Technical Report promotes the goal of non-interference between OSI and non-OSI protocols in this case by reserving:

- a) the IPI and SPI value 1100 1100 to identify the “Internet Protocol” which is the TCP/IP protocol that would, in OSI, be a Network layer protocol; and
- b) the IPI and SPI value 1100 1111 to identify the “Point-to-Point Protocol” (PPP) which is widely used to convey connectionless-mode PDUs over point-to-point links.

The Internet Protocol is defined by RFC 791, and is recognized as a mandatory standard for the TCP/IP Internet community.

The Point-to-Point Protocol is defined in RFC 1548.

The reservation of these IPI/SPI values for non-ISO, non-ITU-T protocols is justified by the otherwise real probability of interference between the Internet Protocol or Point-to-Point Protocol and OSI Network layer protocols in what are expected to be very common multi-protocol network configurations. It does not create a general precedent for the reservation of protocol identification values for non-ISO, non-ITU-T protocols, which must be justified individually on the merits of a particular case.

The specifications of the Internet Protocol, RFC 791, and the Point-to-Point Protocol, RFC 1548, may be obtained from:

Network Information Center  
SRI International  
333 Ravenswood Avenue  
Menlo Park, CA 94025  
U.S.A.