

INTERNATIONAL
STANDARD

ISO
10627-2

First edition
1996-05-01

**Hydraulic agricultural sprayers — Data
sheets —**

Part 2:

Technical specifications related to
components

*Pulvérisateurs agricoles à jet projeté — Fiches techniques —
Partie 2. Spécifications techniques relatives aux composants*



Reference number
ISO 10627-2:1996(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10627-2 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 6, *Equipment for crop protection*.

ISO 10627 consists of the following parts, under the general title *Hydraulic agricultural sprayers — Data sheets*:

- *Part 1: Typical layout*
- *Part 2: Technical specifications related to components*

Annex A forms an integral part of this part of ISO 10627. Annex B is for information only.

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Hydraulic agricultural sprayers — Data sheets —

Part 2:

Technical specifications related to components

1 Scope

This part of ISO 10627 establishes the technical specification of data sheet presentation, for the preparation of documents giving information about dimensions, materials, characteristics and design of component parts of non-air-assisted agricultural sprayers. Data sheets prepared according to this part of ISO 10627 will facilitate discussion between the manufacturers of sprayers and the manufacturers of component parts and accessories.

This part of ISO 10627 does not cover mass and dimensions of the sprayer in total, nor information related to the basic machine required by the manufacturer. Such information is given in ISO 10627-1.

This part of ISO 10627 applies during the conception of the data sheet by the manufacturer or importer of non-air-assisted agricultural sprayers, mounted, towed or self-propelled, used for the protection of crops and application of liquid fertilizers.

A list of International Standards related to this part of ISO 10627 is given in annex B.

2 General specifications

NOTE — Codes are explained in annex A.

2.1 Manufacturer

Name and address of manufacturer:

.....

.....

Distributor/importer:

.....

2.2 Type and year of manufacture

Implement type:

Year of manufacture:

Location of marking (code 101):

2.3 Trade-name(s)

.....

3 Tank specifications

| | Principal tank | Rinsing tank | Other tank |
|--|-------------------------|-------------------------|-------------------------|
| 3.1 Material (code 102) | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| 3.2 Volume | | | |
| Nominal volume: | <input type="text"/> l | <input type="text"/> l | <input type="text"/> l |
| Total volume: | <input type="text"/> l | <input type="text"/> l | <input type="text"/> l |
| 3.3 Dimensions | | | |
| Length: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Width: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Height (to upper edge of filling opening): | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Location (code 304): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.4 Level indicator

| | Principal tank | Rinsing tank | Other tank |
|----------------------------|------------------------|------------------------|------------------------|
| Type (code 303): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Indicating range: | from..... l to l | from..... l to..... l | from..... l to..... l |
| Graduation: | <input type="text"/> l | <input type="text"/> l | <input type="text"/> l |
| Location (code 304): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.5 Filling hole

| | | | |
|---------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Location (code 306): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Diameter: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Tank filling strainer | | | |
| material (code 102): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| diameter: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| depth: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| strainer surface: | <input type="text"/> mm ² | <input type="text"/> mm ² | <input type="text"/> mm ² |
| mesh width: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Design of lid (code 305): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.6 Agitator

| | | | |
|----------------------------|----------------------|----------------------|----------------------|
| Type (code 307): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Design (code 308): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Location (code 310): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.7 Drainage device

| | | | |
|----------------------------|----------------------|----------------------|----------------------|
| Type (code 312): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Design (code 313): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Location (code 314): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.8 Filling device

| | Principal tank | Rinsing tank | Other tank |
|---------------------------------------|--|--|--|
| Type (code 315): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Design (code 316): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Location (code 317): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Volumetric flowrate with water: | <input type="text"/> l/min | <input type="text"/> l/min | <input type="text"/> l/min |
| Shut-off valve | <input type="checkbox"/> YES <input type="checkbox"/> NO | <input type="checkbox"/> YES <input type="checkbox"/> NO | <input type="checkbox"/> YES <input type="checkbox"/> NO |
| location of shut-off valve: | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Filtration device | <input type="checkbox"/> YES <input type="checkbox"/> NO | <input type="checkbox"/> YES <input type="checkbox"/> NO | <input type="checkbox"/> YES <input type="checkbox"/> NO |
| design (code 318): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| location (code 319): | <input type="text"/> | <input type="text"/> | <input type="text"/> |

3.9 Dosing devices for crop protection products

| | | | |
|----------------------------|----------------------|----------------------|----------------------|
| Type (code 320): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Design (code 321): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Location (code 319): | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Measuring range: | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Measuring accuracy: | <input type="text"/> | <input type="text"/> | <input type="text"/> |

4 Pump specifications

4.1 Main pump

| | |
|----------------------------|----------------------|
| Manufacturer: | <input type="text"/> |
| Design (code 402): | <input type="text"/> |
| Designation: | <input type="text"/> |
| Location (code 403): | <input type="text"/> |

Drive (code 404):

Connection:

Nominal pressure: MPa

Nominal speed: r/min

Volumetric flowrate

non-pressurized: l/min

at nominal pressure: l/min

Pressure pulsation damper

design (code 407):

material (code 102):

4.2 Other pumps

Function (code 405):

Manufacturer:

Design (code 402):

Designation:

Location (code 403):

Drive (code 404):

Connection:

Nominal pressure: MPa

Nominal speed: r/min

Volumetric flowrate

non-pressurized: l/min

at nominal pressure: l/min

STANDARDSISO.COM: Click to view the full PDF of ISO 10627-2:1996

Pressure pulsation damper

design (code 407):

material (code 102):

5 Spray boom specifications

5.1 General

Design (code 703):

Working width: m

Number of feeding lines:

Number of spray boom subdivisions:

Spray boom extension YES NO

additional working width: m

5.2 Suspension

Design: Rigid Mobile

If mobile, range of movement: ° up to °

5.3 Height adjustment (code 702)

mechanical, by means of

hydraulic, by means of

other means: which

height adjustment range: m

5.4 Safety device to maintain chosen height spray boom

Design:

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

5.5 Slope compensation system

Design (code 706):

Function (code 707):

Control (code 103):

Swing range:

Range of levelling:

5.6 Nozzles

Nozzle tips

designation:

design (code 711):

manufacturer:

material (code 102):

spray angle at 0,3 MPa:

nozzle spacing:

optimum distance to the target surface:

distance range to the target surface:

optimum spray pressure:

spraying pressure range:

Nozzle holder:

designation:

design (code 715):

function (code 716):

control (code 103):

STANDARDSISO.COM: Click to view the full PDF of ISO 10627-2:1996

material (code 102):

thread dimensions:

bayonet connections:

Anti-drip device

designation:

design (code 720):

material (code 102):

opening pressure: MPa

closing pressure: MPa

Individual shut-off device

design (code 721):

function (code 721):

control (code 103):

Lateral distance: mm

Nozzle supply line

design (code 801):

material (code 102):

inside diameter: mm

outside diameter: mm

5.7 Spray edge working device

Designation:

Design:

Function:

6 Liquid lines specifications

6.1 Suction line(s)

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

6.2 Pressure lines

6.2.1 From pump to central

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

6.2.2 From central to spray boom

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

6.2.3 Agitator line(s)

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

6.3 Return flow lines

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

6.4 Other lines

Number:

Material (code 102):

Design (code 801):

Inside diameter: mm

Length(s): m

7 Filter specifications

7.1 Filling filter

Material (code 102):

Inside diameter: mm

Length: mm

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

Filtering surface: mm²

Mesh width: mm

7.2 Suction side

Number:

Design (code 803):

Location (code 804):

Filter element

material (code 102):

inside diameter: mm

length: mm

filtering surface: mm²

mesh width: mm

7.3 Pressure side

7.3.1 In line

Number:

Design (code 803):

Location (code 804):

Filter element

material (code 102):

inside diameter: mm

length: mm

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

filtering surface: mm²

mesh width: mm

7.3.2 In fittings

Number:

Design (code 803):

Location (code 804):

Filter element

material (code 102):

diameter: mm

length: mm

filtering surface: mm²

mesh width: mm

7.3.3 In spray boom

Number:

Design (code 803):

Location (code 804):

Filter element

material (code 102):

diameter: mm

length: mm

filtering surface: mm²

mesh width: mm

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

7.4 Additional filters

Function:

Number:

Design (code 803):

Location (code 804):

Filter element

material (code 102):

diameter: mm

length: mm

filtering surface: mm²

mesh width: mm

8 Fittings

8.1 Pressure regulator

Design (code 905):

Location (code 901):

Pressure-regulating range: from ... MPa to ... MPa

Control (code 103):

8.2 Main control valves

Design (code 903):

Location (code 901):

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

Control (code 103):

Suck-back control device YES NO

8.3 Pressure relief valve

Design (code 904):

8.4 Shut-off valves

Number:

Design (code 903):

Location (code 901):

Control (code 103):

8.5 Pressure-adjusting valve

Number:

Design (code 902):

Location:

Control (code 103):

8.6 Pressure gauge (manometer)

Number:

Location (code 901):

Scale range:

Graduation:

Diameter of casing:

Damping:

Compensation (code 907):

STANDARDISO.COM : Click to view the full PDF of ISO 10627-2:1996

Accuracy class:

9 Volume regulation system specification

Designation:

Manufacturer:

9.1 System with constant flowrate

Design (code 909):

Function (code 910):

Location (code 911):

Control (code 103):

Working range

pressure:

volumetric flowrate:

p.t.o. speed:

speed of travel:

maximum deviation from calibrated rate:

9.2 System with variable flowrate

Design (code 909):

Function (code 910):

Location (code 911):

Control (code 103):

STANDARDSISO.COM : Click to view the full PDF of ISO 10627-2:1996

Function range

| | |
|---|-----------------------------|
| pressure range: | from ... MPa to ... MPa |
| volumetric flowrate: | from ... l/min to ... l/min |
| p.t.o. speed: | from ... r/min to ... r/min |
| speed of travel: | from ... m/s to ... m/s |
| maximum deviation from calibrated quantity: | from + ... % to - ... % |

9.3 Other regulation systems

| | |
|---|----------------------|
| Design (code 909): | <input type="text"/> |
| Function (code 910): | <input type="text"/> |
| Location: | <input type="text"/> |
| Control (code 103): | <input type="text"/> |
| Working range (necessary for estimate): | <input type="text"/> |

10 Special accessories specifications

10.1 Band and row spraying devices

| | |
|-----------------------|----------------------|
| Number of rows: | <input type="text"/> |
| Designation: | <input type="text"/> |
| Function: | <input type="text"/> |

10.2 Description of further special accessories not otherwise given

(List and describe type and function, give the dimensions.)

11 Specifications for volumes of residue

11.1 Volume of residue in tank

On flat surface

On side slope

| | Side-slope of 8,5° | | Maximum angle given by the manufacturer: | |
|-------------------------|---|---|--|---|
| | In litres | As percentage of nominal tank volume | In litres | As percentage of nominal tank volume |
| | | | <input style="width: 150px; height: 20px;" type="text"/> ° | |
| in the contour | | | | |
| direction of travel | | | | |
| to the left..... | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % |
| to the right..... | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % |
| in the contour gradient | | | | |
| ascending..... | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % |
| descending..... | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % | <input style="width: 50px; height: 20px;" type="text"/> | <input style="width: 50px; height: 20px;" type="text"/> % |

STANDARDSISO.COM · Click to view the full PDF of ISO 10627-2:1996

11.2 Dead volume

On flat surface

On side slope

| | Side-slope of 8,5° | | Maximum angle given by the manufacturer: | |
|------------------------------------|--|--|---|--|
| | In litres | As percentage of nominal tank volume | In litres | As percentage of nominal tank volume |
| | | | <input style="width: 150px; height: 20px; border: 1px solid black;" type="text"/> | |
| in the contour direction of travel | | | | |
| to the left..... | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % |
| to the right..... | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % |
| in the contour gradient | | | | |
| ascending | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % |
| descending..... | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> | <input style="width: 60px; height: 20px; border: 1px solid black;" type="text"/> % |

STANDARDSISO.COM: Click to view the full PDF of ISO 10627-2:1996

Annex A (normative)

Code list

Code list shall be made from each list below.

If the code-No. "99" is used a description should be given which is as exact as possible.

When more than one code is used, the code numbers shall be separated by "+".

101 General/Location of marking

| Implement part | | Location | |
|----------------|------------------------|----------|--------------|
| 0 | no marking | | |
| 1 | at the frame | 1 | front left |
| 2 | at the tank | 2 | front middle |
| 3 | at the linkage of bars | 3 | front right |
| 99 | other | 4 | rear left |
| | | 5 | rear middle |
| | | 6 | rear right |
| | | 7 | left |
| | | 8 | right |
| | | 99 | other |

102 Material

| | |
|----|---|
| 1 | aluminium |
| 2 | special steel |
| 3 | special steel covered by synthetic material |
| 4 | fibreglass |
| 5 | rubber |
| 6 | rubber with textile insert |
| 7 | hard rubber |
| 8 | stainless steel |
| 9 | glass-fibre reinforced synthetic material |
| 10 | brass |
| 11 | buna N rubber |
| 12 | polyamide (Nylon, Perlon) |
| 13 | polyester |
| 14 | polyethylene |
| 15 | polyethylene with textile insert |
| 16 | polyethylene with spiral line (or hoses) |
| 17 | polyoxymethylene |
| 18 | polyvinylchloride |
| 19 | polyvinylchloride with textile insert |
| 20 | polyvinylchloride with spiral (for hoses) |
| 21 | cellular material |
| 22 | steel |
| 23 | steel covered by polyester |
| 24 | rustless steel |
| 25 | galvanized steel |
| 26 | Viton |
| 99 | other |

103 Driving mechanism

- 0 not driven
- 1 mechanically driven by hand
- 2 mechanically driven by p.t.o.
- 3 hydraulically driven
- 4 pneumatically driven
- 5 electrically driven
- 6 electromotively driven
- 7 electropneumatically driven
- 8 electrohydraulically driven
- 9 electromagnetically driven
- 99 other

303 Tank — Level indicator — Type

- 0 no level indicator
- 1 simple scale, transparent background
- 2 simple scale, non-transparent background
- 3 scale on viewing glass
- 4 stand pipe with scale
- 5 stand pipe with scale and float
- 6 scale with float
- 7 round scale with pointer and float in tank
- 8 straight scale with increasing graduation downwards and float in tank
- 9 electronic indication
- 99 other

304 Tank — Level indicator — Location

- | | | | |
|----|----------------|--------------------|-----------------|
| 0 | | no level indicator | |
| 1 | on the face | 1 at front | 1 internal side |
| 2 | on right | 2 on right | 2 external side |
| 3 | at rear | 3 at rear | |
| 4 | on left | 4 on left | |
| 5 | in tractor cab | 5 in middle | |
| 6 | on tank | 6 open choice | |
| 99 | elsewhere | | |

305 Tank — Filling hole — Design of lid

- | | Lock system | Aeration | Seal |
|----|----------------------------|-----------------|----------------------|
| 0 | no lock | 0 no aeration | |
| 1 | lid border with claws | 1 with aeration | 1 no seal |
| 2 | hinged lid | | 2 packing ring |
| 3 | screw cap | | 3 O-ring seal |
| 4 | lid to be inserted | | 4 sealing round cord |
| 5 | lid with a bow-shaped lock | | 5 sealing lip |
| 6 | turn-lock fastener | | 6 labyrinth seal |
| 99 | other | | 99 other |

306 Tank — Filling hole — Location

| | |
|----|-----------------|
| 0 | no filling hole |
| 1 | central |
| 2 | on left |
| 3 | on right |
| 4 | in front |
| 5 | at rear |
| 99 | other |

307 Tank — Agitator — Type

| | |
|----|-----------------------|
| 0 | no agitator |
| 1 | return flow |
| 2 | pressure agitator |
| 3 | with one nozzle tube |
| 4 | with two nozzle tubes |
| 5 | with one injector |
| 6 | with two injectors |
| 7 | turbine |
| 8 | propeller |
| 9 | wobble disc |
| 99 | other |

308 Tank — Agitator — Design

| | |
|----|---------------------------------|
| 0 | no handling |
| 1 | no switch-off |
| 2 | switch-off possible (in series) |
| 3 | switch-off possible (optional) |
| 4 | adjustable (in series) |
| 5 | adjustable (optional) |
| 99 | other |

310 Tank — Agitator — Location

| | |
|----|---|
| 0 | no agitator |
| 1 | centrally above tank bottom |
| 2 | laterally on left above tank bottom |
| 3 | laterally on right above tank bottom |
| 4 | laterally on both sides above tank bottom |
| 5 | laterally on both sides and centrally above tank bottom |
| 99 | other |

312 Tank — Drainage device — Type

| | |
|----|------------------------------------|
| 1 | separate outlet valve |
| 2 | in combination with suction device |
| 99 | other |

313 Tank — Drainage device — Design

- 1 ball valve
- 2 valve
- 3 male fitting
- 4 disconnecting of suction hose
- 5 removal of filter mesh
- 99 other

314 Tank — Drainage device — Location

- 1 on left
- 2 on right
- 3 in front
- 4 at rear
- 5 at suction filter
- 6 at pump
- 7 at tank sump
- 99 other

315 Tank — Filling device — Type

- 0 no filling device
- 1 with connection to water hose
- 2 with main pump of sprayer
- 3 with filling pump
- 4 with injector
- 99 other

316 Tank — Filling device — Design

- 0 no filling device
- 1 suction hose with filter mesh
- 2 suction hose with filter mesh and non-return valve
- 3 hose connection with integral device producing a free jet (prevention of backflow)
- 99 other

317 Tank — Filling device — Location

- 0 no filling device
- 1 at filter valve
- 2 at suction valve
- 3 at pump
- 4 at filling hole
- 5 adjacent to filling hole
- 99 other

318 Tank — Filtration device — Design

- 0 no filtration device
- 1 filling sieve
- 2 filling shower
- 3 injector
- 4 injector with device for tank cleaning
- 99 other

319 Tank — Filtration device, dosing device — Location

- 0 no filtration device
- 1 on right of tank
- 2 on left of tank
- 3 filling hole
- 4 on right of chassis
- 5 on left of chassis
- 99 other

320 Tank — Dosing device — Type

- 0 no dosing apparatus
- 1 intermittent
- 2 continuous (direct to tank)
- 99 other

321 Tank — Dosing device — Design

- 0 no dosing apparatus
- 1 injector with product measuring
- 2 pump with product measuring
- 3 injector with electric volumeter
- 4 pump with electric volumeter
- 5 pump with no product measuring (dosing pump)
- 6 dosing pump with volume indicator
- 7 hydraulically by main stream
- 99 other

402 Pump — Design

| Type | Number of pistons/chambers |
|---------------------------------------|--------------------------------------|
| 0 no pump | 0 no piston/chambers |
| 1 reciprocating pump/in-line | n n = number of pistons/chambers |
| 2 reciprocating pump/star-shaped | |
| 3 reciprocating pump/opposed type | |
| 4 piston pump/in-line | |
| 5 piston pump/star-shaped | |
| 6 piston pump/opposed type | |
| 7 diaphragm pump/opposed type | |
| 8 diaphragm pump/star-shaped | |
| 9 diaphragm pump/opposed type | |
| 10 diaphragm piston pump/in-line | |
| 11 diaphragm piston pump/star-shaped | |
| 12 diaphragm piston pump/opposed type | |
| 13 peristaltic pump | |
| 14 centrifugal pump | |
| 15 roller pump | |
| 16 vane-cell pump | |
| 99 other | |