
Cutter arbors with parallel key and tenon drive —

**Part 4:
Dimensions and designation of tool
holders with 7/24 taper without automatic
tool changers**

Mandrins porte-fraise à entraînement par clavette et tenon —

*Partie 4: Dimensions et désignation des porte-outils à conicité 7/24
sans changement automatique d'outils*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 10649-4:2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10649-4 was prepared by Technical Committee ISO/TC 29, *Small tools*, Subcommittee SC 2, *High speed steel cutting tools and their attachments*.

ISO 10649 consists of the following parts, under the general title *Cutter arbors with parallel key and tenon drive*:

- *Part 1: General dimensions*
- *Part 2: Dimensions and designation of tool holders with hollow taper interface with flange contact surface*
- *Part 3: Dimensions and designation of tool holders with 7/24 taper for automatic tool changers*
- *Part 4: Dimensions and designation of tool holders with 7/24 taper without automatic tool changers*

The dimensions and designations of tool holders with polygonal taper interface with flange contact surface will form the subject of a part 5 and the dimensions and designations of tool holders with modular taper interface with ball track system will form the subject of a part 6.

Introduction

The aim of ISO 10649 (all parts) is to specify the main dimensions for tool holders for this type of interface, and prevent the risk of collision when exchanging the assembled tool within the machine tools.

STANDARDSISO.COM : Click to view the full PDF of ISO 10649-4:2010

Cutter arbors with parallel key and tenon drive —

Part 4:

Dimensions and designation of tool holders with 7/24 taper without automatic tool changers

1 Scope

This part of ISO 10649 specifies the dimensions of cutter arbors with parallel key and tenon drive with 7/24 tapers without automatic tool changers.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 297, *7/24 tapers for tool shanks for manual changing*

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 2768-2, *General tolerances — Part 2: Geometrical tolerances for features without individual tolerance indications*

ISO 2780, *Milling cutters with tenon drive — Interchangeability dimensions for cutter arbors — Metric series*

ISO 10643, *Dimensions of accessories for cutter arbors with parallel key and tenon drive*

ISO 10649-1, *Cutter arbors with parallel key and tenon drive — Part 1: General dimensions*

3 Dimensions

3.1 General

All dimensions and tolerances are given in millimetres. Tolerances not specified shall be of tolerance class “m” in accordance with ISO 2768-1 and of class “K” in accordance with ISO 2768-2.


Figure 1 is schematic and is not intended to specify a given design; only the given dimension shall be met.

The interchangeability dimensions of the milling cutter bearing on the cutter arbors shall be in conformity with ISO 2780. The retaining bolt used has the dimensions specified in ISO 2780.

The dimensions of tool interface for arbors with parallel key and tenon drive shall be in accordance with ISO 10649-1.

3.2 Dimensions of arbors with 7/24 taper shanks without automatic tool changers

The dimensions for cutter arbors with parallel key and tenon drive with 7/24 tapers without automatic tool changers shall be in accordance with the dimensions shown in Figure 1 and given in Table 1.



Key

- 1 tool holder with 7/24 taper in accordance with ISO 297
- 2 parallel key in accordance with ISO 10643
- 3 retaining screw in accordance with ISO 10643
- 4 clutch drive ring in accordance with ISO 10643
- a Taper shank 7/24 in accordance with ISO 297.
- b Not convex.

Figure 1 — Arbors with 7/24 taper shanks without automatic tool changers

Table 1 — Dimensions of arbors with 7/24 taper shanks without automatic tool changers

Shank no.	30				40						45						50						60					
d_1	16	22	27	32	16	22	27	32	40	50	16	22	27	32	40	50	16	22	27	32	40	50	27	32	40	50	60	
d_2	31,75				44,45						57,15						69,85						107,95					
l_1	35			50	52						55				65	55					82							
l_2	25	23	23	36	42	40	40	38	38	36	45	43	43	41	41	39	45	43	43	41	41	39	70	68	68	66	66	

4 Material

The material is left to the manufacturer's discretion; the tensile strength shall be at least 800 N/mm².

The surface hardness shall be (56 + 4) HRC in the area of the taper surface and the surfaces of the spigot. The hardness depth is left to the manufacturer's discretion.