

INTERNATIONAL
STANDARD

ISO
10752

First edition
1994-05-15

**Coal sizing equipment — Performance
evaluation**

*Charbon — Équipement pour la granulométrie — Évaluation de l'aptitude
à l'emploi*



Reference number
ISO 10752:1994(E)

Contents

	Page
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Performance criteria	2
5 Performance parameters	2
6 Performance test procedures	2
7 Analytical procedures	3
8 Evaluation and presentation of performance characteristics	3
9 Tabular and graphical presentation	6

Annexes

A Calculation of the yield of each product of a size separation from size analyses of feed and product materials	13
B Worked example — Vibrating screen	15
C Worked example — Cyclone	22
D Worked example — Deduster	29

STANDARDSISO.COM : Click to view the full PDF of ISO 10752:1994

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10752 was prepared by Technical Committee ISO/TC 27, *Solid mineral fuels*, Subcommittee SC 1, *Coal preparation. Terminology and performance*.

Annex A forms an integral part of this International Standard. Annexes B, C and D are for information only.

STANDARDSISO.COM : Click to view the full PDF of ISO 10752:1994

Introduction

A standard expression of performance is required to define the accuracy of separation of a particular item, to assist in the comparison of the performance of different items of coal sizing equipment and in the prediction of separation results.

STANDARDSISO.COM : Click to view the full PDF of ISO 10752:1994

Coal sizing equipment — Performance evaluation

1 Scope

This International Standard describes the principles and methods for the expression of results of performance tests on sizing equipment used in coal preparation, and includes methods for the evaluation of performance parameters. Performance test procedures and size measurement techniques are recommended.

This International Standard applies to all types of sizing equipment, categorized as follows:

- a) screens;
- b) classifiers;
- c) others.

The procedure described in this International Standard applies to two-product separations. Performance assessment of multiproduct separations can be achieved by consideration of a series of two-product separations.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1170:1977, *Coal and coke* — Calculation of analyses to different bases.

ISO 1213-1:1993, *Solid mineral fuels - Vocabulary — Part 1: Terms relating to coal preparation*.

ISO 1953:1972, *Hard coals* — Size analysis.

ISO 1988:1975, *Hard coal* — Sampling.

3 Definitions

For the purposes of this International Standard, the definitions given in 1213-1 and the following definitions apply.

3.1 General

3.1.1 actual feed (F): Material fed to the sizing equipment during the test period and including any recirculated material.

3.1.2 coarser material: Material that is coarser than the reference size.

3.1.3 finer material: Material that is finer than the reference size.

3.1.4 product: Material discharged from the sizing equipment prior to any further treatment or recirculation.

3.1.5 coarser product (c): That product of size separation that contains a greater proportion of coarser material than does the feed.

3.1.6 finer product (f): That product of size separation that contains a greater proportion of finer material than does the feed.

3.1.7 sharpness of separation: An assessment of the deviation from a perfect separation, usually expressed in terms of mean probable error (E_{pm}).

3.2 Performance parameters

3.2.1 theoretical yield (sizing): The maximum yield of a product at a reference size, as determined from the size distribution curve for the reconstituted feed.

3.2.2 coarser material placement efficiency (E_c): The percentage of coarser material in the reconstituted feed that reports to the coarser product.

3.2.3 finer material placement efficiency (E_f): The percentage of finer material in the reconstituted feed that reports to the finer product.

3.2.4 overall separation index: The sum of the coarser material placement efficiency and the finer material placement efficiency minus 100.

4 Performance criteria

The following criteria should be determined where applicable:

- a) feed rate;
- b) reference size of separation;
- c) sharpness of separation;
- d) misplaced material;
- e) material placement efficiencies;
- f) the degree of difficulty of separation;
- g) material characteristics.

NOTES

- 1 The above criteria will be influenced by test conditions which should therefore be fully reported.
- 2 It is essential that prediction of separation results takes into account the influence of test conditions.
- 3 It is essential that test conditions are made compatible to ensure valid comparisons.
- 4 Conditions should be kept uniform during a test.

5 Performance parameters

For the standard expression of performance of a separation, the criteria in clause 4 should be determined by the following parameters:

- a) the feed rate, expressed on mass and/or volume bases;

- b) the reference size, preferably expressed as both partition size and equal errors size;

NOTE 5 It is recognized that partition size is not always obtainable from the results of a size separation and that an alternative reference size therefore has to be employed. To allow comprehensive comparison of performance, it is recommended that parameters based on equal errors size as the reference be included, in addition to those based on partition size.

- c) the sharpness of separation, expressed in terms of probable error;
- d) the distribution of misplaced material in each product, presented graphically with respect to size, and the particular values of misplaced material in each product on both feed and product bases, each determined at the reference size of separation;
- e) the material placement efficiencies expressed as
 - 1) coarser material placement efficiency (E_c),
 - 2) finer material placement efficiency (E_f),
 - 3) overall separation index derived from 1) and 2);
- f) the degree of difficulty of separation, expressed in terms of near-size material;
- g) other relevant characteristics of the feed material.

6 Performance test procedures

The equipment to be tested, the actual feed composition, and the means of handling the feed and products vary widely. A single standard procedure is not applicable. The following general recommendations are made.

- a) The average feed rate and/or product flow rates should be determined by the most accurate method possible in the particular circumstances. Typical procedures that may be used are
 - 1) direct assessment of the mass and/or volume of the whole of the feed or product during the test;
 - 2) continuous assessment by means of a calibrated belt weigher or flowmeter and integration during the test;
 - 3) weighing timed increments taken at regular intervals during the test.

- b) Samples should be taken from the actual feed and from each of the products. Sampling techniques, initial number of increments and minimum mass of each increment should be chosen so that all samples taken are representative. Sampling techniques, initial number of increments and minimum mass of increment for solids being conveyed by a fluid should comply with existing International Standards if available; for solids under other conditions, ISO 1988 applies.

NOTE 6 Representative samples should be taken from all relevant streams to and from the equipment to be tested, to facilitate checking of results and assessment of the effects of degradation.

- c) It is essential to determine the feed rate and the actual yield of each product on a dry basis in accordance with ISO 1170. This should be achieved in accordance with one of the following procedures.
- 1) The mass of each product should be determined by one or more of the following methods:
 - a. direct weighing of the whole of each product collected over the duration of the test or through continuous weighing and integration over the duration of the test;
 - b. taking regular timed increments over the duration of the test;
 - c. weighing each product collected simultaneously over a selected timed period during the test.

NOTES

7 The methods given in 1) are listed in order of reliability.

8 If it is feasible to measure both the mass of the feed (by belt weigher, weigh hopper, flowmeter, etc.) and the mass of the products, this provides a check.

9 If the mass of one of the products cannot be measured, it can be obtained from a mass balance between the feed and products.

10 Where the solids are conveyed by a fluid, it may be more convenient to make volumetric measurements.

11 Representative samples should be taken from relevant streams to determine moisture contents or concentrations of solids as appropriate, so that the results can be reported on a dry basis.

- 2) In circumstances that prevent the weighing of sufficient streams, size analyses of feed and products can be used to determine the percentage yield of each product, as described in annex A.

NOTE 12 In all circumstances, the method used to determine the actual yield of each product should be reported with each respective value in table 3.

7 Analytical procedures

The method and procedure of size analysis should be selected, as far as possible, to be in agreement with the principle of the equipment under test, to produce results in compatible terms. For example, the results of size analysis by sieving would be compatible with vibrating screens, and the results of size analysis by a series of small cyclones would be compatible with cyclone separators. Size analysis by sieving should be carried out in accordance with ISO 1953. The method and apparatus used, and the basis of the percentages (by mass or volume), shall be stated in the data sheet and in table 1.

The feed sample and each of the product samples should be subjected to size analyses in which the ratio of the upper and lower size limits does not exceed 2:1 for each size fraction. It is recommended that this ratio for size limits be reduced to $\sqrt{2}$:1 for a minimum of two fractions, both above and below the reference size.

NOTES

13 In some circumstances, a ratio of size limits closer than $\sqrt{2}$:1 may be necessary in the region of the reference size, to ensure that each of the size fractions contains not more than 10 % of the sample.

14 Size distribution curves for the products can be used for

- a) providing data for additional partition coefficients;
- b) averaging analytically determined values to improve the derived partition curve.

8 Evaluation and presentation of performance characteristics

8.1 General

All data shall be evaluated and presented in one data sheet, three tables and three figures as follows:

- a) data sheet — test and equipment data;

- b) table 1 — size distribution of feed and products;
- c) table 2 — partition coefficients and misplaced material data;
- d) table 3 — statement of sizing equipment performance;
- e) figure 1 — partition curve;
- f) figure 2 — size distribution curve for the reconstituted feed;
- g) figure 3 — misplaced material curves.

The presentation of the test data may be accomplished by the procedure described below. The specified tabular and graphical formats are given in clause 9. Specific worked examples are included in annexes B, C and D.

NOTES

- 15 Primary calculation procedures are shown in tables 1 and 2. A column number in parentheses denotes a respective value taken from that column.
- 16 The origins of plotted values are shown in figures 1 and 2 by reference to table and column numbers.
- 17 Reference to definitions of performance parameters in clause 3 supports the brief explanation of their derivation given in relevant subclauses and in tables 1 and 2.

8.2 Basic data

The data obtained from a performance test comprise the size analyses of the actual feed and the coarser and finer products and the proportion of material reporting to each product. These basic data are compiled in table 1, columns 1 to 8, and calculated on a reconstituted feed basis in columns 9 to 12.

8.3 Reconstituted feed size distribution

The size distribution curve for the reconstituted feed is constructed as shown in figure 2, by plotting the cumulative percent less than the upper size limit (column 12 of table 1) against the upper size limit (column 1 of table 1).

NOTE 18 It is convenient to use a logarithmic scale for particle size when plotting size distribution curves, to cover a wide range of sizes and to cater for size limits that are in geometric progression.

8.4 Partition curve

The partition curve is constructed as shown in figure 1, by plotting the value of each partition coefficient against the corresponding mean size. It is recommended that each size fraction be represented by its geometric mean size. Geometric mean sizes and partition coefficients are calculated in table 2, columns 13 and 14. The recommended scales are

size: \log_{10} 1 cycle = 50 mm

partition coefficient: 1 % = 2 mm

NOTES

- 19 As an alternative to geometric mean size, each size fraction may be represented by its mid-mass particle size, derived from a known functional relationship or estimated from the reconstituted feed curve.
- 20 As an alternative method of construction, partition coefficients can be plotted as a histogram on a reconstituted feed base, producing an area representative of mass. An intermediate curve is then drawn by equalizing areas within each size fraction. Performance parameters are derived by applying values obtained from the intermediate curve to the size distribution curve for the reconstituted feed.

8.5 Partition size

The partition size, S_{50} , is obtained directly from the partition curve and is entered as a performance parameter in the statement of sizing equipment performance in table 3.

NOTE 21 The partition size can be determined from the misplaced material curves (figure 3) at the minimum value of total misplaced material.

8.6 Sharpness of separation

The 25 %, S_{25} , and 75 %, S_{75} , intercepts are each read from the partition curve (figure 1) and are entered as primary parameters in the statement of sizing equipment performance in table 3. For symmetrical partition curves, the sharpness of separation may be expressed in terms of the mean probable error (E_{pm}) as follows:

$$E_{pm} = \frac{S_{75} - S_{25}}{2} \quad \dots (1)$$

In the more common case of skewed partition curves, the sharpness of separation may be expressed in terms of the upper and lower probable errors as follows:

$$\text{Upper probable error} = S_{75} - S_{50}$$

$$\text{Lower probable error} = S_{50} - S_{25}$$

The upper probable error and lower probable error parameters may be used separately if one of the intercepts is undefined.

8.7 Misplaced material curves

The misplaced materials in the coarser and finer products are calculated, as a percentage of the reconstituted feed, in table 2, columns 15 and 16. Corresponding values are summed to give total misplaced material tabulated in column 17 of table 2. The misplaced material curves are constructed, as shown in figure 3, by plotting values for coarser products (column 15 of table 2), finer products (column 16 of table 2) and total misplaced materials (column 17 of table 2), each against the corresponding upper size limit S_1 (column 1 of table 1). The recommended scales are

size: \log_{10} 1 cycle = 50 mm

misplaced material: 1 % = 5 mm

NOTE 22 If it is necessary to use an alternative scale, this should be a simple multiple of the recommended scale; for an example see annex C, figure C.3.

8.8 Misplaced material

The misplaced material is read from each respective curve at the reference size, or sizes (see note 23), and the values are entered into the statement of sizing equipment performance in table 3. The value of misplaced material for each respective product is converted to a percentage of that product (see note 24), and the converted values are entered into the statement in table 3.

NOTES

23 It is convenient to construct an ordinate on the curves, at the reference size, or sizes, being considered (e.g. S_d , S_{50} , S_e), to assist in reading the three intercepting misplaced values.

24 All values of misplaced material obtained from the curves are in terms of percentages of the reconstituted feed. Conversion to percentages of the respective product can be obtained by multiplying the corresponding curve by 100 and dividing by the yield value of the product under consideration (i.e. Y_c or Y_f).

25 The procedure can be repeated for any other reference size.

8.9 Equal errors size

The equal errors size (S_e) is determined by reading the size that corresponds to the point of intersection of the misplaced material curves for coarser and finer products. Alternatively, the equal errors size can be determined from the size distribution curve for the reconstituted feed, as the size corresponding to the yield of the finer product. The equal errors size is entered into the statement of sizing equipment performance in table 3.

8.10 Theoretical yield

The theoretical yield value at the reference size, or sizes, is determined, for each of the products, from the size distribution curve for the reconstituted feed. Alternatively, each respective theoretical yield value can be determined by subtracting the misplaced material in the product under consideration from the actual yield (Y_c or Y_f) and adding the misplaced material in the complementary product.

EXAMPLE

$$Y_{c,t} = Y_c - M_c + M_f \quad \dots (2)$$

where

$Y_{c,t}$ is the theoretical yield of the coarser product;

Y_c is the yield value of the coarser product;

M_c is the misplaced material in the coarser product;

M_f is the misplaced material in the finer product.

Theoretical yield values are entered into the statement of sizing equipment performance in table 3.

NOTES

26 Misplaced material values are in terms of percentages of reconstituted feed.

27 The theoretical yield of the complementary product can be obtained by difference from 100 %.

8.11 Material placement efficiency

Material placement efficiencies are evaluated and entered into the statement of sizing equipment performance in table 3. The calculations are as follows.

- a) Coarser material placement efficiency (E_c)

$$E_c = \frac{Y_c - M_c}{Y_{c,t}} \times 100 \quad \dots (3)$$

where Y_c , M_c and $Y_{c,t}$ are as defined in 8.10.

- b) Finer material placement efficiency (E_f)

$$E_f = \frac{Y_f - M_f}{Y_{f,t}} \times 100 \quad \dots (4)$$

where

Y_f is the yield value of the finer product;

$Y_{f,t}$ is the theoretical yield of the finer product;

M_f is as defined in 8.10.

- c) Overall separation index (S_i)

$$S_i = E_f + E_c - 100 \quad \dots (5)$$

NOTES

28 Misplaced material values are in terms of percentage of reconstituted feed.

29 Alternative methods are available for the evaluation of the material placement efficiencies.

8.12 Near-size material

The near-size material, i.e. material within $\pm 25\%$ of the reference size or sizes, is determined from the size distribution curve for the reconstituted feed in figure 2, and is entered into the statement of sizing equipment performance in table 3.

Other relevant characteristics of the feed material that influence the degree of difficulty of separation are entered into the test and equipment data sheet, which varies according to the type of equipment under consideration. Examples of data sheets are given in annexes B, C and D.

8.13 Test and equipment data

The presentation of the results of performance tests on coal sizing equipment shall include a report of the equipment details, test conditions and characteristics of the feed material, particularly those that influence the degree of difficulty involved in the separation. This information is entered into the test and equipment data sheet. Since the parameters involved will vary for different categories of equipment, a specimen of the data sheet is not included in the general illustration, but models are presented in the specific worked examples given in annexes B, C and D.

9 Tabular and graphical presentation

Blank tables and specimen figures are given. The use of these is illustrated in annexes B, C and D. The order of presentation shall be as follows:

- data sheet — test and equipment data (see 8.13);
- table 1 — size distribution of feed and products;
- table 2 — partition coefficients and misplaced material data;
- figure 1 — partition curve;
- figure 2 — size distribution curve for the reconstituted feed;
- figure 3 — misplaced material curves;
- table 3 — statement of sizing equipment performance.

Table 1 — Size distribution of feed and products

1	2	Analyses of feed and products						8	9		10	11	12
		3		4		5			6				
Method of analysis (see clause 7)		Actual feed		Coarser product		Finer product		Coarser product		Finer product		Reconstituted feed	
Size limits, mm		Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Actual yield, Y_c %	Size fraction %	Actual yield, Y_f %	Size fraction %	Size fraction %	Cumulative percent less than S_1
Upper	Lower												
	S_1		$\Sigma (3) \uparrow$		$\Sigma (5) \uparrow$		$\Sigma (7) \uparrow$	$(5) \times \frac{Y_c}{100}$	$(7) \times \frac{Y_f}{100}$			$(9) + (10)$	$\Sigma (11) \uparrow$
Totals													

NOTE — A column number in parentheses denotes a respective value taken from that column.

Table 2 — Partition coefficients and misplaced material data

13	14	1	15	16	17
Geometric mean size mm	Partition coefficient (to coarser product) %	Size limit mm	Misplaced material (as a percentage of the reconstituted feed)		
		Upper	Coarser product	Finer product	Total
			Cumulative percent less than S_1	Cumulative percent greater than S_1	
$\sqrt{S_1 \times S_2}$	$\frac{(9)}{(11)} \times 100$	S_1	$\Sigma (9) \uparrow^{1)}$	$\Sigma (10) \downarrow^{2)}$	(15) + (16)

Note — A column number in parentheses denotes a respective value taken from a column in this table or table 1.

1) Summation to considered value of S_1 (in column 1 of table 1) from S_1 equal to zero.

2) Summation from considered value of S_1 (in column 2 of table 1) to S_1 equal to zero.




Figure 1 — Partition curve




Figure 2 — Size distribution curve for the reconstituted feed




Figure 3 — Misplaced material curves

Table 3 — Statement of sizing equipment performance

Performance parameters		Determined values		
Partition curve				
Partition size:	S_{50}			
25 % Intercept:	S_{25}			
75 % Intercept:	S_{75}			
Mean probable error:	$\frac{S_{75} - S_{25}}{2}$			
Upper probable error:	$(S_{75} - S_{50})$			
Lower probable error:	$(S_{50} - S_{25})$			
Misplaced material curves				
Equal errors size:	S_e			
		Percentage of feed (reconstituted)	Percentage of product	
Misplaced material in coarser product (M_c)				
at S_{50}				
at designated size (S_d)				
Misplaced material in finer product (M_f)				
at S_{50}				
at designated size (S_d)				
Total misplaced material				
at S_{50}				
at designated size (S_d)				
at S_e				
Product yield and material placement efficiencies		Method of determination		
Actual yield of coarser product:	Y_c			
Actual yield of finer product:	Y_f			
		at S_d	at S_{50}	at S_e
Theoretical yield of coarser product:	$Y_{c,t}$			
Theoretical yield of finer product:	$Y_{f,t}$			
Coarser material placement efficiency:	E_c			
Finer material placement efficiency:	E_f			
Overall separation index:	I_s			
Degree of difficulty involved				
Near-size material				

Annex A (normative)

Calculation of the yield of each product of a size separation from size analyses of feed and product materials

A.1 Introduction

Clause 6 lists the methods recommended, in order of reliability, for the determination of the yields of the coarser product (Y_c) and the finer product (Y_f) of a size separation.

Clause 6 also describes the circumstances under which these yield values may be calculated from the size analyses of the actual feed and the product materials. The two methods recommended are each based on the principle of least-squares and are outlined in A.2.

It is recognized that several methods exist for the calculation of the yield values, and each can be used with careful interpretation. The recommendations are, however, based on test work carried out under carefully controlled conditions where comparison was made between yield values calculated by several of the available methods, using directly determined values as the standard for comparison.

More sophisticated methods, involving the use of computer programs, are being developed, some of which are already available. Use of these methods can sometimes be justified by the nature of the work involved. Such methods are under review for possible future inclusion in this International Standard.

A.2 Recommended methods for the calculation of yield values from the size analyses

A.2.1 Symbols

The following symbols have been used in the calculations for both recommended methods:

- Y_f is the fractional yield of finer product;
 Y_c is the fractional yield of coarser product
 (= $1 - Y_f$);

i_F is the percentage of the i th fraction in the actual feed;

$i_{F(\text{rec})}$ is the percentage of the i th fraction in the reconstituted feed;

i_f is the percentage of the i th fraction in the finer product;

i_c is the percentage of the i th fraction in the coarser product.

A.2.2 Calculation of yield values from cumulative size analyses

This method is based on a least-squares principle, the yield values being calculated so that the sum of the squared deviations between the reconstituted feed and the actual feed size fractions, taken in terms of the actual feed size fraction, is at a minimum.

Thus:

$$\sum \frac{[i_F - i_{F(\text{rec})}]^2}{i_F} = \text{a minimum value} \quad \dots (A.1)$$

Since

$$i_{F(\text{rec})} = Y_f i_f + i_c (1 - Y_f) \quad \dots (A.2)$$

then, by substitution of (A.2) in (A.1)

$$\sum \frac{(i_F - Y_f i_f - i_c + Y_f i_c)^2}{i_F^2} = \text{a minimum value}$$

Therefore

$$2 \sum \frac{[i_F - i_c - Y_f(i_f - i_c)] \times (i_f - i_c)}{i_F^2} = 0$$

Therefore

$$\sum \frac{(i_F - i_c)(i_f - i_c)}{i_F^2} = Y_f \times \sum \frac{(i_f - i_c)^2}{i_F^2}$$

$$Y_f = \frac{\sum \frac{(i_F - i_c) - (i_f - i_c)}{i_F^2}}{\sum \left[\frac{i_f - i_c}{i_F} \right]^2} \quad \dots (A.3)$$

Using the cumulative form of the size analyses of actual feed, finer and coarser products, equation (A.3) can be rewritten as follows:

$$Y_f = \frac{\sum \left[\frac{(\sum i_F - \sum i_c)(\sum i_f - \sum i_c)}{\sum i_F^2} \right]}{\sum \left[\frac{\sum i_f - \sum i_c}{\sum i_F} \right]^2} \quad \dots (A.4)$$

Thus, equation (A.4) will allow calculation of the yield of the finer product from the cumulative size analyses of the actual feed and the finer and coarser products of the size separation.

A.2.3 Calculation of yield values from elementary size analyses

This method is based on a statistical "goodness of fit" test and is also a least-squares method.

The condition applied is as follows:

$$\sum \left[\frac{i_F - i_{F(\text{rec})}}{i_F} \right]^2 = \text{a minimum value} \quad \dots (A.5)$$

The following equation can be derived from equation (A.5) by a method similar to that used in A.2.2.

$$Y_f = \frac{\sum \left[\frac{(i_F - i_c)(i_f - i_c)}{i_F} \right]}{\sum \left[\frac{(i_f - i_c)^2}{i_F} \right]} \quad \dots (A.6)$$

Equation (A.6) will allow calculation of the yield of the finer product from the elementary size analyses of the actual feed and the finer and coarser products of the size separation.

Table B.1 — Size distribution of feed and products (vibrating screen)

1	2	Analyses of feed and products						8	9		10		11	12	
		3		4		5			6		7				Percentage of reconstituted feed
Method of analysis: Test sieves with square mesh		Actual feed		Coarser product		Finer product		Coarser product		Finer product		Reconstituted feed			
Size limits, mm	Upper	Lower	Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Actual yield $Y_c = 67,6\%$	Size fraction %	Actual yield $Y_f = 32,4\%$	Size fraction %	Size fraction %	Cumulative percent less than S_1	
															Σ (3) ↑
S_1		S_2													
125,0	63,0	8,0	6,0	100,0	7,1	100,0	0	100,0	4,8	0	0	0	4,8	100,0	
63,0	31,5	5,6	13,3	94,0	17,9	92,9	0	100,0	12,1	0	0	0	12,1	95,2	
31,5	16,0	4,0	20,5	80,7	30,4	75,0	0	100,0	20,6	0	0	0	20,6	83,1	
16,0	8,0	2,8	17,9	60,2	26,2	44,6	1,9	100,0	17,7	0,6	0,6	0,6	18,3	62,5	
8,0	5,6	2,0	8,3	42,3	10,5	18,4	6,5	98,1	7,1	2,1	2,1	2,1	9,2	44,2	
5,6	4,0	1,0	7,6	34,0	4,3	7,9	13,3	91,6	2,9	4,3	4,3	4,3	7,2	35,0	
4,0	2,8	0,5	5,9	26,4	1,4	3,6	19,1	78,3	1,0	6,2	6,2	6,2	7,2	27,8	
2,8	2,0	0	4,3	20,5	0,5	2,2	12,3	59,2	0,3	4,0	4,0	4,0	4,3	20,6	
2,0	1,0		6,7	16,2	0,5	1,7	20,4	46,9	0,3	6,6	6,6	6,6	6,9	16,3	
1,0	0,5		3,8	9,5	0,5	1,2	12,6	26,5	0,3	4,1	4,1	4,1	4,4	9,4	
0,5	0		5,7	5,7	0,7	0,7	13,9	13,9	0,5	4,5	4,5	4,5	5,0	5,0	
Totals			100,0	—	100,0	—	100,0	—	67,6	32,4	100,0	—	100,0	—	

NOTE — A column number in parentheses denotes a respective value taken from that column.

Table B.2 — Partition coefficients and misplaced material data (vibrating screen)

13	14	1	15	16	17
Geometric mean size mm	Partition coefficient (to coarser product) %	Size limit mm	Misplaced material (as a percentage of the reconstituted feed)		
		Upper	Coarser product	Finer product	Total
			Cumulative percent less than S_1	Cumulative percent greater than S_1	
$\sqrt{S_1 \times S_2}$	$\frac{(9)}{(11)} \times 100$	S_1	$\Sigma (9) \uparrow^{1)}$	$\Sigma (10) \downarrow^{2)}$	$(15) + (16)$
88,7	100	125,0	67,6	0	67,6
44,5	100	63,0	62,8	0	62,8
22,4	100	31,5	50,7	0	50,7
11,3	96,7	16,0	30,1	0	30,1
6,69	77,2	8,0	12,4	0,6	13,0
4,73	40,3	5,6	5,3	2,7	8,0
3,35	13,9	4,0	2,4	7,0	9,4
2,37	7,0	2,8	1,4	13,2	14,6
1,41	4,3	2,0	1,1	17,2	18,3
0,71	6,8	1,0	0,8	23,8	24,6
—	10,0	0,5	0,5	27,9	28,4
—	—	0	0	32,4	32,4
—	—	—	—	—	—

Note — A column number in parentheses denotes a respective value taken from a column in this table or table B.1.

1) Summation to considered value of S_1 (in column 1 of table B.1) from S_1 equal to zero.

2) Summation from considered value of S_1 (in column 2 of table B.1) to S_1 equal to zero.




Figure B.1 — Partition curve (vibrating screen)




Figure B.2 — Size distribution curve for the reconstituted feed (vibrating screen)




Figure B.3 — Misplaced material curves (vibrating screen)

Table B.3 — Statement of sizing equipment performance (vibrating screen)

Performance parameters		Determined values		
		mm		
Partition curve				
Partition size:	S_{50}	5,2		
25 % Intercept:	S_{25}	4,2		
75 % Intercept:	S_{75}	6,5		
Mean probable error:	$\frac{S_{75} - S_{25}}{2}$	1,15		
Upper probable error:	$(S_{75} - S_{50})$	1,3		
Lower probable error:	$(S_{50} - S_{25})$	1,0		
Misplaced material curves				
Equal errors size:	S_e	4,8		
		Percentage of feed (reconstituted)	Percentage of product	
Misplaced material in coarser product (M_c)				
at S_{50}		4,4	6,5	
at designated size (S_d)	5,0 mm	4,0	5,9	
Misplaced material in finer product (M_f)				
at S_{50}		3,3	10,2	
at designated size (S_d)	5,0 mm	3,7	11,4	
Total misplaced material				
at S_{50}		7,7		
at designated size (S_d)	5,0 mm	7,7		
at (S_e)		7,8		
Product yield and material placement efficiencies				
Actual yield of coarser product:	Y_c	67,6 %		
Actual yield of finer product:	Y_f	32,4 %		
		at S_d	at S_{50}	at S_e
Theoretical yield of coarser product:	$Y_{c,t}$	68,0 %	66,5 %	68,5 %
Theoretical yield of finer product:	$Y_{f,t}$	32,0 %	33,5 %	31,5 %
Coarser material placement efficiency:	E_c	93,5 %	95,0 %	93,3 %
Finer material placement efficiency:	E_f	89,7 %	86,9 %	90,5 %
Overall separation index:	I_s	83,2 %	81,9 %	83,5 %
Degree of difficulty involved				
Near-size material		11,5 %	11,6 %	11,4 %

Annex C (informative)

Worked example — Cyclone

Data sheet 2 — Test and equipment data (cyclone)

Reference	Date of test	Name of plant		
WE/C/1	2/1/84	Coal preparation plant		

Equipment details and duty		Test samples				
Type of sizing unit	Hydrocyclone	Method of sampling	Number of increments	Total sample		
Nominal diameter	75 mm			Volume	Mass of solids	
Inlet type	Volute			litres	kg	
Inlet size	20 mm × 15 mm					
Cylindrical section:		Feed	Manual	24	66	0,607
— length	75 mm	Coarser product	Manual	24	40	0,968
Vortex finder:		Finer product	Manual	24	53	0,275
— diameter	25 mm	Sample analysis				
— length	50 mm		Concentration of solids g/l	Relative density of solids	Method of size analysis	
Conical section:		Feed	9,3	2,6	Coulter counter	
— length	200 mm	Coarser product	24,2	2,6		
— total angle	15°	Finer product	5,2	2,6		
Nozzle:		Flow rates of liquids and solids				
— diameter	25 mm		Method of determination	Flow rate of liquids m ³ /h	Flow rate of solids t/h	Content of solids % (m/m)
Designated size	10 μm	Feed	Calculated	9,57	0,089	100,0
Rated capacity	10 m ³ /h at 2 bar	Coarser product	At regular timed increments	2,07	0,050	56,0
Feed characteristics		Finer product		7,50	0,039	44,0
Nature of feed	Sand					
Source of feed	Chance cone effluent					
Size limits	— 63 μm					
R. D.	2,6					
Test conditions						
Duration of test	2 h					

Table C.1 — Size distribution of feed and products (cyclone)

1	2	3	4	5	6	7	8	9		10		11	12
								Analyses of feed and products		Percentage of reconstituted feed			
Method of analysis: Coulter counter		Actual feed		Coarser product		Finer product		Coarser product		Finer product		Reconstituted feed	
Upper	Lower	Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Size fraction %	Cumulative percent less than S_1	Actual yield $Y_c = 56\%$	Size fraction %	Actual yield $Y_f = 44\%$	Size fraction %	Size fraction %	Cumulative percent less than S_1
			$\Sigma (3) \uparrow$		$\Sigma (5) \uparrow$		$\Sigma (7) \uparrow$	$(5) \times \frac{Y_c}{100}$	$(7) \times \frac{Y_f}{100}$			$(9) + (10)$	$\Sigma (11) \uparrow$
63,00	52,00	2,30	100,00	3,10	100,00	1,20	100,00	1,74	0,53	0,53	0,53	2,27	100,00
52,00	41,00	3,95	97,10	5,30	96,90	2,25	98,80	2,97	0,99	0,99	0,99	3,96	97,73
41,00	33,00	7,75	93,75	9,80	91,60	5,15	96,55	5,49	2,27	2,27	2,27	7,76	93,77
33,00	26,00	11,40	86,00	14,60	81,80	7,25	91,40	8,18	3,19	3,19	3,19	11,37	86,01
26,00	20,00	12,65	74,60	16,80	67,20	7,35	84,15	9,41	3,23	3,23	3,23	12,64	74,64
20,00	16,00	12,55	61,95	14,90	50,40	9,55	76,80	8,34	4,20	4,20	4,20	12,54	62,00
16,00	13,00	10,95	49,40	10,70	35,50	11,35	67,25	5,99	4,99	4,99	4,99	10,98	49,46
13,00	10,00	9,10	38,45	7,40	24,80	11,25	55,90	4,14	4,95	4,95	4,95	9,09	38,48
10,00	8,00	7,60	29,35	5,40	17,40	10,35	44,65	3,02	4,56	4,56	4,56	7,58	29,39
8,00	6,20	6,55	21,75	4,10	12,00	9,65	34,30	2,30	4,25	4,25	4,25	6,55	21,81
6,20	5,00	5,25	15,20	3,10	7,90	7,95	24,65	1,74	3,50	3,50	3,50	5,24	15,26
5,00	4,00	3,75	9,95	2,00	4,80	6,05	16,70	1,12	2,66	2,66	2,66	3,78	10,02
4,00	3,10	2,70	6,20	1,30	2,80	4,55	10,65	0,72	2,00	2,00	2,00	2,72	6,24
3,10	2,50	2,30	3,50	1,00	1,50	4,00	6,10	0,56	1,76	1,76	1,76	2,32	3,52
2,50	2,00	1,20	1,20	0,50	0,50	2,10	2,10	0,28	0,92	0,92	0,92	1,20	1,20
2,00	0	0	0	0	0	0	0	0	0	0	0	—	—
Totals		100,00	—	100,00	—	100,00	—	56,00	44,00	100,00	—	100,00	—

NOTE — A column number in parentheses denotes a respective value taken from that column.

Table C.2 — Partition coefficients and misplaced material data (cyclone)

13	14	1	15	16	17
Geometric mean size mm	Partition coefficient (to coarser product) %	Size limit µm	Misplaced material (as a percentage of the reconstituted feed)		
		Upper	Coarser product	Finer product	Total
			Cumulative percent less than S_1	Cumulative percent greater than S_1	
$\sqrt{S_1 \times S_2}$	$\frac{(9)}{(11)} \times 100$	S_1	$\Sigma (9) \uparrow^{1)}$	$\Sigma (10) \downarrow^{2)}$	$(15) + (16)$
57,24	76,75	63,00	56,00	0	56,00
46,17	75,00	52,00	54,26	0,53	54,79
36,78	70,74	41,00	51,29	1,52	52,81
29,29	71,94	33,00	45,80	3,79	49,59
22,80	74,45	26,00	37,62	6,98	44,60
17,89	66,51	20,00	28,21	10,21	38,42
14,42	54,55	16,00	19,87	14,41	34,28
11,40	45,54	13,00	13,88	19,40	33,28
8,94	39,84	10,00	9,74	24,35	34,09
7,04	35,11	8,00	6,72	28,91	35,63
5,57	32,21	6,20	4,42	33,16	37,58
4,47	29,63	5,00	2,68	36,66	39,34
3,52	26,47	4,00	1,56	39,32	40,88
2,78	24,14	3,10	0,84	41,32	42,16
2,37	23,33	2,50	0,28	43,08	43,36
—	—	2,00	0	44,00	44,00

Note — A column number in parentheses denotes a respective value taken from a column in this table or table C.1.

- 1) Summation to considered value of S_1 (in column 1 of table C.1) from S_1 equal to zero.
- 2) Summation from considered value of S_1 (in column 2 of table C.1) to S_1 equal to zero.




Figure C.1 — Partition curve (cyclone)




Figure C.2 — Size distribution curve for the reconstituted feed (cyclone)




Figure C.3 — Misplaced material curves (cyclone)

Table C.3 — Statement of sizing equipment performance (cyclone)

Performance parameters		Determined values		
		mm		
Partition curve				
Partition size:	S_{50}			12,6
25 % Intercept:	S_{25}			2,9
75 % Intercept:	S_{75}			60,5
Mean probable error:	$\frac{S_{75} - S_{25}}{2}$			28,8
Upper probable error:	$(S_{75} - S_{50})$			47,9
Lower probable error:	$(S_{50} - S_{25})$			9,7
Misplaced material curves				
Equal errors size:	S_e			14,5
		Percentage of feed (reconstituted)	Percentage of product	
Misplaced material in coarser product (M_c)				
at S_{50}		13,5		24,1
at designated size (S_d)	10,0 mm	9,8		17,5
Misplaced material in finer product (M_f)				
at S_{50}		19,8		45,0
at designated size (S_d)	10,0 mm	24,5		55,7
Total misplaced material				
at S_{50}		33,3		
at designated size (S_d)	10,0 mm	34,3		
at (S_e)		33,2		
Product yield and material placement efficiencies				
Actual yield of coarser product:	Y_c		56,0 %	
Actual yield of finer product:	Y_f		44,0 %	
		at S_d	at S_{50}	at S_e
Theoretical yield of coarser product:	$Y_{c,t}$	71,0 %	62,0 %	56,0 %
Theoretical yield of finer product:	$Y_{f,t}$	29,0 %	38,0 %	44,0 %
Coarser material placement efficiency:	E_c	65,1 %	68,5 %	70,4 %
Finer material placement efficiency:	E_f	67,2 %	63,7 %	62,3 %
Overall separation index:	I_s	32,3 %	32,2 %	32,7 %
Degree of difficulty involved				
Near-size material		18,0 %	21,5 %	24,5 %