

---

---

**Winter-sports equipment — Test  
devices for the setting of the  
functional unit ski/boot/binding —  
Requirements and tests**

*Matériel de sports d'hiver — Dispositifs d'essai pour le réglage de  
l'unité fonctionnelle ski/chaussure/fixation — Exigences et essais*

STANDARDSISO.COM : Click to view the full PDF of ISO 11110:2015



STANDARDSISO.COM : Click to view the full PDF of ISO 11110:2015



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Requirements</b> .....	<b>1</b>
3.1 General requirements.....	1
3.1.1 Design.....	1
3.1.2 Release moments and operating range.....	2
3.2 Quantitative requirements.....	2
3.2.1 Accuracy.....	2
3.2.2 Reproducibility.....	2
<b>4 Testing</b> .....	<b>2</b>
4.1 Test conditions.....	2
4.2 Test bindings.....	3
4.3 Setting of test bindings.....	3
4.4 Procedure.....	3
4.5 Reference measurements with reference device.....	4
<b>5 Instructions for use and maintenance</b> .....	<b>5</b>
<b>6 Test report</b> .....	<b>5</b>
<b>7 Marking</b> .....	<b>5</b>
<b>Bibliography</b> .....	<b>7</b>

STANDARDSISO.COM : Click to view the full PDF of ISO 11110:2015

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 83, *Sports and recreational equipment*, Subcommittee SC 4, *Snowsports equipment*.

This second edition cancels and replaces the first edition (ISO 11110:1997), which has been technically revised.

# Winter-sports equipment — Test devices for the setting of the functional unit ski/boot/binding — Requirements and tests

## 1 Scope

This International Standard specifies the tests and requirements for devices used to determine the release moments of ski-bindings in retail sales, rental, and other facilities.

It specifies requirements for the design accuracy, operation, maintenance, and calibration of the test devices used for determining binding release settings.

For other requirements, see appropriate standards (e.g. standards on electronic measuring devices, safety of electrical apparatus, etc.).

This International Standard is to be used in conjunction with ISO 9462 and ISO 8061.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 9462, *Alpine ski-bindings — Requirements and test methods*

ISO 9838, *Alpine and touring ski-bindings — Test soles for ski-binding tests*

## 3 Requirements

### 3.1 General requirements

#### 3.1.1 Design

**3.1.1.1** Setting devices shall be capable of determining the actual release moments of common ski-bindings on the market. They are designed for practical use by retail, rental, and other facilities.

**3.1.1.2** The device shall be capable of completely releasing the boot from the binding.

**3.1.1.3** In order to avoid the skis elasticity to lead to measurement errors, the clamping of the ski shall be as close as possible to the binding. It shall be possible to apply the release load smoothly and without interruption until the maximum release moment has been reached.

The release shall be quasi-static such that the total time required shall not be more than 5 s not less than 2 s.

The speed at the boot toe or heel shall never exceed 20 mm/s, from the beginning of the release process up to the time when the maximum release value is reached.

**3.1.1.4** The device shall be capable of indicating the peak release moment after the test is over.

3.1.1.5 It shall be possible to observe the boot and the binding at all times during the release process.

3.1.1.6 The ski, ski-boot, and ski-binding shall not be damaged by normal use of the test device.

### 3.1.2 Release moments and operating range

3.1.2.1 The test device shall indicate release moments in at least forward bending ( $+M_Y$ ) and in twist ( $+M_Z$  and  $-M_Z$ ). The results are given in Newton metres (Nm).

Release moments shall be in accordance to ISO 9462.

3.1.2.2 The manufacturer of the test device shall specify the Recommended Operating Ranges (ROR) of the test device.

3.1.2.3 The magnitude of the smallest increment which can normally be estimated shall not exceed 1 Nm for  $M_Z$  and 5 Nm for  $M_Y$  or 5 % of the smallest value in the ROR, whichever is the greater.

## 3.2 Quantitative requirements

### 3.2.1 Accuracy

The test device shall be of a design such that when tested by the methods of [Clause 4](#) the difference in the results between the test device and the reference device will be as follows.

- a) The average difference for all test series shall not exceed
  - for  $M_Z$ : 10 % or 4 Nm, whichever is the least restrictive, and
  - for  $M_Y$ : 5 % or 10 Nm, whichever is the least restrictive.
- b) The difference for any individual test series shall not exceed
  - for  $M_Z$ : 10 % or 4 Nm, whichever is the least restrictive, and
  - for  $M_Y$ : 10 % or 15 Nm, whichever is the least restrictive.

If these requirements are not fulfilled for a test series involving one or several particular bindings, the instructions for use of the test device should describe the appropriate actions:

- by excluding these bindings from the application field of the device;
- by giving the amount of correction needed to obtain an accurate measurement, if this is possible by simple means.

### 3.2.2 Reproducibility

The device shall be of a design such that the reproducibility limit  $r$ , when averaged for all series, is not more than 3 %.

## 4 Testing

### 4.1 Test conditions

Carry out the tests at standard atmosphere 23/50 according to ISO 554 with ordinary tolerances.

## 4.2 Test bindings

Take commercial ski-bindings and boots for the tests.

If no obvious influence on the release values can be expected from the boots, a variable length sole according to ISO 9838 can be used.

Conduct the tests on a group of at least six bindings and the boots by the tests specified by the manufacturer of the test device.

Match appropriate bindings to each boot sole and mount according to skis (or simulated skis) in accordance with the binding manufacturer's instructions.

## 4.3 Setting of test bindings

The release indicator values ( $Z$ ) and sole lengths ( $L$ ) shall be as given in [Table 1](#).

**Table 1 — Release indicator values and sole lengths**

Sole	$L$ mm	$Z$
Type C	260	1
	260	1,5
Type A	300	3
	300	10
	340	4
	340	8

These settings and sole lengths shall remain unchanged throughout the test series.

## 4.4 Procedure

Carry out the measurement of the release values for each binding and setting as follows:

- a) On the reference device;
  - Torsion release: 7 measurements for right-hand release and 7 measurements for left-hand release.
  - Forward release: 7 measurements.
- b) On the test device;

After this, measure the release level of the binding with the device to be tested (7 measurements for each direction of release).

- c) On the reference device.

Finally, repeat the initial measurements on the reference device (7 measurements for each direction of release).

Test results should not be visible to the operator during a test series. If a recording device is not used, another person should observe and record each test result.

All releases shall be complete so that the binding has to be relocked and closed before each test.

Test results may be rejected if a procedural error is detected during a test.

For evaluation, delete the highest and lowest test in each series.

Calculate the mean ( $\bar{X}$ ) and standard deviation ( $s$ ) of each series of 5 test device results and 10 reference device results by the method below. Determine the difference  $d$  (as a percentage) and  $D$  (in Nm) and reproducibility limit ( $r$ ) for each test device with respect to the reference device and compare with the limits specified in 3.2.1 and 3.2.2.

Standard deviation:

$$s = \frac{0,43R}{\bar{X}} \cdot 100\% \quad (1)$$

where

$\bar{X}$  is the mean;

$R$  is the range of the measurements.

Difference:

$$d = \frac{\bar{X}_{td} - \bar{X}_{rd}}{\bar{X}_{rd}} \cdot 100\% \quad (2)$$

$$D = \bar{X}_{td} - \bar{X}_{rd} \quad (3)$$

where

$\bar{X}_{td}$  is the mean for test device;

$\bar{X}_{rd}$  is the mean for reference device.

Reproducibility limit:

$$r = \sqrt{s_{td}^2 - s_{rd}^2} \quad (4)$$

If  $s_{rd} > s_{td}$  then  $r = 0$

where

$s_{td}$  is the standard deviation for test device;

$s_{rd}$  is the standard deviation for reference device.

#### 4.5 Reference measurements with reference device

The measurement error of the release value in torsion shall be smaller than  $\pm 1\%$  for values above 50 Nm inclusive and  $\pm 0,5$  Nm for values below 50 Nm.

The measurement error of the release value in forward bending shall be smaller than  $\pm 1\%$  for values above 100 Nm inclusive and  $\pm 2$  Nm for values below 100 Nm.

The test equipment shall be designed to allow application of pure moments without any extraneous forces during the entire release process.

The reference measurements shall also be made with torques even for the evaluation of devices applying release forces.

## 5 Instructions for use and maintenance

Detailed, easily understandable instructions for use shall be provided with the test device.

The instructions for use and the relevant supplementary sheets shall indicate those bindings which cannot be adjusted without correction of the values directly read from the measuring instruments (see 4.2). The procedure (e.g. the application of correction tables) shall be explained in these cases.

The manufacturer shall indicate which binding systems cannot be adjusted by means of the test device.

The instructions for use shall contain simple methods and intervals which make it possible for the service staff to carry out pre-season and random tests for correct functioning and accuracy of measurement (e.g. by means of a calibration binding and a test sole).

Furthermore, the periods shall be given within which the test device is to be calibrated, and the procedure required by the manufacturer of a firm or institution commissioned by the manufacturer. The maximum interval is 2 years.

## 6 Test report

A test report for the description and documentary proof of all calibration processes shall be provided together with the test device. This test report shall include the following information:

- a) reference to this International Standard, i.e. ISO 11110;
- b) equipment number;
- c) date of construction;
- d) basic method (tibia and/or weight) and software version;
- e) acceptance date and values of first calibration;
- f) date of delivery;
- g) location of the device (address);
- h) calibration values obtained at the specific service interval;
- i) field for indication of
  - date,
  - kind of test,
  - result, and
  - symbol (signature).

In addition, the instructions for use shall deal with the maintenance of the equipment (temperature, humidity, calibration, inspection).

Attention shall be drawn to the necessity that release shall take place for both  $+M_Z$  and  $-M_Z$ .

## 7 Marking

Setting test devices according to International Standard shall be marked with the name or trademark of the manufacturer or importer.

The manufacturer may indicate on his own responsibility that the test devices comply with this International Standard by adding "ISO 11110".