
**Plastics piping systems for renovation
of underground non-pressure drainage
and sewerage networks —**

**Part 1:
General**

*Systèmes de canalisations en matières plastiques pour la rénovation
des réseaux d'assainissement gravitaires enterrés —*

Partie 1: Généralités

STANDARDSISO.COM : Click to view the full PDF of ISO 11296-1:2009



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 11296-1:2009



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General terms	1
3.2 Techniques	3
3.3 Characteristics	4
3.4 Origin of materials	5
3.5 Product stages	6
4 Symbols and abbreviated terms	6
4.1 Symbols	6
4.2 Abbreviated terms	6
5 Pipes at the “M” stage	7
5.1 Materials	7
5.2 General characteristics	7
5.3 Material characteristics	7
5.4 Geometric characteristics	7
5.5 Mechanical characteristics	7
5.6 Physical characteristics	7
5.7 Jointing	7
5.8 Marking	7
6 Fittings at the “M” stage	8
6.1 Materials	8
6.2 General characteristics	8
6.3 Material characteristics	8
6.4 Geometric characteristics	8
6.5 Mechanical characteristics	8
6.6 Physical characteristics	8
6.7 Jointing	8
6.8 Marking	8
7 Ancillary components	9
8 Fitness for purpose of the installed lining system at the “I” stage	9
8.1 Materials	9
8.2 General characteristics	9
8.3 Material characteristics	9
8.4 Geometric characteristics	9
8.5 Mechanical characteristics	10
8.6 Physical characteristics	10
8.7 Additional characteristics	10
8.8 Sampling	10
9 Installation practice	10
9.1 Preparatory work	10
9.2 Storage, handling and transport of pipe and fittings	10
9.3 Equipment	10
9.4 Installation	11
9.5 Process-related inspection and testing	12

9.6	Lining termination.....	12
9.7	Reconnection to existing manholes and laterals	12
9.8	Final inspection and testing	12
9.9	Documentation.....	12
	Bibliography	13

STANDARDSISO.COM : Click to view the full PDF of ISO 11296-1:2009

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11296-1 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*.

ISO 11296 consists of the following parts, under the general title *Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks*:

- *Part 1: General*
- *Part 3: Lining with close-fit pipes*
- *Part 4: Lining with cured-in-place pipes*

Lining with continuous pipes is to form the subject of a part 2, lining with discrete pipes is to form the subject of a part 5 and lining with spirally-wound pipes is to form the subject of a part 7.

Introduction

The System Standard, of which this is part 1, specifies the requirements for plastics piping systems of various materials used for the renovation of existing pipelines in a specified application area. System Standards for renovation specify procedures for the following applications:

- plastics piping systems for renovation of underground non-pressure drainage and sewerage networks;
- plastics piping systems for renovation of underground drainage and sewerage networks under pressure;
- plastics piping systems for renovation of underground water supply networks;
- plastics piping systems for renovation of underground gas supply networks.

These System Standards are distinguished from those for conventionally installed plastics piping systems because they set requirements for certain characteristics in the as-installed condition, after site processing. This is in addition to specifying requirements for system components, as manufactured.

Each of the System Standards comprises a part 1 (general) and all applicable renovation technique family-related parts from the following:

- part 2: lining with continuous pipes;
- part 3: lining with close-fit pipes;
- part 4: lining with cured-in-place pipes;
- part 5: lining with discrete pipes;
- part 7: lining with spirally-wound pipes.

The requirements for any given renovation technique family are given in part 1, applied in conjunction with the other relevant part. For example, parts 1 and 2 specify the requirements relating to lining with continuous pipes. For complementary information, see ISO 11295. Not all technique families are applicable to every area of application and this is reflected in the part numbers included in each System Standard.

A consistent structure of clause headings has been adopted for all parts to facilitate direct comparisons across renovation technique families.

Figure 1 gives the common structure and the relationship between ISO 11296 and the System Standards for other application areas.




Figure 1 — Format of the renovation System Standards

STANDARDSISO.COM : Click to view the full PDF of ISO 11296-1:2009

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks —

Part 1: General

1 Scope

This part of ISO 11296 specifies the requirements and test methods for plastics piping systems intended to be used for the renovation of underground non-pressure drainage and sewerage networks, which are operated as gravity systems and subjected to a maximum surcharge pressure of 0,5 bar¹⁾. It is applicable to pipes and fittings as manufactured, as well as to the installed plastics lining system; it is not applicable to the existing pipeline or any annular filler.

This part of ISO 11296 establishes the general requirements common to all relevant renovation techniques (see 3.1.2).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1610:1997, *Construction and testing of drains and sewers*

EN 13508-2, *Conditions of drain and sewer systems outside buildings — Part 2: Visual inspection coding system*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 General terms

3.1.1

pipeline system

interconnecting pipe network for the conveyance of fluids

3.1.2

rehabilitation

all measures for restoring or upgrading the performance of an existing pipeline system

1) 1 bar = 0,1 MPa = 0,1 N/mm² = 10⁵ N/m².

3.1.3

renovation

work incorporating all or part of the original fabric of the pipeline by means of which its performance is improved

3.1.4

replacement

rehabilitation of an existing pipeline system by the installation of a new pipeline system, without incorporating the original fabric

3.1.5

maintenance

keeping an existing pipeline system operational without the installation of additional fabric

3.1.6

repair

rectification of local damage

3.1.7

lining pipe

pipe inserted for renovation purposes

3.1.8

liner

lining pipe after installation

3.1.9

lining system

lining pipe and all relevant fittings for insertion into an existing pipeline for the purposes of renovation

3.1.10

renovated pipeline system

existing pipeline system plus the installed lining system used to renovate it, along with any grout or other annular filling material used

3.1.11

characteristic

property, dimension or other feature of a material or component

3.1.12

declared value

limiting value of a characteristic declared in advance by the lining system supplier, which becomes the requirement for the purposes of assessment of conformity

3.1.13

annular filler

material for grouting annular space between existing pipeline and the lining system

3.1.14

grouting

process of filling voids around the lining system

3.1.15

simulated installation

installation of a lining system into a simulated host pipeline, using representative equipment and processes, in order to provide samples for testing which are representative of an actual installation

3.1.16**simulated host pipeline**

section of pipeline, which is not part of an operational network, but which replicates the environment of an operational network

3.1.17**technique family**

group of renovation techniques which are considered to have common characteristics for standardization purposes

3.2 Techniques

The various techniques for renovation of underground non-pressure drainage and sewerage networks, within the scope of pipeline rehabilitation techniques generally, are shown schematically in Figure 2. For definitions of standardized renovation techniques given in Figure 2, but outside the scope of this part of ISO 11296, see ISO 11295.

This part of ISO 11296 is applicable to the following technique families.

3.2.1**lining with continuous pipes**

lining with pipe made continuous prior to insertion, and which has not been shaped to give it a cross-sectional diameter smaller than its final diameter after installation

3.2.2**lining with close-fit pipes**

lining with a continuous pipe for which the cross-section is reduced to facilitate installation and reverted after installation to provide a close fit to the existing pipe

NOTE There are two options for achieving the reduction in cross-section:

- a) reduction in the pipe manufacturing plant; the pipe is usually supplied coiled on a reel from which it is directly inserted;
- b) reduction on site; the pipe is usually fed through the reduction equipment and simultaneously inserted in one continuous string.

3.2.3**lining with cured-in-place pipes**


lining with a flexible tube impregnated with a thermosetting resin, which produces a pipe after resin cure

3.2.4**lining with discrete pipes**

lining with pipes shorter than the section to be renovated, which are jointed to form a continuous pipe only during insertion, the cross-section of the lining pipe remaining unchanged

3.2.5**lining with spirally-wound pipes**

lining with a profiled strip, spirally wound to form a continuous pipe after installation



^a This part of ISO 11296 applies.

Figure 2 — Technique families for renovation of underground non-pressure drainage and sewerage networks using plastics pipes, within the scope of pipeline rehabilitation techniques

3.3 Characteristics

3.3.1

nominal size

numerical designation of the size of a component, which is a convenient round number approximately equal to the manufacturing dimension in millimetres

3.3.2

nominal size

DN/OD

nominal size, related to the outside diameter

NOTE This is expressed in millimetres.

3.3.3

nominal outside diameter

d_n

specified outside diameter assigned to a nominal size DN/OD

NOTE 1 The nominal outside diameter is the minimum mean outside diameter, $d_{em, min}$ (see 3.3.5).

NOTE 2 This is expressed in millimetres.

3.3.4**mean outside diameter** d_{em}

value of the measurement of the outer circumference of a pipe or spigot end of a fitting in any cross-section, divided by π ($\approx 3,142$), and rounded to the next greater 0,1 mm

3.3.5**minimum mean outside diameter** $d_{em,min}$

minimum value of the mean outside diameter as specified for a given nominal size

3.3.6**wall thickness** e

value of the measurement of the wall thickness at any point around the circumference of a component

3.3.7**mean wall thickness** e_m

arithmetic mean of a number of measurements of the wall thickness regularly spaced around the circumference and in the same cross-section of a component

3.3.8**minimum wall thickness at any point** e_{min}

minimum value of the wall thickness at any point around the circumference of a component, as specified

3.3.9**nominal wall thickness** e_n

numerical designation of the wall thickness of a component, which is a convenient round number, approximately equal to the manufacturing dimension in millimetres

NOTE For thermoplastics solid-wall components the value of nominal wall thickness, e_n , is identical to the specified minimum wall thickness at any point, e_{min} .

3.3.10**standard dimension ratio****SDR**

ratio of the nominal outside diameter, d_n , to its nominal wall thickness, e_n

3.3.11**ring stiffness**

resistance of a pipe to diametric deflection in response to external loading applied along one longitudinal diametric plane

NOTE This definition applies to both short-term and long-term values.

3.4 Origin of materials**3.4.1****virgin material**

material in a form such as granules, powder or liquid, which has not been subjected to use or processing other than required for its manufacture and to which no reprocessible or recyclable material has been added

3.4.2**own reprocessible material**

material prepared from unused pipes and fittings, including trimmings from the production of pipes and fittings, which will be reprocessed in a manufacturer's plant after having previously been processed by the same manufacturer by a process such as moulding or extrusion and for which the complete formulation is known

3.4.3

external reprocessable material

material from unused products or trimmings which will be reprocessed and which were originally processed by another manufacturer

NOTE If a manufacturer has a production of products other than pipes and fittings, reprocessable material from that production is considered as external reprocessable material when used for pipes or fittings production.

3.4.4

recyclable material

material prepared from used products which have been cleaned and crushed or ground

3.5 Product stages

The characteristics of components used for renovation and the materials from which they are made can be considered at the following two distinct stages.

3.5.1

“M” stage

stage as manufactured, i.e. before any subsequent site processing of components associated with the particular renovation technique

NOTE For pipes and fittings at the “M” stage, see Clauses 5 and 6, respectively.

3.5.2

“I” stage

stage as installed, i.e. in final configuration after any site processing of components associated with the particular renovation technique

See Clause 8.

4 Symbols and abbreviated terms

4.1 Symbols

d_{em}	mean outside diameter
$d_{em,min}$	minimum mean outside diameter
d_n	nominal outside diameter
e	wall thickness
e_m	mean wall thickness
e_{min}	minimum wall thickness at any point
e_n	nominal wall thickness

4.2 Abbreviated terms

DN/OD	nominal size, related to the outside diameter
“I”	as installed
“M”	as manufactured
SDR	standard dimension ratio

5 Pipes at the “M” stage

NOTE For pipes at the “I” stage, see Clause 8.

5.1 Materials

No general requirements regarding choice of material apply.

5.2 General characteristics

No general requirements apply.

The choice of colour should follow national identification requirements. Colours used nationally for gas and/or water supply pipes should not be used for sewers within that nation and vice versa.

5.3 Material characteristics

No general material requirements apply.

5.4 Geometric characteristics

No general geometric requirements apply.

5.5 Mechanical characteristics

No general mechanical requirements apply.

5.6 Physical characteristics

No general physical requirements apply.

5.7 Jointing

For the requirements of the jointing techniques used to attach and/or assemble components, the part of ISO 11296 relevant to each technique family applies.

NOTE Integral joints are considered as part of the pipe.

5.8 Marking

Pipes specified in detail in other parts of ISO 11296 shall be permanently and legibly marked in such a way that the marking does not initiate cracks or other types of premature failure and that storage, weathering, handling and installation (see Clause 9) do not affect the legibility of the marking.

These pipes shall be marked with at least the following information:

- a) a reference to this part of ISO 11296, i.e. ISO 11296-1:2009;
- b) the manufacturer's name and/or trademark;
- c) the nominal size or other dimension (e.g. d_n);
- d) the SDR or wall thickness or ring stiffness, as applicable;
- e) the material;

- f) the manufacturer's information in clear figures or in code, providing traceability to production period (specified by at least the year and the month), and the production site if the manufacturer is producing at several sites;
- g) the approval mark, if applicable.

6 Fittings at the "M" stage

NOTE For fittings at the "I" stage, see Clause 8.

6.1 Materials

No general requirements regarding choice of material apply.

6.2 General characteristics

No general requirements apply.

The choice of colour should follow national identification requirements. Colours used nationally for gas and/or water supply pipes should not be used for sewers within that nation and vice versa.

6.3 Material characteristics

No general material requirements apply.

6.4 Geometric characteristics

No general geometric requirements apply.

6.5 Mechanical characteristics

No general mechanical requirements apply.

6.6 Physical characteristics

No general physical requirements apply.

6.7 Jointing

For the requirements of the jointing techniques used to attach and/or assemble components, the part of ISO 11296 relevant to each technique family applies.

NOTE Integral joints are considered as part of the fitting.

6.8 Marking

If fittings are specified by normative reference to another plastics piping System Standard, no marking additional to that specified in the referenced standard shall be required.

Fittings specified in detail in other parts of ISO 11296 shall be marked with at least the following information:

- a) a reference to this part of ISO 11296, i.e. ISO 11296-1:2009;
- b) the manufacturer's name and/or trademark;

- c) the nominal size or other dimension (e.g. d_n);
- d) the SDR or wall thickness or ring stiffness, as applicable;
- e) the material;
- f) the manufacturer's information in clear figures or in code, providing traceability to production period (specified by at least the year and the month), and the production site if the manufacturer is producing at several sites;
- g) the approval mark, if applicable.

7 Ancillary components

This part of ISO 11296 is not applicable to any ancillary components.

8 Fitness for purpose of the installed lining system at the "I" stage

NOTE For pipes and fittings at the "M" stage, see Clauses 5 and 6, respectively.

8.1 Materials

The pipes and fittings may be made of different materials, provided these conform to ISO 11296-3:2009, 5.1 and Clause 6, and ISO 11296-4:2009, 5.1 and 6.1, respectively.

8.2 General characteristics

The installed lining system shall conform to the leaktightness requirements of EN 1610:1997, Clause 13.

This part of ISO 11296 is not applicable to any requirements for chemical, abrasion and jetting resistance.

IMPORTANT — Attention is drawn to the need for care in respect of the potential for any residues of materials, lubricants or other chemical agents from the installation process to damage the surrounding environment.

8.3 Material characteristics

No general material requirements apply.

8.4 Geometric characteristics

The installed lining system shall have a minimum free bore in accordance with the design requirements (e.g. flow capacity, structural stability and routine maintenance).

NOTE 1 Free bore has two aspects. The first (cross-sectional) free bore is to ensure that adequate cross-section is retained for flow capacity and structural stability. The second (dimensional) free bore is to ensure that adequate width and height are retained for routine maintenance equipment to be used, or for access to be maintained in the installed pipeline system.

NOTE 2 The maximum free bore of a renovated pipeline system is limited by the internal dimensions of the existing pipeline at the time of lining and also by the wall thickness and closeness of fit of the installed pipeline system, which will generally vary according to the renovation technique used. For guidance on design aspects, see ISO 11295.