
**Motorcycles — Methods for setting
running resistance on a chassis
dynamometer**

*Motorcycles — Méthodes pour fixer la résistance à l'avancement sur un
banc dynamométrique*

STANDARDSISO.COM : Click to view the full PDF of ISO 11486:2006



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 11486:2006

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols	2
5 Test motorcycle, chassis dynamometer and instruments	3
6 Required accuracy of measurements.....	4
7 Road test.....	4
7.1 Requirement for road	4
7.2 Ambient conditions for the road test.....	4
7.3 Reference speed	5
7.4 Specified speed.....	5
7.5 Coastdown starting speed.....	5
7.6 Coastdown time measurement beginning speed and ending speed	5
7.7 Preparation of test motorcycle.....	5
7.8 Rider and riding position	6
7.9 Measurement of coastdown time.....	6
8 Data processing	8
8.1 Calculation of running resistance force	8
8.2 Running resistance curve fitting	8
8.3 Target running resistance force for chassis dynamometer setting	8
9 Chassis dynamometer setting derived from on-road coastdown measurements.....	8
9.1 Requirements for the equipment	8
9.2 Inertia mass setting	9
9.3 Warming up of chassis dynamometer.....	9
9.4 Adjustment of tyre pressures.....	9
9.5 Motorcycle warming up.....	9
9.6 Procedures for setting chassis dynamometer	9
9.7 Verification of chassis dynamometer	12
10 Chassis dynamometer setting using the running resistance table.....	12
10.1 Applicability.....	12
10.2 Requirements for the equipment	12
10.3 Setting the running resistance force on the chassis dynamometer	14
10.4 The specified speed for the chassis dynamometer	14
10.5 Verification of chassis dynamometer	14
Annex A (normative) Motorcycle description.....	15
Annex B (normative) Chassis dynamometer and instruments description.....	17
Annex C (informative) Record of coastdown time and chassis dynamometer setting.....	19
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11486 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 22, *Motorcycles*.

This second edition cancels and replaces the first edition (ISO 11486:1993), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 11486:2006

Introduction

While ISO 11486:1993 gave only a running resistance setting method by coastdown method for the purpose of fuel consumption measurement, this edition of ISO 11486 has been prepared with the aim of establishing the general setting method that is usable for both exhaust emission testing and fuel consumption testing covering high-speed range driving.

In addition to the coastdown method, the table method is introduced in this edition of ISO 11486. In the coastdown method, the running resistance of each motorcycle is measured individually on the road, and the measured running resistance is reproduced on a chassis dynamometer. The table method is a simple setting method, where the running resistance value of the motorcycle is determined only with its equivalent inertia mass.

When this International Standard is applied to the exhaust emission test or the fuel consumption test, it is essential to follow the requirements specified in those test methods.

STANDARDSISO.COM : Click to view the full PDF of ISO 11486:2006

Motorcycles — Methods for setting running resistance on a chassis dynamometer

1 Scope

This International Standard specifies the measurement method for determining the motorcycle running resistance on the road, and two methods of setting the chassis dynamometer with the motorcycle running resistance. It is applicable to motorcycles as defined in ISO 3833.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO 7117, *Motorcycles — Measurement of maximum speed*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 running resistance

F

total force resistant to a running motorcycle which, when measured by the coastdown method, includes the friction forces in the drive-train

3.2 reference speed

v_0

motorcycle speed at which the running resistance of the motorcycle is calculated and then used for setting the chassis dynamometer

3.3 specified speed

v

motorcycle speed at which the running resistance on the road is measured to determine the running resistance curve

3.4 motorcycle kerb mass

m_k

motorcycle dry mass to which is added the mass of the following:

— fuel: tank filled at least to 90 % of the capacity specified by the manufacturer;

- oils and coolant: filled as specified by the manufacturer;
- auxiliary equipment usually supplied by the manufacturer in addition to that necessary for normal operation [tool-kit, carrier(s), windscreen(s), protective equipment, etc.]

3.5 motorcycle reference mass

m_{ref}
kerb mass of the motorcycle increased by a uniform figure of 75 kg, which represents the mass of a rider

4 Symbols

For the purposes of this document, the symbols in Table 1 apply.

Table 1 — Symbols

Symbol	Definition	Unit
a	The coefficient of polygonal function	—
b	The coefficient of polygonal function	—
c	The coefficient of polygonal function	—
a_T	The rolling resistance force of front wheel	N
b_T	The coefficient of aerodynamic	N/(km/h) ²
d_T	The relative air density under test conditions	—
d_0	The standard ambient relative air density	—
F	The running resistance force	N
F_E	The set running resistance force on the chassis dynamometer	N
$F_E(v_0)$	The set running resistance force at the reference speed on the chassis dynamometer	N
$F_E(v_i)$	The set running resistance force at the specified speed on the chassis dynamometer	N
F_f	The total friction loss	N
$F_f(v_0)$	The total friction loss at the reference speed	N
F_j	The running resistance force	N
$F_j(v_0)$	The running resistance force at the reference speed	N
F_{pau}	The braking force of the power absorbing unit	N
$F_{pau}(v_j)$	The braking force of the power absorbing unit at the specified speed	N
$F_{pau}(v_0)$	The braking force of the power absorbing unit at the reference speed	N
F_T	The running resistance force obtained from the running resistance table	N
F^*	The target running resistance force	N
F_j^*	The target running resistance force at the specified speed	N
$F^*(v_0)$	The target running resistance force at the reference speed on the chassis dynamometer	N
$F^*(v_i)$	The target running resistance force at the specified speed on the chassis dynamometer	N
f_0	The rolling resistance	N
f_0^*	The corrected rolling resistance in the standard ambient conditions	N
f_2	The coefficient of aerodynamic drag	N/(km/h) ²
f_2^*	The corrected coefficient of aerodynamic drag in the standard ambient conditions	N/(km/h) ²

Table 1 (continued)

Symbol	Definition	Unit
K_0	The temperature correction factor for rolling resistance	—
m	The test motorcycle mass	kg
m_a	The actual mass of the test motorcycle	kg
m_i	The equivalent inertia mass	kg
m_{fi}	The flywheel equivalent inertia mass	kg
m_k	The motorcycle kerb mass	kg
m_r	The equivalent inertia mass of all the wheels	kg
m_{ref}	The motorcycle reference mass	kg
m_{rid}	The rider mass	kg
m_{ff}	The rotating mass of the front wheel	kg
m_{r1}	The equivalent inertia mass of the rear wheel and the motorcycle parts rotating with the wheel	kg
p_0	The standard ambient pressure	kPa
p_T	The mean ambient pressure during the test	kPa
T_T	The mean ambient temperature during the test	K
T_0	The standard ambient temperature	K
v	The specified speed	km/h
v_j	The specified speeds which are selected for coastdown time measurement	km/h
v_0	The reference speed	km/h
v_1	The speed at which the measurement of the coastdown time begins	km/h
v_2	The speed at which the measurement of the coastdown time ends	km/h
ΔT_E	The corrected coastdown time at the inertia mass ($m_i + m_{r1}$)	s
ΔT_i	The average coastdown time at the specified speed	s
ΔT_j	The average coastdown time of the two tests	s
ΔT_{road}	The target coastdown time	s
Δt	The coastdown time	s
$\overline{\Delta t}$	The mean coastdown time on the chassis dynamometer without absorption	s
Δt_E	The mean coastdown time on the chassis dynamometer at the reference speed	s
Δt_{ai}	The coastdown time measured during the first road test	s
Δt_{bi}	The coastdown time measured during the second road test	s
Δt_i	The coastdown time corresponding to the reference speed	s
Δv	The coastdown speed interval ($2\Delta v = v_1 - v_2$)	km/h
ε	The chassis dynamometer setting error	—
ρ_0	The standard relative ambient air volumetric mass	kg/m ³

5 Test motorcycle, chassis dynamometer and instruments

A full description of the motorcycle shall be provided in accordance with Annex A.

A full description of the chassis dynamometer and instruments shall be provided in accordance with Annex B.

6 Required accuracy of measurements

Measurements shall be made to the accuracies as specified in Table 2.

Table 2 — Required accuracy of measurements

Parameter	At measured value	Resolution
a) Running resistance force, F	+2 %	—
b) Motorcycle speed (v_1, v_2)	± 1 %	0,45 km/h
c) Coastdown speed interval [$2\Delta v = v_1 - v_2$]	± 1 %	0,10 km/h
d) Coastdown time (Δt)	$\pm 0,5$ %	0,01 s
e) Total motorcycle mass [$m_k + m_{rid}$]	$\pm 1,0$ %	1,4 kg
f) Wind speed	± 10 %	0,1 m/s
g) Wind direction	—	5 deg.
h) Ambient temperature	—	2 K
i) Barometric pressure	—	0,2 kPa

7 Road test

7.1 Requirement for road

The test road shall be flat, level, straight and smoothly paved. The road surface shall be dry and free of obstacles or wind barriers that might impede the measurement of the running resistance. The slope of the surface shall not exceed 0,5 % between any two points at least 2 m apart.

7.2 Ambient conditions for the road test

During data collecting periods, the wind shall be steady. The wind speed and the direction of the wind shall be measured continuously or with adequate frequency at a location where the wind force during coastdown is representative.

The ambient conditions shall be within the following limits:

- maximum wind speed: 3 m/s;
- maximum wind speed for gusts: 5 m/s;
- average wind speed, parallel: 3 m/s;
- average wind speed, perpendicular: 2 m/s;
- maximum relative humidity: 95 %;
- air temperature: 278 K to 308 K.

Standard ambient conditions shall be as follows:

- pressure, p_0 : 100 kPa;
- temperature, T_0 : 293 K;

- relative air density, d_T : 0,9197;
- air volumetric mass, ρ_0 : 1,189 kg/m³.

The relative air density when the motorcycle is tested, calculated in accordance with the formula below, shall not differ by more than 7,5 % from the air density under the standard conditions.

The relative air density, d_T , shall be calculated by the following formula:

$$d_T = d_0 \times \frac{p_T}{p_0} \times \frac{T_0}{T_T} \quad (1)$$

7.3 Reference speed

The reference speed or speeds shall be as defined in the test cycle.

7.4 Specified speed

The specified speed, v , is required to prepare the running resistance curve. To determine the running resistance as a function of motorcycle speed in the vicinity of the reference speed, v_0 , running resistances shall be measured using at least four specified speeds, including the reference speed(s). The range of specified speed points (the interval between the maximum and minimum points) shall extend either side of the reference speed or the reference speed range, if there is more than one reference speed, by at least Δv , as defined in 7.6. The specified speed points, including the reference speed point(s), shall be no greater than 20 km/h apart and the interval of specified speeds should be the same. From the running resistance curve, the running resistance at the reference speed(s) can be calculated.

7.5 Coastdown starting speed

The coastdown starting speed shall be more than 5 km/h above the highest speed at which coastdown time measurement begins, since sufficient time is required, for example to settle the positions of both the motorcycle and rider and to cut the transmitted engine power off before the speed is reduced to v_1 , the speed at which the measurement of the coastdown time is started.

7.6 Coastdown time measurement beginning speed and ending speed

To ensure accuracy in measuring the coastdown time, Δt , and coastdown speed interval, $2\Delta v$, the beginning speed, v_1 , and ending speed, v_2 , in kilometres per hour, the following requirements shall be met:

$$v_1 = v + \Delta v \quad (2)$$

$$v_2 = v - \Delta v \quad (3)$$

Δv shall be 5 km/h when v is less than 60 km/h, and shall be 10 km/h when v is 60 km/h or more.

7.7 Preparation of test motorcycle

7.7.1 The motorcycle shall conform in all its components with the production series, or, if the motorcycle is different from the production series, a full description shall be given in the test report.

7.7.2 The engine, transmission and motorcycle shall be properly run in, in accordance with the manufacturer's requirements.

7.7.3 The motorcycle shall be adjusted in accordance with the manufacturer's requirements, e.g. the viscosity of the oils, tyre pressures, or, if the motorcycle is different from the production series, a full description shall be given in the test report.

7.7.4 The kerb mass of the motorcycle shall be as defined in 3.4.

7.7.5 The total test mass, including the masses of the rider and the instruments, shall be measured before the beginning of the test.

7.7.6 The distribution of the load between the wheels shall be in conformity with the manufacturer's instructions.

7.7.7 When installing the measuring instruments on the test motorcycle, care shall be taken to minimize their effects on the distribution of the load between the wheels. When installing the speed sensor outside the motorcycle, care shall be taken to minimize the additional aerodynamic loss.

7.8 Rider and riding position

7.8.1 The rider shall wear a close-fitting suit (one-piece) or similar clothing, a protective helmet, eye protection, boots and gloves.

7.8.2 The rider in the conditions given in 7.8.1 shall have a mass of $75 \text{ kg} \pm 5 \text{ kg}$ and be $1,75 \text{ m} \pm 0,05 \text{ m}$ tall.

7.8.3 The rider shall be seated on the seat provided, with his feet on the footrests and his arms normally extended. This position shall allow the rider at all times to have proper control of the motorcycle during the coastdown test.

The position of the rider shall remain unchanged during the whole measurement period.

7.9 Measurement of coastdown time

7.9.1 After a warm-up period, the motorcycle shall be accelerated to the coastdown starting speed, at which point the coastdown measurement procedure shall be started.

7.9.2 Since it can be dangerous and difficult from the viewpoint of its construction to have the transmission shifted to neutral, the coasting may be performed solely with the clutch disengaged. For those motorcycles that have no way of cutting the transmitted engine power off prior to coasting, the motorcycle may be towed until it reaches the coastdown starting speed. When the coastdown test is reproduced on the chassis dynamometer, the transmission and clutch shall be in the same condition as during the road test.

7.9.3 The motorcycle steering shall be altered as little as possible and the brakes shall not be operated until the end of the coastdown measurement period.

7.9.4 The first coastdown time, Δt_{ai} , corresponding to the specified speed, v_j , shall be measured as the elapsed time from the motorcycle speed $v_j + \Delta v$ to $v_j - \Delta v$.

7.9.5 The procedure from 7.9.1 to 7.9.4 shall be repeated in the opposite direction to measure the second coastdown time, Δt_{bi} .

7.9.6 The average ΔT_i of the two coastdown times Δt_{ai} and Δt_{bi} shall be calculated by the following equation:

$$\Delta T_i = \frac{\Delta t_{ai} + \Delta t_{bi}}{2} \quad (4)$$

7.9.7 At least four tests shall be performed and the average coastdown time, ΔT_j , calculated by the following equation:

$$\Delta T_j = \frac{1}{n} \sum_{i=1}^n \Delta T_i \quad (5)$$

Tests shall be performed until the statistical accuracy, P , is equal to or less than 3 % ($P \leq 3 \%$).

The statistical accuracy, P , as a percentage, is calculated by the following equation:

$$P = \frac{t s}{\sqrt{n}} \times \frac{100}{\Delta T_j} \quad (6)$$

where

t is the coefficient given in Table 3;

s is the standard deviation given by the following formula:

$$s = \sqrt{\frac{\sum_{i=1}^n (\Delta T_i - \Delta T_j)^2}{n-1}} \quad (7)$$

n is the number of tests.

Table 3 — The coefficient for the statistical accuracy

n	t	$\frac{t}{\sqrt{n}}$
4	3,2	1,60
5	2,8	1,25
6	2,6	1,06
7	2,5	0,94
8	2,4	0,85
9	2,3	0,77
10	2,3	0,73
11	2,2	0,66
12	2,2	0,64
13	2,2	0,61
14	2,2	0,59
15	2,2	0,57

7.9.8 In repeating the test, care shall be taken to start the coastdown after observing the same warm-up procedure and at the same coastdown starting speed.

7.9.9 The measurement of the coastdown times for multiple specified speeds may be made by a continuous coastdown. In this case, the coastdown shall be repeated after observing the same warm-up procedure and at the same coastdown starting speed.

7.9.10 The coastdown time shall be recorded. The example of the record form is given in C.1.

8 Data processing

8.1 Calculation of running resistance force

8.1.1 The running resistance force, F_j , in newtons, at the specified speed, v_j , shall be calculated by the following equation:

$$F_j = \frac{1}{3,6} \times (m + m_r) \times \frac{2\Delta v}{\Delta T_j} \quad (8)$$

m_r should be measured or calculated as appropriate. As an alternative, m_r may be estimated as 7 % of the unladen motorcycle mass.

8.1.2 The running resistance force, F_j , shall be corrected in accordance with 8.2.

8.2 Running resistance curve fitting

The running resistance force, F , shall be calculated as follows:

This following equation shall be fitted to the data set of F_j and v_j obtained above by linear regression to determine the coefficients f_0 and f_2 ,

$$F = f_0 + f_2 v^2 \quad (9)$$

The coefficients f_0 and f_2 determined shall be corrected to the standard ambient conditions by the following equations:

$$f_0^* = f_0 [1 + K_0 (T_T - T_0)] \quad (10)$$

$$f_2^* = f_2 \times \frac{T_T}{T_0} \times \frac{p_0}{p_T} \quad (11)$$

K_0 may be determined based on the empirical data for the particular motorcycle and tyre tests, or may be assumed as follows if the information is not available: $K_0 = 6 \times 10^{-3} K^{-1}$.

8.3 Target running resistance force for chassis dynamometer setting

The target running resistance force, $F^*(v_0)$, on the chassis dynamometer at the reference motorcycle speed, (v_0) , in newtons, is determined by the following equation:

$$F^*(v_0) = f_0^* + f_2^* \times v_0^2 \quad (12)$$

9 Chassis dynamometer setting derived from on-road coastdown measurements

9.1 Requirements for the equipment

9.1.1 The instrumentation for the speed and time measurement shall have the accuracies as specified in Clause 6.

9.1.2 The chassis dynamometer rollers shall be clean, dry and free from anything which might cause the tyre to slip.

9.2 Inertia mass setting

9.2.1 The equivalent inertia mass for the chassis dynamometer shall be the flywheel equivalent inertia mass, m_{fi} , closest to the actual mass of the motorcycle, m_a . The actual mass, m_a , is obtained by adding the rotating mass of the front wheel, m_{rf} , to the total mass of the motorcycle, rider and instruments measured during the road test. Alternatively, the equivalent inertia mass, m_i , can be derived from Table 4. The value of m_{rf} , in kilograms, may be measured or calculated as appropriate, or may be estimated as 3 % of m .

9.2.2 If the actual mass, m_a , cannot be equalized to the flywheel equivalent inertia mass, m_i , to make the target running resistance force, F^* , equal to the running resistance force, F_E (which is to be set to the chassis dynamometer), the corrected coastdown time, ΔT_E , may be adjusted in accordance with the total mass ratio of the target coastdown time, ΔT_{road} , in the following sequence:

$$\Delta T_{road} = \frac{1}{3,6} (m_a + m_{r1}) \frac{2\Delta v}{F^*} \quad (13)$$

$$\Delta T_E = \frac{1}{3,6} (m_i + m_{r1}) \frac{2\Delta v}{F_E} \quad (14)$$

$$F_E = F^* \quad (15)$$

$$\Delta T_E = \Delta T_{road} \times \frac{m_i + m_{r1}}{m_a + m_{r1}} \quad (16)$$

with $0,95 < \frac{m_i + m_{r1}}{m_a + m_{r1}} < 1,05$

m_{r1} may be measured or calculated, in kilograms, as appropriate. As an alternative, m_{r1} may be estimated as 4 % of m .

9.3 Warming up of chassis dynamometer

Before the test, the chassis dynamometer shall be appropriately warmed up to the stabilized frictional force, F_f .

9.4 Adjustment of tyre pressures

The tyre pressures shall be adjusted to the specifications of the manufacturer or to those at which the speed of the motorcycle during the road test and the motorcycle speed obtained on the chassis dynamometer are equal.

9.5 Motorcycle warming up

The test motorcycle shall be warmed up on the chassis dynamometer to the same condition as it was during the road test.

9.6 Procedures for setting chassis dynamometer

The load on the chassis dynamometer, F_E , is, in view of its construction, composed of the total friction loss, F_f , which is the sum of the chassis dynamometer rotating frictional resistance, the tyre rolling resistance, the frictional resistance of the rotating parts in the driving system of the motorcycle and the braking force of the power absorbing unit (pau), F_{pau} , as shown in the following equation:

$$F_E = F_f + F_{pau} \quad (17)$$

The target running resistance force, F^* , in 8.3 should be reproduced on the chassis dynamometer in accordance with the motorcycle speed. Namely:

$$F_E(v_i) = F^*(v_i) \quad (18)$$

9.6.1 Determination of total friction loss

The total friction loss, F_f , on the chassis dynamometer shall be measured by the method in 9.6.1.1 or 9.6.1.2.

9.6.1.1 Motoring by chassis dynamometer

This method applies only to chassis dynamometers capable of driving a motorcycle. The motorcycle shall be driven by the chassis dynamometer steadily at the reference speed, v_0 , with the transmission engaged and the clutch disengaged. The total friction loss, $F_f(v_0)$, at the reference speed, v_0 , is given by the chassis dynamometer force.

9.6.1.2 Coastdown without absorption

The method of measuring the coastdown time is the coastdown method for the measurement of the total friction loss, F_f .

The motorcycle coastdown shall be performed on the chassis dynamometer by the procedure described from 7.9.1 to 7.9.4 with zero chassis dynamometer absorption, and the coastdown time, Δt_i , corresponding to the reference speed, v_0 , shall be measured.

The measurement shall be carried out at least three times, and the mean coastdown time, $\overline{\Delta t}$, shall be calculated by the following equation:

$$\overline{\Delta t} = \frac{1}{n} \sum_{i=1}^n \Delta t_i \quad (19)$$

The total friction loss, $F_f(v_0)$, at the reference speed, v_0 , is calculated by the following equation:

$$F_f(v_0) = \frac{1}{3,6} (m_i + m_{r1}) \frac{2\Delta v}{\Delta t} \quad (20)$$

9.6.2 Calculation of power absorption unit force

The force, $F_{\text{pau}}(v_0)$, to be absorbed by the chassis dynamometer at the reference speed, v_0 , is calculated by subtracting, $F_f(v_0)$, from the target running resistance force, $F^*(v_0)$, as shown in the following equation:

$$F_{\text{pau}}(v_0) = F^*(v_0) - F_f(v_0) \quad (21)$$

9.6.3 Chassis dynamometer setting

According to its type, the chassis dynamometer shall be set by one of the methods described in 9.6.3.1 to 9.6.3.4.

9.6.3.1 Chassis dynamometer with polygonal function

In the case of a chassis dynamometer with polygonal function, in which the absorption characteristics are determined by load values at several speed points, at least three specified speeds, including the reference speed, shall be chosen as the setting points. At each setting point, the chassis dynamometer shall be set to the value, $F_{\text{pau}}(v_j)$, obtained in 9.6.2.

9.6.3.2 Chassis dynamometer with coefficient control

9.6.3.2.1 In the case of a chassis dynamometer with coefficient control, in which the absorption characteristics are determined by given coefficients of a polynomial function, the value of $F_{\text{pau}}(v_j)$ at each specified speed shall be calculated by the procedure in 9.6.1 and 9.6.2.

9.6.3.2.2 Assuming the load characteristics to be:

$$F_{\text{pau}}(v) = av^2 + bv + c \quad (22)$$

the coefficients a , b and c shall be determined by the polynomial regression method.

9.6.3.2.3 The chassis dynamometer shall be set to the coefficients a , b and c obtained in 9.6.3.2.2.

9.6.3.3 Chassis dynamometer with F^* polygonal digital setter

9.6.3.3.1 In the case of a chassis dynamometer with a polygonal digital setter, where a CPU is incorporated in the system, F^* is input directly, and Δt_i , F_f and F_{pau} are automatically measured and calculated to set the chassis dynamometer to the target running resistance force $F^* = f_0^* + f_2^*v^2$.

9.6.3.3.2 In this case, several points in succession are directly input digitally from the data set of F^*_j and v_j , the coastdown is performed and the coastdown time, Δt_i , is measured. After the coastdown test has been repeated several times, F_{pau} is automatically calculated and set at motorcycle speed intervals of 0,1 km/h, in the following sequence:

$$F^* + F_f = \frac{1}{3,6}(m_i + m_{r1}) \frac{2\Delta v}{\Delta t_i} \quad (23)$$

$$F_f = \frac{1}{3,6}(m_i + m_{r1}) \frac{2\Delta v}{\Delta t_i} - F^* \quad (24)$$

$$F_{\text{pau}} = F^* - F_f \quad (25)$$

9.6.3.4 Chassis dynamometer with f_0^*, f_2^* coefficient digital setter

9.6.3.4.1 In the case of a chassis dynamometer with a coefficient digital setter, where a CPU is incorporated in the system, the target running resistance force $F^* = f_0^* + f_2^*v^2$ is automatically set on the chassis dynamometer.

9.6.3.4.2 In this case, the coefficients f_0^* and f_2^* are directly input digitally, the coastdown is performed and the coastdown time, Δt_i , is measured. F_{pau} is automatically calculated and set at motorcycle speed intervals of 0,06 km/h, in the following sequence:

$$F^* + F_f = \frac{1}{3,6}(m_i + m_{r1}) \frac{2\Delta v}{\Delta t_i} \quad (26)$$

$$F_f = \frac{1}{3,6}(m_i + m_{r1}) \frac{2\Delta v}{\Delta t_i} - F^* \quad (27)$$

$$F_{\text{pau}} = F^* - F_f \quad (28)$$

9.7 Verification of chassis dynamometer

9.7.1 Immediately after the initial setting, the coastdown time, Δt_E , on the chassis dynamometer corresponding to the reference speed, v_0 , shall be measured by the same procedure as in 7.9.1 to 7.9.4.

The measurement shall be carried out at least three times, and the mean coastdown time, Δt_E , shall be calculated from the results.

9.7.2 The set running resistance force at the reference speed, $F_E(v_0)$, on the chassis dynamometer is calculated by the following equation:

$$F_E(v_0) = \frac{1}{3,6} (m_i + m_{r1}) \frac{2\Delta v}{\Delta t_E} \quad (29)$$

9.7.3 The setting error, ε , is calculated by the following equation:

$$\varepsilon = \frac{|F_E(v_0) - F^*(v_0)|}{F^*(v_0)} \times 100 \quad (30)$$

9.7.4 The chassis dynamometer shall be readjusted if the setting error does not satisfy the following criteria:

$\varepsilon \leq 2\%$ for $v_0 \geq 50$ km/h;

$\varepsilon \leq 3\%$ for 30 km/h $\leq v_0 < 50$ km/h;

$\varepsilon \leq 10\%$ for $v_0 < 30$ km/h.

9.7.5 The procedure in 9.7.1 to 9.7.3 shall be repeated until the setting error satisfies the criteria.

9.7.6 The chassis dynamometer setting and the observed errors shall be recorded. An example of the record form is given in C.2.

10 Chassis dynamometer setting using the running resistance table

10.1 Applicability

The chassis dynamometer can be set by the use of the running resistance table instead of the running resistance force obtained by the coastdown method. In this table method, the chassis dynamometer shall be set by the reference mass regardless of particular motorcycle characteristics.

Care should be taken for the application of this method to motorcycles having extraordinary characteristics.

10.2 Requirements for the equipment

10.2.1 The requirements for equipment shall be in accordance with 9.1.

10.2.2 The flywheel equivalent inertia mass, m_{fi} , shall be the equivalent inertia mass, m_i , specified in Table 4. The chassis dynamometer shall be set by the rolling resistance of front wheel, a , and the aero drag coefficient, b , specified in Table 4.

Table 4 — The classification of equivalent inertia mass and the running resistance

Reference mass, m_{ref} Kg	Equivalent inertia mass, m_i Kg	Rolling resistance of front wheel, a N	Aero drag coefficient, b N/(km/h) ²
95 < m_{ref} ≤ 105	100	8,8	0,0215
105 < m_{ref} ≤ 115	110	9,7	0,0217
115 < m_{ref} ≤ 125	120	10,6	0,0218
125 < m_{ref} ≤ 135	130	11,4	0,0220
135 < m_{ref} ≤ 145	140	12,3	0,0221
145 < m_{ref} ≤ 155	150	13,2	0,0223
155 < m_{ref} ≤ 165	160	14,1	0,0224
165 < m_{ref} ≤ 175	170	15,0	0,0226
175 < m_{ref} ≤ 185	180	15,8	0,0227
185 < m_{ref} ≤ 195	190	16,7	0,0229
195 < m_{ref} ≤ 205	200	17,6	0,0230
205 < m_{ref} ≤ 215	210	18,5	0,0232
215 < m_{ref} ≤ 225	220	19,4	0,0233
225 < m_{ref} ≤ 235	230	20,2	0,0235
235 < m_{ref} ≤ 245	240	21,1	0,0236
245 < m_{ref} ≤ 255	250	22,0	0,0238
255 < m_{ref} ≤ 265	260	22,9	0,0239
265 < m_{ref} ≤ 275	270	23,8	0,0241
275 < m_{ref} ≤ 285	280	24,6	0,0242
285 < m_{ref} ≤ 295	290	25,5	0,0244
295 < m_{ref} ≤ 305	300	26,4	0,0245
305 < m_{ref} ≤ 315	310	27,3	0,0247
315 < m_{ref} ≤ 325	320	28,2	0,0248
325 < m_{ref} ≤ 335	330	29,0	0,0250
335 < m_{ref} ≤ 345	340	29,9	0,0251
345 < m_{ref} ≤ 355	350	30,8	0,0253
355 < m_{ref} ≤ 365	360	31,7	0,0254
365 < m_{ref} ≤ 375	370	32,6	0,0256
375 < m_{ref} ≤ 385	380	33,4	0,0257
385 < m_{ref} ≤ 395	390	34,3	0,0259
395 < m_{ref} ≤ 405	400	35,2	0,0260
405 < m_{ref} ≤ 415	410	36,1	0,0262
415 < m_{ref} ≤ 425	420	37,0	0,0263
425 < m_{ref} ≤ 435	430	37,8	0,0265
435 < m_{ref} ≤ 445	440	38,7	0,0266
445 < m_{ref} ≤ 455	450	39,6	0,0268
455 < m_{ref} ≤ 465	460	40,5	0,0269
465 < m_{ref} ≤ 475	470	41,4	0,0271
475 < m_{ref} ≤ 485	480	42,2	0,0272
485 < m_{ref} ≤ 495	490	43,1	0,0274
495 < m_{ref} ≤ 505	500	44,0	0,0275
At every 10 kg	At every 10 kg	$a = 0,088m_i^a$	$b = 0,000015m_i + 0,0200^b$
^a The value shall be rounded to one decimal place.			
^b The value shall be rounded to four decimal places.			

10.3 Setting the running resistance force on the chassis dynamometer

The running resistance force on the chassis dynamometer, F_E , shall be determined from the following equation:

$$F_E = F_T = a + b \times v^2 \quad (31)$$

The target running resistance force, F^* , shall be equal to the running resistance force obtained from the running resistance table, F_T , because the correction for the standard ambient conditions is not necessary.

10.4 The specified speed for the chassis dynamometer

The running resistance on the chassis dynamometer shall be verified at the specified speed, v . At least four specified speeds, including the reference speed(s), should be verified. The range of specified speed points (the interval between the maximum and minimum points) shall extend either side of the reference speed or the reference speed range, if there is more than one reference speed, by at least Δv , as defined in 7.6. The specified speed points, including the reference speed point(s), shall be no greater than 20 km/h apart and the interval of specified speeds should be the same.

10.5 Verification of chassis dynamometer

10.5.1 Immediately after the initial setting, the coastdown time on the chassis dynamometer corresponding to the specified speed shall be measured. The motorcycle shall not be set up on the chassis dynamometer during the coastdown time measurement. When the chassis dynamometer speed exceeds the maximum speed of the test cycle, the coastdown time measurement shall start.

The measurement shall be carried out at least three times, and the mean coastdown time, Δt_E , shall be calculated from the results.

10.5.2 The set running resistance force, $F_E(v_j)$, at the specified speed on the chassis dynamometer is calculated by the following equation:

$$F_E(v_j) = \frac{1}{3,6} m_i \frac{2\Delta v}{\Delta t_E} \quad (32)$$

10.5.3 The setting error at the specified speed, ε , is calculated by the following equation:

$$\varepsilon = \frac{|F_E(v_j) - F_T|}{F_T} \times 100 \quad (33)$$

10.5.4 The chassis dynamometer shall be readjusted if the setting error does not satisfy the following criteria:

$$\varepsilon \leq 2 \% \text{ for } v \geq 50 \text{ km/h};$$

$$\varepsilon \leq 3 \% \text{ for } 30 \text{ km/h} \leq v < 50 \text{ km/h};$$

$$\varepsilon \leq 10 \% \text{ for } v < 30 \text{ km/h}.$$

10.5.5 The procedure in 10.5.1 to 10.5.3 shall be repeated until the setting error satisfies the criteria.

10.5.6 The chassis dynamometer setting and the observed errors shall be recorded. An example of the record form is given in C.3.

Annex A (normative)

Motorcycle description

A.1 Motorcycle

Category: Two wheeler/three wheeler

Tradename (-mark):

Model:

Engine model:

Cycle: Two stroke/four stroke

Number and layout of cylinders:

Engine displacement:..... cm³

Gear-box: Manual/automatic

Number of gear ratios (speeds):

Drive ratios: Primary:

Final:

Maximum speed (should be measured in accordance with ISO 7117): km/h

Reference speed:..... km/h (and km/h)

Mileage accumulated at test: km

Others, if there is any alteration:

A.2 Test motorcycle mass

Motorcycle mass: Kerb:..... kg

Reference:..... kg

Rider mass:..... kg

Instruments mass:..... kg

Front wheel loaded mass:..... kg

Rear wheel loaded mass: kg

Test motorcycle mass:..... kg

A.3 Equivalent inertia mass of rotating parts

Drive wheel: Drive train: kg
 Rear wheel and tyre with brake drum or disc: kg
 Steering wheel: Front wheel and tyre: kg
 Percentage of test motorcycle mass: %
 On-road rotating mass: kg
 Percentage of test motorcycle mass: %
 On-bench rotating mass: kg
 Percentage of motorcycle mass: %

A.4 Tyres

Sizes: front: rear:
 Make:

Pressures and dynamic tyre radius:

	Specified pressure	Actual pressure	Dynamic tyre radius
On-road testing:			
Front: kPa kPa mm
Rear: kPa kPa mm
On-bench testing:			
Drive wheel: kPa kPa mm

A.5 Frontal area determination

Rider height: m
 Frontal area: m²

Annex B (normative)

Chassis dynamometer and instruments description

B.1 Chassis dynamometer

Tradename (-mark) and model:

Diameter of roller: m

Chassis dynamometer type: DC/ED

Capacity of power absorbing unit (pau): kW

Speed range: km/h

Power absorption system: polygonal function/coefficient control

Resolution: N

Type of inertia simulation system: mechanical/electrical

Inertia equivalent mass: kg,
in steps of kg

Coastdown timer: digital/analogue/stop-watch

B.2 Speed sensor

Tradename (-mark) and model:

Principle:

Range:

Position of installed sensor:

Resolution:

Output:

B.3 Coastdown meter

Tradename (-mark) and model:

v_1, v_2 speed: Speed setting:

Accuracy:

Resolution:

Speed acquisition time:

Coastdown time: Range:

Accuracy:

Resolution:

Display output:

Number of channels:

STANDARDSISO.COM : Click to view the full PDF of ISO 11486:2006