

INTERNATIONAL STANDARD

ISO
1151-9

First edition
1993-09-15

AMENDMENT 1
1998-10-01

Flight dynamics — Concepts, quantities and symbols —

Part 9:

Models of atmospheric motions along the
trajectory of the aircraft

AMENDMENT 1: Turbulence

Mécanique du vol — Concepts, grandeurs et symboles —

*Partie 9: Modèles de mouvements atmosphériques le long de la trajectoire
de l'avion*

AMENDEMENT 1: Turbulence



Reference number
ISO 1151-9:1993/Amd.1:1998(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Amendment 1 to ISO 1151-9:1993 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 3, *Concepts, quantities and symbols for flight dynamics*.

STANDARDSISO.COM : Click to view the full PDF of ISO 1151-9:1993/Amd.1:1998

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Flight dynamics — Concepts, quantities and symbols —

Part 9:

Models of atmospheric motions along the trajectory of the aircraft

AMENDMENT 1: Turbulence

Page 1

Clause 9.0

Replace the existing clause 9.0 with the following:

"9.0 Introduction

This part of ISO 1151 deals with the concepts and quantities characterizing models of the air motions affecting the dynamic behaviour of the aircraft.

The aircraft motion is only influenced by the wind velocity field in the space surrounding the aircraft trajectory (8.2.1) and by its variations with time. In flight dynamic problems, it is usual to represent this field and its variations with time by considering mathematic models, which are schematic representations of the real wind.

In this part of ISO 1151, the following models are defined:

- constant wind (9.1);
- wind gradients (9.2);
- discrete gusts (9.3);
- three-dimensional wind models (9.4);
- vortices (9.5);
- continuous turbulence (9.6).

In these models it is assumed that the air motions are not perturbed by the presence of the aircraft itself. Other models can be defined by superposition of these models."

Page 6

Add the following new subclause:

9.6 Continuous turbulence

9.6.1 General description of turbulence

At a given moment and in the space surrounding the aircraft trajectory (8.2.1), the field of turbulence velocities (9.6.1.2) may be represented by spectral functions of the dimensions of space.

In 9.6.1.1 to 9.6.1.9, these spectral functions are considered with respect to a given direction.

No.	Term	Definition	Symbol
9.6.1.1	Turbulence	Wind model characterized by a random and rapid variation of the wind velocity \vec{V}_W (2.2.3) with respect to the mean velocity (9.1.3).	\vec{V}_T
9.6.1.2	Turbulence velocity	Difference between the instantaneous local wind velocity \vec{V}_W (2.2.3) and the mean wind velocity $\overline{\vec{V}_W}$ (9.1.3): $\vec{V}_T = \vec{V}_W - \overline{\vec{V}_W}$ NOTE — The temporal mean value of the turbulence velocity in all points of the considered space is zero.	\vec{V}_T
	Turbulence speed	The magnitude of turbulence velocity	V_T
9.6.1.3	Turbulence velocity components	— component of \vec{V}_T along the x axis — component of \vec{V}_T along the y axis — component of \vec{V}_T along the z axis	u_T v_T w_T
9.6.1.4	Turbulence wave-length	Length of a particular period of a spectral function of the turbulence with respect to the considered direction.	l_T
9.6.1.5	Turbulence wave number Turbulence inverse wave-length	Inverse of turbulence wave-length (9.6.1.4): $k_T = \frac{1}{l_T}$	k_T
9.6.1.6	Turbulence spatial frequency	Quantity defined by: $\Omega_T = \frac{2\pi}{l_T}$ where l_T is the turbulence wave-length (9.6.1.4).	Ω_T
9.6.1.7	Basic air velocity Basic airspeed	Difference of the instantaneous flight-path velocity \vec{V}_K (2.2.1) and the mean wind velocity $\overline{\vec{V}_W}$ (9.1.3) given by: $\vec{V}_B = \vec{V}_K - \overline{\vec{V}_W}$ The magnitude of basic air velocity.	\vec{V}_B V_B
9.6.1.8	Turbulence frequency	Quotient of the basic airspeed V_B (9.6.1.7) by the turbulence wave-length l_T (9.6.1.4): $f_T = \frac{V_B}{l_T}$	f_T
9.6.1.9	Temporal frequency	Product of 2π and the turbulence frequency f_T (9.6.1.8) defined as follows: $\omega_T = 2\pi f_T$	ω_T