

INTERNATIONAL
STANDARD

ISO
11591

Fourth edition
2020-10

AMENDMENT 1
2022-10

**Small craft — Field of vision from the
steering position**

AMENDMENT 1

Petits navires — Champ de vision depuis le poste de pilotage
AMENDEMENT 1

STANDARDSISO.COM : Click to view the full PDF of ISO 11591:2020/Amd 1:2022



Reference number
ISO 11591:2020/Amd.1:2022(E)

© ISO 2022

STANDARDSISO.COM : Click to view the full PDF of ISO 11591:2020/Amd 1:2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 188, *Small craft*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 464, *Small Craft*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 11591:2020/Amd 1:2022

Small craft — Field of vision from the steering position

AMENDMENT 1

Clause 1

Replace ISO 8666:2016 with ISO 8666:2020.

Clause 2

Replace ISO 8666:2016 with ISO 8666:2020.

Remove the following normative reference:

ISO 10240:2019, *Small craft — Owner's manual*

4.2.2.1

Replace ISO 8666:2016 with ISO 8666:2020.

4.2.2.2

Replace ISO 8666:2016 with ISO 8666:2020.

4.2.2.2

Add after 4.2.2.2 the following text:

4.2.2.3 Annex A sets the procedure and methods to determine the level reference line and to verify the field of vision in the vertical field for power-driven craft with steering wheel or equivalent fixed installed direct control, which shall be followed.

8.1

Remove the following text:

The owner's manual shall be in accordance with ISO 10240:2019 and shall include the following information.

In place of the removed text, add the following text:

An owner's manual shall be provided with the craft and shall include the following information.

8.2

Remove the following text:

The owner's manual shall be in accordance with ISO 10240:2019 and shall include the following information.

In place of the removed text, add the following text:

An owner's manual shall be provided with the craft and shall include the following information.

8.3

Remove the following text:

The owner's manual shall be in accordance with ISO 10240:2019 and shall include the following information.

In place of the removed text, add the following text:

An owner's manual shall be provided with the craft and shall include the following information.

After 8.3

Add the following new subclause:

8.4 General information

NOTE Requirements for the owner's manual are provided in ISO 10240.

Annex A

Add the following annex.

STANDARDSISO.COM : Click to view the full PDF of ISO 11591:2020/Amd 1:2022

Annex A (normative)

Procedure and methods to determine the level reference line and to verify the field of vision in the vertical field for power-driven craft with steering wheel or equivalent fixed installed direct control

A.1 General

Table A.1 describes the procedure and methods to determine the level reference line and to verify the field of vision

Table A.1 — Procedure to determine the level reference line

Procedure	Method
Step 1: Determine level reference line	Either: — practical method A.2.2; or — a computer aided design (CAD) method.
Step 2: Verify field of vision	Either: — practical method A.4; or — CAD method A.5.
NOTE In general, a CAD method is the use of a computer to design a device or a system, display it on a computer monitor or printer, simulate its operation and provide statistics on its performance. The computer is provided with data concerning the item to be designed, how it is to function and the rules for the way in which the different components can be joined.	

A.2 Procedure to determine the level reference line

A.2.1 Methods available

One of the following methods shall be used to determine the level reference line:

- a) the practical method described in A.2.2; or
- b) a CAD method.

A.2.2 Practical method to determine the level reference line

A.2.2.1 The craft shall be tested in the performance test mass condition (m_p), see ISO 8666:2020, 6.4.

A.2.2.2 Testing shall be conducted on calm water with the wind speed below 18 km/h (10 knots) and maximum wave height of $L_H/75$ m or 0,2 m, whichever is the highest.

NOTE Wave height is the vertical distance between the lowest point of a wave to the highest point.

A.2.2.3 The craft shall be tested from idle up to the maximum full throttle craft speed in two opposite directions.

A.2.2.4 During the test, the following parameters shall be recorded:

- a) speed (knots);
- b) trim angle related to speed (knots);
- c) trim tab usage related to speed (knots).

A.2.2.5 The maximum running trim angle value recorded during the two test runs shall be used as level reference line. Any high trim angles resulting from the transition between displacement and planing mode may be excluded and shall not be used as level reference line.

For planing boats, the transition between displacement and planing mode can be dependent on the installed propulsion system. Therefore, care shall be taken in the evaluation of the field of vision in cases where different power rated propulsion systems are recommended.

A.2.3 Computer aided design (CAD) method to determine the level reference line

The simulation of the craft shall be assessed in the performance test mass condition (m_p).

A.3 Procedure to verify the field of vision in the vertical field

One of the following methods shall be used to verify the field of vision in the vertical field:

- a) the practical method described in A.4; or
- b) the CAD method described in A.5.

A.4 Practical method to verify the field of vision in the vertical field

A.4.1 Set the boat on a cradle (or some other support) on a level surface with at least four boat lengths or 50 m, whichever is less, of unobstructed level space forward of the boat.

A.4.2 Support the hull at the level reference line consistent with the highest running trim angle recorded in A.2.2.5.

A.4.3 Determine the waterline at the level reference line established in A.2.2.5. Measure the distance from the waterline to the ground.

A.4.4 Set up a 0,15 m \pm 0,005 m diameter target at the height above ground as determined in A.4.3.

A.4.5 Any part of the target shall not exceed the vertical vision distance specified in 4.2.2.2.

A.5 Computer aided design method

A.5.1 Simulate the craft established in the level reference waterline determined by procedure in Step 1 of Table A.1. This shall be the hull at a trim angle consistent with the highest running trim angle recorded in A.2.2.5 or by A.2.3 for the CAD method.

A.5.2 Simulate compliance for the field of vision in the vertical field as specified in 4.2.2.2.

A.6 Information to be included in the owner's manual

If the use of trim tabs and/or power trim is necessary to meet the visibility requirements, instructions for the proper use of this equipment shall be included in the owner's manual(s).