

---

---

**Ships and marine technology —  
Marine electromagnetic compasses**

*Navires et technologie maritime — Compas électromagnétiques de  
marine*

STANDARDSISO.COM : Click to view the full PDF of ISO 11606:2022



STANDARDSISO.COM : Click to view the full PDF of ISO 11606:2022



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Composition.....</b>	<b>2</b>
<b>5 Construction and material.....</b>	<b>2</b>
5.1 Requirements.....	2
5.2 Electrical wiring.....	2
5.3 Non-magnetic housing.....	2
5.4 Fore-and-aft marks.....	2
5.5 Graduation.....	2
5.5.1 Graduation of main compass card.....	2
5.5.2 Indication of the repeater indicator.....	3
5.5.3 Centre of the graduation.....	3
5.5.4 Graduation of the verge ring.....	3
5.5.5 Accuracy of fore-and-aft marks.....	3
5.5.6 Readability of the graduation.....	3
5.5.7 Horizontal position of the compass plane.....	3
5.6 Lubber marks.....	3
5.6.1 General.....	3
5.6.2 Accuracy.....	3
5.7 Illumination.....	4
5.8 Compensation of deviation and heeling error.....	4
5.8.1 General.....	4
5.8.2 Indication of compensation.....	4
5.8.3 Protection of compensation.....	4
5.9 Heading output.....	4
5.10 Outputs to other equipment.....	4
5.11 Gimbals.....	5
5.11.1 Direction of gimbal axes.....	5
5.11.2 Angle between the gimbal axes.....	5
5.11.3 Freedom of tilt of the main compass.....	5
5.11.4 Precaution against dislodging of the main compass and the repeater indicators.....	5
5.12 Fitting the main compass.....	5
5.13 Height of the compass card plane.....	5
5.14 Watertightness of repeater indicators.....	5
5.15 Azimuth reading devices.....	5
5.15.1 Provision of azimuth reading devices.....	5
5.15.2 Azimuth sight.....	5
5.16 Construction for maintenance and inspection.....	5
5.17 Protection against changes in power supply.....	6
<b>6 Performance.....</b>	<b>6</b>
6.1 Preconditions.....	6
6.2 Accuracy of heading.....	6
6.2.1 Static accuracy.....	6
6.2.2 Dynamic accuracy.....	6
6.3 Follow-up accuracy of the transmission system.....	6
6.4 Synchronized accuracy between a repeater indicator and the main compass.....	6
6.5 Possibility of compensating the coefficients.....	6
6.6 Electromagnetic compatibility.....	6
<b>7 Precautions against failure.....</b>	<b>7</b>

7.1	Power supply	7
7.2	Backup of compensator data	7
7.3	Failure alarm	7
<b>8</b>	<b>Marking</b>	<b>7</b>
<b>9</b>	<b>Type testing and individual testing</b>	<b>7</b>
9.1	General	7
9.2	Type testing	7
9.3	Individual testing	7
<b>10</b>	<b>Certification</b>	<b>8</b>
10.1	Test certification	8
10.2	Statement issued by or on behalf of the manufacturer	8
10.3	Marking check	8
10.4	Sample checks	8
<b>11</b>	<b>Testing</b>	<b>8</b>
11.1	Testing of units	8
11.1.1	General	8
11.1.2	Condition of the compass	9
11.1.3	Non-magnetic properties (type test only)	9
11.1.4	Graduation of the main compass card	9
11.1.5	Fore-and-aft marks of the main compass	9
11.1.6	Azimuth error of the main compass	9
11.1.7	Graduation of the card of card-type repeater indicators	9
11.1.8	Graduation of the verge ring	9
11.1.9	Readability	9
11.1.10	Horizontal position of compass plane	9
11.1.11	Lubber marks	10
11.1.12	Illumination and dimmer systems	10
11.1.13	Indication of compensation values	10
11.1.14	Examination of the output	10
11.1.15	Direction of gimbal axis and angle between the gimbal axes	10
11.1.16	Freedom of tilt of the main compass	11
11.1.17	Precautions against dislodging	11
11.1.18	Fitting the main compass	11
11.1.19	Height of the main compass card plane	11
11.1.20	Watertightness of repeater indicators	11
11.1.21	Provision of azimuth reading device	11
11.1.22	Azimuth sight	11
11.1.23	Construction for maintenance and inspection	11
11.1.24	Protection against changes in power supply	11
11.2	Performance tests	11
11.2.1	Freedom of tilt of the compasses	11
11.2.2	Accuracy of the fore-and-aft marks of the main compass	12
11.2.3	Accuracy of the main lubber mark	12
11.2.4	Accuracy of the compass	12
11.2.5	Directional error in the horizontal plane	12
11.2.6	Bearing accuracy under the influence of ship's motion	12
11.2.7	Transmission system	12
11.2.8	Synchronized accuracy between a repeater indicator and the main compass	12
11.2.9	Environmental conditions	12
11.2.10	Test of compensation ability	12
11.3	Test of electromagnetic compatibility	13
11.4	Checking of precaution against failure	13
<b>12</b>	<b>Designation</b>	<b>13</b>
	<b>Bibliography</b>	<b>14</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 6, *Navigation and ship operations*.

This third edition cancels and replaces the second edition (ISO 11606:2000), which has been technically revised. It also incorporates the Technical Corrigendum ISO 11606:2000/Cor 1:2005.

The main changes are as follows:

- in [Clause 1](#), added text relating to IMO Resolution MSC.166(78) and the applicability of this document;
- in [Clause 2](#), replaced ISO 449:1997 with ISO 25862:2019, and deleted IEC 61162-1, IEC 61162-2 and IMO Resolution MSC.86(70);
- in [Clause 3](#), added term *electromagnetic compass* ([3.1](#));
- in [5.7](#) and [11.1.12](#), added a provision on displays for presentation and a reference to IEC 62288;
- in [5.10](#), updated interface requirements;
- in [7.3](#), updated failure alarm requirements;
- in [11.2.9](#), updated other environmental conditions requirements;
- deleted former Annex A;
- in the Bibliography, added ISO 22090-2, IEC 61162-1, IEC 61162-2, IEC 61162-450, IEC 62288, IEC 62923-1, IEC 62923-2, IMO Resolution MSC.86(70), IMO Resolution MSC.166(78), IMO Resolution MSC.191(79), IMO Resolution MSC.302(87) and IMO Resolution MSC.466(101).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 11606:2022

# Ships and marine technology — Marine electromagnetic compasses

## 1 Scope

This document specifies general requirements, type tests and individual tests for the marine electromagnetic compasses, intended for steering purposes and/or taking bearings on board ships, required by Chapter V of SOLAS, 1974 and the International Code of Safety for High-Speed Craft (HSC Code). In accordance with IMO Resolution MSC.166(78), this document is applicable to marine electromagnetic compasses fitted before 1 July 2002. For marine electromagnetic compasses installed on or after 1 July 2002, ISO 22090-2 is applicable. The magnetic compasses specified in this document apply to ships the overall length of which is normally not less than 24 m.

NOTE In this document requirements extracted from the recommendations of IMO resolutions are printed in italics.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1069, *Magnetic compasses and binnacles for sea navigation — Vocabulary*

ISO 25862:2019, *Ships and marine technology — Marine magnetic compasses, binnacles and azimuth reading devices*

IEC 60945, *Marine navigation and radiocommunication equipment and systems — General requirements — Methods of testing and required test results*

IMO Resolution A. 694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A. 813(19), *General requirements for electromagnetic compatibility (EMC) for all electrical and electronic ship's equipment*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1069 and the following apply. ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### **electromagnetic compass**

item of the electronic equipment that uses the geomagnetic field to obtain information about the ship's heading

Note 1 to entry: This information is conveyed to the main compass (used for steering and taking bearings), to additional repeater indicators and, if required, to other navigational equipment.

### 3.2

#### **magnetic sensor**

sensor that detects geomagnetic field and supplies appropriate output concerning direction to the processor (3.4)

### 3.3

#### **main compass**

display unit that shows the output of the processor (3.4) with a compass card or an electronic image of a compass card

### 3.4

#### **processor**

device that processes the output of the magnetic sensor (3.2) and provides the ship's magnetic heading and/or true heading

### 3.5

#### **repeater indicator**

additional indicator that may be equipped with a display that uses a different type of compass card

## 4 Composition

The electromagnetic compass system shall consist of a magnetic sensor, a processor, a main compass display and facilities for other repeater indicators and equipment.

## 5 Construction and material

### 5.1 Requirements

Electromagnetic compasses shall fulfil the requirements in 5.2 to 5.17.

### 5.2 Electrical wiring

Electrical wiring, such as that for the direct-current power supply and that for connecting the units, shall not produce any perceptible errors in the heading information.

Twist cables are recommended for this purpose.

### 5.3 Non-magnetic housing

The housing of the magnetic sensor system shall be non-magnetic.

### 5.4 Fore-and-aft marks

[IMO Resolution MSC.86(70), Annex 2, 4.1.1] *Fore-and-aft marks shall be inscribed on the housing of the magnetic sensor system and the bottom part of the binnacle of the main compass. The units shall be installed on the fore-and-aft line of the ship.*

[IMO Resolution MSC.86(70), Annex 2, 4.1.2] *The fore-and-aft marks shall be within  $\pm 0,5^\circ$  of the fore-and-aft axis of the unit.*

### 5.5 Graduation

#### 5.5.1 Graduation of main compass card

The main compass shall be of the compass card type, which shall be graduated in 360 single degrees, starting from North (000°) in the clockwise direction as viewed from above. Each tenth degree shall be marked with the three corresponding numbers. The accuracy of the graduation shall be better than

0,2° on any heading. The cardinal points shall be indicated by the capital letters N, S, E and W; the intermediate points may also be marked.

Alternatively, the North point may be indicated by a suitable symbol.

### 5.5.2 Indication of the repeater indicator

The graduation of the indicator, if of the card type, shall be the same as that of the main compass card. If a repeater indicator is used for steering purposes, it shall be of the card type.

In the case of numerical displays, three-digit numbers, in degrees, shall be shown.

### 5.5.3 Centre of the graduation

The main compass, and repeater indicators to be used for bearing purposes, shall be fitted with a seat for a shadow pin which accommodates bearings or, if no seat is provided, the centre of the graduation shall be clearly indicated.

### 5.5.4 Graduation of the verge ring

The main compass, and repeater indicators to be used for bearing purposes, shall be provided with a verge ring, which is graduated in degrees, for the measurement of bearings relative to the ship's head. The scale shall be graduated in 360 single degrees in clockwise direction as viewed from above.

Both the zero mark indicating the bearing of the ship's head and the 180° mark indicating the bearing of the ship's stern shall be within  $\pm 0,5^\circ$  of the fore-and-aft marks.

### 5.5.5 Accuracy of fore-and-aft marks

The fore-and-aft marks of the main compass, and of repeater indicators to be used for bearing purposes, shall be in the vertical plane passing through the centre of the compass card and the main lubber mark to within  $\pm 0,5^\circ$ .

### 5.5.6 Readability of the graduation

It shall be possible for a person with normal vision to read the main compass card and the indication of the repeater indicator at a distance of 1,0 m, both in daylight and in artificial light.

### 5.5.7 Horizontal position of the compass plane

The plane of the compass card of the main compass, and of repeater indicators to be used for bearing purposes, shall be so balanced that it is horizontal to within  $\pm 2^\circ$ .

## 5.6 Lubber marks

### 5.6.1 General

The main compass display and all repeater indicators shall be fitted with at least one lubber mark, indicating the direction of the ship's head. Additional lubber marks indicating the direction of ship's stem and athwartship are permissible.

The width of the lubber mark shall not be greater than 0,5° on the card or 0,5 mm, whichever is smaller.

The distance between the lubber mark and the outer edge of the card shall not be more than 1,5 mm.

### 5.6.2 Accuracy

The main lubber mark shall be within  $\pm 0,5^\circ$  of the 0° to 180° line of the verge ring.

Additional lubber marks shall be within  $\pm 1^\circ$ .

## 5.7 Illumination

The units shall be provided with adequate provision for illuminating the controls and displays. A device shall be provided for dimming the electric light. If a display is used for presentation, the equipment shall comply with MSC.191(79), as amended by MSC.466(101), and with IEC 62288.

## 5.8 Compensation of deviation and heeling error

### 5.8.1 General

[IMO Resolution MSC.86(70), Annex 2, 4.3] *Provision shall be made for correcting the heeling error and the coefficients A, B, C, D and E. It shall be possible to correct the following values:*

- *vertical component of the ship's magnetic field (producing the heeling error): up to  $\pm 75 \mu\text{T}$ ;*
- *coefficient A: up to  $\pm 3^\circ$ ;*
- *coefficient B: up to  $\pm(720/H)^\circ$ ;*
- *coefficient C: up to  $\pm(720/H)^\circ$ ;*
- *coefficient D: up to  $\pm 7^\circ$ ;*
- *coefficient E: up to  $\pm 3^\circ$ ;*

where *H* is the horizontal component of the geomagnetic flux density in microteslas ( $\mu\text{T}$ ).

The devices for correcting the coefficients *A, B, C, D* and *E* shall not produce any undesired deviation greater than  $1^\circ$ . The devices for correcting heeling error shall not produce any undesired alteration of the vertical component of the ship's magnetic field greater than  $1 \mu\text{T}$ .

### 5.8.2 Indication of compensation

[IMO Resolution MSC.86(70), Annex 2, 4.3.1] *The values used for electronic compensation shall be indicated by adequate means and shall be stored such that values are automatically recovered on switch on.*

### 5.8.3 Protection of compensation

[IMO Resolution MSC.86(70), Annex 2, 4.3.2] *The compensating devices shall be protected against accidental alterations.*

## 5.9 Heading output

[IMO Resolution MSC.86(70), Annex 2, 4.4] *All displays and outputs of heading should be able to indicate true heading. An indication of any deviation and variation applied to compensate the heading shall be capable of being displayed or included in the output.*

The type of heading displayed shall be conspicuously indicated and the type of heading shall be identified with a transmitted heading.

## 5.10 Outputs to other equipment

The electromagnetic compass shall be so designed that it is able to provide the azimuth information, within a transmitting error of not greater than  $\pm 0,5^\circ$ , to the navigational equipment, radars, direction finders, heading control systems and additional position measurement instruments. If these navigational instruments have digital outputs, they shall meet the requirements prescribed in IEC 61162-1, IEC 61162-2 or IEC 61162-450.

## 5.11 Gimbals

### 5.11.1 Direction of gimbal axes

If gimbals are provided, the outer gimbal axis shall be in the fore-and-aft direction.

### 5.11.2 Angle between the gimbal axes

If gimbals are provided, the angle between the axes of the inner and outer gimbals shall be  $90^\circ \pm 1^\circ$ , except if the diameter of the outer gimbal ring is less than 150 mm: in this case, the angle shall be  $90^\circ \pm 2^\circ$ .

### 5.11.3 Freedom of tilt of the main compass

The main compass shall be constructed in such a way that it can revolve about the inner gimbal axis freely up to  $30^\circ$  when the gimbal ring, if fitted, is horizontal.

### 5.11.4 Precaution against dislodging of the main compass and the repeater indicators

The main compass and repeater indicators shall be constructed in such a way that, if they are fitted on gimbals, they return to their normal position and are not dislodged after tilting.

## 5.12 Fitting the main compass

Provision shall be made in the bottom part of the magnetic sensor unit, the main compass and card-type repeater indicators in order to allow correction of any misalignment thereof in respect of the fore-and-aft line of the ship, by an angle of up to  $\pm 5^\circ$ .

## 5.13 Height of the compass card plane

Main compasses shall be so constructed that the plane of the compass card is at least 1 m above the lower surface of the binnacle deck fittings, and capable of taking bearings of celestial bodies and other distant objects.

## 5.14 Watertightness of repeater indicators

The main compass and all repeater indicators intended for use on an open deck shall be waterproof.

## 5.15 Azimuth reading devices

### 5.15.1 Provision of azimuth reading devices

There shall be at least one appropriate azimuth reading device to take bearings of celestial bodies and other distant objects.

### 5.15.2 Azimuth sight

The field of vision shall be at least  $5^\circ$  on each side of the line sight and it shall be possible to take azimuths of celestial bodies and bearings of distant objects whose altitudes are between  $5^\circ$  below and  $60^\circ$  above the horizontal.

This requirement on the accuracy of the azimuth shall be fulfilled in the altitude range from  $5^\circ$  above the horizontal to  $50^\circ$  below the horizontal.

## 5.16 Construction for maintenance and inspection

Equipment shall be so constructed that it is possible to carry out maintenance and inspection easily.

## 5.17 Protection against changes in power supply

[IMO Resolution A.694(17), 4.2] *Means shall be incorporated for the protection of equipment from the effects of excessive current and voltage, transients and accidental reversal of the power supply polarity.*

## 6 Performance

### 6.1 Preconditions

Performance within the temperature range between:

- $-25\text{ °C} \pm 3\text{ °C}$  and  $70\text{ °C} \pm 3\text{ °C}$  for equipment or units intended to be exposed to the weather, and
  - $-15\text{ °C} \pm 3\text{ °C}$  and  $55\text{ °C} \pm 3\text{ °C}$  for equipment or units intended to be protected from the weather,
- shall conform to the requirements of [6.2](#) to [6.6](#).

The use of temperature controllers is permitted.

### 6.2 Accuracy of heading

#### 6.2.1 Static accuracy

[IMO Resolution MSC.86(70), Annex 2, 5.1.1] *The static accuracy of the heading indication shall be within  $\pm 1,0^\circ$ .*

#### 6.2.2 Dynamic accuracy

[IMO Resolution MSC.86(70), Annex 2, 5.1.2] *The dynamic accuracy of the heading indication or output shall be within  $\pm 1,5^\circ$  in addition to the static accuracy as defined. Periods of oscillation shall not be shorter than 30 seconds under the conditions of various sea states and ship motion likely to be experienced in ships.*

### 6.3 Follow-up accuracy of the transmission system

[IMO Resolution MSC.86(70), Annex 2, 5.2] *The follow-up accuracy of the transmission system shall be within  $\pm 1,5^\circ$ , when the sensor is rotated at a rate of  $\pm 20^\circ/\text{s}$ .*

### 6.4 Synchronized accuracy between a repeater indicator and the main compass

The difference between the readings of a repeater indicator and the main compass shall be not more than  $\pm 0,5^\circ$ .

### 6.5 Possibility of compensating the coefficients

It shall be possible to compensate the coefficients *A*, *B*, *C*, *D* and *E* so that the residual value of each coefficient is smaller than  $\pm 0,5^\circ$ .

### 6.6 Electromagnetic compatibility

[IMO Resolution MSC.86(70), Annex 2, 6] *The compass system, with regard to electromagnetic interference and immunity, shall in addition to Resolution A.694(17) comply with Resolution A.813(19). In addition, the compass system may comply with IEC 60533.*

## 7 Precautions against failure

### 7.1 Power supply

A main power supply and an emergency power supply shall be provided. Both power supplies shall have automatic changeover facilities. This subclause does not apply to ships not provided with the emergency supply.

### 7.2 Backup of compensator data

Provision shall be made to ensure that the compensator data cannot be changed unintentionally or by a failure of the system.

### 7.3 Failure alarm

[IMO Resolution MSC.86(70), Annex 2, 6] *An alert shall be provided to indicate a failure of the power supply to the compass system.*

When the compass system has multiple power supplies, and thus remains in operation after failure of one power supply due to the presence of another power supply, the compass system shall on failure of one power supply raise a 'compass power fail' alert of priority caution with an appropriate alert description text.

In case of total power failure to the compass system, the equipment shall provide a status signal (e.g. by normally closed contact) to enable the external equipment to raise the appropriate alert.

NOTE A binary signal, such as normally closed or normally open relay contact, is considered to represent one legacy alert by IEC 62923-1 and IEC 62923-2.

## 8 Marking

Each unit of compasses shall be marked with the following:

- the identification of the manufacturer;
- the equipment type number or identification of the model that was type tested;
- the serial number of the unit;
- the year of manufacture (not necessary if the year of manufacture can be read by the serial number);
- the safe distance for installation on a bridge.

## 9 Type testing and individual testing

### 9.1 General

Unless otherwise stated, all tests shall be carried out at a temperature of  $20\text{ °C} \pm 3\text{ °C}$ .

### 9.2 Type testing

Type testing shall be carried out before the instruments come into regular service. For type testing, only new devices are acceptable.

### 9.3 Individual testing

Individual testing shall be carried out before installation on board ship. It is also desirable to perform the test periodically and after repair, on board ship.

For individual testing, all devices shall be in a clean and serviceable state when tested.

## 10 Certification

### 10.1 Test certification

Devices that have passed the type test or the individual test and comply with the requirements shall be certified in the language of the test authority and in English.

Each type test certificate is valid exclusively for the model tested. In case of alterations or technical improvements that can affect compliance with this document, the model shall be given a new identification number or mark and the type test shall be repeated. All alterations shall be submitted to the original test authority who will decide whether a new type test is necessary.

Copies of the certificate shall be issued on demand. They shall be explicitly marked "copy".

Acceptance of type test certificates and individual test certificates between countries will be a matter for mutual agreement.

### 10.2 Statement issued by or on behalf of the manufacturer

The following requirement applies to type testing only.

The manufacturer or importer shall produce a written statement covering those requirements which cannot be ascertained during the type test. The statement shall contain the following:

- a detailed description of the elements;
- a detailed description of the gimbal ring;
- a description of the installation;
- an operational guide to enable the optimum performance to be attained;
- figures to support the application of type testing.

### 10.3 Marking check

- a) The presence of the markings on the unit of the compass specified in [Clause 8](#) shall be checked by visual inspection.
- b) When [10.3 a\)](#) is fulfilled, the markings specified in [Clause 8](#) shall be written on the certificate.

### 10.4 Sample checks

In order to check that the requirements covered by the statement issued by the manufacturer or importer described in [10.2](#) have been fulfilled, sample checks may be carried out.

## 11 Testing

### 11.1 Testing of units

#### 11.1.1 General

Testing shall be carried out on the following components in accordance with the categories for which they are intended as specified in IEC 60945:

- a) magnetic sensor: exposed to the weather;

- b) processor: protected from the weather or exposed to the weather if intended for use on an open deck;
- c) main compass: protected from the weather or exposed to the weather if intended for use on an open deck;
- d) repeater indicator: protected from the weather or exposed to the weather if intended for use on an open deck.

Tests in the static magnetic field shall be carried out in an authorized test room.

### 11.1.2 Condition of the compass

Carry out a visual inspection of the compass to ensure that it is undamaged, mechanically sound and operating satisfactorily.

### 11.1.3 Non-magnetic properties (type test only)

Examine the housing of the magnetic sensor system (see [5.3](#)) to confirm its non-magnetic properties.

### 11.1.4 Graduation of the main compass card

Carry out a visual inspection. The result shall fulfil the requirements specified in [5.5.1](#).

### 11.1.5 Fore-and-aft marks of the main compass

This examination may be carried out on a compass test stand. After having brought the outer gimbal axis (the fore-and-aft datum line may be used instead) into a vertical plane of sight coinciding with the centre of rotation, rotate the stand until the fore-and-aft marks come into the vertical plane of sight. The fore-and-aft marks error is equal to the angle of rotation of the test stand. The result shall fulfil the requirement specified in [5.4](#).

### 11.1.6 Azimuth error of the main compass

This examination may be carried out on a compass test stand. The result shall fulfil the requirements specified in [5.5.1](#).

### 11.1.7 Graduation of the card of card-type repeater indicators

This examination shall be carried out by visual inspection. The result shall fulfil the requirements specified in [5.5.2](#).

### 11.1.8 Graduation of the verge ring

This examination shall be carried out by visual inspection. The result shall fulfil the requirements specified in [5.5.4](#).

### 11.1.9 Readability

This examination shall be carried out by visual inspection. The result shall fulfil the requirement specified in [5.5.6](#).

### 11.1.10 Horizontal position of compass plane

The main compass and card-type repeater indicators shall be balanced so that the verge ring, or top glass cover, settles in the horizontal plane when the gimbal ring is fixed in a horizontal position. This requirement shall be met whether the azimuth reading device, or other attachment or magnifier, is in position or not. Measurement shall be carried out by placing a spirit-level of suitable sensitivity or other

similar device on the verge ring or top glass cover. The result shall fulfil the requirements specified in [5.5.7](#).

#### **11.1.11 Lubber marks**

##### **11.1.11.1 Main lubber mark and additional lubber marks**

The main lubber mark and additional lubber marks (if any) of the main compass and the compass-type repeater indicators shall be checked. These lubber marks shall fulfil the requirements specified in [5.6](#).

##### **11.1.11.2 Width and location of lubber marks**

These examinations shall be carried out by visual inspection, and shall fulfil the requirements specified in [5.6](#).

##### **11.1.11.3 Lubber mark error**

The examination may be carried out on a compass test stand. After having brought the outer gimbals axis (the fore-and-aft datum line may be used instead) into a vertical plane of sight coinciding with the centre of rotation, rotate the stand until the main lubber mark comes into the vertical plane of sight. The lubber mark error is equal to the angle of rotation of the test stand. The result shall fulfil the requirement specified in [5.6](#).

#### **11.1.12 Illumination and dimmer systems**

These examinations shall be carried out by visual inspection, and shall fulfil the requirements specified in [5.7](#).

If a display is used for presentation, confirm using documented evidence that the equipment complies with IEC 62288.

#### **11.1.13 Indication of compensation values**

The check to determine whether the deviation and heeling-error compensation values are indicated shall be carried out by visual inspection, and shall fulfil the requirements specified in [5.8](#).

#### **11.1.14 Examination of the output**

##### **11.1.14.1 General**

Compliance with the requirements specified in [5.8](#), [5.9](#) and [5.10](#) shall be verified by visual inspection or electrical measurements.

##### **11.1.14.2 Output of ship's heading**

The check to determine that the output of the heading information, obtained after compensating with the values of coefficients *A*, *B*, *C*, *D*, *E* and (geomagnetic) variation, is sent to the main compass, the repeater indicators and the output terminals, shall be carried out by visual inspection, and shall fulfil the requirements specified in [5.9](#).

#### **11.1.15 Direction of gimbal axis and angle between the gimbal axes**

The direction of the outer gimbal axis shall be examined by visual inspection, and shall fulfil the requirement specified in [5.11.1](#).

Measurement of the angle between the gimbal axes may be made by means of graduation of the test stand when, by turning the compass support, first one and then the other gimbal axis is brought into the vertical plane of view passing through the centre of the graduation.

The result shall fulfil the requirements specified in [5.11.2](#). This test is only a type test.

#### **11.1.16 Freedom of tilt of the main compass**

This test may be carried out using a clinometer placed on the top glass cover or verge ring. The result shall fulfil the requirement specified in [5.11.3](#). This test is only a type test.

#### **11.1.17 Precautions against dislodging**

This examination shall be carried out by visual inspection, and the result shall fulfil the requirement specified in [5.11.4](#). This test is only a type test.

#### **11.1.18 Fitting the main compass**

Measure the rotatable allowance by fitting the magnetic sensor unit in accordance with the manufacturer's instructions. Turn the unit to determine the maximum angle of misalignment which can be corrected. The result shall fulfil the requirement specified in [5.12](#).

#### **11.1.19 Height of the main compass card plane**

Measure the height of the main compass card plane; it shall fulfil the requirements specified in [5.13](#).

#### **11.1.20 Watertightness of repeater indicators**

The main compass and the repeater indicators intended for use on an open deck shall fulfil the requirements specified in IEC 60945 for the category "exposed to the weather".

#### **11.1.21 Provision of azimuth reading device**

The azimuth reading device for taking bearings shall fulfil the requirements specified in ISO 25862:2019, Clause 6.

#### **11.1.22 Azimuth sight**

This test may be carried out by visual inspection, and the result shall fulfil the requirements specified in [5.15.2](#).

#### **11.1.23 Construction for maintenance and inspection**

This test shall be carried out by visual inspection. The result shall fulfil the requirements specified in [5.16](#) and IEC 60945.

#### **11.1.24 Protection against changes in power supply**

Means providing protection against changes in power supply shall be checked by the relevant method in IEC 60945, and meet the requirements specified in [5.17](#) and IMO Resolution A.694(17).

### **11.2 Performance tests**

#### **11.2.1 Freedom of tilt of the compasses**

This examination may be carried out by means of a revolving platform with adjustable inclination. When the binnacle is tilted in any direction by an angle of 30°, the main compass and the card-type repeater indicator shall fulfil the requirement specified in [5.11.4](#), and the reading of the main compass shall fulfil the requirements specified in [6.2](#) and [6.3](#).