

---

---

**Rolling bearings — Needle roller  
bearings with machined rings —  
Boundary dimensions, geometrical  
product specifications (GPS) and  
tolerance values**

*Roulements — Roulements à aiguilles avec bagues usinées —  
Dimensions d'encombrement, spécification géométrique des produits  
(GPS) et valeurs de tolérance*

STANDARDSISO.COM : Click to view full PDF of ISO 1206:2018



STANDARDSISO.COM : Click to view the full PDF of ISO 1206:2018



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

Published in Switzerland

# Contents

	Page
Foreword .....	iv
Introduction .....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols</b> .....	<b>1</b>
<b>5 Nominal boundary and chamfer dimensions</b> .....	<b>5</b>
<b>6 Tolerances</b> .....	<b>13</b>
6.1 General .....	13
6.2 Tolerances for complete bearing and bearing without inner ring .....	13
<b>7 Radial internal clearance</b> .....	<b>14</b>
<b>Annex A (informative) Tolerances for shaft raceways for needle roller bearings without inner ring</b> .....	<b>15</b>
<b>Annex B (informative) Symbols and terms as given in ISO 1206:2001 in relation to descriptions given in this document</b> .....	<b>17</b>
<b>Bibliography</b> .....	<b>19</b>

STANDARDSISO.COM : Click to view the full PDF of ISO 1206:2018

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 5, *Needle, cylindrical and spherical roller bearings*.

This fourth edition cancels and replaces the third edition (ISO 1206:2001), which has been technically revised. It also incorporates the amendment ISO 1206:2001/Amd 1:2013.

The main changes to the previous edition are as follows:

- the scope has been extended to dimensions series 59 and special series dimensions;
- the geometrical product specification (GPS) system has been applied.

## Introduction

This document is a machine element geometry standard as defined in the geometrical product specification (GPS) system as presented in the matrix model of ISO 14638.

The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated.

The connection between functional requirements, measuring technique and measuring uncertainty is always intended to be considered. For measurement uncertainty, it is intended that ISO 14253-2 be considered.

STANDARDSISO.COM : Click to view the full PDF of ISO 1206:2018

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 1206:2018

# Rolling bearings — Needle roller bearings with machined rings — Boundary dimensions, geometrical product specifications (GPS) and tolerance values

## 1 Scope

This document specifies the boundary dimensions and normal class tolerance values for needle roller bearings with machined rings.

This document specifies dimensional and geometrical characteristics, and limit deviations from nominal sizes.

These specifications apply to complete needle roller bearings and to bearings without inner ring.

Recommended values for the tolerances for shaft raceways for needle roller bearings without inner ring are given in [Annex A](#).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1101, *Geometrical product specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 5593, *Rolling bearings — Vocabulary*

ISO 14405-1, *Geometrical product specifications (GPS) — Dimensional tolerancing — Part 1: Linear sizes*

ISO/TS 17863, *Geometrical product specification (GPS) — Tolerancing of moveable assemblies*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1101, ISO 5593, ISO 14405-1, and ISO/TS 17863 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

## 4 Symbols

Descriptions for symbols are in accordance with GPS terminology; relationships with traditional terms are described in [Annex B](#), [Table B.1](#). The dimensional and geometrical specifications are described in [Table 1](#).

Tolerance value associated to a characteristic is symbolized by  $t$ , followed by the symbol of characteristic, for example,  $t_{\Delta Cs}$ .

In this document, the ISO default specification operator for size is in accordance with ISO 14405-1; i.e. the two-point size is valid.

Table 1 — Symbols for nominal sizes, characteristics and specification modifiers

Symbol for nominal size <sup>a</sup>	Symbol for characteristic	GPS symbol and specification modifier <sup>b,c</sup>	Description <sup>d</sup>
<i>B</i>			nominal inner ring width
	VBs	(LP) (SR)	range of two-point sizes of inner ring width
	ΔBs	(LP)	deviation of a two-point size of inner ring width from its nominal size
<i>C</i>			nominal outer ring width
	VCs	(LP) (SR)	range of two-point sizes of outer ring width
	ΔCs	(LP)	deviation of a two-point size of outer ring width from its nominal size
<i>d</i>			nominal bore diameter
	Vdmp	(LP) (SD) ACS (SR)	range of mid-range sizes (out of two-point sizes) of bore diameter in any cross-section of a cylindrical bore
	Δdmp	(LP) (SD) ACS	deviation of a mid-range size (out of two-point sizes) of bore diameter in any cross-section from its nominal size
<i>D</i>			nominal outside diameter
	VDmp	(LP) (SD) ACS (SR)	range of mid-range sizes (out of two-point sizes) of outside diameter in any cross-section
	ΔDmp	(LP) (SD) ACS	deviation of a mid-range size (out of two-point sizes) of outside diameter in any cross-section from its nominal size
<i>F<sub>w</sub></i>			nominal bore diameter of needle roller complement
	ΔF <sub>ws</sub>	(GX) (SN) <sup>f</sup>	deviation of the smallest maximum inscribed cylinder size of bore diameter of needle roller complement from its nominal size

<sup>a</sup> Symbols as defined in ISO 15241 except for the format used.

<sup>b</sup> Symbols as defined in ISO 1101 and ISO 14405-1.

<sup>c</sup> Specification modifier (LP) is not indicated on a drawing if the two-point size is applied for both specified limits.

<sup>d</sup> Description based on ISO 1101, ISO 5459 and ISO 14405-1.

<sup>e</sup> Symbols for direction of gravity, G, fixed parts, FP and movable parts, MP, in accordance with ISO/TS 17863 and specific flagnotes (see [Figures 1](#) and [2](#)).


<sup>f</sup> Considering the influence of rotation of needle roller complement.

Table 1 (continued)

Symbol for nominal size <sup>a</sup>	Symbol for characteristic	GPS symbol and specification modifier <sup>b,c</sup>	Description <sup>d</sup>
	Kea	$\textcircled{\text{LP}} \textcircled{\text{SR}} \text{SCS} \textcircled{\perp \text{A}}$ <sup>e</sup>	range of two-point sizes of section height between inner ring bore surface and outer ring outside surface of assembled needle roller set and fixed inner ring in a specific cross section perpendicular to datum, i.e. axis, established from the inner ring bore surface
	Kia	$\textcircled{\text{LP}} \textcircled{\text{SR}} \text{SCS} \textcircled{\perp \text{B}}$ <sup>e</sup>	range of two-point sizes of section height between outer ring outside surface and inner ring bore surface of assembled needle roller bearing, obtained from a specific cross section of turning inner ring and needle roller set and fixed outer ring perpendicular to datum, i.e. axis, established from the outer ring outside surface
<i>r</i>			nominal chamfer dimension
	<i>r<sub>s</sub></i>		single chamfer dimension
<p><sup>a</sup> Symbols as defined in ISO 15241 except for the format used.</p> <p><sup>b</sup> Symbols as defined in ISO 1101 and ISO 14405-1.</p> <p><sup>c</sup> Specification modifier <math>\textcircled{\text{LP}}</math> is not indicated on a drawing if the two-point size is applied for both specified limits.</p> <p><sup>d</sup> Description based on ISO 1101, ISO 5459 and ISO 14405-1.</p> <p><sup>e</sup> Symbols for direction of gravity, G, fixed parts, FP and movable parts, MP, in accordance with ISO/TS 17863 and specific flagnotes (see <a href="#">Figures 1</a> and <a href="#">2</a>).</p> <p><sup>f</sup> Considering the influence of rotation of needle roller complement.</p>			

[Figures 1](#) and [2](#) show GPS specifications for needle roller bearings with and without inner ring, respectively.


These principles shall be applied for all types of needle roller bearings (e.g. with or without cage, with one row or two rows of needle rollers and with or without lubrication groove and lubrication holes in the outer ring).



Key

- ① FP ① - MP ②, G
- ② FP ② - MP ①, G
- ③ the requirements apply at any specific location of the FP for any location of the MP relation to the direction of gravity where the needle rollers are in contact with both raceways of the inner and outer ring

Figure 1 — GPS specifications for needle roller bearing with inner ring



Key

① considering the influence of rotation of needle roller complement

Figure 2 — GPS specifications for needle roller bearing without inner ring

### 5 Nominal boundary and chamfer dimensions

The dimension series described in Tables 2 to 5 are defined in ISO 15. Maximum chamfer dimensions are in accordance with ISO 582.

Special series dimension are given in Table 6 for needle roller bearings with inner ring and in Table 7 for needle roller bearings without inner ring.

Table 2 — Dimension series 48

Dimensions in millimetres

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
110	120	140	30	1
120	130	150	30	1
130	145	165	35	1,1
140	155	175	35	1,1
150	165	190	40	1,1
160	175	200	40	1,1
170	185	215	45	1,1
180	195	225	45	1,1
190	210	240	50	1,5
200	220	250	50	1,5
220	240	270	50	1,5

Table 2 (continued)

Complete bearings and bearings without inner ring				
<i>d</i>	<i>F<sub>w</sub></i>	<i>D</i>	<i>B and C</i>	<i>r<sub>s</sub></i> min.
240	265	300	60	2
260	285	320	60	2
280	305	350	69	2
300	330	380	80	2,1
320	350	400	80	2,1
340	370	420	80	2,1
360	390	440	80	2,1
380	415	480	100	2,1

Table 3 — Dimension series 49

Dimensions in millimetres

Complete bearings and bearings without inner ring				
<i>d</i>	<i>F<sub>w</sub></i>	<i>D</i>	<i>B and C</i>	<i>r<sub>s</sub></i> min.
5	7	13	10	0,15
6	8	15	10	0,15
7	9	17	10	0,15
8	10	19	11	0,2
9	12	20	11	0,3
10	14	22	13	0,3
12	16	24	13	0,3
15	20	28	13	0,3
17	22	30	13	0,3
20	25	37	17	0,3
22	28	39	17	0,3
25	30	42	17	0,3
28	32	45	17	0,3
30	35	47	17	0,3
32	40	52	20	0,6
35	42	55	20	0,6
40	48	62	22	0,6
45	52	68	22	0,6
50	58	72	22	0,6
55	63	80	25	1
60	68	85	25	1
65	72	90	25	1
70	80	100	30	1
75	85	105	30	1
80	90	110	30	1
85	100	120	35	1,1
90	105	125	35	1,1

Table 3 (continued)

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
95	110	130	35	1,1
100	115	140	40	1,1
110	125	150	40	1,1
120	135	165	45	1,1
130	150	180	50	1,5
140	160	190	50	1,5
150	170	210	60	2
160	180	220	60	2
170	190	230	60	2
180	205	250	69	2
190	215	260	69	2
200	225	280	80	2,1
220	245	300	80	2,1
240	265	320	80	2,1
260	290	360	100	2,1
280	310	380	100	2,1
300	340	420	118	3
320	360	440	118	3
340	380	460	118	3
360	400	480	118	3
380	430	520	140	4
400	450	540	140	4
420	470	560	140	4
440	490	600	160	4

Table 4 — Dimension series 59

Dimensions in millimetres

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
12	16	24	16	0,3
15	20	28	18	0,3
17	22	30	18	0,3
20	25	37	23	0,3
22	28	39	23	0,3
25	30	42	23	0,3
28	32	45	23	0,3
30	35	47	23	0,3
32	40	52	27	0,6
35	42	55	27	0,6
40	48	62	30	0,6

Table 4 (continued)

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
45	52	68	30	0,6
50	58	72	30	0,6
55	63	80	34	1
60	68	85	34	1
65	72	90	34	1
70	80	100	40	1
75	85	105	40	1
80	90	110	40	1
85	100	120	46	1,1
90	105	125	46	1,1
95	110	130	46	1,1
100	115	140	54	1,1
105	120	145	54	1,1
110	125	150	54	1,1
120	135	165	60	1,1
130	150	180	67	1,5
140	160	190	67	1,5

Table 5 — Dimension series 69

Dimensions in millimetres

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
10	14	22	22	0,3
12	16	24	22	0,3
15	20	28	23	0,3
17	22	30	23	0,3
20	25	37	30	0,3
22	28	39	30	0,3
25	30	42	30	0,3
28	32	45	30	0,3
30	35	47	30	0,3
32	40	52	36	0,6
35	42	55	36	0,6
40	48	62	40	0,6
45	52	68	40	0,6
50	58	72	40	0,6
55	63	80	45	1
60	68	85	45	1
65	72	90	45	1
70	80	100	54	1

Table 5 (continued)

Complete bearings and bearings without inner ring				
$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min.
75	85	105	54	1
80	90	110	54	1
85	100	120	63	1,1
90	105	125	63	1,1
95	110	130	63	1,1
100	115	140	71	1,1

Table 6 — Special series dimensions for needle roller bearings with inner ring

Dimensions in millimetres

$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min. <sup>a</sup>
5	8	15	12	0,15
5	8	15	16	0,15
6	9	16	12	0,15
6	9	16	16	0,15
7	10	17	12	0,15
7	10	17	16	0,15
9	12	19	12	0,3
9	12	19	16	0,3
9	15	26	16	0,3
10	14	22	16	0,3
10	14	22	20	0,3
12	16	24	20	0,3
15	19	27	16	0,3
15	19	27	20	0,3
15	22	35	20	0,6
17	21	29	16	0,3
17	21	29	20	0,3
17	24	37	20	0,6
20	24	32	16	0,3
20	24	32	20	0,3
20	28	42	20	0,6
22	26	34	16	0,3
22	26	34	20	0,3
25	29	38	20	0,3
25	29	38	30	0,3
25	32	47	22	0,3
28	32	42	20	0,3
28	32	42	30	0,3
30	35	45	20	0,3

<sup>a</sup> Chamfer dimensions  $r_s$  min. are selected minimum values which are used in major manufacturers. It is recommended to contact manufacturers for actual chamfer dimensions.

Table 6 (continued)

<i>d</i>	<i>F<sub>w</sub></i>	<i>D</i>	<i>B and C</i>	<i>r<sub>s</sub></i> min. <sup>a</sup>
30	35	45	30	0,3
30	37	52	22	0,6
32	37	47	20	0,3
32	37	47	30	0,3
35	40	50	20	0,3
35	40	50	30	0,3
35	43	58	22	0,6
38	43	53	20	0,3
38	43	53	30	0,3
40	45	55	20	0,3
40	45	55	30	0,3
40	50	65	22	1
42	47	57	20	0,3
42	47	57	30	0,3
45	50	62	25	0,3
45	50	62	35	0,3
45	55	72	22	0,6
50	55	68	25	0,3
50	55	68	35	0,3
50	60	80	28	1,1
55	60	72	25	0,3
55	60	72	35	0,3
55	65	85	28	1,1
60	68	82	25	0,6
60	68	82	35	0,6
60	70	90	28	1,1
65	73	90	25	0,6
65	73	90	35	0,6
65	75	95	28	1,1
70	80	95	25	1
70	80	95	35	1
75	85	105	25	1
75	85	105	35	1
80	90	110	25	1
80	90	110	35	1
80	95	115	32	1
85	95	115	26	1
85	95	115	36	1
90	100	120	26	1
90	100	120	36	1
95	105	125	26	1

<sup>a</sup> Chamfer dimensions *r<sub>s</sub>* min. are selected minimum values which are used in major manufacturers. It is recommended to contact manufacturers for actual chamfer dimensions.

Table 6 (continued)

$d$	$F_w$	$D$	$B$ and $C$	$r_s$ min. <sup>a</sup>
95	105	125	36	1
100	110	130	30	1
100	110	130	40	1
100	115	135	32	1,1

<sup>a</sup> Chamfer dimensions  $r_s$  min. are selected minimum values which are used in major manufacturers. It is recommended to contact manufacturers for actual chamfer dimensions.

STANDARDSISO.COM : Click to view the full PDF of ISO 1206:2018

Table 7 — Special series dimensions for needle roller bearings without inner ring

Dimensions in millimetres

$F_w$	$D$	$C$	$r_s$ min. <sup>a</sup>
5	10	10	0,15
5	10	12	0,15
6	12	10	0,15
6	12	12	0,15
7	14	10	0,15
7	14	12	0,15
15	23	16	0,3
15	23	20	0,3
17	25	16	0,3
17	25	20	0,3
18	26	13	0,3
18	26	16	0,3
18	26	20	0,3
20	28	16	0,3
20	28	20	0,3
20	32	20	0,3
22	30	16	0,3
22	30	20	0,3
25	33	16	0,3
25	33	20	0,3
25	38	20	0,3
28	37	20	0,3
28	37	30	0,3
30	40	20	0,3
30	40	30	0,3
30	45	22	0,6
35	50	22	0,6
38	48	20	0,3
38	48	30	0,3
40	55	22	0,6
42	52	20	0,3
42	52	30	0,3
45	58	20	0,6
45	60	22	0,6
55	70	22	0,6
60	75	22	0,6
65	78	35	0,6
65	82	25	0,6
70	85	25	0,6
70	85	35	0,6

<sup>a</sup> Chamfer dimensions  $r_s$  min. are selected minimum values which are used in major manufacturers. It is recommended to contact manufacturers for actual chamfer dimensions.

Table 7 (continued)

$F_w$	$D$	$C$	$r_s$ min. <sup>a</sup>
70	88	25	0,6
75	92	25	0,6
75	92	35	0,6
75	95	30	1
95	115	30	1

<sup>a</sup> Chamfer dimensions  $r_s$  min. are selected minimum values which are used in major manufacturers. It is recommended to contact manufacturers for actual chamfer dimensions.

## 6 Tolerances

### 6.1 General

In [Tables 8](#) to [10](#), the symbols U and L are used as follows.

U = upper limit deviation

L = lower limit deviation

### 6.2 Tolerances for complete bearing and bearing without inner ring

See [Tables 8](#) to [10](#).

**Table 8 — Inner ring: tolerance class normal**

Limit deviations and tolerance values in micrometres

$d$ mm		$t_{\Delta dmp}$		$t_{Vdmp}$	$t_{Kia}$	$t_{\Delta Bs}$		$t_{VBs}$
>	≤	U	L			U	L	
2,5	10	0	-8	6	10	0	-120	15
10	18	0	-8	6	10	0	-120	20
18	30	0	-10	8	13	0	-120	20
30	50	0	-12	9	15	0	-120	20
50	80	0	-15	11	20	0	-150	25
80	120	0	-20	15	25	0	-200	25
120	180	0	-25	19	30	0	-250	30
180	250	0	-30	23	40	0	-300	30
250	315	0	-35	26	50	0	-350	35
315	400	0	-40	30	60	0	-400	40
400	500	0	-45	34	65	0	-450	50

**Table 9 — Outer ring: tolerance class normal**

Limit deviations and tolerance values in micrometres

D mm		$t_{\Delta Dmp}$		$t_{VDmp}$	$t_{Kea}$	$t_{\Delta Cs}$	$t_{VCs}$
>	≤	U	L			U	L
6	18	0	-8	6	15	Identical to $t_{\Delta Bs}$ and $t_{VBs}$ of inner ring of same bearing <sup>a</sup>	
18	30	0	-9	7	15		
30	50	0	-11	8	20		
50	80	0	-13	10	25		
80	120	0	-15	11	35		
120	150	0	-18	14	40		
150	180	0	-25	19	45		
180	250	0	-30	23	50		
250	315	0	-35	26	60		
315	400	0	-40	30	70		
400	500	0	-45	34	80		
500	630	0	-50	38	100		

<sup>a</sup> For bearings without inner ring, the values for the corresponding bearing with inner ring apply.

**Table 10 — Bore diameter of needle roller complement of bearings without inner ring**

Limit deviations in micrometres

$F_w$ mm		$t_{\Delta Fws}$	
>	≤	U	L
3	6	+18	+10
6	10	+22	+13
10	18	+27	+16
18	30	+33	+20
30	50	+41	+25
50	80	+49	+30
80	120	+58	+36
120	180	+68	+43
180	250	+79	+50
250	315	+88	+56
315	400	+98	+62
400	500	+108	+68

## 7 Radial internal clearance

Radial internal clearance of complete bearings is the arithmetical mean of the radial distances through which one of the rings may be displaced relative to the other, from one eccentric extreme position to the diametrically opposite extreme position, in different angular directions and without being subjected to any external load.

Values for radial internal clearance of complete bearings are given in ISO 5753-1.