
**Plain bearings — Hydrodynamic plain
thrust pad bearings under steady-state
conditions**

Part 3:

**Guide values for the calculation of thrust
pad bearings**

*Paliers lisses — Butées hydrodynamiques à patins géométrie fixe
fonctionnant en régime stationnaire*

*Partie 3: Paramètres opérationnels admissibles pour le calcul des butées
à segments*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 12131-3:2001

© ISO 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Guide values for avoiding damage caused by wear	1
4 Guide values to avoid mechanical overloading	2
5 Guide values to avoid thermal overloading	4
Bibliography.....	5

STANDARDSISO.COM : Click to view the full PDF of ISO 12131-3:2001

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 12131 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 12131-3 was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 4, *Methods of calculation of plain bearings*.

ISO 12131 consists of the following parts, under the general title *Plain bearings — Hydrodynamic plain thrust pad bearings under steady-state conditions*:

- *Part 1: Calculation of thrust pad bearings*
- *Part 2: Functions for the calculation of thrust pad bearings*
- *Part 3: Guide values for the calculation of thrust pad bearings*

Introduction

In order to achieve that pad thrust bearings calculated in accordance with ISO 12131-1 are sufficiently reliable in operation, it is necessary that the calculated operational parameters h_{\min} , T_B or T_2 and \bar{p} do not fall below or exceed the guide values h_{\lim} , T_{\lim} and \bar{p}_{\lim} .

For limiting cases at high specific loads and/or high rotational frequencies, more accurate calculations are necessary taking into consideration thermal, elastic, hydrodynamic and/or turbulence effects.

The guide values represent limiting values in the tribological system plain bearing unit which are dependent on geometry and technology. These are empirical values which still give sufficient reliability in operation even when subjected to slight disturbing influences (see clause 4 of ISO 12131-1:2001).

The empirical values given can be modified for specific fields of application.

STANDARDSISO.COM : Click to view the full PDF of ISO 12131-3:2001

Plain bearings — Hydrodynamic plain thrust pad bearings under steady-state conditions

Part 3: Guide values for the calculation of thrust pad bearings

1 Scope

This part of ISO 12131 specifies guide values for avoiding damage to thrust-pad bearings in service.

The explanation of the symbols as well as examples for calculation are given in ISO 12131-1.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 12131. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 12131 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 4381, *Plain bearings — Lead and tin casting alloys for multilayer plain bearings.*

ISO 4382-1, *Plain bearings — Copper alloys — Part 1: Cast copper alloys for solid and multilayer thick-walled plain bearings.*

ISO 4382-2, *Plain bearings — Copper alloys — Part 2: Wrought copper alloys for solid plain bearings.*

ISO 4383, *Plain bearings — Multilayer materials for thin-walled plain bearings.*

ISO 12131-1:2001, *Plain bearings — Hydrodynamic plain thrust bearings under steady-state conditions — Part 1: Calculation of thrust pad bearings.*

3 Guide values for avoiding damage caused by wear

To achieve minimum wear and low susceptibility to failure full lubrication of the plain bearing unit is aimed at by taking into account the minimum permissible lubricant film thickness h_{lim} . The lubricant should be free from dirt as this may result in increasing wear, scoring and local overheating which would impair the correct functioning of the plain bearing. If necessary, the lubricant has to be filtered.

The minimum lubricant film thickness $h_{lim,tr}$ as a characteristic value for the transition into mixed lubrication (see 5.7 of ISO 12131-1:2001) can be determined in accordance with ^[1] using the following empirical equation:

$$h_{lim,tr} = \sqrt{\frac{D \times R_z}{3\,000}} \quad (1)$$

This simple equation takes into account that in general machining tolerances increase with increasing size of the work piece.

As in this case, however, the machining method and the actual condition of the machine tools have a great influence, the value $h_{lim,tr}$ calculated on this basis is of only limited information value.

Faulty manufacturing of shafts, flanges or thrust collars and the exceeding of permissible tolerances rapidly results in failure of the plain thrust bearings.

Further, it is of importance how long a machine is operated under mixed lubrication during starting and stopping. For higher sliding velocities it is suitable to also increase the minimum permissible lubricant film thicknesses for standard operation so that, e.g. during stopping the range of mixed lubrication is not reached too quickly.

Guide values for the minimum permissible lubricant film thickness h_{lim} may be calculated as follows:

$$h_{lim} = C \times \sqrt{U \times D \times \frac{F_{st}}{F}} \quad (2)$$

with $C = 1,6 \times 10^{-5}$ up to $6,3 \times 10^{-5}$ and with F_{st}/F , ratio between the load carrying capacity under stationary conditions F_{st} and the bearing force F at nominal rotational frequency.

When equation (2) is used it is to be observed that

$$h_{lim} > h_{lim,tr} \quad (3)$$

It is recommended that $h_{lim} \geq 1,25 \times h_{lim,tr}$

Empirical values for h_{lim} are given in Tables 1 and 2.

4 Guide values to avoid mechanical overloading

The maximum permissible specific bearing load \bar{p}_{lim} results from the requirement that deformation of the sliding surfaces shall lead neither to an impairment of the correct functioning nor to cracks. Besides the composition of the bearing material there is still a great number of other decisive influencing factors such as, e.g. the manufacturing process, the material structure, the thickness of bearing material as well as the shape and type of the bearing backing. Irrespective of this, it has to be checked whether there is already full loading during starting. If the specific bearing load during starting $\bar{p} > 3 \text{ N/mm}^2$, a hydrostatic arrangement shall be provided, if appropriate, otherwise wear on the sliding surfaces may occur. The data given in Table 3 are general empirical values for \bar{p}_{lim} .

Table 1 — Guide values for the minimum permissible lubricant film thickness h_{lim} for $F_{st}/F = 1$, calculated with $C = 2 \times 10^{-5}$

Mean sliding diameter D (thrust ring diameter) mm		Mean sliding velocity of thrust collar U m/s					
		$1 \leq U \leq 2,4$	$2,4 < U \leq 4$	$4 < U \leq 6,3$	$6,3 < U \leq 10$	$10 < U \leq 24$	$24 < U \leq 40$
		Minimum permissible lubricant film thickness h_{lim} μm					
24	63	8	8	9,5	12	17	24
63	160	13	13	15	19	28	38
160	400	20	20	24	30	44	60
400	1 000	32	32	38	48	69	95

Table 2 — Guide values for the minimum permissible lubricant film thickness h_{lim} for $F_{st}/F = 0,25$, calculated with $C = 2 \times 10^{-5}$

Mean sliding diameter D (thrust ring diameter) mm		Mean sliding velocity of thrust collar U m/s					
		$1 \leq U \leq 2,4$	$2,4 < U \leq 4$	$4 < U \leq 6,3$	$6,3 < U \leq 10$	$10 < U \leq 24$	$24 < U \leq 40$
		Minimum permissible lubricant film thickness h_{lim} μm					
24	63	8	8	8	8	8,6	12
63	160	13	13	13	13	14	19
160	400	20	20	20	20	22	30
400	1 000	32	32	32	34	34	47

For $F_{st}/F = 0$, the values of the first column in Tables 1 and 2 are valid independent of the sliding velocity.

Table 3 — Guide values for the maximum permissible specific bearing load \bar{p}_{lim}

Bearing material group ^a	\bar{p}_{lim} MPa ^b
Pb and Sn alloys	5 (15)
CuPb alloys	7 (20)
CuSn alloys	7 (25)
AlSn alloys	7 (18)
AlZn alloys	7 (20)

^a For materials see ISO 4381, ISO 4382-1, ISO 4382-2 and ISO 4383.

^b So far the values in parentheses have been used in particular cases only. Exceptionally they may be permitted for specific operating conditions, e.g. for very low sliding velocities. 1 MPa = 1 N/mm².