
Plain bearings — Quality characteristics — Statistical process control (SPC)

Paliers lisses — Caractéristiques de qualité — Contrôle statistique du procédé (CSP)

STANDARDSISO.COM : Click to view the full PDF of ISO 12302:2017



STANDARDSISO.COM : Click to view the full PDF of ISO 12302:2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 SPC methods	1
5 Selection of SPC quality characteristics	1
6 Geometric quality characteristics	2
7 Material quality characteristics	4

STANDARDSISO.COM : Click to view the full PDF of ISO 12302:2017

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 5, *Quality analysis and assurance*.

This second edition cancels and replaces the first edition (ISO 12302:1993), which has been technically revised.

Plain bearings — Quality characteristics — Statistical process control (SPC)

1 Scope

This document specifies for plain bearings (except thick-walled half-bearings) those quality characteristics in accordance with ISO 12301 which can be used to regulate and control a production process on the basis of statistical process control (SPC).

It covers dimensional variables but does not take account of attributes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12301, *Plain bearings — Quality control techniques and inspection of geometrical and material quality characteristics*

3 Terms and definitions

For the purposes of this document, the following definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

quality characteristic

characteristic by means of which the quality of a plain bearing is assessed

3.2

statistical process control

SPC

control of quality characteristics of plain bearings during the production process by means of statistical techniques in order to comply with quality requirements

4 SPC methods

The applied statistical methods used to achieve control of a production process may be different and thus are to be agreed upon between the manufacturer and customer.

5 Selection of SPC quality characteristics

Depending on the intended purpose, function, etc. of the plain bearings to be used, the manufacturer and customer shall select and stipulate the particular characteristics for SPC according to [Clause 6](#).

It should be noted that the designated characteristics in the matrix of [Clause 6](#) have been prepared as a guide.

6 Geometric quality characteristics

The quality characteristics are classified into three groups: preferred, optional or unsuitable.

Following the order of the specified characteristics in accordance with ISO 12301, these quality characteristics are listed in the form of a matrix as:

- preferred with “yes”;
- optional with “(yes)”;
- unsuitable with “no”;
- not relevant with “—”.

Those quality characteristics which are marked with “(yes)” and “no” are accompanied by an explanation in the column “remarks” in [Table 1](#).

A horizontal dash (—) in a column means that this characteristic is not relevant for the specific type of plain bearing.

Table 1 — Geometric quality characteristics

Subclause No. (according to ISO 12301)	Quality characteristic	Type of plain bearing						Remarks
		Thin-walled halfbearing a	Wrapped bush b	Unsplit metallic bush c	Solid polymer bush d	Sintered bush e	Thrust washer (ring and half) f	
6.1	Wall thickness							
6.1.1	Line measurement	no	no	no	no	no	—	a and b to e : There is an unlimited number of values on a single measuring line ranging between minimum and maximum
6.1.2	Point measurement (defined)	yes	(yes)	yes	yes	(yes)	yes	b : Only where it is possible to measure at predetermined points e : For closed tolerance requirement, 100 % grading may be requested as an alternative to SPC
6.2	Outside diameter	—	yes	yes	yes	yes	(yes)	f : Blanking tool; tool checking by means of initial product acceptance with each order

Table 1 (continued)

Subclause No. (according to ISO 12301)	Quality characteristic	Type of plain bearing						Remarks
		Thin-walled half-bearing a	Wrapped bush b	Unsplit metallic bush c	Solid polymer bush d	Sintered bush e	Thrust washer (ring and half) f	
6.3	Inside diameter	—	(yes)	yes	yes	yes	(yes)	b : Normally determined by wall thickness and outside diameter f : Blanking tool; tool checking by means of initial product acceptance with each order
6.4	Width	(yes)	(yes)	(yes)	(yes)	(yes)	—	a and b to e : Not a primary characteristic
6.5	Locating features	no	—	—	—	—	no	a and f : Are only locating aids
6.6	Lubricant feed and distribution features	no	no	no	no	—	no	a , b to d and f : Not a primary characteristic
6.7	Surface conditions	no	no	no	no	no	no	a and b to f : No Gaussian distribution of measured values
6.8	Crush height	yes	—	—	—	—	—	
6.9	Free spread	(yes)	—	—	—	—	—	a : Not a primary characteristic
6.10	Straightness of sliding surface	no	—	—	—	—	—	a : Graphical evaluation in most cases
6.11	Joint face taper	(yes)	—	—	—	—	—	a : Not a primary characteristic
6.12	Back contact (proportion of surface area)	no	—	—	—	—	—	a : Attribute (qualitative) characteristic
6.13	Joint displacement	—	(yes)	—	—	—	—	b : Will be adjusted when fitting the bush into the housing bore; attribute characteristic
6.14	Height of thrust half-washer (thickness)	—	—	—	—	—	(yes)	f : Blanking tool; tool checking by means of initial product acceptance with each order
6.15	Flatness	—	—	—	—	—	no	f : Attribute (qualitative) characteristic

Table 1 (continued)

Subclause No. (according to ISO 12301)	Quality characteristic	Type of plain bearing						Remarks
		Thin-walled halfbearing a	Wrapped bush b	Unsplit metallic bush c	Solid polymer bush d	Sintered bush e	Thrust washer (ring and half) f	
6.16	Flange diameter	(yes)	(yes)	(yes)	(yes)	(yes)	—	a and b to e: Not a primary characteristic
6.17	Distance between flanges	(yes)	(yes)	(yes)	(yes)	(yes)	—	a and b to e: Not a primary characteristic
6.18	Flange thickness	(yes)	(yes)	(yes)	(yes)	(yes)	—	a and b to e: Measuring point shall be defined
6.19	Perpendicularity (squareness) of flange	(yes)	(yes)	(yes)	(yes)	(yes)	—	a and b to e: Not a primary characteristic
6.20	Geometric deviations	—	—	(yes)	(yes)	(yes)	—	c, d and e: Not a primary characteristic

7 Material quality characteristics

Control of the material manufacturing processes depends on a large number of parameters which involve “process-knowledge”. The manufacturer shall decide which parameters are to be checked using statistical techniques in accordance with customer requirements.