

---

---

**Earth-moving machinery — Operation  
and maintenance — Maintainability  
guidelines**

*Engins de terrassement — Emploi et entretien — Lignes directrices  
pour la maintenabilité*

STANDARDSISO.COM : Click to view the full PDF of ISO 12510:2004



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 12510:2004

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

**Contents**

Page

<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 General</b> .....	<b>1</b>
<b>5 Location of items</b> .....	<b>2</b>
<b>6 Access system</b> .....	<b>3</b>
<b>7 Access apertures</b> .....	<b>3</b>
<b>8 Covers</b> .....	<b>4</b>
<b>9 Tools</b> .....	<b>4</b>
<b>10 Service instrumentation</b> .....	<b>4</b>
<b>11 Labelling</b> .....	<b>4</b>
<b>12 Accompanying documentation</b> .....	<b>5</b>
<b>Annex A</b> (informative) <b>Matrixes of maintainability</b> .....	<b>7</b>
<b>Bibliography</b> .....	<b>11</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12510 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 3, *Operation and maintenance*.

STANDARDSISO.COM : Click to view the full PDF of ISO 12510:2004

# Earth-moving machinery — Operation and maintenance — Maintainability guidelines

## 1 Scope

This International Standard establishes guidelines for the incorporation of design features that promote safety, efficiency, reliability and ease of maintenance and service operations on earth-moving machinery as defined in ISO 6165.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6165, *Earth-moving machinery — Basic types — Vocabulary*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### test points

points which provide access to information about the status of the machine, either for routine checking of correct operation or for isolating malfunctions

### 3.2

#### service points

points which provide access for lubrication, filling, draining or similar servicing operations

## 4 General

Machines should be designed and built so that routine maintenance operations can be carried out safely, whenever possible with the engine stopped. Where it is only possible to undertake inspection or maintenance with the engine running, arrangements should be made to minimize the risk of contact with moving or hot parts.

Annex A gives examples of matrixes of maintainability for different categories of components and from different perspectives.

## 5 Location of items

### 5.1 Components

**5.1.1** Where the visual inspection of, for example, oil levels and gauges is required, the test points should be located so that personnel can see them without the removal of panels or other components.

**5.1.2** Components requiring routine servicing should be located away from parts of the machine which may have high temperatures.

**5.1.3** Components needing frequent servicing or replacement should be located in accessible locations where no other components need to be removed to give access to them.

**5.1.4** For those maintenance tasks which have a critical visual requirement, components should be located so that they can be easily seen and easily illuminated with a lamp.

**5.1.5** Components should be designed and located so that they can be installed and removed along a straight or slightly curved path, rather than through an angled path.

**5.1.6** Easily damaged components should be located away from areas where frequent or heavy maintenance work is necessary or have protective guards.

**5.1.7** Components intended to be manually lifted out of position should be located where they can be pulled out. Where high levels of pulling force are required, provision should be made above the component and within its recess for bracing with one hand while the other is used for pulling. In this situation, a handle for pulling the component should be considered.

**5.1.8** Where components cannot be located for direct accessibility, pull-out drawers or racks should be considered. For heavy components, these should be provided with limit stops which are easily released so as to prevent components being dropped.

**5.1.9** Components normally maintained by the same maintenance operative (i.e. fitter, electrician, engineer) should be grouped together whenever possible.

**5.1.10** If applicable, fuses should be grouped together in a single, readily accessible location so that they can be seen and replaced without the removal of parts or sub-assemblies. It should be possible to replace fuses without the use of tools. Spare fuses should be located adjacent to the fuse holder and labelled for fuse value. The fuses may be covered by a guard, provided that it can be removed without tools.

### 5.2 Test and service points

**5.2.1** Accessible test points should be provided for checking for correct operation and for fault diagnosis.

**5.2.2** Where possible, test points should be grouped together in a layout which reflects the layout of the units being tested.

**5.2.3** Test points should be located close to the controls and displays used in the checking operation, so that personnel can operate the controls and observe the displays simultaneously.

**5.2.4** Test and service points should be located on those parts of the equipment which will be most accessible when the equipment is assembled and installed on the machine.

**5.2.5** Where possible, test and service points should be located where they do not require the removal of any components or items in order to gain access.

**5.2.6** Test and service points should be located so that all points in a given procedure can be accessed through one opening.

- 5.2.7** Test and service points should be located away or shielded from unshielded moving parts or other dangerous areas.
- 5.2.8** Lubrication points should be located so that they are easily accessible using guide tubes or extended fittings if necessary. Grouped lubrication points are preferable.
- 5.2.9** Where possible, access to lubrication points should not require the removal of covers.
- 5.2.10** Lubrication fittings should conform to the requirements of ISO 6392-1.
- 5.2.11** Dipsticks and other such level indicators should be located in an accessible position and should be capable of being fully withdrawn without touching other pieces of equipment.
- 5.2.12** Fluid replenishing points should be located to minimize the consequence of spillage that results in damaged equipment.
- 5.2.13** Drain points should be visible and accessible to operate, and be located within reach of personnel and at such a place where mud or other debris will not clog them.
- 5.2.14** Drain points should be placed where they will not drain on personnel or sensitive equipment.
- 5.2.15** Drain points should be located to permit fluid drainage directly into a waste container.
- 5.2.16** Drain, fill and level plugs should conform to the requirements of ISO 6302.

## **6 Access system**

Adequate access systems conforming to the requirements of ISO 2867 should be provided to the maintenance areas.

## **7 Access apertures**

### **7.1 Location**

- 7.1.1** Access should be provided to all components, test and service points and other items which require routine testing, servicing, adjusting, replacement or repair.
- 7.1.2** Wherever possible, access apertures should be located so that only one cover needs to be removed to replace or service any single component.
- 7.1.3** Apertures should be designed and located to minimize the occasions when it becomes necessary to remove components or cables in order to reach any item requiring servicing or replacement.
- 7.1.4** Apertures should align with the components being maintained (see 5.1.4 and 5.1.5).
- 7.1.5** Apertures should be located to permit access to the related displays, controls and test points.

### **7.2 Size and shape**

- 7.2.1** The size and shape of an aperture should be that which provides the passage of components, allows the specified method of grasping of components during removal and refit, and provides sufficient clearance for the use of hand and powered tools.
- 7.2.2** Minimum aperture dimensions should be in accordance with ISO 2860.

## 8 Covers

- 8.1 Hinged covers should open sufficiently to provide enough space for all maintenance tasks.
- 8.2 Wherever possible, all cover fasteners should be of the same size and type.
- 8.3 The number of fasteners holding a hatch cover should be minimized and, whenever possible, hinges and quick-release fasteners should be used.
- 8.4 Where handles can cause a safety hazard, they should be recessed or hinged.
- 8.5 Wherever possible, handles should be located relative to the centre of gravity of the cover to prevent it swinging or tilting when lifted.
- 8.6 Handle location should take into consideration the postures which need to be adopted during lifting so that, for example, excessive reach can be prevented.
- 8.7 Handles or covers should have no sharp edges or protrusions.

## 9 Tools

- 9.1 Where possible, machinery should be designed so that on-site, routine maintenance and adjustment work can be carried out using tools in accordance with ISO 4510-1.
- 9.2 Provision should be made on the machine for secure and accessible storage of the hand tools required for routine maintenance.

## 10 Service instrumentation

- 10.1 Machinery should be designed to facilitate the use of service instrumentation in accordance with ISO 6012.
- 10.2 Diagnostic ports should conform to the requirements of ISO 8925.

## 11 Labelling

### 11.1 General

- 11.1.1 Adequate labels should be provided to assist maintenance activities for identification and instruction.
- 11.1.2 Labels should be located where they will not be obliterated, for example, by grease or dirt.
- 11.1.3 Labels should be located so they can be read while performing the tasks to which they pertain.
- 11.1.4 Labels which read horizontally are preferable to those which read vertically.
- 11.1.5 The choice of colour should optimize contrast to enhance legibility for information or instructional type labels.
- 11.1.6 Materials should be used which will minimize the risk of loss of label information.
- 11.1.7 Labels should be placed in such locations as to minimize risk of damage during machine operation or from the environment.

**11.1.8** Electrical wires and cables should be identified and marked in accordance with the requirements of ISO 9247.

**11.1.9** When circumstances at the operating position make the provision of individual labels difficult, individual labels may be replaced by a composite label.

## **11.2 Component identification**

**11.2.1** Component serial number labels should be located in such a manner as to maximize visibility.

**11.2.2** Labels should be located on a permanent structure of the component not normally considered a replaceable item and which does not readily lend itself to substitution.

## **11.3 Instructions**

**11.3.1** Instructions as to the task procedures and the requirements should be presented on a label when the task consists of a series of steps which may be confused if left to memory and where it is not possible for the operator to refer to the maintenance manual or the required speed of operation precludes its use.

**11.3.2** When instructions applicable to the maintenance of a covered unit are labelled on the inside of a hinged cover, the lettering should be orientated so that it is readable when the cover is opened.

## **11.4 Warnings**

Warning labels should be provided which comply with ISO 9244.

## **11.5 Maintenance information**

Labels should use symbols conforming with ISO 6405-1 and ISO 6405-2.

## **12 Accompanying documentation**

### **12.1 General**

There should be three sets of written instructions, which should comply with ISO 6750:1984 as and when appropriate:

- an operator's manual (including a lubrication chart);
- a maintenance manual;
- a spare parts list.

### **12.2 Operator's manual**

The operator's manual should contain at least the following items:

- a description of the machine, with sketches;
- instructions for use of the machine, presented in an unambiguous manner;
- instructions for routine (e.g. daily) maintenance checks which could be made by the operator;
- instructions for transporting, handling and storage of the machine, and the equipment and attachments with which it is supplied.

### 12.3 Maintenance manual

The maintenance manual should contain the lists of operations (and their frequency) to be carried out on the machine other than those routine maintenance checks (see 12.2) necessary to maintain the machine in a safe and operable condition. The maintenance manual should include electrical, hydraulic and pneumatic circuit diagrams, whenever applicable.

### 12.4 Spare parts list

The spare parts list should contain all the related spare parts, together with unambiguous identification and information on the location of the part to be replaced.

### 12.5 Storage of documentation

The operator's manual and lubrication chart should be stored on the machine.

STANDARDSISO.COM : Click to view the full PDF of ISO 12510:2004

## Annex A (informative)

### Matrixes of maintainability

#### A.1 Components to be maintained

Components may be classified into two categories for maintenance purposes:

- a) **liquids (oil, fuel and water) and vapours:** fuel, coolant, lubricant oil (engine, torque converter, transmission, axle, final drive, swing device), hydraulic tank, air intake system, brake reservoir, window washer, cab ventilation system (filter), air conditioner (refrigerant, filter);
- b) **mechanical devices:** fan belt, cylinder/valve, chassis spring/shock absorber, tire/wheel, track roller/link and sprocket, recoil steering/ spring wheel, steering cylinder/linkage, steering (crawler), cutting edge/tooth, belts for air conditioner/ compressor/ condenser.

#### A.2 Definition of levels at each perspective

The components to be maintained (see A.1) may be taken into account at different levels, and from different perspectives, for example:

**a) working position:**

- level 1: standing or sitting above or alongside machine
- level 2: standing or sitting below machine
- level 3: lying down above or alongside machine
- level 4: looking up from below machine

**b) type of work:**

- level 1: maintained without removing a cover or a cap
- level 2: maintained by removing a cover or a cap without using any tool
- level 3: maintained by using only ISO 4510-1 and ISO 4510-2 tools
- level 4: maintained by using other special tool or device

**c) safety:**

- level 1: maintenance without a moving part and with no danger
- level 2: maintenance within a moving part and protected by a safety device (working e.g. under “boom” and on “track shoes”)
- level 3: maintenance without a safety device and risking injury if an indicated instruction is not followed correctly (e.g. maintenance of internal pressure, high temperature)
- level 4: maintenance without a safety device and risking serious injury or death if an indicated instruction is not followed correctly.

**A.3 Matrixes of maintainability**

Matrixes of maintainability can be established for the different categories of components to be maintained from different perspectives. See Tables A.1 and A.2.

**Table A.1 — Matrix of maintainability for liquids and vapours**

Perspective	Components to be maintained													
	Fuel	Coolant	Lubricant oil						Hydraulic tank <sup>a</sup>	Air intake system	Brake reservoir <sup>b</sup>	Window washer	Air conditioner	
			Engine	Torque converter	Transmission	Axle	Final drive	Swing device					Refrigerant	Filter
<b>A.1.1 Inspection</b>														
A.1.1.1 Working position	1	1	1	1	1	2	2	1	1	1	1	1	1	1
A.1.1.2 Type of work	1	2	2	2	2	3	3	2	1	2	2	2	2	2
A.1.1.3 Safety	1	3	2	2	2	2	2	2	2	2	2	2	2	2
A.1.1.4 Prevention of working errors — checking port should be covered to prevent dirt or sand from entering during checking	-	-	-	-	-	+	+	-	-	+	-	-	-	-
<b>A.1.2 Draining</b>														
A.1.2.1 Working position	2	2	2	2	2	2	2	2	2	-	-	-	-	-
A.1.2.2 Type of work	3	3	3	3	3	3	3	3	3	-	-	-	-	-
A.1.2.3 Safety	2	3	3	3	3	3	3	3	3					
A.1.2.4 Ease of work — Drain plug should be so protected as to prevent it from being worn or deformed by rock and sand.	+	+	-	-	-	+	+	-	-	-	-	-	-	-
A.1.2.5 Prevention of working errors — Only one drain port should be provided for each hydraulic unit. — All oil should drain from under the machine when inclined at 10° max. angle in all directions.	+	+	+	+	+	+	+	+	+	-	-	-	-	-
A.1.2.6 Environmental protection — Draining portion should be designed to drain all oil to a receptacle without spilling to surroundings. — There should be enough space under the drain port to place a receptacle having capacity to contain all drained oil.	+	+	+	+	+	+	+	+	+	-	-	-	-	-
A.1.2.7 Drain system should be so constructed as to control the drain flow.	+	-	+	+	+	+	-	+	-	-	-	-	-	-