

---

---

**Road vehicles — Liquefied natural gas  
(LNG) fuel system components —**

**Part 11:  
Fittings**

*Véhicules routiers — Équipements pour véhicules utilisant le gaz naturel liquéfié (GNL) comme combustible —*

*Partie 11: Raccords*

STANDARDSISO.COM : Click to view the full PDF of ISO 12614-11:2021



STANDARDSISO.COM : Click to view the full PDF of ISO 12614-11:2021



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Marking</b> .....	<b>2</b>
<b>5 Construction and assembly</b> .....	<b>2</b>
<b>6 Test</b> .....	<b>2</b>
6.1 Applicability.....	2
6.2 Hydrostatic strength.....	3
6.3 Continued operation.....	3
6.4 Vibration resistance.....	3
6.5 Pull-off.....	3
<b>Bibliography</b> .....	<b>5</b>

STANDARDSISO.COM : Click to view the full PDF of ISO 12614-11:2021

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects of gaseous fuels*.

This second edition cancels and replaces the first edition (ISO 12614-11:2014), which has been technically revised.

The main changes compared to the previous edition are as follows:

- editorial changes.

A list of all parts in the ISO 12614 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Road vehicles — Liquefied natural gas (LNG) fuel system components —

## Part 11: Fittings

### 1 Scope

This document specifies tests and requirements for the fittings, a liquefied natural gas fuel system component intended for use on the types of motor vehicles defined in ISO 3833.

This document is not applicable to the following:

- a) fuel containers;
- b) stationary gas engines;
- c) container mounting hardware;
- d) electronic fuel management;
- e) refuelling receptacles.

It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this document and tested according to the appropriate functional tests.

All references to pressure in this document are to be considered gauge pressures unless otherwise specified.

This document is based upon a working pressure for natural gas as a fuel of 1,6 MPa [16 bar<sup>1</sup>]. Other working pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, 2 MPa (20 bar) working pressure system will require pressures to be multiplied by 1,25.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12614-1, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 1: General requirements and definitions*

ISO 12614-2, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 2: Performance and general test methods*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12614-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

1) 1 bar = 0,1 MPa = 105 Pa; 1 MPa = 1 N/mm<sup>2</sup>.

— IEC Electropedia: available at <https://www.electropedia.org/>

## 4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark, or symbol;
- b) the model designation (part number);
- c) the working pressure or pressure and temperature range;
- d) the serial number or date code.

The following additional markings are recommended:

- i) the direction of flow (when necessary for correct installation);
- ii) the type of fuel;
- iii) electrical ratings (if applicable);
- iv) the symbol of the certification agency;
- v) the type approval number;
- vi) reference to this document (i.e. ISO 12614-11).

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

## 5 Construction and assembly

The fittings shall comply with the applicable provisions of ISO 12614-1 and ISO 12614-2 and with the tests specified in [Clause 6](#).

The fittings shall be compatible with rigid fuel line.

## 6 Test

### 6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).

**Table 1 — Tests applicable**

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this document
Hydrostatic strength	X	X	X (see <a href="#">6.2</a> )
Leakage	X	X	
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X	X	X (see <a href="#">6.3</a> )
Corrosion resistance	X	X	
Oxygen ageing	X	X	
Electrical over voltages			
Non-metallic material immersion	X	X	

Table 1 (continued)

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this document
Vibration resistance	X		X (see 6.4)
Brass material compatibility	X	X	
Pull-off	X		X (see 6.5)

## 6.2 Hydrostatic strength

The fitting shall be tested according to the procedure for testing hydrostatic strength specified in ISO 12614-2.

The test pressure shall be four times the working pressure.

NOTE The higher hydrostatic test pressure for the rigid fuel line than the other ISO 12614 series components is due to the necessary provisions to cope for eventual damage or abrasions under normal operation.

## 6.3 Continued operation

**6.3.1** Subject the fitting to continued operation for a total of 100 cycles. The fitting shall only be tested while connected with a rigid fuel line.

**6.3.2** Fittings shall be subjected to 25 connection/disconnection cycles. Fittings declared to the customer as single use may be tested per the manufacturer's specification. Single use fittings may be tested per manufacturers guidance.

**6.3.3** Perform the leakage test in accordance with ISO 12614-2:2021, Clause 6.

## 6.4 Vibration resistance

Vibrate the fittings, pressurized to their working pressure and sealed at both ends, for 30 min along each of the three orthogonal axes at the most severe resonant frequencies determined as follows:

- by an acceleration of 1,5g;
- within a sinusoidal frequency range of 10 Hz to 500 Hz;
- with a sweep time of 10 min.

At the completion of the test, the fittings shall not show any indication of fatigue or component damage and shall meet the leakage test requirements.

Following the vibration testing, perform the hydrostatic test in accordance with 6.2.

## 6.5 Pull-off

Test the fitting attached to its rigid fuel line and coupled to its mating part or parts, according to the following procedure and acceptance criterion. Secure the subject specimen in an appropriate test fixture, then statically apply a tensile load along the rigid fuel line axis at a maximum rate of 250 N/min until the rigid fuel line separates from the fitting.

## ISO 12614-11:2021(E)

The force,  $F$ , in Newtons, required to pull apart the rigid fuel line from its fitting shall be in minimum and calculated as:

$$F = (\pi \times d^2 \times P) / 10 \quad (1)$$

where

$d$  is the internal diameter, in millimetres;

$P$  is the pressure, in bar.

[Formula \(1\)](#) already includes a safety factor of four.

STANDARDSISO.COM : Click to view the full PDF of ISO 12614-11:2021