

INTERNATIONAL STANDARD

ISO
12646

First edition
2008-06-01

AMENDMENT 1
2010-09-01

Graphic technology — Displays for colour proofing — Characteristics and viewing conditions

AMENDMENT 1

*Technologie graphique — Affichages pour la réalisation d'épreuves en
couleur — Caractéristiques et conditions d'examen visuel*

AMENDEMENT 1

STANDARDSISO.COM : Click to view the full PDF of ISO 12646:2008/Amd 1:2010



Reference number
ISO 12646:2008/Amd.1:2010(E)

© ISO 2010

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 12646:2008/Amd 1:2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 12646:2008 was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

STANDARDSISO.COM : Click to view the full PDF of ISO 12646:2008/Amd.1:2010

STANDARDSISO.COM : Click to view the full PDF of ISO 12646:2008/Amd 1:2010

Graphic technology — Displays for colour proofing — Characteristics and viewing conditions

AMENDMENT 1

Page 1, Normative references

Remove the date of the normative reference, ISO 13655:—¹), and delete its footnote at the bottom of the page. Replace it with the following undated normative reference:

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

Page 4, 4.4

Replace the text by the following:

The display should be visually uniform when displaying flat white, grey and black images. When measured as described in 5.3, at a setting of R=G=B=255, all luminance values should be within 5 % of the luminance of the centre and shall be within 10 % of it. For R=G=B=128, all luminance values should be within 6,5 % of the luminance of the centre and shall be within 13 % of it. For R=G=B=64, all luminance values should be within 7,5 % of the luminance of the centre and shall be within 15 % of it. However, there should be no areas of significant visual non-uniformity between the points marked in Figure 2 regardless of the RGB level set.

For the entire display, measured at least at the positions stated in 5.3, the chromaticity of every neutral image (defined by equal digital values for R, G and B) shall be within a radius of 0,005 (in u' , v') from the chromaticity values measured at the centre of the display.

NOTE 1 The uniformity of chromaticity is specified in 4.8.

NOTE 2 There is no simple relationship between the chromaticity coordinates (u' , v') and colour differences. Therefore, specifying the chromaticity of neutral images in terms of a radius of 0,005 (in u' , v') results in a variation in colour difference as a function of CIE L^* . This corresponds to an average CIE 2000 colour difference (as defined in ISO 13655) of approximately 0,8 at a CIE L^* value of 5 and a difference of 4,0 at a CIE L^* of 95.

Page 6, 4.10

Replace the last paragraph with the following:

The measured tristimulus values shall be transformed to CIELAB values using the white point chosen by the software application vendor. The average of the CIE 2000 colour differences between these values and the CIELAB values intended to be displayed by the software characterizing the display (e.g. an ICC monitor profile) should not exceed 1 and shall not exceed 2. The maximum CIE 2000 colour differences between the individual values and the CIELAB values intended to be displayed by the software characterizing the display (e.g. an ICC monitor profile) should not exceed 3 and shall not exceed 6.

Page 7, 4.11

Replace third paragraph with the following:

In the contrast inversion test, for a given RGB drive state, and for all points on the display, the luminance at angles off the DVD should not exceed the luminance at the DVD.

Page 12, 5.6.1.2 f)

Replace the text with the following:

- f) The sampling interval should be 5 nm and shall not exceed 10 nm. The bandwidth, as defined in ISO 13655, shall be identical to the sampling interval. If the measurements are taken at sampling intervals smaller than 5 nm, the procedure for widening the bandwidth specified in ISO 13655 shall be used for deriving and reporting data at 5 nm intervals.

STANDARDSISO.COM : Click to view the full PDF of ISO 12646:2008/Amd.1:2010