

---

---

**Synchronous belt drives — Metric  
pitch, curvilinear profile systems G, H,  
R and S, belts and pulleys**

*Transmissions synchrones — Pas métrique, systèmes à denture  
curviligne G, H, R et S, courroies et poulies*

STANDARDSISO.COM : Click to view the full PDF of ISO 13050:2022



STANDARDSISO.COM : Click to view the full PDF of ISO 13050:2022



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative reference.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Symbols.....</b>	<b>1</b>
<b>5 Synchronous belt drive system types.....</b>	<b>2</b>
<b>6 Belt nomenclature.....</b>	<b>3</b>
<b>7 Pulley nomenclature.....</b>	<b>3</b>
<b>8 Profile system G.....</b>	<b>4</b>
8.1 Belt dimensions and tolerances.....	4
8.1.1 Belt tooth dimensions.....	4
8.1.2 Belt widths and tolerances.....	4
8.1.3 Pitch length measurement.....	5
8.2 Pulleys, profile system G.....	6
8.2.1 General.....	6
8.2.2 Generating tool rack.....	7
8.2.3 Pulley groove profile dimensions and tolerances.....	9
8.2.4 Pulley outside diameters.....	10
8.2.5 Pulley width.....	12
<b>9 Profile system H.....</b>	<b>13</b>
9.1 Belt dimensions and tolerances.....	13
9.1.1 Belt tooth dimensions.....	13
9.1.2 Belt widths and tolerances.....	14
9.1.3 Pitch length measurement.....	15
9.2 Pulleys, profile system H.....	17
9.2.1 General.....	17
9.2.2 Generating tool rack.....	17
9.2.3 Pulley groove profile dimensions and tolerances.....	21
9.2.4 Pulley outside diameters.....	22
9.2.5 Pulley width.....	25
<b>10 Profile system R.....</b>	<b>27</b>
10.1 Belt dimensions and tolerances.....	27
10.1.1 Belt tooth dimensions.....	27
10.1.2 Belt widths and tolerances.....	28
10.1.3 Pitch length measurement.....	28
10.2 Pulleys, profile system R.....	30
10.2.1 General.....	30
10.2.2 Generating tool rack.....	31
10.2.3 Pulley groove profile dimensions and tolerances.....	32
10.2.4 Pulley outside diameters.....	34
10.2.5 Pulley width.....	37
<b>11 Profile system S.....</b>	<b>38</b>
11.1 Belt dimensions and tolerances.....	38
11.1.1 Belt tooth dimensions.....	38
11.1.2 Belt widths and tolerances.....	39
11.1.3 Pitch length measurement.....	40
11.2 Pulleys, profile system S.....	42
11.2.1 General.....	42
11.2.2 Generating tool rack.....	42
11.2.3 Pulley groove profile dimensions and tolerances.....	43

11.2.4 Pulley outside diameters .....	44
11.2.5 Pulley width.....	46
<b>Annex A (informative) Belt pitch lengths and tolerances .....</b>	<b>48</b>
<b>Annex B (informative) Relationship between centre distance and belt pitch length .....</b>	<b>50</b>
<b>Annex C (informative) Pulley tolerances .....</b>	<b>52</b>
<b>Annex D (informative) Flange dimensions .....</b>	<b>55</b>
<b>Bibliography .....</b>	<b>56</b>

STANDARDSISO.COM : Click to view the full PDF of ISO 13050:2022

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 4, *Synchronous belt drives*.

This third edition cancels and replaces the second edition (ISO 13050:2014), which has been technically revised.

The main changes are as follows:

- in [Formulae \(1\) and \(2\)](#), “ $A_0$ ” has been added before the first square bracket;
- the formulae in the document have been renumbered and symbols are now used;
- the nomenclature has been changed in [Tables 1 and 14](#), and [Figures 1 and 11](#);
- belt width measurement methods were improved in [8.1.2](#), [9.1.2](#), [10.1.2](#), [11.1.2](#);
- total measuring forces are now for reference only in [8.1.3.2](#), [9.1.3.2](#), [10.1.3.2](#), [11.1.3.2](#);
- belt length measurement procedures were enhanced in [8.1.3.3](#), [9.1.3.3](#), [10.1.3.3](#), [11.1.3.3](#);
- the taper specification in [Annex C](#) was removed.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 13050:2022

# Synchronous belt drives — Metric pitch, curvilinear profile systems G, H, R and S, belts and pulleys

## 1 Scope

This document specifies the principal characteristics of metric pitch curvilinear synchronous endless belts and pulleys in G, H, R, and S profile systems for use in synchronous belt drives (also known in the past as timing belt drives, positive belt drives, gear belt drives) for mechanical power transmission and where positive indexing or synchronization can be required.

The principal belt and pulley characteristics include the following:

- a) nominal belt tooth dimensions;
- b) belt tooth pitch spacing;
- c) belt length and width dimensions and tolerances;
- d) belt length measurement specifications;
- e) pulley groove dimensions and tolerances;
- f) pulley diameter and width dimensions and tolerances;
- g) pulley quality specification.

## 2 Normative reference

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 254, *Belt drives — Pulleys — Quality, finish and balance*

ISO 5288, *Synchronous belt drives — Vocabulary*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5288 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

## 4 Symbols

For the purpose of this document, the symbols given in ISO 5288 and the following apply,

Symbol	Definition	Symbol	Definition
$a$	Pitch line differential	$h_r$	Reference rack tooth height

$2A$	Reference rack tooth angle	$h_t$	Tooth height
$b_f$	Minimum flanged pulley width	$L_p$	Belt pitch length
$b'_f$	Minimum unflanged pulley width	$n_g$	Number of grooves
$b_g$	Reference rack width at tooth tip	$P_b$	Tooth pitch
$b_r$	Width at groove crest	$r_a$	Radius at tooth tip
$b_t$	Reference rack width at tooth root	$r_r$	Radius at tooth root
$C$	Centre distance	$r_t$	Radius at the groove crest
$d$	Pitch diameter	$S$	Width at tooth root
$d_o$	Outside diameter	$2\beta$	Tooth angle
$h_d$	Total height of a double-sided belt	$2\phi$	Groove angle
$h_s$	Total height of a single-sided belt		

## 5 Synchronous belt drive system types

Four profile systems and 14 profiles for curvilinear synchronous drives are standardized.

### Profile system G

Profile G8M  
(Tooth/groove pitch 8 mm)

Profile G14M  
(Tooth/groove pitch 14 mm)

### Profile system H

Profile H3M  
(Tooth/groove pitch 3 mm)

Profile H5M  
(Tooth/groove pitch 5 mm)

Profile H8M  
(Tooth/groove pitch 8 mm)

Profile H14M  
(Tooth/groove pitch 14 mm)

### Profile system R

Profile R3M  
(Tooth/groove pitch 3 mm)

Profile R5M  
(Tooth/groove pitch 5 mm)

Profile R8M  
(Tooth/groove pitch 8 mm)

Profile R14M  
(Tooth/groove pitch 14 mm)

Profile R20M  
(Tooth/groove pitch 20 mm)

### Profile system S

Profile S8M  
(Tooth/groove pitch 8 mm)

Profile S14M  
(Tooth/groove pitch 14 mm)

Profile H20M  
(Tooth/groove pitch 20 mm)

## 6 Belt nomenclature

A belt is identified as follows:

- a) the belt length or pitch length in millimetres, e.g. 1 400 mm;
- b) the profile system, e.g. “G”, “H”, “R”, or “S”;
- c) the pitch or tooth pitch in millimetres, e.g. 14 mm;
- d) the width or belt width in millimetres, e.g. 40 mm (for Profile system S, the width in millimetres  $\times$  10);
- e) double-sided belts are designated by adding the letter “D” before the designation of the profile system.

EXAMPLE A synchronous belt in the above profile systems of 1 400 mm length, 14 mm pitch, and 40 mm wide is identified as follows:

### Profile system G

1400-G14M-40  
1400-DG14M-40

### Profile system R

1400-R14M-40  
1400-DR14M-40

### Profile system H

1400-H14M-40  
1400-DH14M-40

### Profile system S

1400-S14M-400  
1400-DS14M-400

## 7 Pulley nomenclature

A pulley is identified as follows:

- a) the letter “P” indicates a pulley;
- b) the number of grooves, e.g. 30;
- c) the profile system, e.g. “G”, “H”, “R”, or “S”;
- d) the pitch or groove pitch in millimetres, e.g. 14 mm;
- e) the width or belt width in millimetres, e.g. 40 mm (for profile system S, the width in millimetres  $\times$  10).

EXAMPLE A pulley in the above profile systems of 30 grooves, 14 mm pitch, and 40 mm wide is identified as follows:

### Profile system G

P30-R14M-40

### Profile system R

P30-G14M-40

### Profile system H

P30-H14M-40

### Profile system S

P30-S14M-400

## 8 Profile system G

### 8.1 Belt dimensions and tolerances


#### 8.1.1 Belt tooth dimensions

The nominal belt tooth dimensions are given in [Table 1](#) and shown in [Figure 1](#).

**Table 1 — Nominal tooth dimensions**

Dimensions in millimetres

Profile	Belt pitch	$S$	$h_s$	$h_t$	$r_r$	$A_o$	$a$	$x_o$	$L_1$
G8M	8	5,200	5,87	3,43	0,74	2,29	0,80	0,379	1,378
G14M	14	9,100	10,11	6,00	1,30	4,00	1,40	0,661	2,422



**Figure 1 — Tooth dimensions — Profile system G**

#### Detail of tooth face

For  $A_o \geq x \geq x_o$ :

$$y = A_o \left[ \ln \left( A_o / x + \sqrt{(A_o / x)^2 - 1} \right) - \sqrt{1 - (x / A_o)^2} \right] \quad (1)$$

NOTE 1  $x_o$  corresponds to  $y = h_t$ .

NOTE 2  $L_1$  is equal to  $S - 2(A_o - x_o)$ .

NOTE 3 Indicated base tooth profile remains constant in all parts.

NOTE 4 “o” reference points remain in contact with the part outer surface generated by part radius of curvature.

NOTE 5 Groove profile bottom surface in circular part form is an arc whose chordal distance is  $L_1$  and whose radius originates at the part centre.

#### 8.1.2 Belt widths and tolerances

Belt widths and tolerances are given in [Table 2](#). Evenly measure at least three points throughout circumference and average them.

Table 2 — Widths and width tolerances

Dimensions in millimetres

Profile	Nominal belt width	Tolerance on width for belt pitch lengths		
		Up to and including 840 mm	Over 840 mm and up to and including 1 680 mm	Over 1 680 mm
G8M	12	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	21	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	36	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	62	+1,2 -1,2	+1,2 -1,6	+1,6 -1,6
G14M	20	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	37	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	68	+1,2 -1,6	+1,6 -1,6	+1,6 -2,0
	90	+1,6 -1,6	+1,6 -2,0	+2,0 -2,0
	125	+2,4 -2,4	+2,4 -2,8	+2,4 -3,2

### 8.1.3 Pitch length measurement

See [Annex A](#) for tolerances and [Annex B](#) for the relationship between the centre distance and the belt pitch length.

#### 8.1.3.1 Measuring fixture (see [Figure 2](#))

The pitch length of a synchronous belt shall be determined by placing the belt on a measuring fixture composed of the following elements.

**8.1.3.1.1 Two pulleys of equal diameter**, as specified in [Table 3](#), of the proper belt profile and having standard tooth space dimensions. These pulleys should be made to the tolerances shown in [Table 3](#). One pulley shall be free to rotate on a fixed-position shaft, while the other shall be free to rotate on a moveable shaft to permit the centre distance to change.

**8.1.3.1.2 Means of applying a total measuring force** to the moveable pulley.

**8.1.3.1.3 Means of measuring the centre** distance between the two pulleys with the necessary degree of accuracy for centre distance measurement.


#### 8.1.3.2 Total measuring force

The total measuring force to be applied for measuring belts is given in [Table 4](#). The forces shown in [Table 4](#) are for reference only.

#### 8.1.3.3 Procedure

In measuring the pitch length of a synchronous belt, the belt should be rotated at least two revolutions to seat it properly and to divide the total force equally between the two spans of the belt. The pitch length shall be calculated by adding the pitch circumference of one of the pulleys to twice the measured centre distance.

Centre-to-centre distance measurement methodology should include multiple sensor readings from a minimum of 3 belt revolutions averaged together.



**Key**

- 1 centre distance
- 2 total measuring force

**Figure 2 — Diagram of fixture for measuring pitch length**

**Table 3 — Belt length measuring pulleys**

Dimensions in millimetres

Profile	Number of grooves	Pitch circumference	Outside diameter <sup>a</sup>	Radial runout F.I.M. <sup>b</sup>	Axial runout F.I.M. <sup>b</sup>
G8M	34	272	84,980 ±0,013	0,013	0,025
G14M	40	560	175,454 ±0,025	0,013	0,051

<sup>a</sup> Pulleys outside of the diameter tolerance range specified can be used if the resulting belt length measurements are corrected for the actual pulley diameters.

<sup>b</sup> F.I.M means the full indicator movement.

NOTE The number of pulley teeth specified in [Table 3](#) determines the recommended sizes for measuring the belt pitch length. Practically, other sizes of pulleys could be used provided both pulleys are of equal size, and meet the outside diameter tolerance, radial runout, and axial runout specifications of [Table 3](#).

**Table 4 — Total measuring force**

Forces in Newtons

Profile	Belt width mm								
	12	20	21	36	37	62	68	90	125
G8M	267	—	467	756	—	1 223	—	—	—
G14M	—	1 179	—	—	2 046	—	3 447	4 315	5 627

NOTE Total measuring forces are for reference only.

## 8.2 Pulleys, profile system G

### 8.2.1 General

See [Annex C](#) for tolerances.

The pulley is characterized by a curvilinear groove profile. This groove profile is defined as the profile formed by the generating tool rack form required to machine-finish the curvilinear profile. The profile is different for each pulley diameter, but can be closely approximated by a nominal groove profile over specified ranges of number of grooves.

### 8.2.2 Generating tool rack

Dimensions and tolerances for the generating tool rack for pulleys with profile system G are given in [Table 5](#) and shown in [Figure 3](#).




Figure 3 — Pulley generating tool rack dimensions

Table 5 — Pulley generating tool rack dimensions

Dimensions in millimetres

Profile	Number of grooves	$P_b$	$h_r$	$P_0$ (X,Y)	$r_1$	$P_1$ (X,Y)	$r_2$	$P_2$ (X,Y)	$r_3$	$P_3$ (X,Y)	$r_4$	$P_4$ (X,Y)	$r_5$	$P_5$ (X,Y)	$r_6$	$P_6$ (X,Y)	$r_7$	$P_7$ (X,Y)	$r_8$	$P_8$ (X,Y)	X	
<b>G8M</b>	22 to 27	7,784	3,541	3,480 0	0,842	2,710 -0,433	1,459 1,086	2,567 -0,788	—	—	8,833	2,427 -1,275	5,882	1,841 -2,580	3,123	1,324 -3,235	1,450	0,979 -3,491	0,552	0,856 -3,541	0,856	0,856
	28 to 37	7,843	3,513	3,448 0	0,828	2,746 -0,348	1,086 0,918	2,578 -0,715	—	—	9,487	2,447 -1,193	5,901	1,894 -2,486	3,152	1,367 -3,177	1,505	1,009 -3,447	0,640	0,843 -3,513	0,843	0,843
	38 to 58	7,891	3,487	3,426 0	0,819	2,829 -0,232	0,918	2,583 -0,668	—	—	9,964	2,462 -1,126	5,921	1,940 -2,402	3,181	1,410 -3,119	1,562	1,024 -3,414	0,669	0,831 -3,487	0,831	0,831
	59 to 89	7,930	3,467	3,412 0	0,818	2,943 -0,130	0,846	2,586 -0,632	—	—	10,385	2,470 -1,082	5,932	1,978 -2,328	3,205	1,443 -3,072	1,614	1,039 -3,384	0,725	0,820 -3,467	0,820	0,820
	90 to 250	8,040	3,452	3,558 0	0,846	3,040 -0,164	0,957	2,751 -0,512	1,984	2,617 -0,873	8,275	2,345 -1,724	5,111	1,978 -2,495	3,042	1,559 -3,056	1,725	1,181 -3,359	0,805	0,951 -3,452	0,951	0,951
		27 to 29	13,674	6,174	6,009 0	1,461	4,777 -0,684	2,188	4,536 -1,222	9,728	4,405 -1,696	11,867	3,768 -3,487	9,625	3,161 -4,619	6,114	2,486 -5,489	3,338	1,808 -6,041	1,511	1,505 -6,174	1,505
<b>G14M</b>	30 to 35	13,725	6,147	5,986 0	1,453	4,738 -0,717	2,206	4,519 -1,244	9,448	4,418 -1,626	11,919	3,800 -3,408	9,584	3,213 -4,531	6,129	2,522 -5,436	3,433	1,850 -5,990	1,588	1,496 -6,147	1,496	1,496
	36 to 45	13,780	6,117	5,961 0	1,446	4,685 -0,780	2,241	4,490 -1,312	—	—	13,051	3,951 -3,041	10,115	3,297 -4,387	6,163	2,582 -5,356	3,489	1,883 -5,942	1,672	1,485 -6,117	1,485	1,485
	46 to 60	13,831	6,090	5,940 0	1,437	4,652 -0,815	2,180	4,484 -1,313	—	—	13,091	3,971 -2,983	10,092	3,417 -4,172	6,222	2,649 -5,267	3,541	1,913 -5,899	1,745	1,476 -6,090	1,476	1,476
	61 to 90	13,879	6,065	5,919 0	1,429	4,608 -0,883	2,151	4,484 -1,285	—	—	13,183	3,988 -2,928	10,067	3,463 -4,081	6,236	2,702 -5,193	3,586	1,940 -5,857	1,812	1,467 -6,065	1,467	1,467
	91 to 149	13,927	6,040	5,900 0	1,420	4,568 -0,955	2,586	4,476 -1,292	—	—	13,304	4,014 -2,848	10,051	3,505 -3,997	6,245	2,746 -5,128	3,629	1,969 -5,815	1,872	1,458 -6,040	1,458	1,458
	150 to 250	13,956	6,024	5,887 0	1,414	4,537 -1,031	5,757	4,458 -1,352	—	—	13,150	4,030 -2,799	10,051	3,533 -3,938	6,249	2,701 -5,171	3,652	1,983 -5,792	1,908	1,453 -6,024	1,453	1,453

8.2.3 Pulley groove profile dimensions and tolerances

Dimensions and tolerances for the pulley groove profile for G8M and G14M pulleys are given in Table 6 and shown in Figures 4 and 5.

Table 6 — Pulley groove profile dimensions

Dimensions in millimetres

Profile	Number of grooves	$b_r$	$h_g$	$r_t$	$A_o$	$x_o$	$L_1$	$a$
G8M	22 to 89	5,400	3,43	0,80	2,29	0,379	1,60	0,80
	90 to 250	5,660	3,43	0,80	2,29	0,379	1,60	0,80
G14M	28 to over	9,450	6,00	1,40	4,00	0,661	2,80	1,40




Figure 4 — Pulley groove profile

For  $A_o \geq x \geq x_o$ :

$$y = A_o \left[ \ln \left( \frac{A_o}{x} + \sqrt{\left( \frac{A_o}{x} \right)^2 - 1} \right) - \sqrt{1 - \left( \frac{x}{A_o} \right)^2} \right] \quad (2)$$


NOTE 1  $x_o$  corresponds to  $y = h_t$ .

NOTE 2  $L_1$  is equal to  $S - 2(A_o - x_o)$ .

NOTE 3 Indicated base tooth profile remains constant in all parts.

NOTE 4 "o" reference points remain in contact with the part outer surface generated by part radius of curvature.

NOTE 5 Groove profile bottom surface in circular part form is an arc whose chordal distance is  $L_1$  and whose radius originates at the part centre.



NOTE The true profile of the groove sides can only be produced by plotting the function associated with the cross-section.

Figure 5 — Groove profile — Tolerance bands — Millimetres


#### 8.2.4 Pulley outside diameters

Pulleys outside diameters for the standard pulleys are given in [Table 7](#). The relationship of the pulley outside and pitch diameters is illustrated in [Figure 6](#) and [Formulae \(3\)](#) and [\(4\)](#).

$$d = \frac{n_g \times P_b}{\pi} \quad (3)$$

$$d_o = d - 2a \quad (4)$$

where  $a$  is given in [Table 1](#).

**Key**

- 1 pitch
- 2 belt pitch line
- 3 belt tooth
- 4 pitch diameter
- 5 outside diameter
- 6 pulley groove

**Figure 6 — Pulley dimensions****Table 7 — Standard pulley sizes**

Dimensions in millimetres

Number of grooves	Profile			
	G8M		G14M	
	Pitch diameter	Outside diameter	Pitch diameter	Outside diameter
22	56,02	54,42	—	—
25	63,66	62,06	—	—
28	71,30	69,70	124,78	121,98
29	—	—	129,23	126,43
30	76,39	74,79	133,69	130,89
31	—	—	138,15	135,35
32	81,49	79,89	142,60	139,80
33	—	—	147,06	144,26
34	86,58	84,98	151,52	148,72
35	—	—	155,9	153,17

Table 7 (continued)

Number of grooves	Profile			
	G8M		G14M	
	Pitch diameter	Outside diameter	Pitch diameter	Outside diameter
36	91,67	90,07	160,43	157,63
37	—	—	164,88	162,08
38	96,77	95,17	169,34	166,54
39	—	—	173,80	171,00
40	101,86	100,26	178,25	175,45
42	106,95	105,35	—	—
43	—	—	191,62	188,82
44	—	—	196,08	193,28
45	114,59	112,99	200,54	197,74
48	122,23	120,63	213,90	211,10
50	127,32	125,72	222,82	220,02
53	134,96	133,36	236,19	233,39
56	142,60	141,00	249,55	246,75
60	152,79	151,19	267,38	264,58
63	160,43	158,83	280,75	277,95
64	162,97	161,37	285,21	282,41
67	170,61	169,01	298,57	295,77
71	180,80	179,20	316,40	313,60
72	—	—	320,86	318,06
75	190,99	189,39	334,23	331,43
80	203,72	202,12	356,51	353,71
90	229,18	227,58	401,07	398,27
112	285,21	283,61	499,11	496,31
140	356,51	354,91	623,89	621,09
168	—	—	748,66	745,86
192	488,92	487,32	—	—
180	458,37	456,77	802,14	799,34
192	—	—	855,62	852,82
200	—	—	891,27	888,47
224	570,41	568,81	998,22	995,42

### 8.2.5 Pulley width


The standard nominal pulley width, and the minimum actual pulley width required,  $b_f$  for flanged pulleys,  $b'_f$  for unflanged pulleys are given in [Table 8](#) and shown in [Figure 7](#). Users are advised that the values given for  $b'_f$  apply also to pulleys with only one flange (see [Annex D](#)).

**Table 8 — Standard pulley widths**

Dimensions in millimetres

Profile	Standard nominal pulley width	Minimum pulley width	
		Flanged $b_f$	Unflanged $b'_f$
G8M	12	14	22
	21	23	30
	36	40	47
	62	66	74
G14M	20	26	35
	37	44	52
	68	76	85
	90	99	107
	125	134	143

The minimum unflanged pulley width can be reduced when the alignment of the drive can be controlled, but shall not be less than the minimum flanged pulley width.

**Figure 7 — Minimum pulley width**

## 9 Profile system H

### 9.1 Belt dimensions and tolerances

#### 9.1.1 Belt tooth dimensions

The nominal belt tooth dimensions are the same for single-sided and double-sided belts; they are given in [Table 9](#) and shown in [Figure 8](#).

Table 9 — Nominal tooth dimensions

Dimensions in millimetres

Profile	Belt pitch	$h_s$	$h_d$	$h_t$	$P_1$ (X, Y)	$P_5$ (X, Y)	$r_1$	$P_2$ (X, Y)	$P_6$ (X, Y)	$P_3$ (X, Y)	$P_7$ (X, Y)	$r_2$	$P_4$ (X, Y)	$P_8$ (X, Y)	$a$
H3M	3	2,4	—	1,21	-1,14 0,00	—	0,30	-0,83 -0,30	—	-0,83 -0,35	—	0,86	0,00 -1,21	—	0,381
DH3M	3	—	3,2	—	—	-1,14 0,76	0,30	—	-0,83 1,06	—	-0,83 1,11	0,86	—	0,00 1,97	0,381
H5M	5	3,8	—	2,08	-1,85 0,00	—	0,41	-1,44 -0,42	—	-1,44 -0,53	—	1,50	0,00 -2,08	—	0,572
DH5M	5	—	5,3	—	—	-1,85 1,14	0,41	—	-1,44 1,56	—	-1,44 1,67	1,50	—	0,00 3,22	0,572
H8M	8	6,0	—	3,38	-3,30 0,00	—	0,76	-2,55 -0,65	—	-2,47 -1,17	—	2,59	0,00 -3,38	—	0,686
DH8M	8	—	8,1	—	—	-3,30 1,37	0,76	—	-2,55 2,02	—	-2,47 2,54	2,59	—	0,00 4,75	0,686
H14M	14	10,0	—	6,02	-5,78 0,00	—	1,42	-4,36 -1,29	—	-4,30 -1,97	—	4,46	0,00 -6,02	—	1,397
DH14M	14	—	14,8	—	—	-5,78 2,79	1,42	—	-4,36 4,08	—	-4,30 4,76	4,46	—	0,00 8,81	1,397
H20M	20	13,2	—	8,68	-8,34 0,00	—	2,03	-6,32 -1,84	—	-6,22 -2,90	—	6,40	0,00 -8,68	—	2,159




Figure 8 — Tooth dimensions - Profile system H

9.1.2 Belt widths and tolerances

Belt widths and tolerances are given in Table 10. Evenly measure three points throughout circumference and average them.

Table 10 — Widths and width tolerances

Dimensions in millimetres

Profile	Nominal belt width	Tolerance on width for belt pitch lengths		
		Up to and including 840 mm	Over 840 mm and up to and including 1 680 mm	Over 1 680 mm
H3M, DH3M	6	+0,4	+0,4	—
	9	-0,8	-0,8	—
H5M, DH5M	15	+0,8	+0,8	+0,8
		-0,8	-1,2	-1,2
	9	+0,4	+0,4	—
H8M, DH8M	15	+0,8	+0,8	+0,8
	25	-0,8	-1,2	-1,2
	20	+0,8	+0,8	+0,8
H14M, DH14M	30	-0,8	-1,2	-1,2
	50	+0,8	+1,2	+1,2
		-1,2	-1,2	-1,6
	85	+1,6	+1,6	+2,0
H20M		-1,6	-2,0	-2,0
	40	+0,8	+1,2	+1,2
		-1,2	-1,2	-1,6
	55	+1,2	+1,2	+1,6
		-1,2	-1,6	-1,6
H20M	85	+1,6	+1,6	+2,0
		-1,6	-2,0	-2,0
	115	+2,4	+2,4	+2,4
	170	-2,4	-2,8	-3,2
	115	+2,4	+2,4	+2,4
	170	-2,4	-2,8	-3,2
H20M	230	—	—	+4,8
	290	—	—	-6,4
	340	—	—	—
		—	—	—

### 9.1.3 Pitch length measurement

See [Annex A](#) for tolerances and [Annex B](#) for the relationship between the centre distance and the belt pitch length.

#### 9.1.3.1 Measuring fixture (see [Figure 9](#))

The pitch length of a synchronous belt shall be determined by placing the belt on a measuring fixture composed of the following elements.

**9.1.3.1.1 Two pulleys of equal diameter**, as specified in [Table 11](#), of the proper belt type and having standard tooth space dimensions. These pulleys should be made to the tolerances shown in [Table 11](#). One pulley shall be free to rotate on a fixed-position shaft, while the other shall be free to rotate on a moveable shaft to permit the centre distance to change.

**9.1.3.1.2 Means of applying a total measuring force** to the moveable pulley.

**9.1.3.1.3 Means of measuring the centre distance** between the two pulleys with the necessary degree of accuracy for centre distance measurement.

**9.1.3.2 Total measuring force**


The total measuring force to be applied for measuring belts is given in [Table 12](#). The forces shown in [Table 12](#) are for reference only.

**9.1.3.3 Procedure**

In measuring the pitch length of a synchronous belt, the belt should be rotated at least two revolutions to seat it properly and to divide the total force equally between the two spans of the belt. The pitch length shall be calculated by adding the pitch circumference of one of the pulleys to twice the measured centre distance.

Centre-to-centre distance measurement methodology should include multiple sensor readings from a minimum of 3 belt revolutions averaged together.

Check double-sided belts on both tooth faces.



- Key**
- 1 centre distance
  - 2 total measuring force

**Figure 9 – Diagram of fixture for measuring pitch length**

**Table 11 — Belt length measuring pulleys**

Dimensions in millimetres

Profile	Number of grooves	Pitch circumference	Outside diameter <sup>a</sup>	Radial runout F.I.M. <sup>b</sup>	Axial runout F.I.M. <sup>b</sup>
H3M, DH3M	30	90	27,886 ±0,013	0,013	0,025
H5M, DH5M	20	100	30,687 ±0,013	0,013	0,025
H8M, DH8M	34	272	85,208 ±0,013	0,013	0,025

<sup>a</sup> Pulleys outside of the diameter tolerance range specified can be used if the resulting belt length measurements are corrected for the actual pulley diameters.

<sup>b</sup> F.I.M. means full indicator movement.

Table 11 (continued)

Profile	Number of grooves	Pitch circumference	Outside diameter <sup>a</sup>	Radial runout F.I.M. <sup>b</sup>	Axial runout F.I.M. <sup>b</sup>
H14M, DH14M	40	560	175,46 ±0,025	0,013	0,051
H20M	40	800	250,33 ±0,036	0,013	0,076

<sup>a</sup> Pulleys outside of the diameter tolerance range specified can be used if the resulting belt length measurements are corrected for the actual pulley diameters.

<sup>b</sup> F.I.M. means full indicator movement.

NOTE The number of pulley teeth specified in [Table 11](#) determines the recommended sizes for measuring the belt pitch length. Practically, other sizes of pulleys could be used provided both pulleys are of equal size, and meet the outside diameter tolerance, radial runout, and axial runout specifications of [Table 11](#).

Table 12 — Total measuring force

Forces in Newtons

Profile	Belt width mm														
	6	9	15	20	25	30	40	50	55	85	115	170	230	290	340
H3M, DH3M	45	76	138	—	—	—	—	—	—	—	—	—	—	—	—
H5M, DH5M	—	111	214	—	376	—	—	—	—	—	—	—	—	—	—
H8M, DH8M	—	—	—	470	—	750	—	1 320	—	2 310	—	—	—	—	—
H14M, DH14M	—	—	—	—	—	—	1 350	—	2 130	3 660	5 180	7 960	—	—	—
H20M	—	—	—	—	—	—	—	—	—	—	6 961	10 729	14 839	18 949	22 374

NOTE Total measuring forces are for reference only.

## 9.2 Pulleys, profile system H

### 9.2.1 General

See [Annex C](#) for tolerances.

The pulley is characterized by a curvilinear groove profile. This groove profile is defined as the profile formed by the generating tool rack form required to machine-finish the curvilinear profile. The profile is different for each pulley diameter, but can be closely approximated by a nominal groove profile over specified ranges of number of grooves.

### 9.2.2 Generating tool rack

Dimensions and tolerances for the generating tool rack for pulleys with profile system H are given in [Table 13](#) and shown in [Figure 10](#).




Figure 10 — Pulley generating tool rack form

STANDARDSISO.COM : Click to view the full PDF of ISO 13050:2022

Table 13 — Pulley generating tool rack dimensions

Profile	Num-ber of grooves	$P_b$ $\pm 0,012$	$h_r$ $\pm 0,015$	$P_0$ (X,Y)	$r_1$ $\pm 0,012$	$P_1$ (X,Y)	$r_2$ $\pm 0,012$	$P_2$ (X,Y)	$r_3$ $\pm 0,012$	$P_3$ (X,Y)	$r_4$ $\pm 0,012$	$P_4$ (X,Y)	$r_5$ $\pm 0,012$	$P_5$ (X,Y)	X
H3M	9 to 13	3,000	1,196	1,423 0	0,414	1,061 -0,213	—	—	$\infty$	0,712 -0,840	0,559	0,574 -1,004	0,869	0,029 -1,196	0,029
	14 to 25	3,000	1,173	1,324 0	0,254	1,139 -0,080	0,792	0,992 -0,213	$\infty$	0,747 -0,860	0,254	0,687 -0,944	0,844	0,114 -1,168	0,114
	26 to 80	3,000	1,227	1,223 0	0,262	0,982 -0,159	2,616	0,820 -0,679	—	—	0,493	0,733 -0,877	0,869	0,036 -1,227	0,036
	81 to 200	3,000	1,232	1,333 0	0,358	0,981 -0,290	—	—	$\infty$	0,923 -0,554	—	—	0,866	0,077 -1,232	0,077
H5M	12 to 16	5,000	1,986	2,344 0	0,659	1,739 -0,316	4,475	1,522 -0,720	$\infty$	1,124 -1,560	0,691	0,773 -1,895	1,133	0,328 -1,986	0,328
	17 to 31	5,000	2,024	2,242 0	0,610	1,871 -0,126	1,434	1,540 -0,593	$\infty$	1,163 -1,566	0,612	1,013 -1,789	1,219	0,295 -2,024	0,295
	32 to 79	5,000	2,032	2,073 0	0,493	1,675 -0,203	1,359	1,501 -0,566	$\infty$	1,370 -1,035	1,402	1,088 -1,617	1,300	0,135 -2,032	0,135
	80 to 200	5,000	2,056	2,160 0	0,610	1,564 -0,483	—	—	$\infty$	1,443 -1,050	—	—	1,471	0,043 -2,065	0,043
H8M	22 to 27	8,000	3,289	3,805 0	1,143	2,738 -0,648	—	—	$\infty$	2,322 -1,801	—	—	2,553	0 -3,289	—
	28 to 89	8,000	3,612	3,754 0	1,067	2,748 -0,711	12,903	2,360 -2,024	—	—	0,726	2,283 -2,215	2,744	0 -3,612	—
	90 to 200	8,000	3,632	3,617 0	0,940	2,697 -0,757	—	—	$\infty$	2,459 -1,948	—	—	2,637	0 -3,632	—
H14M	28 to 36	14,000	6,320	6,761 0	1,880	5,037 -1,133	20,828	4,064 -3,904	—	—	1,143	3,909 -4,242	4,717	0 -6,320	—
	37 to 89	14,000	6,223	6,599 0	1,829	4,890 -1,176	15,748	4,204 -3,493	—	—	1,143	4,089 -3,802	4,663	0 -6,223	—
	90 to 216	14,000	6,350	6,546 0	1,905	4,704 -1,425	20,117	4,288 -3,439	—	—	0,254	4,270 -3,498	4,623	0 -6,350	—

Table 13 (continued)

Profile	Num-ber of grooves	$P_b$ ±0,012	$h_r$ ±0,015	$P_0$ (X,Y)	$r_1$ ±0,012	$P_1$ (X,Y)	$r_2$ ±0,012	$P_2$ (X,Y)	$r_3$ ±0,012	$P_3$ (X,Y)	$r_4$ ±0,012	$P_4$ (X,Y)	$r_5$ ±0,012	$P_5$ (X,Y)	X
H20M	34 to 45	20,000	8,644	9,786 0	2,814	7,105 -1,852	—	—	∞	5,972 -4,947	—	—	5,625	0,753 -8,644	0,753
	46 to 100	20,000	8,591	9,529 0	2,667	7,041 -1,662	20,329	6,015 -5,121	—	—	—	—	5,842	0,711 -8,591	0,711
	101 to 220	20,000	8,690	9,787 0	2,676	7,305 -1,760	—	—	∞	6,165 -4,855	—	—	5,733	0,739 -8,690	0,739

STANDARDSISO.COM : Click to view the full PDF of ISO 13050:2022

### 9.2.3 Pulley groove profile dimensions and tolerances


Dimensions and tolerances for the pulley grooves with profile H are given in [Table 14](#) and shown in [Figure 11](#).

**Table 14 — Pulley groove profile dimensions**

Dimensions in millimetres

Profile	Number of grooves	$h_g$	$X$	$R_1$	$\phi$	$r_t$	Profile band <sup>a</sup>
H3M	10 to 13	1,190	0,029	0,991	15	0,181	±0,051
	14 to 25	1,179	0,112	0,889	9	0,229	
	26 to 80	1,219	0,028	0,927	8	0,191	
	81 to 200	1,234	0,074	0,925	4	0,301	
H5M	12 to 16	1,989	0,307	1,265	10	0,432	±0,051
	17 to 25	2,009	0,320	1,270	6	0,508	
	26 to 80	2,052	0,081	1,438	2	0,488	
	81 to 200	2,056	0,028	1,552	5	0,569	
H8M	22 to 27	3,295	0,000	2,675	11,3	0,874	+0,090 -0,080
	28 to 89	3,604	0,000	2,629	7	1,024	
	90 to 200	3,630	0,000	2,639	6,6	1,008	
H14M	28 to 32	6,327	0,000	4,859	7,1	1,544	+0,090 -0,080
	33 to 36	6,328	0,000	4,834	5,2	1,613	
	37 to 57	6,198	0,000	4,737	9,3	1,654	
	58 to 89	6,198	0,000	4,669	8,9	1,902	
	90 to 153	6,328	0,000	4,636	6,9	1,704	
	154 to 216	6,327	0,000	4,597	8,6	1,770	
H20M	32 to 45	8,649	0,544	6,185	15	2,184	±0,089
	46 to 100	8,661	0,544	6,185	10	2,540	
	101 to 220	8,700	0,544	6,185	18	2,540	

<sup>a</sup> The profile band tolerance thru  $r_t$  blends into the pulley OD tolerance so that the pulley OD and profile band tolerances do not conflict.



- Key**
- 1 minimum
  - 2 maximum

**Figure 11 — Pulley groove profile and tolerance bands**

### 9.2.4 Pulley outside diameters

Pulley outside diameters for the standard pulleys are given in [Table 15](#). The relationship of the pulley outside and pitch diameters is illustrated in [Figure 12](#) and [Formulae \(3\)](#) (shown also in [8.2.4](#)) and [\(5\)](#) as can be seen here below.


$$d = \frac{n_g \times P_b}{\pi}$$

$$d_o = d - 2a + N' \tag{5}$$

where

$a$  is given in [Table 9](#);

$N'$  is given in [Table 16](#).



**Key**

- 1 pitch
- 2 belt pitch line
- 3 belt tooth
- 4 pitch diameter
- 5 outside diameter
- 6 pulley groove

**Figure 12 — Pulley dimensions**

**Table 15 — Standard pulley sizes**

Dimensions in millimetres

Number of grooves	Profile									
	H3M		H5M		H8M		H14M		H20M	
	Pitch diameter	Outside diameter								
14	13,37	12,61	22,28	21,14	—	—	—	—	—	—
15	14,32	13,56	23,87	22,73	—	—	—	—	—	—
16	15,28	14,52	25,46	24,32	—	—	—	—	—	—
17	16,23	15,47	27,06	25,91	—	—	—	—	—	—
18	17,19	16,43	28,65	27,50	—	—	—	—	—	—
19	18,14	17,38	30,24	29,10	—	—	—	—	—	—
20	19,10	18,34	31,83	30,69	—	—	—	—	—	—

Table 15 (continued)

Number of grooves	Profile									
	H3M		H5M		H8M		H14M		H20M	
	Pitch diame- ter	Outside diame- ter	Pitch diame- ter	Outside diame- ter	Pitch diame- ter	Outside diame- ter	Pitch diame- ter	Outside diame- ter	Pitch diameter	Outside diameter
21	20,05	19,29	33,42	32,28	—	—	—	—	—	—
22	21,01	20,25	35,01	33,87	56,02	54,65	—	—	—	—
24	22,92	22,16	38,20	37,05	61,12	59,74	—	—	—	—
25	—	—	—	—	63,66	62,29	—	—	—	—
26	24,83	24,07	41,38	40,24	66,21	64,84	—	—	—	—
28	26,74	25,98	44,56	43,42	71,30	70,08	124,78	122,12	—	—
29	—	—	—	—	—	—	129,23	126,57	—	—
30	28,65	27,89	47,75	46,60	76,39	75,13	133,69	130,99	—	—
32	30,56	29,80	50,93	49,79	81,49	80,16	142,60	139,88	—	—
34	32,47	31,71	54,11	52,97	86,58	85,21	151,52	148,79	216,45	212,13
36	34,38	33,62	57,30	56,15	91,67	90,30	160,43	157,68	229,18	224,87
38	36,29	35,53	60,48	59,34	96,77	95,39	169,34	166,60	241,92	237,60
40	38,20	37,44	63,66	62,52	101,86	100,49	178,25	175,49	254,65	250,33
43	41,06	40,30	68,44	67,29	—	—	—	—	—	—
44	42,02	41,25	70,03	68,89	112,05	110,67	196,08	193,28	280,11	275,79
46	43,93	43,16	73,21	72,07	—	—	—	—	—	—
48	45,48	45,07	76,39	75,25	122,23	120,86	213,90	211,11	305,58	301,26
49	46,79	46,03	77,99	76,84	—	—	—	—	—	—
50	47,75	46,98	79,58	78,43	—	—	—	—	—	—
52	49,66	48,89	82,76	81,62	—	—	231,73	228,94	331,04	326,72
55	52,52	51,76	87,54	86,39	—	—	—	—	—	—
56	—	—	89,13	87,98	142,60	141,23	249,55	246,76	356,51	325,19
60	57,30	56,53	95,49	94,35	—	—	267,38	264,59	381,97	377,65
62	—	—	98,68	97,53	—	—	—	—	—	—
64	—	—	—	—	162,97	161,60	285,21	282,41	407,44	403,12
65	62,07	61,31	103,45	102,31	—	—	—	—	—	—
68	—	—	—	—	—	—	303,03	300,24	432,90	428,58
70	66,85	66,08	111,41	110,27	—	—	—	—	—	—
72	68,75	67,99	—	—	183,35	181,97	320,86	318,06	458,37	454,05
75	71,62	70,86	119,37	118,22	—	—	—	—	—	—
78	74,48	73,72	124,14	123,00	—	—	—	—	—	—
80	76,39	75,63	127,32	126,18	203,72	202,35	356,51	353,71	509,30	504,98
90	85,94	85,18	143,24	142,10	229,18	227,81	401,07	398,28	572,96	568,64
100	95,49	94,73	159,15	158,01	—	—	—	—	—	—

Table 15 (continued)

Number of grooves	Profile									
	H3M		H5M		H8M		H14M		H20M	
	Pitch diameter	Outside diameter								
110	105,04	104,28	175,07	173,93	—	—	—	—	—	—
112	—	—	—	—	285,21	283,83	499,11	496,32	713,01	708,70
120	114,59	113,83	190,99	189,84	—	—	—	—	—	—
130	124,14	123,38	206,90	205,76	—	—	—	—	—	—
140	133,69	132,92	222,82	221,67	—	—	—	—	—	—
144	—	—	—	—	366,69	365,32	641,71	638,92	916,73	912,41
150	143,24	142,48	238,73	237,59	—	—	—	—	—	—
160	152,79	152,03	254,65	235,50	—	—	—	—	—	—
168	—	—	—	—	427,81	426,44	748,66	745,87	1 069,52	1 065,20
192	—	—	—	—	488,92	487,55	855,62	852,82	1 222,31	1 217,99
216	—	—	—	—	—	—	962,57	959,78	1 375,10	1 370,78

Table 16 — Values of chordal correction factor  $N'$ 

Dimensions in millimetres

Number of grooves	Profile	
	H8M	H14M
	Value of $N'$	Value of $N'$
28	0,15	0,15
29	0,15	0,13
30	0,10	0,09
31	0,08	0,09
32	0,05	0,08
33	0,03	0,08
34		0,08
35		0,05
36		0,05
37		0,05
38		0,05
39		0,03
40		0,03

NOTE  $N'$  values for H3M, H5M, and H20M are zero.

### 9.2.5 Pulley width


The standard nominal pulley width and the minimum actual pulley width required,  $b_f$  for flanged pulleys,  $b'_f$  for unflanged pulleys are given in Table 17 and shown in Figure 13. Users are advised that the values given for  $b'_f$  apply also to pulleys with only one flange (see Annex D).

**Table 17 — Standard pulley widths**

Dimensions in millimetres

Profile	Standard nominal pulley width	Minimum pulley width	
		Flanged $b_f$	Unflanged $b'_f$
H3M	6	8	11
	9	11	14
	15	17	20
H5M	9	11	15
	15	17	21
	25	27	31
H8M	20	22	30
	30	32	40
	50	53	60
	85	89	96
H14M	40	42	55
	55	58	70
	85	89	101
	115	120	131
	170	175	186
H20M	115	120	134
	170	175	189
	230	235	251
	290	300	311
	340	350	361

The minimum unflanged pulley width can be reduced when the alignment of the drive can be controlled but shall not be less than the minimum flanged pulley width.



**Figure 13 — Minimum pulley width**

## 10 Profile system R

### 10.1 Belt dimensions and tolerances


#### 10.1.1 Belt tooth dimensions

The nominal belt tooth dimensions are the same for single-sided and double-sided belts; they are given in [Table 18](#) and shown in [Figure 14](#).

**Table 18 — Nominal tooth dimensions**

Dimensions in millimetres

Profile	Belt pitch	$2\beta$	$S$	$h_s$	$h_d$	$h_t$	$r_r$	$a$	$K$
R3M	3	$32^\circ$	1,95	2,40	—	1,27	0,380	0,381	3,056 7
DR3M	3	$32^\circ$	1,95	—	3,30	1,27	0,380	0,381	3,056 7
R5M	5	$32^\circ$	3,30	3,80	—	2,15	0,630	0,570	1,795 0
DR5M	5	$32^\circ$	3,30	—	5,44	2,15	0,630	0,570	1,795 0
R8M	8	$32^\circ$	5,49	5,40	—	3,25	1,00	0,686	1,095 4
DR8M	8	$32^\circ$	5,49	—	8,37	3,25	1,00	0,686	1,095 4
R14M	14	$32^\circ$	9,61	9,70	—	6,13	1,75	1,397	0,625 0
DR14M	14	$32^\circ$	9,61	—	15,05	6,13	1,75	1,397	0,625 0
R20M	20	$32^\circ$	13,75	14,50	—	8,75	2,50	2,160	0,043 8



**Figure 14 — Tooth dimensions — Profile system R**

10.1.2 Belt widths and tolerances

Belt widths and tolerances are given in [Table 19](#). Evenly measure three points throughout circumference and average them.

Table 19 — Widths and width tolerances

Dimensions in millimetres

Profile	Nominal belt width	Tolerance on width for belt pitch lengths		
		Up to and including 840 mm	Over 840 mm and up to and including 1 680 mm	Over 1 680 mm
R3M, DR3M	6 9	+0,4 - 0,8	+0,4 -0,8	—
	15	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
R5M, DR5M	9	+0,4 -0,8	+0,4 -0,8	—
	15 25	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
R8M, DR8M	20 30	+0,8 -0,8	+0,8 -1,2	+0,8 -1,2
	50	+0,8 -1,2	+1,2 -1,2	+1,2 -1,6
	85	+1,6 -1,6	+1,6 -2,0	+2,0 -2,0
R14M, DR14M	40	+0,8 -1,2	+1,2 -1,2	+1,2 -1,6
	55	+1,2 -1,2	+1,2 -1,6	+1,6 -1,6
	85	+1,6 -1,6	+1,6 -2,0	+2,0 -2,0
	115 170	+2,4 -2,4	+2,4 -2,8	+2,4 -3,2
R20M	115 170	+2,4 -2,4	+2,4 -2,8	+2,4 -3,2
	230 290 340	—	—	+4,8 -6,4

10.1.3 Pitch length measurement

See [Annex A](#) for tolerances and [Annex B](#) for the relationship between the centre distance and the belt pitch length.

10.1.3.1 Measuring fixture (see [Figure 15](#))

The pitch length of a synchronous belt shall be determined by placing the belt on a measuring fixture composed of the following elements.

**10.1.3.1.1 Two pulleys of equal diameter**, as specified in [Table 20](#) of the proper belt type and having standard tooth space dimensions. These pulleys should be made to the tolerances shown in [Table 20](#). One pulley shall be free to rotate on a fixed-position shaft, while the other shall be free to rotate on a moveable shaft to permit the centre distance to change.

**10.1.3.1.2 Means of applying a total measuring force** to the moveable pulley.

**10.1.3.1.3 Means of measuring the centre distance** between the two pulleys with the necessary degree of accuracy for centre distance measurement.

### 10.1.3.2 Total measuring force


The total measuring force to be applied for measuring belts is given in [Table 21](#). The forces shown in [Table 21](#) are for reference only.

### 10.1.3.3 Procedure

In measuring the pitch length of a synchronous belt, the belt should be rotated at least two revolutions to seat it properly and to divide the total force equally between the two lengths of the belt. The pitch length shall be calculated by adding the pitch circumference of one of the pulleys to twice the measured centre distance.

Centre-to-centre distance measurement methodology should include multiple sensor readings from a minimum of 3 belt revolutions averaged together.

Check double-sided belts on both tooth faces.



#### Key

- 1 centre distance
- 2 total measuring force

**Figure 15** — Diagram of fixture for measuring pitch length

**Table 20 — Belt length measuring pulleys**

Dimensions in millimetres

Profile	Number of grooves	Pitch circumference	Outside diameter <sup>a</sup>	Radial runout	Axial runout
				F.I.M. <sup>b</sup>	F.I.M. <sup>b</sup>
R3M, DR3M	30	90	27,886 ±0,013	0,013	0,025
R5M, DR5M	20	100	30,687 ±0,013	0,013	0,025
R8M, DR8M	34	272	85,208 ±0,013	0,013	0,025
R14M, DR14M	40	560	175,46 ±0,025	0,013	0,051
R20M	40	800	250,33 ±0,036	0,013	0,076

<sup>a</sup> For pulleys outside of the diameter tolerance range specified, consult the belt manufacturer.  
<sup>b</sup> F.I.M. means full indicator movement.

NOTE The number of pulley teeth specified in [Table 20](#) determines the recommended sizes for measuring the belt pitch length. Practically, other sizes of pulleys could be used provided both pulleys are of equal size, and meet the outside diameter tolerance, radial runout, and axial runout specifications of [Table 20](#).

**Table 21 — Total measuring force**

Forces in Newtons

Profile	Belt width mm														
	6	9	15	20	25	30	40	50	55	85	115	170	230	290	340
R3M, DR3M	45	76	138	—	—	—	—	—	—	—	—	—	—	—	—
R5M, DR5M	—	111	214	—	376	—	—	—	—	—	—	—	—	—	—
R8M, DR8M	—	—	—	470	—	750	—	1 320	—	2 310	—	—	—	—	—
R14M, DR14M	—	—	—	—	—	—	1 350	—	2 130	3 660	5 180	7 960	—	—	—
R20M	—	—	—	—	—	—	—	—	—	—	6 961	10 729	14 839	18 949	22 374

NOTE Total measuring forces are for reference only.

## 10.2 Pulleys, profile system R

### 10.2.1 General

See [Annex C](#) for tolerances.

The pulley is characterized by a curvilinear groove profile. This groove profile is defined as the profile formed by the generating tool rack form required to machine-finish the curvilinear profile. The profile is different for each pulley diameter, but can be closely approximated by a nominal groove profile over specified ranges of number of grooves.

10.2.2 Generating tool rack

Dimensions and tolerances for the generating tool rack for R8M and R14M pulleys are given in [Table 22](#) and [Figure 16](#).

Table 22 — Pulley generating tool rack dimensions

Dimensions in millimetres

Profile	Number of grooves	$P_b$ ±0,012	$2A$ ± 0,50°	$b_t$	$h_p$ ref.	$h_r$	$W_p$ ref.	$W_r$ ref.	$W_t$	$r_2$ ±0,025	$K$
R3M	8 to 15	2,761	32,00	2,06 +0,05 -0,00	0,925	1,15 ±0,025	0,966 0	0,234	0,870 +0,05 -0,00	0,31	3,285 0
R3M	16 to 30	2,867	32,00	2,06 +0,05 -0,00	0,925	1,15 ±0,025	0,966 0	0,340	0,870 +0,05 -0,00	0,31	3,285 0
R3M	31 and over	3,000	32,00	2,00 +0,05 -0,00	0,896	1,20 ±0,025	0,913 0	0,367	0,798 +0,05 -0,00	0,41	3,394 0
R5M	10 to 21	4,761	32,00	3,48 ±0,025	1,604	2,06 +0,05 -0,00	1,609 0	0,332	1,379 ±0,025	0,63	1,896 0
R5M	22 and over	5,000	32,00	3,48 ±0,025	1,604	2,06 +0,05 -0,00	1,609 0	0,571	1,379 ±0,025	0,63	1,896 0
R8M	22 to 27	7,780	36,00	5,900 ±0,025	2,828	3,45 +0 -0,05	2,75	0,577	1,820 ±0,025	0,90	0,837 3
R8M	28 and over	7,890	36,00	5,900 ±0,025	2,794	3,45 +0 -0,05	2,74	0,612	1,840 ±0,025	0,95	0,847 7
R14M	28 and over	13,800	36,00	10,45 +0,05 -0,00	4,930	6,04 +0,05 -0	4,87	1,020	3,320 ±0,025	1,60	0,479 9
R20M	30 and over	19,692	36,00	14,85 +0,05 -0,00	6,703	8,50 +0,05 -0	6,841	1,604	4,970 ±0,025	2,60	0,353 2




Figure 16 — Pulley generating tool rack form

10.2.3 Pulley groove profile dimensions and tolerances

Dimensions and tolerances for the pulley grooves with profile R are given in Table 23 and Table 24 and shown in Figures 17 and 18.

Table 23 — Pulley groove profile dimensions

Dimensions in millimetres

Pro- file	Number of teeth	$h_g$	$X_A$	$X_B$	$Y_B$	$X'_c$	$Y'_c$	$K$	$r_t$	$R_D$
R3M	8 to 15	1,15	0,39	4,00	0,08	0,54	0,94	3,210 0	0,28	4,00
	16 to 30	1,15	0,40	4,00	0,00	0,53	0,93	3,285 0	0,30	13,00
	31 and over	1,20	0,40	4,00	0,00	0,53	0,93	3,394 0	0,40	18,00
R5M	10 to 21	2,06	0,63	4,00	0,06	0,97	1,70	1,790 0	0,63	9,00
	22 and over	2,06	0,70	4,00	0,00	0,95	1,66	1,829 0	0,50	18,00
R8M	22 to 27	3,47	0,92	4,00	0,11	1,75	2,61	0,847 7	0,90	22,00
	28 and over	3,47	0,92	4,00	0,00	1,75	2,61	0,847 7	0,95	22,00
R14M	28 and over	6,04	1,64	4,00	0,00	3,21	4,93	0,479 9	1,60	32,00
R20M	30 and over	8,50	2,50	4,00	0,00	4,40	6,80	0,349 0	2,42	150,00




Figure 17 — Pulley groove profile

The true profile of the R-type pulley groove can only be produced by plotting the parabolic function associated with the cross section and the number of grooves. Table 24 provides the tip radii dimensions to be used with these generations. Figure 18 illustrates the pulley groove tolerance bands.

Table 24 — Pulley tip radii

Dimensions in millimetres

Profile	Number of grooves	$r_t^a$
R3M	8 to 15	0,28
	16 to 30	0,30
	31 and over	0,40
R5M	10 to 21	0,63
	22 and over	0,50
R8M	22 to 27	0,90
	28 and over	0,95
R14M	28 and over	1,60
R20M	30 and over	2,42

<sup>a</sup> The profile band tolerance thru  $r_t$  blends into the pulley Outside diameter tolerance so that the pulley Outside diameter and profile band tolerances do not conflict.




Figure 18 — Pulley groove tolerance band


#### 10.2.4 Pulley outside diameters

Pulleys outside diameters for the standard pulleys are given in [Table 25](#). The relationship of the pulley outside and pitch diameters is illustrated in [Figure 19](#) and [Formulae \(3\)](#) and [\(4\)](#) as can be seen here below.

$$d = \frac{n_g \times P_b}{\pi}$$

$$d_0 = d - 2a$$

where  $a$  is the value given in [Table 18](#).



**Key**

- 1 pitch
- 2 belt pitch line
- 3 belt tooth
- 4 pitch diameter
- 5 outside diameter
- 6 pulley groove

**Figure 19 — Pulley dimensions**

**Table 25 — Standard pulley sizes**

Dimensions in millimetres

Number of grooves	Profile									
	R3M		R5M		R8M		R14M		R20M	
	Pitch diameter	Outside diameter								
14	13,37	12,61	22,28	21,14	—	—	—	—	—	—
15	14,32	13,56	23,87	22,73	—	—	—	—	—	—
16	15,28	14,52	25,46	24,32	—	—	—	—	—	—
17	16,23	15,47	27,06	25,91	—	—	—	—	—	—
18	17,19	16,43	28,65	27,50	—	—	—	—	—	—
19	18,14	17,38	30,24	29,10	—	—	—	—	—	—
20	19,10	18,34	31,83	30,69	—	—	—	—	—	—

Table 25 (continued)

Number of grooves	Profile									
	R3M		R5M		R8M		R14M		R20M	
	Pitch diameter	Outside diameter								
21	20,05	19,29	33,42	32,28	—	—	—	—	—	—
22	21,01	20,25	35,01	33,87	56,02	54,65	—	—	—	—
24	22,92	22,16	38,20	37,05	61,12	59,74	—	—	—	—
25	—	—	—	—	63,66	62,29	—	—	—	—
26	24,83	24,07	41,38	40,24	66,21	64,84	—	—	—	—
28	26,74	25,98	44,56	43,42	71,30	69,93	124,78	121,98	—	—
29	—	—	—	—	—	—	129,23	126,44	—	—
30	28,65	27,89	47,75	46,60	76,39	75,02	133,69	130,90	—	—
32	30,56	29,80	50,93	49,79	81,49	80,12	142,60	139,81	—	—
34	32,47	31,71	54,11	52,97	86,58	85,21	151,52	148,72	216,45	212,13
36	34,38	33,62	57,30	56,15	91,67	90,30	160,43	157,63	229,18	224,87
38	36,29	35,53	60,48	59,34	96,77	95,39	169,34	166,55	241,92	237,60
40	38,20	37,44	63,66	62,52	101,86	100,49	178,25	175,46	254,65	250,33
43	41,06	40,30	68,44	67,29	—	—	—	—	—	—
44	42,02	41,25	70,03	68,89	112,05	110,67	196,08	193,28	280,11	275,79
46	43,93	43,16	73,21	72,07	—	—	—	—	—	—
48	45,48	45,07	76,39	75,25	122,23	120,86	213,90	211,11	305,58	301,26
49	46,79	46,03	77,99	76,84	—	—	—	—	—	—
50	47,75	46,98	79,58	78,43	—	—	—	—	—	—
52	49,66	48,89	82,76	81,62	—	—	231,73	228,94	331,04	326,72
55	52,52	51,76	87,54	86,39	—	—	—	—	—	—
56	—	—	89,13	87,98	142,60	141,23	249,55	246,76	356,51	325,19
60	57,30	56,53	95,49	94,35	—	—	267,38	264,59	381,97	377,65
62	—	—	98,68	97,53	—	—	—	—	—	—
64	—	—	—	—	162,97	161,60	285,21	282,41	407,44	403,12
65	62,07	61,31	103,45	102,31	—	—	—	—	—	—
68	—	—	—	—	—	—	303,03	300,24	432,90	428,58
70	66,85	66,08	111,41	110,27	—	—	—	—	—	—
72	68,75	67,99	—	—	183,35	181,97	320,86	318,06	458,37	454,05
75	71,62	70,86	119,37	118,22	—	—	—	—	—	—
78	74,48	73,72	124,14	123,00	—	—	—	—	—	—
80	76,39	75,63	127,32	126,18	203,72	202,35	356,51	353,71	509,30	504,98
90	85,94	85,18	143,24	142,10	229,18	227,81	401,07	398,28	572,96	568,64
100	95,49	94,73	159,15	158,01	—	—	—	—	—	—

Table 25 (continued)

Number of grooves	Profile									
	R3M		R5M		R8M		R14M		R20M	
	Pitch diameter	Outside diameter								
110	105,04	104,28	175,07	173,93	—	—	—	—	—	—
112	—	—	—	—	285,21	283,83	499,11	496,32	713,01	708,70
120	114,59	113,83	190,99	189,84	—	—	—	—	—	—
130	124,14	123,38	206,90	205,76	—	—	—	—	—	—
140	133,69	132,92	222,82	221,67	—	—	—	—	—	—
144	—	—	—	—	366,69	365,32	641,71	638,92	916,73	912,41
150	143,24	142,48	238,73	237,59	—	—	—	—	—	—
160	152,79	152,03	254,65	235,50	—	—	—	—	—	—
168	—	—	—	—	427,81	426,44	748,66	745,87	1 069,52	1 065,20
192	—	—	—	—	488,92	487,55	855,62	852,82	1 222,31	1 217,99
216	—	—	—	—	—	—	962,57	959,78	1 375,10	1 370,78

### 10.2.5 Pulley width

The standard nominal pulley width, and the minimum actual pulley width required,  $b_f$  for flanged pulleys,  $b'_f$  for unflanged pulleys (see Figure 20), are given in Table 26. Users are advised that the values given for  $b'_f$  apply also to pulleys with only one flange (see Annex D).




Figure 20 — Minimum pulley width

Table 26 — Standard pulley widths

Dimensions in millimetres

Profile	Standard nominal pulley width	Minimum pulley width	
		Flanged $b_f$	Unflanged $b'_f$
R3M	6	8	11
	9	11	14
	15	17	20
R5M	9	11	15
	15	17	21
	25	27	31
R8M	20	22	30
	30	32	40
	50	53	60
	85	89	96
R14M	40	42	55
	55	58	70
	85	89	101
	115	120	131
	170	175	186
R20M	115	120	134
	170	175	189
	230	235	251
	290	300	311
	340	350	361

The minimum unflanged pulley width can be reduced when the alignment of the drive can be controlled, but shall not be less than the minimum flanged pulley width.

## 11 Profile system S

### 11.1 Belt dimensions and tolerances

#### 11.1.1 Belt tooth dimensions

The nominal belt tooth dimensions are the same for single-sided and double-sided belts; they are given in [Table 27](#) and shown in [Figure 21](#).

Table 27 — Nominal tooth dimensions

Dimensions in millimetres

Profile	Belt pitch	$h_s$	$h_d$	$h_t$	$S$	$r_{bb}$	$r_a$	$r_r$	$Y$	$a$
S8M	8	5,3	—	3,05	5,20	5,20	0,80	0,80	0,686	0,686
DS8M	8	—	7,47	3,05	5,20	5,20	0,80	0,80	0,686	0,686
S14M	14	10,2	—	5,30	9,10	9,10	1,40	1,40	1,397	1,397
DS14M	14	—	13,39	5,30	9,10	9,10	1,40	1,40	1,397	1,397




Figure 21 — Tooth dimensions - Profile system S

11.1.2 Belt widths and tolerances

Belt widths and tolerances are given in Table 28. Evenly measure three points throughout circumference and average them.

Table 28 — Widths and width tolerances

Dimensions in millimetres

Profile	Nominal belt width	Tolerance on width for belt pitch lengths		
		Up to and including 840 mm	Over 840 mm up to and including 1 680 mm	Over 1 680 mm
S8M DS8M	15	±0,8	±0,8	±0,8
	20			
	25			
	30	±0,8	±1,2	±1,2
	40			
	50	-1,2	±1,2	-1,6
	60	±1,2	1,6	±1,6
	85	±1,6	±1,6 -2,0	±2,0

Table 28 (continued)

Profile	Nominal belt width	Tolerance on width for belt pitch lengths		
		Up to and including 840 mm	Over 840 mm up to and including 1 680 mm	Over 1 680 mm
S14M DS14M	40	±0,8 -1,2	±1,2	±1,2 -1,6
	55	±1,2	±1,2	±1,6
	60	±1,2	-1,6	±1,6
	80	±1,6	±1,6	±2,0
	85	±1,6	-2,0	±2,0
	100	±1,6	±1,6 -2,0	±2,0
	115	±2,4	±2,4	±2,4
	120 170	±2,4	±2,4 -2,8	±2,4 -3,2

11.1.3 Pitch length measurement

See [Annex A](#) for tolerances and [Annex B](#) for the relationship between the centre distance and the belt pitch length.

11.1.3.1 Measuring fixture (see [Figure 22](#))

The pitch length of a synchronous belt shall be determined by placing the belt on a measuring fixture composed of the following elements.

**11.1.3.1.1 Two pulleys of equal diameter**, as specified in [Table 29](#) of the proper belt type and having standard tooth space dimensions. These pulleys should be made to the tolerances shown in [Table 29](#). One pulley shall be free to rotate on a fixed-position shaft, while the other shall be free to rotate on a moveable shaft to permit the centre distance to change.

**11.1.3.1.2 Means of applying a total measuring force** to the moveable pulley.

**11.1.3.1.3 Means of measuring the centre distance** between the two pulleys with the necessary degree of accuracy for centre distance measurement.

11.1.3.2 Total measuring force


The total measuring force to be applied for measuring belts is given in [Table 30](#). The forces shown in [Table 30](#) are for reference only.

11.1.3.3 Procedure

In measuring the pitch length of a synchronous belt, the belt should be rotated at least two revolutions to seat it properly and to divide the total force equally between the two lengths of the belt. The pitch length shall be calculated by adding the pitch circumference of one of the pulleys to twice the measured centre distance.

Centre-to-centre distance measurement methodology should include multiple sensor readings from a minimum of 3 belt revolutions averaged together.

Check double-sided belts on both tooth faces.

**Key**

- 1 centre distance  
2 total measuring force

**Figure 22 — Diagram of fixture for measuring pitch length****Table 29 — Belt length measuring pulleys**

Dimensions in millimetres

Profile	Number of grooves	Pitch circumference	Outside diameter <sup>a</sup>	Radial runout F.I.M. <sup>b</sup>	Axial runout F.I.M. <sup>b</sup>
S8M, DS8M	34	272	85,208 ±0,013	0,013	0,025
S14M, DS14M	40	560	175,460 ±0,025	0,013	0,051

<sup>a</sup> Pulleys outside of the diameter tolerance range specified can be used if the resulting belt length measurements are corrected for the actual pulley diameters.

<sup>b</sup> F.I.M. means full indicator movement.

NOTE The number of pulley teeth specified in [Table 29](#) determines the recommended sizes for measuring the belt pitch length. Practically, other sizes of pulleys could be used provided both pulleys are of equal size, and meet the outside diameter tolerance, radial runout, and axial runout specifications of [Table 29](#).

**Table 30 — Total measuring force**

Forces in Newtons

Profile	Belt width mm													
	15	20	25	30	40	50	55	60	80	85	100	115	120	170
S8M, DS8M	570	790	1 020	1 250	1 740	2 240	—	2 770	—	4 120	—	—	—	—
S14M, DS14M	—	—	—	—	2 420	—	3 480	3 840	5 340	5 720	6 880	8 070	8 470	12 600

NOTE Total measuring forces are for reference only.

## 11.2 Pulleys, profile system S

### 11.2.1 General

See [Annex C](#) for tolerances.

The pulley is characterized by a curvilinear groove profile. This groove profile is defined as the profile formed by the generating tool rack form required to machine-finish the curvilinear profile. The profile is different for each pulley diameter but can be closely approximated by a nominal groove profile over specified ranges of number of grooves.

### 11.2.2 Generating tool rack

Dimensions and tolerances for the generating tool rack for pulleys with profile system S are given in [Table 31](#) and [Figure 23](#).

**Table 31 — Pulley generating tool rack dimensions**

Dimensions in millimetres

Profile	Number of grooves	$P_b$ ±0,012	$h_r$ +0,05 -0,00	$b_t$ +0,05 -0,00	$r_1$ +0,05 -0,00	$r_2$ ±0,03	$r_3$ ±0,03	$r_4$ ±0,03	$r_5$ ±0,10	X	W	a	Y
S8M	22 and over	8,000	2,830	5,200	5,300	0,750	2,710	0,400	4,040	5,040	1,130	0,686	0,686
Optional S8M	22 to 26	7,611	2,830	4,220	4,740	0,800	—	0,270	5,680	—	—	—	0,256
	27 to 33	7,689	2,830	4,220	4,740	0,800	—	0,290	5,280	—	—	—	0,279
	34 to 46	7,767	2,830	4,220	4,740	0,800	—	0,320	4,920	—	—	—	0,299
	47 to 74	7,844	2,830	4,220	4,740	0,800	—	0,350	4,590	—	—	—	0,321
	75 to 216	7,928	2,830	4,220	4,740	0,800	—	0,380	4,280	—	—	—	0,342
S14M	28 and over	14,000	4,950	9,100	9,28	1,310	4,800	0,700	7,070	8,840	1,980	1,397	1,397
Optional S14M	28 to 34	13,441	4,950	7,500	8,380	1,360	—	0,520	9,170	—	—	—	0,784
	35 to 47	13,577	4,950	7,500	8,380	1,360	—	0,560	8,570	—	—	—	0,819
	48 to 75	13,716	4,950	7,500	8,380	1,360	—	0,610	8,030	—	—	—	0,856
	76 to 216	13,876	4,950	7,500	8,380	1,360	—	0,660	7,460	—	—	—	0,896

NOTE Optional tool rack dimensions represent a refinement of the original patent holder's design. Selection of standard or optional to be agreed between manufacturer and user.




Figure 23 — Pulley generating tool rack form

11.2.3 Pulley groove profile dimensions and tolerances


Dimensions and tolerances for the pulley grooves with profile S are given in Table 32 and shown in Figure 24.

Table 32 — Pulley groove profile dimensions

Dimensions in millimetres

Profile	Number of grooves	$B_g^a$ +0,10 -0,00	$h_g$ $\pm 0,03$	$R_5$ $\pm 0,01$	$R_4$ $\pm 0,01$	$R_2$ +0,10 -0,00	$R_1$ +0,10 -0,00	$a$	$Y$
S8M	22 and over	5,20	2,83	4,04	0,40	0,75	5,30	0,686	0,686
S14M	28 and over	9,10	4,95	7,07	0,70	1,31	9,28	1,397	1,397

<sup>a</sup> The  $B_g$  dimension is an arc length, not a cord length.



- Key**
- 1 minimum
  - 2 maximum

**Figure 24 — Pulley groove profile**

**11.2.4 Pulley outside diameters**

Pulley outside diameters for the standard pulleys are given in [Table 33](#). The relationship of the pulley outside and pitch diameters is illustrated in [Figure 25](#) and [Formulae \(3\)](#) and [\(4\)](#) as can be seen here below.

$$d = \frac{n_g \times P_b}{\pi}$$

$$d_0 = d - 2a$$

where *a* is the value given in [Table 27](#).

**Table 33 — Standard pulley sizes**

Dimensions in millimetres

Number of grooves	Profile			
	S8M		S14M	
	Pitch diameter	Outside diameter	Pitch diameter	Outside diameter
22	56,02	54,65	—	—
24	61,12	59,74	—	—
26	66,21	64,84	—	—
28	71,30	69,93	124,78	121,98
29	—	—	129,23	126,44

Table 33 (continued)

Number of grooves	Profile			
	S8M		S14M	
	Pitch diameter	Outside diameter	Pitch diameter	Outside diameter
30	76,39	75,02	133,69	130,90
32	81,49	80,12	142,60	139,81
34	86,58	85,21	151,52	148,72
36	91,67	90,30	160,43	157,63
38	96,77	95,39	169,34	166,55
40	101,86	100,49	178,25	175,46
44	112,05	110,67	196,08	193,28
48	122,23	120,86	213,90	211,11
52	—	—	231,73	228,94
56	142,60	141,23	249,55	246,76
60	—	—	267,38	264,59
64	162,97	161,60	285,21	282,41
68	—	—	303,03	300,24
72	183,35	181,97	320,86	318,06
80	203,72	202,35	356,51	353,71
90	229,18	227,81	401,07	398,28
112	285,21	283,83	499,11	496,32
144	366,69	365,32	641,71	638,92
168	—	—	748,66	745,87
192	488,92	487,55	855,62	852,82
216	—	—	962,57	959,78