

First edition
1996-12-15

AMENDMENT 1
2020-01

**Liquefied petroleum gases —
Assessment of the dryness of propane
— Valve freeze method**

AMENDMENT 1

*Gaz de pétrole liquéfiés — Évaluation de la siccité du propane —
Méthode de givrage de vanne*

AMENDEMENT 1

STANDARDSISO.COM : Click to view the full PDF of ISO 13758:1996/Amd 1:2020



Reference number
ISO 13758:1996/Amd.1:2020(E)

© ISO 2020

STANDARDSISO.COM : Click to view the full PDF of ISO 13758:1996/Amd 1:2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 13758:1996/Amd 1:2020

Liquefied petroleum gases — Assessment of the dryness of propane — Valve freeze method

AMENDMENT 1

Normative reference

Replace reference to ISO 4257:1988 with the following.

ISO 4257, *Liquefied petroleum gases — Method of sampling*

Clause 7

Add the following new Clause 7 and renumber all subsequent clauses and subclauses accordingly.

7 Apparatus verification

Verify the correct flow rate through the valve in accordance with the procedure given in Annex A. Valves that cannot be adjusted to meet the requirements of the verification procedure or those suspected of being otherwise defective shall be returned to the manufacturer for recondition and recalibration.

Annex A

Add the following annex.

Annex A (normative)

Verification of the correct flow rate through the valve

A.1 Apparatus

A.1.1 Flow meter, calibrated in ml/min, capable of reading within the range 500 ml/min to 900 ml/min.

A.1.2 Reference valve, with a flow rate calibration certificate.

A.1.3 Adaptor and seal, to connect the valve vent hole to the flow meter.

A.2 Materials

A.2.1 Verification gas, nitrogen, capable of being provided at a pressure of 275 kPa \pm 5 kPa at 21 °C.

A.3 Procedure

A.3.1 The flow rate is measured via the side vent hole in the valve with the valve set in the analysis mode.

NOTE Using a flow meter with the valve set in the purge mode can damage the flow meter, as the flow rate in the purge mode is approximately 5 l/min.

A.3.2 Connect the reference valve ([A.1.2](#)) to the nitrogen source and using the adaptor and seal ([A.1.3](#)), connect the flow meter ([A.1.1](#)).

A.3.3 Set the reference valve ([A.1.2](#)) in the purge mode and open the nitrogen source (see Note to [A.3.1](#)). Set the valve in the analysis mode and check that the flow rate is 700 ml/min \pm 100 ml/min.

A.3.4 Shut off the nitrogen supply and replace the reference valve with the test valve.

A.3.5 Set the LPG freeze test valve (5.1) in the purge mode and open the nitrogen source. Set the test valve to the analysis mode and read the flow meter. For the valve to be functioning correctly the flow rate shall be between 600 ml/min and 800 ml/min.

A.3.6 If the flow rate through the valve is outside the range 600 ml/min to 800 ml/min, adjust the valve in accordance with the manufacturer's instructions.

A.3.7 If the valve cannot be adjusted to come into range, return it to the manufacturer for recondition and recalibration.