
Machine tools safety — Presses —

**Part 4:
Safety requirements for pneumatic
presses**

Sécurité des machines outils — Presses —

Partie 4: Exigences de sécurité pour les presses pneumatiques

STANDARDSISO.COM : Click to view the full PDF of ISO 16092-4:2019



STANDARDSISO.COM : Click to view the full PDF of ISO 16092-4:2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 List of significant hazards	2
5 Safety requirements and/or measures	2
5.1 General.....	2
5.2 Basic design considerations.....	2
5.2.1 Hydraulic and pneumatic systems — Common features.....	2
5.2.2 Pneumatic systems.....	2
5.2.3 Hydraulic systems.....	2
5.2.4 Electric systems.....	2
5.3 Mechanical hazards in the tools area.....	2
5.3.1 Major danger zone.....	2
5.3.2 Safeguarding measures.....	2
5.3.3 Other safety requirements.....	2
5.3.4 Release of trapped persons between the tools.....	2
5.3.5 Release of persons trapped inside enclosed areas.....	3
5.3.6 Prevention of gravity fall during maintenance or repair.....	3
5.3.7 Prevention of unintended gravity fall during production (down-stroking press).....	3
5.4 Control and monitoring system.....	3
5.4.1 Control and monitoring functions.....	3
5.4.2 Muting.....	4
5.4.3 Selection devices.....	4
5.4.4 Position sensors.....	4
5.4.5 Control devices.....	4
5.4.6 Valves.....	4
5.4.7 Performance level of safety functions.....	4
5.5 Tool-setting, trial strokes, maintenance and lubrication.....	19
5.6 Mechanical hazards — Other.....	19
5.7 Slips, trips and falls.....	19
5.8 Protection against other hazards.....	19
6 Verification of the safety requirements and/or measures	19
7 Information for use	20
7.1 General.....	20
7.2 Marking.....	20
7.3 Warnings.....	21
7.4 Instruction handbook.....	21
Annex A (informative) Additional significant hazards, hazardous situations and protective measures	22
Annex B (normative) Calculation of minimum distances	23
Annex C (informative) Examples and principles of pneumatic press and power interlocking	24
Bibliography	27

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 39, *Machine tools*, Subcommittee SC 10, *Safety*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

A list of all parts in the ISO 16092 series can be found on the ISO website.

Introduction

This document is a type-C standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organisations, market surveillance etc.)

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e. g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers)

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

The machinery concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document.

When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 16092-4:2019

Machine tools safety — Presses —

Part 4: Safety requirements for pneumatic presses

1 Scope

This document, in addition to ISO 16092-1, specifies the technical safety requirements and measures to be adopted by persons undertaking the design, manufacture and supply of pneumatic presses which are intended to work cold metal or material partly of cold metal.

This document deals with all significant hazards relevant for pneumatic presses, when they are used as intended and under the conditions of misuse which are reasonably foreseeable by the manufacturer (see [Clause 4](#)). All the phases of the lifetime of the machinery as described in ISO 12100:2010, 5.4, have been taken into consideration.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4413:2010, *Hydraulic fluid power — General rules and safety requirements for systems and their components*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

ISO 13849-1:2015, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*

ISO 16092-1:2017, *Machine tools safety — Presses — Part 1: General safety requirements*

ISO 13851:2019, *Safety of machinery — Two-hand control devices — Functional aspects and design principles*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100:2010, ISO 13849-1:2015, ISO 16092-1:2017 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

restraint valve

device which protects against a gravity fall of the slide/ram

3.2

overall closing time

time interval from the initiation of a slide movement at TDC to the termination of the movement (the closing of tools) at BDC

4 List of significant hazards

This clause contains all the significant hazards, hazardous situations and events identified by risk assessment as significant for the machines defined in the scope and which require a specific action to eliminate or reduce the risk.

These hazards are listed in ISO 16092-1:2017, Annex A. Additional hazards are listed in [Table A.1](#).

5 Safety requirements and/or measures

5.1 General

Pneumatic presses shall comply with the safety requirements and/or protective/risk reduction measures of this clause. In addition, the machine shall be designed according to the principles of ISO 12100 for relevant but not significant hazards which are not dealt with by this document.

5.2 Basic design considerations

5.2.1 Hydraulic and pneumatic systems — Common features

ISO 16092-1:2017, 5.2.1, shall apply.

5.2.2 Pneumatic systems

ISO 16092 1:2017, 5.2.2, shall apply.

5.2.3 Hydraulic systems

In addition to the requirements given in ISO 16092-1:2017, 5.2.3, the following shall apply.

Where a pneumatic press is fitted with a pneumatic/hydraulic intensifier, the general requirements in ISO 4413 shall be followed in designing the hydraulic system.

5.2.4 Electric systems

ISO 16092 1:2017, 5.2.4, shall apply.

5.3 Mechanical hazards in the tools area

5.3.1 Major danger zone

ISO 16092-1:2017, 5.3.1, shall apply.

5.3.2 Safeguarding measures

ISO 16092-1:2017, 5.3.2, shall apply

5.3.3 Other safety requirements

ISO 16092-1:2017, 5.3.3, shall apply.

5.3.4 Release of trapped persons between the tools

ISO 16092-1:2017, 5.3.4, shall apply.

5.3.5 Release of persons trapped inside enclosed areas

ISO 16092-1:2017, 5.3.5, shall apply.

5.3.6 Prevention of gravity fall during maintenance or repair

In addition to the requirements given in ISO 16092-1:2017, 5.3.6, the following shall apply.

On presses with an opening stroke length of more than 500 mm and a depth of table of more than 800 mm, a mechanical restraint device shall be permanently fixed and integrated with the press. It can be manually operated.

If an integrated device, when active, cannot be easily seen from the operator's position, an additional clear indication of the position of the device shall be provided.

5.3.7 Prevention of unintended gravity fall during production (down-stroking press)

5.3.7.1 Measures shall be provided to prevent unintended gravity fall of the slide/ram in the production mode with manual or automatic feed or removal (see [Tables 1](#) and [2](#)). Such a fall can be due to a failure of the pneumatic system, mechanical failure or a failure of the electrical control system.

In this case, the following shall be provided:

- a mechanical restraint device;
- a pneumatic restraint device, as defined in [5.3.7.2](#); or
- a combination of a single valve pneumatic restraint device and a mechanical restraint device.

The restraint devices shall operate automatically and be effective whenever the tool is stopped and access to the tools is possible for the operator.

5.3.7.2 The restraint device shall consist of one or more of the following measures, provided that they are capable of holding up the slide/ram:

- a) return spring;
- b) clamping device;
- c) two pneumatic restraint valves, one of which is fitted as close as possible to the cylinder outlet, using flanged or welded pipework, capable of holding the slide/ram.

5.4 Control and monitoring system

5.4.1 Control and monitoring functions

5.4.1.1 In addition to the requirements given in ISO 16092-1:2017, 5.4.1, the following control and monitoring functions shall apply.

5.4.1.2 For presses pneumatically controlled with a stroke length equal to or less than 30 mm, and a maximum press force equal to or less than 1 000 N, the two-hand control device shall be fixed at the minimum distance as calculated by [Formula \(1\)](#):

$$t = 3 \times t_{\max} \quad (1)$$

where

t is the overall response time;

t_{\max} is the maximum overall closing time (see also [Annex B](#)).

NOTE The factor 3 is intended to compensate the type of two-hand control device selected.

This subclause applies to presses fitted with two-hand control devices used for normal operation. They shall at least correspond to type IIIB of ISO 13851;

It shall not be possible for the overall closing time to be exceeded by any adjustment.

5.4.1.3 Power interlocking, as defined in ISO 14119:2013, 3.31, may be provided for presses fitted with interlocking guards. The guard interlocking device shall be positively linked with the valve to directly control the flow of fluid to and from the cylinder (see [Annex C](#)).

5.4.2 Muting

In addition to the requirements given in ISO 16092-1:2017, 5.4.2, the following shall apply.

The means for setting the start point at which the safeguarding system is muted during the closing stroke shall be:

- a position signal when the tools are closed; and
- a pressure signal or suitable alternative signals which actuate when the machine begins to apply the force.

5.4.3 Selection devices

ISO 16092-1:2017, 5.4.3, shall apply.

5.4.4 Position sensors

ISO 16092-1:2017, 5.4.4, shall apply.

5.4.5 Control devices

ISO 16092-1:2017, 5.4.5, shall apply.


5.4.6 Valves

Manual override devices shall not be directly fitted to restraint valves. If manual override devices are incorporated into other valves for test or maintenance purposes, they shall require the use of a tool to operate the override.

This override shall be of the non-locking type.

5.4.7 Performance level of safety functions

Safety functions of a pneumatic press shall meet the requirements stated in the [Tables 1](#) and [2](#). [Figure 1](#) shows an example of all relevant parts of a control system of pneumatic press with a safety function to stop any down stroke of the slide by ESPE using AOPD.

**Key**

- 1 overall SRP/CS of a safety function "Stop slide down stroke by ESPE using AOPD"
- 2 "Input": ESPE using AOPD
- 3 "Logic": control parts (plausibility check of selection, Logic of AOPD, Logic of muting...)
- 4 output: pneumatic safety-related part
- 5 pneumatic actuator

Figure 1 — Example of a safety function with all relevant safety-related parts

The performance levels in [Tables 1](#) and [2](#) are the minimum required performance levels and already take the probability of occurrence into account.

Table 1 — Summary of requirements for the operator safeguarding of the danger zones at the tools, die cushions, work-piece ejectors and transfer systems areas (see ISO 16092-1:2017, 5.3.1) for different modes of operation — Mode of production: Single cycle, manual feed or removal

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Closed tools used as the only means of protection [see ISO 16092-1:2017, 5.3.2.1 a)]	Movement (e.g. closing stroke) of the slide, die cushions, workpiece ejectors	Cycle initiation/stop	PL a	Cat B	Any ^g	Any	Pneumatic system (e.g. air valves)
Closed tools used in a press with other operating modes with different main safety systems [see ISO 16092-1:2017, 5.3.2.1 a)]							
Fixed enclosing guard used as the only means of protection [see ISO 16092-1:2017, 5.3.2.1 b)]	Movement (e.g. closing stroke) of the slide, die cushions, workpiece ejectors and transfer systems	Cycle initiation/stop	PL a	Cat B	Any ^g	Any	Pneumatic system (e.g. air valves)
Interlocking guard with or without guard locking (with or without early opening feature) or control guard (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements (e.g. closing stroke) of the slide and die cushions	Cycle initiation by other control device than the guard	PL a	Cat B	Any but not actuated by the guard itself ^g	Any	Logic control shall act on the appropriate part of the pneumatic or electrical control system

STANDARDSISO.COM · Click to view the full PDF of ISO 16092-4:2019

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Interlocking guard with or without guard locking (with or without early opening feature) or control guard (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements (e.g. closing stroke) of the slide and die cushions	Cycle initiation by control guard	PL a	Cat B	Interlocking device of the guard	Any	Logic control shall act on the appropriate part of the pneumatic or electrical control system
		Stop by interlocking device of guard without guard locking [see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 b)]	PL e ^{b,c}	Cat 4	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Pneumatic system (e.g. air valves)
Stop by interlocking device of guard with guard locking [see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 a)]	Interlocking device with guard locking (2 sensors or equivalent solution) ^{e,f}						
Interlocking guard with or without guard locking (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements (e.g. closing stroke) of the slide and die cushions	Conditional unlocking of guard	PL d	Cat 3 for input and logic, Cat 2 for output	Sensor or other suitable detection device to confirm that standstill of slide and die cushion is achieved	Safety-related logic	Pre-actuator of the guard locking
		Muting in case of early opening guard and control guard without guard locking [see ISO 16092-1:2017, 5.4.2]	Same as of the safety function on which muting is acting ^g	—	Position signal or suitable alternative	—	—
Interlocking guard with or without guard locking (with or without early opening feature) or control guard (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements of work-piece ejectors and transfer systems	Stop by interlocking device of guard without guard locking [see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 b)]	PL d ^{b,d}	Cat 3	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electrical, hydraulic or pneumatic system
		Stop by interlocking device of guard with guard locking [see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 a)]	PL d ^{b,d}	Cat 3	Interlocking device with guard locking (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electrical, hydraulic or pneumatic system

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function		
				Requirement for category of input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)
Interlocking guard with or without guard locking (with or without early opening feature) or control guard (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements of work-piece ejectors and transfer systems	Conditional unblocking of guard	PL c	Cat 3 for input and logic, Cat 2 for output	Safety-related logic	Pre-actuator of the guard locking
		Muting in case of early opening guard and control guard without guard locking [see ISO 16092-1:2017, 5.4.2]	Same as of the safety function on which muting is acting ^q	—	—	—
Interlocking guard with or without guard locking (with or without early opening feature) or control guard (with or without early opening feature) [see ISO 16092-1:2017, 5.3.2.1 c), d) and e)]	Movements of the slide, die cushions, workpiece ejectors and transfer systems	Prevention of restart by an additional safeguarding of a control guard by AOPD [see ISO 16092-1:2017, 5.3.2.9]	PL e ⁿ	Cat 4	Safety-related logic	Logic control shall act on the appropriate part of the electrical control system
		Prevention of restart by an additional safeguarding of a control guard by interlocking guard [see ISO 16092-1:2017, 5.3.2.9]	PL c ^{o,p}	Cat 1 for input, Cat 3 for logic and output	Safety-related logic	Logic control shall act on the appropriate part of the electrical control system

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Interlocking guard with or without guard locking [see ISO 16092-1:2017, 5.6.1]	Drive and transmission [see ISO 16092-1:2017, 5.6.1]	Stop by interlocking device of guard without guard locking	PL c	Cat 1	Interlocking device	Safety-related logic	Electric, hydraulic or pneumatic system
		Stop by interlocking device of guard with guard locking					
Interlocking guard with or without guard locking [see ISO 16092-1:2017, 5.6.1]	Drive and transmission [see ISO 16092-1:2017, 5.6.1]	Conditional unlocking of guard	PL c	Cat 1	Sensor or other suitable detection device to confirm that standstill of drive and transmission is achieved	Safety-related logic	Pre-actuator of the guard locking
Interlocking guard opened for tool setting only [see ISO 16092-1:2017, 5.3.2.1 c) and 5.5.6]	Movements of the slide, die cushions, work-piece ejectors and transfer systems	Stop by interlocking device of guard	PL c	Cat 1 for input, Cat 3 for logic and output	Interlocking device	Safety-related logic	Same output than those used for safeguarding measures used in production mode
ESPE using AOPD [see ISO 16092-1:2017 5.3.2.1 f) and 5.3.2.11]	Movements (e.g. closing stroke) of the slide and die cushions	Cycle initiation by other control device than the AOPD	PL a	Cat B	Any but not actuated by the AOPD itself ^g	Any	Logic control shall act on the appropriate part of the electrical control system
ESPE using AOPD [see ISO 16092-1:2017 5.3.2.1 f) and 5.3.2.11]	Movements (e.g. closing stroke) of the slide and die cushions	Cycle initiation by AOPD	PL a	Cat B	AOPD	Any	Logic control shall act on the appropriate part of the electrical control system
ESPE using AOPD [see ISO 16092-1:2017 5.3.2.1 f) and 5.3.2.11]	Movements (e.g. closing stroke) of the slide and die cushions	Stop by AOPD	PL e ^c	Cat 4	AOPD	Safety-related logic	Pneumatic system (e.g. air valves)

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
ESPE using AOPD [see ISO 16092-1:2017, 5.3.2.1 f) and 5.3.2.11]	Movements (e.g. closing stroke) of the slide and die cushions	Muting [see ISO 16092-1:2017, 5.4.2]	Same as of the safety function on which muting is acting ^q	—	Position signal or suitable alternative	—	—
	Movements of workpiece ejectors and transfer systems	Stop by AOPD Muting [see ISO 16092-1:2017, 5.4.2] Not allowed for transfer system	PL d ^d	Cat 3	AOPD	Safety-related logic	Electrical, hydraulic or pneumatic system
ESPE using AOPD [see ISO 16092-1:2017, 5.3.2.1 f) and 5.3.2.11]	Movements of the slide, die cushions, workpiece ejectors and transfer systems	Prevention of restart by an additional safeguarding by AOPD [see ISO 16092-1:2017, 5.3.2.11 c)]	Same as of the safety function on which muting is acting ^q	—	Position signal or suitable alternative	—	—
	Movements of the slide, die cushions, workpiece ejectors and transfer systems	Prevention of restart by an additional safeguarding by interlocking guard [see ISO 16092-1:2017, 5.3.2.11 c)]	PL d	Cat 3	AOPD	Safety-related logic	Logic control shall act on the appropriate part of the electrical control system
Two-hand control device [see ISO 16092-1:2017, 5.3.2.1 g) and 5.3.2.12]	Movements (e.g. closing stroke) of the slide and die cushions	Stop and cycle initiation by two-hand control device	PL c ^{o,p}	Cat 1 for input, Cat 3 for logic and output	Interlocking device	Safety-related logic	Logic control shall act on the appropriate part of the electrical control system
			PL e ^{b,c}	Cat 4	Push buttons of two-hand control device ^{g,h}	Safety-related logic	Pneumatic system (e.g. air valves)

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Two-hand control device [see ISO 16092-1:2017, 5.3.2.1 g) and 5.3.2.12]	Movements (e.g. closing stroke) of the slide and die cushions	Stop and cycle initiation for pneumatic presses with a stroke length equal or less than 30 mm and a maximum press force of 1 000 N or less (see 5.4.1.8)	PL d ^{b,d}	Cat 3	Push buttons of two-hand control devices ^{g,h}	Safety-related logic	Pneumatic system (e.g. air valves)
	Movements of workpiece ejectors and transfer systems	Muting (see ISO 16092-1:2017, 5.4.2)	Same as of the safety function on which muting is acting ^q	—	Position signal or suitable alternative	—	—
Two-hand control device [see ISO 16092-1:2017, 5.3.2.1 g) and 5.3.2.12]	Movements of workpiece ejectors and transfer systems	Stop and cycle initiation by two-hand control device	PL d ^{b,d}	Cat 3	Push buttons of two-hand control devices ^{g,h}	Safety-related logic	Electrical, hydraulic or pneumatic system
	Movements of the slide, die cushions, workpiece ejectors and transfer systems	Muting (see ISO 16092-1:2017, 5.4.2) Not allowed for transfer system Additional means to restrict access (see ISO 16092-1:2017, 5.3.2.12) Stop by interlocking device of guard Additional means to restrict access (see ISO 16092-1:2017, 5.3.2.12) Stop by ESPE using AOPD or AOPDDR	PL d ^{b,d}	—	Position signal or suitable alternative	—	—
				Cat 3	Interlocking device (2 sensors or equivalent solution) AOPD or AOPDDR	Safety-related logic	Electrical, hydraulic or pneumatic system

Table 1 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Safety systems which need reset	Movements of the slide, die cushions, workpiece ejectors and transfer systems	Manual reset (see ISO 16092-1:2017, 5.4.1.3)	Same as of the safety function on which it is acting ^m	Any Cat for input ^l , Same category as of the selected safety functions for logic and output	Push button	Safety-related logic ^l	Logic control shall act on the appropriate part of the electrical control system
		Means of selection (see ISO 16092-1:2017, 5.4.3.1)	Same as the highest PL _r among the selected functions		Selection means, e.g. selector switch, electronic key system	Safety-related logic to check plausibility of inputs ^l	
Mechanical restraint device	Movements of the slide	Interlocking to the press control system (see 5.3.7)	PL c	Cat 1	Interlocking device	Safety-related logic	Pneumatic system (e.g. air valves)
Emergency stop device	Movement (e.g. closing stroke) of the slide, die cushions, workpiece ejectors and transfer systems	Emergency stop function (see ISO 16092-1:2017, 5.4.1.6, 5.4.5.2 and 5.4.5.3)	PL c	Cat 1	Emergency stop push button ^h	Safety-related logic	Electrical, hydraulic or pneumatic system (e.g. air valves)

^a In the table, "Requirement for category of Input, Logic and Output" means the following relationships between the requirements of categories for Input, Logic or Output part:

- Cat. 4, 3 or 2 can apply instead of Cat. 1;
- Cat. 4 or 3 can apply instead of Cat. 2;
- Cat. 4 can apply instead of Cat. 3.



Table 2 — Summary of requirements for the operator safeguarding of the danger zones at the tools, die cushions, work-piece ejectors and transfer systems areas (See ISO 16092-1:2017, 5.3.1) for different modes of operation — Mode of production: Automatic cycle, Solely automatic feed and removal

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Closed tools used as the only means of protection (see ISO 16092-1:2017, 5.3.2.1 a)	Movement (e.g. closing stroke) of the slide, die cushions, workpiece ejectors	Cycle initiation/stop	PL a	Cat B	Any ^g	Any	Pneumatic system (e.g. air valves)
Closed tools used in a press with other operating modes with different main safety systems (see ISO 16092-1:2017, 5.3.2.1 a)							
Fixed enclosing guard used as the only means of protection (see ISO 16092-1:2017, 5.3.2.1 b)	Movements of the slide, die cushions, work-piece ejectors and transfer systems	Cycle initiation/stop	PL a	Cat B	Any ^g	Any	Pneumatic system (e.g. air valves)
Interlocking guard with or without guard locking (see ISO 16092-1:2017, 5.3.2.1 c)	Movements (e.g. closing stroke) of the slide and die cushions	Cycle initiation by other control device than the guard	PL a	Cat B	Any but not actuated by the guard itself ^g	Any	Logic control shall act on the appropriate part of the pneumatic or electrical control system
		Stop by interlocking device of guard without guard locking [see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 b)]	PL d ^{b,d}	Cat 3	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Pneumatic system (e.g. air valves)

STANDARDSISO.COM : Click to view the full PDF of ISO 16092-4:2019

Table 2 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Interlocking guard with or without guard locking (see ISO 16092-1:2017, 5.3.2.1 c)	Movements (e.g. closing stroke) of the slide and die cushions	Stop by interlocking device of guard with guard locking (see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 a)	PL d ^b	Cat 2 ^j	Interlocking device with guard locking (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Pneumatic system (e.g. air valves)
		Conditional unlocking of guard	PL c	Cat 3 for input and logic, Cat 2 ^j for output	Sensor or other suitable detection device to confirm that standstill of slide and die cushion is achieved	Safety-related logic	Pre-actuator of the guard locking
Interlocking guard with or without guard locking (see ISO 16092-1:2017, 5.3.2.1 c)	Movements of work-piece ejectors and transfer systems	Stop by interlocking device of guard without guard locking (see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 b)	PL d ^{b,d}	Cat 3	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electrical, hydraulic or pneumatic system
		Conditional unlocking of guard	PL d ^b	Cat 2 ^j	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electrical, hydraulic or pneumatic system
Interlocking guard with or without guard locking (see ISO 16092-1:2017, 5.6.1)	Movements of work-piece ejectors and transfer systems	Stop by interlocking device of guard with guard locking (see ISO 16092-1:2017, 5.3.2.7 and 5.3.2.10 a)	PL c	Cat 3 for input and logic, Cat 2 ^j for output	Sensor or other suitable detection device to confirm that standstill of work-piece ejectors and transfer systems is achieved	Safety-related logic	Pre-actuator of the guard locking
		Conditional unlocking of guard	PL c	Cat 1	Interlocking device (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electric, hydraulic or pneumatic system

Table 2 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Interlocking guard with or without guard locking (see ISO 16092-1:2017, 5.6.1)	Drive and transmission (see ISO 16092-1:2017, 5.6.1)	Stop by interlocking device of guard with guard locking	PL c	Cat 1	Interlocking device with guard locking (2 sensors or equivalent solution) ^{e,f}	Safety-related logic	Electric, hydraulic or pneumatic system
		Conditional unlocking of guard	PL c	Cat 1	Sensor or other suitable detection device to confirm that standstill of drive and transmission is achieved	Safety-related logic	Pre-actuator of the guard locking
Interlocking guard opened for tool setting only (see ISO 16092-1:2017, 5.3.2.1 c and 5.5.6)	Movements of the slide, die cushions, work-piece ejectors and transfer systems	Stop by interlocking device of guard	PL c	Cat 1 for input, Cat 3 for logic and output	Interlocking device	Safety-related logic	Same output than those used for safeguarding measures used in production mode
		Cycle initiation by other control device than the AOPD	PL a	Cat B	Any but not actuated by the AOPD itself ^g	Any	Logic control shall act on the appropriate part of the electrical control system
ESPE using AOPD (see ISO 16092-1:2017 5.3.2.1 f and 5.3.2.1 I)	Movements (e.g. closing stroke) of the slide and die cushions	Stop by AOPD	PL d ^d	Cat 3	AOPD	Safety-related logic	Pneumatic system (e.g. air valves)
Common features							
Safety systems which need reset	Movements of the slide, die cushions, work-piece ejectors and transfer systems	Manual reset (see ISO 16092-1:2017, 5.4.1.3)	Same as of the safety function on which it is acting ^l	Any Cat for input ^k , Same category as of the selected safety functions for logic and output	Push button	Safety-related logic ^k	Logic control shall act on the appropriate part of the electrical control system

Table 2 (continued)

Main safety system	Hazardous movement	Safety function	Minimum required PL (PL _r) for safety function and I, L and O	Basis for the design of input, logic, output of safety function			
				Requirement for category of Input, Logic and Output ^a	I — Input (sensor area)	L — Logic (control)	O — Output (pre-actuator)
Safety systems which need selection means	Movements of the slide, die cushions, work-piece ejectors and transfer systems	Means of selection (see ISO 16092-1:2017, 5.4.3.1)	Same as the highest PL _r among the selected functions	Any Cat for input ^k , Same category as of the selected safety functions for logic and output	Selection means, e.g. selector switch, electronic key system	Safety-related logic to check plausibility of inputs ^l	Logic control shall act on the appropriate part of the electrical control system
Mechanical restraint device	Movements of the slide	Interlocking to the press control system (see 5.3.7)	PL _c	Cat 1	Interlocking device	Safety-related logic	Pneumatic system (e.g. air valves)
Slow speed and hold to run control (See ISO 16092-1:2017, 5.3.3.4)	Movements of handling device	Slow speed	PL _c	Cat 2 ^j	Encoder or suitable alternative		Electrical, hydraulic or pneumatic system
		Hold to run control			2 electro-mechanical contacts (1 for initiation, 1 for diagnostic) ^{g,h}		
Inching device	Movements of handling device	Start and automatic stop of a limited stroke	PL _c	Cat 4 for Start Input Cat 3 for Logic and Output	Any for start ^g	Safety-related logic utilizing e.g. fault resistant position detection or time depending on machine speed	Electrical, hydraulic or pneumatic system
Emergency stop device	Movement (e.g. closing stroke) of the slide, die cushions, work-piece ejectors and transfer systems	Emergency stop function (see ISO 16092-1:2017, 5.4.1.6, 5.4.5.2 and 5.4.5.3)	PL _c	Cat 1	Emergency stop push button ^h	Safety-related logic	Electrical, hydraulic or pneumatic system (e.g. air valves)

^a In the table, "Requirement for category of Input, Logic and Output" means the following relationships between the requirements or categories for Input, Logic or Output part:
 — Cat. 4, 3 or 2 can apply instead of Cat. 1
 — Cat. 4 or 3 can apply instead of Cat. 2
 — Cat. 4 can apply instead of Cat. 3.

5.5 Tool-setting, trial strokes, maintenance and lubrication

In addition to the requirements given in ISO 16092-1: 2017, 5.5, the following shall apply.

Movement during tool-setting, for maintenance and lubrication:

Facilities shall be provided to allow the movement of the slide/ram during tool-setting, maintenance and lubrication to be carried out with guards and protective devices in position and operational (see ISO 16092-1:2017, 5.3.2.1)

Where this is not practicable, at least one of the following facilities shall be provided:

- a) a two-hand control device in accordance with ISO 16092-1:2017, 5.5.7. If it is not of type IIIC (or not of type IIIB in accordance with 5.4.1.2), it needs to be arranged so that it cannot be used for production (e.g. by its positioning and distance from the tools area, using slow speed, equal or less than 10 mm/s, limited movement);
- b) a hold-to-run control device used in conjunction with slow closing speed (equal to or less than 10 mm/s).

5.6 Mechanical hazards — Other

ISO 16092-1:2017, 5.6, shall apply.

5.7 Slips, trips and falls

ISO 16092-1:2017, 5.7, shall apply.

5.8 Protection against other hazards

ISO 16092-1:2017, 5.8, shall apply.

6 Verification of the safety requirements and/or measures

Table 3 indicates by crosses the method(s) by which the safety requirements and protective measures described in Clause 5 and Annex B, shall be verified, together with a reference to the corresponding subclauses in this document.

Table 3 — Means of verification of the safety requirements and/or measures for type testing

Subclause	Safety requirements and/or measures	Visual inspection ^a	Performance check/test ^b	Measurement ^c	Drawings/ Calculations/ Technical data ^d
5.2	Basic design considerations				
5.2.3	Hydraulic systems				
5.2.3	Pneumatic/hydraulic intensifier	x	x		x
5.3	Mechanical hazards in the tools area				
5.3.6	Prevention of gravity fall during maintenance or repair				
5.3.6	Mechanical restraint device	x	x	x	x
5.3.7	Prevention of unintended gravity fall during production (down-stroking press)				
5.3.7.1	Mechanical, pneumatic or combined restraint devices	x	x	x	x

Table 3 (continued)

Subclause	Safety requirements and/or measures	Visual inspection ^a	Performance check/test ^b	Measurement ^c	Drawings/Calculations/Technical data ^d
5.4	Control and monitoring system				
5.4.1	Control and monitoring functions				
5.4.1.2	Overall response time		x	x	x
	Stroke length ≤30 mm	x	x	x	x
	Press force 1 000 N		x	x	x
5.4.1.3	Power interlocking	x	x		x
5.4.2	Muting				
5.4.2	Position and pressure signal, or suitable alternative signals	x	x		x
5.4.6	Valves				
5.4.6	No override on restraint valves	x			x
	Tool need for manual override	x	x		x
	Non-locking type	x	x		x
5.4.7	Performance of safety functions				
	Requirements of Tables 1 and 2 are met	x	x	x	x
5.5	Toolsetting, trial strokes, maintenance, lubrication				
5.5	Guards and protective devices in position and operational	x	x		x
	or: Two-hand control devices	x	x	x	x
	or: Hold-to-run control device with slow speed	x	x	x	x
7	Information for use				
7.4	Instruction handbook	x			x
Annex B	Minimum (safety) distances			x	x
^a Visual inspection is used to verify the features necessary for the requirement by visual examination of the components supplied. ^b A performance check/test verifies that the features provided perform their function in such a way that the requirement is met. ^c Measurement verifies by the use of instruments that requirements are met, to the specified limits. ^d Drawings/calculations/technical data verifies that the design characteristics of the components provided meet the requirements.					

7 Information for use

7.1 General

ISO 16092-1:2017, 7.1, shall apply.

7.2 Marking

ISO 16092-1:2017, 7.2, shall apply.

7.3 Warnings

ISO 16092-1:2017, 7.3, shall apply.

7.4 Instruction handbook

In addition to the requirements given in ISO 16092-1:2017, 7.4, the following shall apply.

- a) In particular, the instructions for installation shall state that the installer fit pressure switches in the line if air pressure can exceed the maximum air inlet pressure defined by the manufacturer, by more than 10 %.
- b) Instructions on how to ensure that the increasing leakage speed of the slide/ram during use does not exceed 5 mm/s. This shall be maintained.

The instruction handbook shall inform the operator that:

- additional means of protection can be necessary to minimize the operator's exposure to hazardous substances that can be processed by the user.

NOTE 1 As these substances are not defined in this clause, the necessary means are not included in the scope of this document.

- additional precautions can be necessary to minimize the risk from fire and explosion depending on the use of the press.

NOTE 2 Where flammable substances are used, EN 1127-1 provides guidance.

STANDARDSISO.COM : Click to view the full PDF of ISO 16092-4:2019